

TEST REPORT

Reference No.	: WTD25D05135627W004
FCC ID	: 2BAA5-MNSBA44H
Applicant	: AcoustMax International Corporation
Address	: Room 501, Lingyun Building, HongLang North 2 Road, Baoan District, ShenZhen, 518101, China
Manufacturer	: Shenzhen Fudeyuan Digital Technology Co., Ltd.
Address	: 1st Floor, No.3, Road 4 Dawei, Xingiao Community Xingiao Street, Baoan District, Shenzhen, 518000, Guangdong, China
Product	: Monster Soundstage Pro
Model(s)	: MNSBA44H, MNSBA44H-X, MNSBA44H PLUS, MNSBA44H-2, MNSBA44H-S, MNSBA44H-C, MNSBA44H-PRO, MNSBA44H-PROX, MNSBA44H-712, Xbar189DW-7.1.2
Standards	: FCC 47CFR Part 2 Subpart J Section 2.1091
Date of Receipt sample	: 2025-05-28
Date of Test	: 2025-06-04 to 2025-06-12
Date of Issue	: 2025-08-07
Test Result	: Pass

Remarks:

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

Prepared By:
Waltek Testing Group Co., Ltd.

Address: No. 77, Houjie Section, Guantai Road, Houjie Town, Dongguan City, Guangdong, China
Tel: +86-769-2267 6998
Fax: +86-769-2267 6828

Compiled by:

Estel Qian

Estel Qian / Project Engineer

Approved by:

Deval Qin



Deval Qin / Designated Reviewer

2. Contents

	Page
1. COVER PAGE.....	1
2. CONTENTS.....	2
3. REVISION HISTORY.....	3
4. GENERAL INFORMATION.....	4
4.1. GENERAL DESCRIPTION OF E.U.T.....	4
4.2. DETAILS OF E.U.T.	4
4.3. TEST FACILITY	5
4.4. SUBCONTRACTED	5
4.5. ABNORMALITIES FROM STANDARD CONDITIONS.....	5
5. TEST SUMMARY.....	6
6. RF EXPOSURE.....	7
6.1. DEFINITIONS	7
6.2. METHOD OF EVALUATION	7
6.3. EVALUATION RESULTS	9

3. Revision History

Test Report No.	Date of Receipt Sample	Date of Test	Date of Issue	Purpose	Comment	Approved
WTD25D05135627W004	2025-05-28	2025-06-04 to 2025-06-12	2025-08-07	Original	-	Valid

4. General Information

4.1. General Description of E.U.T.

Product:	Monster Soundstage Pro
Model(s):	MNSBA44H, MNSBA44H-X, MNSBA44H PLUS, MNSBA44H-2, MNSBA44H-S, MNSBA44H-C, MNSBA44H-PRO, MNSBA44H-PROX, MNSBA44H-712, Xbar189DW-7.1.2
Model Description:	Only the model names are different. Model MNSBA44H was tested in the report.
Test Sample No.:	1-1/1
Bluetooth Version:	V5.4
Hardware Version:	V1.2
Software Version:	V36

4.2. Details of E.U.T.

Operation Frequency:	2402~2480MHz
Max. RF output power:	Bluetooth: 5.58dBm BLE: 4.12dBm
Modulation Technology:	Bluetooth: GFSK, $\pi/4$ DQPSK, 8DPSK BLE: GFSK
Antenna installation:	internal permanent antenna
Antenna Gain:	BT: 1.8dBi BLE: 1.68dBi

Note:

#: The antenna gain is provided by the applicant, and the applicant should be responsible for its authenticity, WALTEK lab has not verified the authenticity of its information.

Ratings: AC 110-240V, 50/60Hz

4.3. Test Facility

The test facility has a test site registered with the following organizations:

ISED CAB identifier: CN0013. Test Firm Registration No.: 7760A.

Waltek Testing Group Co., Ltd. Has been registered and fully described in a report filed with the

Industry Canada. The acceptance letter from the Industry Canada is maintained in our files.

Registration number 7760A, October 15, 2016.

FCC Designation No.: CN1201. Test Firm Registration No.: 523476.

Waltek Testing Group Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration number 523476, September 10, 2019.

4.4. Subcontracted

Whether parts of tests for the product have been subcontracted to other labs:

Yes No

If Yes, list the related test items and lab information:

Test Lab: N/A

Lab address: N/A

Test items: N/A

4.5. Abnormalities from Standard Conditions

None.

5. Test Summary

Test Items	Test Requirement	Result
Exposure of Humans to RF Fields	47 CFR Part 2 §2. 1091	PASS

6. RF Exposure

Test Requirement: FCC 47CFR Part 2 Subpart J Section 2.1091

47 CFR Part 1 §1.1307

47 CFR Part 1 §1.1310

Evaluation Method: KDB 447498 D01 General RF Exposure Guidance v06

6.1. Definitions

According to § 2.1093 (b), A mobile device is defined as a transmitting device designed to be used in other than fixed locations and to generally be used in such a way that a separation distance of at least 20 centimeters is normally maintained between the RF source's radiating structure(s) and the body of the user or nearby persons.

This device belongs to mobile device and with multiple RF sources.

6.2. Method of Evaluation

**Determination of Exemption:
For single RF sources**

Option A

Option A 1-mW Test Exemption

Applies to all frequencies and all distances

- a) Could be considered SAR-based and MPE-based exclusions
- b) $P < 1\text{mW}$
- c) Limitation—when there are simultaneously operating transmitters this exclusion only applies when all simultaneously operating transmitters meet this exemption
- d) Refer 1.1307(b)(3)(i)(A) and 1.1307(b)(3)(ii)(A)

Option B SAR-Based Exemption

Frequency range 300 MHz -6 GHz, $5\text{mm} \leq \text{distance} \leq 40\text{cm}$

- a) The maximum time-averaged power or effective radiated power (ERP), whichever is greater, $\leq P_{th}$.
- b) P_{th} is calculated based on separation distance d cm from transmitter to person for the device operating at f GHz.

$$P_{th} (\text{mW}) = \begin{cases} ERP_{20\text{ cm}}(d/20\text{ cm})^x & d \leq 20\text{ cm} \\ ERP_{20\text{ cm}} & 20\text{ cm} < d \leq 40\text{ cm} \end{cases}$$

Where

$$x = -\log_{10} \left(\frac{60}{ERP_{20\text{ cm}} \sqrt{f}} \right) \text{ and } f \text{ is in GHz;}$$

and

$$ERP_{20\text{ cm}} (\text{mW}) = \begin{cases} 2040f & 0.3\text{ GHz} \leq f < 1.5\text{ GHz} \\ 3060 & 1.5\text{ GHz} \leq f \leq 6\text{ GHz} \end{cases}$$

d = the separation distance (cm);

Option C MPE-Based Exemption

1.1307(b)(3)(i)(C): ERP is below a threshold calculated based on the distance R between the person and the antenna / radiating structure, where $R > \lambda / 2\pi$.

Table 1 to § 1.1307(b)(3)(i)(C) - Single RF Sources Subject to Routine Environmental Evaluation

RF Source frequency (MHz)	Threshold ERP (watts)
0.3-1.34	1,920 R^2 .
1.34-30	3,450 R^2/f^2 .
30-300	3.83 R^2 .
300-1,500	0.0128 R^2f .
1,500-100,000	19.2 R^2 .

Note: R in meters, f in MHz

For multiple RF sources

According to 47CFR 1.1307(b)(3)(ii), the calculation formula is as follow:

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure Limit_k} \leq 1$$

6.3. Evaluation Results

This device belongs to mobile device (separation distance of at least 20 centimeters is normally maintained between the RF source's radiating structure(s) and the body of the user or nearby persons) and with multiple RF sources.

Option B is applicable.

Single Source Transmissions

Description	Frequency GHz	Conducted Power dBm	Gain dBi	Tune-up dB	ERP mW	ERP _{th} mW	Ratio
BT	2.441	5.58	1.84	±1.0	4.24	3060	0.00138
BLE	2.402	4.12	1.68	±1.0	2.92	3060	0.00095

Note:

EIRP= Conducted Power +Gain, ERP=EIRP-2.15

Simultaneous Transmissions

Description	Calculation	Limit
BT+BLE	0.00234	≤1.0

Note:

1. For conservativeness, the lowest frequency of each band is used to determine the limit of that band.
2. Chose the maximum power to do analysis.
3. BT and BLE can transmit simultaneously.

Conclusion:

RF Exposure is FCC compliant.

=====End of Report=====