



REPORT No.: SZ24070295W04

TEST REPORT

APPLICANT : Linkplay Technology Inc.

PRODUCT NAME : WiiM Amp Stereo Streaming Amplifier

MODEL NAME : AMP001

BRAND NAME : WiiM

FCC ID : 2BABF-AMP001B

STANDARD(S) : 47 CFR Part 15 Subpart E

RECEIPT DATE : 2024-07-31

TEST DATE : 2024-08-16 to 2024-09-05

ISSUE DATE : 2024-09-18



Edited by:

Zeng Xiaoying
Zeng Xiaoying (Rapporteur)

Approved by:

Shen Junsheng
Shen Junsheng (Supervisor)

NOTE: This document is issued by Shenzhen Morlab Communications Technology Co., Ltd., the test report shall not be reproduced except in full without prior written permission of the company. The test results apply only to the particular sample(s) tested and to the specific tests carried out which is available on request for validation and information confirmed at our website.

MORLAB

Shenzhen Morlab Communications Technology Co., Ltd.
FL.1-3, Building A, FeiYang Science Park, No.8 LongChang Road,
Block67, BaoAn District, ShenZhen, Guangdong Province, P. R. China

Tel: 86-755-36698555

Http://www.morlab.cn

Fax: 86-755-36698525

E-mail: service@morlab.cn





DIRECTORY

1. Summary of Test Result	3
1.1. Testing Applied Standards	4
1.2. Test Equipment List	5
1.3. Measurement Uncertainty	7
1.4. Testing Laboratory	7
2. General Description	8
2.1. Information of Applicant and Manufacturer	8
2.2. Information of EUT	8
2.3. Channel List of EUT	9
2.4. Test Configuration of EUT	10
2.5. Test Conditions	10
2.6. Test Setup Layout Diagram	11
3. Test Results	14
3.1. Conducted Emission	14
3.2. Restricted Frequency Bands	15
3.3. Radiated Emission	17
Annex A Test Data and Result	19

Change History		
Version	Date	Reason for change
1.0	2024-09-18	First edition



1. Summary of Test Result

No.	Section	Description	Test Date	Test Engineer	Result	Method Determination /Remark
1	15.203	Antenna Requirement	N/A	N/A	N/A ^{Note1}	N/A
2	ANSI C63.10	Duty Cycle of the Test Signal	N/A	N/A	N/A ^{Note1}	N/A
3	15.407(a)	Maximum Conducted Output Power	N/A	N/A	N/A ^{Note1}	N/A
4	15.407(a)(e)	Emission Bandwidth	N/A	N/A	N/A ^{Note1}	N/A
5	15.407(a)	Peak Power Spectral Density	N/A	N/A	N/A ^{Note1}	N/A
6	15.407(g)	Frequency Stability	N/A	N/A	N/A ^{Note1}	N/A
7	15.407(h)	DFS	N/A	N/A	N/A ^{Note1}	N/A
8	15.207	Conducted Emission	Aug. 16, 2024	Fan Shengquan	PASS	No deviation
9	15.407(b)	Restricted Frequency Bands	Aug. 25, 2024	Zhong Xiangyun	PASS	No deviation
10	15.407(b)	Radiated Emission	Aug. 30, 2024	Zhong Xiangyun	PASS	No deviation

Note 1: The test results of all conducted test items please refer to the module FCC test report (Report No.: SZ24040154W04), which issued on Jul. 26, 2024.

Note 2: The tests of Conducted Emission and Radiated Emission were performed according to the method of measurements prescribed in ANSI C63.102013.

Note 3: These RF tests were performed according to the method of measurements prescribed in KDB 789033 D02 v02r01.

Note 4: These RF tests were performed according to the method of measurements prescribed in KDB 905462 D02 UNII DFS Compliance Procedures New Rules v02.

Note 5: Additions to, deviation, or exclusions from the method shall be judged in the "method determination" column of add, deviate or exclude from the specific method shall be explained in the "Remark" of the above table.



Note 6: When the test result is a critical value, we will use the measurement uncertainty give the judgment result based on the 95% confidence intervals.

1.1. Testing Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 15 Subpart E Radio Frequency Devices



1.2. Test Equipment List

1.2.1 Conducted Emission Test Equipment

Equipment	Serial No.	Type	Manufacturer	Cal. Date	Due Date
Receiver	MY56400093	N9038A	KEYSIGHT	2024.01.25	2025.01.24
LISN	8127449	NSLK 8127	Schwarzbeck	2024.02.02	2025.02.01
Pulse Limiter (10dB)	VTSD 9561 F-B #206	VTSD 9561-F	Schwarzbeck	2024.05.30	2025.05.29
RF Coaxial Cable (DC-100MHz)	BNC	MRE04	Qualwave	2024.07.02	2025.07.01

1.2.2 List of Software Used

Description	Manufacturer	Software Version
Morlab EMCR	Morlab	V1.2
TS+ -[JS32-CE]	Tonscend	V2.5.0.0

**1.2.4 Radiated Test Equipment**

Equipment	Serial No.	Type	Manufacturer	Cal. Date	Due Date
Signal Analyzer	MY56060145	N9020A	Agilent	2024.05.30	2025.05.29
Test Antenna - Bi-Log	9163-519	VULB 9163	Schwarzbeck	2024.06.22	2025.06.21
Test Antenna - Loop	1519-022	FMZB1519	Schwarzbeck	2024.06.03	2025.06.02
Test Antenna – Horn	01774	BBHA 9120D	Schwarzbeck	2024.06.22	2025.06.21
Test Antenna – Horn	BBHA9170 #773	BBHA9170	Schwarzbeck	2024.06.22	2025.06.21
Preamplifier (10MHz-6GHz)	46732	S10M100L38 02	LUCIX CORP.	2024.05.30	2025.05.29
Preamplifier (2GHz-18GHz)	61171/61172	S020180L32 03	LUCIX CORP.	2024.05.30	2025.05.29
Preamplifier (18GHz-40GHz)	DS77209	DCLNA0118-40C-S	Decentest	2024.05.30	2025.05.29
RF Coaxial Cable (DC-18GHz)	MRE001	PE330	Pasternack	2024.05.30	2025.05.29
RF Coaxial Cable (DC-18GHz)	MRE002	CLU18	Pasternack	2024.05.30	2025.05.29
RF Coaxial Cable (DC-18GHz)	MRE003	CLU18	Pasternack	2024.05.30	2025.05.29
RF Coaxial Cable (DC-40GHz)	22290045	QA360-40-K K-0.5	Qualwave	2024.07.03	2025.07.02
RF Coaxial Cable (DC-40GHz)	22290046	QA360-40-K KF-2	Qualwave	2024.07.03	2025.07.02
RF Coaxial Cable (DC-18GHz)	22120181	QA500-18-N N-5	Qualwave	2024.07.03	2025.07.02
Anechoic Chamber	N/A	9m*6m*6m	CRT	2022.05.10	2025.05.09



1.3. Measurement Uncertainty

Test Items	Uncertainty	Remark
Restricted Frequency Bands	±5%	Confidence levels of 95%
Radiated Emission	±2.95dB	Confidence levels of 95%
Conducted Emission	±2.44dB	Confidence levels of 95%

1.4. Testing Laboratory

Laboratory Name	Shenzhen Morlab Communications Technology Co., Ltd.
Laboratory Address	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China
Telephone	+86 755 36698555
Facsimile	+86 755 36698525
FCC Designation Number	CN1192
FCC Test Firm Registration Number	226174



2. General Description

2.1. Information of Applicant and Manufacturer

Applicant	Linkplay Technology Inc.
Applicant Address	8000 Jarvis Avenue Suite #130, Newark, CA 94560
Manufacturer	Linkplay Technology Inc.
Manufacturer Address	8000 Jarvis Avenue Suite #130, Newark, CA 94560

2.2. Information of EUT

Product Name:	WiiM Amp Stereo Streaming Amplifier
Sample No.:	3#
Hardware Version:	A98D V02+Main Board V02
Software Version:	Linkplay.5.2623956
Modulation Technology:	OFDM, OFDMA
Modulation Mode:	802.11a, 802.11n (HT20), 802.11n (HT40) 802.11ac (VHT20), 802.11ac (VHT40), 802.11ac (VHT80) 802.11ax (HEW20), 802.11ax (HEW40), 802.11ax (HEW80)
Operating Frequency Range:	5180MHz-5240MHz; 5260MHz-5320MHz; 5500MHz-5720MHz; 5745MHz-5825MHz
Antenna Type:	PIFA Antenna
Antenna Gain:	ANT1: 2.67dBi; ANT2: 2.67dBi

Note 1: The test results of all conducted test items please refer to the module FCC test report (Report No.: SZ24040154W04), which issued on Jul. 26, 2024. We only recorded the radiated test result in this report.

Note 2: The EUT has two antennas that cannot transmit simultaneously. Both of the two antennas were evaluated separately, only the worst test result (ANT1) were recorded in the test report.

Note 3: For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacturer.

2.3.Channel List of EUT

(U-NII-1) 5180MHz-5240MHz				
Bandwidth	Channel	Frequency (MHz)	Channel	Frequency (MHz)
20MHz	36	5180	40	5200
	44	5220	48	5240
40MHz	38	5190	46	5230
80MHz	42	5210		
(U-NII-2A) 5260MHz-5320MHz				
Bandwidth	Channel	Frequency (MHz)	Channel	Frequency (MHz)
20MHz	52	5260	56	5280
	60	5300	64	5320
40MHz	54	5270	62	5310
80MHz	58	5290		
(U-NII-2C) 5500MHz-5720MHz				
Bandwidth	Channel	Frequency (MHz)	Channel	Frequency (MHz)
20MHz	100	5500	105	5520
	108	5540	112	5560
	116	5580	120	5600
	124	5620	128	5640
	132	5660	136	5680
	140	5700	144	5720
40MHz	102	5510	110	5550
	118	5590	126	5630
	134	5670	142	5710
80MHz	106	5530	122	5610
	138	5690		
(U-NII-3) 5745MHz-5825MHz				
Bandwidth	Channel	Frequency (MHz)	Channel	Frequency (MHz)
20MHz	149	5745	153	5765
	157	5785	161	5805
	165	5825		
40MHz	151	5755	159	5795
80MHz	155	5775		

Note 1: The black bold channels were selected for test.

2.4. Test Configuration of EUT

2.4.1. Modulation Type and Data Rate of EUT

Mode	Bandwidth (MHz)	Modulation Technology	Modulation Type	Data Rate	RU Size
802.11a	20	OFDM	BPSK	6/9/12/18/24/36/48/54Mbps	N/A
			QPSK		
			16QAM		
			64QAM		
802.11n	20/40 (HT20/40)	OFDM	BPSK	MCS0~MCS7	N/A
			QPSK		
			16QAM		
			64QAM		
802.11ac	20/40/80 (VHT20/40/80)	OFDM	BPSK	MCS0~MCS9	N/A
			QPSK		
			16QAM		
			64QAM		
			256QAM		
802.11ax	20/40/80 (HEW20/40/80)	OFDM/ OFDMA	BPSK	MCS0~MCS11	26/52/106/242/484
			QPSK		
			16QAM		
			64QAM		
			256QAM		
			1024QAM		


Note1: The worst-case mode (bold face) in all data rates has been determined during the pre-scan, only the test data of the worst-case were recorded in this report.

2.5. Test Conditions

Temperature (°C)	15–35
Relative Humidity (%)	30–60
Atmospheric Pressure (kPa)	86–106


2.6. Test Setup Layout Diagram

2.6.1. Conducted Emission Measurement




2.6.2.Radiation Measurement


1) For radiated emissions from 9kHz to 30MHz



2) For radiated emissions from 30MHz to 1GHz



3) For radiated emissions above 1GHz



3. Test Results

3.1. Conducted Emission

3.1.1. Requirement

According to FCC section 15.207, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150kHz to 30MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 Ω line impedance stabilization network (LISN).

Frequency Range (MHz)	Conducted Limit (dB μ V)	
	Quai-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
5 - 30	60	50

Note:

- (a) The lower limit shall apply at the band edges.
- (b) The limit decreases linearly with the logarithm of the frequency in the range 0.15 - 0.50MHz.

3.1.2. Test Procedures

The Table-top EUT was placed upon a non-metallic table 0.8m above the horizontal metal reference ground plane. EUT was connected to LISN and LISN was connected to reference Ground Plane. EUT was 80cm from LISN. The set-up and test methods were according to ANSI C63.10: 2013.

3.1.3. Test Setup Layout

Refer to chapter 2.6.2 in this report.

3.1.4. Test Result

Refer to Annex A.1 in this report.

3.2. Restricted Frequency Bands

3.2.1. Requirement

The peak emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:

- (1) For transmitters operating in the 5.15–5.25 GHz band: all emissions outside of the 5.15–5.35 GHz band shall not exceed an EIRP of -27dBm/MHz.
- (2) For transmitters operating in the 5.25–5.35 GHz band: all emissions outside of the 5.15–5.35 GHz band shall not exceed an EIRP of -27dBm/MHz.
- (3) For transmitters operating in the 5.47–5.725 GHz band: all emissions outside of the 5.47–5.725 GHz band shall not exceed an EIRP of -27dBm/MHz.
- (4) For transmitters operating in the 5.725-5.85 GHz band:
 - (i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

The following formula is used to convert the equipment isotropic radiated power(e.i.r.p.) to field strength (dBμV/m);

$$E = 1000000 \times \sqrt{30P} / 3 \mu\text{V/m}$$

where P is the EIRP in Watts

Therefore: -27 dBm/MHz = 68.23 dBuV/m



Unwanted emissions below 1 GHz must comply with the general field strength limits set forth in § 15.209. According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength ($\mu\text{V/m}$)	Measurement Distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

For Above 1000MHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), also should comply with the radiated emission limits specified in Section 15.209(a)(above table).

3.2.2.Test Procedures

The EUT is located in a 3m Semi-Anechoic Chamber; the antenna factors, cable loss and so on of the site as factors are calculated to correct the reading.

KDB 789033 Section H) 3)5)6(d)) was used in order to prove compliance

For the Test Antenna:

Test Antenna is 3m away from the EUT. Test Antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength.

3.2.3.Test Setup Layout

Refer to chapter 2.6.3 in this report.

3.2.4.Test Result

Refer to Annex A.2 in this report.

3.3. Radiated Emission

3.3.1. Requirement

The peak emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:

- (1) For transmitters operating in the 5.15–5.25 GHz band: all emissions outside of the 5.15–5.35 GHz band shall not exceed an EIRP of -27dBm/MHz.
- (2) For transmitters operating in the 5.25–5.35 GHz band: all emissions outside of the 5.15–5.35 GHz band shall not exceed an EIRP of -27dBm/MHz.
- (3) For transmitters operating in the 5.47–5.725 GHz band: all emissions outside of the 5.47–5.725 GHz band shall not exceed an EIRP of -27dBm/MHz.
- (4) For transmitters operating in the 5.725-5.85 GHz band: All emissions within the frequency range from the band edge to 10 MHz above or below the band edge shall not exceed an e.i.r.p. of -17 dBm/MHz; for frequencies 10 MHz or greater above or below the band edge, emissions shall not exceed an e.i.r.p. of -27 dBm/MHz.

The following formula is used to convert the equipment isotropic radiated power(e.i.r.p.) to field strength (dBμV/m);

$$E = 1000000 \times \sqrt{30P} / 3 \mu\text{V/m}$$

where P is the EIRP in Watts

Therefore: -27 dBm/MHz = 68.23 dBuV/m

Unwanted emissions below 1 GHz must comply with the general field strength limits set forth in § 15.209. According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (μV/m)	Measurement Distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3



For Above 1000MHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), also should comply with the radiated emission limits specified in Section 15.209(a)(above table).

3.3.2.Test Procedures

The EUT is placed on a non-conducting table 80 cm above the ground plane for measurement below 1GHz; 1.5 m above the ground plane for measurement above 1GHz. The antenna to EUT distance is 3meters. The EUT is configured in accordance with ANSI C63.10. The EUT is set to transmit in a continuous mode.

For measurements below 30MHz, the emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9kHz-90 kHz, 110kHz-490 kHz. Radiated emission limits in these two bands are based on measurements employing an average detector.

For measurements below 1GHz the resolution bandwidth is set to 100kHz for peak detection measurements or 120kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.

For measurements above 1GHz the resolution bandwidth is set to 1MHz, the video band width is set to 3MHz for peak measurements and as applicable for average measurements.

The EUT is rotated through 360 degrees to maximize emissions received. The antenna is scanned from 1 to 4 meters above the ground plane to further maximize the emission. Measurements are made with the antenna polarized in both the vertical and the horizontal positions. For measurements above 1 GHz, keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response.

3.3.3.Test Setup Layout

Refer to chapter 2.6.3 in this report.

3.3.4.Test Result

Refer to Annex A.3 in this report.



Annex A Test Data and Result

A.1. Conducted Emission

The maximum conducted interference is searched using Peak (PK), if the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. Set RBW=9kHz, VBW=30kHz. Refer to recorded points and plots below.

Note: Both of the test voltage AC 120V/60Hz and AC 230V/50Hz were considered and tested respectively, only the results of the worst case AC 120V/60Hz were recorded in this report.

A. Test Setup:

Test Mode: EUT + PC +PC Adapter + WIFI TX

Test voltage: AC 120V/60Hz


The measurement results are obtained as below:

$E [dB\mu V] = U_R + L_{Cable\ loss} [dB] + A_{Factor}$

U_R : Receiver Reading


A_{Factor} : Voltage division factor of LISN

B. Test Plot:



(L Phase)

No.	Fre. (MHz)	Emission Level (dBμV)		Limit (dBμV)		Power-line	Verdict
		Quai-peak	Average	Quai-peak	Average		
1	0.2308	40.74	26.61	62.42	52.42	Line	PASS
2	0.2713	38.27	25.12	61.08	51.08		PASS
3	0.4739	30.99	25.69	56.45	46.45		PASS
4	0.8934	29.04	22.10	56.00	46.00		PASS
5	1.6994	28.27	22.53	56.00	46.00		PASS
6	10.2446	27.64	24.99	60.00	50.00		PASS



(N Phase)

No.	Fre. (MHz)	Emission Level (dBμV)		Limit (dBμV)		Power-line	Verdict
		Quai-peak	Average	Quai-peak	Average		
1	0.1592	49.74	29.57	65.51	55.51	Neutral	PASS
2	0.2582	43.73	39.24	61.49	51.49		PASS
3	0.3437	38.34	23.93	59.11	49.11		PASS
4	0.5143	39.81	36.58	56.00	46.00		PASS
5	0.7623	33.17	27.06	56.00	46.00		PASS
6	3.8887	28.50	22.33	56.00	46.00		PASS



A.2. Restricted Frequency Bands

The lowest and highest channels are tested to verify the Restricted Frequency Bands.

The measurement results are obtained as below:

$$E \text{ [dB}\mu\text{V/m]} = U_R + A_T + A_{\text{Factor}} \text{ [dB]}; A_T = L_{\text{Cable loss}} \text{ [dB]} - G_{\text{preamp}} \text{ [dB]}$$

A_T : Total correction Factor except Antenna

U_R : Receiver Reading

G_{preamp} : Preamplifier Gain

A_{Factor} : Antenna Factor at 3m


Note 1: Restricted Frequency Bands were performed when antenna was at vertical and horizontal polarity, and only the worse test condition (Horizontal) was recorded in this test report.

Note 2: Restricted Frequency Bands were performed in X, Y, Z axis direction, and only the worst axis test condition was recorded in this test report.


Note 3: All test modes and bandwidth were considered and evaluated respectively by performing full test, only the worst data were recorded for each bandwidth.

802.11a Mode


Channel	Frequency (MHz)	Detector	Receiver Reading U_R (dB μ V)	A_T (dB)	A_{Factor} (dB@3m)	Max. Emission E (dB μ V/m)	Limit (dB μ V/m)	Verdict
		PK/ AV						
36	5143.28	PK	47.55	-21.29	32.20	58.46	74	PASS
36	5148.72	AV	36.41	-21.29	32.20	47.32	54	PASS
64	5350.80	PK	51.96	-20.66	32.20	63.50	74	PASS
64	5350.38	AV	33.70	-20.66	32.20	45.24	54	PASS
100	5469.20	PK	50.63	-20.24	32.20	62.59	68.23	PASS
100	5460.00	AV	32.55	-20.24	32.20	44.51	54	PASS
144	5727.30	PK	48.38	-20.24	32.20	60.34	68.23	PASS
149	5725.00	PK	59.80	-21.11	32.20	70.89	122.23	PASS
165	5850.00	PK	50.01	-21.11	32.20	61.10	122.23	PASS




(PEAK, Channel 36, 802.11a)




(AVERAGE, Channel 36, 802.11a)




(PEAK, Channel 64, 802.11a)




(AVERAGE, Channel 64, 802.11a)




(PEAK, Channel 100, 802.11a)




(AVERAGE, Channel 100, 802.11a)



(PEAK, Channel 144, 802.11a)




(PEAK, Channel 149, 802.11a)




(PEAK, Channel 165, 802.11a)

**802.11n (HT40) Mode**

Channel	Frequency (MHz)	Detector	Receiver Reading U_R (dB μ V)	A_T (dB)	A_{Factor} (dB@3m)	Max. Emission E (dB μ V/m)	Limit (dB μ V/m)	Verdict
		PK/ AV						
38	5147.91	PK	46.77	-21.29	32.20	57.68	74	PASS
38	5148.60	AV	38.41	-21.29	32.20	49.32	54	PASS
62	5352.60	PK	45.62	-20.66	32.20	57.16	74	PASS
62	5350.50	AV	36.53	-20.66	32.20	48.07	54	PASS
102	5469.71	PK	49.57	-20.24	32.20	61.53	68.23	PASS
102	5460.00	AV	38.27	-20.24	32.20	50.23	54	PASS
142	5731.71	PK	43.88	-20.24	32.20	55.84	68.23	PASS
151	5720.00	PK	54.62	-21.11	32.20	65.71	110.83	PASS
159	5850.00	PK	45.17	-21.11	32.20	56.26	110.83	PASS




(PEAK, Channel 38, 802.11n (HT40))




(AVERAGE, Channel 38, 802.11n (HT40))




(PEAK, Channel 62, 802.11n (HT40))




(AVERAGE, Channel 62, 802.11n (HT40))




(PEAK, Channel 102, 802.11n (HT40))




(AVERAGE, Channel 102, 802.11n (HT40))



(PEAK, Channel 142, 802.11n (HT40))




(PEAK, Channel 151, 802.11n (HT40))




(PEAK, Channel 159, 802.11n (HT40))

**802.11ac (VHT80) Mode**


Channel	Frequency (MHz)	Detector	Receiver Reading U_R (dBμV)	A_T (dB)	A_{Factor} (dB@3m)	Max. Emission E (dBμV/m)	Limit (dBμV/m)	Verdict
		PK/ AV						
42	5138.00	PK	49.49	-21.29	32.20	60.40	74	PASS
42	5150.00	AV	40.63	-21.29	32.20	51.54	54	PASS
58	5362.00	PK	49.20	-20.66	32.20	60.74	74	PASS
58	5351.80	AV	38.08	-20.66	32.20	49.62	54	PASS
106	5461.63	PK	46.89	-20.24	32.20	58.85	74	PASS
106	5460.00	AV	32.43	-20.24	32.20	44.39	54	PASS
138	5737.14	PK	40.79	-20.24	32.20	52.75	68.23	PASS
155	5720.00	PK	51.73	-21.11	32.20	62.82	110.83	PASS
155	5850.00	PK	43.30	-21.11	32.20	54.39	122.23	PASS




(PEAK, Channel 42, 802.11ac (VHT80))




(AVERAGE, Channel 42, 802.11ac (VHT80))




(PEAK, Channel 58, 802.11ac (VHT80))




(AVERAGE, Channel 58, 802.11ac (VHT80))




(PEAK, Channel 106, 802.11ac (VHT80))



(AVERAGE, Channel 106, 802.11ac (VHT80))



(PEAK, Channel 138, 802.11ac (VHT80))



(PEAK, Channel 155, 802.11ac (VHT80))



A.3. Radiated Emission

According to ANSI C63.10, because of peak detection will yield amplitudes equal to or greater than amplitudes measured with the quasi-peak (or average) detector, the measurement data from a spectrum analyzer peak detector will represent the worst-case results, if the peak measured value complies with the quasi-peak (or average) limit, it is unnecessary to perform an quasi-peak measurement (or average).

The measurement results are obtained as below:

$$E \text{ [dB}\mu\text{V/m]} = U_R + A_T + A_{\text{Factor}} \text{ [dB]}; A_T = L_{\text{Cable loss}} \text{ [dB]} - G_{\text{preamp}} \text{ [dB]}$$

A_T : Total correction Factor except Antenna

U_R : Receiver Reading

G_{preamp} : Preamplifier Gain

A_{Factor} : Antenna Factor at 3m

During the test, the total correction Factor A_T and A_{Factor} were built in test software.

Note1: All radiated emission tests were performed in X, Y, Z axis direction. And only the worst axis (Y axis) test condition was recorded in this test report.


Note2: For the frequency, which started from 9kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit was not recorded.

Note3: For the frequency, which started from 18GHz to 40GHz, was pre-scanned and the result which was 20dB lower than the limit was not recorded.

Note 4: All test modes, bandwidth and channel were considered and evaluated respectively by performing full test, only the worst data were recorded.


**802.11a Mode**

Plot for Channel 44



Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
110.510	32.12	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
2415.467	44.78	N/A	N/A	68.23	N/A	N/A	Horizontal	PASS
3126.680	42.53	N/A	N/A	68.23	N/A	N/A	Horizontal	PASS
4734.440	48.71	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
7980.760	46.79	N/A	N/A	68.23	N/A	N/A	Horizontal	PASS
13574.040	47.57	N/A	N/A	68.23	N/A	N/A	Horizontal	PASS


(Antenna Horizontal, 30MHz to 18GHz)



Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
109.540	31.22	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
2404.800	44.86	N/A	N/A	68.23	N/A	N/A	Vertical	PASS
4029.120	46.82	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
4743.680	48.84	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
7087.560	46.95	N/A	N/A	68.23	N/A	N/A	Vertical	PASS
13490.880	47.61	N/A	N/A	68.23	N/A	N/A	Vertical	PASS


(Antenna Vertical, 30MHz to 18GHz)

Plot for Channel 60



Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
108.570	32.02	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
2403.733	45.64	N/A	N/A	68.23	N/A	N/A	Horizontal	PASS
3126.680	43.81	N/A	N/A	68.23	N/A	N/A	Horizontal	PASS
4743.680	48.95	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
7993.080	46.76	N/A	N/A	68.23	N/A	N/A	Horizontal	PASS
13574.040	47.71	N/A	N/A	68.23	N/A	N/A	Horizontal	PASS

(Antenna Horizontal, 30MHz to 18GHz)




Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
109.540	32.60	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
2417.600	45.23	N/A	N/A	68.23	N/A	N/A	Vertical	PASS
3129.760	42.53	N/A	N/A	68.23	N/A	N/A	Vertical	PASS
4734.440	48.75	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
5288.840	48.56	N/A	N/A	68.23	N/A	N/A	Vertical	PASS
11778.400	47.47	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 30MHz to 18GHz)




Plot for Channel 120



Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
113.420	32.14	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
2466.133	45.45	N/A	N/A	68.23	N/A	N/A	Horizontal	PASS
3135.920	42.75	N/A	N/A	68.23	N/A	N/A	Horizontal	PASS
4056.840	47.49	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
4743.680	49.45	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
11193.200	47.94	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 30MHz to 18GHz)




Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
110.510	32.34	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
2404.267	44.82	N/A	N/A	68.23	N/A	N/A	Vertical	PASS
3123.600	44.87	N/A	N/A	68.23	N/A	N/A	Vertical	PASS
4740.600	48.98	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
5695.400	48.37	N/A	N/A	68.23	N/A	N/A	Vertical	PASS
11193.200	47.82	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 30MHz to 18GHz)



Plot for Channel 157



Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
99.840	31.83	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
2449.067	46.04	N/A	N/A	68.23	N/A	N/A	Horizontal	PASS
3120.520	42.58	N/A	N/A	68.23	N/A	N/A	Horizontal	PASS
4740.600	49.95	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
5769.320	48.47	N/A	N/A	68.23	N/A	N/A	Horizontal	PASS
11559.720	48.77	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 30MHz to 18GHz)



Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
113.420	32.83	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
2400.000	44.83	N/A	N/A	68.23	N/A	N/A	Vertical	PASS
3132.840	42.50	N/A	N/A	68.23	N/A	N/A	Vertical	PASS
4731.360	48.54	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
5806.280	48.57	N/A	N/A	68.23	N/A	N/A	Vertical	PASS
11581.280	48.62	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 30MHz to 18GHz)

END OF REPORT