

## RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

FCC ID: 2BABX-IOT40

### EUT Specification

| EUT                               | Wifi Digital Photo Frame  |
|-----------------------------------|---|
| <b>Frequency band (Operating)</b> | <input type="checkbox"/> WLAN: 2.412GHz ~ 2.462GHz<br><input type="checkbox"/> WLAN: 5.18GHz ~ 5.24GHz<br><input type="checkbox"/> WLAN: 5.745GHz ~ 5.825GHz<br><input checked="" type="checkbox"/> Others: Bluetooth: 2402-2480MHz<br>FDD Band 2: 1850.7 MHz – 1909.3 MHz<br>FDD Band 4: 1710.7 MHz – 1754.3 MHz<br>FDD Band 5: 824.7 MHz – 848.3 MHz<br>FDD Band 7: 2502.5 MHz – 2567.5 MHz |
| <b>Device category</b>            | <input type="checkbox"/> Portable (<20cm separation)<br><input checked="" type="checkbox"/> Mobile (>20cm separation)<br><input type="checkbox"/> Others _____  |
| <b>Exposure classification</b>    | <input type="checkbox"/> Occupational/Controlled exposure<br><input checked="" type="checkbox"/> General Population/Uncontrolled exposure   |
| <b>Antenna diversity</b>          | <input checked="" type="checkbox"/> Single antenna<br><input type="checkbox"/> Multiple antennas<br><input type="checkbox"/> Tx diversity<br><input type="checkbox"/> Rx diversity<br><input type="checkbox"/> Tx/Rx diversity  |
| <b>Antenna gain (Max)</b>         | BLE: 0.5 dBi<br>FDD Band 2: 2.19dBi<br>FDD Band 4: -1.90dBi<br>FDD Band 5: -6.11dBi<br>FDD Band 7: -1.65dBi   |
| <b>Evaluation applied</b>         | <input checked="" type="checkbox"/> MPE Evaluation<br><input type="checkbox"/> SAR Evaluation   |

### Limits for Maximum Permissible Exposure(MPE)

| Frequency Range(MHz)   | Electric Field Strength(V/m) | Magnetic Field Strength(A/m) | Power Density(mW/cm <sup>2</sup> ) | Average Time |
|--|------------------------------|------------------------------|------------------------------------|--------------|
| <b>(A) Limits for Occupational/Control Exposures</b>         |                              |                              |                                    |              |
| <b>300-1500</b>  | --                           | --                           | <b>F/300</b>                       | <b>6</b>     |
| <b>1500-100000</b>   | --                           | --                           | <b>5</b>                           | <b>6</b>     |
| <b>(B) Limits for General Population/Uncontrol Exposures</b> |                              |                              |                                    |              |
| <b>300-1500</b>  | --                           | --                           | <b>F/1500</b>                      | <b>30</b>    |
| <b>1500-100000</b>   | --                           | --                           | <b>1</b>                           | <b>30</b>    |

**Friis transmission formula:  $P_d = (P_{out} * G) / (4 * \pi * R^2)$**

Where

$P_d$ = Power density in mW/cm<sup>2</sup>

$P_{out}$ =output power to antenna in mW

$G$ = gain of antenna in linear scale

$\pi=3.1416$

$R$ = distance between observation point and center of the radiator in cm

$P_d$  the limit of MPE. If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

### Max Measurement Result

| Operating Mode | Measured Power | Max. Tune up Power | Antenna Gain | Power density at 20cm | Power density Limits (mW/cm <sup>2</sup> ) |
|----------------|----------------|--------------------|--------------|-----------------------|--|
|                | (dBm)          | (dBm)              | (dBi)        | (mW/cm <sup>2</sup> ) |  |
| BLE            | 6.83           | 7.00               | 0.5          | 0.0011                | 1  |
| LTE Band 2     | 23.27          | 23.50              | 2.19         | 0.0738                | 1  |
| LTE Band 4     | 22.78          | 23.00              | -1.90        | 0.0256                | 1  |
| LTE Band 5     | 24.12          | 24.50              | -6.11        | 0.0137                | 0.55                                       |
| LTE Band 7     | 23.03          | 23.50              | -1.65        | 0.0305                | 1  |

**The LTE and BLE can transmit simultaneously, the worst case is transmitting at BLE+LTE Band 2 mode:**

$$\sum_i \frac{S_i}{S_{Limit,i}}$$

$$= S_{BLE}/S_{Limit-BLE} + S_{LTE B2}/S_{Limit-LTE B2}$$

$$= 0.0011/1 + 0.0738/1$$

$$= 0.0749$$

$$< 1.0$$

**Result:** No Standalone SAR test is required.