

TEST REPORT

Applicant Name : GLAZERO INTERNATIONAL INC
Address : 8 The Green, Suite A in the City of Dover. Zip code 19901.
Report Number : 2504P41792E-RF
FCC ID: 2BACU-C9L2

Test Standard (s)

47 CFR §1.1307& §2.1091

Sample Description

Product Type: SolarCam D1 Lite
Model No.: C9L, DC9L, C9L2DA11
Trade Mark: aosu, DEKCO, saatto, zoohi
Date Received: 2025-08-01
Report Date: 2025-08-13

Test Result:	The EUT complied with the standards above.
--------------	--

Prepared and Checked By:



Amanda Wei
EMC Engineer

Approved By:



Bob.Liao
EMC Engineer

Note: This report must not be used by the customer to claim product certification, approval, or endorsement by A2LA, or any agency of the Federal Government. The information marked “#” is provided by the applicant, the laboratory is not responsible for its authenticity and this information can affect the validity of the result in the test report. Customer model name, addresses, names, trademarks etc. are included but no need marked.
This report cannot be reproduced except in full, without prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

Shenzhen Accurate Technology Co., Ltd.

Floor 1, KuMaKe Building, Dongzhou Community, Guangming Street, Guangming District, Shenzhen, Guangdong, China.

Tel: +86 755-26503290

Web: www.atc-lab.com

TABLE OF CONTENTS

DOCUMENT REVISION HISTORY	3
GENERAL INFORMATION	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
TEST FACILITY	4
RF EXPOSURE	5
APPLICABLE STANDARD.....	5
TEST RESULT	5
EXHIBIT A-EUT PHOTOGRAPHS	6

DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
Rev.00	2504P41792E-RF	Original Report	2025-08-13

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Product	SolarCam D1 Lite
Tested Model	C9L
Multiple Model	DC9L, C9L2DA11
Model Difference [#]	The multiple models are electrically identical with the test model except for model name, brands and sales channels. Please refer to DOS letter for details. The applicant provided model "C9L" for testing.
Voltage Range [#]	DC 5V from Type C port DC 3.7V from rechargeable battery

Frequency Range	BLE 1M: 2402-2480MHz 2.4G Wi-Fi: 2412-2462MHz
Antenna Specification [#]	Dipole Antenna: 3.2 dBi (It is provided by the applicant.)
Sample Serial Number	31PU-3 (Assigned by ATC, Shenzhen)
Sample/EUT Status	Good condition

Objective

This test report is in accordance with Part 1-Subpart I and Part 2-Subpart J, Radiofrequency Radiation Exposure of the Federal Communication Commission rules.

The tests were performed in order to determine compliance with §1.1307 & §2.1091 rules.

Test Facility

The test site used by Shenzhen Accurate Technology Co., Ltd. to collect test data is located on the Floor 1, KuMaKe Building, Dongzhou Community, Guangming Street, Guangming District, Shenzhen, Guangdong, China.

Accredited by American Association for Laboratory Accreditation (A2LA). The Certificate Number is 4297.01.

RF EXPOSURE

Applicable Standard

According to FCC §1.1307(b), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB 447498 D04 Interim General RF Exposure Guidance v01, clause 2.1.4 –MPE-Based Exemption:

An alternative to the SAR-based exemption is provided in § 1.1307(b)(3)(i)(C), for a much wider frequency range, from 300 kHz to 100 GHz, applicable for separation distances greater or equal to $\lambda/2\pi$, where λ is the free-space operating wavelength in meters. The MPE-based test exemption condition is in terms of ERP, defined as the product of the maximum antenna gain and the delivered maximum time-averaged power. For this case, a RF source is an RF exempt device if its ERP (watts) is no more than a frequency-dependent value, as detailed tabular form in Appendix B. These limits have been derived based on the basic specifications on Maximum Permissible Exposure (MPE) considered for the FCC rules in § 1.1310(e)(1).

Table to § 1.1307(b)(3)(i)(C) - Single RF Sources Subject to Routine Environmental Evaluation

RF Source frequency (MHz)	Threshold ERP (watts)
0.3-1.34	$1,920 R^2$.
1.34-30	$3,450 R^2/f^2$.
30-300	$3.83 R^2$.
300-1,500	$0.0128 R^2f$.
1,500-100,000	$19.2R^2$.

f = frequency in MHz;

R = minimum separation distance from the body of a nearby person (appropriate units, e.g., m);

Test result

For worst case:

Mode	Frequency Range (MHz)	Tune-Up Conducted Output Power [#] (dBm)	Antenna Gain [#]		ERP		Evaluation Distance (cm)	MPE-Based Exemption (mW)
			(dBi)	(dBd)	(dBm)	(mW)		
BLE	2402-2480	5.5	3.2	1.05	6.55	4.52	20	768.0
2.4G WIFI	2412-2462	18.0	3.2	1.05	19.05	80.35	20	768.0

Note 1: The tune-up power and antenna gain are declared by the applicant.

Note 2: 0dBd=2.15dBi.

Note 3: The BLE and 2.4G WIFI can't transmission simultaneously.

To maintain compliance with the FCC's RF exposure guidelines, place the equipment at least 20cm from nearby persons.

Result: Compliance.

EXHIBIT A-EUT PHOTOGRAPHS

Please refer to the Attachment No.1 2504P41792E-RF EUT External Photos and Attachment No.2 2504P41792E-RF EUT Internal Photos

******* END OF REPORT *******