

# RF Exposure

<b>Applicant</b>	: GLAZERO INTERNATIONAL INC
<b>Address</b>	: 8 The Green, Suite A in the City of Dover. Zip code 19901.
<b>Product Name</b>	: SolarCam T2 Ultra
<b>Brand Mark</b>	: AOSU, DEKCO, Saato, Zooli
<b>Model</b>	: C9X11
<b>Series model</b>	: C9X, DC9X, C9X12, C9X13, C9X14, C9X15, C9X16
<b>FCC ID</b>	: 2BACU-C9X
<b>Report Number</b>	: BLA-EMC-202508-A2603
<b>Date of Receipt</b>	: Aug. 7, 2025
<b>Date of Test</b>	: Aug. 7, 2025 to Sep. 12, 2025
<b>Test Standard</b>	: KDB447498D04 General RF Exposure Guidance v01
<b>Test Result</b>	: Pass

Compiled by: *Hugh*

Review by: *Xavier*

Approved by: *Blue Zheng*

Issued Date: Sep. 12, 2025

**BlueAsia of Technical Services(Shenzhen) Co.,Ltd.**

Address: Building C, No. 107, Shihuan Road, Shiyan Sub-District, Baoan District, Shenzhen, Guangdong Province, China



*The test report is effective only with both signature and specialized stamp and The result(s) shown in this report refer only to the sample(s) tested. Without written approval of BlueAsia, this report can't be reproduced except in full. The results described in this report do not represent the quality or characteristics of the sampled batch, nor do they represent any similar or identical products that are not explicitly stated.*



## Table of Contents

<b>1</b>	<b>General information .....</b>	<b>4</b>
1.1	General information .....	4
1.2	General description of EUT .....	4
<b>2</b>	<b>RF Exposure Compliance Requirement .....</b>	<b>6</b>
2.1	Standard Requirement .....	6
2.2	Limits .....	6
2.3	Result .....	7

## Revise Record

Version No.	Date	Description
01	Sep. 12, 2025	Original

BlueAsia

## 1 General information

### 1.1 General information

Applicant	GLAZERO INTERNATIONAL INC
Address	8 The Green, Suite A in the City of Dover. Zip code 19901.
Manufacturer	Shenzhen Zhiling Technology Co., Ltd
Address	Room 201, Building A, No.1 Qianwan Road, Qianhai Shenzhen-HongKong Cooperation Zone, Shenzhen, Guangdong, China
Factory	Luxshare Precision Industry Co., Ltd.
Address	2F Comprehensive Building No.313 Beihuan Road Qingxi Town Dongguan City, Guangdong Province. China
Factory	Dongguan Anran smart technology Co., LTD
Address	Building6, No.10Hongniu Road, Huangjiang Town, Dongguan, Guangdong, China
Factory	LEADER TECH VIET NAM COMPANY LIMITED
Address	D16A and D16B factory, Lot 99B, No.2,15 Street, VSIP Nghe An Industrial Park, Hung Nguyen Town, Hung Nguyen District, Nghe An Province, Viet Nam.

### 1.2 General description of EUT

Product name	SolarCam T2 Ultra
Model no.	C9X11
Series model	C9X, DC9X, C9X12, C9X13, C9X14, C9X15, C9X16
Desc of series model	The software and hardware of the product are consistent between the reported model and the main certification model, and the difference is only used to distinguish different sales channels.
Operation Frequency:	2412MHz-2462MHz
Operation Frequency:	802.11b/g/n(HT20): 2412MHz to 2462MHz 802.11n(HT40): 2422MHz to 2452MHz
Modulation Type:	802.11b: DSSS (CCK, DQPSK, DBPSK) 802.11g/n: OFDM (64QAM, 16QAM, QPSK, BPSK)
Channel Spacing:	5MHz
Number of Channels:	802.11b/g/n(HT20): 11 802.11n(HT40): 7
Antenna Type:	PCB antenna
Antenna Gain:	2.12dBi(Provided by customer)

**BlueAsia** of Technical Services (Shenzhen) Co., Ltd

Tel: +86-755-23059481

Email: [marketing@cblueasia.com](mailto:marketing@cblueasia.com) [www.cblueasia.com](http://www.cblueasia.com)

Version:v1.1

Power supply or adapter information	DC3.6V by battery
Hardware Version	V1.2
Software Version	2.0.126
<i>Note: For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacturer.</i>	

BlueAsia

## 2 RF Exposure Compliance Requirement

### 2.1 Standard Requirement

According to 447498 D04 Interim General RF Exposure Guidance v01

Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR condition, listed below, is satisfied.

### 2.2 Limits

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}}(d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases} \quad (\text{B.2})$$

where

$$x = -\log_{10} \left( \frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right)$$

and  $f$  is in GHz,  $d$  is the separation distance (cm), and  $ERP_{20\text{cm}}$  is per Formula (B.1).

Example values shown in Table B.2 are for illustration only.

Table B.2—Example Power Thresholds (mW)

Frequency (MHz)	Distance (mm)									
	5	10	15	20	25	30	35	40	45	50
300	39	65	88	110	129	148	166	184	201	217
450	22	44	67	89	112	135	158	180	203	226
835	9	25	44	66	90	116	145	175	207	240
1900	3	12	26	44	66	92	122	157	195	236
2450	3	10	22	38	59	83	111	143	179	219
3600	2	8	18	32	49	71	96	125	158	195
5800	1	6	14	25	40	58	80	106	136	169

$$P_{th} \text{ (mW)} = ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases} \quad (\text{B.1})$$

## 2.3 Result

$$\text{EIRP} = \text{pt} \times \text{gt} = (\text{E} \times \text{d})^2/30$$

Where:

pt = transmitter output power in watts,

gt = numeric gain of the transmitting antenna (unitless),

E = electric field strength in V/m, ---  $10((\text{dBuV/m})/20)/106$

d = measurement distance in meters (m) ---3m

$$\text{Spot} = (\text{Exd})^2/30 \times \text{gt}$$

$$\text{Ant gain} = 2.12 \text{ dBi}$$

## 2.4 GWIFI

Max Output power =14.698dBm @ 2437MHz 802.11g

$$\text{ERP} = 14.698 + 2.12 - 2.15 = 14.668 \text{ dBm}$$

So

ERP is worse case

$$10^{1.4698} = 29.499 \text{ mW} < 3060 \text{ mW}$$

Comply with RF exposure exemption limit.

----END OF REPORT----

The test report is effective only with both signature and specialized stamp, the result(s) shown in this report refer only to the sample(s) tested. Without written approval of BlueAsia, this report can't be reproduced except in full.