

EMF TEST REPORT

Test Report No. : OT-234-RWD-020
Reception No. : 2301000193
Applicant : Dreamfarm Solution Co., Ltd.
Address : Office 1, 7F Junwave sunworld clinic-dong, 444, Dongbaekjukjeon-daero, Giheung-gu, Yongin-si, Gyeonggi-do, Republic of Korea
Manufacturer : Dreamfarm Solution Co., Ltd.
Address : Office 1, 7F Junwave sunworld clinic-dong, 444, Dongbaekjukjeon-daero, Giheung-gu, Yongin-si, Gyeonggi-do, Republic of Korea
Type of Equipment : Housefarm
FCC ID. : 2BAD5-HFMODEL7
Model Name : HF22F
Multiple Model Name : N/A
Serial number : N/A
Total page of Report : 7 pages (including this page)
Date of Incoming : December 06, 2022
Date of issue : April 17, 2023

SUMMARY

The equipment complies with the regulation; **FCC CFR 47 PART 1.1310**

This test report only contains the result of a single test of the sample supplied for the examination.

It is not a generally valid assessment of the features of the respective products of the mass-production.

This report is not correlated with the "KS Q ISO/IEC 17025 and KOLAS accreditation" of Korean Laboratory Accreditation Scheme.



Tested by
Yun-Bok, Wi / Prj. Engineer
ONETECH Corp.

Reviewed by
Tae-Ho, Kim / Chief Engineer
ONETECH Corp.

Approved by
Jae-Ho, Lee / Chief Engineer
ONETECH Corp.

It should not be reproduced except in full, without the written approval of ONETECH Corp.

OTC-TRF-RF-001(0)

ONETECH Corp.: 43-14, Jinsaegol-gil, Chowol-eup, Gwangju-si, Gyeonggi-do, 12735, Korea (TEL: 82-31-799-9500, FAX: 82-31-799-9599)

CONTENTS

	PAGE
1. VERIFICATION OF COMPLIANCE	4
2. GENERAL INFORMATION	5
2.1 PRODUCT DESCRIPTION.....	5
2.2 ALTERNATIVE TYPE(S)/MODEL(S); ALSO COVERED BY THIS TEST REPORT.....	5
3. EUT MODIFICATIONS.....	5
4. MAXIMUM PERMISSIBLE EXPOSURE.....	6
4.1 RF EXPOSURE CALCULATION	6
4.2 EUT DESCRIPTION.....	6
4.3 CALCULATED MPE SAFE DISTANCE.....	7

Revision History

Rev. No.	Issue Report No.	Issued Date	Revisions	Section Affected
0	OT-234-RWD-020	April 17, 2023	Initial Release	All

1. VERIFICATION OF COMPLIANCE

Applicant : Dreamfarm Solution Co., Ltd.
Address : Office 1, 7F Junwave sunworld clinic-dong, 444, Dongbaekjukjeon-daero, Giheung-gu, Yongin-si, Gyeonggi-do, Republic of Korea
Contact Person : Jihoon, Jeong / Leader
Telephone No. : +82-10-8798-4252
FCC ID : 2BAD5-HFMODEL7
Model Name : HF22F
Brand Name : -
Serial Number : N/A
Date : April 17, 2023

EQUIPMENT CLASS	DTS – DIGITAL TRNSMISSION SYSTEM
E.U.T. DESCRIPTION	Housefarm
THIS REPORT CONCERNS	Original Grant
MEASUREMENT PROCEDURES	KDB 447498 D01 General RF Exposure Guidance v06
TYPE OF EQUIPMENT TESTED	Pre-Production
KIND OF EQUIPMENT	
AUTHORIZATION REQUESTED	Certification
Modifications on the Equipment to Achieve Compliance	None

- The above equipment was tested by ONETECH Corp. for compliance with the requirement set forth in the FCC Rules and Regulations. This said equipment in the configuration described in this report, shows the maximum emission levels emanating from equipment are within the compliance requirements.

2. GENERAL INFORMATION

2.1 Product Description

The Dreamfarm Solution Co., Ltd., Model HF22F (referred to as the EUT in this report) is a Housefarm. The product specification described herein was obtained from product data sheet or user's manual.

DEVICE TYPE	Housefarm
OPERATING FREQUENCY	2 412 MHz ~ 2 462 MHz (802.11b/g/n(HT20))
MODULATION TYPE	802.11b: DSSS Modulation (DBPSK/DQPSK/CCK) 802.11g/n(HT20): OFDM Modulation (BPSK/QPSK/16QAM/64QAM)
RF OUTPUT POWER	17.04 dBm (802.11b) 14.91 dBm (802.11g) 15.66 dBm (802.11n_HT20)
ANTENNA TYPE	PCB Antenna
ANTENNA GAIN	0.49 dBi
List of each Osc. or crystal Freq.(Freq. >= 1 MHz)	26 MHz
RATED SUPPLY VOLTAGE	DC 12.0 V

2.2 Alternative type(s)/model(s); also covered by this test report.

- None

3. EUT MODIFICATIONS

- None

4. MAXIMUM PERMISSIBLE EXPOSURE

4.1 RF Exposure Calculation

According to the FCC rule 1.1310 table 1B, the limit for the maximum permissible RF exposure for an uncontrolled environment are $f/1500 \text{ mW/cm}^2$ for the frequency range between 300 MHz and 1 500 MHz and 1.0 mW/cm^2 for the frequency range between 1 500 MHz and 100 000 MHz.

The electric field generated for a 1 mW/cm^2 exposure is calculated as follows:

$$E = \sqrt{(30 * P * G) / d}, \text{ and } S = E^2 / Z = E^2 / 377, \text{ because } 1 \text{ mW/cm}^2 = 10 \text{ W/m}^2$$

Where

S = Power density in mW/cm^2 , Z = Impedance of free space, 377Ω

E = Electric field strength in V/m , G = Numeric antenna gain, and d = distance in meter

Combining equations and rearranging the terms to express the distance as a function of the remaining variable

$$d = \sqrt{(30 * P * G) / (377 * 10 S)}$$

Changing to units of mW and cm , using $P (\text{mW}) = P (\text{W}) / 1000$, $d (\text{cm}) = 0.01 * d (\text{m})$

$$d = 0.282 * \sqrt{(P * G) / S}$$

Where

d = distance in cm , P = Power in mW , G = Numeric antenna gain, and S = Power density in mW/cm^2

4.2 EUT Description

Kind of EUT	Housefarm
Device Category	<input type="checkbox"/> Portable (< 20 cm separation) <input type="checkbox"/> Mobile (> 20 cm separation) <input checked="" type="checkbox"/> Others
Exposure	<input checked="" type="checkbox"/> MPE
Evaluation Applied	<input type="checkbox"/> SAR <input type="checkbox"/> N/A

4.3 Calculated MPE Safe Distance

According to above equation, the following result was obtained.

Operating Freq. Band (MHz)	Operating Mode	Target Power W/tolerance (dBm)	Max tune up power		Antenna Gain		Safe Distance (cm)	Power Density (mW/cm ²) @ 20 cm Separation	Limit (mW/cm ²)
			(dBm)	(mW)	Log	Linear			
2 400 ~ 2 483.5	802.11b	17.04 ± 1.0	18.04	63.68	0.49	1.12	2.38	0.014 2	1
	802.11g	14.91 ± 1.0	15.91	38.99			1.86	0.008 7	1
	802.11n_HT20	15.66 ± 1.0	16.66	46.34			2.03	0.010 3	1

According to above table, for 2 400 ~ 2483.5 MHz Band(802.11 b), safe distance,

$$D = 0.282 * \sqrt{(63.68 * 1.12) / 1.00} = 2.38 \text{ cm.}$$

For getting power density at 20 cm separation in above table, following formula was used.

$$S = P * G / (4\pi * R^2) = 63.68 * 1.12 / (4 * \pi * 20^2) = 0.014 2$$

Where:

S = Power Density,

P = Power input to the external antenna (Output power from the EUT antenna port (dBm) – cable loss (dB)),

G = Gain of Transmit Antenna (linear gain), R = Distance from Transmitting Antenna