

Radio Frequency Exposure

1.1 Radio Frequency Exposure Compliance

1.1.1 Electromagnetic Fields

RESULT:

Pass

Test Specification

Test item	:	WIFI Module IEEE 802.11 a/b/g/n/ac 2T/2R
Identification / Type No.	:	DCT1ER2611
FCC ID	:	2BAD6-8METZIFPD
IC	:	30102-8METZIFPD
HVIN	:	DCT1ER2611
Test standard	:	CFR47 FCC Part 2: Section 2.1093 CFR47 FCC Part 1: Section 1.1310 FCC KDB Publication 447498 v06 RSS-102 Issue 5 February 2021

Product Classification

This device defined as a transmitting device designed to be used in other than fixed locations and to generally be used in such a way that a separation distance of at 20 cm is normally maintained between the transmitter's radiating structure(s) and the body of the user or nearby persons.

1.1.2 Radio Frequency Exposure Limit

For FCC:

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)
300-1,500	--	--	f/1500
1,500-100,000	--	--	1.0

For IC:

Frequency Range (MHz)	Electric Field (V/m rms)	Magnetic Field (A/m rms)	Power Density (W/m ²)	Reference Period (minutes)
0.003-10 ²¹	83	90	-	Instantaneous*
0.1-10	-	0.73/ f ^{0.5}	-	6**
1.1-10	87/ f ^{0.5}	-	-	6**
10-20	27.46	0.0728	2	6
20-48	58.07/ f ^{0.25}	0.1540/ f ^{0.25}	8.944/ f ^{0.5}	6
48-300	22.06	0.05852	1.291	6
300-6000	3.142 f ^{0.3417}	0.008335 f ^{0.3417}	0.02619 f ^{0.6834}	6
6000-15000	61.4	0.163	10	6
15000-150000	61.4	0.163	10	616000/ f ^{1.2}
150000-300000	0.158 f ^{0.5}	4.21 x 10 ⁻⁴ f ^{0.5}	6.67 x 10 ⁻⁵ f	616000/ f ^{1.2}

Note: f is frequency in MHz.
*Based on nerve stimulation (NS).
** Based on specific absorption rate (SAR).

1.1.3 Radio Frequency Exposure Calculation Formula

$$S = \frac{PG}{4\pi R^2}$$

where: S = power density (in appropriate units, e.g. mW/cm²)

P = power input to the antenna (in appropriate units, e.g., mW)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

or:

$$S = \frac{EIRP}{4\pi R^2}$$

where: EIRP = equivalent (or effective) isotropically radiated power

1.1.4 Calculation Result

1)

Stand-alone transmission MPE

Mode	*Measured RF Output Power (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	FCC Limit (mW/cm ²)	Power Density (W/m ²)	IC Limit (W/m ²)
2.4GHz Wi-Fi	20.513	2.08	20	0.036	1.0	0.360	5.3
5GHz Wi-Fi	16.993	3.01	20	0.020	1.0	0.199	9.0

Note:

1. 2.4GHz Wi-Fi RF Output Power: Refer to test report CN23ZEGF 001
2. 5GHz Wi-Fi RF Output Power: Refer to test report CN23ZEGF 002

2) Simultaneous transmission MPE

Not applicant, as 2.4GHz Wi-Fi and 5GHz Wi-Fi share the same antenna.

1.1.5 Conclusion

Therefore the maximum calculations result of above are meet the requirement of Radio Frequency Exposure (MPE) limit.