



CTC Laboratories, Inc.

1-2/F., Building 2, Jiaquan Building, Guanlan High-Tech Park, Shenzhen, Guangdong, China

Tel: +86-755-27521059 Fax: +86-755-27521011 <http://www.sz-ctc.org.cn>

Maximum Permissible Exposure Evaluation

FCC ID: 2BAG3MS20A15

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) Radiation as specified in §1.1307(b)

EUT Specification

Product Name:	EveLab Insight-Eve V Skin Imaging Analysis System
Trade Mark:	EveLab Insight
Model/Type reference:	MS20A15
Listed Model(s):	/
Frequency band (Operating)	BT: 2.402GHz ~ 2.480GHz 2.4G WIFI: 2.412GHz ~ 2.462GHz 5G WIFI: 5.150GHz ~ 5.250GHz, 5.725GHz ~ 5.850GHz
Device category	☐ Portable (<5mm separation) ☐ Mobile (>20cm separation) ☒ Fixed (>20cm separation) ☐ Others
Exposure classification	☐ Occupational/Controlled exposure (S=5mW/cm2) ☒ General Population/Uncontrolled exposure (S=1mW/cm2)
Antenna diversity	☐ Single antenna ☒ Multiple antenna ☐ Tx diversity ☐ Rx diversity ☐ Tx/Rx diversity
Antenna gain (Max)	BT ANT: 3.21dBi 2.4G WIFI ANT1&ANT2: 3.21dBi, Directional gain: 6.22dBi 5G WIFI U-NII-1 ANT1&ANT2: 3.28dBi, Directional gain: 6.29dBi 5G WIFI U-NII-3 ANT1&ANT2: 2.83dBi, Directional gain: 5.84dBi
Evaluation applied	☒ MPE Evaluation ☐ SAR Evaluation

CTC Laboratories, Inc.

1-2/F., Building 2, Jiaquan Building, Guanlan High-Tech Park, Shenzhen, Guangdong, China

Tel.: (86)755-27521059

Fax: (86)755-27521011

[Http://www.sz-ctc.org.cn](http://www.sz-ctc.org.cn)



For anti-fake verification, please visit the official website of Certification and Accreditation Administration of the People's Republic of China : yz.cnca.cn

**Limits for Maximum Permissible Exposure (MPE)**

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density(mW/cm ²)	Average Time
(A) Limits for Occupational/Control Exposures				
300-1500	--	--	F/300	6
1500-100000	--	--	5	6
(B) Limits for General Population/Uncontrol Exposures				
300-1500	--	--	F/1500	6
1500-100000	--	--	1	30

Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where

P_d = Power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

P_d the limit of MPE 1mW/cm². If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

Measurement Result

Only show the value of the worst antenna.

BLE - Worst case						
Type	Channel Frequency (MHz)	Max. Measured Power (dBm)	Max. Tune up Power (dBm)	Antenna Gain (dBi)	Power density at 20cm (mW/cm ²)	Power density Limits (mW/cm ²)
GFSK	2480	-0.37	0.00	3.21	0.0004	1

BR/EDR - Worst case						
Type	Channel Frequency (MHz)	Max. Measured Power (dBm)	Max. Tune up Power (dBm)	Antenna Gain (dBi)	Power density at 20cm (mW/cm ²)	Power density Limits (mW/cm ²)
8-DPSK	2441	9.34	9.50	3.21	0.0037	1

2.4G WIFI - Worst case						
Type	Channel Frequency (MHz)	Max. Measured Power (dBm)	Max. Tune up Power (dBm)	Antenna Gain (dBi)	Power density at 20cm (mW/cm ²)	Power density Limits (mW/cm ²)
802.11 B	2437	17.26	17.50	3.21	0.0234	1



5G WIFI U-NII-1 - Worst case						
Type	Channel Frequency (MHz)	Max. Measured Power (dBm)	Max. Tune up Power (dBm)	Antenna Gain (dBi)	Power density at 20cm (mW/cm ²)	Power density Limits (mW/cm ²)
802.11 A	5180	15.91	16.50	3.28	0.0189	1

5G WIFI U-NII-3 - Worst case						
Type	Channel Frequency (MHz)	Max. Measured Power (dBm)	Max. Tune up Power (dBm)	Antenna Gain (dBi)	Power density at 20cm (mW/cm ²)	Power density Limits (mW/cm ²)
802.11 AC20	5745	16.10	16.50	5.84	0.0341	1

The BT and WIFI can transmit simultaneously.

Worst case					
Type	Channel Frequency (MHz)	Antenna Gain (dBi)	Power density at 20cm (mW/cm ²)	BT+WIFI Power density at 20cm (mW/cm ²)	Power density Limits (mW/cm ²)
8-DPSK	2441	3.21	0.0037	0.0612	1
802.11 B	2437	3.21	0.0234		
802.11 AC20	5745	5.84	0.0341		

Note:

1. Calculate by Worst-case mode
2. Max. Tune Up Power by Manufacturer's Declaration, and Max. Tune Up Power is used to calculate.
3. For a more detailed features description, please refer to the RF Test Report.

*****THE END*****