



RF Exposure Evaluation Report

APPLICANT : Shanghai Amphenol Airwave Communication Electronics Co., Ltd

EQUIPMENT : WiFi Module

BRAND NAME : Amphenol

MODEL NAME : B102C

FCC ID : 2BAG9-B102C00101

STANDARD : 47 CFR Part 2.1091
FCC KDB 447498 D01 v06

The product evaluation date was started from Apr. 07, 2023 and completed on Apr. 07, 2023. We, Sporton International Inc. (Kunshan),, would like to declare that the device has been evaluated in accordance with 47 CFR Part 2.1091 and FCC KDB 447498 D01 v06, and pass the limit. Without written approval of Sporton International Inc. (Kunshan),, the test report shall not be reproduced except in full.

Approved by: Si Zhang



Sportun International Inc. (Kunshan)
No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300
People's Republic of China



Table of Contents

1. ADMINISTRATION DATA	4
1.1. Testing Laboratory	4
2. DESCRIPTION OF EQUIPMENT UNDER TEST (EUT)	5
3. MAXIMUM RF TUNE UP POWER AMONG PRODUCTION UNITS	6
4. RF EXPOSURE EVALUATION	6
5. RADIO FREQUENCY RADIATION EXPOSURE EVALUATION	7
5.1. Standalone Power Density Calculation	7



Revision History



1. Administration Data

1.1. Testing Laboratory

Sportun International Inc. (Kunshan) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

Testing Laboratory			
Test Firm	Sportun International Inc. (Kunshan)		
Test Site Location	No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China TEL : +86-512-57900158 FAX : +86-512-57900958		
Test Site No.	Sportun Site No.	FCC Designation No.	FCC Test Firm Registration No.
	SAR01-KS	CN1257	314309

Applicant	
Company Name	Shanghai Amphenol Airwave Communication Electronics Co., Ltd
Address	No.689 Shen Nan Road, Xin Zhuang Industry Park, Shanghai, PR China

Manufacturer	
Company Name	Sichuan AI-Link Technology Co., Ltd.
Address	Anzhou Industrial Park, Mianyang, Sichuan, P.R.C



2. Description of Equipment Under Test (EUT)

Product Feature & Specification	
EUT Type	WiFi Module
Brand Name	Amphenol
Model Name	B102C
FCC ID	2BAG9-B102C00101
Wireless Technology and Frequency Range	Bluetooth: 2402 MHz ~ 2480 MHz
Mode	Bluetooth LE
Antenna Type	Bluetooth : On-Board PCB Antenna
Antenna Gain	Bluetooth: gain 1.40 dBi
HW Version	V1.0.0.0
SW Version	B102C_b0101v01
EUT Stage	Identical Prototype
Remark:	
1. The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.	

Comments and Explanations:

1. The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.
2. The maximum RF output tune up power, antenna gain also the safe distance used for evaluate RF exposure were declared by manufacturer.



3. Maximum RF Tune Up power among production units

<Bluetooth>

Mode	Maximum Average Power (dBm)
Bluetooth LE	5.0

4. RF Exposure Evaluation

According to ANSI/IEEE C95.1-1992, the criteria listed in Table 1 shall be used to evaluate the environmental impact of human exposure to radio frequency (RF) radiation as specified in §1.1310.

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3-3.0	614		1.63	*(100)
3.0-30		1842/f	4.89/f	*(900/f ²)
30-300		61.4	0.163	1.0
300-1500				f/300
1500-100,000				5
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614		1.63	*(100)
1.34-30		824/f	2.19/f	*(180/f ²)
30-300		27.5	0.073	0.2
300-1500				f/1500
1500-100,000				1.0

The MPE was calculated at 20 cm to show compliance with the power density limit.

The following formula was used to calculate the Power Density:

$$S = \frac{PG}{4\pi R^2}$$

Where:

S = Power Density

P = Output Power at Antenna Terminals

G = Gain of Transmit Antenna (linear gain)

R = Distance from Transmitting Antenna



5. Radio Frequency Radiation Exposure Evaluation

5.1. Standalone Power Density Calculation

Band	Frequency (MHz)	Antenna Gain (dBi)	Maximum Power (dBm)	Maximum EIRP (dBm)	Average EIRP (mW)	Power Density at 20cm (mW/cm^2)	Limit (mW/cm^2)
Bluetooth	2402.0	1.40	5.00	6.400	4.365	0.001	1.000

Note:

1. For conservativeness, the lowest frequency of each band is used to determine the MPE limit of that band.
2. Chose the maximum power to do MPE analysis.

Conclusion:

According to 47 CFR §2.1091, the RF exposure analysis concludes that the RF Exposure is FCC compliant.

-----THE END-----