



Fangguang Inspection & Testing Co., Ltd.



# RF Exposure Evaluation Declaration

Report No.: S202311075127E05

Issue Date: 01-10-2024

**Applicant:** Jiangsu Shushi Technology Co., Ltd.  
**Address:** NO.9 Nanxu Road, RunZhou District, Zhenjiang, Jiangsu, China  
**FCC ID:** 2BAGQ-3RMB01033WBZ  
**Product:** Smart Bridge MZ1  
**Model No.:** 3RMB01033WBZ  
**Trade Mark:** ThirdReality  
**FCC Rule Part(s):** CFR 47, FCC Part 2.1091 Radio frequency radiation exposure evaluation: mobile devices.  
**Item Receipt date:** Nov. 15, 2023  
**Test Date:** Nov. 15~ Dec. 7, 2023

Compiled By

Chuang Li

( Chuang Li )

Senior Test Engineer

Line Chen

(Line Chen)

Engineer Manager

Approved By



The test results relate only to the samples tested.

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in KDB 558074 D01. Test results reported herein relate only to the item(s) tested.

The test report shall not be reproduced except in full without the written approval of Fangguang Inspection & Testing Co., Ltd. Wuxi Branch

The test report must not be used by the client to claim product certifications, approval, or endorsement by NVLAP, NIST or any agency of U.S. Government.

## Revision History

Report No.	Version	Description	Issue Date
S202311075127E05	Rev. 01	/	01-10-2024

## 1. PRODUCT INFORMATION

### 1.1. Equipment Description

Product Name:	Smart Bridge MZ1
Model Name:	3RMB01033WBZ
Trade Mark:	ThirdReality
Input Voltage Range:	DC 5V
Wi-Fi Specification:	802.11b/g/n20
Bluetooth Version:	5.0
Zigbee Version	3.0

### 1.2. Product Specification Subjective to this Report

Frequency Range:	802.11b/g/n20: 2412 ~ 2462MHz BLE:2402~2480MHz Zigbee:2405~2480MHz
Channel Number:	802.11b/g/n20: 11 BLE:40 Zigbee:16
Type of Modulation:	802.11b: DSSS 802.11g/n: OFDM BLE:GFSK Zigbee: O-QPSK
Data Rate:	802.11b: 1/2/5.5/11Mbps 802.11g: 6/9/12/18/24/36/48/54Mbps 802.11n: MCS0~MCS7 BLE:1Mbps
Antenna Type:	Ceramic antenna
Antenna Gain:	2.8 dBi

## 2. RF Exposure Evaluation

### 2.1. Limits

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

#### LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Average Time (Minutes)
(A) Limits for Occupational/ Control Exposures				
300-1500	--	--	f/300	6
1500-100,000	--	--	5	6
(B) Limits for General Population/ Uncontrolled Exposures				
300-1500	--	--	f/1500	6
1500-100,000	--	--	1	30

f= Frequency in MHz

Calculation Formula:  $Pd = (Pout \cdot G) / (4 \cdot \pi \cdot r^2)$

Where

Pd = power density in mW/cm<sup>2</sup>

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

r = distance between observation point and center of the radiator in cm

Pd is the limit of MPE, 1mW/cm<sup>2</sup>. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

## 2.2. Test Result of RF Exposure Evaluation

Product	Smart Bridge MZ1					
Test Item	RF Exposure Evaluation					

Mode	Frequency (MHz)	Maximum Conducted Output Power (dBm)	Antenna Gain (dBi)	PG		MPE (mW/cm <sup>2</sup> )	MPE Limits (mW/cm <sup>2</sup> )
				(dBm)	(mW)		
WIFI	2412~2462	18.29	2.8	21.09	128.53	0.07	1.00
BLE	2402~2480	9.37	2.8	12.17	16.48	0.01	1.00
Zigbee	2405~2480	9.47	2.8	12.27	16.87	0.01	1.00

Remark: 1. MPE use distance is 20cm from manufacturer declaration of user manual.

Remark: 2. Use the maximum gain of all bands when evaluating

Remark: 3. BT and Zigbee can't transmit simultaneously.

### CONCULISON:

The Max Power Density at R (20 cm) = 0.07mW/cm<sup>2</sup> < 1mW/cm<sup>2</sup>.

So the EUT complies with the requirement.

————— The End —————