

5 FCC §2.1091, §15.247 - 102- RF Exposure

5.1 Applicable Standards

According to FCC §15.247(i), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for General Population/Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minutes)
Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	* (100)	30
1.34-30	824/f	2.19/f	* (180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

f = frequency in MHz

* = Plane-wave equivalent power density

5.2 MPE Prediction

Predication of MPE limit at a given distance, Equation from OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2$$

Where: S = power density

P = power input to antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

5.3 MPE Results for the FCC

<u>Maximum peak output power at antenna input terminal (dBm):</u>	<u>16.99</u>
<u>Maximum peak output power at antenna input terminal (mW):</u>	<u>50.00</u>
<u>Prediction distance (cm):</u>	<u>20</u>
<u>Prediction frequency (MHz):</u>	<u>902.3</u>
<u>Maximum Antenna Gain, typical (dBi):</u>	<u>-0.91</u>
<u>Maximum Antenna Gain (numeric):</u>	<u>0.81</u>
<u>Power density of prediction frequency at 20.0 cm (mW/cm²):</u>	<u>0.008</u>
<u>FCC MPE limit for uncontrolled exposure at prediction frequency (mW/cm²):</u>	<u>0.60</u>

The device is compliant with the requirement MPE limit for uncontrolled exposure. The maximum power density at the distance of 20 cm is 0.008mW/cm². Limit is 0.60 mW/cm².