





Report No.: FA4D1930

Radio Exposure Evaluation Report

FCC ID : 2BAH4WF-3

Equipment : Silvanet Wildfire Sensor

Model Name : WF-3

Applicant : Dryad Networks GmbH

Eisenbahnstr. 37, 16225 Eberswalde, Germany

Manufacturer : Dryad Networks GmbH

Eisenbahnstr. 37, 16225 Eberswalde, Germany

Standard : 47 CFR FCC Part 2 Subpart J, section 2.1091

The product was received on Dec. 19, 2024, and testing was started from Jan. 14, 2025 and completed on Jan. 21, 2025. We, SPORTON INTERNATIONAL INC. Hsinhua Laboratory, would like to declare that the tested sample has been evaluated in accordance with the procedures given in 47 CFR FCC Part 2 Subpart J, section 2.1091 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. Hsinhua Laboratory, the test report shall not be reproduced except in full.

Approved by: Jackson Tsai

SPORTON INTERNATIONAL INC. Hsinhua Laboratory

No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333411, Taiwan (R.O.C.)

TEL: 886-3-327-3456 FAX: 886-3-327-0973

Report Template No.: HE1-A1 Ver5.0

FCC ID: 2BAH4WF-3

Page Number : 1 of 9

Issued Date : Mar. 10, 2025

Report Version : 01

Table of Contents

HISTO	RY OF THIS TEST REPORT	.3
	ARY OF TEST RESULT	
	GENERAL DESCRIPTION	
	Information	
1.2	Applicable Standards	.5
1.3	Testing Location	.5
2	MAXIMUM PERMISSIBLE EXPOSURE	.6
2.1	Limit of Maximum Permissible Exposure	.6
2.2	RF Exposure Exempt Measurement	
2.3	Multiple RF Sources Exposure	
2.4	MPE Calculation Method	.8
2.5	Calculated Result and Limit	.9
DI 4	weeks of FUT VO	

Photographs of EUT V01

TEL: 886-3-327-3456 Page Number : 2 of 9
FAX: 886-3-327-0973 Issued Date : Mar. 10, 2025

Report Template No.: HE1-A1 Ver5.0

FCC ID: 2BAH4WF-3

Report Version : 01



History of this test report

Report No.	Version	Description	Issued Date
FA4D1930	01	Initial issue of report	Mar. 10, 2025

TEL: 886-3-327-3456 Page Number : 3 of 9
FAX: 886-3-327-0973 Issued Date : Mar. 10, 2025

Report Template No.: HE1-A1 Ver5.0

FCC ID: 2BAH4WF-3

Report Version : 01

Report No.: FA4D1930

Summary of Test Result

Report No.: FA4D1930

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
2	-	Exposure evaluation	PASS	-

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

None

Reviewed by: Ryan Hsiao

Report Producer: Michelle Tsai

TEL: 886-3-327-3456 Page Number : 4 of 9
FAX: 886-3-327-0973 Issued Date : Mar. 10, 2025

Report Template No.: HE1-A1 Ver5.0 Report Version : 01

FCC ID: 2BAH4WF-3



1 General Description

1.1 Information

1.1.1 EUT General Information

RF General Information						
Evaluation Mode	Frequency Range (MHz)	Modulation Type				
LoRa	902–928	LoRa (125kHz/500kHz)				

Report No.: FA4D1930

1.1.2 Antenna Information

Ar	nt.	Port	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
_	1	1	Dryad	Sensor01Gen-3	Wire Monopole Antenna	N/A	2.6

For LoRa function:

Ant. 1 (port 1) could transmit/receive.

1.2 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR FCC Part 2 Subpart J, section 2.1091
- KDB 447498 D04 Interim General RF Exposure Guidance v01

The following reference test guidance is not within the scope of accreditation of TAF.

- 47 CFR Part 1.1307
- 47 CFR Part 1.1310

1.3 Testing Location

Test	Test Lab. : Sporton International Inc. Hsinhua Laboratory							
\boxtimes	Hsinhua ADD: No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333411, Taiwan (R.O.C.)							
	(TAF: 3785)	TEL: 886-3-327-3456 FAX: 886-3-327-0973						
	Test site Designation No. TW3785 with FCC.							

TEL: 886-3-327-3456 Page Number : 5 of 9
FAX: 886-3-327-0973 Issued Date : Mar. 10, 2025

Report Version

: 01

Report Template No.: HE1-A1 Ver5.0

FCC ID: 2BAH4WF-3



2 Maximum Permissible Exposure

2.1 Limit of Maximum Permissible Exposure

(A) Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm²)	Averaging Time E ², H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f ²)*	6
30-300	61.4	0.163	1.0	6
300-1500	-	-	F/300	6
1500-100,000	-	-	5	6

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)		
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f ²)*	30
30-300	27.5	0.073	0.2	30
300-1500	-	-	F/1500	30
1500-100,000	-	-	1.0	30

Note: f = frequency in MHz; *Plane-wave equivalent power density

2.2 RF Exposure Exempt Measurement

Option	Refer Std.	Exemption Exposure Thresholds (TL)
А	§1.1307(b)(3)(i)(A)	Available maximum time-averaged power is no more than 1 mW
В	§1.1307(b)(3)(i)(B)	$Pth(mW) = \begin{cases} ERP_{20cm}(d/20cm)^{x} \to d \le 20cm \\ ERP_{20cm} \to 20cm < d \le 40cm \end{cases}$ $x = -\log_{10}\left(\frac{60}{ERP_{20cm}\sqrt{f}}\right) \text{ and f is in GHz}$ $\begin{cases} ERP_{20cm} : 0.3GHz \le f < 1.5GHz \to 2040f(mW) \\ ERP_{20cm} : 1.5GHz \le f \le 6GHz \to 3060(mW) \end{cases}$
C	§1.1307(b)(3)(i)(C)	$\begin{cases} 0.3 \sim 1.34 MHz \rightarrow ERP(W) = 1920 R^2 \\ 1.34 \sim 30 MHz \rightarrow ERP(W) = 3450 R^2 / f^2 \\ 30 \sim 300 MHz \rightarrow ERP(W) = 3.83 R^2 \\ 300 \sim 1500 MHz \rightarrow ERP(W) = 0.0128 R^2 f \\ 1500 \sim 100000 MHz \rightarrow ERP(W) = 19.2 R^2 \end{cases}$ f is in MHz; R is in m; R > $\lambda/2\pi$

TEL: 886-3-327-3456 Page Number : 6 of 9
FAX: 886-3-327-0973 Issued Date : Mar. 10, 2025

Report Template No.: HE1-A1 Ver5.0

FCC ID: 2BAH4WF-3

Report Version : 01

Report No.: FA4D1930



2.3 Multiple RF Sources Exposure

Refer Std.	Exemption Exposure Thresholds (TL)
§1.1307(b)(3)(ii)(A)	The available maximum time-averaged power of each source is no more than 1 mW and there is a separation distance of two centimeters between any portion of a radiating structure operating and the nearest portion of any other radiating structure in the same device, except if the sum of multiple sources is less than 1 mW during the time-averaging period, in which case they may be treated as a single source (separation is not required)
§1.1307(b)(3)(ii)(B)	$ \sum_{i=1}^{a} \frac{P_i}{P_{th,i}} + \sum_{j=1}^{b} \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^{c} \frac{Evaluated_k}{ExposureLimit_k} \leq 1 $ a = number of fixed, mobile, or portable RF sources claiming exemption using paragraph $\S 1.1307(b)(3)(i)(B)$ of this section for P , including existing exempt transmitters and those being added. b = number of fixed, mobile, or portable RF sources claiming exemption using paragraph $\S 1.1307(b)(3)(i)(C)$ of this section for Threshold ERP, including existing exempt transmitters and those being added. c = number of existing fixed, mobile, or portable RF sources with known evaluation for the specified minimum distance including existing evaluated transmitters. P_i = the available maximum time-averaged power or the ERP, whichever is greater, for fixed, mobile, or portable RF source i at a distance between 0.5 cm and 40 cm (inclusive). $P_{th,i}$ = the exemption threshold power (P_{th}) according to paragraph $\S 1.1307(b)(3)(i)(B)$ of this section for fixed, mobile, or portable RF source i. ERP_j = the ERP of fixed, mobile, or portable RF source j. $ERP_{th,j}$ = exemption threshold ERP for fixed, mobile, or portable RF source j, at a distance of at least $\lambda/2\pi$ according to the applicable formula of paragraph $\S 1.1307$ (b)(3)(i)(C) of this section. $Evaluated_k$ = the maximum reported SAR or MPE of fixed, mobile, or portable RF source k either in the device or at the transmitter site from an existing evaluation at the location of exposure. $Evaluated$ Limit = either the general population/uncontrolled maximum permissible exposure (MPE) or specific absorption rate (SAR) limit for each fixed, mobile, or portable RF source k, as applicable from $\S 1.1310$ of this chapter.

TEL: 886-3-327-3456 Page Number : 7 of 9
FAX: 886-3-327-0973 Issued Date : Mar. 10, 2025

Report Template No.: HE1-A1 Ver5.0

FCC ID: 2BAH4WF-3

Report Version : 01

Report No.: FA4D1930

2.4 MPE Calculation Method

The MPE was calculated at 20 cm to show compliance with the power density limit. The following formula was used to calculate the Power Density:

Report No.: FA4D1930

$$E (V/m) = \frac{\sqrt{30 \times P \times G}}{d}$$
 Power Density: $Pd (W/m^2) = \frac{E^2}{377}$

E = Electric field (V/m)

P = RF output power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$

TEL: 886-3-327-3456 Page Number : 8 of 9
FAX: 886-3-327-0973 Issued Date : Mar. 10, 2025

Report Template No.: HE1-A1 Ver5.0 Report Version : 01

FCC ID: 2BAH4WF-3



2.5 **Calculated Result and Limit**

Exposure Environment: General Population / Uncontrolled Exposure

LoRa

Mode	DG	Power	ERP	Tolerance	Tune-up ERP	Distance	Option	TL ERP	TL Ratio
	(dBi)	(dBm)	(dBm)	(dB)	(mW)	(cm)		(mW)	
0.9G;LoRa-500	2.60	13.31	13.76	0.50	26.669	20	В	2194.1	0.0122
0.9G-1;LoRa-500	2.60	13.46	13.91	0.50	27.606	20	В	2215.9	0.0125
0.9G;LoRa-125	2.60	13.34	13.79	0.50	26.853	20	В	2195.8	0.0122

-THE END---

FAX: 886-3-327-0973

Report Template No.: HE1-A1 Ver5.0

FCC ID: 2BAH4WF-3

TEL: 886-3-327-3456

: 9 of 9 Page Number Issued Date : Mar. 10, 2025

Report No.: FA4D1930

Report Version : 01