



# RF Test Report

**Applicant:** Procon Analytics LLC  
**Address:** 17361 Armstrong Avenue Irvine, CA 92614  
**Product:** Dagger QI  
**Model No.:** 4-6460-20  
**Brand Name:** Procon Analytics LLC  
**FCC ID:** 2BAH7DQI01  
**Standards:** FCC CFR47 Part 15C  
**Report No.:** PD20250111-R3B  
**Issue Date:** 2025/07/22  
**Test Result:** PASS \*

\* Testing performed at Hefei Panwin Technology Co., Ltd. on the above equipment indicates the product meets the requirements of the relevant standards.

**Reviewed By:** Jerry Zhang

**Approved By:** Alec Yang

## Hefei Panwin Technology Co., Ltd.

Floor 1, Zone E, Plant 2#, Mingzhu Industrial Park, No.106 Chuangxin Avenue, High-tech Zone, Hefei City, Anhui Province, China  
TEL: +86-0551-63811775



# Test Report

Report No.: PD20250111-R3B  
Report Version: 01

## Revision History

Report No.	Version	Description	Issue Date	Note
PD20250111-R3B	1	Initial Report	2025/07/22	Valid

## CONTENTS

<b>1 General Information .....</b>	<b>5</b>
1.1 Notes of the Test Report .....	5
1.2 Test Facility .....	5
1.3 Testing Laboratory .....	5
<b>2 General Description of Equipment under Test.....</b>	<b>6</b>
2.1 Details of Application .....	6
2.2 General Information .....	6
2.3 Application Standards .....	7
<b>3 Test Condition .....</b>	<b>8</b>
3.1 Test Configuration .....	8
3.2 Carrier Frequency and Channel .....	9
3.3 Equipment List .....	10
3.4 Support Equipment List .....	11
3.5 Test Uncertainty .....	11
<b>4 Test Items Description .....</b>	<b>12</b>
4.1 Output Power Measurement .....	12
4.2 6dB and 99% Bandwidth Measurement .....	14
4.3 Power Spectral Density Measurement .....	15
4.4 Conducted Band Edges and Spurious Emission Measurement .....	16
4.5 Radiated Band Edges and Spurious Emission Measurement .....	17
4.6 AC Conducted Emission Measurement .....	21
4.7 Antenna Requirements .....	23
<b>ANNEX A: Test Results of Conducted Test .....</b>	<b>24</b>
<b>ANNEX B: Test Results of Radiated Test .....</b>	<b>36</b>
<b>ANNEX C: The EUT Appearance .....</b>	<b>43</b>
<b>ANNEX D: Test Setup Photograph .....</b>	<b>44</b>

## Test Summary

No.	Test Case	FCC Rules	Verdict
1	Output Power Measurement	15.247(b)	PASS
2	6dB and 99% Bandwidth Measurement	15.247(a)(2)	PASS
3	Power Spectral Density Measurement	15.247(e)	PASS
4	Conducted Band Edges and Spurious Emission Measurement	15.247(d)	PASS
5	Radiated Band Edges and Spurious Emission Measurement	15.247(d)	PASS
6	AC Conducted Emission Measurement	15.207	NA
7	Antenna Requirements	15.203 & 15.247(b)	PASS

Date of Testing: 2025/06/27 to 2025/07/19

Date of Sample Received: 2025/06/25

• We, Hefei Panwin Technology Co., Ltd., would like to declare that the tested sample has been evaluated in accordance with the procedures given in applied standard(s) in **Section 2.3** of this report and shown compliance with the applicable technical standards.

• All indications of PASS/FAIL in this report are based on interpretations and/or observations of test results.

Measurement Uncertainties were not taken into account and are published for informational purposes only.

## 1 General Information

### 1.1 Notes of the Test Report

This report is invalid without signature of auditor and approver or with any alterations. The report shall not be partially reproduced without written approval of the testing company. Entrusted test results are only responsible for incoming samples. If there is any objection to the testing report, it shall be raised to the testing company within 15 days from the date of receiving the report. In the test results, "NA" means "not applicable", and the test items marked with "Δ" are subcontracted projects.

### 1.2 Test Facility

#### A2LA (Certificate Number: 6849.01)

Hefei Panwin Technology Co., Ltd. has been accredited by American Association for Laboratory Accreditation to perform measurement.

#### FCC (Designation Number: CN1361, Test Firm Registration Number: 473156)

Hefei Panwin Technology Co., Ltd. has been accredited on the US Federal Communications Commission list of test facilities recognized to perform measurements.

### 1.3 Testing Laboratory

Company Name	Hefei Panwin Technology Co., Ltd.
Address	Floor 1, Zone E, Plant 2#, Mingzhu Industrial Park, No.106 Chuangxin Avenue, High-tech Zone, Hefei City, Anhui Province, China
Telephone	+86-0551-63811775
Post Code	230031

## 2 General Description of Equipment under Test

### 2.1 Details of Application

<b>Applicant</b>	Procon Analytics LLC
<b>Applicant Address</b>	17361 Armstrong Avenue Irvine, CA 92614
<b>Manufacturer</b>	Procon Analytics LLC
<b>Manufacturer Address</b>	17361 Armstrong Avenue Irvine, CA 92614

### 2.2 General Information

<b>Product</b>	Dagger QI
<b>Model</b>	4-6460-20
<b>SN</b>	Radiated: AKGSQQ-8079723533
<b>Hardware Version</b>	V1.1
<b>Software Version</b>	/
<b>Antenna Type</b>	Chip Antenna
<b>Antenna Gain</b>	5.01dBi
<b>Max. Conducted Power</b>	BLE: 2.78dBm
<b>Operating voltage</b>	Typical: EVB DC12V, Battery 3.6V
<b>Type of Modulation</b>	Bluetooth LE 5.0: GFSK
<b>Operating Frequency Range(s)</b>	Bluetooth LE: 2402 to 2480MHz

**Note:** The declared of product specification for EUT and/or Antenna presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

## 2.3 Application Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 15 Subpart C §15.247
- FCC KDB 558074 D01 15.247 Meas Guidance v05r02
- ANSI C63.10-2013

**Remark:**

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

## 3 Test Condition

### 3.1 Test Configuration

#### Test mode

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture). The worst cases were recorded in this report.

Radiated measurements are performed by rotating the EUT in three different orthogonal test planes (Z, X, Y axis), receiver antenna polarization (horizontal and vertical), the worst emission was found in Z position and the worst case was recorded.

Test Mode	Data Rate
Bluetooth LE	1Mbps
	2Mbps

### 3.2 Carrier Frequency and Channel

Frequency Band	Channel	Freq.(MHz)	Channel	Freq.(MHz)
2400-2483.5 MHz	0	2402	21	2444
	1	2404	22	2446
	2	2406	23	2448
	3	2408	24	2450
	4	2410	25	2452
	5	2412	26	2454
	6	2414	27	2456
	7	2416	28	2458
	8	2418	29	2460
	9	2420	30	2462
	10	2422	31	2464
	11	2424	32	2466
	12	2426	33	2468
	13	2428	34	2470
	14	2430	35	2472
	15	2432	36	2474
	16	2434	37	2476
	17	2436	38	2478
	18	2438	39	2480
	19	2440	-	-
	20	2442	-	-

### 3.3 Equipment List

**Conducted**

Instrument	Manufacturer	Model	Asset No.	Cal. Interval	Cal. Due Date
Spectrum Analyzer	KEYSIGHT	N9020B	PWC0048	1 Year	2025/09/11
RF Control Unit	Tonseced	JS0806-2	PWC0055	/	/
DC Power	Keysight	E3640A	PWC0046	1 Year	2025/09/12
Shielded Chamber	Maorui	MR543	PWC0041	3 Years	2026/08/26
Test Software	Tonseced	JS1120-3 V3.2.22	/	/	/

**Radiated**

Instrument	Manufacturer	Model	Asset No.	Cal. Interval	Cal. Due Date
EMI Test Receiver	R&S	ESR7	PWB0023	1 Year	2025/09/11
Spectrum Analyzer	R&S	FSV3044	PWB0024	1 Year	2025/09/11
Loop Antenna	R&S	HFH2-Z2E	PWB0026	1 Year	2025/09/13
TRILOG Broadband Antenna	Schwarzbeck	VULB9162	PWB0029	1 Year	2025/09/09
Double-Ridged Guide Antenna	ETS-Lindgren	3117	PWB0031	1 Year	2025/09/26
k Type Horn Antenna	Steatite Antennas	QMS-00880	PWB0035	1 Year	2025/09/08
Pre-Amplifier	R&S	SCU40F1	PWB0036	1 Year	2025/09/11
Pre-Amplifier	COM-MW	DLNA8	PWB0094	1 Year	2025/09/11
Pre-Amplifier	R&S	SCU18F	PWB0034	1 Year	2025/09/11
Pre-Amplifier	R&S	OSP220 (OSP-B155G)	PWB0042	1 Year	2025/09/11
Anechoic Chamber	ETS.LINDGREN	Fact 3-2m	PWB0003	3 Years	2026/06/05
Test Software	Tonscend	JS32 V5.0.0	/	/	/

### 3.4 Support Equipment List

Equipment	Manufacturer	Description	Model	Serial Number
RF cable	/	2.4GHz:0.4dB	/	/
EVB	/	/	QDM095-EA-NA	D14K5EN01000074
Serial board	/	USB to serial portboard	/	/

### 3.5 Test Uncertainty

No.	Parameter	Uncertainty
1	DTS Bandwidth	1.9 %
2	Occupied channel bandwidth	1.9 %
3	Duty Cycle	0.11 %
4	Maximum Conducted Output Power	1.18 dB
5	Maximum Power Spectral Density Level	0.98 dB
6	Band-edge Compliance	1.21 dB
7	Unwanted Emissions In Non-restricted Frequency Bands	9kHz-7GHz: 1.21 dB 7GHz-40GHz: 3.31 dB
8	Radiated Band Edges and Spurious Emission	Below 1GHz: 4.88 dB Above 1GHz: 5.06 dB
9	Temperature	3 °C
10	Humidity	1.3 %
11	Supply Voltages	0.006 V

## 4 Test Items Description

### Ambient condition

#### Shielded Chamber

Temperature [°C]	22.2 to 24.7
Humidity [%RH]	43 to 54
Pressure [kPa]	100.2 to 102.3

#### Anechoic Chamber

Temperature [°C]	20.3 to 23.5
Humidity [%RH]	46 to 54
Pressure [kPa]	99.4 to 100.4

## 4.1 Output Power Measurement

### 4.1.1 Limit of Output Power

Rule Part 15.247 (b) (3) specifies that “For systems using digital modulation in the 902-928 MHz 2400-2483.5 MHz: 1 Watt.”

### 4.1.2 Measuring Instruments


The section 3.3 of List of Measuring Equipment of this test report is used for test.

### 4.1.3 Test Procedures

The testing follows the Measurement Procedure of ANSI C63.10-2013 clause 11.9.1.1.

The following procedure shall be used when an instrument with a resolution bandwidth that is greater than the DTS bandwidth is available to perform the measurement:

- 1) Set the RBW  $\geq$ DTS bandwidth.
- 2) Set VBW  $\geq$ [3  $\times$  RBW].
- 3) Set span  $\geq$ [3  $\times$  RBW].
- 4) Sweep time = auto couple.
- 5) Detector = peak.
- 6) Trace mode = max hold.
- 7) Allow trace to fully stabilize.
- 8) Use peak marker function to determine the peak amplitude level.

**4.1.4 Test Setup****4.1.5 Test Results**

See ANNEX A.1.

## 4.2 6dB and 99% Bandwidth Measurement

### 4.2.1 Limit of 6dB and 99% Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz


### 4.2.2 Measuring Instruments

The section 3.3 of List of Measuring Equipment of this test report is used for test.

### 4.2.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 11.8 & 6.9.3.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
5. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) is set 1% to 5% of the 99% OBW and the VBW is set to 3 times of the RBW.
6. Measure and record the results in the test report.

### 4.2.4 Test Setup



### 4.2.5 Test Results

See ANNEX A.2.

## 4.3 Power Spectral Density Measurement

### 4.3.1 Limit of Power Spectral Density

Rule Part 15.247(e) specifies that" For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

### 4.3.2 Measuring Instruments

The section 3.3 of List of Measuring Equipment of this test report is used for test.


### 4.3.3 Test Procedures

The testing follows ANSI C63.10-2013 clause 11.10.2

The following procedure shall be used if maximum peak conducted output power was used to determine compliance, and it is optional if the maximum conducted (average) output power was used to determine compliance:

- 1) Set analyzer center frequency to DTS channel center frequency.
- 2) Set the span to 1.5 times the DTS bandwidth.
- 3) Set the RBW to  $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$ .
- 4) Set the VBW  $\geq [3 \times \text{RBW}]$ .
- 5) Detector = peak.
- 6) Sweep time = auto couple.
- 7) Trace mode = max hold.
- 8) Allow trace to fully stabilize.
- 9) Use the peak marker function to determine the maximum amplitude level within the RBW.
- 10) If measured value exceeds requirement, then reduce RBW (but no less than 3 kHz) and repeat.

### 4.3.4 Test Setup



### 4.3.5 Test Result of Power Spectral Density

Please refer to ANNEX A.3.

## 4.4 Conducted Band Edges and Spurious Emission Measurement

### 4.4.1 Limit of Conducted Band Edges and Spurious Emission

All harmonics/spurious must be at least 20 dB down from the highest emission level within the authorized band. In any 100 kHz bandwidth outside of the authorized frequency band, the emissions which fall in the non-restricted bands shall be attenuated at least 20 dB relative to the maximum PSD level in 100 kHz by RF conducted measurement.


### 4.4.2 Measuring Instruments

The section 3.3 of List of Measuring Equipment of this test report is used for test

### 4.4.3 Test Procedure

1. The testing follows ANSI C63.10-2013 clause 11.13.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

### 4.4.4 Test Setup



### 4.4.5 Test Result

Please refer to ANNEX A.4.

## 4.5 Radiated Band Edges and Spurious Emission Measurement

### 4.5.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.




Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30-88	100	3
88 -216	150	3
216 - 960	200	3
Above 960	500	3

### 4.5.2 Measuring Instruments

The section 3.3 of List of Measuring Equipment of this test report is used for test.

**4.5.3 Test Procedures**

1. The testing follows ANSI C63.10-2013 clause 11.12.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level -Preamp Factor = Level
6. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
7. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than peak limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
8. Use the following spectrum analyzer settings:
  - (1) Span shall wide enough to fully capture the emission being measured.
  - (2) Set RBW=100 kHz for  $f < 1$  GHz; VBW  $\geq$  RBW; Sweep = auto; Detector function = peak; Trace = max hold.
  - (3) Set RBW = 1 MHz, VBW= 3MHz for  $\geq 1$  GHz for peak measurement  
For average measurement:  
VBW= 10 Hz, when duty cycle is no less than 98 percent.  
VBW  $\geq 1/T$ , when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

**4.5.4 Test Setup****For radiated emissions below 30MHz****For radiated emissions from 30MHz to 1GHz****For radiated emissions above 1GHz****4.5.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)**

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and semi-Anechoic chamber, and the result came out

---

very similar.

## 4.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to ANNEX B.1.

## 4.5.7 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic or 40GHzwhichever is lower)

Please refer to ANNEX B.1.

## 4.5.8 Duty Cycle

Please refer to ANNEX A.5.

## 4.6 AC Conducted Emission Measurement

### 4.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dB $\mu$ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

Decreases with the logarithm of the frequency.


### 4.6.2 Measuring Instruments

The section 3.3 of List of Measuring Equipment of this test report is used for test.

### 4.6.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 6.2.
2. The mains terminal disturbance voltage test was conducted in a shielded room.
3. The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a  $50\Omega/50\mu\text{H} + 5\Omega$  linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.
4. The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane.
5. The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.
6. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10-2013 on conducted measurement.

#### 4.6.4 Test Setup



#### 4.6.5 Uncertainty Measurement

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT.

The listed uncertainties are the worst case uncertainty for the entire range of measurement. Please note that the uncertainty values are provided for informational purposes only and are not used in determining the PASS/FAIL results.

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of  $k=2$ .

CASE	Uncertainty
Continuous Emission (AC port)	2.92 dB

#### 4.6.6 Test Result

**Remark:** The product is DC powered, this test item is not applicable.

## 4.7 Antenna Requirements

### 4.7.1 Standard Applicable

15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

15.247(b) (4) requirement: The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and(b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6dBi.

### 4.7.2 Antenna Anti-Replacement Construction

The antenna is Internal on the main PCB and no consideration of replacement. The best case gain of the antenna is 5.01dBi.

----- THE END -----


## ANNEX A: Test Results of Conducted Test


### A.1 Conducted Output Power

#### Test Result Peak

Test Mode	Antenna	Frequency [MHz]	Conducted Peak Power[dBm]	Conducted Limit[dBm]	EIRP[dBm]	EIRP Limit[dBm]	Verdict
BLE_1M	Ant1	2402	2.60	≤30	7.61	≤36	PASS
BLE_1M	Ant1	2440	2.68	≤30	7.69	≤36	PASS
BLE_1M	Ant1	2480	2.77	≤30	7.78	≤36	PASS
BLE_2M	Ant1	2402	2.60	≤30	7.61	≤36	PASS
BLE_2M	Ant1	2440	2.69	≤30	7.70	≤36	PASS
BLE_2M	Ant1	2480	2.78	≤30	7.79	≤36	PASS

#### Test Graphs





## A.2 6dB and 99% Bandwidth


### Test Result 6dB Bandwidth


Test Mode	Antenna	Frequency[MHz]	DTS BW[MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
BLE_1M	Ant1	2402	0.688	2401.660	2402.348	0.5	PASS
BLE_1M	Ant1	2440	0.676	2439.668	2440.344	0.5	PASS
BLE_1M	Ant1	2480	0.692	2479.656	2480.348	0.5	PASS
BLE_2M	Ant1	2402	1.128	2401.456	2402.584	0.5	PASS
BLE_2M	Ant1	2440	1.136	2439.444	2440.580	0.5	PASS
BLE_2M	Ant1	2480	1.088	2479.456	2480.544	0.5	PASS

### Test Result 99% Bandwidth


Test Mode	Antenna	Frequency[MHz]	OCB [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
BLE_1M	Ant1	2402	1.0575	2401.4874	2402.5449	---	---
BLE_1M	Ant1	2440	1.0221	2439.5092	2440.5313	---	---
BLE_1M	Ant1	2480	1.0578	2479.4867	2480.5445	---	---
BLE_2M	Ant1	2402	2.0585	2400.9987	2403.0572	---	---
BLE_2M	Ant1	2440	2.0933	2438.9766	2441.0699	---	---
BLE_2M	Ant1	2480	2.0705	2478.9886	2481.0591	---	---


### Test Graphs\_6dB Bandwidth





## Test Graphs\_99% Bandwidth





BLE\_2M-Ant1-2440

BLE\_2M-Ant1-2480





## A.3 Power Spectral Density

## Test Result

Test Mode	Antenna	Frequency[MHz]	Result[dBm/3kHz]	Limit[dBm/3kHz]	Verdict
BLE_1M	Ant1	2402	-12.57	≤8.00	PASS
BLE_1M	Ant1	2440	-12.47	≤8.00	PASS
BLE_1M	Ant1	2480	-12.53	≤8.00	PASS
BLE_2M	Ant1	2402	-15.11	≤8.00	PASS
BLE_2M	Ant1	2440	-14.90	≤8.00	PASS
BLE_2M	Ant1	2480	-14.95	≤8.00	PASS

## Test Graphs





## A.4 Conducted Band Edges and Spurious Emission

### Test Result

#### Band Edges


Test Mode	Antenna	Ch Name	Frequency[MHz]	Ref Level[dBm]	Result[dBm]	Limit[dBm]	Verdict
BLE_1M	Ant1	Low	2402	2.50	-46.95	≤-17.5	PASS
BLE_1M	Ant1	High	2480	2.58	-52.03	≤-17.42	PASS
BLE_2M	Ant1	Low	2402	2.53	-31.47	≤-17.47	PASS
BLE_2M	Ant1	High	2480	2.63	-50.21	≤-17.37	PASS

#### Spurious Emission

Test Mode	Antenna	Frequency[MHz]	Freq Range[MHz]	Ref Level[dBm]	Result[dBm]	Limit[dBm]	Verdict
BLE_1M	Ant1	2402	30~1000	2.50	-68.66	≤-17.5	PASS
BLE_1M	Ant1	2402	1000~26500	2.50	-41.77	≤-17.5	PASS
BLE_1M	Ant1	2440	30~1000	2.60	-69.39	≤-17.4	PASS
BLE_1M	Ant1	2440	1000~26500	2.60	-40.81	≤-17.4	PASS
BLE_1M	Ant1	2480	30~1000	2.58	-68.96	≤-17.42	PASS
BLE_1M	Ant1	2480	1000~26500	2.58	-43.2	≤-17.42	PASS
BLE_2M	Ant1	2402	30~1000	2.53	-69.49	≤-17.47	PASS
BLE_2M	Ant1	2402	1000~26500	2.53	-42.99	≤-17.47	PASS
BLE_2M	Ant1	2440	30~1000	2.61	-69.31	≤-17.39	PASS
BLE_2M	Ant1	2440	1000~26500	2.61	-40	≤-17.39	PASS
BLE_2M	Ant1	2480	30~1000	2.63	-68.82	≤-17.37	PASS
BLE_2M	Ant1	2480	1000~26500	2.63	-41.32	≤-17.37	PASS

### Test Graphs


#### Band Edges





## Spurious Emission







## A.5 Duty Cycle

### Test Result

Test Mode	Antenna	Frequency[MHz]	ON Time[ms]	Period[ms]	Duty Cycle[%]	Duty Cycle Factor[dB]
BLE_1M	Ant1	2402	0.40	0.63	63.49	1.97
BLE_1M	Ant1	2440	0.40	0.63	63.49	1.97
BLE_1M	Ant1	2480	0.40	0.63	63.49	1.97
BLE_2M	Ant1	2402	0.21	0.63	33.33	4.77
BLE_2M	Ant1	2440	0.21	0.63	33.33	4.77
BLE_2M	Ant1	2480	0.21	0.63	33.33	4.77

### Test Graphs





## ANNEX B: Test Results of Radiated Test


## B.1 Radiated Band Edges and Spurious Emission


## Test Result\_Band Edges

Note: Both vertical and horizontal polarities have been evaluated, and the test data only shows the worst-case.  
Level=Reading+Factor; Margin=Limit-Level; V=Vertical, H=Horizontal.

Data List									
Test Mode	Frequency [MHz]	Reading [dB $\mu$ V]	Level [dB $\mu$ V/m]	Factor [dB/m]	Limit [dB $\mu$ V/m]	Margin [dB]	Pol.	Det	
BLE_1M_2402	2388.6175	46.86	58.91	12.05	74.00	15.09	H	PK	
	2388.4225	34.99	47.05	12.06	54.00	6.95	V	AV	
BLE_1M_2480	2483.6125	49.43	62.10	12.67	74.00	11.90	V	PK	
	2483.7125	35.15	47.83	12.68	54.00	6.17	H	AV	
BLE_2M_2402	2388.2275	46.59	58.66	12.07	74.00	15.34	H	PK	
	2387.7725	34.91	47.00	12.09	54.00	7.00	H	AV	
BLE_2M_2480	2483.875	50.22	62.91	12.69	74.00	11.09	V	PK	
	2483.9	35.60	48.30	12.70	54.00	5.70	V	AV	

## Test Graphs\_Band Edges





**Test Result\_Spurious Emission**

Note1: Test result Sweep the whole frequency band through the range from 9kHz to the 10th harmonic of the carrier the Emissions in the frequency band 9kHz-30MHz and 18GHz-26.5GHz are more than 20dB below the limit are not reported.

Note2: Both vertical and horizontal polarities have been evaluated, and the test data only shows the worst-case. Level=Reading+Factor; Margin=Limit-Level; V=Vertical , H=Horizontal.


Data List									
Test Mode	Frequency [MHz]	Reading [dB $\mu$ V]	Level [dB $\mu$ V/m]	Factor [dB/m]	Limit [dB $\mu$ V/m]	Margin [dB]	Pol.	Det	
BLE_1M_2402	4803.5854	54.34	61.68	7.34	74.00	12.32	H	PK	
	4803.5854	44.16	51.50	7.34	54.00	2.50	H	AV	
	7206.3375	43.29	56.97	13.68	74.00	17.03	H	PK	
	7206.3375	30.50	44.18	13.68	54.00	9.82	H	AV	
	9608.2175	34.94	47.86	12.92	74.00	26.14	H	PK	
	9608.2175	21.66	34.58	12.92	54.00	19.42	H	AV	
	12009.7425	33.18	47.82	14.64	74.00	26.18	V	PK	
	12009.7425	20.67	35.31	14.64	54.00	18.69	V	AV	
	14411.6775	33.15	49.52	16.37	74.00	24.48	H	PK	
	14411.6775	20.25	36.62	16.37	54.00	17.38	H	AV	
	16813.9425	33.11	54.93	21.82	74.00	19.07	V	PK	
	16813.9425	19.21	41.03	21.82	54.00	12.97	V	AV	
BLE_1M_2440	4880.1359	51.36	58.84	7.48	74.00	15.16	H	PK	
	4880.1359	41.24	48.72	7.48	54.00	5.28	H	AV	
	7320.3625	43.96	58.38	14.42	74.00	15.62	H	PK	
	7320.3625	30.73	45.15	14.42	54.00	8.85	H	AV	
	9759.5325	34.75	48.50	13.75	74.00	25.50	H	PK	
	9759.5325	21.62	35.37	13.75	54.00	18.63	H	AV	
	12200.4575	34.07	47.93	13.86	74.00	26.07	H	PK	
	12200.4575	21.35	35.21	13.86	54.00	18.79	H	AV	
	14640.1625	33.17	50.58	17.41	74.00	23.42	V	PK	
	14640.1625	20.00	37.41	17.41	54.00	16.59	V	AV	


	17079.7425	30.71	54.17	23.46	74.00	19.83	V	PK
	17079.7425	17.42	40.88	23.46	54.00	13.12	V	AV
BLE_1M_2480	4960.1598	49.01	56.41	7.40	74.00	17.59	H	PK
	4960.1598	37.88	45.28	7.40	54.00	8.72	H	AV
	7440.2025	43.48	57.92	14.44	74.00	16.08	H	PK
	7440.2025	30.21	44.65	14.44	54.00	9.35	H	AV
	9920.1875	34.19	47.98	13.79	74.00	26.02	V	PK
	9920.1875	21.52	35.31	13.79	54.00	18.69	V	AV
	12399.8875	34.22	49.01	14.79	74.00	24.99	H	PK
	12399.8875	21.02	35.81	14.79	54.00	18.19	H	AV
	14880.1675	32.91	50.09	17.18	74.00	23.91	H	PK
	14880.1675	20.20	37.38	17.18	54.00	16.62	H	AV
	17360.4925	29.80	53.15	23.35	74.00	20.85	V	PK
	17360.4925	17.01	40.36	23.35	54.00	13.64	V	AV
BLE_2M_2402	4803.952	53.26	60.60	7.34	74.00	13.40	H	PK
	4803.952	38.52	45.86	7.34	54.00	8.14	H	AV
	7205.7175	43.63	57.31	13.68	74.00	16.69	H	PK
	7205.7175	30.52	44.20	13.68	54.00	9.80	H	AV
	9607.6675	34.47	47.39	12.92	74.00	26.61	V	PK
	9607.6675	21.46	34.38	12.92	54.00	19.62	V	AV
	12010.3875	33.57	48.21	14.64	74.00	25.79	V	PK
	12010.3875	20.38	35.02	14.64	54.00	18.98	V	AV
	14412.2825	33.21	49.58	16.37	74.00	24.42	H	PK
	14412.2825	20.02	36.39	16.37	54.00	17.61	H	AV
	16813.8225	31.60	53.42	21.82	74.00	20.58	H	PK
	16813.8225	19.01	40.83	21.82	54.00	13.17	H	AV
BLE_2M_2440	4879.6703	49.95	57.43	7.48	74.00	16.57	V	PK
	4879.6703	35.68	43.16	7.48	54.00	10.84	V	AV
	7319.7075	43.07	57.49	14.42	74.00	16.51	H	PK

BLE_2M_2480	7319.7075	30.21	44.63	14.42	54.00	9.37	H	AV
	9760.4425	34.58	48.33	13.75	74.00	25.67	H	PK
	9760.4425	21.55	35.30	13.75	54.00	18.70	H	AV
	12199.7275	34.41	48.27	13.86	74.00	25.73	V	PK
	12199.7275	21.10	34.96	13.86	54.00	19.04	V	AV
	14639.5975	32.57	49.98	17.41	74.00	24.02	H	PK
	14639.5975	19.95	37.36	17.41	54.00	16.64	H	AV
	17079.9775	30.87	54.33	23.46	74.00	19.67	V	PK
	17079.9775	17.32	40.78	23.46	54.00	13.22	V	AV
	4959.8771	48.37	55.77	7.40	74.00	18.23	H	PK
BLE_2M_2480	4959.8771	34.21	41.61	7.40	54.00	12.39	H	AV
	7440.2325	42.84	57.28	14.44	74.00	16.72	V	PK
	7440.2325	30.00	44.44	14.44	54.00	9.56	V	AV
	9919.5175	34.00	47.79	13.79	74.00	26.21	H	PK
	9919.5175	21.40	35.19	13.79	54.00	18.81	H	AV
	12400.4175	33.40	48.19	14.79	74.00	25.81	V	PK
	12400.4175	20.77	35.56	14.79	54.00	18.44	V	AV
	14879.7125	33.79	50.97	17.18	74.00	23.03	H	PK
	14879.7125	20.12	37.30	17.18	54.00	16.70	H	AV
	17360.2925	29.91	53.26	23.35	74.00	20.74	V	PK
	17360.2925	17.08	40.43	23.35	54.00	13.57	V	AV

Data List								
Test Mode	Frequency [MHz]	Reading [dB $\mu$ V]	Level [dB $\mu$ V/m]	Factor [dB/m]	Limit [dB $\mu$ V/m]	Margin [dB]	Pol.	Det
BLE_2M_2480	41.587877	31.63	15.68	-15.95	40.00	24.32	H	QP
	98.761558	27.72	10.53	-17.19	43.50	32.97	V	QP
	238.120471	24.31	9.95	-14.36	46.00	36.05	V	QP
	449.095036	23.97	13.33	-10.64	46.00	32.67	H	QP

	725.992065	24.83	18.13	-6.70	46.00	27.87	V	QP
	909.876486	23.11	20.47	-2.64	46.00	25.53	V	QP

**Test Graphs\_Spurious Emission**




## ANNEX C: The EUT Appearance

The EUT Appearance (internal and external photographs) are submitted separately.

**ANNEX D: Test Setup Photograph**

The Test Setup Photographs are submitted separately.