



TEST REPORT

Applicant Name : PVSure Pte Ltd
Address : 31 Toh Guan Road East 06-02 Singapore 608608 Singapore
Report Number : RA230130-04403E-RF-00B
FCC ID: 2BAHAPVS01

Test Standard (s)

FCC PART 15.247

Sample Description

Product Type: PVBuddy™ Sensor
Model No.: PVS01
Multiple Model(s) No.: N/A
Trade Mark: N/A
Date Received: 2023/01/30
Report Date: 2023/03/29

Test Result:	Pass*
--------------	-------

* In the configuration tested, the EUT complied with the standards above.

Prepared and Checked By:

Andy Yu
EMC Engineer

Approved By:

Candy Li
EMC Engineer

Note: This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk "★".

Shenzhen Accurate Technology Co., Ltd. is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with an asterisk "★". Customer model name, addresses, names, trademarks etc. are not considered data.

This report cannot be reproduced except in full, without prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

Shenzhen Accurate Technology Co., Ltd.

1/F., Building A, Changyuan New Material Port, Science & Industry Park, Nanshan District, Shenzhen, Guangdong, P.R. China
Tel: +86 755-26503290 Fax: +86 755-26503396 Web: www.atc-lab.com

TABLE OF CONTENTS

DOCUMENT REVISION HISTORY	4
GENERAL INFORMATION.....	5
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	5
OBJECTIVE	5
TEST METHODOLOGY	5
MEASUREMENT UNCERTAINTY	6
SYSTEM TEST CONFIGURATION	7
DESCRIPTION OF TEST CONFIGURATION	7
EQUIPMENT MODIFICATIONS	8
EUT EXERCISE SOFTWARE	8
DUTY CYCLE	8
SUPPORT EQUIPMENT LIST AND DETAILS	12
EXTERNAL I/O CABLE.....	12
BLOCK DIAGRAM OF TEST SETUP	13
SUMMARY OF TEST RESULTS	14
TEST EQUIPMENT LIST	15
FCC§15.247 (I), §1.1307 (B) (3) &§2.1091 – RF EXPOSURE	17
APPLICABLE STANDARD	17
RESULT	17
FCC §15.203 - ANTENNA REQUIREMENT.....	18
APPLICABLE STANDARD	18
ANTENNA CONNECTOR CONSTRUCTION	18
FCC §15.207 (A) – AC LINE CONDUCTED EMISSIONS	19
APPLICABLE STANDARD	19
EUT SETUP	19
EMI TEST RECEIVER SETUP.....	19
TEST PROCEDURE	19
TRANSD FACTOR & MARGIN CALCULATION.....	20
TEST DATA	20
FCC §15.209, §15.205 & §15.247(D) - SPURIOUS EMISSIONS	25
APPLICABLE STANDARD	25
EUT SETUP	25
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	26
TEST PROCEDURE	26
FACTOR & MARGIN CALCULATION	26
TEST DATA	26
FCC §15.247(A) (2) – 6 DB EMISSION BANDWIDTH & OCCUPIED BANDWIDTH	38
APPLICABLE STANDARD	38
TEST PROCEDURE	38
TEST DATA	38

FCC §15.247(B) (3) - MAXIMUM CONDUCTED OUTPUT POWER	56
APPLICABLE STANDARD	56
TEST PROCEDURE	56
TEST DATA	57
FCC §15.247(D) – 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE	60
APPLICABLE STANDARD	60
TEST PROCEDURE	60
TEST DATA	60
FCC §15.247(E) - POWER SPECTRAL DENSITY.....	66
APPLICABLE STANDARD	66
TEST PROCEDURE	66
TEST DATA	66

DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
0	RA230130-04403E-RF-00B	Original Report	2023/03/29

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Frequency Range	BLE: 2402-2480MHz Wi-Fi: 2412-2462MHz
Maximum Conducted Output Power	BLE 1M: 11.64dBm (Peak) Wi-Fi: 18.30dBm(802.11b), 15.74dBm(802.11g) 16.34dBm(802.11n20) ,16.13dBm(802.11n40)
Modulation Technique	BLE: GFSK Wi-Fi: DSSS, OFDM
Antenna Specification*	3.42dBi (provided by the applicant)
Voltage Range	DC5V from USB Port
Sample serial number	1ZIL-2for Conducted and Radiated Emissions Test 1ZIB-1 for RF Conducted Test (Assigned by ATC)
Sample/EUT Status	Good condition

Objective

This test report is in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communication Commission's rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

And KDB 558074 D01 15.247 Meas Guidance v05r02.

All emissions measurement was performed at Shenzhen Accurate Technology Co., Ltd. The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Each test item follows test standards and with no deviation.

Measurement Uncertainty

Parameter		Uncertainty
Occupied Channel Bandwidth		5%
RF output power, conducted		0.73dB
Unwanted Emission, conducted		1.6dB
AC Line Conducted emission		2.72dB
Emissions, Radiated	30MHz - 1GHz	4.28dB
	1GHz- 18GHz	4.98dB
	18GHz- 26.5GHz	5.06dB
Temperature		1°C
Humidity		6%
Supply voltages		0.4%

Note: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

Test Facility

The test site used by Shenzhen Accurate Technology Co., Ltd. to collect test data is located on the 1/F., Building A, Changyuan New Material Port, Science & Industry Park, Nanshan District, Shenzhen, Guangdong, P.R. China.

The test site has been approved by the FCC under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No.: 708358, the FCC Designation No.: CN1189. Accredited by American Association for Laboratory Accreditation (A2LA) The Certificate Number is 429 7.01.

Listed by Innovation, Science and Economic Development Canada (ISED), the Registration Number is 5077A.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

For 802.11b, 802.11g, 802.11n-HT20, 802.11n-HT40 mode, total 11 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	8	2447
2	2417	9	2452
3	2422	10	2457
4	2427	11	2462
5	2432	/	/
6	2437	/	/
7	2442	/	/

802.11b, 802.11g and 802.11n-HT20 mode was tested with Channel 1, 6 and 11.

802.11n-HT40 mode was tested with Channel 3, 6 and 9.

For BLE mode, 40 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	20	2442
1	2404	21	2444
2	2406	22	2446
3	2408	23	2448
4	2410	24	2450
5	2412	25	2452
6	2414	26	2454
7	2416	27	2456
8	2418	28	2458
9	2420	29	2460
10	2422	30	2462
11	2424	31	2464
12	2426	32	2466
13	2428	33	2468
14	2430	34	2470
15	2432	35	2472
16	2434	36	2474
17	2436	37	2476
18	2438	38	2478
19	2440	39	2480

EUT was tested with Channel 0, 19 and 39.

Equipment Modifications

No modification was made to the EUT tested.

EUT Exercise Software

“EspRFTTestTool_v2.8_Manua *” exercise software was used.

The device was tested with the worst case was performed as below:


Mode	Data rate	Power Level*		
		Low Channel	Middle Channel	High Channel
802.11b	1Mbps	0	0	0
802.11g	6Mbps	10	10	10
802.11n-HT20	MCS0	10	10	10
802.11n-HT40	MCS0	0	0	0
BLE	1Mbps	8	8	8

Note: the power level was provided by applicant.

Duty cycle

BLE


Mode	T _{on} (ms)	T _{on+off} (ms)	Duty Cycle (%)	1/T Minimum VBW(kHz)	Duty Cycle Correction Faction(dB)
BLE 1M	2.095	2.505	83.63	0.477	0.78




2.4G Wi-Fi

Mode	T _{on} (ms)	T _{on+off} (ms)	Duty Cycle (%)	1/T Minimum VBW(kHz)	Duty Cyle Correction Faction(dB)
802.11b	1.0075	1.125	89.56	0.993	0.48
802.11g	0.617	0.690	89.42	1.621	0.49
802.11n- HT20	0.613	0.685	89.49	1.631	0.48
802.11n- HT40	/	/	100	/	/


802.11b




802.11g



802.11n20



802.11n40



Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
TECNO	Adapter	U330TSA	Unknown

External I/O Cable


Cable Description	Length (m)	From Port	To
Un-shield Un-Detachable DC Power Cable	0.3	Adapter	EUT

Block Diagram of Test Setup

For conducted emission



For Radiated Emissions:



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
FCC§15.247 (i), §1.1307 (b) (3) & §2.1091	RF Exposure	Compliant
§15.203	Antenna Requirement	Compliant
§15.207 (a)	AC Line Conducted Emissions	Compliant
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliant
§15.247 (a)(2)	6 dB Emission Bandwidth & Occupied Bandwidth	Compliant
§15.247(b)(3)	Maximum Conducted Output Power	Compliant
§15.247(d)	100 kHz Bandwidth of Frequency Band Edge	Compliant
§15.247(e)	Power Spectral Density	Compliant

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Conducted emission test					
Rohde& Schwarz	EMI Test Receiver	ESCI	100784	2022/11/25	2023/11/24
Rohde & Schwarz	L.I.S.N.	ENV216	101314	2022/11/25	2023/11/24
Anritsu Corp	50 Coaxial Switch	MP59B	6100237248	2022/12/07	2023/12/06
Unknown	RF Coaxial Cable	No.17	N0350	2022/11/25	2023/11/24
Conducted Emission Test Software: e3 19821b (V9)					
Radiated emission test					
Rohde & Schwarz	Test Receiver	ESR	102725	2022/11/25	2023/11/24
Rohde & Schwarz	Spectrum Analyzer	FSV40	101949	2022/11/25	2023/11/24
SONOMA INSTRUMENT	Amplifier	310 N	186131	2022/11/08	2023/11/07
A.H. Systems, inc.	Preamplifier	PAM-0118P	135	2022/11/08	2023/11/07
Quinstar	Amplifier	QLW-18405536-J0	15964001002	2022/11/08	2023/11/07
Schwarzbeck	Bilog Antenna	VULB9163	9163-323	2021/07/06	2024/07/05
Schwarzbeck	Horn Antenna	BBHA9120D	9120D-1067	2022/11/30	2025/11/29
Schwarzbeck	HORN ANTENNA	BBHA9170	9170-359	2022/12/26	2025/12/25
Radiated Emission Test Software: e3 19821b (V9)					
Unknown	RF Coaxial Cable	No.10	N050	2022/11/25	2023/11/24
Unknown	RF Coaxial Cable	No.11	N1000	2022/11/25	2023/11/24
Unknown	RF Coaxial Cable	No.12	N040	2022/11/25	2023/11/24
Unknown	RF Coaxial Cable	No.13	N300	2022/11/25	2023/11/24
Unknown	RF Coaxial Cable	No.14	N800	2022/11/25	2023/11/24
Unknown	RF Coaxial Cable	No.15	N600	2022/11/25	2023/11/24
Unknown	RF Coaxial Cable	No.16	N650	2022/11/25	2023/11/24
Wainwright	High Pass Filter	WHKX3.6/18 G-10SS	5	2022/11/25	2023/11/24

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
RF Conducted Test					
Rohde & Schwarz	Spectrum Analyzer	FSV-40	101948	2022/11/25	2023/11/24
SPECTRUM ANALYZER	Rohde & Schwarz	FSU26	200982	2022/07/04	2023/07/03
Agilent	USB wideband power sensor	U2021XA	MY54250003	2022/06/27	2023/06/26
WEINSCHTEL	10dB Attenuator	5324	AU 3842	2022/11/25	2023/11/24
Unknown	RF Cable	Unknown	1	Each time	

* **Statement of Traceability:** Shenzhen Accurate Technology Co., Ltd. attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC§15.247 (i), §1.1307 (b) (3) & §2.1091 – RF EXPOSURE

Applicable Standard

According to subpart 15.247 (i) and subpart 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

According to KDB 447498 D04 Interim General RF Exposure Guidance

MPE-Based Exemption:

General frequency and separation-distance dependent MPE-based effective radiated power(ERP) thresholds are in Table B.1 [Table 1 of § 1.1307(b)(1)(i)(C)] to support an exemption from further evaluation from 300 kHz through 100 GHz.

Table 1 to § 1.1307(b)(3)(i)(C) - Single RF Sources Subject to Routine Environmental Evaluation

RF Source frequency (MHz)	Threshold ERP (watts)
0.3-1.34	$1,920 R^2$.
1.34-30	$3,450 R^2/f^2$.
30-300	$3.83 R^2$.
300-1,500	$0.0128 R^2 f$.
1,500-100,000	$19.2 R^2$.

R is the minimum separation distance in meters

f = frequency in MHz

Result

Mode	Frequency (MHz)	Antenna Gain		Tune up conducted power (dBm)	ERP		Evaluation Distance (m)	ERP Limit (W)
		(dBi)	(dBd)		(dBm)	(W)		
BLE	2402-2480	3.42	1.27	12.0	13.27	0.021	0.2	0.768
Wi-Fi	2412-2462	3.42	1.27	19.0	20.27	0.106	0.2	0.768

Note: Wi-Fi and Bluetooth cannot transmit simultaneous,

To maintain compliance with the FCC's RF exposure guidelines, place the equipment at least 20cm from nearby persons.

Result: Compliance

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.
- c. Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Antenna Connector Construction

The EUT has one internal antenna which was permanently attached, and the maximum antenna gain is 3.42dBi, fulfill the requirement of this section. Please refer to the EUT photos.


Result: Compliant.

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC§15.207

EUT Setup



- Note: 1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All final data was recorded in the Quasi-peak and average detection mode.

Transd Factor & Margin Calculation

The Transd factor is calculated by adding LISN VDF (Voltage Division Factor) and Cable Loss. The basic equation is as follows:

$$\text{Transd Factor} = \text{LISN VDF} + \text{Cable Loss}$$

The “**Over limit**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over limit of -7 dB means the emission is 7 dB below the limit. The equation for calculation is as follows:

$$\begin{aligned}\text{Over Limit} &= \text{Level} - \text{Limit} \\ \text{Level} &= \text{Read Level} + \text{Factor}\end{aligned}$$


Test Data

Environmental Conditions

Temperature:	23 °C
Relative Humidity:	52 %
ATM Pressure:	101.3 kPa


The testing was performed by Lipa Wu on 2023-02-07.

EUT operation mode: Transmitting

BLE (Worst case is low channel)**AC 120V/60 Hz, Line**


Site : Shielding Room
 Condition: Line
 Job No. : RA230130-04403E-RF
 Mode : BLE&Transmitting
 Power : AC 120V 60Hz

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dBuV	dBuV	dB	
1	0.167	9.90	15.76	25.66	55.13	-29.47	Average
2	0.167	9.90	29.89	39.79	65.13	-25.34	QP
3	0.202	9.90	13.36	23.26	53.52	-30.26	Average
4	0.202	9.90	26.49	36.39	63.52	-27.13	QP
5	0.482	9.80	26.42	36.22	46.31	-10.09	Average
6	0.482	9.80	28.75	38.55	56.31	-17.76	QP
7	0.500	9.80	30.06	39.86	46.00	-6.14	Average
8	0.500	9.80	30.83	40.63	56.00	-15.37	QP
9	2.091	9.92	14.44	24.36	46.00	-21.64	Average
10	2.091	9.92	16.87	26.79	56.00	-29.21	QP
11	6.369	9.96	7.13	17.09	50.00	-32.91	Average
12	6.369	9.96	11.13	21.09	60.00	-38.91	QP

AC 120V/60 Hz, Neutral


Site : Shielding Room
 Condition: Neutral
 Job No. : RA230130-04403E-RF
 Mode : BLE&Transmitting
 Power : AC 120V 60Hz

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dBuV	dBuV	dB	
1	0.187	9.80	11.78	21.58	54.17	-32.59	Average
2	0.187	9.80	27.52	37.32	64.17	-26.85	QP
3	0.244	9.82	7.82	17.64	51.97	-34.33	Average
4	0.244	9.82	21.85	31.67	61.97	-30.30	QP
5	0.500	9.90	19.05	28.95	46.00	-17.05	Average
6	0.500	9.90	27.38	37.28	56.00	-18.72	QP
7	0.659	9.83	15.69	25.52	46.00	-20.48	Average
8	0.659	9.83	18.54	28.37	56.00	-27.63	QP
9	2.721	9.83	-1.76	8.07	46.00	-37.93	Average
10	2.721	9.83	4.93	14.76	56.00	-41.24	QP
11	6.235	10.02	0.77	10.79	50.00	-39.21	Average
12	6.235	10.02	8.19	18.21	60.00	-41.79	QP

2.4G Wi-Fi (Worst case is 802.11b, low channel)**AC 120V/60 Hz, Line**

Site : Shielding Room
 Condition: Line
 Job No. : RA230130-04403E-RF
 Mode : 2.4G WiFi&Transmitting
 Power : AC 120V 60Hz

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dBuV	dBuV	dB	
1	0.161	9.90	15.50	25.40	55.41	-30.01	Average
2	0.161	9.90	29.92	39.82	65.41	-25.59	QP
3	0.180	9.90	18.27	28.17	54.49	-26.32	Average
4	0.180	9.90	27.83	37.73	64.49	-26.76	QP
5	0.231	9.88	10.17	20.05	52.41	-32.36	Average
6	0.231	9.88	23.62	33.50	62.41	-28.91	QP
7	0.500	9.80	30.11	39.91	46.00	-6.09	Average
8	0.500	9.80	30.88	40.68	56.00	-15.32	QP
9	2.112	9.92	13.94	23.86	46.00	-22.14	Average
10	2.112	9.92	16.58	26.50	56.00	-29.50	QP
11	5.239	9.95	7.51	17.46	50.00	-32.54	Average
12	5.239	9.95	12.18	22.13	60.00	-37.87	QP

AC 120V/60 Hz, Neutral

Site : Shielding Room
 Condition: Neutral
 Job No. : RA230130-04403E-RF
 Mode : 2.4G WiFi&Transmitting
 Power : AC 120V 60Hz

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dBuV	dBuV	dB	
1	0.167	9.80	13.36	23.16	55.11	-31.95	Average
2	0.167	9.80	29.87	39.67	65.11	-25.44	QP
3	0.179	9.80	14.06	23.86	54.53	-30.67	Average
4	0.179	9.80	29.77	39.57	64.53	-24.96	QP
5	0.214	9.81	8.08	17.89	53.05	-35.16	Average
6	0.214	9.81	25.06	34.87	63.05	-28.18	QP
7	0.500	9.90	19.13	29.03	46.00	-16.97	Average
8	0.500	9.90	27.47	37.37	56.00	-18.63	QP
9	2.306	9.82	-1.50	8.32	46.00	-37.68	Average
10	2.306	9.82	5.45	15.27	56.00	-40.73	QP
11	22.521	10.20	0.54	10.74	50.00	-39.26	Average
12	22.521	10.20	6.93	17.13	60.00	-42.87	QP


FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS

Applicable Standard


FCC §15.247 (d); §15.209; §15.205;

EUT Setup

Below 1 GHz:



Above 1GHz:



The radiated emission tests were performed in the 3 meters test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

EMI Test Receiver & Spectrum Analyzer Setup

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Measurement
30 MHz – 1000 MHz	100 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1MHz	3 MHz	/	PK
	1MHz	10 Hz ^{Note 1}	/	Average
	1MHz	> 1/T ^{Note 2}	/	Average

Note 1: when duty cycle is no less than 98%

Note 2: when duty cycle is less than 98%

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz, peak and Average detection modes for frequencies above 1 GHz.

Factor & Margin Calculation

The Factor is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain. The basic equation is as follows:

$$\text{Factor} = \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Over Limit/Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over Limit/margin of -7dB means the emission is 7dB below the limit. The equation for calculation is as follows:

$$\begin{aligned} \text{Over Limit/Margin} &= \text{Level} / \text{Corrected Amplitude} - \text{Limit} \\ \text{Level} / \text{Corrected Amplitude} &= \text{Read Level} + \text{Factor} \end{aligned}$$

Test Data

Environmental Conditions

Temperature:	24~25.5 °C
Relative Humidity:	52~59 %
ATM Pressure:	101.1 kPa

The testing was performed by Jimi Zheng on 2023-02-08 for below 1GHz and Jimi Zheng on 2023-02-10 for above 1GHz


EUT operation mode: Transmitting (Pre-scan in the X, Y and Z axes of orientation, the worst case X-axis of orientation was recorded)

30MHz-1GHz:

Note: When the test result of Peak was less than the limit of QP, just the peak value was recorded.

BLE (Worst case is low channel)

Horizontal:



Site : chamber


Condition: 3m HORIZONTAL

Job No. : RA230130-04403E-RF

Test Mode: BLE Transmitting


	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	40.488	-10.27	29.50	19.23	40.00	-20.77	Peak
2	114.565	-12.66	35.11	22.45	43.50	-21.05	Peak
3	126.661	-14.50	35.78	21.28	43.50	-22.22	Peak
4	250.521	-10.74	39.06	28.32	46.00	-17.68	Peak
5	320.077	-8.45	34.14	25.69	46.00	-20.31	Peak
6	760.037	-0.55	31.16	30.61	46.00	-15.39	Peak

Vertical



Site : chamber
 Condition: 3m VERTICAL
 Job No. : RA230130-04403E-RF
 Test Mode: BLE Transmitting

	Freq	Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	50.254	-9.92	35.38	25.46	40.00	-14.54	Peak
2	111.054	-12.11	33.57	21.46	43.50	-22.04	Peak
3	151.531	-15.18	34.42	19.24	43.50	-24.26	Peak
4	244.554	-10.61	35.40	24.79	46.00	-21.21	Peak
5	440.003	-5.64	32.48	26.84	46.00	-19.16	Peak
6	640.050	-1.92	30.93	29.01	46.00	-16.99	Peak

2.4G Wi-Fi (Worst case is 802.11b, low channel)**Horizontal:**

Site : chamber


Condition: 3m HORIZONTAL

Job No. : RA230130-04403E-RF

Test Mode: 2.4G WIFI Transmitting

	Freq Factor		Read Level	Level	Limit	Over	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	40.417	-10.28	28.70	18.42	40.00	-21.58	Peak
2	58.793	-10.19	29.33	19.14	40.00	-20.86	Peak
3	126.163	-14.42	36.05	21.63	43.50	-21.87	Peak
4	168.562	-13.72	32.57	18.85	43.50	-24.65	Peak
5	239.357	-10.91	36.87	25.96	46.00	-20.04	Peak
6	613.407	-2.43	28.99	26.56	46.00	-19.44	Peak

Vertical



Site : chamber

Condition: 3m VERTICAL

Job No. : RA230130-04403E-RF

Test Mode: 2.4G WIFI Transmitting

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	51.278	-9.95	35.92	25.97	40.00	-14.03	Peak
2	106.665	-11.94	32.58	20.64	43.50	-22.86	Peak
3	155.501	-14.88	34.30	19.42	43.50	-24.08	Peak
4	254.505	-10.63	33.19	22.56	46.00	-23.44	Peak
5	440.003	-5.64	32.45	26.81	46.00	-19.19	Peak
6	800.031	-0.35	32.04	31.69	46.00	-14.31	Peak

1-25 GHz:**BLE 1M:**

Frequency (MHz)	Receiver		Turntable Angle Degree	Rx Antenna		Factor (dB/m)	Absolute Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/Ave		Height (m)	Polar (H/V)				
Low Channel(2402MHz)									
2359.73	63.60	PK	73	2.3	H	-7.19	56.41	74	-17.59
2359.73	49.65	AV	73	2.3	H	-7.19	42.46	54	-11.54
2343.29	62.69	PK	158	1.2	V	-7.19	55.50	74	-18.50
2343.29	49.15	AV	158	1.2	V	-7.19	41.96	54	-12.04
2390	61.80	PK	199	1.3	H	-7.22	54.58	74	-19.42
2390	49.49	AV	199	1.3	H	-7.22	42.27	54	-11.73
2390	61.74	PK	166	1.8	V	-7.22	54.52	74	-19.48
2390	49.42	AV	166	1.8	V	-7.22	42.20	54	-11.80
4804	58.51	PK	279	2.3	H	-3.51	55.00	74	-19.00
4804	45.76	AV	279	2.3	H	-3.51	42.25	54	-11.75
4804	57.88	PK	101	2.3	V	-3.51	54.37	74	-19.63
4804	43.97	AV	101	2.3	V	-3.51	40.46	54	-13.54
Middle Channel(2440MHz)									
4880	58.31	PK	225	2.3	H	-3.38	54.93	74	-19.07
4880	45.37	AV	225	2.3	H	-3.38	41.99	54	-12.01
4880	58.15	PK	163	1.4	V	-3.38	54.77	74	-19.23
4880	44.20	AV	163	1.4	V	-3.38	40.82	54	-13.18
High Channel(2480 MHz)									
2483.5	71.92	PK	51	1.4	H	-7.20	64.72	74	-9.28
2483.5	51.83	AV	51	1.4	H	-7.20	44.63	54	-9.37
2483.5	72.08	PK	93	1.3	V	-7.20	64.88	74	-9.12
2483.5	56.76	AV	93	1.3	V	-7.20	49.56	54	-4.44
2483.75	73.74	PK	247	2.1	H	-7.20	66.54	74	-7.46
2483.75	55.27	AV	247	2.1	H	-7.20	48.07	54	-5.93
2483.51	74.59	PK	34	2	V	-7.20	67.39	74	-6.61
2483.51	57.50	AV	34	2	V	-7.20	50.3	54	-3.70
4960	58.72	PK	142	2.3	H	-3.01	55.71	74	-18.29
4960	46.15	AV	142	2.3	H	-3.01	43.14	54	-10.86
4960	57.71	PK	340	2.2	V	-3.01	54.70	74	-19.30
4960	43.43	AV	340	2.2	V	-3.01	40.42	54	-13.58

Wi-Fi:

Frequency (MHz)	Receiver		Turntable Angle Degree	Rx Antenna		Factor (dB/m)	Absolute Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/Ave		Height (m)	Polar (H/V)				
802.11b									
Low Channel(2412MHz)									
2355.44	64.02	PK	151	1.4	H	-7.19	56.83	74	-17.17
2355.44	50.99	AV	151	1.4	H	-7.19	43.80	54	-10.20
2337.26	62.67	PK	273	1.4	V	-7.20	55.47	74	-18.53
2337.26	49.43	AV	273	1.4	V	-7.20	42.23	54	-11.77
2390	62.93	PK	258	1.3	H	-7.22	55.71	74	-18.29
2390	50.27	AV	258	1.3	H	-7.22	43.05	54	-10.95
2390	62.42	PK	16	1.2	V	-7.22	55.20	74	-18.80
2390	50.01	AV	16	1.2	V	-7.22	42.79	54	-11.21
4824	61.38	PK	3	1.2	H	-3.52	57.86	74	-16.14
4824	51.74	AV	3	1.2	H	-3.52	48.22	54	-5.78
4824	59.82	PK	213	1.7	V	-3.52	56.30	74	-17.70
4824	48.43	AV	213	1.7	V	-3.52	44.91	54	-9.09
Middle Channel(2437MHz)									
4874	61.39	PK	91	2.1	H	-3.42	57.97	74	-16.03
4874	51.70	AV	91	2.1	H	-3.42	48.28	54	-5.72
4874	60.32	PK	181	2.4	V	-3.42	56.9	74	-17.10
4874	49.17	AV	181	2.4	V	-3.42	45.75	54	-8.25
High Channel(2462MHz)									
2483.5	65.03	PK	185	2.2	H	-7.20	57.83	74	-16.17
2483.5	51.50	AV	185	2.2	H	-7.20	44.3	54	-9.70
2483.5	63.04	PK	147	1.7	V	-7.20	55.84	74	-18.16
2483.5	50.42	AV	147	1.7	V	-7.20	43.22	54	-10.78
2483.56	66.48	PK	103	1.1	H	-7.20	59.28	74	-14.72
2483.56	53.27	AV	103	1.1	H	-7.20	46.07	54	-7.93
2490.1	64.22	PK	233	2	V	-7.19	57.03	74	-16.97
2490.1	50.97	AV	233	2	V	-7.19	43.78	54	-10.22
4924	62.07	PK	193	1.9	H	-3.16	58.91	74	-15.09
4924	53.20	AV	193	1.9	H	-3.16	50.04	54	-3.96
4924	58.31	PK	333	1.9	V	-3.16	55.15	74	-18.85
4924	47.95	AV	333	1.9	V	-3.16	44.79	54	-9.21

Frequency (MHz)	Receiver		Turntable Angle Degree	Rx Antenna		Factor (dB/m)	Absolute Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/Ave		Height (m)	Polar (H/V)				
802.11g									
Low Channel(2412MHz)									
2383.81	65.13	PK	113	2.2	H	-7.21	57.92	74	-16.08
2383.81	52.04	AV	113	2.2	H	-7.21	44.83	54	-9.17
2381.62	63.90	PK	50	1	V	-7.21	56.69	74	-17.31
2381.62	50.52	AV	50	1	V	-7.21	43.31	54	-10.69
2390	64.07	PK	323	1.5	H	-7.22	56.85	74	-17.15
2390	51.80	AV	323	1.5	H	-7.22	44.58	54	-9.42
2390	63.02	PK	71	2.4	V	-7.22	55.80	74	-18.20
2390	50.09	AV	71	2.4	V	-7.22	42.87	54	-11.13
4824	59.61	PK	1	1.8	H	-3.52	56.09	74	-17.91
4824	44.98	AV	1	1.8	H	-3.52	41.46	54	-12.54
4824	58.53	PK	32	2.3	V	-3.52	55.01	74	-18.99
4824	43.60	AV	32	2.3	V	-3.52	40.08	54	-13.92
Middle Channel(2437MHz)									
4874	59.43	PK	277	2.5	H	-3.42	56.01	74	-17.99
4874	44.84	AV	277	2.5	H	-3.42	41.42	54	-12.58
4874	58.51	PK	204	2.1	V	-3.42	55.09	74	-18.91
4874	43.70	AV	204	2.1	V	-3.42	40.28	54	-13.72
High Channel(2462MHz)									
2483.5	68.13	PK	216	1.9	H	-7.20	60.93	74	-13.07
2483.5	54.24	AV	216	1.9	H	-7.20	47.04	54	-6.96
2483.5	63.68	PK	319	1.4	V	-7.20	56.48	74	-17.52
2483.5	51.12	AV	319	1.4	V	-7.20	43.92	54	-10.08
2483.7	68.46	PK	157	2.3	H	-7.20	61.26	74	-12.74
2483.7	54.39	AV	157	2.3	H	-7.20	47.19	54	-6.81
2489.36	65.56	PK	156	1.1	V	-7.19	58.37	74	-15.63
2489.36	51.50	AV	156	1.1	V	-7.19	44.31	54	-9.69
4924	59.54	PK	58	2.4	H	-3.16	56.38	74	-17.62
4924	45.07	AV	58	2.4	H	-3.16	41.91	54	-12.09
4924	57.76	PK	206	1.9	V	-3.16	54.60	74	-19.40
4924	43.29	AV	206	1.9	V	-3.16	40.13	54	-13.87

Frequency (MHz)	Receiver		Turntable Angle Degree	Rx Antenna		Factor (dB/m)	Absolute Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/Ave		Height (m)	Polar (H/V)				
802.11n20									
Low Channel(2412MHz)									
2389.02	65.94	PK	72	1.7	H	-7.22	58.72	74	-15.28
2389.02	52.82	AV	72	1.7	H	-7.22	45.60	54	-8.40
2389.83	65.10	PK	321	2.2	V	-7.22	57.88	74	-16.12
2389.83	50.89	AV	321	2.2	V	-7.22	43.67	54	-10.33
2390	65.03	PK	50	2.1	H	-7.22	57.81	74	-16.19
2390	52.35	AV	50	2.1	H	-7.22	45.13	54	-8.87
2390	63.47	PK	20	1	V	-7.22	56.25	74	-17.75
2390	50.38	AV	20	1	V	-7.22	43.16	54	-10.84
4824	59.48	PK	176	2.2	H	-3.52	55.96	74	-18.04
4824	44.77	AV	176	2.2	H	-3.52	41.25	54	-12.75
4824	58.41	PK	96	2	V	-3.52	54.89	74	-19.11
4824	43.70	AV	96	2	V	-3.52	40.18	54	-13.82
Middle Channel(2437MHz)									
4874	59.31	PK	132	1.5	H	-3.42	55.89	74	-18.11
4874	44.65	AV	132	1.5	H	-3.42	41.23	54	-12.77
4874	58.43	PK	3	1.5	V	-3.42	55.01	74	-18.99
4874	43.64	AV	3	1.5	V	-3.42	40.22	54	-13.78
High Channel(2462MHz)									
2483.5	69.77	PK	75	1.4	H	-7.20	62.57	74	-11.43
2483.5	55.42	AV	75	1.4	H	-7.20	48.22	54	-5.78
2483.5	64.06	PK	201	2.5	V	-7.20	56.86	74	-17.14
2483.5	51.50	AV	201	2.5	V	-7.20	44.3	54	-9.70
2483.7	70.49	PK	180	2.5	H	-7.20	63.29	74	-10.71
2483.7	55.71	AV	180	2.5	H	-7.20	48.51	54	-5.49
2489.03	65.23	PK	125	2.3	V	-7.19	58.04	74	-15.96
2489.03	51.82	AV	125	2.3	V	-7.19	44.63	54	-9.37
4924	58.99	PK	202	1.3	H	-3.16	55.83	74	-18.17
4924	44.74	AV	202	1.3	H	-3.16	41.58	54	-12.42
4924	58.30	PK	328	1.6	V	-3.16	55.14	74	-18.86
4924	43.45	AV	328	1.6	V	-3.16	40.29	54	-13.71

Frequency (MHz)	Receiver		Turntable Angle Degree	Rx Antenna		Factor (dB/m)	Absolute Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/Ave		Height (m)	Polar (H/V)				
802.11n40									
Low Channel(2422MHz)									
2389.94	67.10	PK	348	2.1	H	-7.22	59.88	74	-14.12
2389.94	53.51	AV	348	2.1	H	-7.22	46.29	54	-7.71
2387.87	65.42	PK	215	2	V	-7.22	58.20	74	-15.80
2387.87	51.04	AV	215	2	V	-7.22	43.82	54	-10.18
2390	65.89	PK	226	1.6	H	-7.22	58.67	74	-15.33
2390	53.13	AV	226	1.6	H	-7.22	45.91	54	-8.09
2390	63.55	PK	107	1.5	V	-7.22	56.33	74	-17.67
2390	50.58	AV	107	1.5	V	-7.22	43.36	54	-10.64
4844	58.90	PK	323	1.2	H	-3.54	55.36	74	-18.64
4844	43.93	AV	323	1.2	H	-3.54	40.39	54	-13.61
4844	57.74	PK	229	1.9	V	-3.54	54.20	74	-19.80
4844	43.16	AV	229	1.9	V	-3.54	39.62	54	-14.38
Middle Channel(2437MHz)									
4874	58.87	PK	150	2.5	H	-3.42	55.45	74	-18.55
4874	43.90	AV	150	2.5	H	-3.42	40.48	54	-13.52
4874	58.16	PK	68	1.5	V	-3.42	54.74	74	-19.26
4874	43.41	AV	68	1.5	V	-3.42	39.99	54	-14.01
High Channel(2452MHz)									
2483.5	70.06	PK	253	1.8	H	-7.20	62.86	74	-11.14
2483.5	57.79	AV	253	1.8	H	-7.20	50.59	54	-3.41
2483.5	64.71	PK	37	1.6	V	-7.20	57.51	74	-16.49
2483.5	52.42	AV	37	1.6	V	-7.20	45.22	54	-8.78
2487.76	72.03	PK	41	2.4	H	-7.19	64.84	74	-9.16
2487.76	58.92	AV	41	2.4	H	-7.19	51.73	54	-2.27
2486.59	65.98	PK	44	2.2	V	-7.20	58.78	74	-15.22
2486.59	53.17	AV	44	2.2	V	-7.20	45.97	54	-8.03
4904	59.06	PK	124	1.7	H	-3.26	55.80	74	-18.20
4904	44.19	AV	124	1.7	H	-3.26	40.93	54	-13.07
4904	57.87	PK	145	1	V	-3.26	54.61	74	-19.39
4904	43.25	AV	145	1	V	-3.26	39.99	54	-14.01

Note:



Corrected Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor

Corrected Amplitude = Corrected Factor + Reading

Margin = Corrected. Amplitude - Limit

The other spurious emission which is in the noise floor level was not recorded.


The test result of peak was less than the limit of average, so just peak value were recorded.

1-18 GHz:**Pre-scan for 802.11 b, High Channel****Horizontal****Vertical**


18 -25GHz:

Pre-scan for 802.11 b, High Channel

Horizontal



Vertical



FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH & OCCUPIED BANDWIDTH


Applicable Standard

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Test Procedure

Test Method: ANSI C63.10-2013 Clause 11.8.1 & Clause 6.9.3

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 6 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.



Test Data

Environmental Conditions

Temperature:	25.3~26.4 °C
Relative Humidity:	40~50 %
ATM Pressure:	101.0 kPa

The testing was performed by Gleen Jiang from 2023-02-11 to 2023-02-14.

EUT operation mode: Transmitting


Test Result: Compliant.

BLE


Channel	Frequency (MHz)	6 dB Emission Bandwidth (MHz)	99% Emission Bandwidth (MHz)	Limit (kHz)
BLE 1M				
Low	2402	0.648	1.013	≥500
Middle	2440	0.648	1.011	≥500
High	2480	0.651	1.014	≥500

6dB Bandwidth:


Low Channel



Middle Channel




High Channel




99% Emission Bandwidth:


Low Channel



Middle Channel



High Channel




2.4G WiFi


Channel	Frequency (MHz)	6 dB Emission Bandwidth (MHz)	99% Emission Bandwidth (MHz)	Limit (kHz)
802.11b mode				
Low	2412	10.11	13.60	≥ 500
Middle	2437	10.11	13.48	≥ 500
High	2462	10.11	13.56	≥ 500
802.11g mode				
Low	2412	16.44	17.84	≥ 500
Middle	2437	16.41	17.88	≥ 500
High	2462	16.44	18.00	≥ 500
802.11n-HT20 mode				
Low	2412	17.64	19.00	≥ 500
Middle	2437	17.67	18.84	≥ 500
High	2462	17.67	18.76	≥ 500
802.11n-HT40 mode				
Low	2422	32.94	34.56	≥ 500
Middle	2437	33.24	34.48	≥ 500
High	2452	32.88	34.48	≥ 500

6dB Bandwidth:
802.11b

Low Channel



Middle Channel



Ref 25 dBm * Att 30 dB * RBW 100 kHz Delta 2 [T1] -1.72 dB 10.110000000 MHz

Offset 10.5 dB

Marker 1 [T1] 2.456930000 GHz 2.61 dBm


Marker 3 [T1] 2.462480000 GHz 2.63 dBm

D1 1.63 dBm


1 PK VIEW

Center 2.462 GHz 3 MHz/ Span 30 MHz


Low Channel



Middle Channel




High Channel




802.11n-HT20


Low Channel



Middle Channel




High Channel




802.11n-HT40


Low Channel



Middle Channel




High Channel




99% Emission Bandwidth:
802.11b

Low Channel




Middle Channel




[illegible]


Low Channel



Middle Channel




High Channel




802.11n-HT20


Low Channel



Middle Channel




High Channel



802.11n-HT40

Low Channel



FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER

Applicable Standard


According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

Test Procedure


Test Method: ANSI C63.10-2013 Clause 11.9.1.1 & 11.9.2.3.2

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
3. Add a correction factor to the display.

For Wi-Fi mode:



For BLE mode:



Test Data

Environmental Conditions

Temperature:	25.3~26.4 °C
Relative Humidity:	40~50 %
ATM Pressure:	101.0 kPa

The testing was performed by Gleen Jiang from 2023-02-11 to 2023-02-14.


EUT operation mode: Transmitting

Test Result: Compliant.


BLE

Channel	Frequency (MHz)	Max Conducted Peak Output Power (dBm)	Limit (dBm)
BLE 1M			
Low	2402	11.64	30
Middle	2440	9.71	30
High	2480	9.15	30


Low Channel



Middle Channel



High Channel



2.4G Wi-Fi

Channel	Frequency (MHz)	Max Conducted Average Output Power (dBm)	Limit (dBm)
802.11b mode			
Low	2412	18.30	30
Middle	2437	17.39	30
High	2462	17.22	30
802.11g mode			
Low	2412	15.74	30
Middle	2437	15.50	30
High	2462	15.38	30
802.11n HT20 mode			
Low	2412	16.34	30
Middle	2437	15.26	30
High	2462	14.54	30
802.11n HT40 mode			
Low	2422	16.13	30
Middle	2437	14.91	30
High	2452	14.49	30


FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE**Applicable Standard**

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

Test Method: ANSI C63.10-2013 Clause 11.11

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

**Test Data****Environmental Conditions**

Temperature:	25.3~26.4 °C
Relative Humidity:	40~50 %
ATM Pressure:	101.0 kPa

The testing was performed by Gleen Jiang from 2023-02-11 to 2023-02-14.


EUT operation mode: Transmitting

Test Result: Compliant.


Conducted Band Edge Result:

BLE

Band Edge, Left Side




Band Edge, Right Side




2.4 G WiFi


802.11b: Band Edge, Left Side




802.11b: Band Edge, Right Side




802.11g: Band Edge, Left Side




802.11g: Band Edge, Right Side



802.11n HT20: Band Edge, Left Side



802.11n HT20: Band Edge, Right Side



Ref 25 dBm * Att 30 dB * RBW 100 kHz * VBW 300 kHz * SWT 1 s

Marker 1 [T1] -30.18 dBm 2.413275000 GHz
Marker 2 [T1] -31.18 dBm 2.399775000 GHz
Marker 3 [T1]

1 PK VIEW

30B

Start 2.31 GHz 13.5 MHz/ Stop 2.445 GHz

Ref 25 dBm * Att 30 dB

* RBW 100 kHz * VBW 300 kHz * SWT 1 s

Marker 3 [T1] 2.483500000 GHz -41.66 dBm

Marker 1 [T1] 2.430000000 GHz -2.30 dBm

Marker 2 [T1] 2.443230000 GHz -38.72 dBm

2.484530000 GHz

1 PK VIEW

Start 2.43 GHz 7 MHz/ Stop 2.5 GHz


FCC §15.247(e) - POWER SPECTRAL DENSITY

Applicable Standard

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

Test Procedure

Test Method: ANSI C63.10-2013 Clause 11.10.2 for BLE
ANSI C63.10-2013 Clause 11.10.5 for Wi-Fi 802.11b/g/n20
ANSI C63.10-2013 Clause 11.10.3 for Wi-Fi 802.11n40



Test Data

Environmental Conditions

Temperature:	25.3~26.4 °C
Relative Humidity:	40~50 %
ATM Pressure:	101.0 kPa

The testing was performed by Gleen Jiang from 2023-02-11 to 2023-02-14.


EUT operation mode: Transmitting

Test Result: Compliant.


BLE

Channel	Frequency (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)
BLE 1M			
Low	2402	-4.75	≤8
Middle	2440	-6.84	≤8
High	2480	-7.44	≤8


Power Spectral Density, Low Channel



Power Spectral Density, Middle Channel




Power Spectral Density, High Channel




2.4G Wi-Fi

Channel	Frequency (MHz)	Reading PSD (dBm/10kHz)	Duty cycle Factor(dB)	PSD (dBm/10kHz)	Limit (dBm/3kHz)
802.11b mode					
Low	2412	-8.36	0.48	-7.88	≤ 8
Middle	2437	-8.78	0.48	-8.30	≤ 8
High	2462	-9.26	0.48	-8.78	≤ 8
802.11g mode					
Low	2412	-12.51	0.49	-12.02	≤ 8
Middle	2437	-12.70	0.49	-12.21	≤ 8
High	2462	-13.13	0.49	-12.64	≤ 8
802.11n-HT20 mode					
Low	2412	-12.74	0.48	-12.26	≤ 8
Middle	2437	-13.10	0.48	-12.62	≤ 8
High	2462	-13.20	0.48	-12.72	≤ 8
802.11n-HT40 mode					
Low	2422	-15.73	0	-15.73	≤ 8
Middle	2437	-15.82	0	-15.82	≤ 8
High	2452	-16.12	0	-16.12	≤ 8


Power Spectral Density, 802.11b Low Channel




Power Spectral Density, 802.11b Middle Channel




Power Spectral Density, 802.11b High Channel




Power Spectral Density, 802.11g Low Channel




Power Spectral Density, 802.11g Middle Channel




Power Spectral Density, 802.11g High Channel




Power Spectral Density, 802.11n-HT20 Low Channel




Power Spectral Density, 802.11n-HT20 Middle Channel




Power Spectral Density, 802.11n-HT20 High Channel




Power Spectral Density, 802.11n-HT40 Low Channel



Power Spectral Density, 802.11n-HT40 Middle Channel



Power Spectral Density, 802.11n-HT40 High Channel



***** END OF REPORT *****