

## LTE Band 12

### MEASUREMENT 1


Low Band SAR (Channel 23060):

Date: 09/27/2023


|                                        |                                                                                           |
|----------------------------------------|-------------------------------------------------------------------------------------------|
| Frequency (MHz)                        | 704.000000                                                                                |
| Relative permittivity (real part)      | 42.126667                                                                                 |
| Relative permittivity (imaginary part) | 23.264000                                                                                 |
| Conductivity (S/m)                     | 0.914404                                                                                  |
| Variation (%)                          | -0.970000                                                                                 |
| Crest Factor                           | 1.0                                                                                       |
| Probe Conversion factor                | 1.71                                                                                      |
| E-Field Probe:                         | SSE2 (SN 25/22 EPG0375)                                                                   |
| Area Scan                              | <u>dx=8mm dy=8mm, h= 5.00 mm</u>                                                          |
| ZoomScan                               | <u>5x5x7,dx=8mm dy=8mm</u><br><u>dz=5mm,Complete/ndx=8mm dy=8mm, h=</u><br><u>5.00 mm</u> |

|                 |                            |
|-----------------|----------------------------|
| Phantom         | <u>Validation plane</u>    |
| Device Position | <u>Body back(0mm)</u>      |
| Band            | <u>LTE band 12(1 RB#0)</u> |

#### SURFACE SAR




#### VOLUME SAR




Maximum location: X=-12.00, Y=16.00 SAR Peak:2.44 W/kg


|                |          |
|----------------|----------|
| SAR 10g (W/Kg) | 0.477371 |
| SAR 1g (W/Kg)  | 0.917043 |



| Z (mm)     | 0.00   | 4.00   | 9.00   | 14.00  | 19.00  |
|------------|--------|--------|--------|--------|--------|
| SAR (W/Kg) | 2.4082 | 1.5666 | 0.9080 | 0.5480 | 0.3616 |



Hot spot position



## MEASUREMENT 2


Low Band SAR (Channel 23060):

Date: 09/27/2023


|                                        |                                                                                             |
|----------------------------------------|---------------------------------------------------------------------------------------------|
| Frequency (MHz)                        | 704.000000                                                                                  |
| Relative permittivity (real part)      | 42.126667                                                                                   |
| Relative permittivity (imaginary part) | 23.264000                                                                                   |
| Conductivity (S/m)                     | 0.914404                                                                                    |
| Variation (%)                          | -1.460000                                                                                   |
| Crest Factor                           | 1.0                                                                                         |
| Probe Conversion factor                | 1.71                                                                                        |
| E-Field Probe:                         | SSE2 (SN 25/22 EPG0375)                                                                     |
| Area Scan                              | <u>dx=8mm dy=8mm, h= 5.00 mm</u>                                                            |
| ZoomScan                               | <u>5x5x7, dx=8mm dy=8mm</u><br><u>dz=5mm, Complete/ndx=8mm dy=8mm, h=</u><br><u>5.00 mm</u> |

|                 |                        |
|-----------------|------------------------|
| Phantom         | Validation plane       |
| Device Position | Body back(hotspot 0mm) |
| Band            | LTE band 12(1 RB#0)    |

### SURFACE SAR




### VOLUME SAR




Maximum location: X=-12.00, Y=16.00 SAR Peak: 2.44W/kg


|                |          |
|----------------|----------|
| SAR 10g (W/Kg) | 0.477785 |
| SAR 1g (W/Kg)  | 0.907850 |



| Z (mm)     | 0.00   | 4.00   | 9.00   | 14.00  | 19.00  |
|------------|--------|--------|--------|--------|--------|
| SAR (W/Kg) | 2.4112 | 1.5678 | 0.9084 | 0.5485 | 0.3627 |



Hot spot position




## LTE Band 41


### MEASUREMENT 1

|                                        |                                                                                           |                  |
|----------------------------------------|-------------------------------------------------------------------------------------------|------------------|
| High Band SAR (Channel 41490):         |                                                                                           | Date: 10/25/2023 |
| Frequency (MHz)                        | 2680.000000                                                                               |                  |
| Relative permittivity (real part)      | 39.009335                                                                                 |                  |
| Relative permittivity (imaginary part) | 13.553667                                                                                 |                  |
| Conductivity (S/m)                     | 1.952481                                                                                  |                  |
| Variation (%)                          | -3.680000                                                                                 |                  |
| Crest Factor                           | 1.0                                                                                       |                  |
| Probe Conversion factor                | 4.36                                                                                      |                  |
| E-Field Probe:                         | SSE2 (SN 25/22 EPG0375)                                                                   |                  |
| Area Scan                              | <u>dx=12mm dy=12mm, h= 5.00 mm</u>                                                        |                  |
| ZoomScan                               | <u>5x5x7,dx=5mm dy=5mm</u><br><u>dz=5mm,Complete/ndx=8mm dy=8mm, h=</u><br><u>5.00 mm</u> |                  |
| Phantom                                | Validation plane                                                                          |                  |
| Device Position                        | Body back(0mm)                                                                            |                  |
| Band                                   | <u>LTE band 41(1 RB#0)</u>                                                                |                  |

#### SURFACE SAR




#### VOLUME SAR




Maximum location: X=-8.00, Y=24.00 SAR Peak: 1.48W/kg


|                |          |
|----------------|----------|
| SAR 10g (W/Kg) | 0.327641 |
| SAR 1g (W/Kg)  | 0.737289 |



| Z (mm)     | 0.00   | 4.00   | 9.00   | 14.00  | 19.00  |
|------------|--------|--------|--------|--------|--------|
| SAR (W/Kg) | 1.4764 | 0.8138 | 0.3601 | 0.1580 | 0.0786 |



Hot spot position



## MEASUREMENT 2


High Band SAR (Channel 41490):

Date: 10/25/2023


|                                        |                                                                                             |
|----------------------------------------|---------------------------------------------------------------------------------------------|
| Frequency (MHz)                        | 2680.000000                                                                                 |
| Relative permittivity (real part)      | 39.009335                                                                                   |
| Relative permittivity (imaginary part) | 13.553667                                                                                   |
| Conductivity (S/m)                     | 1.952481                                                                                    |
| Variation (%)                          | -1.050000                                                                                   |
| Crest Factor                           | 1.0                                                                                         |
| Probe Conversion factor                | 4.36                                                                                        |
| E-Field Probe:                         | SSE2 (SN 25/22 EPG0375)                                                                     |
| Area Scan                              | <u>dx=12mm dy=12mm, h= 5.00 mm</u>                                                          |
| ZoomScan                               | <u>5x5x7, dx=5mm dy=5mm</u><br><u>dz=5mm, Complete/ndx=8mm dy=8mm, h=</u><br><u>5.00 mm</u> |

|                 |                               |
|-----------------|-------------------------------|
| Phantom         | Validation plane              |
| Device Position | <u>Body back(hotspot 0mm)</u> |
| Band            | <u>LTE band 41(1 RB#0)</u>    |

### SURFACE SAR




### VOLUME SAR




Maximum location: X=-8.00, Y=24.00 SAR Peak: 1.45 W/kg


|                |          |
|----------------|----------|
| SAR 10g (W/Kg) | 0.331748 |
| SAR 1g (W/Kg)  | 0.738260 |



| Z (mm)     | 0.00   | 4.00   | 9.00   | 14.00  | 19.00  |
|------------|--------|--------|--------|--------|--------|
| SAR (W/Kg) | 1.4481 | 0.8160 | 0.3736 | 0.1691 | 0.0841 |



Hot spot position



## LTE Band 66


### MEASUREMENT 1

High Band SAR (Channel132572): Date: 09/29/2023


|                                        |                                                                                             |
|----------------------------------------|---------------------------------------------------------------------------------------------|
| Frequency (MHz)                        | 1770.000000                                                                                 |
| Relative permittivity (real part)      | 40.115910                                                                                   |
| Relative permittivity (imaginary part) | 14.136136                                                                                   |
| Conductivity (S/m)                     | 1.360603                                                                                    |
| Variation (%)                          | 0.280000                                                                                    |
| Crest Factor                           | 1.0                                                                                         |
| Probe Conversion factor                | 1.71                                                                                        |
| E-Field Probe:                         | SSE2 (SN 25/22 EPG0375)                                                                     |
| Area Scan                              | <u>dx=8mm dy=8mm, h= 5.00 mm</u>                                                            |
| ZoomScan                               | <u>5x5x7, dx=8mm dy=8mm</u><br><u>dz=5mm, Complete/ndx=8mm dy=8mm, h=</u><br><u>5.00 mm</u> |

|                 |                      |
|-----------------|----------------------|
| Phantom         | Validation plane     |
| Device Position | Body back(0mm)       |
| Band            | LTE band 66(1 RB#99) |

#### SURFACE SAR




#### VOLUME SAR




Maximum location: X=-18.00, Y=-18.00 SAR Peak: 0.63 W/kg


|                |          |
|----------------|----------|
| SAR 10g (W/Kg) | 0.275792 |
| SAR 1g (W/Kg)  | 0.393658 |



| Z (mm)     | 0.00   | 4.00   | 9.00   | 14.00  | 19.00  |
|------------|--------|--------|--------|--------|--------|
| SAR (W/Kg) | 0.6287 | 0.3690 | 0.1845 | 0.0978 | 0.0617 |



## Hot spot position



## MEASUREMENT 2


High Band SAR (Channel132572):

Date: 09/29/2023


|                                        |                                                                                             |
|----------------------------------------|---------------------------------------------------------------------------------------------|
| Frequency (MHz)                        | 1770.000000                                                                                 |
| Relative permittivity (real part)      | 40.115910                                                                                   |
| Relative permittivity (imaginary part) | 14.136136                                                                                   |
| Conductivity (S/m)                     | 1.360603                                                                                    |
| Variation (%)                          | -0.830000                                                                                   |
| Crest Factor                           | 1.0                                                                                         |
| Probe Conversion factor                | 1.71                                                                                        |
| E-Field Probe:                         | SSE2 (SN 25/22 EPG0375)                                                                     |
| Area Scan                              | <u>dx=8mm dy=8mm, h= 5.00 mm</u>                                                            |
| ZoomScan                               | <u>5x5x7, dx=8mm dy=8mm</u><br><u>dz=5mm, Complete/ndx=8mm dy=8mm, h=</u><br><u>5.00 mm</u> |

|                 |                        |
|-----------------|------------------------|
| Phantom         | Validation plane       |
| Device Position | Body back(hotspot 0mm) |
| Band            | LTE band 66(1 RB#99)   |

### SURFACE SAR




### VOLUME SAR




Maximum location: X=-9.00, Y=1.00 SAR Peak: 0.78 W/kg


|                |          |
|----------------|----------|
| SAR 10g (W/Kg) | 0.219906 |
| SAR 1g (W/Kg)  | 0.429674 |



| Z (mm)     | 0.00   | 4.00   | 9.00   | 14.00  | 19.00  |
|------------|--------|--------|--------|--------|--------|
| SAR (W/Kg) | 0.7760 | 0.4616 | 0.2349 | 0.1256 | 0.0781 |



## Hot spot position



## LTE Band 71


### MEASUREMENT 1

Middle Band SAR (Channel 133322):


Date: 09/27/2023

|                                        |                                                                                           |
|----------------------------------------|-------------------------------------------------------------------------------------------|
| Frequency (MHz)                        | 683.000000                                                                                |
| Relative permittivity (real part)      | 42.126667                                                                                 |
| Relative permittivity (imaginary part) | 23.264000                                                                                 |
| Conductivity (S/m)                     | 0.914404                                                                                  |
| Variation (%)                          | -2.160000                                                                                 |
| Crest Factor                           | 1.0                                                                                       |
| Probe Conversion factor                | 4.36                                                                                      |
| E-Field Probe:                         | SSE2 (SN 25/22 EPG0375)                                                                   |
| Area Scan                              | <u>dx=8mm dy=8mm, h= 5.00 mm</u>                                                          |
| ZoomScan                               | <u>5x5x7,dx=8mm dy=8mm</u><br><u>dz=5mm,Complete/ndx=8mm dy=8mm, h=</u><br><u>5.00 mm</u> |
| Phantom                                | Validation plane                                                                          |
| Device Position                        | Body back(0mm)                                                                            |
| Band                                   | <u>LTE band 71(1 RB#99)</u>                                                               |

#### SURFACE SAR




#### VOLUME SAR




Maximum location: X=-12.00, Y=16.00 SAR Peak: 2.46 W/kg


|                |          |
|----------------|----------|
| SAR 10g (W/Kg) | 0.479790 |
| SAR 1g (W/Kg)  | 0.924765 |



| Z (mm)     | 0.00   | 4.00   | 9.00   | 14.00  | 19.00  |
|------------|--------|--------|--------|--------|--------|
| SAR (W/Kg) | 2.4272 | 1.5751 | 0.9101 | 0.5479 | 0.3615 |



Hot spot position




## MEASUREMENT 2

Middle Band SAR (Channel 133322):


Date: 09/27/2023

|                                        |                                                                                           |
|----------------------------------------|-------------------------------------------------------------------------------------------|
| Frequency (MHz)                        | 683.000000                                                                                |
| Relative permittivity (real part)      | 42.126667                                                                                 |
| Relative permittivity (imaginary part) | 23.264000                                                                                 |
| Conductivity (S/m)                     | 0.914404                                                                                  |
| Variation (%)                          | -0.970000                                                                                 |
| Crest Factor                           | 1.0                                                                                       |
| Probe Conversion factor                | 4.36                                                                                      |
| E-Field Probe:                         | SSE2 (SN 25/22 EPG0375)                                                                   |
| Area Scan                              | <u>dx=8mm dy=8mm, h= 5.00 mm</u>                                                          |
| ZoomScan                               | <u>5x5x7,dx=8mm dy=8mm</u><br><u>dz=5mm,Complete/ndx=8mm dy=8mm, h=</u><br><u>5.00 mm</u> |
| Phantom                                | Validation plane                                                                          |
| Device Position                        | Body back(hotspot 0mm)                                                                    |
| Band                                   | <u>LTE band 71(1 RB#99)</u>                                                               |

### SURFACE SAR




### VOLUME SAR




Maximum location: X=-12.00, Y=16.00 SAR Peak: 2.45 W/kg


|                |          |
|----------------|----------|
| SAR 10g (W/Kg) | 0.478632 |
| SAR 1g (W/Kg)  | 0.939769 |



| Z (mm)     | 0.00   | 4.00   | 9.00   | 14.00  | 19.00  |
|------------|--------|--------|--------|--------|--------|
| SAR (W/Kg) | 2.4159 | 1.5693 | 0.9083 | 0.5482 | 0.3629 |



Hot spot position




## WLAN 2.4G


### MEASUREMENT 1

|                                        |                                                                                           |                  |
|----------------------------------------|-------------------------------------------------------------------------------------------|------------------|
| Low Band SAR (Channel 1):              |                                                                                           | Date: 10/19/2023 |
| Frequency (MHz)                        | 2412.000000                                                                               |                  |
| Relative permittivity (real part)      | 39.226002                                                                                 |                  |
| Relative permittivity (imaginary part) | 13.207000                                                                                 |                  |
| Conductivity (S/m)                     | 1.788081                                                                                  |                  |
| Variation (%)                          | 1.340000                                                                                  |                  |
| Crest Factor                           | 1.0                                                                                       |                  |
| Probe Conversion factor                | 2.31                                                                                      |                  |
| E-Field Probe:                         | SSE2 (SN 25/22 EPG0375)                                                                   |                  |
| Area Scan                              | <u>dx=12mm dy=12mm, h= 5.00 mm</u>                                                        |                  |
| ZoomScan                               | <u>5x5x7,dx=5mm dy=5mm</u><br><u>dz=5mm,Complete/ndx=8mm dy=8mm, h=</u><br><u>5.00 mm</u> |                  |
| Phantom                                | Validation plane                                                                          |                  |
| Device Position                        | Body back(0mm)                                                                            |                  |
| Band                                   | IEEE 802.11b ISM                                                                          |                  |

#### SURFACE SAR




#### VOLUME SAR




Maximum location: X=1.00, Y=23.00 SAR Peak: 0.44 W/kg


|                |          |
|----------------|----------|
| SAR 10g (W/Kg) | 0.165423 |
| SAR 1g (W/Kg)  | 0.273691 |



| Z (mm)     | 0.00   | 4.00   | 9.00   | 14.00  | 19.00  |
|------------|--------|--------|--------|--------|--------|
| SAR (W/Kg) | 0.4497 | 0.1577 | 0.0368 | 0.0175 | 0.0072 |



Hot spot position




## MEASUREMENT 2

Low Band SAR (Channel 1):


Date: 10/19/2023

|                                        |                                                                                           |
|----------------------------------------|-------------------------------------------------------------------------------------------|
| Frequency (MHz)                        | 2412.000000                                                                               |
| Relative permittivity (real part)      | 39.226002                                                                                 |
| Relative permittivity (imaginary part) | 13.207000                                                                                 |
| Conductivity (S/m)                     | 1.788081                                                                                  |
| Variation (%)                          | -1.380000                                                                                 |
| Crest Factor                           | 1.0                                                                                       |
| Probe Conversion factor                | 2.31                                                                                      |
| E-Field Probe:                         | SSE2 (SN 25/22 EPG0375)                                                                   |
| Area Scan                              | <u>dx=12mm dy=12mm, h= 5.00 mm</u>                                                        |
| ZoomScan                               | <u>5x5x7,dx=5mm dy=5mm</u><br><u>dz=5mm,Complete/ndx=8mm dy=8mm, h=</u><br><u>5.00 mm</u> |
| Phantom                                | Validation plane                                                                          |
| Device Position                        | Body back(0mm)                                                                            |
| Band                                   | <u>IEEE 802.11b ISM(hotspot)</u>                                                          |

### SURFACE SAR




### VOLUME SAR




Maximum location: X=-15.00, Y=58.00 SAR Peak: 0.57 W/kg


|                |          |
|----------------|----------|
| SAR 10g (W/Kg) | 0.187182 |
| SAR 1g (W/Kg)  | 0.283788 |



| Z (mm)     | 0.00   | 4.00   | 9.00   | 14.00  | 19.00  |
|------------|--------|--------|--------|--------|--------|
| SAR (W/Kg) | 0.3732 | 0.2107 | 0.0935 | 0.0368 | 0.0124 |



Hot spot position



## WLAN 5.2G


### MEASUREMENT 1

SAR (Channel 40):


Date: 10/29/2023

|                                        |                                                                                           |
|----------------------------------------|-------------------------------------------------------------------------------------------|
| Frequency (MHz)                        | 5200.000000                                                                               |
| Relative permittivity (real part)      | 35.068832                                                                                 |
| Relative permittivity (imaginary part) | 13.679428                                                                                 |
| Conductivity (S/m)                     | 5.220788                                                                                  |
| Variation (%)                          | -1.180000                                                                                 |
| Crest Factor                           | 1.0                                                                                       |
| Probe Conversion factor                | 2.01                                                                                      |
| E-Field Probe:                         | SSE2 (SN 25/22 EPG0375)                                                                   |
| Area Scan                              | <u>dx=4mm dy=4mm, h= 2.00 mm</u>                                                          |
| ZoomScan                               | <u>5x5x7,dx=8mm dy=8mm</u><br><u>dz=5mm,Complete/ndx=8mm dy=8mm, h=</u><br><u>5.00 mm</u> |
| Phantom                                | Validation plane                                                                          |
| Device Position                        | Body back(0mm)                                                                            |
| Band                                   | IEEE 802.11a                                                                              |

#### SURFACE SAR




#### VOLUME SAR




Maximum location: X=16.00, Y=63.00 SAR Peak: 0.30 W/kg


|                |          |
|----------------|----------|
| SAR 10g (W/Kg) | 0.140642 |
| SAR 1g (W/Kg)  | 0.168531 |



| Z (mm)     | 0.00   | 4.00   | 9.00   | 14.00  | 19.00  |
|------------|--------|--------|--------|--------|--------|
| SAR (W/Kg) | 0.3372 | 0.1876 | 0.0816 | 0.0317 | 0.0109 |



Hot spot position




## MEASUREMENT 2

SAR (Channel 40):


Date: 10/29/2023

|                                        |                                                                                           |
|----------------------------------------|-------------------------------------------------------------------------------------------|
| Frequency (MHz)                        | 5200.000000                                                                               |
| Relative permittivity (real part)      | 35.068832                                                                                 |
| Relative permittivity (imaginary part) | 13.679428                                                                                 |
| Conductivity (S/m)                     | 5.220788                                                                                  |
| Variation (%)                          | -0.510000                                                                                 |
| Crest Factor                           | 1.0                                                                                       |
| Probe Conversion factor                | 2.01                                                                                      |
| E-Field Probe:                         | SSE2 (SN 25/22 EPG0375)                                                                   |
| Area Scan                              | <u>dx=4mm dy=4mm, h= 2.00 mm</u>                                                          |
| ZoomScan                               | <u>5x5x7,dx=8mm dy=8mm</u><br><u>dz=5mm,Complete/ndx=8mm dy=8mm, h=</u><br><u>5.00 mm</u> |
| Phantom                                | Validation plane                                                                          |
| Device Position                        | Body back(hotspot 0mm)                                                                    |
| Band                                   | <u>IEEE 802.11a</u>                                                                       |

### SURFACE SAR




### VOLUME SAR




Maximum location: X=19.00, Y=-12.00 SAR Peak: 0.34 W/kg


|                |          |
|----------------|----------|
| SAR 10g (W/Kg) | 0.151431 |
| SAR 1g (W/Kg)  | 0.205420 |



| Z (mm)     | 0.00   | 4.00   | 9.00   | 14.00  | 19.00  |
|------------|--------|--------|--------|--------|--------|
| SAR (W/Kg) | 0.3397 | 0.1890 | 0.0823 | 0.0317 | 0.0117 |



Hot spot position




## WLAN 5.8G


### MEASUREMENT 1

|                                        |                                                                   |                  |
|----------------------------------------|-------------------------------------------------------------------|------------------|
| SAR (Channel 159):                     |                                                                   | Date: 11/01/2023 |
| Frequency (MHz)                        | 5795.000000                                                       |                  |
| Relative permittivity (real part)      | 38.352823                                                         |                  |
| Relative permittivity (imaginary part) | 13.671675                                                         |                  |
| Conductivity (S/m)                     | 5.430828                                                          |                  |
| Variation (%)                          | -1.620000                                                         |                  |
| Crest Factor                           | 1.0                                                               |                  |
| Probe Conversion factor                | 2.13                                                              |                  |
| E-Field Probe:                         | SSE2 (SN 25/22 EPG0375)                                           |                  |
| Area Scan                              | dx=4mm dy=4mm, h= 2.00 mm                                         |                  |
| ZoomScan                               | 5x5x7,dx=8mm dy=8mm<br>dz=5mm,Complete/ndx=8mm dy=8mm, h= 5.00 mm |                  |
| Phantom                                | Validation plane                                                  |                  |
| Device Position                        | Body back(0mm)                                                    |                  |
| Band                                   | IEEE 802.11ac VHT40                                               |                  |

#### SURFACE SAR



#### VOLUME SAR




Maximum location: X=15.00, Y=60.00 SAR Peak: 0.34 W/kg

SAR 10g (W/Kg)


0.101431

SAR 1g (W/Kg)


0.195420



| Z (mm)     | 0.00   | 4.00   | 9.00   | 14.00  | 19.00  |
|------------|--------|--------|--------|--------|--------|
| SAR (W/Kg) | 0.3410 | 0.1901 | 0.0791 | 0.0327 | 0.0109 |



Hot spot position




## MEASUREMENT 2

SAR (Channel 159):


Date: 11/01/2023

|                                        |                                                                                           |
|----------------------------------------|-------------------------------------------------------------------------------------------|
| Frequency (MHz)                        | 5795.000000                                                                               |
| Relative permittivity (real part)      | 38.352823                                                                                 |
| Relative permittivity (imaginary part) | 13.671675                                                                                 |
| Conductivity (S/m)                     | 5.430828                                                                                  |
| Variation (%)                          | 1.950000                                                                                  |
| Crest Factor                           | 1.0                                                                                       |
| Probe Conversion factor                | 2.13                                                                                      |
| E-Field Probe:                         | SSE2 (SN 25/22 EPG0375)                                                                   |
| Area Scan                              | <u>dx=4mm dy=4mm, h= 2.00 mm</u>                                                          |
| ZoomScan                               | <u>5x5x7,dx=8mm dy=8mm</u><br><u>dz=5mm,Complete/ndx=8mm dy=8mm, h=</u><br><u>5.00 mm</u> |
| Phantom                                | <u>Validation plane</u>                                                                   |
| Device Position                        | <u>Body back(0mm)</u>                                                                     |
| Band                                   | <u>IEEE 802.11ac HT40(hotspot)</u>                                                        |

### SURFACE SAR




### VOLUME SAR




Maximum location: X=19.00, Y=-12.00 SAR Peak: 0.69 W/kg


|                |          |
|----------------|----------|
| SAR 10g (W/Kg) | 0.163397 |
| SAR 1g (W/Kg)  | 0.242473 |



| Z (mm)     | 0.00   | 4.00   | 9.00   | 14.00  | 19.00  |
|------------|--------|--------|--------|--------|--------|
| SAR (W/Kg) | 0.6971 | 0.3951 | 0.1904 | 0.0694 | 0.0381 |



Hot spot position



BT


## MEASUREMENT 1

Middle Band SAR (Channel 39):


Date: 10/19/2023

|                                        |                                                                                           |
|----------------------------------------|-------------------------------------------------------------------------------------------|
| Frequency (MHz)                        | 2441.000000                                                                               |
| Relative permittivity (real part)      | 39.217999                                                                                 |
| Relative permittivity (imaginary part) | 13.211000                                                                                 |
| Conductivity (S/m)                     | 1.791558                                                                                  |
| Variation (%)                          | 0.420000                                                                                  |
| Crest Factor                           | 1.0                                                                                       |
| Probe Conversion factor                | 2.31                                                                                      |
| E-Field Probe:                         | SSE2 (SN 25/22 EPG0375)                                                                   |
| Area Scan                              | <u>dx=12mm dy=12mm, h= 5.00 mm</u>                                                        |
| ZoomScan                               | <u>5x5x7,dx=5mm dy=5mm</u><br><u>dz=5mm,Complete/ndx=8mm dy=8mm, h=</u><br><u>5.00 mm</u> |
| Phantom                                | Validation plane                                                                          |
| Device Position                        | Body back(0mm)                                                                            |
| Band                                   | <u>8DPSK</u>                                                                              |

### SURFACE SAR




### VOLUME SAR




Maximum location: X=-29.00, Y=6.00 SAR Peak: 0.22 W/kg


|                |          |
|----------------|----------|
| SAR 10g (W/Kg) | 0.058107 |
| SAR 1g (W/Kg)  | 0.098117 |





| Z (mm)     | 0.00   | 4.00   | 9.00   | 14.00  | 19.00  |
|------------|--------|--------|--------|--------|--------|
| SAR (W/Kg) | 0.2186 | 0.1441 | 0.0851 | 0.0523 | 0.0350 |



Hot spot position



## Appendix A: EUT Photos



## Liquid depth



The Body Liquid of 835MHz (15.4cm)



The Body Liquid of 1800MHz (15.2 cm)



The Body Liquid of 1900MHz (16.4 cm)



The Body Liquid of 2450MHz (15.3cm)



The Body Liquid of 2600MHz (16.5cm)

The Body Liquid of 5000-6000MHz (16.5cm)




The Body Liquid of 750MHz (15.4cm)



The Head Liquid of 1900MHz (15.5cm)




The Head Liquid of 2450MHz (15.6cm)



The Head Liquid of 835MHz (15.3cm)




The Head Liquid of 1800MHz (15.2cm)



The Head Liquid of 2600MHz (15.1cm)



The Body Liquid of 5000-6000MHz MHz (15.8cm)




The Head Liquid of 750MHz (15.4cm)


## Appendix B: Test Setup Photos




Body worn – Front (0mm)



Body worn – Back (0mm)



Body worn – Top (0mm)



Hotspo Top (0mm)



Hotspo Front (0mm)



Hotspo Back (0mm)

## Appendix C: Probe Calibration Certificate

COMOSAR E-FIELD Probe



### COMOSAR E-Field Probe Calibration Report

Ref : ACR.180.7.22.BES.B

**SHENZHEN TONGCE TESTING LAB**  
**2101 & 2201, ZHENCHANG FACTORY RENSHAN INDUSTRIAL**  
**ZONE, FUHAI SUBDISTRICT, BAO'AN DISTRICT SHENZHEN,**  
**GUANGDONG, 518103, PEOPLE'S REPUBLIC OF CHINA**  
**MVG COMOSAR DOSIMETRIC E-FIELD PROBE**  
**SERIAL NO.: SN 25/22 EPG0375**

**Calibrated at MVG**  
**Z.I. de la pointe du diable**  
**Technopôle Brest Iroise – 295 avenue Alexis de Rochon**  
**29280 PLOUZANE - FRANCE**

**Calibration date: 06/29/2023**



Accreditations #2-6789  
Scope available on [www.cofrac.fr](http://www.cofrac.fr)

**The use of the Cofrac brand and the accreditation references is prohibited from any reproduction.**

#### Summary:

This document presents the method and results from an accredited COMOSAR Dosimetric E-Field Probe calibration performed at MVG, using the CALIPROBE test bench, for use with a MVG COMOSAR system only. The test results covered by accreditation are traceable to the International System of Units (SI).



## COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref: ACR.180.7.22.BES.B

|                                   | <i>Name</i>    | <i>Function</i>         | <i>Date</i> | <i>Signature</i> |
|-----------------------------------|----------------|-------------------------|-------------|------------------|
| <i>Prepared by :</i>              | Jérôme Le Gall | Measurement Responsible | 6/30/2023   |                  |
| <i>Checked &amp; approved by:</i> | Jérôme Luc     | Technical Manager       | 6/30/2023   |                  |
| <i>Authorized by:</i>             | Yann Toutain   | Laboratory Director     | 7/05/2023   |                  |

|                       | <i>Customer Name</i>        |
|-----------------------|-----------------------------|
| <i>Distribution :</i> | Shenzhen Tongce Testing Lab |

| <i>Issue</i> | <i>Name</i>    | <i>Date</i> | <i>Modifications</i> |
|--------------|----------------|-------------|----------------------|
| A            | Jérôme Le Gall | 6/30/2023   | Initial release      |
|              |                |             |                      |
|              |                |             |                      |
|              |                |             |                      |

Page: 2/11

**Template\_ACR.DDD.N.YY.MVGB.ISSUE\_COMOSAR Probe vK**

*This document shall not be reproduced, except in full or in part, without the written approval of MVG. The information contained herein is to be used only for the purpose for which it is submitted and is not to be released in whole or part without written approval of MVG.*

Page 146 of 244



COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref: ACR.180.7.22.BES.B

TABLE OF CONTENTS

|     |                                       |    |
|-----|---------------------------------------|----|
| 1   | Device Under Test .....               | 4  |
| 2   | Product Description .....             | 4  |
| 2.1 | General Information .....             | 4  |
| 3   | Measurement Method .....              | 4  |
| 3.1 | Linearity .....                       | 4  |
| 3.2 | Sensitivity .....                     | 4  |
| 3.3 | Lower Detection Limit .....           | 5  |
| 3.4 | Isotropy .....                        | 5  |
| 3.1 | Boundary Effect .....                 | 5  |
| 4   | Measurement Uncertainty .....         | 6  |
| 5   | Calibration Measurement Results ..... | 6  |
| 5.1 | Sensitivity in air .....              | 6  |
| 5.2 | Linearity .....                       | 7  |
| 5.3 | Sensitivity in liquid .....           | 8  |
| 5.4 | Isotropy .....                        | 9  |
| 6   | List of Equipment .....               | 10 |



## COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref: ACR.180.7.22.BES.B

### 1 DEVICE UNDER TEST

| Device Under Test                        |                                                                         |
|------------------------------------------|-------------------------------------------------------------------------|
| Device Type                              | COMOSAR DOSIMETRIC E FIELD PROBE                                        |
| Manufacturer                             | MVG                                                                     |
| Model                                    | SSE2                                                                    |
| Serial Number                            | SN 25/22 EPGO375                                                        |
| Product Condition (new / used)           | New                                                                     |
| Frequency Range of Probe                 | 0.15 GHz-6GHz                                                           |
| Resistance of Three Dipoles at Connector | Dipole 1: R1=0.197 MΩ<br>Dipole 2: R2=0.230 MΩ<br>Dipole 3: R3=0.208 MΩ |

### 2 PRODUCT DESCRIPTION

#### 2.1 GENERAL INFORMATION

MVG's COMOSAR E field Probes are built in accordance to the IEC/IEEE 62209-1528 and FCC KDB865664 D01 standards.



Figure 1 – MVG COMOSAR Dosimetric E field Probe

|                                            |        |
|--------------------------------------------|--------|
| Probe Length                               | 330 mm |
| Length of Individual Dipoles               | 2 mm   |
| Maximum external diameter                  | 8 mm   |
| Probe Tip External Diameter                | 2.5 mm |
| Distance between dipoles / probe extremity | 1 mm   |

### 3 MEASUREMENT METHOD

The IEC/IEEE 62209-1528 and FCC KDB865664 D01 standards provide recommended practices for the probe calibrations, including the performance characteristics of interest and methods by which to assess their affect. All calibrations / measurements performed meet the fore mentioned standards.

#### 3.1 LINEARITY

The evaluation of the linearity was done in free space using the waveguide, performing a power sweep to cover the SAR range 0.01W/kg to 100W/kg.

#### 3.2 SENSITIVITY

The sensitivity factors of the three dipoles were determined using a two step calibration method (air and tissue simulating liquid) using waveguides as outlined in the standards.

Page: 4/11

Template\_ACR.DDD.N.YY.MVGB.ISSUE\_COMOSAR Probe vK

This document shall not be reproduced, except in full or in part, without the written approval of MVG. The information contained herein is to be used only for the purpose for which it is submitted and is not to be released in whole or part without written approval of MVG.



### 3.3 LOWER DETECTION LIMIT

The lower detection limit was assessed using the same measurement set up as used for the linearity measurement. The required lower detection limit is 10 mW/kg.

### 3.4 ISOTROPY

The axial isotropy was evaluated by exposing the probe to a reference wave from a standard dipole with the dipole mounted under the flat phantom in the test configuration suggested for system validations and checks. The probe was rotated along its main axis from 0 to 360 degrees in 15-degree steps. The hemispherical isotropy is determined by inserting the probe in a thin plastic box filled with tissue-equivalent liquid, with the plastic box illuminated with the fields from a half wave dipole. The dipole is rotated about its axis (0°–180°) in 15° increments. At each step the probe is rotated about its axis (0°–360°).

### 3.1 BOUNDARY EFFECT

The boundary effect is defined as the deviation between the SAR measured data and the expected exponential decay in the liquid when the probe is oriented normal to the interface. To evaluate this effect, the liquid filled flat phantom is exposed to fields from either a reference dipole or waveguide. With the probe normal to the phantom surface, the peak spatial average SAR is measured and compared to the analytical value at the surface.

The boundary effect uncertainty can be estimated according to the following uncertainty approximation formula based on linear and exponential extrapolations between the surface and  $d_{be} + d_{step}$  along lines that are approximately normal to the surface:

$$SAR_{uncertainty} [\%] = \Delta SAR_{be} \frac{(d_{be} + d_{step})^2}{2d_{step}} \frac{(e^{-d_{be}/\delta} - e^{-(d_{be} + d_{step})/\delta})}{\delta/2} \quad \text{for } (d_{be} + d_{step}) < 10 \text{ mm}$$

where

|                     |                                                                                                                                                                                                      |
|---------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| $SAR_{uncertainty}$ | is the uncertainty in percent of the probe boundary effect                                                                                                                                           |
| $d_{be}$            | is the distance between the surface and the closest <i>zoom-scan</i> measurement point, in millimetre                                                                                                |
| $\Delta_{step}$     | is the separation distance between the first and second measurement points that are closest to the phantom surface, in millimetre, assuming the boundary effect at the second location is negligible |
| $\delta$            | is the minimum penetration depth in millimetres of the head tissue-equivalent liquids defined in this standard, i.e., $\delta \approx 14$ mm at 3 GHz;                                               |
| $\Delta SAR_{be}$   | in percent of SAR is the deviation between the measured SAR value, at the distance $d_{be}$ from the boundary, and the analytical SAR value.                                                         |

The measured worst case boundary effect SAR uncertainty[%] for scanning distances larger than 4mm is 1.0% Limit ,2%).



#### 4 MEASUREMENT UNCERTAINTY

The guidelines outlined in the IEC/IEEE 62209-1528 and FCC KDB865664 D01 standards were followed to generate the measurement uncertainty associated with an E-field probe calibration using the waveguide technique. All uncertainties listed below represent an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2, traceable to the Internationally Accepted Guides to Measurement Uncertainty.

| Uncertainty analysis of the probe calibration in waveguide |                       |                          |         |    |                          |
|------------------------------------------------------------|-----------------------|--------------------------|---------|----|--------------------------|
| ERROR SOURCES                                              | Uncertainty value (%) | Probability Distribution | Divisor | ci | Standard Uncertainty (%) |
| Expanded uncertainty<br>95 % confidence level k = 2        |                       |                          |         |    | 14 %                     |

#### 5 CALIBRATION MEASUREMENT RESULTS

| Calibration Parameters |             |
|------------------------|-------------|
| Liquid Temperature     | 20 +/- 1 °C |
| Lab Temperature        | 20 +/- 1 °C |
| Lab Humidity           | 30-70 %     |

##### 5.1 SENSITIVITY IN AIR

|                                                           |                                                           |                                                           |
|-----------------------------------------------------------|-----------------------------------------------------------|-----------------------------------------------------------|
| Normx dipole<br>1 ( $\mu\text{V}/(\text{V}/\text{m})^2$ ) | Normy dipole<br>2 ( $\mu\text{V}/(\text{V}/\text{m})^2$ ) | Normz dipole<br>3 ( $\mu\text{V}/(\text{V}/\text{m})^2$ ) |
| 0.64                                                      | 0.53                                                      | 0.44                                                      |

|                      |                      |                      |
|----------------------|----------------------|----------------------|
| DCP dipole 1<br>(mV) | DCP dipole 2<br>(mV) | DCP dipole 3<br>(mV) |
| 106                  | 108                  | 109                  |

Calibration curves  $e_i=f(V)$  ( $i=1,2,3$ ) allow to obtain E-field value using the formula:


$$E = \sqrt{E_1^2 + E_2^2 + E_3^2}$$



## COMOSAR E-FIELD PROBE CALIBRATION REPORT


Ref: ACR.180.7.22.BES.B

### Calibration curves



### 5.2 LINEARITY

#### Linearity



Linearity: +/-1.94% (+/-0.09dB)



COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref: ACR.180.7.22.BES.B

5.3 SENSITIVITY IN LIQUID

| <u>Liquid</u> | <u>Frequency<br/>(MHz +/-<br/>100MHz)</u> | <u>ConvF</u> |
|---------------|-------------------------------------------|--------------|
| HL750         | 750                                       | 1.71         |
| BL750         | 750                                       | 1.78         |
| HL900         | 900                                       | 1.91         |
| BL900         | 900                                       | 1.96         |
| HL1800        | 1800                                      | 2.08         |
| BL1800        | 1800                                      | 2.16         |
| HL2000        | 2000                                      | 2.03         |
| BL2000        | 2000                                      | 2.10         |
| HL2450        | 2450                                      | 2.31         |
| BL2450        | 2450                                      | 2.37         |
| HL2600        | 2600                                      | 2.16         |
| BL2600        | 2600                                      | 2.23         |
| HL3500        | 3500                                      | 2.21         |
| BL3500        | 3500                                      | 2.28         |
| HL3700        | 3700                                      | 3.45         |
| BL3700        | 3700                                      | 3.15         |
| HL4600        | 4600                                      | 3.30         |
| BL4600        | 4600                                      | 3.70         |
| HL5200        | 5200                                      | 2.01         |
| BL5200        | 5200                                      | 2.08         |
| HL5600        | 5600                                      | 2.07         |
| BL5600        | 5600                                      | 2.12         |
| HL5800        | 5800                                      | 2.06         |
| BL5800        | 5800                                      | 2.13         |

LOWER DETECTION LIMIT: 7mW/kg




COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref: ACR.180.7.22.BES.B

5.4 ISOTROPY

HL1800 MHz





## COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref: ACR.180.7.22.BES.B

### 6 LIST OF EQUIPMENT

| Equipment Summary Sheet            |                      |                         |                                               |                                               |
|------------------------------------|----------------------|-------------------------|-----------------------------------------------|-----------------------------------------------|
| Equipment Description              | Manufacturer / Model | Identification No.      | Current Calibration Date                      | Next Calibration Date                         |
| CALIPROBE Test Bench               | Version 2            | NA                      | Validated. No cal required.                   | Validated. No cal required.                   |
| Network Analyzer                   | Rohde & Schwarz ZVM  | 100203                  | 08/2021                                       | 08/2024                                       |
| Network Analyzer                   | Agilent 8753ES       | MY40003210              | 10/2023                                       | 10/2026                                       |
| Network Analyzer – Calibration kit | HP 85033D            | 3423A08186              | 06/2021                                       | 06/2027                                       |
| Multimeter                         | Keithley 2000        | 1160271                 | 02/2023                                       | 02/2026                                       |
| Signal Generator                   | Rohde & Schwarz SMB  | 106589                  | 03/2022                                       | 03/2025                                       |
| Amplifier                          | MVG                  | MODU-023-C-0002         | Characterized prior to test. No cal required. | Characterized prior to test. No cal required. |
| Power Meter                        | NI-USB 5680          | 170100013               | 06/2021                                       | 06/2024                                       |
| Power Meter                        | Rohde & Schwarz NRVD | 832839-056              | 11/2023                                       | 11/2026                                       |
| Directional Coupler                | Krytar 158020        | 131467                  | Characterized prior to test. No cal required. | Characterized prior to test. No cal required. |
| Waveguide                          | MVG                  | SN 32/16 WG4_1          | Validated. No cal required.                   | Validated. No cal required.                   |
| Liquid transition                  | MVG                  | SN 32/16 WGLIQ_0G900_1  | Validated. No cal required.                   | Validated. No cal required.                   |
| Waveguide                          | MVG                  | SN 32/16 WG6_1          | Validated. No cal required.                   | Validated. No cal required.                   |
| Liquid transition                  | MVG                  | SN 32/16 WGLIQ_1G500_1  | Validated. No cal required.                   | Validated. No cal required.                   |
| Waveguide                          | MVG                  | SN 32/16 WG8_1          | Validated. No cal required.                   | Validated. No cal required.                   |
| Liquid transition                  | MVG                  | SN 32/16 WGLIQ_1G800B_1 | Validated. No cal required.                   | Validated. No cal required.                   |
| Liquid transition                  | MVG                  | SN 32/16 WGLIQ_1G800H_1 | Validated. No cal required.                   | Validated. No cal required.                   |
| Waveguide                          | MVG                  | SN 32/16 WG10_1         | Validated. No cal required.                   | Validated. No cal required.                   |
| Liquid transition                  | MVG                  | SN 32/16 WGLIQ_3G500_1  | Validated. No cal required.                   | Validated. No cal required.                   |
| Waveguide                          | MVG                  | SN 32/16 WG12_1         | Validated. No cal required.                   | Validated. No cal required.                   |

Page: 10/11

**Template\_ACR.DDD.N.YY.MVGB.ISSUE\_COMOSAR Probe vK**

This document shall not be reproduced, except in full or in part, without the written approval of MVG. The information contained herein is to be used only for the purpose for which it is submitted and is not to be released in whole or part without written approval of MVG.



COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref: ACR.180.7.22.BES.B

|                                  |              |                           |                                |                                |
|----------------------------------|--------------|---------------------------|--------------------------------|--------------------------------|
| Liquid transition                | MVG          | SN 32/16<br>WGLIQ_5G000_1 | Validated. No cal<br>required. | Validated. No cal<br>required. |
| Temperature / Humidity<br>Sensor | Testo 184 H1 | 44225320                  | 06/2021                        | 06/2024                        |



## Dielectric Probe Calibration Report

Ref : ACR.138.4.33.SATU.A

**SHENZHEN TONGCE TESTING LAB**  
**2101&2201, ZHENCHANG FACTORY, RENSHAN**  
**INDUSTRIAL ZONE, FUHAI SUBDISTRICT, BAOAN**  
**DISTRICT, SHENZHEN, GUANGDONG, 518103,**  
**PEOPLES REPUBLIC OF CHINA**  
**MVG COMOSAR DOSIMETRIC E-FIELD PROBE**  
**FREQUENCY: 0.3-6 GHZ**  
**SERIAL NO.: SN 19/15 OCPG 71**

**Calibrated at MVG US**  
**2105 Barrett Park Dr. - Kennesaw, GA 30144**



**Calibration Date: 06/05/2021**

### *Summary:*

This document presents the method and results from an accredited Dielectric Probe calibration performed in MVG USA using the LIMESAR test bench. All calibration results are traceable to national metrology institutions.



## SAR DIELECTRIC PROBE CALIBRATION REPORT

Ref: ACR.138.4.33..SATUA

|               | Name          | Function        | Date       | Signature            |
|---------------|---------------|-----------------|------------|----------------------|
| Prepared by : | Jérôme LUC    | Product Manager | 06/05/2021 | <i>JS</i>            |
| Checked by :  | Jérôme LUC    | Product Manager | 06/05/2021 | <i>JS</i>            |
| Approved by : | Kim RUTKOWSKI | Quality Manager | 06/05/2021 | <i>Kim Rutkowski</i> |

|                | Customer Name                  |
|----------------|--------------------------------|
| Distribution : | SHENZHEN TONGCE<br>TESTING LAB |

| Issue | Date       | Modifications   |
|-------|------------|-----------------|
| A     | 06/05/2021 | Initial release |
|       |            |                 |
|       |            |                 |
|       |            |                 |

Page: 2/7

This document shall not be reproduced, except in full or in part, without the written approval of MVG.  
The information contained herein is to be used only for the purpose for which it is submitted and is not to be released in whole or part without written approval of MVG.

Page 157 of 244



SAR DIELECTRIC PROBE CALIBRATION REPORT

Ref: ACR.138.4.33..SATU.A

TABLE OF CONTENTS

|     |                                           |   |
|-----|-------------------------------------------|---|
| 1   | Introduction.....                         | 4 |
| 2   | Device Under Test .....                   | 4 |
| 3   | Product Description .....                 | 4 |
| 3.1 | General Information .....                 | 4 |
| 4   | Measurement Method .....                  | 5 |
| 4.1 | Liquid Permittivity Measurements .....    | 5 |
| 5   | Measurement Uncertainty .....             | 5 |
| 5.1 | Dielectric Permittivity Measurement ..... | 5 |
| 6   | Calibration Measurement Results .....     | 6 |
| 6.1 | Liquid Permittivity Measurement .....     | 6 |
| 7   | List of Equipment .....                   | 7 |

Page: 3/7

*This document shall not be reproduced, except in full or in part, without the written approval of MVG.  
The information contained herein is to be used only for the purpose for which it is submitted and is not to  
be released in whole or part without written approval of MVG.*

Page 158 of 244



## SAR DIELECTRIC PROBE CALIBRATION REPORT

Ref: ACR.138.4.33..SATU.A

## 1 INTRODUCTION

This document contains a summary of the suggested methods and requirements set forth by the IEEE 1528 and CEI/IEC 62209 standards for liquid permittivity measurements and the measurements that were performed to verify that the product complies with the fore mentioned standards.

## 2 DEVICE UNDER TEST

| Device Under Test              |                          |
|--------------------------------|--------------------------|
| Device Type                    | LIMESAR DIELECTRIC PROBE |
| Manufacturer                   | MVG                      |
| Model                          | SCLMP                    |
| Serial Number                  | SN 19/15 OCPG 71         |
| Product Condition (new / used) | Used                     |

A yearly calibration interval is recommended.

## 3 PRODUCT DESCRIPTION

### 3.1 GENERAL INFORMATION

MVG's Dielectric Probes are built in accordance to the IEEE 1528 and CEI/IEC 62209 standards. The product is designed for use with the LIMESAR test bench only.



Figure 1 – MVG LIMESAR Dielectric Probe

Page: 4/7

*This document shall not be reproduced, except in full or in part, without the written approval of MVG.  
The information contained herein is to be used only for the purpose for which it is submitted and is not to be released in whole or part without written approval of MVG.*



#### 4 MEASUREMENT METHOD

The IEEE 1528, OET 65 Bulletin C and CEI/IEC 62209-1 & 2 standards outline techniques for dielectric property measurements. The LIMESAR test bench employs one of the methods outlined in the standards, using a contact probe or open-ended coaxial transmission-line probe and vector network analyzer. The standards recommend the measurement of two reference materials that have well established and stable dielectric properties to validate the system, one for the calibration and one for checking the calibration. The LIMESAR test bench uses De-ionized water as the reference for the calibration and either DMS or Methanol as the reference for checking the calibration. The following measurements were performed to verify that the product complies with the fore mentioned standards.

##### 4.1 LIQUID PERMITTIVITY MEASUREMENTS

The permittivity of a liquid with well established dielectric properties was measured and the measurement results compared to the values provided in the fore mentioned standards.

#### 5 MEASUREMENT UNCERTAINTY

All uncertainties listed below represent an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2, traceable to the Internationally Accepted Guides to Measurement Uncertainty.

##### 5.1 DIELECTRIC PERMITTIVITY MEASUREMENT

The following uncertainties apply to the Dielectric Permittivity measurement:

| Uncertainty analysis of Permittivity Measurement      |                           |                          |            |    |                              |
|-------------------------------------------------------|---------------------------|--------------------------|------------|----|------------------------------|
| ERROR SOURCES                                         | Uncertainty value (+/- %) | Probability Distribution | Divisor    | ci | Standard Uncertainty (+/- %) |
| Repeatability (n repeats, mid-band)                   | 4.00%                     | N                        | 1          | 1  | 4.000%                       |
| Deviation from reference liquid                       | 5.00%                     | R                        | $\sqrt{3}$ | 1  | 2.887%                       |
| Network analyser-drift, linearity                     | 2.00%                     | R                        | $\sqrt{3}$ | 1  | 1.155%                       |
| Test-port cable variations                            | 0.00%                     | U                        | $\sqrt{2}$ | 1  | 0.000%                       |
| Combined standard uncertainty                         |                           |                          |            |    | 5.066%                       |
| Expanded uncertainty (confidence level of 95%, k = 2) |                           |                          |            |    | 10.0%                        |

| Uncertainty analysis of Conductivity Measurement      |                           |                          |            |    |                              |
|-------------------------------------------------------|---------------------------|--------------------------|------------|----|------------------------------|
| ERROR SOURCES                                         | Uncertainty value (+/- %) | Probability Distribution | Divisor    | ci | Standard Uncertainty (+/- %) |
| Repeatability (n repeats, mid-band)                   | 3.50%                     | N                        | 1          | 1  | 3.500%                       |
| Deviation from reference liquid                       | 3.00%                     | R                        | $\sqrt{3}$ | 1  | 1.732%                       |
| Network analyser-drift, linearity                     | 2.00%                     | R                        | $\sqrt{3}$ | 1  | 1.155%                       |
| Test-port cable variations                            | 0.00%                     | U                        | $\sqrt{2}$ | 1  | 0.000%                       |
| Combined standard uncertainty                         |                           |                          |            |    | 4.072%                       |
| Expanded uncertainty (confidence level of 95%, k = 2) |                           |                          |            |    | 8.1%                         |

Page: 5/7

*This document shall not be reproduced, except in full or in part, without the written approval of MVG.  
The information contained herein is to be used only for the purpose for which it is submitted and is not to be released in whole or part without written approval of MVG.*



SAR DIELECTRIC PROBE CALIBRATION REPORT

Ref: ACR.138.4.33..SATU.A


## 6 CALIBRATION MEASUREMENT RESULTS

### Measurement Condition

|                    |         |
|--------------------|---------|
| Software           | LIMESAR |
| Liquid Temperature | 21°C    |
| Lab Temperature    | 21°C    |
| Lab Humidity       | 44%     |

### 6.1 LIQUID PERMITTIVITY MEASUREMENT

A liquid of known characteristics (methanol at 20°C) is measured with the probe and the results (complex permittivity  $\epsilon' + j\epsilon''$ ) are compared with the well-known theoretical values for this liquid.



Page: 6/7

*This document shall not be reproduced, except in full or in part, without the written approval of MVG.  
The information contained herein is to be used only for the purpose for which it is submitted and is not to be released in whole or part without written approval of MVG.*



**SAR DIELECTRIC PROBE CALIBRATION REPORT**

Ref: ACR.138.4.33..SATU.A

**7 LIST OF EQUIPMENT**

| Equipment Summary Sheet         |                      |                    |                             |                             |
|---------------------------------|----------------------|--------------------|-----------------------------|-----------------------------|
| Equipment Description           | Manufacturer / Model | Identification No. | Current Calibration Date    | Next Calibration Date       |
| LIMESAR Test Bench              | Version 3            | NA                 | Validated. No cal required. | Validated. No cal required. |
| Network Analyzer                | Rhode & Schwarz ZVA  | SN100132           | 02/2021                     | 02/2024                     |
| Methanol CAS 67-56-1            | Alpha Aesar          | Lot D13W011        | Validated. No cal required. | Validated. No cal required. |
| Temperature and Humidity Sensor | Control Company      | 11-661-9           | 09/2023                     | 09/2024                     |

Page: 7/7

*This document shall not be reproduced, except in full or in part, without the written approval of MVG.  
The information contained herein is to be used only for the purpose for which it is submitted and is not to be released in whole or part without written approval of MVG.*

Page 162 of 244

## Appendix D: Dipole Calibration Report

SID750



### SAR Reference Dipole Calibration Report

Ref : ACR.156.3.15.SATU.A

**SHENZHEN TONGCE TESTING LAB**  
2101&2201, ZHENCHANG FACTORY, RENSHAN  
INDUSTRIAL ZONE, FUHAI SUBDISTRICT, BAOAN  
DISTRICT, SHENZHEN, GUANGDONG, 518103,  
PEOPLES REPUBLIC OF CHINA

**COMOSAR REFERENCE DIPOLE**  
FREQUENCY: 750 MHZ  
SERIAL NO.: SN 16/15 DIP 0G750-368

**Calibrated at MVG US**  
2105 Barrett Park Dr. - Kennesaw, GA 30144



**Calibration Date: 06/05/2021**

#### *Summary:*

This document presents the method and results from an accredited SAR reference dipole calibration performed in MVG USA using the COMOSAR test bench. All calibration results are traceable to national metrology institutions.



## SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.156.3.15.SATU.A

|               | Name          | Function        | Date       | Signature |
|---------------|---------------|-----------------|------------|-----------|
| Prepared by : | Jérôme LUC    | Product Manager | 06/05/2021 |           |
| Checked by :  | Jérôme LUC    | Product Manager | 06/05/2021 |           |
| Approved by : | Kim RUTKOWSKI | Quality Manager | 06/05/2021 |           |

|                | Customer Name               |
|----------------|-----------------------------|
| Distribution : | SHENZHEN TONGCE TESTING LAB |

| Issue | Date       | Modifications   |
|-------|------------|-----------------|
| A     | 06/05/2021 | Initial release |
|       |            |                 |
|       |            |                 |
|       |            |                 |

Page: 2/11

This document shall not be reproduced, except in full or in part, without the written approval of MTG.  
The information contained herein is to be used only for the purpose for which it is submitted and is not to be released in whole or part without written approval of MTG.

Page 164 of 244



## SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.156.3.15.SATU.A

## TABLE OF CONTENTS

|     |                                                |    |
|-----|------------------------------------------------|----|
| 1   | Introduction.....                              | 4  |
| 2   | Device Under Test .....                        | 4  |
| 3   | Product Description .....                      | 4  |
| 3.1 | General Information .....                      | 4  |
| 4   | Measurement Method .....                       | 5  |
| 4.1 | Return Loss Requirements .....                 | 5  |
| 4.2 | Mechanical Requirements .....                  | 5  |
| 5   | Measurement Uncertainty .....                  | 5  |
| 5.1 | Return Loss .....                              | 5  |
| 5.2 | Dimension Measurement .....                    | 5  |
| 5.3 | Validation Measurement .....                   | 5  |
| 6   | Calibration Measurement Results .....          | 6  |
| 6.1 | Return Loss and Impedance In Head Liquid ..... | 6  |
| 6.2 | Return Loss and Impedance In Body Liquid ..... | 6  |
| 6.3 | Mechanical Dimensions .....                    | 6  |
| 7   | Validation measurement .....                   | 7  |
| 7.1 | Head Liquid Measurement .....                  | 7  |
| 7.2 | SAR Measurement Result With Head Liquid .....  | 8  |
| 7.3 | Body Liquid Measurement .....                  | 9  |
| 7.4 | SAR Measurement Result With Body Liquid .....  | 10 |
| 8   | List of Equipment .....                        | 11 |

Page: 3/11

*This document shall not be reproduced, except in full or in part, without the written approval of MVG.  
The information contained herein is to be used only for the purpose for which it is submitted and is not to  
be released in whole or part without written approval of MVG.*

Page 165 of 244



## 1 INTRODUCTION

This document contains a summary of the requirements set forth by the IEEE 1528, FCC KDBs and CEI/IEC 62209 standards for reference dipoles used for SAR measurement system validations and the measurements that were performed to verify that the product complies with the fore mentioned standards.

## 2 DEVICE UNDER TEST

| Device Under Test              |                                  |
|--------------------------------|----------------------------------|
| Device Type                    | COMOSAR 750 MHz REFERENCE DIPOLE |
| Manufacturer                   | MVG                              |
| Model                          | SID750                           |
| Serial Number                  | SN 16/15 DIP 0G750-368           |
| Product Condition (new / used) | Used                             |

A yearly calibration interval is recommended.

## 3 PRODUCT DESCRIPTION

### 3.1 GENERAL INFORMATION

MVG's COMOSAR Validation Dipoles are built in accordance to the IEEE 1528, FCC KDBs and CEI/IEC 62209 standards. The product is designed for use with the COMOSAR test bench only.



Figure 1 – MVG COMOSAR Validation Dipole



#### 4 MEASUREMENT METHOD

The IEEE 1528, FCC KDBs and CEI/IEC 62209 standards provide requirements for reference dipoles used for system validation measurements. The following measurements were performed to verify that the product complies with the fore mentioned standards.

##### 4.1 RETURN LOSS REQUIREMENTS

The dipole used for SAR system validation measurements and checks must have a return loss of  $\geq 10$  dB or better. The return loss measurement shall be performed against a liquid filled flat phantom with the phantom constructed as outlined in the fore mentioned standards.

##### 4.2 MECHANICAL REQUIREMENTS

The IEEE Std. 1528 and CEI/IEC 62209 standards specify the mechanical components and dimensions of the validation dipoles, with the dimensions frequency and phantom shell thickness dependent. The COMOSAR test bench employs a 2 mm phantom shell thickness therefore the dipoles sold for use with the COMOSAR test bench comply with the requirements set forth for a 2 mm phantom shell thickness.

#### 5 MEASUREMENT UNCERTAINTY

All uncertainties listed below represent an expanded uncertainty expressed at approximately the 95 confidence level using a coverage factor of  $k=2$ , traceable to the Internationally Accepted Guides to Measurement Uncertainty.

##### 5.1 RETURN LOSS

The following uncertainties apply to the return loss measurement:

| Frequency band | Expanded Uncertainty on Return Loss |
|----------------|-------------------------------------|
| 400-6000MHz    | 0.1 dB                              |

##### 5.2 DIMENSION MEASUREMENT

The following uncertainties apply to the dimension measurements:

| Length (mm) | Expanded Uncertainty on Length |
|-------------|--------------------------------|
| 3 - 300     | 0.05 mm                        |

##### 5.3 VALIDATION MEASUREMENT

The guidelines outlined in the IEEE 1528, FCC KDBs, CENELEC EN50361 and CEI/IEC 62209 standards were followed to generate the measurement uncertainty for validation measurements.

| Scan Volume | Expanded Uncertainty |
|-------------|----------------------|
| 1 g         | 20.3 %               |

Page: 5/11

*This document shall not be reproduced, except in full or in part, without the written approval of MVG.  
The information contained herein is to be used only for the purpose for which it is submitted and is not to be released in whole or part without written approval of MVG.*




## SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.156.3.15.SATU.A

|      |        |
|------|--------|
| 10 g | 20.1 % |
|------|--------|


### 6 CALIBRATION MEASUREMENT RESULTS

#### 6.1 RETURN LOSS AND IMPEDANCE IN HEAD LIQUID



| Frequency (MHz) | Return Loss (dB) | Requirement (dB) | Impedance                   |
|-----------------|------------------|------------------|-----------------------------|
| 750             | -26.63           | -20              | $54.1 \Omega + 1.4 j\Omega$ |

#### 6.2 RETURN LOSS AND IMPEDANCE IN BODY LIQUID



| Frequency (MHz) | Return Loss (dB) | Requirement (dB) | Impedance                   |
|-----------------|------------------|------------------|-----------------------------|
| 750             | -24.18           | -20              | $52.4 \Omega + 5.8 j\Omega$ |

#### 6.3 MECHANICAL DIMENSIONS

| Frequency MHz | L mm        |          | h mm        |          | d mm       |          |
|---------------|-------------|----------|-------------|----------|------------|----------|
|               | required    | measured | required    | measured | required   | measured |
| 300           | 420.0 ± 1 % |          | 250.0 ± 1 % |          | 6.35 ± 1 % |          |

Page: 6/11

This document shall not be reproduced, except in full or in part, without the written approval of MVG.  
The information contained herein is to be used only for the purpose for which it is submitted and is not to be released in whole or part without written approval of MVG.



**SAR REFERENCE DIPOLE CALIBRATION REPORT**

Ref: ACR.156.3.15.SATU.A

|      |             |      |             |      |            |      |
|------|-------------|------|-------------|------|------------|------|
| 450  | 290.0 ±1 %. |      | 166.7 ±1 %. |      | 6.35 ±1 %. |      |
| 750  | 176.0 ±1 %. | PASS | 100.0 ±1 %. | PASS | 6.35 ±1 %. | PASS |
| 835  | 161.0 ±1 %. |      | 89.8 ±1 %.  |      | 3.6 ±1 %.  |      |
| 900  | 149.0 ±1 %. |      | 83.3 ±1 %.  |      | 3.6 ±1 %.  |      |
| 1450 | 89.1 ±1 %.  |      | 51.7 ±1 %.  |      | 3.6 ±1 %.  |      |
| 1500 | 80.5 ±1 %.  |      | 50.0 ±1 %.  |      | 3.6 ±1 %.  |      |
| 1640 | 79.0 ±1 %.  |      | 45.7 ±1 %.  |      | 3.6 ±1 %.  |      |
| 1750 | 75.2 ±1 %.  |      | 42.9 ±1 %.  |      | 3.6 ±1 %.  |      |
| 1800 | 72.0 ±1 %.  |      | 41.7 ±1 %.  |      | 3.6 ±1 %.  |      |
| 1900 | 68.0 ±1 %.  |      | 39.5 ±1 %.  |      | 3.6 ±1 %.  |      |
| 1950 | 66.3 ±1 %.  |      | 38.5 ±1 %.  |      | 3.6 ±1 %.  |      |
| 2000 | 64.5 ±1 %.  |      | 37.5 ±1 %.  |      | 3.6 ±1 %.  |      |
| 2100 | 61.0 ±1 %.  |      | 35.7 ±1 %.  |      | 3.6 ±1 %.  |      |
| 2300 | 55.5 ±1 %.  |      | 32.6 ±1 %.  |      | 3.6 ±1 %.  |      |
| 2450 | 51.5 ±1 %.  |      | 30.4 ±1 %.  |      | 3.6 ±1 %.  |      |
| 2600 | 48.5 ±1 %.  |      | 28.8 ±1 %.  |      | 3.6 ±1 %.  |      |
| 3000 | 41.5 ±1 %.  |      | 25.0 ±1 %.  |      | 3.6 ±1 %.  |      |
| 3500 | 37.0 ±1 %.  |      | 26.4 ±1 %.  |      | 3.6 ±1 %.  |      |
| 3700 | 34.7 ±1 %.  |      | 26.4 ±1 %.  |      | 3.6 ±1 %.  |      |

## 7 VALIDATION MEASUREMENT

The IEEE Std. 1528, FCC KDBs and CEI/IEC 62209 standards state that the system validation measurements must be performed using a reference dipole meeting the fore mentioned return loss and mechanical dimension requirements. The validation measurement must be performed against a liquid filled flat phantom, with the phantom constructed as outlined in the fore mentioned standards. Per the standards, the dipole shall be positioned below the bottom of the phantom, with the dipole length centered and parallel to the longest dimension of the flat phantom, with the top surface of the dipole at the described distance from the bottom surface of the phantom.

### 7.1 HEAD LIQUID MEASUREMENT

| Frequency<br>MHz | Relative permittivity ( $\epsilon_r$ ) |          | Conductivity ( $\sigma$ ) S/m |          |
|------------------|----------------------------------------|----------|-------------------------------|----------|
|                  | required                               | measured | required                      | measured |
| 300              | 45.3 ±5 %                              |          | 0.87 ±5 %                     |          |
| 450              | 43.5 ±5 %                              |          | 0.87 ±5 %                     |          |
| 750              | 41.9 ±5 %                              | PASS     | 0.89 ±5 %                     | PASS     |
| 835              | 41.5 ±5 %                              |          | 0.90 ±5 %                     |          |
| 900              | 41.5 ±5 %                              |          | 0.97 ±5 %                     |          |
| 1450             | 40.5 ±5 %                              |          | 1.20 ±5 %                     |          |
| 1500             | 40.4 ±5 %                              |          | 1.23 ±5 %                     |          |
| 1640             | 40.2 ±5 %                              |          | 1.31 ±5 %                     |          |
| 1750             | 40.1 ±5 %                              |          | 1.37 ±5 %                     |          |

Page: 7/11

*This document shall not be reproduced, except in full or in part, without the written approval of MVG.  
The information contained herein is to be used only for the purpose for which it is submitted and is not to be released in whole or part without written approval of MVG.*



## SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.156.3.15.SATU.A

|      |            |  |            |  |
|------|------------|--|------------|--|
| 1800 | 40.0 ± 5 % |  | 1.40 ± 5 % |  |
| 1900 | 40.0 ± 5 % |  | 1.40 ± 5 % |  |
| 1950 | 40.0 ± 5 % |  | 1.40 ± 5 % |  |
| 2000 | 40.0 ± 5 % |  | 1.40 ± 5 % |  |
| 2100 | 39.8 ± 5 % |  | 1.49 ± 5 % |  |
| 2300 | 39.5 ± 5 % |  | 1.67 ± 5 % |  |
| 2450 | 39.2 ± 5 % |  | 1.80 ± 5 % |  |
| 2600 | 39.0 ± 5 % |  | 1.96 ± 5 % |  |
| 3000 | 38.5 ± 5 % |  | 2.40 ± 5 % |  |
| 3500 | 37.9 ± 5 % |  | 2.91 ± 5 % |  |

### 7.2 SAR MEASUREMENT RESULT WITH HEAD LIQUID

The IEEE Std. 1528 and CEI/IEC 62209 standards state that the system validation measurements should produce the SAR values shown below (for phantom thickness of 2 mm), within the uncertainty for the system validation. All SAR values are normalized to 1 W forward power. In bracket, the measured SAR is given with the used input power.

|                                           |                                                            |
|-------------------------------------------|------------------------------------------------------------|
| Software                                  | OPENSAR V4                                                 |
| Phantom                                   | SN 20/09 SAM71                                             |
| Probe                                     | SN 18/11 EPG122                                            |
| Liquid                                    | Head Liquid Values: $\epsilon_{ps}$ : 41.8 $\sigma$ : 0.90 |
| Distance between dipole center and liquid | 15.0 mm                                                    |
| Area scan resolution                      | $dx=8mm/dy=8mm$                                            |
| Zoon Scan Resolution                      | $dx=8mm/dy=8mm/dz=5mm$                                     |
| Frequency                                 | 750 MHz                                                    |
| Input power                               | 20 dBm                                                     |
| Liquid Temperature                        | 21 °C                                                      |
| Lab Temperature                           | 21 °C                                                      |
| Lab Humidity                              | 45 %                                                       |

| Frequency<br>MHz | 1 g SAR (W/kg/W) |             | 10 g SAR (W/kg/W) |             |
|------------------|------------------|-------------|-------------------|-------------|
|                  | required         | measured    | required          | measured    |
| 300              | 2.85             |             | 1.94              |             |
| 450              | 4.58             |             | 3.06              |             |
| 750              | 8.49             | 8.31 (0.73) | 5.55              | 5.71 (0.54) |
| 835              | 9.56             |             | 6.22              |             |
| 900              | 10.9             |             | 6.99              |             |
| 1450             | 29               |             | 16                |             |
| 1500             | 30.5             |             | 16.8              |             |
| 1640             | 34.2             |             | 18.4              |             |
| 1750             | 36.4             |             | 19.3              |             |
| 1800             | 38.4             |             | 20.1              |             |

Page: 8/11


This document shall not be reproduced, except in full or in part, without the written approval of MVG.  
The information contained herein is to be used only for the purpose for which it is submitted and is not to be released in whole or part without written approval of MVG.



## SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.156.3.15.SATU.A

|      |      |  |      |  |
|------|------|--|------|--|
| 1900 | 39.7 |  | 20.5 |  |
| 1950 | 40.5 |  | 20.9 |  |
| 2000 | 41.1 |  | 21.1 |  |
| 2100 | 43.6 |  | 21.9 |  |
| 2300 | 48.7 |  | 23.3 |  |
| 2450 | 52.4 |  | 24   |  |
| 2600 | 55.3 |  | 24.6 |  |
| 3000 | 63.8 |  | 25.7 |  |
| 3500 | 67.1 |  | 25   |  |



### 7.3 BODY LIQUID MEASUREMENT

| Frequency<br>MHz | Relative permittivity ( $\epsilon_r'$ ) |          | Conductivity ( $\sigma$ ) S/m |          |
|------------------|-----------------------------------------|----------|-------------------------------|----------|
|                  | required                                | measured | required                      | measured |
| 150              | 61.9 $\pm$ 5 %                          |          | 0.80 $\pm$ 5 %                |          |
| 300              | 58.2 $\pm$ 5 %                          |          | 0.92 $\pm$ 5 %                |          |
| 450              | 56.7 $\pm$ 5 %                          |          | 0.94 $\pm$ 5 %                |          |
| 750              | 55.5 $\pm$ 5 %                          | PASS     | 0.96 $\pm$ 5 %                | PASS     |
| 835              | 55.2 $\pm$ 5 %                          |          | 0.97 $\pm$ 5 %                |          |
| 900              | 55.0 $\pm$ 5 %                          |          | 1.05 $\pm$ 5 %                |          |
| 915              | 55.0 $\pm$ 5 %                          |          | 1.06 $\pm$ 5 %                |          |
| 1450             | 54.0 $\pm$ 5 %                          |          | 1.30 $\pm$ 5 %                |          |
| 1610             | 53.8 $\pm$ 5 %                          |          | 1.40 $\pm$ 5 %                |          |
| 1800             | 53.3 $\pm$ 5 %                          |          | 1.52 $\pm$ 5 %                |          |
| 1900             | 53.3 $\pm$ 5 %                          |          | 1.52 $\pm$ 5 %                |          |
| 2000             | 53.3 $\pm$ 5 %                          |          | 1.52 $\pm$ 5 %                |          |
| 2100             | 53.2 $\pm$ 5 %                          |          | 1.62 $\pm$ 5 %                |          |
| 2450             | 52.7 $\pm$ 5 %                          |          | 1.95 $\pm$ 5 %                |          |

Page: 9/11

This document shall not be reproduced, except in full or in part, without the written approval of MVG.  
The information contained herein is to be used only for the purpose for which it is submitted and is not to be released in whole or part without written approval of MVG.



## SAR REFERENCE DIPOLE CALIBRATION REPORT


Ref: ACR.156.3.15.SATU.A

|      |            |  |            |  |
|------|------------|--|------------|--|
| 2600 | 52.5 ±5 %  |  | 2.16 ±5 %  |  |
| 3000 | 52.0 ±5 %  |  | 2.73 ±5 %  |  |
| 3500 | 51.3 ±5 %  |  | 3.31 ±5 %  |  |
| 5200 | 49.0 ±10 % |  | 5.30 ±10 % |  |
| 5300 | 48.9 ±10 % |  | 5.42 ±10 % |  |
| 5400 | 48.7 ±10 % |  | 5.53 ±10 % |  |
| 5500 | 48.6 ±10 % |  | 5.65 ±10 % |  |
| 5600 | 48.5 ±10 % |  | 5.77 ±10 % |  |
| 5800 | 48.2 ±10 % |  | 6.00 ±10 % |  |

### 7.4 SAR MEASUREMENT RESULT WITH BODY LIQUID

|                                           |                                                          |
|-------------------------------------------|----------------------------------------------------------|
| Software                                  | OPENSAR V4                                               |
| Phantom                                   | SN 20/09 SAM71                                           |
| Probe                                     | SN 18/11 EPG122                                          |
| Liquid                                    | Body Liquid Values: $\epsilon_s' : 56.3$ $\sigma : 0.98$ |
| Distance between dipole center and liquid | 15.0 mm                                                  |
| Area scan resolution                      | $dx=8mm/dy=8mm$                                          |
| Zoon Scan Resolution                      | $dx=8mm/dy=8mm/dz=5mm$                                   |
| Frequency                                 | 750 MHz                                                  |
| Input power                               | 20 dBm                                                   |
| Liquid Temperature                        | 21 °C                                                    |
| Lab Temperature                           | 21 °C                                                    |
| Lab Humidity                              | 45 %                                                     |

| Frequency<br>MHz | 1 g SAR (W/kg/W) | 10 g SAR (W/kg/W) |
|------------------|------------------|-------------------|
|                  | measured         | measured          |
| 750              | 8.46 (0.77)      | 5.81 (0.45)       |



Page: 10/11

This document shall not be reproduced, except in full or in part, without the written approval of MVG.  
The information contained herein is to be used only for the purpose for which it is submitted and is not to be released in whole or part without written approval of MVG.

Page 172 of 244



## 8 LIST OF EQUIPMENT

| Equipment Summary Sheet         |                      |                    |                                               |                                               |
|---------------------------------|----------------------|--------------------|-----------------------------------------------|-----------------------------------------------|
| Equipment Description           | Manufacturer / Model | Identification No. | Current Calibration Date                      | Next Calibration Date                         |
| SAM Phantom                     | MVG                  | SN-20/09-SAM71     | Validated. No cal required.                   | Validated. No cal required.                   |
| COMOSAR Test Bench              | Version 3            | NA                 | Validated. No cal required.                   | Validated. No cal required.                   |
| Network Analyzer                | Rhode & Schwarz ZVA  | SN100132           | 02/2021                                       | 02/2024                                       |
| Calipers                        | Carrera              | CALIPER-01         | 02/2021                                       | 02/2024                                       |
| Reference Probe                 | MVG                  | EPG122 SN 18/11    | 02/2023                                       | 02/2024                                       |
| Multimeter                      | Keithley 2000        | 1188656            | 02/2021                                       | 02/2024                                       |
| Signal Generator                | Agilent E4438C       | MY49070581         | 02/2021                                       | 02/2024                                       |
| Amplifier                       | Aethercomm           | SN 046             | Characterized prior to test. No cal required. | Characterized prior to test. No cal required. |
| Power Meter                     | HP E4418A            | US38261498         | 02/2021                                       | 02/2024                                       |
| Power Sensor                    | HP ECP-E26A          | US37181460         | 02/2021                                       | 02/2024                                       |
| Directional Coupler             | Narda 4216-20        | 01386              | Characterized prior to test. No cal required. | Characterized prior to test. No cal required. |
| Temperature and Humidity Sensor | Control Company      | 11-661-9           | 02/2021                                       | 02/2024                                       |

Page: 11/11

*This document shall not be reproduced, except in full or in part, without the written approval of MVG.  
The information contained herein is to be used only for the purpose for which it is submitted and is not to be released in whole or part without written approval of MVG.*



## SAR Reference Dipole Calibration Report

Ref : ACR.156.4.15.SATU.A

### SHENZHEN TONGCE TESTING LAB

2101&2201, ZHENCHANG FACTORY, RENSHAN INDUSTRIAL  
ZONE, FUHAI SUBDISTRICT, BAOAN DISTRICT, SHENZHEN  
GUANGDONG, 518103, PEOPLES REPUBLIC OF CHINA  
**MVG COMOSAR REFERENCE DIPOLE**

**FREQUENCY: 835 MHZ**

**SERIAL NO.: SN 16/15 DIP 0G835-369**

**Calibrated at MVG US**

2105 Barrett Park Dr. - Kennesaw, GA 30144



**Calibration Date: 06/05/2021**

#### *Summary:*

This document presents the method and results from an accredited SAR reference dipole calibration performed in MVG USA using the COMOSAR test bench. All calibration results are traceable to national metrology institutions.



## SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.156.4.15.SATU.A

|               | Name          | Function        | Date       | Signature |
|---------------|---------------|-----------------|------------|-----------|
| Prepared by : | Jérôme LUC    | Product Manager | 06/05/2021 |           |
| Checked by :  | Jérôme LUC    | Product Manager | 06/05/2021 |           |
| Approved by : | Kim RUTKOWSKI | Quality Manager | 06/05/2021 |           |

|                | Customer Name                  |
|----------------|--------------------------------|
| Distribution : | SHENZHEN TONGCE<br>TESTING LAB |

| Issue | Date       | Modifications   |
|-------|------------|-----------------|
| A     | 06/05/2021 | Initial release |
|       |            |                 |
|       |            |                 |
|       |            |                 |



SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.156.4.15.SATU.A

TABLE OF CONTENTS

|     |                                                |    |
|-----|------------------------------------------------|----|
| 1   | Introduction.....                              | 4  |
| 2   | Device Under Test .....                        | 4  |
| 3   | Product Description .....                      | 4  |
| 3.1 | General Information .....                      | 4  |
| 4   | Measurement Method .....                       | 5  |
| 4.1 | Return Loss Requirements .....                 | 5  |
| 4.2 | Mechanical Requirements .....                  | 5  |
| 5   | Measurement Uncertainty .....                  | 5  |
| 5.1 | Return Loss .....                              | 5  |
| 5.2 | Dimension Measurement .....                    | 5  |
| 5.3 | Validation Measurement .....                   | 5  |
| 6   | Calibration Measurement Results .....          | 6  |
| 6.1 | Return Loss and Impedance In Head Liquid ..... | 6  |
| 6.2 | Return Loss and Impedance In Body Liquid ..... | 6  |
| 6.3 | Mechanical Dimensions .....                    | 6  |
| 7   | Validation measurement .....                   | 7  |
| 7.1 | Head Liquid Measurement .....                  | 7  |
| 7.2 | SAR Measurement Result With Head Liquid .....  | 8  |
| 7.3 | Body Liquid Measurement .....                  | 9  |
| 7.4 | SAR Measurement Result With Body Liquid .....  | 10 |
| 8   | List of Equipment .....                        | 11 |

Page: 3/11

*This document shall not be reproduced, except in full or in part, without the written approval of MVG.  
The information contained herein is to be used only for the purpose for which it is submitted and is not to be released in whole or part without written approval of MVG.*



## SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.156.4.15.SATU.A

## 1 INTRODUCTION

This document contains a summary of the requirements set forth by the IEEE 1528, FCC KDBs and CEI/IEC 62209 standards for reference dipoles used for SAR measurement system validations and the measurements that were performed to verify that the product complies with the fore mentioned standards.

## 2 DEVICE UNDER TEST

| Device Under Test              |                                  |
|--------------------------------|----------------------------------|
| Device Type                    | COMOSAR 835 MHz REFERENCE DIPOLE |
| Manufacturer                   | MVG                              |
| Model                          | SID835                           |
| Serial Number                  | SN 16/15 DIP 0G835-369           |
| Product Condition (new / used) | Used                             |

A yearly calibration interval is recommended.

## 3 PRODUCT DESCRIPTION

### 3.1 GENERAL INFORMATION

MVG's COMOSAR Validation Dipoles are built in accordance to the IEEE 1528, FCC KDBs and CEI/IEC 62209 standards. The product is designed for use with the COMOSAR test bench only.



Figure 1 – MVG COMOSAR Validation Dipole

Page: 4/11

*This document shall not be reproduced, except in full or in part, without the written approval of MVG.  
The information contained herein is to be used only for the purpose for which it is submitted and is not to be released in whole or part without written approval of MVG.*



#### 4 MEASUREMENT METHOD

The IEEE 1528, FCC KDBs and CEI/IEC 62209 standards provide requirements for reference dipoles used for system validation measurements. The following measurements were performed to verify that the product complies with the fore mentioned standards.

##### 4.1 RETURN LOSS REQUIREMENTS

The dipole used for SAR system validation measurements and checks must have a return loss of -20 dB or better. The return loss measurement shall be performed against a liquid filled phantom, with the phantom constructed as outlined in the fore mentioned standards.

##### 4.2 MECHANICAL REQUIREMENTS

The IEEE Std. 1528 and CEI/IEC 62209 standards specify the mechanical components and dimensions of the validation dipoles, with the dimensions frequency and phantom shell thickness dependent. The COMOSAR test bench employs a 2 mm phantom shell thickness therefore the dipoles sold for use with the COMOSAR test bench comply with the requirements set forth for a 2 mm phantom shell thickness.

#### 5 MEASUREMENT UNCERTAINTY

All uncertainties listed below represent an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of  $k=2$ , traceable to the Internationally Accepted Guides to Measurement Uncertainty.

##### 5.1 RETURN LOSS

The following uncertainties apply to the return loss measurement:

| Frequency band | Expanded Uncertainty on Return Loss |
|----------------|-------------------------------------|
| 400-6000MHz    | 0.1 dB                              |

##### 5.2 DIMENSION MEASUREMENT

The following uncertainties apply to the dimension measurements:

| Length (mm) | Expanded Uncertainty on Length |
|-------------|--------------------------------|
| 3 - 300     | 0.05 mm                        |

##### 5.3 VALIDATION MEASUREMENT

The guidelines outlined in the IEEE 1528, FCC KDBs, CENELEC EN50361 and CEI/IEC 62209 standards were followed to generate the measurement uncertainty for validation measurements.

| Scan Volume | Expanded Uncertainty |
|-------------|----------------------|
| 1 g         | 20.3 %               |

Page: 5/11

*This document shall not be reproduced, except in full or in part, without the written approval of MVG.  
The information contained herein is to be used only for the purpose for which it is submitted and is not to be released in whole or part without written approval of MVG.*




## SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.156.4.15.SATU.A

|      |        |
|------|--------|
| 10 g | 20.1 % |
|------|--------|


### 6 CALIBRATION MEASUREMENT RESULTS

#### 6.1 RETURN LOSS AND IMPEDANCE IN HEAD LIQUID



| Frequency (MHz) | Return Loss (dB) | Requirement (dB) | Impedance                   |
|-----------------|------------------|------------------|-----------------------------|
| 835             | -32.78           | -20              | $51.5 \Omega + 1.7 j\Omega$ |

#### 6.2 RETURN LOSS AND IMPEDANCE IN BODY LIQUID



| Frequency (MHz) | Return Loss (dB) | Requirement (dB) | Impedance                   |
|-----------------|------------------|------------------|-----------------------------|
| 835             | -23.99           | -20              | $47.3 \Omega + 5.6 j\Omega$ |

#### 6.3 MECHANICAL DIMENSIONS

| Frequency MHz | L mm        |          | h mm        |          | d mm       |          |
|---------------|-------------|----------|-------------|----------|------------|----------|
|               | required    | measured | required    | measured | required   | measured |
| 300           | 420.0 ± 1 % |          | 250.0 ± 1 % |          | 6.35 ± 1 % |          |

Page: 6/11

This document shall not be reproduced, except in full or in part, without the written approval of MVG.  
The information contained herein is to be used only for the purpose for which it is submitted and is not to be released in whole or part without written approval of MVG.



## SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.156.4.15.SATU.A

|      |             |      |             |      |            |      |
|------|-------------|------|-------------|------|------------|------|
| 450  | 290.0 ±1 %. |      | 166.7 ±1 %. |      | 6.35 ±1 %. |      |
| 750  | 176.0 ±1 %. |      | 100.0 ±1 %. |      | 6.35 ±1 %. |      |
| 835  | 161.0 ±1 %. | PASS | 89.8 ±1 %.  | PASS | 3.6 ±1 %.  | PASS |
| 900  | 149.0 ±1 %. |      | 83.3 ±1 %.  |      | 3.6 ±1 %.  |      |
| 1450 | 89.1 ±1 %.  |      | 51.7 ±1 %.  |      | 3.6 ±1 %.  |      |
| 1500 | 80.5 ±1 %.  |      | 50.0 ±1 %.  |      | 3.6 ±1 %.  |      |
| 1640 | 79.0 ±1 %.  |      | 45.7 ±1 %.  |      | 3.6 ±1 %.  |      |
| 1750 | 75.2 ±1 %.  |      | 42.9 ±1 %.  |      | 3.6 ±1 %.  |      |
| 1800 | 72.0 ±1 %.  |      | 41.7 ±1 %.  |      | 3.6 ±1 %.  |      |
| 1900 | 68.0 ±1 %.  |      | 39.5 ±1 %.  |      | 3.6 ±1 %.  |      |
| 1950 | 66.3 ±1 %.  |      | 38.5 ±1 %.  |      | 3.6 ±1 %.  |      |
| 2000 | 64.5 ±1 %.  |      | 37.5 ±1 %.  |      | 3.6 ±1 %.  |      |
| 2100 | 61.0 ±1 %.  |      | 35.7 ±1 %.  |      | 3.6 ±1 %.  |      |
| 2300 | 55.5 ±1 %.  |      | 32.6 ±1 %.  |      | 3.6 ±1 %.  |      |
| 2450 | 51.5 ±1 %.  |      | 30.4 ±1 %.  |      | 3.6 ±1 %.  |      |
| 2600 | 48.5 ±1 %.  |      | 28.8 ±1 %.  |      | 3.6 ±1 %.  |      |
| 3000 | 41.5 ±1 %.  |      | 25.0 ±1 %.  |      | 3.6 ±1 %.  |      |
| 3500 | 37.0 ±1 %.  |      | 26.4 ±1 %.  |      | 3.6 ±1 %.  |      |
| 3700 | 34.7 ±1 %.  |      | 26.4 ±1 %.  |      | 3.6 ±1 %.  |      |

## 7 VALIDATION MEASUREMENT

The IEEE Std. 1528, FCC KDBs and CEI/IEC 62209 standards state that the system validation measurements must be performed using a reference dipole meeting the fore mentioned return loss and mechanical dimension requirements. The validation measurement must be performed against a liquid filled flat phantom, with the phantom constructed as outlined in the fore mentioned standards. Per the standards, the dipole shall be positioned below the bottom of the phantom, with the dipole length centered and parallel to the longest dimension of the flat phantom, with the top surface of the dipole at the described distance from the bottom surface of the phantom.

### 7.1 HEAD LIQUID MEASUREMENT

| Frequency<br>MHz | Relative permittivity ( $\epsilon_r'$ ) |          | Conductivity ( $\sigma$ ) S/m |          |
|------------------|-----------------------------------------|----------|-------------------------------|----------|
|                  | required                                | measured | required                      | measured |
| 300              | 45.3 ±5 %                               |          | 0.87 ±5 %                     |          |
| 450              | 43.5 ±5 %                               |          | 0.87 ±5 %                     |          |
| 750              | 41.9 ±5 %                               |          | 0.89 ±5 %                     |          |
| 835              | 41.5 ±5 %                               | PASS     | 0.90 ±5 %                     | PASS     |
| 900              | 41.5 ±5 %                               |          | 0.97 ±5 %                     |          |
| 1450             | 40.5 ±5 %                               |          | 1.20 ±5 %                     |          |
| 1500             | 40.4 ±5 %                               |          | 1.23 ±5 %                     |          |
| 1640             | 40.2 ±5 %                               |          | 1.31 ±5 %                     |          |
| 1750             | 40.1 ±5 %                               |          | 1.37 ±5 %                     |          |

Page: 7/11

*This document shall not be reproduced, except in full or in part, without the written approval of MVG.  
The information contained herein is to be used only for the purpose for which it is submitted and is not to be released in whole or part without written approval of MVG.*



## SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.156.4.15.SATU.A

|      |           |  |           |  |
|------|-----------|--|-----------|--|
| 1800 | 40.0 ±5 % |  | 1.40 ±5 % |  |
| 1900 | 40.0 ±5 % |  | 1.40 ±5 % |  |
| 1950 | 40.0 ±5 % |  | 1.40 ±5 % |  |
| 2000 | 40.0 ±5 % |  | 1.40 ±5 % |  |
| 2100 | 39.8 ±5 % |  | 1.49 ±5 % |  |
| 2300 | 39.5 ±5 % |  | 1.67 ±5 % |  |
| 2450 | 39.2 ±5 % |  | 1.80 ±5 % |  |
| 2600 | 39.0 ±5 % |  | 1.96 ±5 % |  |
| 3000 | 38.5 ±5 % |  | 2.40 ±5 % |  |
| 3500 | 37.9 ±5 % |  | 2.91 ±5 % |  |

### 7.2 SAR MEASUREMENT RESULT WITH HEAD LIQUID

The IEEE Std. 1528 and CEI/IEC 62209 standards state that the system validation measurements should produce the SAR values shown below (for phantom thickness of 2 mm), within the uncertainty for the system validation. All SAR values are normalized to 1 W forward power. In bracket, the measured SAR is given with the used input power.

|                                           |                                                         |
|-------------------------------------------|---------------------------------------------------------|
| Software                                  | OPENSAR V4                                              |
| Phantom                                   | SN 20/09 SAM71                                          |
| Probe                                     | SN 18/11 EPG122                                         |
| Liquid                                    | Head Liquid Values: $\epsilon_p$ : 42.3 $\sigma$ : 0.92 |
| Distance between dipole center and liquid | 15.0 mm                                                 |
| Area scan resolution                      | $dx=8mm/dy=8mm$                                         |
| Zoon Scan Resolution                      | $dx=8mm/dy=8mm/dz=5mm$                                  |
| Frequency                                 | 835 MHz                                                 |
| Input power                               | 20 dBm                                                  |
| Liquid Temperature                        | 21 °C                                                   |
| Lab Temperature                           | 21 °C                                                   |
| Lab Humidity                              | 45 %                                                    |

| Frequency<br>MHz | 1 g SAR (W/kg/W) |             | 10 g SAR (W/kg/W) |             |
|------------------|------------------|-------------|-------------------|-------------|
|                  | required         | measured    | required          | measured    |
| 300              | 2.85             |             | 1.94              |             |
| 450              | 4.58             |             | 3.06              |             |
| 750              | 8.49             |             | 5.55              |             |
| 835              | 9.56             | 9.53 (0.82) | 6.22              | 6.12 (0.58) |
| 900              | 10.9             |             | 6.99              |             |
| 1450             | 29               |             | 16                |             |
| 1500             | 30.5             |             | 16.8              |             |
| 1640             | 34.2             |             | 18.4              |             |
| 1750             | 36.4             |             | 19.3              |             |
| 1800             | 38.4             |             | 20.1              |             |

Page: 8/11


*This document shall not be reproduced, except in full or in part, without the written approval of MVG.  
The information contained herein is to be used only for the purpose for which it is submitted and is not to be released in whole or part without written approval of MVG.*



## SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.156.4.15.SATU.A

|      |      |  |      |  |
|------|------|--|------|--|
| 1900 | 39.7 |  | 20.5 |  |
| 1950 | 40.5 |  | 20.9 |  |
| 2000 | 41.1 |  | 21.1 |  |
| 2100 | 43.6 |  | 21.9 |  |
| 2300 | 48.7 |  | 23.3 |  |
| 2450 | 52.4 |  | 24   |  |
| 2600 | 55.3 |  | 24.6 |  |
| 3000 | 63.8 |  | 25.7 |  |
| 3500 | 67.1 |  | 25   |  |



### 7.3 BODY LIQUID MEASUREMENT

| Frequency<br>MHz | Relative permittivity ( $\epsilon_r'$ ) |          | Conductivity ( $\sigma$ ) S/m |          |
|------------------|-----------------------------------------|----------|-------------------------------|----------|
|                  | required                                | measured | required                      | measured |
| 150              | 61.9 $\pm$ 5 %                          |          | 0.80 $\pm$ 5 %                |          |
| 300              | 58.2 $\pm$ 5 %                          |          | 0.92 $\pm$ 5 %                |          |
| 450              | 56.7 $\pm$ 5 %                          |          | 0.94 $\pm$ 5 %                |          |
| 750              | 55.5 $\pm$ 5 %                          |          | 0.96 $\pm$ 5 %                |          |
| 835              | 55.2 $\pm$ 5 %                          | PASS     | 0.97 $\pm$ 5 %                | PASS     |
| 900              | 55.0 $\pm$ 5 %                          |          | 1.05 $\pm$ 5 %                |          |
| 915              | 55.0 $\pm$ 5 %                          |          | 1.06 $\pm$ 5 %                |          |
| 1450             | 54.0 $\pm$ 5 %                          |          | 1.30 $\pm$ 5 %                |          |
| 1610             | 53.8 $\pm$ 5 %                          |          | 1.40 $\pm$ 5 %                |          |
| 1800             | 53.3 $\pm$ 5 %                          |          | 1.52 $\pm$ 5 %                |          |
| 1900             | 53.3 $\pm$ 5 %                          |          | 1.52 $\pm$ 5 %                |          |
| 2000             | 53.3 $\pm$ 5 %                          |          | 1.52 $\pm$ 5 %                |          |
| 2100             | 53.2 $\pm$ 5 %                          |          | 1.62 $\pm$ 5 %                |          |
| 2450             | 52.7 $\pm$ 5 %                          |          | 1.95 $\pm$ 5 %                |          |

Page: 9/11

This document shall not be reproduced, except in full or in part, without the written approval of MVG.  
The information contained herein is to be used only for the purpose for which it is submitted and is not to be released in whole or part without written approval of MVG.



## SAR REFERENCE DIPOLE CALIBRATION REPORT


Ref: ACR.156.4.15.SATU.A

|      |            |  |            |  |
|------|------------|--|------------|--|
| 2600 | 52.5 ±5 %  |  | 2.16 ±5 %  |  |
| 3000 | 52.0 ±5 %  |  | 2.73 ±5 %  |  |
| 3500 | 51.3 ±5 %  |  | 3.31 ±5 %  |  |
| 5200 | 49.0 ±10 % |  | 5.30 ±10 % |  |
| 5300 | 48.9 ±10 % |  | 5.42 ±10 % |  |
| 5400 | 48.7 ±10 % |  | 5.53 ±10 % |  |
| 5500 | 48.6 ±10 % |  | 5.65 ±10 % |  |
| 5600 | 48.5 ±10 % |  | 5.77 ±10 % |  |
| 5800 | 48.2 ±10 % |  | 6.00 ±10 % |  |

### 7.4 SAR MEASUREMENT RESULT WITH BODY LIQUID

|                                           |                                              |
|-------------------------------------------|----------------------------------------------|
| Software                                  | OPENSAR V4                                   |
| Phantom                                   | SN 20/09 SAM71                               |
| Probe                                     | SN 18/11 EPG122                              |
| Liquid                                    | Body Liquid Values: eps' : 53.3 sigma : 0.97 |
| Distance between dipole center and liquid | 15.0 mm                                      |
| Area scan resolution                      | dx=8mm/dy=8mm                                |
| Zoon Scan Resolution                      | dx=8mm/dy=8mm/dz=5mm                         |
| Frequency                                 | 835 MHz                                      |
| Input power                               | 20 dBm                                       |
| Liquid Temperature                        | 21 °C                                        |
| Lab Temperature                           | 21 °C                                        |
| Lab Humidity                              | 45 %                                         |

| Frequency MHz | 1 g SAR (W/kg/W) | 10 g SAR (W/kg/W) |
|---------------|------------------|-------------------|
|               | measured         | measured          |
| 835           | 9.62 (0.91)      | 6.44 (0.59)       |



Page: 10/11

This document shall not be reproduced, except in full or in part, without the written approval of MVG.  
The information contained herein is to be used only for the purpose for which it is submitted and is not to be released in whole or part without written approval of MVG.



## 8 LIST OF EQUIPMENT

| Equipment Summary Sheet         |                      |                    |                                               |                                               |
|---------------------------------|----------------------|--------------------|-----------------------------------------------|-----------------------------------------------|
| Equipment Description           | Manufacturer / Model | Identification No. | Current Calibration Date                      | Next Calibration Date                         |
| SAM Phantom                     | MVG                  | SN-20/09-SAM71     | Validated. No cal required.                   | Validated. No cal required.                   |
| COMOSAR Test Bench              | Version 3            | NA                 | Validated. No cal required.                   | Validated. No cal required.                   |
| Network Analyzer                | Rhode & Schwarz ZVA  | SN100132           | 02/2021                                       | 02/2024                                       |
| Calipers                        | Carrera              | CALIPER-01         | 02/2021                                       | 02/2024                                       |
| Reference Probe                 | MVG                  | EPG122 SN 18/11    | 02/2023                                       | 02/2024                                       |
| Multimeter                      | Keithley 2000        | 1188656            | 02/2021                                       | 02/2024                                       |
| Signal Generator                | Agilent E4438C       | MY49070581         | 02/2021                                       | 02/2024                                       |
| Amplifier                       | Aethercomm           | SN 046             | Characterized prior to test. No cal required. | Characterized prior to test. No cal required. |
| Power Meter                     | HP E4418A            | US38261498         | 02/2021                                       | 02/2024                                       |
| Power Sensor                    | HP ECP-E26A          | US37181460         | 02/2021                                       | 02/2024                                       |
| Directional Coupler             | Narda 4216-20        | 01386              | Characterized prior to test. No cal required. | Characterized prior to test. No cal required. |
| Temperature and Humidity Sensor | Control Company      | 11-661-9           | 02/2021                                       | 02/2024                                       |

Page: 11/11

*This document shall not be reproduced, except in full or in part, without the written approval of MVG.  
The information contained herein is to be used only for the purpose for which it is submitted and is not to be released in whole or part without written approval of MVG.*



## SAR Reference Dipole Calibration Report

Ref : ACR.156.6.15.SATU.A

### SHENZHEN TONGCE TESTING LAB

2101&2201, ZHENCHANG FACTORY, RENSHAN INDUSTRIAL  
ZONE, FUHAI SUBDISTRICT, BAOAN DISTRICT, SHENZHEN,  
GUANGDONG, 518103, PEOPLES REPUBLIC OF CHINA  
**MVG COMOSAR REFERENCE DIPOLE**

**FREQUENCY: 1800 MHZ**

**SERIAL NO.: SN 16/15 DIP 1G800-371**

**Calibrated at MVG US**

2105 Barrett Park Dr. - Kennesaw, GA 30144



**Calibration Date: 06/05/2021**

#### *Summary:*

This document presents the method and results from an accredited SAR reference dipole calibration performed in MVG USA using the COMOSAR test bench. All calibration results are traceable to national metrology institutions.



## SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.156.6.15.SATU.A

|               | Name          | Function        | Date       | Signature            |
|---------------|---------------|-----------------|------------|----------------------|
| Prepared by : | Jérôme LUC    | Product Manager | 06/05/2021 | <i>JS</i>            |
| Checked by :  | Jérôme LUC    | Product Manager | 06/05/2021 | <i>JS</i>            |
| Approved by : | Kim RUTKOWSKI | Quality Manager | 06/05/2021 | <i>Kim Rutkowski</i> |

|                | Customer Name               |
|----------------|-----------------------------|
| Distribution : | SHENZHEN TONGCE TESTING LAB |

| Issue | Date       | Modifications   |
|-------|------------|-----------------|
| A     | 06/05/2021 | Initial release |
|       |            |                 |
|       |            |                 |
|       |            |                 |

Page: 2/11

This document shall not be reproduced, except in full or in part, without the written approval of MVG.  
The information contained herein is to be used only for the purpose for which it is submitted and is not to be released in whole or part without written approval of MVG.



## TABLE OF CONTENTS

|     |                                                |    |
|-----|------------------------------------------------|----|
| 1   | Introduction.....                              | 4  |
| 2   | Device Under Test .....                        | 4  |
| 3   | Product Description .....                      | 4  |
| 3.1 | General Information .....                      | 4  |
| 4   | Measurement Method .....                       | 5  |
| 4.1 | Return Loss Requirements .....                 | 5  |
| 4.2 | Mechanical Requirements .....                  | 5  |
| 5   | Measurement Uncertainty .....                  | 5  |
| 5.1 | Return Loss .....                              | 5  |
| 5.2 | Dimension Measurement .....                    | 5  |
| 5.3 | Validation Measurement .....                   | 5  |
| 6   | Calibration Measurement Results .....          | 6  |
| 6.1 | Return Loss and Impedance In Head Liquid ..... | 6  |
| 6.2 | Return Loss and Impedance In Body Liquid ..... | 6  |
| 6.3 | Mechanical Dimensions .....                    | 6  |
| 7   | Validation measurement .....                   | 7  |
| 7.1 | Head Liquid Measurement .....                  | 7  |
| 7.2 | SAR Measurement Result With Head Liquid .....  | 8  |
| 7.3 | Body Liquid Measurement .....                  | 9  |
| 7.4 | SAR Measurement Result With Body Liquid .....  | 10 |
| 8   | List of Equipment .....                        | 11 |

Page: 3/11

*This document shall not be reproduced, except in full or in part, without the written approval of MVG.  
The information contained herein is to be used only for the purpose for which it is submitted and is not to be released in whole or part without written approval of MVG.*



## SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.156.6.15.SATU.A

## 1 INTRODUCTION

This document contains a summary of the requirements set forth by the IEEE 1528, FCC KDBs and CEI/IEC 62209 standards for reference dipoles used for SAR measurement system validations and the measurements that were performed to verify that the product complies with the fore mentioned standards.

## 2 DEVICE UNDER TEST

| Device Under Test              |                                   |
|--------------------------------|-----------------------------------|
| Device Type                    | COMOSAR 1800 MHz REFERENCE DIPOLE |
| Manufacturer                   | MVG                               |
| Model                          | SID1800                           |
| Serial Number                  | SN 16/15 DIP 1G800-371            |
| Product Condition (new / used) | Used                              |

A yearly calibration interval is recommended.

## 3 PRODUCT DESCRIPTION

### 3.1 GENERAL INFORMATION

MVG's COMOSAR Validation Dipoles are built in accordance to the IEEE 1528, FCC KDBs and CEI/IEC 62209 standards. The product is designed for use with the COMOSAR test bench only.



Figure 1 – MVG COMOSAR Validation Dipole

Page: 4/11

*This document shall not be reproduced, except in full or in part, without the written approval of MVG.  
The information contained herein is to be used only for the purpose for which it is submitted and is not to be released in whole or part without written approval of MVG.*



#### 4 MEASUREMENT METHOD

The IEEE 1528, FCC KDBs and CEI/IEC 62209 standards provide requirements for reference dipoles used for system validation measurements. The following measurements were performed to verify that the product complies with the fore mentioned standards.

##### 4.1 RETURN LOSS REQUIREMENTS

The dipole used for SAR system validation measurements and checks must have a return loss of -20 dB or better. The return loss measurement shall be performed against a liquid filled flat phantom, with the phantom constructed as outlined in the fore mentioned standards.

##### 4.2 MECHANICAL REQUIREMENTS

The IEEE Std. 1528 and CEI/IEC 62209 standards specify the mechanical components and dimensions of the validation dipoles, with the dimensions frequency and phantom shell thickness dependent. The COMOSAR test bench employs a 2 mm phantom shell thickness therefore the dipoles sold for use with the COMOSAR test bench comply with the requirements set forth for a 2 mm phantom shell thickness.

#### 5 MEASUREMENT UNCERTAINTY

All uncertainties listed below represent an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of  $k=2$ , traceable to the Internationally Accepted Guides to Measurement Uncertainty.

##### 5.1 RETURN LOSS

The following uncertainties apply to the return loss measurement:

| Frequency band | Expanded Uncertainty on Return Loss |
|----------------|-------------------------------------|
| 400-6000MHz    | 0.1 dB                              |

##### 5.2 DIMENSION MEASUREMENT

The following uncertainties apply to the dimension measurements:

| Length (mm) | Expanded Uncertainty on Length |
|-------------|--------------------------------|
| 3 - 300     | 0.05 mm                        |

##### 5.3 VALIDATION MEASUREMENT

The guidelines outlined in the IEEE 1528, FCC KDBs, CENELEC EN50361 and CEI/IEC 62209 standards were followed to generate the measurement uncertainty for validation measurements.

| Scan Volume | Expanded Uncertainty |
|-------------|----------------------|
| 1 g         | 20.3 %               |

Page: 5/11

*This document shall not be reproduced, except in full or in part, without the written approval of MVG.  
The information contained herein is to be used only for the purpose for which it is submitted and is not to be released in whole or part without written approval of MVG.*