

STS

LAB



RADIO TEST REPORT

Report No.:STS2302096W01

Issued for

Shenzhen Liandian Communication Technology Co.LTD

402, No.2200161,Niuhu Community, Guanlan Street, Longhua District, Shenzhen, Guangdong Province, China

Product Name:	WIFI6 module
Brand:	N/A
Model Number:	LDTX-P18852E-V00
Series Model(s):	N/A
FCC ID:	2BAIP-P18852E
Test Standard:	FCC Part 15.247

Any reproduction of this document must be done in full. No single part of this document may be reproduced without permission from STS, all test data presented in this report is only applicable to presented test sample.

Shenzhen STS Test Services Co., Ltd.
A 1/F, Building B, Zhuoke Science Park, No.190 Chongqing Road, HepingShequ, Fuyong Sub-District, Bao'an District, Shenzhen, Guang Dong, China
TEL: +86-755 3688 6288 FAX: +86-755 3688 6277 E-mail:sts@stsapp.com





TEST RESULT CERTIFICATION

Applicant's Name: Shenzhen Liandian Communication Technology Co.LTD
Address: 402, No.2200161,Niuhu Community, Guanlan Street, Longhua District, Shenzhen, Guangdong Province, China
Manufacturer's Name: Shenzhen Liandian Communication Technology Co.LTD
Address: 402, No.2200161,Niuhu Community, Guanlan Street, Longhua District, Shenzhen, Guangdong Province, China

Product Description

Product Name: WIFI6 module
Brand: N/A
Model Number: LDTX-P18852E-V00
Series Model(s): N/A

Test Standards: FCC Part15.247

Test Procedure: ANSI C63.10-2013

This device described above has been tested by STS, the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of STS, this document may be altered or revised by STS, personal only, and shall be noted in the revision of the document.

Date of Test:


Date of receipt of test item: 15 Feb. 2023
Date (s) of performance of tests: 15 Feb. 2023 ~ 26 May. 2023
Date of Issue: 26 May. 2023
Test Result: **Pass**

Testing Engineer : 

(Chris Chen)

Technical Manager : 

(Sean she)

Authorized Signatory : 

(Bovey Yang)





Table of Contents

1. SUMMARY OF TEST RESULTS	6
1.1 TEST FACTORY	7
1.2 MEASUREMENT UNCERTAINTY	7
2. GENERAL INFORMATION	8
2.1 GENERAL DESCRIPTION OF THE EUT	8
2.2 DESCRIPTION OF THE TEST MODES	10
2.3 TEST SOFTWARE AND POWER LEVEL	10
2.4 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	11
2.5 DESCRIPTION OF NECESSARY ACCESSORIES AND SUPPORT UNITS	12
2.6 EQUIPMENTS LIST	13
3. EMC EMISSION TEST	14
3.1 CONDUCTED EMISSION MEASUREMENT	14
3.2 TEST PROCEDURE	15
3.3 TEST SETUP	15
3.4 EUT OPERATING CONDITIONS	15
3.5 TEST RESULTS	16
4. RADIATED EMISSION MEASUREMENT	18
4.1 RADIATED EMISSION LIMITS	18
4.2 TEST PROCEDURE	20
4.3 TEST SETUP	21
4.4 EUT OPERATING CONDITIONS	21
4.5 FIELD STRENGTH CALCULATION	22
4.6 TEST RESULTS	23
5. CONDUCTED SPURIOUS & BAND EDGE EMISSION	36
5.1 LIMIT	36
5.2 TEST PROCEDURE	36
5.3 TEST SETUP	36
5.4 EUT OPERATION CONDITIONS	36
5.5 TEST RESULTS	36
6. POWER SPECTRAL DENSITY TEST	37
6.1 LIMIT	37
6.2 TEST PROCEDURE	37
6.3 TEST SETUP	37



Table of Contents

6.4 EUT OPERATION CONDITIONS	37
6.5 TEST RESULTS	37
7. BANDWIDTH TEST	38
7.1 LIMIT	38
7.2 TEST PROCEDURE	38
7.3 TEST SETUP	38
7.4 EUT OPERATION CONDITIONS	38
7.5 TEST RESULTS	38
8. PEAK OUTPUT POWER TEST	39
8.1 LIMIT	39
8.2 TEST PROCEDURE	39
8.3 TEST SETUP	40
8.4 EUT OPERATION CONDITIONS	40
8.5 TEST RESULTS	40
9. ANTENNA REQUIREMENT	41
9.1 STANDARD REQUIREMENT	41
9.2 EUT ANTENNA	41
APPENDIX 1-TEST DATA	42
1. DUTY CYCLE	42
2. MAXIMUM AVERAGE CONDUCTED OUTPUT POWER	46
3. MAXIMUM PEAK CONDUCTED OUTPUT POWER	50
4. -6DB BANDWIDTH	54
5. MAXIMUM POWER SPECTRAL DENSITY LEVEL	58
6. BAND EDGE	62
7. CONDUCTED RF SPURIOUS EMISSION	67
APPENDIX 2- EUT TEST PHOTO	74

**Revision History**

Rev.	Issue Date	Report NO.	Effect Page	Contents
00	26 May. 2023	STS2302096W01	ALL	Initial Issue





1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:
KDB 558074 D01 15.247 Meas Guidance v05r02.

FCC Part 15.247, Subpart C			
Standard Section	Test Item	Judgment	Remark
15.207	Conducted Emission	PASS	--
15.247 (a)(2)	6dB Bandwidth	PASS	--
15.247 (b)(3)	Output Power	PASS	--
15.209	Radiated Spurious Emission	PASS	--
15.247 (d)	Conducted Spurious & Band Edge Emission	PASS	--
15.247 (e)	Power Spectral Density	PASS	--
15.205	Restricted bands of operation	PASS	--
Part 15.247(d)/ Part 15.209(a)	Band Edge Emission	PASS	--
15.203	Antenna Requirement	PASS	--

NOTE:

- (1) 'N/A' denotes test is not applicable in this Test Report.
- (2) All tests are according to ANSI C63.10-2013.



1.1 TEST FACTORY

SHENZHEN STS TEST SERVICES CO., LTD

Add. : A 1/F, Building B, Zhuoke Science Park, No.190 Chongqing Road, HepingShequ, Fuyong Sub-District, Bao'an District, Shenzhen, Guang Dong, China

FCC test Firm Registration Number: 625569

IC test Firm Registration Number: 12108A

A2LA Certificate No.: 4338.01

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of **k=2**, providing a level of confidence of approximately **95 %**.

No.	Item	Uncertainty
1	RF output power, conducted	$\pm 1.197\text{dB}$
2	Unwanted Emissions, conducted	$\pm 2.896\text{dB}$
3	All emissions, radiated 9K-30MHz	$\pm 3.84\text{dB}$
4	All emissions, radiated 30M-1GHz	$\pm 3.94\text{dB}$
5	All emissions, radiated 1G-6GHz	$\pm 4.59\text{dB}$
6	All emissions, radiated>6G	$\pm 5.22\text{dB}$
7	Conducted Emission (9KHz-150KHz)	$\pm 2.14\text{dB}$
8	Conducted Emission (150KHz-30MHz)	$\pm 2.54\text{dB}$



2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF THE EUT

Product Name	WIFI6 module															
Brand	N/A															
Model Number	LDTX-P18852E-V00															
Series Model(s)	N/A															
Model Difference	N/A															
Product Description	<p>The EUT is a WIFI6 module</p> <table border="1"><tr><td>Operation Frequency:</td><td>2402~2480 MHz</td></tr><tr><td>Modulation Type:</td><td>GFSK</td></tr><tr><td>Radio Technology:</td><td>BLE</td></tr><tr><td>Bluetooth Configuration:</td><td>LE(Support 1M PHY, 2M PHY)</td></tr><tr><td>Number Of Channel:</td><td>40</td></tr><tr><td>Antenna Type:</td><td>SMA Antenna</td></tr><tr><td>Antenna Gain (dBi)</td><td>5dBi</td></tr></table>		Operation Frequency:	2402~2480 MHz	Modulation Type:	GFSK	Radio Technology:	BLE	Bluetooth Configuration:	LE(Support 1M PHY, 2M PHY)	Number Of Channel:	40	Antenna Type:	SMA Antenna	Antenna Gain (dBi)	5dBi
Operation Frequency:	2402~2480 MHz															
Modulation Type:	GFSK															
Radio Technology:	BLE															
Bluetooth Configuration:	LE(Support 1M PHY, 2M PHY)															
Number Of Channel:	40															
Antenna Type:	SMA Antenna															
Antenna Gain (dBi)	5dBi															
Channel List	Please refer to the Note 3.															
Rating	Input: DC 3.3V 0.5A															
Hardware version number	V1.0															
Software version number	N/A															
Connecting I/O Port(s)	Please refer to the Note 1.															

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User Manual.
2. The antenna information refer the manufacturer provide report, applicable only to the tested sample identified in the report. Due to the incorrect antenna information, a series of problems such as the accuracy of the test results will be borne by the customer.



3.

Channel List							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
00	2402	10	2422	20	2442	30	2462
01	2404	11	2424	21	2444	31	2464
02	2406	12	2426	22	2446	32	2466
03	2408	13	2428	23	2448	33	2468
04	2410	14	2430	24	2450	34	2470
05	2412	15	2432	25	2452	35	2472
06	2414	16	2434	26	2454	36	2474
07	2416	17	2436	27	2456	37	2476
08	2418	18	2438	28	2458	38	2478
09	2420	19	2440	29	2460	39	2480



2.2 DESCRIPTION OF THE TEST MODES

For conducted test items and radiated spurious emissions

Each of these EUT operation mode(s) or test configuration mode(s) mentioned below was evaluated respectively.

Worst Mode	Description	Data/Modulation
Mode 1	TX CH00(2402MHz)	1 MHz/GFSK
Mode 2	TX CH19(2440MHz)	1 MHz/GFSK
Mode 3	TX CH39(2480MHz)	1 MHz/GFSK

Worst Mode	Description	Data/Modulation
Mode 4	TX CH00(2402MHz)	2M PHY /GFSK
Mode 5	TX CH19(2440MHz)	2M PHY /GFSK
Mode 6	TX CH39(2480MHz)	2M PHY /GFSK

Note:

- (1) The measurements are performed at all Bit Rate of Transmitter, the worst data was reported.
- (2) We have been tested for all available U.S. voltage and frequencies (For 120V, 50/60Hz and 240V, 50/60Hz) for which the device is capable of operation, and the worst case of 120V/60Hz is shown in the report.
- (3) The battery is fully-charged during the radiated and RF conducted test.

For AC Conducted Emission

Test Case	
AC Conducted Emission	Mode 7 : Keeping BT TX


2.3 TEST SOFTWARE AND POWER LEVEL

During testing channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level.


RF Function	Type	Mode Or Modulation type	ANT Gain(dBi)	Power Class	Software For Testing
BLE(With 2M PHY)	BLE_1M PHY	GFSK	5	default	bluetooth RF Test Tool
	BLE_2M PHY	GFSK	5	default	

2.4 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

Radiated Spurious Emission Test



Conducted Emission Test





2.5 DESCRIPTION OF NECESSARY ACCESSORIES AND SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Necessary accessories

Item	Equipment	Mfr/Brand	Model/Type No.	Length	Note
N/A	N/A	N/A	N/A	N/A	N/A

Support units

Item	Equipment	Mfr/Brand	Model/Type No.	Length	Note
E-1	Personal computer	HP	500-320cx	N/A	N/A
E-2	Notebook Adapter	LENOVO	ADLX45DLC3A	N/A	N/A
C-1	USB Cable	N/A	N/A	150cm	NO

Note:

- (1) For detachable type I/O cable should be specified the length in cm in『Length』column.
- (2) "YES" is means "with core"; "NO" is means "without core".



2.6 EQUIPMENTS LIST

RF Radiation Test Equipment					
Kind of Equipment	Manufacturer	Type No.	Serial No.	Last Calibration	Calibrated Until
Temperature & Humidity	SW-108	SuWei	N/A	2023.03.01	2024.02.28
Pre-Amplifier (0.1M-3GHz)	EM	EM330	060665	2022.07.04	2023.07.03
Pre-Amplifier (1G-18GHz)	SKET	LNPA-01018G-45	SK2018080901	2022.09.29	2023.09.28
Pre-amplifier (18G-40G)	SKET	LNPA_1840-50	SK2018101801	2022.07.23	2023.07.22
Positioning Controller	MF	MF-7802	MF-780208587	N/A	N/A
Signal Analyzer	R&S	FSV 40-N	101823	2022.09.29	2023.09.28
Switch Control Box	N/A	N/A	N/A	N/A	N/A
Filter Box	BALUN Technology	SU319E	BL-SZ1530051	N/A	N/A
Active loop Antenna	ZHINAN	ZN30900C	16035	2023.02.28	2024.02.27
Bilog Antenna	TESEQ	CBL6111D	34678	2022.09.30	2024.09.29
Horn Antenna	SCHWARZBECK	BBHA 9120D	02014	2021.10.11	2023.10.10
Horn Antenna	A-INFOMW	LB-180400-KF	J211020657	2021.09.28	2023.09.27
Antenna Mast	MF	MFA-440H	N/A	N/A	N/A
Turn Table	MF	SC100_1	60531	N/A	N/A
AC Power Source	APC	KDF-11010G	F214050035	N/A	N/A
DC Power Supply	Zhaoxin	RXN 605D	20R605D11010081	N/A	N/A
Test SW	EZ-EMC	Ver.STSLAB-03A1 RE			
Conduction Test equipment					
Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
Test Receiver	R&S	ESCI	101427	2022.09.29	2023.09.28
LISN	R&S	ENV216	101242	2022.09.28	2023.09.27
LISN	EMCO	3810/2NM	23625	2022.09.28	2023.09.27
Temperature & Humidity	HH660	Mieo	N/A	2022.09.30	2023.09.29
Test SW	EZ-EMC	Ver.STSLAB-03A1 CE			
RF Connected Test					
Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
Signal Analyzer	Agilent	N9020A	MY51510623	2023.03.01	2024.02.28
Switch control box	MW	MW100-RFCB	N/A	N/A	N/A
Temperature & Humidity	HH660	Mieo	N/A	2022.09.30	2023.09.29
Test SW	MW	MTS 8310_2.0.0.0			



3. EMC EMISSION TEST

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 POWER LINE CONDUCTED EMISSION LIMITS

The radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table.

FREQUENCY (MHz)	Conducted Emission limit (dBuV)	
	Quasi-peak	Average
0.15 -0.5	66 - 56 *	56 - 46 *
0.50 -5.0	56.00	46.00
5.0 -30.0	60.00	50.00

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of “ * ” marked band means the limitation decreases linearly with the logarithm of the frequency in the range.


The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

3.2 TEST PROCEDURE

- a. The EUT is 0.8 m from the horizontal ground plane and 0.4 m from the vertical ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments are powered from additional LISN(s). The LISN provides 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN is at least 80 cm from the nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

3.3 TEST SETUP



Note:

1. Support units were connected to second LISN.
2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes support units.

3.4 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.




3.5 TEST RESULTS

Temperature:	21.7(C)	Relative Humidity:	42%RH
Test Voltage:	AC 120V/60Hz	Phase:	L
Test Mode:	Mode 7		

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(d B)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.3020	12.05	10.75	22.80	60.19	-37.39	QP
2	0.3020	5.23	10.75	15.98	50.19	-34.21	AVG
3	0.8100	20.97	10.33	31.30	56.00	-24.70	QP
4	0.8100	15.65	10.33	25.98	46.00	-20.02	AVG
5	1.6260	14.57	10.30	24.87	56.00	-31.13	QP
6	1.6260	6.44	10.30	16.74	46.00	-29.26	AVG
7	2.4060	14.91	10.32	25.23	56.00	-30.77	QP
8	2.4060	7.01	10.32	17.33	46.00	-28.67	AVG
9	4.7500	14.78	10.45	25.23	56.00	-30.77	QP
10	4.7500	5.17	10.45	15.62	46.00	-30.38	AVG
11	11.3300	14.61	11.34	25.95	60.00	-34.05	QP
12	11.3300	-0.72	11.34	10.62	50.00	-39.38	AVG

Remark:

1. All readings are Quasi-Peak and Average values
2. Margin = Result (Result =Reading + Factor)–Limit
3. Factor=LISN factor+Cable loss+Limiter (10dB)






Temperature:	21.7(C)	Relative Humidity:	42%RH
Test Voltage:	AC 120V/60Hz	Phase:	N
Test Mode:	Mode 7		

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(d B)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1700	10.37	10.34	20.71	64.96	-44.25	QP
2	0.1700	2.02	10.34	12.36	54.96	-42.60	AVG
3	0.2980	12.17	10.78	22.95	60.30	-37.35	QP
4	0.2980	5.61	10.78	16.39	50.30	-33.91	AVG
5	0.8020	21.05	10.35	31.40	56.00	-24.60	QP
6	0.8020	15.45	10.35	25.80	46.00	-20.20	AVG
7	1.2380	14.85	10.32	25.17	56.00	-30.83	QP
8	1.2380	6.77	10.32	17.09	46.00	-28.91	AVG
9	2.4860	15.12	10.41	25.53	56.00	-30.47	QP
10	2.4860	6.95	10.41	17.36	46.00	-28.64	AVG
11	6.0820	15.86	10.55	26.41	60.00	-33.59	QP
12	6.0820	6.09	10.55	16.64	50.00	-33.36	AVG

Remark:

1. All readings are Quasi-Peak and Average values
2. Margin = Result (Result =Reading + Factor)–Limit
3. Factor=LISN factor+Cable loss+Limiter (10dB)





4. RADIATED EMISSION MEASUREMENT

4.1 RADIATED EMISSION LIMITS

In any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the Restricted band specified on Part15.205(a)&209(a) limit in the table and according to ANSI C63.10-2013 below has to be followed.

LIMITS OF RADIATED EMISSION MEASUREMENT (Frequency Range 9kHz-1000MHz)

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	(dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

LIMITS OF RESTRICTED FREQUENCY BANDS

FREQUENCY (MHz)	FREQUENCY (MHz)	FREQUENCY (MHz)	FREQUENCY (GHz)
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	Above 38.6
13.36-13.41			



For Radiated Emission

Spectrum Parameter	Setting
Attenuation	Auto
Detector	Peak/QP/AV
Start Frequency	9 KHz/150KHz(Peak/QP/AV)
Stop Frequency	150KHz/30MHz(Peak/QP/AV)
RB / VB (emission in restricted band)	200Hz (From 9kHz to 0.15MHz)/ 9KHz (From 0.15MHz to 30MHz); 200Hz (From 9kHz to 0.15MHz)/ 9KHz (From 0.15MHz to 30MHz)

Spectrum Parameter	Setting
Attenuation	Auto
Detector	Peak/QP
Start Frequency	30 MHz(Peak/QP)
Stop Frequency	1000 MHz (Peak/QP)
RB / VB (emission in restricted band)	120 KHz / 300 KHz

Spectrum Parameter	Setting
Attenuation	Auto
Detector	Peak/AV
Start Frequency	1000 MHz(Peak/AV)
Stop Frequency	10th carrier harmonic(Peak/AV)
RB / VB (emission in restricted band)	1 MHz / 3 MHz(Peak) 1 MHz/1/T MHz(AVG)

For Restricted band

Spectrum Parameter	Setting
Detector	Peak/AV
Start/Stop Frequency	Lower Band Edge: 2310 to 2410 MHz Upper Band Edge: 2475 to 2500 MHz
RB / VB	1 MHz / 3 MHz(Peak) 1 MHz/1/T MHz(AVG)



Receiver Parameter	Setting
Start ~ Stop Frequency	9kHz~90kHz / RB 200Hz for PK & AV
Start ~ Stop Frequency	90kHz~110kHz / RB 200Hz for QP
Start ~ Stop Frequency	110kHz~490kHz / RB 200Hz for PK & AV
Start ~ Stop Frequency	490kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

4.2 TEST PROCEDURE


- a. The measuring distance at 3 m shall be used for measurements at frequency 0.009MHz up to 1GHz, and above 1GHz.
- b. The EUT was placed on the top of a rotating table 0.8 m (above 1GHz is 1.5 m) above the ground at a 3 m anechoic chamber test site. The table was rotated 360 degree to determine the position of the highest radiation.
- c. The height of the equipment shall be 0.8 m (above 1GHz is 1.5 m); the height of the test antenna shall vary between 1 m to 4 m. Horizontal and vertical polarization of the antenna are set to make the measurement.
- d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and QuasiPeak detector mode will be re-measured.
- e. If the Peak Mode measured value is compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and no additional QP Mode measurement was performed.
- f. For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note:


Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported.

4.3 TEST SETUP


(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



(C) Radiated Emission Test-Up Frequency Above 1GHz



4.4 EUT OPERATING CONDITIONS

Please refer to section 3.4 of this report.



4.5 FIELD STRENGTH CALCULATION

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor (if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CL - AG$$

Where

FS = Field Strength

CL = Cable Attenuation Factor (Cable Loss)

RA = Reading Amplitude

AG = Amplifier Gain

AF = Antenna Factor

For example

Frequency (MHz)	FS (dB μ V/m)	RA (dB μ V/m)	AF (dB)	CL (dB)	AG (dB)	Factor (dB)
300	40	58.1	12.2	1.6	31.9	-18.1

$$\text{Factor} = AF + CL - AG$$



4.6 TEST RESULTS

(Between 9KHz – 30 MHz)

Temperature:	23.1(C)	Relative Humidity:	60%RH
Test Voltage:	DC 3.3V	Polarization:	--
Test Mode:	TX Mode		

Freq.	Reading	Limit	Margin	State
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F
--	--	--	--	PASS
--	--	--	--	PASS

Note:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor = $40 \log (\text{specific distance}/\text{test distance})$ (dB);
Limit line = specific limits(dBuv) + distance extrapolation factor.



(30MHz -1000MHz)


1M PHY

Temperature:	23.1(C)	Relative Humidity:	60%RH
Test Voltage:	DC 3.3V	Phase:	Horizontal
Test Mode:	Mode 1/2/3/4/5/6 (Mode 5 worst mode)		

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/ m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	139.6100	51.97	-18.02	33.95	43.50	-9.55	peak
2	288.0200	50.70	-15.26	35.44	46.00	-10.56	peak
3	445.1600	46.59	-9.87	36.72	46.00	-9.28	peak
4	647.8900	40.54	-4.88	35.66	46.00	-10.34	peak
5	817.6400	38.84	-1.97	36.87	46.00	-9.13	peak
6	976.7200	35.75	2.45	38.20	54.00	-15.80	peak

Remark:

- Margin = Result (Result =Reading + Factor)-Limit
- Factor= Antenna factor+Cable attenuation factor(cable loss)-Amplifier gain






Temperature:	23.1(C)	Relative Humidity:	60%RH
Test Voltage:	DC 3.3V	Phase:	Vertical
Test Mode:	Mode 1/2/3/4/5/6 (Mode 5 worst mode)		

No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	Factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	84.3200	54.59	-22.35	32.24	40.00	-7.76	peak
2	207.5100	55.34	-20.54	34.80	43.50	-8.70	peak
3	385.9900	47.67	-11.86	35.81	46.00	-10.19	peak
4	494.6300	45.47	-8.12	37.35	46.00	-8.65	peak
5	798.2400	38.77	-2.03	36.74	46.00	-9.26	peak
6	891.3600	38.38	-0.66	37.72	46.00	-8.28	peak

Remark:

- Margin = Result (Result =Reading + Factor)-Limit
- Factor= Antenna factor+Cable attenuation factor(cable loss)-Amplifier gain






2M PHY

Temperature:	23.1(C)	Relative Humidity:	60%RH
Test Voltage:	DC 3.3V	Phase:	Horizontal
Test Mode:	Mode 1/2/3/4/5/6 (Mode 5 worst mode)		

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/ m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	139.6100	51.94	-18.02	33.92	43.50	-9.58	peak
2	296.7500	51.20	-14.92	36.28	46.00	-9.72	peak
3	445.1600	44.62	-9.87	34.75	46.00	-11.25	peak
4	510.1500	45.22	-7.94	37.28	46.00	-8.72	peak
5	672.1400	40.10	-4.52	35.58	46.00	-10.42	peak
6	799.2100	39.74	-2.04	37.70	46.00	-8.30	peak

Remark:

- Margin = Result (Result =Reading + Factor)-Limit
- Factor= Antenna factor+Cable attenuation factor(cable loss)-Amplifier gain






Temperature:	23.1(C)	Relative Humidity:	60%RH
Test Voltage:	DC 3.3V	Phase:	Vertical
Test Mode:	Mode 1/2/3/4/5/6 (Mode 5 worst mode)		

No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	Factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	83.3500	53.69	-22.52	31.17	40.00	-8.83	peak
2	296.7500	48.75	-14.92	33.83	46.00	-12.17	peak
3	445.1600	46.50	-9.87	36.63	46.00	-9.37	peak
4	594.5400	41.34	-5.84	35.50	46.00	-10.50	peak
5	799.2100	38.73	-2.04	36.69	46.00	-9.31	peak
6	935.9800	37.47	1.04	38.51	46.00	-7.49	peak

Remark:

1. Margin = Result (Result =Reading + Factor)-Limit
2. Factor= Antenna factor+Cable attenuation factor(cable loss)-Amplifier gain





(1GHz-25GHz) Spurious emission Requirements

1M PHY
GFSK

Frequency (MHz)	Meter Reading (dB μ V)	Amplifier (dB)	Loss (dB)	Antenna Factor (dB/m)	Corrected Factor (dB)	Emission Level (dB μ V/m)	Limits (dB μ V/m)	Margin (dB)	Detector Type	Comment
Low Channel (GFSK/2402 MHz)										
3264.70	62.22	44.70	6.70	28.20	-9.80	52.42	74.00	-21.58	PK	Vertical
3264.70	50.42	44.70	6.70	28.20	-9.80	40.62	54.00	-13.38	AV	Vertical
3264.71	61.27	44.70	6.70	28.20	-9.80	51.47	74.00	-22.53	PK	Horizontal
3264.71	50.77	44.70	6.70	28.20	-9.80	40.97	54.00	-13.03	AV	Horizontal
4804.49	58.79	44.20	9.04	31.60	-3.56	55.23	74.00	-18.77	PK	Vertical
4804.49	50.14	44.20	9.04	31.60	-3.56	46.58	54.00	-7.42	AV	Vertical
4804.32	58.84	44.20	9.04	31.60	-3.56	55.28	74.00	-18.72	PK	Horizontal
4804.32	50.15	44.20	9.04	31.60	-3.56	46.59	54.00	-7.41	AV	Horizontal
5359.74	49.38	44.20	9.86	32.00	-2.34	47.04	74.00	-26.96	PK	Vertical
5359.74	39.42	44.20	9.86	32.00	-2.34	37.07	54.00	-16.93	AV	Vertical
5359.74	48.38	44.20	9.86	32.00	-2.34	46.04	74.00	-27.96	PK	Horizontal
5359.74	38.47	44.20	9.86	32.00	-2.34	36.13	54.00	-17.87	AV	Horizontal
7205.74	54.61	43.50	11.40	35.50	3.40	58.01	74.00	-15.99	PK	Vertical
7205.74	43.92	43.50	11.40	35.50	3.40	47.32	54.00	-6.68	AV	Vertical
7205.76	54.87	43.50	11.40	35.50	3.40	58.27	74.00	-15.73	PK	Horizontal
7205.76	44.37	43.50	11.40	35.50	3.40	47.77	54.00	-6.23	AV	Horizontal
Middle Channel (GFSK/2440 MHz)										
3263.08	61.40	44.70	6.70	28.20	-9.80	51.60	74.00	-22.40	PK	Vertical
3263.08	50.81	44.70	6.70	28.20	-9.80	41.01	54.00	-12.99	AV	Vertical
3262.96	61.53	44.70	6.70	28.20	-9.80	51.73	74.00	-22.27	PK	Horizontal
3262.96	50.38	44.70	6.70	28.20	-9.80	40.58	54.00	-13.42	AV	Horizontal
4880.04	58.41	44.20	9.04	31.60	-3.56	54.85	74.00	-19.15	PK	Vertical
4880.04	49.35	44.20	9.04	31.60	-3.56	45.79	54.00	-8.21	AV	Vertical
4880.12	58.32	44.20	9.04	31.60	-3.56	54.76	74.00	-19.24	PK	Horizontal
4880.12	49.22	44.20	9.04	31.60	-3.56	45.66	54.00	-8.34	AV	Horizontal
5357.19	48.48	44.20	9.86	32.00	-2.34	46.14	74.00	-27.86	PK	Vertical
5357.19	39.80	44.20	9.86	32.00	-2.34	37.45	54.00	-16.55	AV	Vertical
5357.39	48.49	44.20	9.86	32.00	-2.34	46.15	74.00	-27.85	PK	Horizontal
5357.05	39.42	44.20	9.86	32.00	-2.34	37.08	54.00	-16.92	AV	Horizontal
7320.85	53.98	43.50	11.40	35.50	3.40	57.38	74.00	-16.62	PK	Vertical
7320.85	44.97	43.50	11.40	35.50	3.40	48.37	54.00	-5.63	AV	Vertical
7320.45	53.58	43.50	11.40	35.50	3.40	56.98	74.00	-17.02	PK	Horizontal
7320.45	44.91	43.50	11.40	35.50	3.40	48.31	54.00	-5.69	AV	Horizontal



High Channel (GFSK/2480 MHz)										
3264.77	61.43	44.70	6.70	28.20	-9.80	51.63	74.00	-22.37	PK	Vertical
3264.77	50.12	44.70	6.70	28.20	-9.80	40.32	54.00	-13.68	AV	Vertical
3264.67	61.24	44.70	6.70	28.20	-9.80	51.44	74.00	-22.56	PK	Horizontal
3264.67	50.28	44.70	6.70	28.20	-9.80	40.48	54.00	-13.52	AV	Horizontal
4960.44	58.93	44.20	9.04	31.60	-3.56	55.37	74.00	-18.63	PK	Vertical
4960.44	49.28	44.20	9.04	31.60	-3.56	45.72	54.00	-8.28	AV	Vertical
4960.56	58.27	44.20	9.04	31.60	-3.56	54.71	74.00	-19.29	PK	Horizontal
4960.56	49.41	44.20	9.04	31.60	-3.56	45.85	54.00	-8.15	AV	Horizontal
5359.77	48.74	44.20	9.86	32.00	-2.34	46.39	74.00	-27.61	PK	Vertical
5359.77	39.52	44.20	9.86	32.00	-2.34	37.18	54.00	-16.82	AV	Vertical
5359.75	47.22	44.20	9.86	32.00	-2.34	44.87	74.00	-29.13	PK	Horizontal
5359.75	38.04	44.20	9.86	32.00	-2.34	35.70	54.00	-18.30	AV	Horizontal
7439.96	54.91	43.50	11.40	35.50	3.40	58.31	74.00	-15.69	PK	Vertical
7439.96	44.55	43.50	11.40	35.50	3.40	47.95	54.00	-6.05	AV	Vertical
7439.70	54.60	43.50	11.40	35.50	3.40	58.00	74.00	-16.00	PK	Horizontal
7439.70	44.47	43.50	11.40	35.50	3.40	47.87	54.00	-6.13	AV	Horizontal

Note:

1) Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Emission Level = Reading + Factor.

2) The frequency emission of peak points that did not show above the forms are at least 20dB below the limit, the frequency emission is mainly from the environment noise.



2M PHY GFSK

Frequency (MHz)	Meter Reading (dB μ V)	Amplifier (dB)	Loss (dB)	Antenna Factor (dB/m)	Corrected Factor (dB)	Emission Level (dB μ V/m)	Limits (dB μ V/m)	Margin (dB)	Detector Type	Comment
Low Channel (GFSK/2402 MHz)										
3264.76	61.20	44.70	6.70	28.20	-9.80	51.40	74.00	-22.60	PK	Vertical
3264.76	51.32	44.70	6.70	28.20	-9.80	41.52	54.00	-12.48	AV	Vertical
3264.76	61.88	44.70	6.70	28.20	-9.80	52.08	74.00	-21.92	PK	Horizontal
3264.76	50.05	44.70	6.70	28.20	-9.80	40.25	54.00	-13.75	AV	Horizontal
4804.54	58.21	44.20	9.04	31.60	-3.56	54.65	74.00	-19.35	PK	Vertical
4804.54	49.59	44.20	9.04	31.60	-3.56	46.03	54.00	-7.97	AV	Vertical
4804.40	59.04	44.20	9.04	31.60	-3.56	55.48	74.00	-18.52	PK	Horizontal
4804.40	50.32	44.20	9.04	31.60	-3.56	46.76	54.00	-7.24	AV	Horizontal
5359.72	48.97	44.20	9.86	32.00	-2.34	46.63	74.00	-27.37	PK	Vertical
5359.72	39.09	44.20	9.86	32.00	-2.34	36.75	54.00	-17.25	AV	Vertical
5359.63	47.33	44.20	9.86	32.00	-2.34	44.98	74.00	-29.02	PK	Horizontal
5359.63	39.43	44.20	9.86	32.00	-2.34	37.09	54.00	-16.91	AV	Horizontal
7205.68	54.04	43.50	11.40	35.50	3.40	57.44	74.00	-16.56	PK	Vertical
7205.68	43.80	43.50	11.40	35.50	3.40	47.20	54.00	-6.80	AV	Vertical
7205.87	53.58	43.50	11.40	35.50	3.40	56.98	74.00	-17.02	PK	Horizontal
7205.87	44.96	43.50	11.40	35.50	3.40	48.36	54.00	-5.64	AV	Horizontal
Middle Channel (GFSK/2440 MHz)										
3263.03	60.90	44.70	6.70	28.20	-9.80	51.10	74.00	-22.90	PK	Vertical
3263.03	50.43	44.70	6.70	28.20	-9.80	40.63	54.00	-13.37	AV	Vertical
3263.21	61.98	44.70	6.70	28.20	-9.80	52.18	74.00	-21.82	PK	Horizontal
3263.21	51.27	44.70	6.70	28.20	-9.80	41.47	54.00	-12.53	AV	Horizontal
4879.87	58.55	44.20	9.04	31.60	-3.56	54.99	74.00	-19.01	PK	Vertical
4879.87	49.62	44.20	9.04	31.60	-3.56	46.06	54.00	-7.94	AV	Vertical
4880.16	58.81	44.20	9.04	31.60	-3.56	55.25	74.00	-18.75	PK	Horizontal
4880.16	49.78	44.20	9.04	31.60	-3.56	46.22	54.00	-7.78	AV	Horizontal
5357.18	49.34	44.20	9.86	32.00	-2.34	46.99	74.00	-27.01	PK	Vertical
5357.18	39.49	44.20	9.86	32.00	-2.34	37.14	54.00	-16.86	AV	Vertical
5357.39	47.88	44.20	9.86	32.00	-2.34	45.54	74.00	-28.46	PK	Horizontal
5357.11	39.09	44.20	9.86	32.00	-2.34	36.75	54.00	-17.25	AV	Horizontal
7320.85	54.09	43.50	11.40	35.50	3.40	57.49	74.00	-16.51	PK	Vertical
7320.85	44.65	43.50	11.40	35.50	3.40	48.05	54.00	-5.95	AV	Vertical
7320.41	54.24	43.50	11.40	35.50	3.40	57.64	74.00	-16.36	PK	Horizontal
7320.41	43.97	43.50	11.40	35.50	3.40	47.37	54.00	-6.63	AV	Horizontal



High Channel (GFSK/2480 MHz)										
3264.79	61.99	44.70	6.70	28.20	-9.80	52.19	74.00	-21.81	PK	Vertical
3264.79	50.35	44.70	6.70	28.20	-9.80	40.55	54.00	-13.45	AV	Vertical
3264.77	62.05	44.70	6.70	28.20	-9.80	52.25	74.00	-21.75	PK	Horizontal
3264.77	51.19	44.70	6.70	28.20	-9.80	41.39	54.00	-12.61	AV	Horizontal
4960.36	58.79	44.20	9.04	31.60	-3.56	55.23	74.00	-18.77	PK	Vertical
4960.36	50.39	44.20	9.04	31.60	-3.56	46.83	54.00	-7.17	AV	Vertical
4960.38	59.48	44.20	9.04	31.60	-3.56	55.92	74.00	-18.08	PK	Horizontal
4960.38	49.37	44.20	9.04	31.60	-3.56	45.81	54.00	-8.19	AV	Horizontal
5359.79	48.07	44.20	9.86	32.00	-2.34	45.73	74.00	-28.27	PK	Vertical
5359.79	39.44	44.20	9.86	32.00	-2.34	37.09	54.00	-16.91	AV	Vertical
5359.60	47.77	44.20	9.86	32.00	-2.34	45.43	74.00	-28.57	PK	Horizontal
5359.60	38.45	44.20	9.86	32.00	-2.34	36.10	54.00	-17.90	AV	Horizontal
7439.85	53.83	43.50	11.40	35.50	3.40	57.23	74.00	-16.77	PK	Vertical
7439.85	44.11	43.50	11.40	35.50	3.40	47.51	54.00	-6.49	AV	Vertical
7439.70	54.48	43.50	11.40	35.50	3.40	57.88	74.00	-16.12	PK	Horizontal
7439.70	43.81	43.50	11.40	35.50	3.40	47.21	54.00	-6.79	AV	Horizontal

Note:

1) Factor = Antenna Factor + Cable Loss – Pre-amplifier.


Emission Level = Reading + Factor.

2) The frequency emission of peak points that did not show above the forms are at least 20dB below the limit, the frequency emission is mainly from the environment noise.




4.6 TEST RESULTS (Restricted Bands Requirements)

1M PHY
GFSK-Low
Horizontal



No.	Frequency (MHz)	Reading (dB _{uV})	Correct Factor(dB/m)	Result (dB _{uV/m})	Limit (dB _{uV/m})	Margin (dB)	Remark
1	2359.100	47.13	3.88	51.01	74.00	-22.99	peak
2	2390.000	38.90	4.34	43.24	74.00	-30.76	peak

Vertical




No.	Frequency (MHz)	Reading (dB _{uV})	Correct Factor(dB/m)	Result (dB _{uV/m})	Limit (dB _{uV/m})	Margin (dB)	Remark
1	2383.600	45.10	4.24	49.34	74.00	-24.66	peak
2	2390.000	46.45	4.34	50.79	74.00	-23.21	peak




GFSK-High

Horizontal



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	40.47	4.60	45.07	74.00	-28.93	peak
2	2488.750	41.63	4.62	46.25	74.00	-27.75	peak


Vertical



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	55.76	4.60	60.36	74.00	-13.64	peak
2	2483.500	29.87	4.60	34.47	54.00	-19.53	AVG
3	2487.825	49.81	4.62	54.43	74.00	-19.57	peak
4	2487.825	28.64	4.62	33.26	54.00	-20.74	AVG




2M PHY
GFSK-Low
Horizontal



No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dB _{uV})	Factor(dB/m)	(dB _{uV/m})	(dB _{uV/m})	(dB)	
1	2356.400	47.04	3.83	50.87	74.00	-23.13	peak
2	2390.000	40.98	4.34	45.32	74.00	-28.68	peak

Vertical




No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dB _{uV})	Factor(dB/m)	(dB _{uV/m})	(dB _{uV/m})	(dB)	
1	2386.300	46.24	4.28	50.52	74.00	-23.48	peak
2	2390.000	40.01	4.34	44.35	74.00	-29.65	peak




GFSK-High

Horizontal



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	48.89	4.60	53.49	74.00	-20.51	peak
2	2486.375	45.65	4.61	50.26	74.00	-23.74	peak

Vertical



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	47.56	4.60	52.16	74.00	-21.84	peak
2	2485.575	46.93	4.61	51.54	74.00	-22.46	peak

5. CONDUCTED SPURIOUS & BAND EDGE EMISSION

5.1 LIMIT

According to FCC section 15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

5.2 TEST PROCEDURE

Spectrum Parameter	Setting
Detector	Peak
Start/Stop Frequency	30 MHz to 10th carrier harmonic
RB / VB (emission in restricted band)	100 KHz/300 KHz
Trace-Mode:	Max hold

For Band edge

Spectrum Parameter	Setting
Detector	Peak
Start/Stop Frequency	Lower Band Edge: 2300 – 2407 MHz Upper Band Edge: 2475 – 2500 MHz
RB / VB (emission in restricted band)	100 KHz/300 KHz
Trace-Mode:	Max hold

5.3 TEST SETUP



The EUT is connected to the Spectrum Analyzer; the RF load attached to the EUT antenna terminal is 50 Ohm; the path loss as the factor is calibrated to correct the reading. Make the measurement with the spectrum analyzer's resolution bandwidth(RBW) = 100 kHz. In order to make an accurate measurement, set the span greater than RBW.

5.4 EUT OPERATION CONDITIONS

Please refer to section 3.4 of this report.

5.5 TEST RESULTS

Note: The test data please refer to APPENDIX 1.



6. POWER SPECTRAL DENSITY TEST

6.1 LIMIT

FCC Part 15.247,Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(e)	Power Spectral Density	$\leq 8 \text{ dBm}$ (RBW $\geq 3 \text{ kHz}$)	2400-2483.5	PASS

6.2 TEST PROCEDURE

1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to 1.5 times the DTS channel bandwidth.
3. Set the RBW to: $100 \text{ kHz} \geq \text{RBW} \geq 3 \text{ kHz}$.
4. Set the VBW $\geq 3 \times \text{RBW}$.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

6.3 TEST SETUP



6.4 EUT OPERATION CONDITIONS

Please refer to section 3.4 of this report.

6.5 TEST RESULTS

Note: The test data please refer to APPENDIX 1.



7. BANDWIDTH TEST

7.1 LIMIT

FCC Part 15.247, Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(a)(2)	Bandwidth	>= 500KHz (6dB bandwidth)	2400-2483.5	PASS

7.2 TEST PROCEDURE

The automatic bandwidth measurement capability of an instrument may be employed using the X dB bandwidth mode with X set to 6 dB, if the functionality described above (i.e., RBW = 100 kHz, $VBW \geq 3RBW$, peak detector with maximum hold) is implemented by the instrumentation function. When using this capability, care shall be taken so that the bandwidth measurement is not influenced by any intermediate power nulls in the fundamental emission that might be ≥ 6 dB.

7.3 TEST SETUP



7.4 EUT OPERATION CONDITIONS

Please refer to section 3.4 of this report.

7.5 TEST RESULTS

Note: The test data please refer to APPENDIX 1.



8. PEAK OUTPUT POWER TEST

8.1 LIMIT

FCC Part 15.247, Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(b)(3)	Output Power	1 watt or 30dBm	2400-2483.5	PASS

8.2 TEST PROCEDURE

One of the following procedures may be used to determine the maximum peak conducted output power of a DTS EUT.

RBW \geq DTS bandwidth

The following procedure shall be used when an instrument with a resolution bandwidth that is greater than the DTS bandwidth is available to perform the measurement:

- a) Set the RBW \geq DTS bandwidth.
- b) Set VBW \geq [3 \times RBW].
- c) Set span \geq [3 \times RBW].
- d) Sweep time = auto couple.
- e) Detector = peak.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use peak marker function to determine the peak amplitude level.

Integrated band power method:

The following procedure can be used when the maximum available RBW of the instrument is less than the DTS bandwidth:


- a) Set the RBW = 1 MHz.
- b) Set the VBW \geq [3 \times RBW].
- c) Set the span \geq [1.5 \times DTS bandwidth].
- d) Detector = peak.
- e) Sweep time = auto couple.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.

h) Use the instrument's band/channel power measurement function with the band limits set equal to the DTS bandwidth edges (for some instruments, this may require a manual override to select the peak detector). If the instrument does not have a band power function, then sum the spectrum levels (in linear power units) at intervals equal to the RBW extending across the DTS channel bandwidth.

PKPM1 Peak power meter method:

The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall use a fast-responding diode detector.

8.3 TEST SETUP



8.4 EUT OPERATION CONDITIONS

Please refer to section 3.4 of this report.

8.5 TEST RESULTS

Note: The test data please refer to APPENDIX 1.



9. ANTENNA REQUIREMENT

9.1 STANDARD REQUIREMENT

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

9.2 EUT ANTENNA

The EUT antenna is SMA Antenna. It comply with the standard requirement.






APPENDIX 1-TEST DATA


1. Duty Cycle

Condition	Mode	Frequency (MHz)	Duty Cycle (%)	Correction Factor (dB)	1/T (kHz)
NVNT	BLE 1M	2402	63.12	2	2.53
NVNT	BLE 1M	2440	63.12	2	2.53
NVNT	BLE 1M	2480	63.12	2	2.53
NVNT	BLE 2M	2402	33.44	4.76	4.78
NVNT	BLE 2M	2440	33.49	4.75	4.77
NVNT	BLE 2M	2480	33.52	4.75	4.77






Duty Cycle NVNT BLE 1M 2480MHz




Duty Cycle NVNT BLE 2M 2402MHz






Duty Cycle NVNT BLE 2M 2440MHz



Duty Cycle NVNT BLE 2M 2480MHz








2. Maximum Average Conducted Output Power

Condition	Mode	Frequency (MHz)	Conducted Power (dBm)	Duty Factor (dB)	Total Power (dBm)	Limit (dBm)	Verdict
NVNT	BLE 1M	2402	-4.27	2	-2.27	<=30	Pass
NVNT	BLE 1M	2440	-2.42	2	-0.42	<=30	Pass
NVNT	BLE 1M	2480	-3.07	2	-1.07	<=30	Pass
NVNT	BLE 2M	2402	-4.43	4.76	0.33	<=30	Pass
NVNT	BLE 2M	2440	-3.56	4.75	1.19	<=30	Pass
NVNT	BLE 2M	2480	-3.6	4.75	1.15	<=30	Pass











3. Maximum Peak Conducted Output Power


Condition	Mode	Frequency (MHz)	Conducted Power (dBm)	Limit (dBm)	Verdict
NVNT	BLE 1M	2402	1.54	<=30	Pass
NVNT	BLE 1M	2440	2.75	<=30	Pass
NVNT	BLE 1M	2480	2.73	<=30	Pass
NVNT	BLE 2M	2402	1.7	<=30	Pass
NVNT	BLE 2M	2440	2.98	<=30	Pass
NVNT	BLE 2M	2480	2.9	<=30	Pass






Test Graphs

Peak Power NVNT BLE 1M 2402MHz




Peak Power NVNT BLE 1M 2440MHz






Peak Power NVNT BLE 1M 2480MHz



Peak Power NVNT BLE 2M 2402MHz










4. -6dB Bandwidth

Condition	Mode	Frequency (MHz)	-6 dB Bandwidth (MHz)	Limit -6 dB Bandwidth (MHz)	Verdict
NVNT	BLE 1M	2402	0.6485	>=0.5	Pass
NVNT	BLE 1M	2440	0.6426	>=0.5	Pass
NVNT	BLE 1M	2480	0.6481	>=0.5	Pass
NVNT	BLE 2M	2402	1.0949	>=0.5	Pass
NVNT	BLE 2M	2440	1.0984	>=0.5	Pass
NVNT	BLE 2M	2480	0.9484	>=0.5	Pass














5. Maximum Power Spectral Density Level

Condition	Mode	Frequency (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
NVNT	BLE 1M	2402	-13.73	<=8	Pass
NVNT	BLE 1M	2440	-13.35	<=8	Pass
NVNT	BLE 1M	2480	-12.05	<=8	Pass
NVNT	BLE 2M	2402	-14.43	<=8	Pass
NVNT	BLE 2M	2440	-14.83	<=8	Pass
NVNT	BLE 2M	2480	-15.34	<=8	Pass














6. Band Edge


Condition	Mode	Frequency (MHz)	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	BLE 1M	2402	-52.22	<=-20	Pass
NVNT	BLE 1M	2480	-53.23	<=-20	Pass
NVNT	BLE 2M	2402	-34.51	<=-20	Pass
NVNT	BLE 2M	2480	-52.7	<=-20	Pass
















7. Conducted RF Spurious Emission


Condition	Mode	Frequency (MHz)	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	BLE 1M	2402	-41.37	<=-20	Pass
NVNT	BLE 1M	2440	-42.23	<=-20	Pass
NVNT	BLE 1M	2480	-42.55	<=-20	Pass
NVNT	BLE 2M	2402	-41.33	<=-20	Pass
NVNT	BLE 2M	2440	-41.69	<=-20	Pass
NVNT	BLE 2M	2480	-42.73	<=-20	Pass



















APPENDIX 2- EUT TEST PHOTO

Note: See test photos in setup photo document for the actual connections between Product and support equipment.

*****END OF THE REPORT*****

