


EUT:	Android board	Model Name:	RCS-3901
Test Mode:	TX	Test Voltage:	DC 12V from adapter AC 120V/60Hz


For U-NII-3


Channel	Test Channel	Frequency (MHz)	6dB bandwidth (MHz)	Limit (kHz)	Result
11a	CH149	5745	15.072	500	Pass
11a	CH157	5785	14.18	500	Pass
11a	CH165	5825	15.352	500	Pass
11n (HT20)	CH149	5745	16.664	500	Pass
11n (HT20)	CH157	5785	15.672	500	Pass
11n (HT20)	CH165	5825	15.116	500	Pass
11n (HT40)	CH151	5755	35.352	500	Pass
11n (HT40)	CH159	5795	35.632	500	Pass

Channel	Test Channel	Frequency (MHz)	6dB bandwidth (MHz)	Limit (kHz)	Result
11ac (HT20)	CH149	5745	15.548	500	Pass
11ac (HT20)	CH157	5785	15.14	500	Pass
11ac (HT20)	CH165	5825	17.108	500	Pass
11ac (HT40)	CH151	5755	35.376	500	Pass
11ac (HT40)	CH159	5795	35.144	500	Pass
11ac (HT80)	CH155	5775	75.136	500	Pass

Test plots:
For U-NII-3







5.8 Out Of Band Emission

5.8.1 Limit

According to FCC §15.407(b).


Undesirable emission limits. Except as shown in paragraph (b)(7) of this section, the maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:

- (1) For transmitters operating in the 5.15–5.25 GHz band: All emissions outside of the 5.15–5.35 GHz band shall not exceed an e.i.r.p. of –27 dBm/MHz.
- (2) For transmitters operating in the 5.25–5.35 GHz band: All emissions outside of the 5.15–5.35 GHz band shall not exceed an e.i.r.p. of –27 dBm/MHz.
- (3) For transmitters operating in the 5.47–5.725 GHz band: All emissions outside of the 5.47–5.725 GHz band shall not exceed an e.i.r.p. of –27 dBm/MHz.
- (4) For transmitters operating solely in the 5.725–5.850 GHz band:
 - (i) All emissions shall be limited to a level of –27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.


5.8.2 Test Procedure


- a) Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- b) Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
- c) Set RBW of spectrum analyzer to 1 MHz with a convenient frequency span.
- d) Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
- e) Repeat above procedures until all measured frequencies were complete.


5.8.3 Test Setup





5.8.4 Test Results
































5.9 Spurious RF Conducted Emissions

5.9.1 Limit

According to FCC §15.407(b).


Undesirable emission limits. Except as shown in paragraph (b)(7) of this section, the maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:

- (1) For transmitters operating in the 5.15–5.25 GHz band: All emissions outside of the 5.15–5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (2) For transmitters operating in the 5.25–5.35 GHz band: All emissions outside of the 5.15–5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (3) For transmitters operating in the 5.47–5.725 GHz band: All emissions outside of the 5.47–5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (4) For transmitters operating solely in the 5.725–5.850 GHz band:
 - (i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

5.9.2 Test Procedure

The Spurious RF conducted emissions compliance of RF radiated emission should be measured by following the guidance in ANSI C63.10-2013 with respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization etc. Set RBW=100kHz and VBW=300kHz to measure the peak field strength, and measure frequency range from 9kHz to 26.5GHz.

5.9.3 Test Setup




5.9.4 Test Results

Note:


- 1: The measurement frequency range is from 9kHz to the 10th harmonic of the fundamental

frequency; The lowest, middle and highest channels are tested to verify the spurious emissions and band edge measurement data.


2: The three modulated high, medium and low channels have been tested. The report only shows the worst mode. The worst mode is 802.11b CH01/06/11.




11n (HT40) CH38




11n (HT40) CH46




11ac (HT20) CH36




11ac (HT20) CH40





11ac (HT20) CH48




11ac (HT40) CH38









11n (HT40) CH54




11n (HT40) CH62




11ac (HT20) CH52



11ac (HT20) CH56



11ac (HT20) CH64



11ac (HT40) CH54

