

FCC TEST REPORT

FCC ID: 2BAM4-PC-AAC19

Report Number..... : ZKT-230307L1354-04

Date of Test..... : Mar. 07, 2023 -- Mar. 31, 2023

Date of issue : Mar. 31, 2023

Total number of pages : 113

Test Result : PASS

Testing Laboratory..... : **Shenzhen ZKT Technology Co., Ltd.**

Address : 1/F, No. 101, Building B, No. 6, Tangwei Community Industrial Avenue, Fuhai Street, Bao'an District, Shenzhen, China

Applicant's name : Shenzhen Kaida Technology Co., LTD

Address : 4 / F, building C, No. 9, Huayuan Xincun Avenue, xiangjiaotang community, Bantian street, Longgang District, Shenzhen

Manufacturer's name : Shenzhen Kaida Technology Co., LTD

Address : 4 / F, building C, No. 9, Huayuan Xincun Avenue, xiangjiaotang community, Bantian street, Longgang District, Shenzhen

Test specification:

Standard : FCC CFR Title 47 Part 15 Subpart E Section 15.407
ANSI C63.10:2013

Test procedure..... : KDB 789033 D02 General U-NII Test Procedures New Rules v01r02

Non-standard test method : N/A

Test Report Form No. : TRF-EL-110_V0

Test Report Form(s) Originator : ZKT Testing

Master TRF : Dated: 2020-01-06

This device described above has been tested by ZKT, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of ZKT, this document may be altered or revised by ZKT, personal only, and shall be noted in the revision of the document.

Product name..... : mini-pc


Trademark : N/A

Model/Type reference : PC-AAC19, PC-K001, PC-K002, PC-K003, PC-K004, PC-K005, PC-D006, PC-D007, PC-D008, PC-D009, PC-D10, PC-B011, PC-B012, PC-B013, PC-B014, PC-B015, PC-C016, PC-C017, PC-C018, PC-C019, PC-C020, PC-N031, PC-N034


Ratings..... : DC12.0V-3A 36W from adapter

Testing procedure and testing location:**Testing Laboratory.....: Shenzhen ZKT Technology Co., Ltd.**Address.....: 1/F, No. 101, Building B, No. 6, Tangwei Community
Industrial Avenue, Fuhai Street, Bao'an District,
Shenzhen, China

Tested by (name + signature).....: Alen He



Reviewer (name + signature).....: Joe Liu



Approved (name + signature).....: Lake Xie



Table of Contents

	Page
1. VERSION	5
2. SUMMARY OF TEST RESULTS	6
3. GENERAL INFORMATION	7
3.1 GENERAL DESCRIPTION OF EUT	7
3.2 DESCRIPTION OF TEST MODES	8
3.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	8
3.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)	8
3.5EQUIPMENTS LIST FOR ALL TEST ITEMS	9
4. EMC EMISSION TEST	11
4.1 CONDUCTED EMISSION MEASUREMENT	11
4.1.1 POWER LINE CONDUCTED EMISSION LIMITS	11
4.1.2 TEST PROCEDURE	11
4.1.3 DEVIATION FROM TEST STANDARD	11
4.1.4 TEST SETUP	11
4.1.5 EUT OPERATING CONDITIONS	12
4.1.6 TEST RESULTS	12
4.2 RADIATED EMISSION MEASUREMENT	14
4.2.1 RADIATED EMISSION LIMITS	14
4.2.2 TEST PROCEDURE	15
4.2.3 DEVIATION FROM TEST STANDARD	15
4.2.4 TEST SETUP	15
4.2.5 EUT OPERATING CONDITIONS	16
4.2.6 TEST RESULTS	17
5.POWER SPECTRAL DENSITY TEST	44
5.1 APPLIED PROCEDURES / LIMIT	44
5.2 TEST PROCEDURE	44
5.3 DEVIATION FROM STANDARD	44
5.4 TEST SETUP	44
5.5 EUT OPERATION CONDITIONS	45
5.6 TEST RESULT	45
6. -26 DB & 6DBM EMISSION BANDWIDTH	46
6.1 APPLIED PROCEDURES / LIMIT	46
6.2 TEST PROCEDURE	46
6.3 DEVIATION FROM STANDARD	46
6.4 TEST SETUP	46
6.5 EUT OPERATION CONDITIONS	46
6.6 TEST RESULT	46

7. OUTPUT POWER TEST	47
7.1 APPLIED PROCEDURES/LIMIT	47
7.2 DEVIATION FROM STANDARD	47
7.3 TEST SETUP	47
7.4 EUT OPERATION CONDITIONS	47
8. OUT OF BAND EDGE EMISSION	48
8.1 TEST PROCEDURE	48
8.2 DEVIATION FROM STANDARD	48
8.3 TEST SETUP	48
8.4 EUT OPERATION CONDITIONS	48
8.5 TEST RESULTS	48
9. FREQUENCY STABILITY MEASUREMENT	49
9.4 TEST RESULT	49
10.ANTENNA REQUIREMENT	53
11.APPENDIX1---5.2GWIFI	54
12.APPENDIX1---5.8GWIFI	82
13. TEST SETUP PHOTO	113
14. EUT CONSTRUCTIONAL DETAILS	113

1. VERSION

Report No.	Version	Description	Approved
ZKT-230307L1354-03	Rev.01	Initial issue of report	Mar. 31, 2023

2. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

FCC Part15 (15.407) , Subpart C			
Standard Section	Test Item	Result	Remark
15.203/15.247 (c)	Antenna requirement	PASS	
15.207	AC Power Line Conducted Emission	PASS	
15.407 (a) (b)	Spurious Radiated Emissions and Band Edge	PASS	
15.407 (e) /15.403(i)	6 dB bandwidth, 26dB Emission Bandwidth& 99% Occupied Bandwidth	PASS	
15.407 (a)	Power Spectral Density	PASS	
15.407 (a)(1)(2)(3)	Maximum conducted output power	PASS	
15.407 (g)	Frequency Stability	PASS	

NOTE:

(1)" N/A" denotes test is not applicable in this Test Report

2.1 TEST FACILITY

Shenzhen ZKT Technology Co., Ltd.

Add. : 1/F, No. 101, Building B, No. 6, Tangwei Community Industrial Avenue, Fuhai Street, Bao'an District, Shenzhen, China

FCC Test Firm Registration Number: 692225

Designation Number: CN1299

IC Registered No.: 27033

2.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %

No.	Item	Uncertainty
1	3m camber radiated spurious emissions(30MHz-1GHz)	U=4.3dB
2	3m camber radiated spurious emissions(1GHz-18GHz)	U=4.5dB
3	3m camber radiated spurious emissions(18GHz-40GHz)	U=3.34dB
4	Conducted adjacent channel power	U=1.38 dB
5	Conducted output power uncertainty above 1GHz	U=1.576 dB
6	Conducted output power uncertainty below 1GHz	U=1.28dB
7	Humidity	U=5.3%
8	Temperature	U=0.59℃
9	radiated disturbance (30MHz-1GHz)	U=4.8dB
10	radiated disturbance (1GHz-6GHz)	U=4.9dB
11	radiated disturbance (6GHz-18GHz)	U=5.0dB

3. GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

Product Name:	mini-pc	
Model No.:	PC-AAC19	
Model List:	PC-K001, PC-K002, PC-K003, PC-K004, PC-K005, PC-D006, PC-D007, PC-D008, PC-D009, PC-D10, PC-B011, PC-B012, PC-B013, PC-B014, PC-B015, PC-C016, PC-C017, PC-C018, PC-C019, PC-C020, PC-N031, PC-N034	
Model difference:	Motherboard circuits, such as BOMs and PCBs, are consistent, but there may be differences in configuration (such as CPU model, main model-CPU is N5105 and N5095 for series models, memory size, hard disk size, display screen size, etc.), resulting in different models, or different models due to different customer requirements. However, these differences do not affect the EMC/RF performance of the product itself. The CPU model for this test is N5105, memory: 8G+256, and model: PC-AAC19	
Hardware Version:	V1.1	
Software Version:	V12.0	
Sample(s) Status:	Engineer sample	
IEEE802.11 WLAN mode supported	802.11a/n/ac(20MHz channel bandwidth) 802.11n/ac(40MHz channel bandwidth) 802.11 ac (80MHz channel bandwidth)	
Date rate	802.11ac:MCS0-MCS11 802.11n: MCS0-MCS7 802.11a: 6.5-54Mbps	
Modulation	OFDM/OFDMA	
U-NII-1	Frequency Range	802.11a/n/ac(20MHz) : 5180-5240MHz 802.11n/ac(40MHz) : 5190-5230MHz 802.11 ac (80MHz) : 5210MHz
U-NII-1	Channels	802.11 a/n/ac (20MHz): 4 802.11 ac /n (40MHz): 2 802.11 ac (80MHz): 1
U-NII-3	Frequency Range	802.11 a/n/ac(20MHz) : 5745-5825 MHz 802.11 n/ac (40MHz): 5755-5795 MHz 802.11 ac (80MHz): 5775 MHz
U-NII-3	Channels	802.11 a/n/ac(20MHz) : 5 802.11 n/ac (40MHz): 2 802.11 ac (80MHz): 1
Antenna Type:	FPC antenna	
Antenna gain:	WIFI ANT1 & WIFI ANT2: 3.46dBi; MIMO Gain: 6.47 dBi	
Power supply:	DC12.0V-3A 36W from adapter	

Note: $MIMO\ Gain = 10 \cdot \log[(10^{G1/20} + 10^{G2/20} + \dots)^2 / N_{ant}]$, so MIMO Gain is 6.47dBi > 6dBi

U-NII-1		U-NII-3	
CH.	Frequency (MHz)	CH.	Frequency (MHz)
36	5180	149	5745
40	5200	...	...
44	5220	157	5785
48	5240	...	...
		165	5825

802.11a/n/ac(20MHz) Frequency / Channel Operations

U-NII-1		U-NII-3	
CH.	Frequency (MHz)	CH.	Frequency (MHz)
38	5190	151	5755
46	5230	159	5795

802.11n /ac(40MHz BW) Frequency / Channel Operations

U-NII-1		U-NII-3	
CH.	Frequency (MHz)	CH.	Frequency (MHz)
42	5210	155	5775

802.11ac (80MHz BW) Frequency / Channel Operations

3.2 DESCRIPTION OF TEST MODES

Worst Case Configuration: transmitting both 2.4GHz mode and 5GHz mode


Description	5 GHz Emission
Antenna	MIMO
Channel	165
Operating Frequency (MHz)	802.11n20
Data Rate (Mbps)	OFDM/MCS9
Mode	U-NII-3 - 5745MHz

3.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED


Conducted Emission



Radiated Emission



Conducted Spurious



3.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
1	Adapter	Shenzhen RUIYU technology Co.,Ltd.	MODEL:RYF909C120300VE INPUT:100-240~50/60Hz 1.5A OUTPUT:12.0V-3A 36W	/	SDOC
2					
3					

Item	Shielded Type	Ferrite Core	Length	Note

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.

3.5EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation Test equipment

Item	Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
1	Spectrum Analyzer (9kHz-26.5GHz)	KEYSIGHT	9020A	MY55370835	Oct. 18, 2022	Oct. 17, 2023
2	Spectrum Analyzer (1GHz-40GHz)	R&S	FSQ	100363	Oct. 17, 2022	Oct. 16, 2023
3	EMI Test Receiver (9kHz-7GHz)	R&S	ESCI7	101169	Oct. 18, 2022	Oct. 17, 2023
4	Bilog Antenna (30MHz-1500MHz)	Schwarzbeck	VULB9168	N/A	Oct. 17, 2022	Oct. 16, 2023
5	Horn Antenna (1GHz-18GHz)	Agilent	AH-118	071145	Oct. 17, 2022	Oct. 16, 2023
6	Loop Antenna	TESEQ	HLA6121	58357	Oct. 17, 2022	Oct. 16, 2023
7	Amplifier (30-1000MHz)	EM Electronics	EM330 Amplifier	060747	Oct. 17, 2022	Oct. 16, 2023
8	Amplifier (1GHz-26.5GHz)	Agilent	8449B	3008A00315	Oct. 18, 2022	Oct. 17, 2023
9	RF cables1 (9kHz-30MHz)	N/A	9kHz-30MHz	N/A	Oct. 18, 2022	Oct. 17, 2023
10	RF cables2 (30MHz-1GHz)	N/A	30MHz-1GHz	N/A	Oct. 18, 2022	Oct. 17, 2023
11	RF cables3 (1GHz-40GHz)	N/A	1GHz-40GHz	N/A	Oct. 18, 2022	Oct. 17, 2023
12	ESG Signal Generator	Agilent	E4421B	N/A	Oct. 18, 2022	Oct. 17, 2023
13	Signal Generator	Agilent	N5182A	N/A	Oct. 22, 2022	Oct. 21, 2023
14	Magnetic Field Probe Tester	Narda	ELT-400	0-0344	Oct. 17, 2022	Oct. 16, 2023
15	MWRF Power Meter Test system	MW	MW100-RPCB	N/A	Oct. 22, 2022	Oct. 21, 2023
16	Power sensor	KEYSIGHT	U200H	MY51190005	Oct. 22, 2022	Oct. 21, 2023
17	D.C. Power Supply	LongWei	TPR-6405D	N/A	Oct. 22, 2022	Oct. 21, 2023
18	EMC Software	Frad	EZ-EMC	Ver.EMC-CON 3A1.1	\	\
19	RF Software	MW	MTS8310	V2.0.0.0	\	\
20	Turntable	MF	MF-7802BS	N/A	\	\
21	Antenna tower	MF	MF-7802BS	N/A	\	\

Conduction Test equipment

Item	Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
1	LISN	R&S	ENV216	101471	Oct. 22, 2022	Oct. 21, 2023
2	LISN	CYBERTEK	EM5040A	E1850400149	Oct. 22, 2022	Oct. 21, 2023
3	Test Cable	N/A	C01	N/A	Oct. 18, 2022	Oct. 17, 2023

4	Test Cable	N/A	C02	N/A	Oct. 18, 2022	Oct. 17, 2023
5	EMI Test Receiver	R&S	ESCI3	101393	Oct. 17, 2022	Oct. 16, 2023
6	EMC Software	Frad	EZ-EMC	Ver.EMC-CON 3A1.1	\	\

4. EMC EMISSION TEST

4.1 CONDUCTED EMISSION MEASUREMENT

Test Requirement:	FCC Part15 C Section 15.207
Test Method:	ANSI C63.10:2013
Test Frequency Range:	150KHz to 30MHz
Receiver setup:	RBW=9KHz, VBW=30KHz, Sweep time=auto

4.1.1 POWER LINE CONDUCTED EMISSION LIMITS

FREQUENCY (MHz)	Limit (dBuV)		Standard
	Quasi-peak	Average	
0.15 -0.5	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	56.00	46.00	FCC
5.0 -30.0	60.00	50.00	FCC

Note:

(1) *Decreases with the logarithm of the frequency.


4.1.2 TEST PROCEDURE

1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. The EUT is a tabletop system; a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10:2013.
2. Support equipment, if needed, was placed as per ANSI C63.10:2013
3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10:2013.
4. The adapter received AC120V/60Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
5. All support equipments received AC power from a second LISN, if any.
6. The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
7. Analyzer / Receiver scanned from 150 KHz to 30MHz for emissions in each of the test modes.e.
- 8 For the actual test configuration, please refer to the related Item –EUT Test Photos.

4.1.3 DEVIATION FROM TEST STANDARD

No deviation

4.1.4 TEST SETUP




4.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

We pretest AC 120V , the worst voltage was AC 120V and the data recording in the report.


4.1.6 TEST RESULTS

Temperature :	26°C	Relative Humidity:	54%
Pressure :	101kPa	Phase :	L
Test Voltage :	AC 120V/60Hz		



No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1	0.1539	39.84	9.75	49.59	65.78	-16.19	QP	
2	0.1539	24.49	9.75	34.24	55.78	-21.54	AVG	
3 *	0.5660	29.62	9.84	39.46	46.00	-6.54	AVG	
4	0.5700	38.40	9.84	48.24	56.00	-7.76	QP	
5	1.0540	20.50	9.75	30.25	46.00	-15.75	AVG	
6	1.0580	28.78	9.75	38.53	56.00	-17.47	QP	
7	5.9260	19.09	9.64	28.73	50.00	-21.27	AVG	
8	5.9580	30.23	9.64	39.87	60.00	-20.13	QP	
9	15.4420	27.60	9.65	37.25	60.00	-22.75	QP	
10	15.6460	14.91	9.64	24.55	50.00	-25.45	AVG	
11	24.5220	16.87	9.47	26.34	50.00	-23.66	AVG	
12	25.0980	26.60	9.46	36.06	60.00	-23.94	QP	

Temperature :	26°C	Relative Humidity:	54%
Pressure :	101kPa	Phase :	N
Test Voltage :	AC 120V/60Hz		



No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1	0.1500	41.30	9.75	51.05	65.99	-14.94	QP	
2	0.1539	24.73	9.75	34.48	55.78	-21.30	AVG	
3 *	0.5660	30.28	9.84	40.12	46.00	-5.88	AVG	
4	0.5700	39.59	9.84	49.43	56.00	-6.57	QP	
5	1.0260	29.26	9.76	39.02	56.00	-16.98	QP	
6	1.0540	19.11	9.75	28.86	46.00	-17.14	AVG	
7	4.1820	28.91	9.68	38.59	56.00	-17.41	QP	
8	4.1820	16.98	9.68	26.66	46.00	-19.34	AVG	
9	5.9660	18.73	9.64	28.37	50.00	-21.63	AVG	
10	6.0580	30.07	9.64	39.71	60.00	-20.29	QP	
11	10.4500	26.68	9.79	36.47	60.00	-23.53	QP	
12	10.7340	14.86	9.78	24.64	50.00	-25.36	AVG	

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Measurement Level = Reading level + Correct Factor
4. The test data shows only the worst case- MIMO (5.8G-802.11n20 Low channel)

4.2 RADIATED EMISSION MEASUREMENT

4.2.1 RADIATED EMISSION LIMITS

1. Radiated emissions from 9 kHz to 25 GHz were measured according to the methods defines in ANSI C63.10-2013. The EUT was placed above the ground plane, 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz. The interface cable and equipment positions were varied within limits of reasonable applications to determine the positions producing maximum radiated emissions.
2. For transmitters operating in the 5150-5250 MHz band: all emissions outside of the 5150-5350 MHz band shall not exceed an EIRP of -27 dBm/MHz.
3. For transmitters operating in the 5250-5350 MHz band: all emissions outside of the 5150-5350 MHz band shall not exceed an EIRP of -27 dBm/MHz. Devices operating in the 5250-5350 MHz band that generate emissions in the 5150-5250 MHz band must meet all applicable technical requirements for operation in the 5150-5250 MHz band (including indoor use) or alternatively meet an out-of-band emission EIRP limit of -27 dBm/MHz in the 5150-5250 MHz band.
4. For transmitters operating in the 5470-5600 MHz and 5650-5725 MHz band: all emissions outside of the 5470-5600 MHz and 5650-5725 MHz band shall not exceed an EIRP of -27 dBm/MHz.
5. KDB789033v02r01G2)c) As specified in 15.407(b), emissions above 1000 MHz that are outside of the restricted bands are subject to a peak emission limit of -27 dBm/MHz (or -17 dBm/MHz as specified in 15.407(b)(4)). However, an out-of-band emission that complies with both the average and peak limits of 15.209 is not required to satisfy the -27 dBm/MHz or -17 dBm/MHz peak emission limit.

According to §15.209(a), except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT

FREQUENCY (MHz)	Limit (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

4.2.2 TEST PROCEDURE

Below 1GHz test procedure as below:

- a. The EUT was placed on the top of a rotating table 0.1 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

Above 1GHz test procedure as below:

- g. Different between above is the test site, change from Semi- Anechoic Chamber to fully Anechoic Chamber and change from table 0.8 metre to 1.5 metre (Above 18GHz the distance is 1 meter and table is 1.5 metre).
- h. Test the EUT in the lowest channel ,the middle channel ,the Highest channel

Note:


Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

4.2.3 DEVIATION FROM TEST STANDARD


No deviation

4.2.4 TEST SETUP


(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



(C) Radiated Emission Test-Up Frequency Above 1GHz



4.2.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.


4.2.6 TEST RESULTS

Between 9KHz – 30MHz


The emission from 9 kHz to 30MHz was pre-tested and found the result was 20dB lower than the limit, and according to 15.31(o) & RSS-Gen 6.13, the test result no need to reported.

Between 30MHz – 1GHz

Temperature:	26°C	Relative Humidity:	54%
Pressure:	101 kPa	Polarization:	Horizontal
Test Voltage:	AC 120V/60Hz		



Temperature:	26°C	Relative Humidity:	54%
Pressure:	101kPa	Polarization:	Vertical
Test Voltage:	AC 120V/60Hz		



Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.
3. The test data shows only the worst case- MIMO (5.8G-802.11n20 high channel)

ANT1-802.11a

Polar (H/V)	Frequency	Meter Reading	Pre-ampl ifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel:5180MHz									
V	10360	47.80	30.55	5.77	24.66	47.68	74.00	-26.32	PK
V	10360	35.33	30.55	5.77	24.66	35.21	54.00	-18.79	AV
V	15540	49.67	30.33	6.32	24.55	50.21	74.00	-23.79	PK
V	15540	40.41	30.33	6.32	24.55	40.95	54.00	-13.05	AV
V	20720	49.18	30.85	7.45	24.69	50.47	74.00	-23.53	PK
V	20720	39.41	30.85	7.45	24.69	40.70	54.00	-13.30	AV
H	10360	47.87	30.55	5.77	24.66	47.75	74.00	-26.25	PK
H	10360	40.08	30.55	5.77	24.66	39.96	54.00	-14.04	AV
H	15540	47.48	30.33	6.32	24.55	48.02	74.00	-25.98	PK
H	15540	38.83	30.33	6.32	24.55	39.37	54.00	-14.63	AV
H	20720	49.31	30.85	7.45	24.69	50.60	74.00	-23.40	PK
H	20720	41.61	30.85	7.45	24.69	42.90	54.00	-11.10	AV

Polar (H/V)	Frequency	Meter Reading	Pre-ampl ifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Middle Channel:5200MHz									
V	10400	46.78	30.55	5.77	24.66	46.66	74.00	-27.34	PK
V	10400	35.65	30.55	5.77	24.66	35.53	54.00	-18.47	AV
V	15600	49.38	30.33	6.32	24.55	49.92	74.00	-24.08	PK
V	15600	39.10	30.33	6.32	24.55	39.64	54.00	-14.36	AV
V	20800	51.58	30.85	7.45	24.69	52.87	74.00	-21.13	PK
V	20800	40.99	30.85	7.45	24.69	42.28	54.00	-11.72	AV
H	10400	46.92	30.55	5.77	24.66	46.80	74.00	-27.20	PK
H	10400	39.36	30.55	5.77	24.66	39.24	54.00	-14.76	AV
H	15600	48.04	30.33	6.32	24.55	48.58	74.00	-25.42	PK
H	15600	38.76	30.33	6.32	24.55	39.30	54.00	-14.70	AV
H	20800	50.29	30.85	7.45	24.69	51.58	74.00	-22.42	PK
H	20800	39.00	30.85	7.45	24.69	40.29	54.00	-13.71	AV

Polar (H/V)	Frequency	Meter Reading	Pre-ampl ifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
High Channel:5240MHz									
V	10480	47.67	30.55	5.77	24.66	47.55	74.00	-26.45	PK
V	10480	35.38	30.55	5.77	24.66	35.26	54.00	-18.74	AV
V	15720	48.94	30.33	6.32	24.55	49.48	74.00	-24.52	PK
V	15720	40.25	30.33	6.32	24.55	40.79	54.00	-13.21	AV
V	20960	51.07	30.85	7.45	24.69	52.36	74.00	-21.64	PK
V	20960	41.06	30.85	7.45	24.69	42.35	54.00	-11.65	AV
H	10480	46.72	30.55	5.77	24.66	46.60	74.00	-27.40	PK
H	10480	39.96	30.55	5.77	24.66	39.84	54.00	-14.16	AV
H	15720	48.11	30.33	6.32	24.55	48.65	74.00	-25.35	PK
H	15720	38.95	30.33	6.32	24.55	39.49	54.00	-14.51	AV
H	20960	50.67	30.85	7.45	24.69	51.96	74.00	-22.04	PK
H	20960	38.84	30.85	7.45	24.69	40.13	54.00	-13.87	AV

Polar (H/V)	Frequency	Meter Reading	Pre-ampli fier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
High Channel:5745MHz									
V	11490	48.07	30.55	5.77	24.66	47.95	74.00	-26.05	PK

V	11490	34.91	30.55	5.77	24.66	34.79	54.00	-19.21	AV
V	17235	48.80	30.33	6.32	24.55	49.34	74.00	-24.66	PK
V	17235	39.41	30.33	6.32	24.55	39.95	54.00	-14.05	AV
V	22980	49.17	30.85	7.45	24.69	50.46	74.00	-23.54	PK
V	22980	41.21	30.85	7.45	24.69	42.50	54.00	-11.50	AV
H	11490	45.78	30.55	5.77	24.66	45.66	74.00	-28.34	PK
H	11490	39.73	30.55	5.77	24.66	39.61	54.00	-14.39	AV
H	17235	47.87	30.33	6.32	24.55	48.41	74.00	-25.59	PK
H	17235	41.50	30.33	6.32	24.55	42.04	54.00	-11.96	AV
H	22980	51.11	30.85	7.45	24.69	52.40	74.00	-21.60	PK
H	22980	38.88	30.85	7.45	24.69	40.17	54.00	-13.83	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
High Channel:5785MHz									
V	11570	48.63	30.55	5.77	24.66	48.51	74.00	-25.49	PK
V	11570	34.22	30.55	5.77	24.66	34.10	54.00	-19.90	AV
V	17355	48.70	30.33	6.32	24.55	49.24	74.00	-24.76	PK
V	17355	41.34	30.33	6.32	24.55	41.88	54.00	-12.12	AV
V	23140	48.84	30.85	7.45	24.69	50.13	74.00	-23.87	PK
V	23140	39.35	30.85	7.45	24.69	40.64	54.00	-13.36	AV
H	11570	48.42	30.55	5.77	24.66	48.30	74.00	-25.70	PK
H	11570	39.18	30.55	5.77	24.66	39.06	54.00	-14.94	AV
H	17355	47.88	30.33	6.32	24.55	48.42	74.00	-25.58	PK
H	17355	39.68	30.33	6.32	24.55	40.22	54.00	-13.78	AV
H	23140	51.39	30.85	7.45	24.69	52.68	74.00	-21.32	PK
H	23140	41.70	30.85	7.45	24.69	42.99	54.00	-11.01	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
High Channel:5825MHz									
V	11650	47.80	30.55	5.77	24.66	47.68	74.00	-26.32	PK
V	11650	36.08	30.55	5.77	24.66	35.96	54.00	-18.04	AV
V	17475	48.48	30.33	6.32	24.55	49.02	74.00	-24.98	PK
V	17475	40.41	30.33	6.32	24.55	40.95	54.00	-13.05	AV
V	23300	49.02	30.85	7.45	24.69	50.31	74.00	-23.69	PK
V	23300	40.63	30.85	7.45	24.69	41.92	54.00	-12.08	AV
H	11650	47.34	30.55	5.77	24.66	47.22	74.00	-26.78	PK
H	11650	39.95	30.55	5.77	24.66	39.83	54.00	-14.17	AV
H	17475	47.96	30.33	6.32	24.55	48.50	74.00	-25.50	PK
H	17475	41.33	30.33	6.32	24.55	41.87	54.00	-12.13	AV
H	23300	50.86	30.85	7.45	24.69	52.15	74.00	-21.85	PK
H	23300	41.46	30.85	7.45	24.69	42.75	54.00	-11.25	AV

ANT1-802.11n20

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
Low Channel:5180MHz									
V	10360	48.52	30.55	5.77	24.66	48.40	74.00	-25.60	PK
V	10360	34.95	30.55	5.77	24.66	34.83	54.00	-19.17	AV
V	15540	49.03	30.33	6.32	24.55	49.57	74.00	-24.43	PK
V	15540	40.46	30.33	6.32	24.55	41.00	54.00	-13.00	AV
V	20720	50.12	30.85	7.45	24.69	51.41	74.00	-22.59	PK

V	20720	41.59	30.85	7.45	24.69	42.88	54.00	-11.12	AV
H	10360	46.82	30.55	5.77	24.66	46.70	74.00	-27.30	PK
H	10360	39.12	30.55	5.77	24.66	39.00	54.00	-15.00	AV
H	15540	47.17	30.33	6.32	24.55	47.71	74.00	-26.29	PK
H	15540	41.73	30.33	6.32	24.55	42.27	54.00	-11.73	AV
H	20720	50.65	30.85	7.45	24.69	51.94	74.00	-22.06	PK
H	20720	41.38	30.85	7.45	24.69	42.67	54.00	-11.33	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amp lifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
Middle Channel:5200MHz									
V	10400	47.50	30.55	5.77	24.66	47.38	74.00	-26.62	PK
V	10400	34.59	30.55	5.77	24.66	34.47	54.00	-19.53	AV
V	15600	48.02	30.33	6.32	24.55	48.56	74.00	-25.44	PK
V	15600	39.51	30.33	6.32	24.55	40.05	54.00	-13.95	AV
V	20800	50.12	30.85	7.45	24.69	51.41	74.00	-22.59	PK
V	20800	40.91	30.85	7.45	24.69	42.20	54.00	-11.80	AV
H	10400	46.54	30.55	5.77	24.66	46.42	74.00	-27.58	PK
H	10400	38.43	30.55	5.77	24.66	38.31	54.00	-15.69	AV
H	15600	47.36	30.33	6.32	24.55	47.90	74.00	-26.10	PK
H	15600	40.06	30.33	6.32	24.55	40.60	54.00	-13.40	AV
H	20800	50.11	30.85	7.45	24.69	51.40	74.00	-22.60	PK
H	20800	41.49	30.85	7.45	24.69	42.78	54.00	-11.22	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
High Channel:5240MHz									
V	10480	48.28	30.55	5.77	24.66	48.16	74.00	-25.84	PK
V	10480	34.64	30.55	5.77	24.66	34.52	54.00	-19.48	AV
V	15720	48.65	30.33	6.32	24.55	49.19	74.00	-24.81	PK
V	15720	39.14	30.33	6.32	24.55	39.68	54.00	-14.32	AV
V	20960	50.51	30.85	7.45	24.69	51.80	74.00	-22.20	PK
V	20960	40.72	30.85	7.45	24.69	42.01	54.00	-11.99	AV
H	10480	46.22	30.55	5.77	24.66	46.10	74.00	-27.90	PK
H	10480	39.37	30.55	5.77	24.66	39.25	54.00	-14.75	AV
H	15720	47.94	30.33	6.32	24.55	48.48	74.00	-25.52	PK
H	15720	40.25	30.33	6.32	24.55	40.79	54.00	-13.21	AV
H	20960	50.86	30.85	7.45	24.69	52.15	74.00	-21.85	PK
H	20960	41.18	30.85	7.45	24.69	42.47	54.00	-11.53	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
High Channel:5745MHz									
V	11490	46.81	30.55	5.77	24.66	46.69	74.00	-27.31	PK
V	11490	35.34	30.55	5.77	24.66	35.22	54.00	-18.78	AV
V	17235	47.93	30.33	6.32	24.55	48.47	74.00	-25.53	PK
V	17235	41.12	30.33	6.32	24.55	41.66	54.00	-12.34	AV
V	22980	51.54	30.85	7.45	24.69	52.83	74.00	-21.17	PK
V	22980	41.13	30.85	7.45	24.69	42.42	54.00	-11.58	AV
H	11490	46.87	30.55	5.77	24.66	46.75	74.00	-27.25	PK
H	11490	38.10	30.55	5.77	24.66	37.98	54.00	-16.02	AV
H	17235	48.36	30.33	6.32	24.55	48.90	74.00	-25.10	PK
H	17235	39.34	30.33	6.32	24.55	39.88	54.00	-14.12	AV

H	22980	51.10	30.85	7.45	24.69	52.39	74.00	-21.61	PK
H	22980	40.08	30.85	7.45	24.69	41.37	54.00	-12.63	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
High Channel:5785MHz									
V	11570	49.23	30.55	5.77	24.66	49.11	74.00	-24.89	PK
V	11570	35.25	30.55	5.77	24.66	35.13	54.00	-18.87	AV
V	17355	48.70	30.33	6.32	24.55	49.24	74.00	-24.76	PK
V	17355	40.76	30.33	6.32	24.55	41.30	54.00	-12.70	AV
V	23140	48.77	30.85	7.45	24.69	50.06	74.00	-23.94	PK
V	23140	40.74	30.85	7.45	24.69	42.03	54.00	-11.97	AV
H	11570	46.38	30.55	5.77	24.66	46.26	74.00	-27.74	PK
H	11570	39.01	30.55	5.77	24.66	38.89	54.00	-15.11	AV
H	17355	48.44	30.33	6.32	24.55	48.98	74.00	-25.02	PK
H	17355	40.75	30.33	6.32	24.55	41.29	54.00	-12.71	AV
H	23140	51.44	30.85	7.45	24.69	52.73	74.00	-21.27	PK
H	23140	39.77	30.85	7.45	24.69	41.06	54.00	-12.94	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
High Channel:5825MHz									
V	11650	47.20	30.55	5.77	24.66	47.08	74.00	-26.92	PK
V	11650	36.00	30.55	5.77	24.66	35.88	54.00	-18.12	AV
V	17475	49.44	30.33	6.32	24.55	49.98	74.00	-24.02	PK
V	17475	39.61	30.33	6.32	24.55	40.15	54.00	-13.85	AV
V	23300	49.60	30.85	7.45	24.69	50.89	74.00	-23.11	PK
V	23300	41.37	30.85	7.45	24.69	42.66	54.00	-11.34	AV
H	11650	45.93	30.55	5.77	24.66	45.81	74.00	-28.19	PK
H	11650	38.62	30.55	5.77	24.66	38.50	54.00	-15.50	AV
H	17475	47.75	30.33	6.32	24.55	48.29	74.00	-25.71	PK
H	17475	39.04	30.33	6.32	24.55	39.58	54.00	-14.42	AV
H	23300	48.85	30.85	7.45	24.69	50.14	74.00	-23.86	PK
H	23300	40.16	30.85	7.45	24.69	41.45	54.00	-12.55	AV

ANT1-802.11n40

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
Low Channel:5190MHz									
V	10360	49.28	30.55	5.77	24.66	49.16	74.00	-24.84	PK
V	10360	36.69	30.55	5.77	24.66	36.57	54.00	-17.43	AV
V	15540	48.05	30.33	6.32	24.55	48.59	74.00	-25.41	PK
V	15540	39.58	30.33	6.32	24.55	40.12	54.00	-13.88	AV
V	20720	50.54	30.85	7.45	24.69	51.83	74.00	-22.17	PK
V	20720	40.32	30.85	7.45	24.69	41.61	54.00	-12.39	AV
H	10360	48.32	30.55	5.77	24.66	48.20	74.00	-25.80	PK
H	10360	38.83	30.55	5.77	24.66	38.71	54.00	-15.29	AV
H	15540	48.09	30.33	6.32	24.55	48.63	74.00	-25.37	PK
H	15540	39.38	30.33	6.32	24.55	39.92	54.00	-14.08	AV
H	20720	50.69	30.85	7.45	24.69	51.98	74.00	-22.02	PK
H	20720	40.42	30.85	7.45	24.69	41.71	54.00	-12.29	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
Middle Channel:5230MHz									
V	10460	48.16	30.55	5.77	24.66	48.04	74.00	-25.96	PK
V	10460	36.52	30.55	5.77	24.66	36.40	54.00	-17.60	AV
V	15690	49.52	30.33	6.32	24.55	50.06	74.00	-23.94	PK
V	15690	41.00	30.33	6.32	24.55	41.54	54.00	-12.46	AV
V	20920	48.93	30.85	7.45	24.69	50.22	74.00	-23.78	PK
V	20920	40.94	30.85	7.45	24.69	42.23	54.00	-11.77	AV
H	10460	48.57	30.55	5.77	24.66	48.45	74.00	-25.55	PK
H	10460	38.92	30.55	5.77	24.66	38.80	54.00	-15.20	AV
H	15690	46.87	30.33	6.32	24.55	47.41	74.00	-26.59	PK
H	15690	40.32	30.33	6.32	24.55	40.86	54.00	-13.14	AV
H	20920	49.51	30.85	7.45	24.69	50.80	74.00	-23.20	PK
H	20920	39.78	30.85	7.45	24.69	41.07	54.00	-12.93	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
High Channel:5755MHz									
V	11510	48.44	30.55	5.77	24.66	48.32	74.00	-25.68	PK
V	11510	35.62	30.55	5.77	24.66	35.50	54.00	-18.50	AV
V	17265	48.07	30.33	6.32	24.55	48.61	74.00	-25.39	PK
V	17265	40.77	30.33	6.32	24.55	41.31	54.00	-12.69	AV
V	23020	50.53	30.85	7.45	24.69	51.82	74.00	-22.18	PK
V	23020	39.86	30.85	7.45	24.69	41.15	54.00	-12.85	AV
H	11510	47.64	30.55	5.77	24.66	47.52	74.00	-26.48	PK
H	11510	39.02	30.55	5.77	24.66	38.90	54.00	-15.10	AV
H	17265	46.97	30.33	6.32	24.55	47.51	74.00	-26.49	PK
H	17265	40.37	30.33	6.32	24.55	40.91	54.00	-13.09	AV
H	23020	51.28	30.85	7.45	24.69	52.57	74.00	-21.43	PK
H	23020	41.69	30.85	7.45	24.69	42.98	54.00	-11.02	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
High Channel:5795MHz									
V	11590	49.48	30.55	5.77	24.66	49.36	74.00	-24.64	PK
V	11590	36.26	30.55	5.77	24.66	36.14	54.00	-17.86	AV
V	17385	48.14	30.33	6.32	24.55	48.68	74.00	-25.32	PK
V	17385	39.35	30.33	6.32	24.55	39.89	54.00	-14.11	AV
V	23180	51.40	30.85	7.45	24.69	52.69	74.00	-21.31	PK
V	23180	40.32	30.85	7.45	24.69	41.61	54.00	-12.39	AV
H	11590	46.82	30.55	5.77	24.66	46.70	74.00	-27.30	PK
H	11590	39.24	30.55	5.77	24.66	39.12	54.00	-14.88	AV
H	17385	48.11	30.33	6.32	24.55	48.65	74.00	-25.35	PK
H	17385	40.39	30.33	6.32	24.55	40.93	54.00	-13.07	AV
H	23180	51.29	30.85	7.45	24.69	52.58	74.00	-21.42	PK
H	23180	38.83	30.85	7.45	24.69	40.12	54.00	-13.88	AV

ANT1--802.11ac20

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
Low Channel:5180MHz									
V	10360	47.41	30.55	5.77	24.66	47.29	74.00	-26.71	PK

V	10360	34.61	30.55	5.77	24.66	34.49	54.00	-19.51	AV
V	15540	48.12	30.33	6.32	24.55	48.66	74.00	-25.34	PK
V	15540	38.95	30.33	6.32	24.55	39.49	54.00	-14.51	AV
V	20720	49.71	30.85	7.45	24.69	51.00	74.00	-23.00	PK
V	20720	39.13	30.85	7.45	24.69	40.42	54.00	-13.58	AV
H	10360	46.66	30.55	5.77	24.66	46.54	74.00	-27.46	PK
H	10360	40.68	30.55	5.77	24.66	40.56	54.00	-13.44	AV
H	15540	46.87	30.33	6.32	24.55	47.41	74.00	-26.59	PK
H	15540	38.87	30.33	6.32	24.55	39.41	54.00	-14.59	AV
H	20720	49.04	30.85	7.45	24.69	50.33	74.00	-23.67	PK
H	20720	39.52	30.85	7.45	24.69	40.81	54.00	-13.19	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
Middle Channel:5200MHz									
V	10400	49.62	30.55	5.77	24.66	49.50	74.00	-24.50	PK
V	10400	34.27	30.55	5.77	24.66	34.15	54.00	-19.85	AV
V	15600	47.89	30.33	6.32	24.55	48.43	74.00	-25.57	PK
V	15600	40.48	30.33	6.32	24.55	41.02	54.00	-12.98	AV
V	20800	50.25	30.85	7.45	24.69	51.54	74.00	-22.46	PK
V	20800	41.05	30.85	7.45	24.69	42.34	54.00	-11.66	AV
H	10400	46.32	30.55	5.77	24.66	46.20	74.00	-27.80	PK
H	10400	38.62	30.55	5.77	24.66	38.50	54.00	-15.50	AV
H	15600	48.02	30.33	6.32	24.55	48.56	74.00	-25.44	PK
H	15600	40.72	30.33	6.32	24.55	41.26	54.00	-12.74	AV
H	20800	49.46	30.85	7.45	24.69	50.75	74.00	-23.25	PK
H	20800	39.38	30.85	7.45	24.69	40.67	54.00	-13.33	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
High Channel:5240MHz									
V	10480	49.11	30.55	5.77	24.66	48.99	74.00	-25.01	PK
V	10480	35.26	30.55	5.77	24.66	35.14	54.00	-18.86	AV
V	15720	48.03	30.33	6.32	24.55	48.57	74.00	-25.43	PK
V	15720	38.96	30.33	6.32	24.55	39.50	54.00	-14.50	AV
V	20960	50.47	30.85	7.45	24.69	51.76	74.00	-22.24	PK
V	20960	39.48	30.85	7.45	24.69	40.77	54.00	-13.23	AV
H	10480	47.49	30.55	5.77	24.66	47.37	74.00	-26.63	PK
H	10480	37.82	30.55	5.77	24.66	37.70	54.00	-16.30	AV
H	15720	48.38	30.33	6.32	24.55	48.92	74.00	-25.08	PK
H	15720	39.99	30.33	6.32	24.55	40.53	54.00	-13.47	AV
H	20960	49.71	30.85	7.45	24.69	51.00	74.00	-23.00	PK
H	20960	41.42	30.85	7.45	24.69	42.71	54.00	-11.29	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
High Channel:5745MHz									
V	11490	48.33	30.55	5.77	24.66	48.21	74.00	-25.79	PK
V	11490	34.76	30.55	5.77	24.66	34.64	54.00	-19.36	AV
V	17235	48.56	30.33	6.32	24.55	49.10	74.00	-24.90	PK
V	17235	41.11	30.33	6.32	24.55	41.65	54.00	-12.35	AV
V	22980	49.03	30.85	7.45	24.69	50.32	74.00	-23.68	PK

V	22980	40.49	30.85	7.45	24.69	41.78	54.00	-12.22	AV
H	11490	48.25	30.55	5.77	24.66	48.13	74.00	-25.87	PK
H	11490	39.96	30.55	5.77	24.66	39.84	54.00	-14.16	AV
H	17235	48.24	30.33	6.32	24.55	48.78	74.00	-25.22	PK
H	17235	40.79	30.33	6.32	24.55	41.33	54.00	-12.67	AV
H	22980	50.96	30.85	7.45	24.69	52.25	74.00	-21.75	PK
H	22980	39.21	30.85	7.45	24.69	40.50	54.00	-13.50	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
High Channel:5785MHz									
V	11570	49.42	30.55	5.77	24.66	49.30	74.00	-24.70	PK
V	11570	33.81	30.55	5.77	24.66	33.69	54.00	-20.31	AV
V	17355	48.37	30.33	6.32	24.55	48.91	74.00	-25.09	PK
V	17355	39.75	30.33	6.32	24.55	40.29	54.00	-13.71	AV
V	23140	49.23	30.85	7.45	24.69	50.52	74.00	-23.48	PK
V	23140	40.69	30.85	7.45	24.69	41.98	54.00	-12.02	AV
H	11570	47.77	30.55	5.77	24.66	47.65	74.00	-26.35	PK
H	11570	38.78	30.55	5.77	24.66	38.66	54.00	-15.34	AV
H	17355	46.80	30.33	6.32	24.55	47.34	74.00	-26.66	PK
H	17355	38.80	30.33	6.32	24.55	39.34	54.00	-14.66	AV
H	23140	49.99	30.85	7.45	24.69	51.28	74.00	-22.72	PK
H	23140	39.71	30.85	7.45	24.69	41.00	54.00	-13.00	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
High Channel:5825MHz									
V	11650	47.42	30.55	5.77	24.66	47.30	74.00	-26.70	PK
V	11650	36.30	30.55	5.77	24.66	36.18	54.00	-17.82	AV
V	17475	49.21	30.33	6.32	24.55	49.75	74.00	-24.25	PK
V	17475	41.08	30.33	6.32	24.55	41.62	54.00	-12.38	AV
V	23300	49.49	30.85	7.45	24.69	50.78	74.00	-23.22	PK
V	23300	38.88	30.85	7.45	24.69	40.17	54.00	-13.83	AV
H	11650	47.64	30.55	5.77	24.66	47.52	74.00	-26.48	PK
H	11650	37.93	30.55	5.77	24.66	37.81	54.00	-16.19	AV
H	17475	48.76	30.33	6.32	24.55	49.30	74.00	-24.70	PK
H	17475	39.71	30.33	6.32	24.55	40.25	54.00	-13.75	AV
H	23300	48.94	30.85	7.45	24.69	50.23	74.00	-23.77	PK
H	23300	39.14	30.85	7.45	24.69	40.43	54.00	-13.57	AV

ANT1-802.11ac40

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
Low Channel:5190MHz									
V	10360	48.52	30.55	5.77	24.66	48.40	74.00	-25.60	PK
V	10360	36.18	30.55	5.77	24.66	36.06	54.00	-17.94	AV
V	15540	47.89	30.33	6.32	24.55	48.43	74.00	-25.57	PK
V	15540	38.87	30.33	6.32	24.55	39.41	54.00	-14.59	AV
V	20720	49.27	30.85	7.45	24.69	50.56	74.00	-23.44	PK
V	20720	40.52	30.85	7.45	24.69	41.81	54.00	-12.19	AV
H	10360	47.08	30.55	5.77	24.66	46.96	74.00	-27.04	PK

H	10360	39.94	30.55	5.77	24.66	39.82	54.00	-14.18	AV
H	15540	48.69	30.33	6.32	24.55	49.23	74.00	-24.77	PK
H	15540	40.63	30.33	6.32	24.55	41.17	54.00	-12.83	AV
H	20720	49.19	30.85	7.45	24.69	50.48	74.00	-23.52	PK
H	20720	39.73	30.85	7.45	24.69	41.02	54.00	-12.98	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
Middle Channel:5230MHz									
V	10460	49.05	30.55	5.77	24.66	48.93	74.00	-25.07	PK
V	10460	36.22	30.55	5.77	24.66	36.10	54.00	-17.90	AV
V	15690	48.32	30.33	6.32	24.55	48.86	74.00	-25.14	PK
V	15690	40.46	30.33	6.32	24.55	41.00	54.00	-13.00	AV
V	20920	51.40	30.85	7.45	24.69	52.69	74.00	-21.31	PK
V	20920	41.46	30.85	7.45	24.69	42.75	54.00	-11.25	AV
H	10460	47.97	30.55	5.77	24.66	47.85	74.00	-26.15	PK
H	10460	39.68	30.55	5.77	24.66	39.56	54.00	-14.44	AV
H	15690	46.89	30.33	6.32	24.55	47.43	74.00	-26.57	PK
H	15690	41.14	30.33	6.32	24.55	41.68	54.00	-12.32	AV
H	20920	48.92	30.85	7.45	24.69	50.21	74.00	-23.79	PK
H	20920	39.05	30.85	7.45	24.69	40.34	54.00	-13.66	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
High Channel:5755MHz									
V	11510	49.74	30.55	5.77	24.66	49.62	74.00	-24.38	PK
V	11510	36.73	30.55	5.77	24.66	36.61	54.00	-17.39	AV
V	17265	49.08	30.33	6.32	24.55	49.62	74.00	-24.38	PK
V	17265	41.55	30.33	6.32	24.55	42.09	54.00	-11.91	AV
V	23020	51.24	30.85	7.45	24.69	52.53	74.00	-21.47	PK
V	23020	39.23	30.85	7.45	24.69	40.52	54.00	-13.48	AV
H	11510	48.48	30.55	5.77	24.66	48.36	74.00	-25.64	PK
H	11510	39.75	30.55	5.77	24.66	39.63	54.00	-14.37	AV
H	17265	48.42	30.33	6.32	24.55	48.96	74.00	-25.04	PK
H	17265	39.31	30.33	6.32	24.55	39.85	54.00	-14.15	AV
H	23020	51.38	30.85	7.45	24.69	52.67	74.00	-21.33	PK
H	23020	41.12	30.85	7.45	24.69	42.41	54.00	-11.59	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
High Channel:5795MHz									
V	11510	47.43	30.55	5.77	24.66	47.31	74.00	-26.69	PK
V	11510	34.06	30.55	5.77	24.66	33.94	54.00	-20.06	AV
V	17265	49.38	30.33	6.32	24.55	49.92	74.00	-24.08	PK
V	17265	40.24	30.33	6.32	24.55	40.78	54.00	-13.22	AV
V	23020	50.81	30.85	7.45	24.69	52.10	74.00	-21.90	PK
V	23020	39.42	30.85	7.45	24.69	40.71	54.00	-13.29	AV
H	11510	48.35	30.55	5.77	24.66	48.23	74.00	-25.77	PK
H	11510	40.16	30.55	5.77	24.66	40.04	54.00	-13.96	AV
H	17265	48.09	30.33	6.32	24.55	48.63	74.00	-25.37	PK
H	17265	41.43	30.33	6.32	24.55	41.97	54.00	-12.03	AV

H	23020	50.93	30.85	7.45	24.69	52.22	74.00	-21.78	PK
H	23020	41.20	30.85	7.45	24.69	42.49	54.00	-11.51	AV

ANT1-802.11ac80

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
5210MHz									
V	10420	48.49	30.55	5.77	24.66	48.37	74.00	-25.63	PK
V	10420	35.46	30.55	5.77	24.66	35.34	54.00	-18.66	AV
V	15630	48.28	30.33	6.32	24.55	48.82	74.00	-25.18	PK
V	15630	40.46	30.33	6.32	24.55	41.00	54.00	-13.00	AV
V	20840	50.68	30.85	7.45	24.69	51.97	74.00	-22.03	PK
V	20840	39.96	30.85	7.45	24.69	41.25	54.00	-12.75	AV
H	10420	47.35	30.55	5.77	24.66	47.23	74.00	-26.77	PK
H	10420	38.13	30.55	5.77	24.66	38.01	54.00	-15.99	AV
H	15630	46.82	30.33	6.32	24.55	47.36	74.00	-26.64	PK
H	15630	39.17	30.33	6.32	24.55	39.71	54.00	-14.29	AV
H	20840	49.96	30.85	7.45	24.69	51.25	74.00	-22.75	PK
H	20840	40.01	30.85	7.45	24.69	41.30	54.00	-12.70	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
High Channel:5775MHz									
V	11550	47.82	30.55	5.77	24.66	47.70	74.00	-26.30	PK
V	11550	35.51	30.55	5.77	24.66	35.39	54.00	-18.61	AV
V	17325	48.32	30.33	6.32	24.55	48.86	74.00	-25.14	PK
V	17325	39.70	30.33	6.32	24.55	40.24	54.00	-13.76	AV
V	23100	48.84	30.85	7.45	24.69	50.13	74.00	-23.87	PK
V	23100	39.56	30.85	7.45	24.69	40.85	54.00	-13.15	AV
H	11550	46.30	30.55	5.77	24.66	46.18	74.00	-27.82	PK
H	11550	39.44	30.55	5.77	24.66	39.32	54.00	-14.68	AV
H	17325	46.85	30.33	6.32	24.55	47.39	74.00	-26.61	PK
H	17325	39.31	30.33	6.32	24.55	39.85	54.00	-14.15	AV
H	23100	51.58	30.85	7.45	24.69	52.87	74.00	-21.13	PK
H	23100	38.89	30.85	7.45	24.69	40.18	54.00	-13.82	AV

ANT2-802.11a

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
Low Channel:5180MHz									
V	10360	48.23	30.55	5.77	24.66	48.11	74.00	-25.89	PK
V	10360	35.59	30.55	5.77	24.66	35.47	54.00	-18.53	AV
V	15540	49.22	30.33	6.32	24.55	49.76	74.00	-24.24	PK
V	15540	38.97	30.33	6.32	24.55	39.51	54.00	-14.49	AV
V	20720	49.80	30.85	7.45	24.69	51.09	74.00	-22.91	PK
V	20720	40.49	30.85	7.45	24.69	41.78	54.00	-12.22	AV
H	10360	48.42	30.55	5.77	24.66	48.30	74.00	-25.70	PK
H	10360	39.49	30.55	5.77	24.66	39.37	54.00	-14.63	AV
H	15540	48.24	30.33	6.32	24.55	48.78	74.00	-25.22	PK
H	15540	39.69	30.33	6.32	24.55	40.23	54.00	-13.77	AV
H	20720	49.24	30.85	7.45	24.69	50.53	74.00	-23.47	PK
H	20720	39.74	30.85	7.45	24.69	41.03	54.00	-12.97	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
Middle Channel:5200MHz									
V	10400	47.73	30.55	5.77	24.66	47.61	74.00	-26.39	PK
V	10400	35.05	30.55	5.77	24.66	34.93	54.00	-19.07	AV
V	15600	47.83	30.33	6.32	24.55	48.37	74.00	-25.63	PK
V	15600	40.22	30.33	6.32	24.55	40.76	54.00	-13.24	AV
V	20800	50.52	30.85	7.45	24.69	51.81	74.00	-22.19	PK
V	20800	41.51	30.85	7.45	24.69	42.80	54.00	-11.20	AV
H	10400	48.37	30.55	5.77	24.66	48.25	74.00	-25.75	PK
H	10400	38.24	30.55	5.77	24.66	38.12	54.00	-15.88	AV
H	15600	47.29	30.33	6.32	24.55	47.83	74.00	-26.17	PK
H	15600	40.86	30.33	6.32	24.55	41.40	54.00	-12.60	AV
H	20800	50.87	30.85	7.45	24.69	52.16	74.00	-21.84	PK
H	20800	38.81	30.85	7.45	24.69	40.10	54.00	-13.90	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
High Channel:5240MHz									
V	10480	48.92	30.55	5.77	24.66	48.80	74.00	-25.20	PK
V	10480	35.71	30.55	5.77	24.66	35.59	54.00	-18.41	AV
V	15720	48.06	30.33	6.32	24.55	48.60	74.00	-25.40	PK
V	15720	39.40	30.33	6.32	24.55	39.94	54.00	-14.06	AV
V	20960	50.42	30.85	7.45	24.69	51.71	74.00	-22.29	PK
V	20960	39.96	30.85	7.45	24.69	41.25	54.00	-12.75	AV
H	10480	47.77	30.55	5.77	24.66	47.65	74.00	-26.35	PK
H	10480	38.55	30.55	5.77	24.66	38.43	54.00	-15.57	AV
H	15720	47.65	30.33	6.32	24.55	48.19	74.00	-25.81	PK
H	15720	39.39	30.33	6.32	24.55	39.93	54.00	-14.07	AV
H	20960	50.48	30.85	7.45	24.69	51.77	74.00	-22.23	PK
H	20960	38.90	30.85	7.45	24.69	40.19	54.00	-13.81	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
High Channel:5745MHz									
V	11490	49.60	30.55	5.77	24.66	49.48	74.00	-24.52	PK
V	11490	36.34	30.55	5.77	24.66	36.22	54.00	-17.78	AV
V	17235	48.44	30.33	6.32	24.55	48.98	74.00	-25.02	PK
V	17235	40.22	30.33	6.32	24.55	40.76	54.00	-13.24	AV
V	22980	50.47	30.85	7.45	24.69	51.76	74.00	-22.24	PK
V	22980	40.87	30.85	7.45	24.69	42.16	54.00	-11.84	AV
H	11490	47.37	30.55	5.77	24.66	47.25	74.00	-26.75	PK
H	11490	38.04	30.55	5.77	24.66	37.92	54.00	-16.08	AV
H	17235	46.91	30.33	6.32	24.55	47.45	74.00	-26.55	PK
H	17235	40.10	30.33	6.32	24.55	40.64	54.00	-13.36	AV
H	22980	49.34	30.85	7.45	24.69	50.63	74.00	-23.37	PK
H	22980	40.89	30.85	7.45	24.69	42.18	54.00	-11.82	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBUV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBUV/m)	Limits (dBUV/m)	Margin (dB)	Detector Type
High Channel:5785MHz									
V	11570	49.61	30.55	5.77	24.66	49.49	74.00	-24.51	PK
V	11570	33.82	30.55	5.77	24.66	33.70	54.00	-20.30	AV
V	17355	49.13	30.33	6.32	24.55	49.67	74.00	-24.33	PK
V	17355	38.90	30.33	6.32	24.55	39.44	54.00	-14.56	AV
V	23140	51.58	30.85	7.45	24.69	52.87	74.00	-21.13	PK
V	23140	41.06	30.85	7.45	24.69	42.35	54.00	-11.65	AV
H	11570	46.12	30.55	5.77	24.66	46.00	74.00	-28.00	PK
H	11570	40.44	30.55	5.77	24.66	40.32	54.00	-13.68	AV
H	17355	48.19	30.33	6.32	24.55	48.73	74.00	-25.27	PK
H	17355	38.84	30.33	6.32	24.55	39.38	54.00	-14.62	AV
H	23140	51.28	30.85	7.45	24.69	52.57	74.00	-21.43	PK
H	23140	40.87	30.85	7.45	24.69	42.16	54.00	-11.84	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBUV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBUV/m)	Limits (dBUV/m)	Margin (dB)	Detector Type
High Channel:5825MHz									
V	11650	48.76	30.55	5.77	24.66	48.64	74.00	-25.36	PK
V	11650	35.54	30.55	5.77	24.66	35.42	54.00	-18.58	AV
V	17475	48.63	30.33	6.32	24.55	49.17	74.00	-24.83	PK
V	17475	38.99	30.33	6.32	24.55	39.53	54.00	-14.47	AV
V	23300	50.12	30.85	7.45	24.69	51.41	74.00	-22.59	PK
V	23300	40.71	30.85	7.45	24.69	42.00	54.00	-12.00	AV
H	11650	47.60	30.55	5.77	24.66	47.48	74.00	-26.52	PK
H	11650	39.92	30.55	5.77	24.66	39.80	54.00	-14.20	AV
H	17475	48.38	30.33	6.32	24.55	48.92	74.00	-25.08	PK
H	17475	39.61	30.33	6.32	24.55	40.15	54.00	-13.85	AV
H	23300	50.32	30.85	7.45	24.69	51.61	74.00	-22.39	PK
H	23300	39.20	30.85	7.45	24.69	40.49	54.00	-13.51	AV

ANT2-802.11n20

Polar (H/V)	Frequency (MHz)	Meter Reading (dBUV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBUV/m)	Limits (dBUV/m)	Margin (dB)	Detector Type
Low Channel:5180MHz									
V	10360	47.28	30.55	5.77	24.66	47.16	74.00	-26.84	PK
V	10360	33.79	30.55	5.77	24.66	33.67	54.00	-20.33	AV
V	15540	48.84	30.33	6.32	24.55	49.38	74.00	-24.62	PK
V	15540	41.09	30.33	6.32	24.55	41.63	54.00	-12.37	AV
V	20720	49.69	30.85	7.45	24.69	50.98	74.00	-23.02	PK
V	20720	38.95	30.85	7.45	24.69	40.24	54.00	-13.76	AV
H	10360	48.47	30.55	5.77	24.66	48.35	74.00	-25.65	PK
H	10360	37.77	30.55	5.77	24.66	37.65	54.00	-16.35	AV
H	15540	46.98	30.33	6.32	24.55	47.52	74.00	-26.48	PK
H	15540	41.35	30.33	6.32	24.55	41.89	54.00	-12.11	AV
H	20720	49.20	30.85	7.45	24.69	50.49	74.00	-23.51	PK
H	20720	41.61	30.85	7.45	24.69	42.90	54.00	-11.10	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBUV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBUV/m)	Limits (dBUV/m)	Margin (dB)	Detector Type
-------------	-----------------	----------------------	--------------------	-----------------	---------------------	-------------------------	-----------------	-------------	---------------

Middle Channel:5200MHz									
V	10400	46.83	30.55	5.77	24.66	46.71	74.00	-27.29	PK
V	10400	34.49	30.55	5.77	24.66	34.37	54.00	-19.63	AV
V	15600	48.90	30.33	6.32	24.55	49.44	74.00	-24.56	PK
V	15600	40.98	30.33	6.32	24.55	41.52	54.00	-12.48	AV
V	20800	50.44	30.85	7.45	24.69	51.73	74.00	-22.27	PK
V	20800	39.65	30.85	7.45	24.69	40.94	54.00	-13.06	AV
H	10400	46.19	30.55	5.77	24.66	46.07	74.00	-27.93	PK
H	10400	39.34	30.55	5.77	24.66	39.22	54.00	-14.78	AV
H	15600	47.91	30.33	6.32	24.55	48.45	74.00	-25.55	PK
H	15600	38.88	30.33	6.32	24.55	39.42	54.00	-14.58	AV
H	20800	50.75	30.85	7.45	24.69	52.04	74.00	-21.96	PK
H	20800	39.04	30.85	7.45	24.69	40.33	54.00	-13.67	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
High Channel:5240MHz									
V	10480	48.49	30.55	5.77	24.66	48.37	74.00	-25.63	PK
V	10480	34.18	30.55	5.77	24.66	34.06	54.00	-19.94	AV
V	15720	48.77	30.33	6.32	24.55	49.31	74.00	-24.69	PK
V	15720	41.55	30.33	6.32	24.55	42.09	54.00	-11.91	AV
V	20960	50.12	30.85	7.45	24.69	51.41	74.00	-22.59	PK
V	20960	40.39	30.85	7.45	24.69	41.68	54.00	-12.32	AV
H	10480	48.50	30.55	5.77	24.66	48.38	74.00	-25.62	PK
H	10480	38.05	30.55	5.77	24.66	37.93	54.00	-16.07	AV
H	15720	47.24	30.33	6.32	24.55	47.78	74.00	-26.22	PK
H	15720	40.10	30.33	6.32	24.55	40.64	54.00	-13.36	AV
H	20960	50.07	30.85	7.45	24.69	51.36	74.00	-22.64	PK
H	20960	39.95	30.85	7.45	24.69	41.24	54.00	-12.76	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
High Channel:5745MHz									
V	11490	49.29	30.55	5.77	24.66	49.17	74.00	-24.83	PK
V	11490	35.35	30.55	5.77	24.66	35.23	54.00	-18.77	AV
V	17235	49.55	30.33	6.32	24.55	50.09	74.00	-23.91	PK
V	17235	39.71	30.33	6.32	24.55	40.25	54.00	-13.75	AV
V	22980	51.43	30.85	7.45	24.69	52.72	74.00	-21.28	PK
V	22980	38.81	30.85	7.45	24.69	40.10	54.00	-13.90	AV
H	11490	45.85	30.55	5.77	24.66	45.73	74.00	-28.27	PK
H	11490	39.48	30.55	5.77	24.66	39.36	54.00	-14.64	AV
H	17235	48.12	30.33	6.32	24.55	48.66	74.00	-25.34	PK
H	17235	39.53	30.33	6.32	24.55	40.07	54.00	-13.93	AV
H	22980	50.81	30.85	7.45	24.69	52.10	74.00	-21.90	PK
H	22980	39.29	30.85	7.45	24.69	40.58	54.00	-13.42	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
High Channel:5785MHz									
V	11570	49.11	30.55	5.77	24.66	48.99	74.00	-25.01	PK
V	11570	35.35	30.55	5.77	24.66	35.23	54.00	-18.77	AV

V	17355	49.55	30.33	6.32	24.55	50.09	74.00	-23.91	PK
V	17355	40.62	30.33	6.32	24.55	41.16	54.00	-12.84	AV
V	23140	49.93	30.85	7.45	24.69	51.22	74.00	-22.78	PK
V	23140	39.44	30.85	7.45	24.69	40.73	54.00	-13.27	AV
H	11570	47.96	30.55	5.77	24.66	47.84	74.00	-26.16	PK
H	11570	40.27	30.55	5.77	24.66	40.15	54.00	-13.85	AV
H	17355	47.46	30.33	6.32	24.55	48.00	74.00	-26.00	PK
H	17355	39.07	30.33	6.32	24.55	39.61	54.00	-14.39	AV
H	23140	50.44	30.85	7.45	24.69	51.73	74.00	-22.27	PK
H	23140	41.11	30.85	7.45	24.69	42.40	54.00	-11.60	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBUV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBUV/m)	Limits (dBUV/m)	Margin (dB)	Detector Type
High Channel:5825MHz									
V	11650	48.62	30.55	5.77	24.66	48.50	74.00	-25.50	PK
V	11650	35.78	30.55	5.77	24.66	35.66	54.00	-18.34	AV
V	17475	49.45	30.33	6.32	24.55	49.99	74.00	-24.01	PK
V	17475	38.93	30.33	6.32	24.55	39.47	54.00	-14.53	AV
V	23300	50.31	30.85	7.45	24.69	51.60	74.00	-22.40	PK
V	23300	39.62	30.85	7.45	24.69	40.91	54.00	-13.09	AV
H	11650	46.52	30.55	5.77	24.66	46.40	74.00	-27.60	PK
H	11650	37.84	30.55	5.77	24.66	37.72	54.00	-16.28	AV
H	17475	47.58	30.33	6.32	24.55	48.12	74.00	-25.88	PK
H	17475	38.89	30.33	6.32	24.55	39.43	54.00	-14.57	AV
H	23300	49.96	30.85	7.45	24.69	51.25	74.00	-22.75	PK
H	23300	41.28	30.85	7.45	24.69	42.57	54.00	-11.43	AV

ANT2-802.11n40

Polar (H/V)	Frequency (MHz)	Meter Reading (dBUV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBUV/m)	Limits (dBUV/m)	Margin (dB)	Detector Type
Low Channel:5190MHz									
V	10360	49.19	30.55	5.77	24.66	49.07	74.00	-24.93	PK
V	10360	35.84	30.55	5.77	24.66	35.72	54.00	-18.28	AV
V	15540	48.71	30.33	6.32	24.55	49.25	74.00	-24.75	PK
V	15540	39.49	30.33	6.32	24.55	40.03	54.00	-13.97	AV
V	20720	50.01	30.85	7.45	24.69	51.30	74.00	-22.70	PK
V	20720	41.09	30.85	7.45	24.69	42.38	54.00	-11.62	AV
H	10360	47.60	30.55	5.77	24.66	47.48	74.00	-26.52	PK
H	10360	40.24	30.55	5.77	24.66	40.12	54.00	-13.88	AV
H	15540	46.80	30.33	6.32	24.55	47.34	74.00	-26.66	PK
H	15540	40.10	30.33	6.32	24.55	40.64	54.00	-13.36	AV
H	20720	49.50	30.85	7.45	24.69	50.79	74.00	-23.21	PK
H	20720	40.53	30.85	7.45	24.69	41.82	54.00	-12.18	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBUV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBUV/m)	Limits (dBUV/m)	Margin (dB)	Detector Type
Middle Channel:5230MHz									
V	10460	46.83	30.55	5.77	24.66	46.71	74.00	-27.29	PK
V	10460	34.93	30.55	5.77	24.66	34.81	54.00	-19.19	AV
V	15690	48.75	30.33	6.32	24.55	49.29	74.00	-24.71	PK
V	15690	39.57	30.33	6.32	24.55	40.11	54.00	-13.89	AV
V	20920	50.08	30.85	7.45	24.69	51.37	74.00	-22.63	PK

V	20920	40.04	30.85	7.45	24.69	41.33	54.00	-12.67	AV
H	10460	47.93	30.55	5.77	24.66	47.81	74.00	-26.19	PK
H	10460	38.75	30.55	5.77	24.66	38.63	54.00	-15.37	AV
H	15690	47.70	30.33	6.32	24.55	48.24	74.00	-25.76	PK
H	15690	39.95	30.33	6.32	24.55	40.49	54.00	-13.51	AV
H	20920	51.50	30.85	7.45	24.69	52.79	74.00	-21.21	PK
H	20920	40.89	30.85	7.45	24.69	42.18	54.00	-11.82	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
High Channel:5755MHz									
V	11510	48.21	30.55	5.77	24.66	48.09	74.00	-25.91	PK
V	11510	34.23	30.55	5.77	24.66	34.11	54.00	-19.89	AV
V	17265	48.46	30.33	6.32	24.55	49.00	74.00	-25.00	PK
V	17265	39.31	30.33	6.32	24.55	39.85	54.00	-14.15	AV
V	23020	49.17	30.85	7.45	24.69	50.46	74.00	-23.54	PK
V	23020	40.32	30.85	7.45	24.69	41.61	54.00	-12.39	AV
H	11510	45.82	30.55	5.77	24.66	45.70	74.00	-28.30	PK
H	11510	38.04	30.55	5.77	24.66	37.92	54.00	-16.08	AV
H	17265	47.64	30.33	6.32	24.55	48.18	74.00	-25.82	PK
H	17265	41.23	30.33	6.32	24.55	41.77	54.00	-12.23	AV
H	23020	51.64	30.85	7.45	24.69	52.93	74.00	-21.07	PK
H	23020	40.70	30.85	7.45	24.69	41.99	54.00	-12.01	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
High Channel:5795MHz									
V	11590	48.76	30.55	5.77	24.66	48.64	74.00	-25.36	PK
V	11590	35.42	30.55	5.77	24.66	35.30	54.00	-18.70	AV
V	17385	48.92	30.33	6.32	24.55	49.46	74.00	-24.54	PK
V	17385	41.53	30.33	6.32	24.55	42.07	54.00	-11.93	AV
V	23180	49.18	30.85	7.45	24.69	50.47	74.00	-23.53	PK
V	23180	39.71	30.85	7.45	24.69	41.00	54.00	-13.00	AV
H	11590	47.27	30.55	5.77	24.66	47.15	74.00	-26.85	PK
H	11590	38.63	30.55	5.77	24.66	38.51	54.00	-15.49	AV
H	17385	47.98	30.33	6.32	24.55	48.52	74.00	-25.48	PK
H	17385	39.78	30.33	6.32	24.55	40.32	54.00	-13.68	AV
H	23180	49.08	30.85	7.45	24.69	50.37	74.00	-23.63	PK
H	23180	40.10	30.85	7.45	24.69	41.39	54.00	-12.61	AV

ANT2--802.11ac20

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
Low Channel:5180MHz									
V	10360	47.35	30.55	5.77	24.66	47.23	74.00	-26.77	PK
V	10360	35.16	30.55	5.77	24.66	35.04	54.00	-18.96	AV
V	15540	48.28	30.33	6.32	24.55	48.82	74.00	-25.18	PK
V	15540	39.43	30.33	6.32	24.55	39.97	54.00	-14.03	AV
V	20720	51.72	30.85	7.45	24.69	53.01	74.00	-20.99	PK
V	20720	41.09	30.85	7.45	24.69	42.38	54.00	-11.62	AV
H	10360	47.04	30.55	5.77	24.66	46.92	74.00	-27.08	PK
H	10360	39.24	30.55	5.77	24.66	39.12	54.00	-14.88	AV

H	15540	48.41	30.33	6.32	24.55	48.95	74.00	-25.05	PK
H	15540	41.32	30.33	6.32	24.55	41.86	54.00	-12.14	AV
H	20720	50.45	30.85	7.45	24.69	51.74	74.00	-22.26	PK
H	20720	38.87	30.85	7.45	24.69	40.16	54.00	-13.84	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amp lifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
Middle Channel:5200MHz									
V	10400	49.39	30.55	5.77	24.66	49.27	74.00	-24.73	PK
V	10400	34.58	30.55	5.77	24.66	34.46	54.00	-19.54	AV
V	15600	49.02	30.33	6.32	24.55	49.56	74.00	-24.44	PK
V	15600	40.94	30.33	6.32	24.55	41.48	54.00	-12.52	AV
V	20800	49.69	30.85	7.45	24.69	50.98	74.00	-23.02	PK
V	20800	41.63	30.85	7.45	24.69	42.92	54.00	-11.08	AV
H	10400	46.26	30.55	5.77	24.66	46.14	74.00	-27.86	PK
H	10400	40.58	30.55	5.77	24.66	40.46	54.00	-13.54	AV
H	15600	48.07	30.33	6.32	24.55	48.61	74.00	-25.39	PK
H	15600	41.72	30.33	6.32	24.55	42.26	54.00	-11.74	AV
H	20800	51.31	30.85	7.45	24.69	52.60	74.00	-21.40	PK
H	20800	40.15	30.85	7.45	24.69	41.44	54.00	-12.56	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
High Channel:5240MHz									
V	10480	48.10	30.55	5.77	24.66	47.98	74.00	-26.02	PK
V	10480	34.50	30.55	5.77	24.66	34.38	54.00	-19.62	AV
V	15720	48.89	30.33	6.32	24.55	49.43	74.00	-24.57	PK
V	15720	40.54	30.33	6.32	24.55	41.08	54.00	-12.92	AV
V	20960	49.17	30.85	7.45	24.69	50.46	74.00	-23.54	PK
V	20960	41.00	30.85	7.45	24.69	42.29	54.00	-11.71	AV
H	10480	47.23	30.55	5.77	24.66	47.11	74.00	-26.89	PK
H	10480	39.87	30.55	5.77	24.66	39.75	54.00	-14.25	AV
H	15720	48.37	30.33	6.32	24.55	48.91	74.00	-25.09	PK
H	15720	41.22	30.33	6.32	24.55	41.76	54.00	-12.24	AV
H	20960	50.04	30.85	7.45	24.69	51.33	74.00	-22.67	PK
H	20960	41.05	30.85	7.45	24.69	42.34	54.00	-11.66	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
High Channel:5745MHz									
V	11490	47.81	30.55	5.77	24.66	47.69	74.00	-26.31	PK
V	11490	34.76	30.55	5.77	24.66	34.64	54.00	-19.36	AV
V	17235	49.71	30.33	6.32	24.55	50.25	74.00	-23.75	PK
V	17235	39.88	30.33	6.32	24.55	40.42	54.00	-13.58	AV
V	22980	49.56	30.85	7.45	24.69	50.85	74.00	-23.15	PK
V	22980	40.56	30.85	7.45	24.69	41.85	54.00	-12.15	AV
H	11490	48.31	30.55	5.77	24.66	48.19	74.00	-25.81	PK
H	11490	38.19	30.55	5.77	24.66	38.07	54.00	-15.93	AV
H	17235	48.61	30.33	6.32	24.55	49.15	74.00	-24.85	PK
H	17235	39.88	30.33	6.32	24.55	40.42	54.00	-13.58	AV
H	22980	51.20	30.85	7.45	24.69	52.49	74.00	-21.51	PK

H	22980	40.79	30.85	7.45	24.69	42.08	54.00	-11.92	AV
---	-------	-------	-------	------	-------	-------	-------	--------	----

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
High Channel:5785MHz									
V	11570	47.78	30.55	5.77	24.66	47.66	74.00	-26.34	PK
V	11570	35.01	30.55	5.77	24.66	34.89	54.00	-19.11	AV
V	17355	48.71	30.33	6.32	24.55	49.25	74.00	-24.75	PK
V	17355	40.37	30.33	6.32	24.55	40.91	54.00	-13.09	AV
V	23140	49.09	30.85	7.45	24.69	50.38	74.00	-23.62	PK
V	23140	40.79	30.85	7.45	24.69	42.08	54.00	-11.92	AV
H	11570	46.65	30.55	5.77	24.66	46.53	74.00	-27.47	PK
H	11570	40.44	30.55	5.77	24.66	40.32	54.00	-13.68	AV
H	17355	48.26	30.33	6.32	24.55	48.80	74.00	-25.20	PK
H	17355	41.71	30.33	6.32	24.55	42.25	54.00	-11.75	AV
H	23140	49.12	30.85	7.45	24.69	50.41	74.00	-23.59	PK
H	23140	41.33	30.85	7.45	24.69	42.62	54.00	-11.38	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
High Channel:5825MHz									
V	11650	48.55	30.55	5.77	24.66	48.43	74.00	-25.57	PK
V	11650	34.95	30.55	5.77	24.66	34.83	54.00	-19.17	AV
V	17475	48.26	30.33	6.32	24.55	48.80	74.00	-25.20	PK
V	17475	39.44	30.33	6.32	24.55	39.98	54.00	-14.02	AV
V	23300	49.48	30.85	7.45	24.69	50.77	74.00	-23.23	PK
V	23300	40.87	30.85	7.45	24.69	42.16	54.00	-11.84	AV
H	11650	47.52	30.55	5.77	24.66	47.40	74.00	-26.60	PK
H	11650	37.99	30.55	5.77	24.66	37.87	54.00	-16.13	AV
H	17475	47.19	30.33	6.32	24.55	47.73	74.00	-26.27	PK
H	17475	39.86	30.33	6.32	24.55	40.40	54.00	-13.60	AV
H	23300	50.20	30.85	7.45	24.69	51.49	74.00	-22.51	PK
H	23300	40.88	30.85	7.45	24.69	42.17	54.00	-11.83	AV

ANT2-802.11ac40

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
Low Channel:5190MHz									
V	10360	47.96	30.55	5.77	24.66	47.84	74.00	-26.16	PK
V	10360	36.59	30.55	5.77	24.66	36.47	54.00	-17.53	AV
V	15540	48.83	30.33	6.32	24.55	49.37	74.00	-24.63	PK
V	15540	39.49	30.33	6.32	24.55	40.03	54.00	-13.97	AV
V	20720	51.65	30.85	7.45	24.69	52.94	74.00	-21.06	PK
V	20720	40.06	30.85	7.45	24.69	41.35	54.00	-12.65	AV
H	10360	45.88	30.55	5.77	24.66	45.76	74.00	-28.24	PK
H	10360	38.58	30.55	5.77	24.66	38.46	54.00	-15.54	AV
H	15540	47.11	30.33	6.32	24.55	47.65	74.00	-26.35	PK
H	15540	41.02	30.33	6.32	24.55	41.56	54.00	-12.44	AV
H	20720	49.31	30.85	7.45	24.69	50.60	74.00	-23.40	PK
H	20720	40.89	30.85	7.45	24.69	42.18	54.00	-11.82	AV

Polar (H/V)	Frequency	Meter Readin g	Pre-ampli fier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Middle Channel:5230MHz									
V	10460	49.03	30.55	5.77	24.66	48.91	74.00	-25.09	PK
V	10460	36.58	30.55	5.77	24.66	36.46	54.00	-17.54	AV
V	15690	47.77	30.33	6.32	24.55	48.31	74.00	-25.69	PK
V	15690	40.70	30.33	6.32	24.55	41.24	54.00	-12.76	AV
V	20920	50.82	30.85	7.45	24.69	52.11	74.00	-21.89	PK
V	20920	39.52	30.85	7.45	24.69	40.81	54.00	-13.19	AV
H	10460	47.93	30.55	5.77	24.66	47.81	74.00	-26.19	PK
H	10460	40.07	30.55	5.77	24.66	39.95	54.00	-14.05	AV
H	15690	48.17	30.33	6.32	24.55	48.71	74.00	-25.29	PK
H	15690	41.15	30.33	6.32	24.55	41.69	54.00	-12.31	AV
H	20920	51.42	30.85	7.45	24.69	52.71	74.00	-21.29	PK
H	20920	40.26	30.85	7.45	24.69	41.55	54.00	-12.45	AV

Polar (H/V)	Frequency	Meter Reading	Pre-amp lifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
High Channel:5755MHz									
V	11510	48.85	30.55	5.77	24.66	48.73	74.00	-25.27	PK
V	11510	34.07	30.55	5.77	24.66	33.95	54.00	-20.05	AV
V	17265	47.90	30.33	6.32	24.55	48.44	74.00	-25.56	PK
V	17265	40.75	30.33	6.32	24.55	41.29	54.00	-12.71	AV
V	23020	49.30	30.85	7.45	24.69	50.59	74.00	-23.41	PK
V	23020	39.19	30.85	7.45	24.69	40.48	54.00	-13.52	AV
H	11510	46.05	30.55	5.77	24.66	45.93	74.00	-28.07	PK
H	11510	38.44	30.55	5.77	24.66	38.32	54.00	-15.68	AV
H	17265	47.95	30.33	6.32	24.55	48.49	74.00	-25.51	PK
H	17265	40.92	30.33	6.32	24.55	41.46	54.00	-12.54	AV
H	23020	51.03	30.85	7.45	24.69	52.32	74.00	-21.68	PK
H	23020	39.08	30.85	7.45	24.69	40.37	54.00	-13.63	AV

Polar (H/V)	Frequency	Meter Reading	Pre-amp lifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
High Channel:5795MHz									
V	11510	49.47	30.55	5.77	24.66	49.35	74.00	-24.65	PK
V	11510	33.99	30.55	5.77	24.66	33.87	54.00	-20.13	AV
V	17265	49.58	30.33	6.32	24.55	50.12	74.00	-23.88	PK
V	17265	40.74	30.33	6.32	24.55	41.28	54.00	-12.72	AV
V	23020	49.65	30.85	7.45	24.69	50.94	74.00	-23.06	PK
V	23020	40.09	30.85	7.45	24.69	41.38	54.00	-12.62	AV
H	11510	46.25	30.55	5.77	24.66	46.13	74.00	-27.87	PK
H	11510	37.83	30.55	5.77	24.66	37.71	54.00	-16.29	AV
H	17265	47.31	30.33	6.32	24.55	47.85	74.00	-26.15	PK
H	17265	39.00	30.33	6.32	24.55	39.54	54.00	-14.46	AV
H	23020	49.34	30.85	7.45	24.69	50.63	74.00	-23.37	PK
H	23020	38.83	30.85	7.45	24.69	40.12	54.00	-13.88	AV

ANT2-802.11ac80

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
5210MHz									
V	10420	47.37	30.55	5.77	24.66	47.25	74.00	-26.75	PK
V	10420	36.25	30.55	5.77	24.66	36.13	54.00	-17.87	AV
V	15630	48.87	30.33	6.32	24.55	49.41	74.00	-24.59	PK
V	15630	40.62	30.33	6.32	24.55	41.16	54.00	-12.84	AV
V	20840	49.86	30.85	7.45	24.69	51.15	74.00	-22.85	PK
V	20840	39.19	30.85	7.45	24.69	40.48	54.00	-13.52	AV
H	10420	46.46	30.55	5.77	24.66	46.34	74.00	-27.66	PK
H	10420	40.15	30.55	5.77	24.66	40.03	54.00	-13.97	AV
H	15630	47.38	30.33	6.32	24.55	47.92	74.00	-26.08	PK
H	15630	41.06	30.33	6.32	24.55	41.60	54.00	-12.40	AV
H	20840	51.67	30.85	7.45	24.69	52.96	74.00	-21.04	PK
H	20840	38.90	30.85	7.45	24.69	40.19	54.00	-13.81	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
High Channel:5775MHz									
V	11550	47.93	30.55	5.77	24.66	47.81	74.00	-26.19	PK
V	11550	34.31	30.55	5.77	24.66	34.19	54.00	-19.81	AV
V	17325	49.71	30.33	6.32	24.55	50.25	74.00	-23.75	PK
V	17325	41.16	30.33	6.32	24.55	41.70	54.00	-12.30	AV
V	23100	49.78	30.85	7.45	24.69	51.07	74.00	-22.93	PK
V	23100	41.48	30.85	7.45	24.69	42.77	54.00	-11.23	AV
H	11550	46.96	30.55	5.77	24.66	46.84	74.00	-27.16	PK
H	11550	39.43	30.55	5.77	24.66	39.31	54.00	-14.69	AV
H	17325	47.58	30.33	6.32	24.55	48.12	74.00	-25.88	PK
H	17325	41.23	30.33	6.32	24.55	41.77	54.00	-12.23	AV
H	23100	51.37	30.85	7.45	24.69	52.66	74.00	-21.34	PK
H	23100	39.93	30.85	7.45	24.69	41.22	54.00	-12.78	AV

MIMO-802.11n20

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
Low Channel:5180MHz									
V	10360	47.06	30.55	5.77	24.66	46.94	74.00	-27.06	PK
V	10360	36.51	30.55	5.77	24.66	36.39	54.00	-17.61	AV
V	15540	48.70	30.33	6.32	24.55	49.24	74.00	-24.76	PK
V	15540	41.30	30.33	6.32	24.55	41.84	54.00	-12.16	AV
V	20720	49.47	30.85	7.45	24.69	50.76	74.00	-23.24	PK
V	20720	41.10	30.85	7.45	24.69	42.39	54.00	-11.61	AV
H	10360	47.93	30.55	5.77	24.66	47.81	74.00	-26.19	PK
H	10360	38.65	30.55	5.77	24.66	38.53	54.00	-15.47	AV
H	15540	47.55	30.33	6.32	24.55	48.09	74.00	-25.91	PK
H	15540	40.30	30.33	6.32	24.55	40.84	54.00	-13.16	AV
H	20720	50.64	30.85	7.45	24.69	51.93	74.00	-22.07	PK
H	20720	41.14	30.85	7.45	24.69	42.43	54.00	-11.57	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
Middle Channel:5200MHz									
V	10400	48.35	30.55	5.77	24.66	48.23	74.00	-25.77	PK
V	10400	36.50	30.55	5.77	24.66	36.38	54.00	-17.62	AV
V	15600	49.26	30.33	6.32	24.55	49.80	74.00	-24.20	PK
V	15600	39.57	30.33	6.32	24.55	40.11	54.00	-13.89	AV
V	20800	49.59	30.85	7.45	24.69	50.88	74.00	-23.12	PK
V	20800	39.09	30.85	7.45	24.69	40.38	54.00	-13.62	AV
H	10400	46.97	30.55	5.77	24.66	46.85	74.00	-27.15	PK
H	10400	38.92	30.55	5.77	24.66	38.80	54.00	-15.20	AV
H	15600	48.34	30.33	6.32	24.55	48.88	74.00	-25.12	PK
H	15600	41.18	30.33	6.32	24.55	41.72	54.00	-12.28	AV
H	20800	49.40	30.85	7.45	24.69	50.69	74.00	-23.31	PK
H	20800	41.05	30.85	7.45	24.69	42.34	54.00	-11.66	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
High Channel:5240MHz									
V	10480	49.48	30.55	5.77	24.66	49.36	74.00	-24.64	PK
V	10480	35.95	30.55	5.77	24.66	35.83	54.00	-18.17	AV
V	15720	48.04	30.33	6.32	24.55	48.58	74.00	-25.42	PK
V	15720	38.79	30.33	6.32	24.55	39.33	54.00	-14.67	AV
V	20960	51.24	30.85	7.45	24.69	52.53	74.00	-21.47	PK
V	20960	39.92	30.85	7.45	24.69	41.21	54.00	-12.79	AV
H	10480	45.82	30.55	5.77	24.66	45.70	74.00	-28.30	PK
H	10480	39.71	30.55	5.77	24.66	39.59	54.00	-14.41	AV
H	15720	47.98	30.33	6.32	24.55	48.52	74.00	-25.48	PK
H	15720	39.07	30.33	6.32	24.55	39.61	54.00	-14.39	AV
H	20960	51.32	30.85	7.45	24.69	52.61	74.00	-21.39	PK
H	20960	40.34	30.85	7.45	24.69	41.63	54.00	-12.37	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
High Channel:5745MHz									
V	11490	46.91	30.55	5.77	24.66	46.79	74.00	-27.21	PK
V	11490	34.85	30.55	5.77	24.66	34.73	54.00	-19.27	AV
V	17235	49.50	30.33	6.32	24.55	50.04	74.00	-23.96	PK
V	17235	39.63	30.33	6.32	24.55	40.17	54.00	-13.83	AV
V	22980	50.90	30.85	7.45	24.69	52.19	74.00	-21.81	PK
V	22980	41.52	30.85	7.45	24.69	42.81	54.00	-11.19	AV
H	11490	46.75	30.55	5.77	24.66	46.63	74.00	-27.37	PK
H	11490	38.74	30.55	5.77	24.66	38.62	54.00	-15.38	AV
H	17235	47.67	30.33	6.32	24.55	48.21	74.00	-25.79	PK
H	17235	39.40	30.33	6.32	24.55	39.94	54.00	-14.06	AV
H	22980	50.99	30.85	7.45	24.69	52.28	74.00	-21.72	PK
H	22980	39.66	30.85	7.45	24.69	40.95	54.00	-13.05	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
High Channel:5785MHz									
V	11570	49.69	30.55	5.77	24.66	49.57	74.00	-24.43	PK
V	11570	34.93	30.55	5.77	24.66	34.81	54.00	-19.19	AV
V	17355	48.79	30.33	6.32	24.55	49.33	74.00	-24.67	PK
V	17355	40.74	30.33	6.32	24.55	41.28	54.00	-12.72	AV
V	23140	49.73	30.85	7.45	24.69	51.02	74.00	-22.98	PK
V	23140	39.62	30.85	7.45	24.69	40.91	54.00	-13.09	AV
H	11570	45.78	30.55	5.77	24.66	45.66	74.00	-28.34	PK
H	11570	39.69	30.55	5.77	24.66	39.57	54.00	-14.43	AV
H	17355	48.62	30.33	6.32	24.55	49.16	74.00	-24.84	PK
H	17355	41.25	30.33	6.32	24.55	41.79	54.00	-12.21	AV
H	23140	51.54	30.85	7.45	24.69	52.83	74.00	-21.17	PK
H	23140	41.24	30.85	7.45	24.69	42.53	54.00	-11.47	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
High Channel:5825MHz									
V	11650	47.48	30.55	5.77	24.66	47.36	74.00	-26.64	PK
V	11650	33.89	30.55	5.77	24.66	33.77	54.00	-20.23	AV
V	17475	49.08	30.33	6.32	24.55	49.62	74.00	-24.38	PK
V	17475	40.10	30.33	6.32	24.55	40.64	54.00	-13.36	AV
V	23300	50.15	30.85	7.45	24.69	51.44	74.00	-22.56	PK
V	23300	41.20	30.85	7.45	24.69	42.49	54.00	-11.51	AV
H	11650	48.50	30.55	5.77	24.66	48.38	74.00	-25.62	PK
H	11650	37.84	30.55	5.77	24.66	37.72	54.00	-16.28	AV
H	17475	48.34	30.33	6.32	24.55	48.88	74.00	-25.12	PK
H	17475	39.49	30.33	6.32	24.55	40.03	54.00	-13.97	AV
H	23300	51.71	30.85	7.45	24.69	53.00	74.00	-21.00	PK
H	23300	40.81	30.85	7.45	24.69	42.10	54.00	-11.90	AV

MIMO-802.11n40

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
Low Channel:5190MHz									
V	10360	47.66	30.55	5.77	24.66	47.54	74.00	-26.46	PK
V	10360	35.97	30.55	5.77	24.66	35.85	54.00	-18.15	AV
V	15540	49.73	30.33	6.32	24.55	50.27	74.00	-23.73	PK
V	15540	40.23	30.33	6.32	24.55	40.77	54.00	-13.23	AV
V	20720	50.12	30.85	7.45	24.69	51.41	74.00	-22.59	PK
V	20720	40.33	30.85	7.45	24.69	41.62	54.00	-12.38	AV
H	10360	45.94	30.55	5.77	24.66	45.82	74.00	-28.18	PK
H	10360	40.07	30.55	5.77	24.66	39.95	54.00	-14.05	AV
H	15540	47.90	30.33	6.32	24.55	48.44	74.00	-25.56	PK
H	15540	40.67	30.33	6.32	24.55	41.21	54.00	-12.79	AV
H	20720	50.60	30.85	7.45	24.69	51.89	74.00	-22.11	PK
H	20720	41.40	30.85	7.45	24.69	42.69	54.00	-11.31	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
Middle Channel:5230MHz									
V	10460	47.39	30.55	5.77	24.66	47.27	74.00	-26.73	PK
V	10460	36.14	30.55	5.77	24.66	36.02	54.00	-17.98	AV
V	15690	48.42	30.33	6.32	24.55	48.96	74.00	-25.04	PK
V	15690	41.52	30.33	6.32	24.55	42.06	54.00	-11.94	AV
V	20920	51.19	30.85	7.45	24.69	52.48	74.00	-21.52	PK
V	20920	40.93	30.85	7.45	24.69	42.22	54.00	-11.78	AV
H	10460	47.27	30.55	5.77	24.66	47.15	74.00	-26.85	PK
H	10460	37.96	30.55	5.77	24.66	37.84	54.00	-16.16	AV
H	15690	47.32	30.33	6.32	24.55	47.86	74.00	-26.14	PK
H	15690	39.82	30.33	6.32	24.55	40.36	54.00	-13.64	AV
H	20920	50.09	30.85	7.45	24.69	51.38	74.00	-22.62	PK
H	20920	39.66	30.85	7.45	24.69	40.95	54.00	-13.05	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
High Channel:5755MHz									
V	11510	48.49	30.55	5.77	24.66	48.37	74.00	-25.63	PK
V	11510	36.32	30.55	5.77	24.66	36.20	54.00	-17.80	AV
V	17265	49.40	30.33	6.32	24.55	49.94	74.00	-24.06	PK
V	17265	40.59	30.33	6.32	24.55	41.13	54.00	-12.87	AV
V	23020	49.24	30.85	7.45	24.69	50.53	74.00	-23.47	PK
V	23020	39.51	30.85	7.45	24.69	40.80	54.00	-13.20	AV
H	11510	48.72	30.55	5.77	24.66	48.60	74.00	-25.40	PK
H	11510	40.13	30.55	5.77	24.66	40.01	54.00	-13.99	AV
H	17265	47.96	30.33	6.32	24.55	48.50	74.00	-25.50	PK
H	17265	40.30	30.33	6.32	24.55	40.84	54.00	-13.16	AV
H	23020	49.24	30.85	7.45	24.69	50.53	74.00	-23.47	PK
H	23020	38.84	30.85	7.45	24.69	40.13	54.00	-13.87	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
High Channel:5795MHz									
V	11590	49.38	30.55	5.77	24.66	49.26	74.00	-24.74	PK
V	11590	34.71	30.55	5.77	24.66	34.59	54.00	-19.41	AV
V	17385	48.56	30.33	6.32	24.55	49.10	74.00	-24.90	PK
V	17385	41.37	30.33	6.32	24.55	41.91	54.00	-12.09	AV
V	23180	49.05	30.85	7.45	24.69	50.34	74.00	-23.66	PK
V	23180	39.52	30.85	7.45	24.69	40.81	54.00	-13.19	AV
H	11590	46.19	30.55	5.77	24.66	46.07	74.00	-27.93	PK
H	11590	39.68	30.55	5.77	24.66	39.56	54.00	-14.44	AV
H	17385	48.34	30.33	6.32	24.55	48.88	74.00	-25.12	PK
H	17385	40.38	30.33	6.32	24.55	40.92	54.00	-13.08	AV
H	23180	49.86	30.85	7.45	24.69	51.15	74.00	-22.85	PK
H	23180	39.29	30.85	7.45	24.69	40.58	54.00	-13.42	AV

MIMO--802.11ac20

Polar (H/V)	Frequency	Meter Reading	Pre-ampl ifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel:5180MHz									
V	10360	48.57	30.55	5.77	24.66	48.45	74.00	-25.55	PK
V	10360	34.13	30.55	5.77	24.66	34.01	54.00	-19.99	AV
V	15540	47.80	30.33	6.32	24.55	48.34	74.00	-25.66	PK
V	15540	39.58	30.33	6.32	24.55	40.12	54.00	-13.88	AV
V	20720	51.65	30.85	7.45	24.69	52.94	74.00	-21.06	PK
V	20720	39.51	30.85	7.45	24.69	40.80	54.00	-13.20	AV
H	10360	48.40	30.55	5.77	24.66	48.28	74.00	-25.72	PK
H	10360	37.93	30.55	5.77	24.66	37.81	54.00	-16.19	AV
H	15540	47.89	30.33	6.32	24.55	48.43	74.00	-25.57	PK
H	15540	40.13	30.33	6.32	24.55	40.67	54.00	-13.33	AV
H	20720	49.13	30.85	7.45	24.69	50.42	74.00	-23.58	PK
H	20720	41.14	30.85	7.45	24.69	42.43	54.00	-11.57	AV

Polar (H/V)	Frequency	Meter Reading	Pre-amp lifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detecto r Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Middle Channel:5200MHz									
V	10400	48.10	30.55	5.77	24.66	47.98	74.00	-26.02	PK
V	10400	35.06	30.55	5.77	24.66	34.94	54.00	-19.06	AV
V	15600	49.32	30.33	6.32	24.55	49.86	74.00	-24.14	PK
V	15600	38.89	30.33	6.32	24.55	39.43	54.00	-14.57	AV
V	20800	51.10	30.85	7.45	24.69	52.39	74.00	-21.61	PK
V	20800	40.98	30.85	7.45	24.69	42.27	54.00	-11.73	AV
H	10400	47.25	30.55	5.77	24.66	47.13	74.00	-26.87	PK
H	10400	38.59	30.55	5.77	24.66	38.47	54.00	-15.53	AV
H	15600	48.75	30.33	6.32	24.55	49.29	74.00	-24.71	PK
H	15600	40.94	30.33	6.32	24.55	41.48	54.00	-12.52	AV
H	20800	51.20	30.85	7.45	24.69	52.49	74.00	-21.51	PK
H	20800	38.98	30.85	7.45	24.69	40.27	54.00	-13.73	AV

Polar (H/V)	Frequency	Meter Reading	Pre-ampl ifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
High Channel:5240MHz									
V	10480	48.57	30.55	5.77	24.66	48.45	74.00	-25.55	PK
V	10480	33.82	30.55	5.77	24.66	33.70	54.00	-20.30	AV
V	15720	49.01	30.33	6.32	24.55	49.55	74.00	-24.45	PK
V	15720	40.92	30.33	6.32	24.55	41.46	54.00	-12.54	AV
V	20960	49.10	30.85	7.45	24.69	50.39	74.00	-23.61	PK
V	20960	38.79	30.85	7.45	24.69	40.08	54.00	-13.92	AV
H	10480	48.32	30.55	5.77	24.66	48.20	74.00	-25.80	PK
H	10480	40.44	30.55	5.77	24.66	40.32	54.00	-13.68	AV
H	15720	47.82	30.33	6.32	24.55	48.36	74.00	-25.64	PK
H	15720	39.80	30.33	6.32	24.55	40.34	54.00	-13.66	AV
H	20960	49.82	30.85	7.45	24.69	51.11	74.00	-22.89	PK
H	20960	39.12	30.85	7.45	24.69	40.41	54.00	-13.59	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
High Channel:5745MHz									
V	11490	47.50	30.55	5.77	24.66	47.38	74.00	-26.62	PK
V	11490	36.65	30.55	5.77	24.66	36.53	54.00	-17.47	AV
V	17235	48.36	30.33	6.32	24.55	48.90	74.00	-25.10	PK
V	17235	40.67	30.33	6.32	24.55	41.21	54.00	-12.79	AV
V	22980	50.56	30.85	7.45	24.69	51.85	74.00	-22.15	PK
V	22980	39.25	30.85	7.45	24.69	40.54	54.00	-13.46	AV
H	11490	46.11	30.55	5.77	24.66	45.99	74.00	-28.01	PK
H	11490	40.18	30.55	5.77	24.66	40.06	54.00	-13.94	AV
H	17235	47.00	30.33	6.32	24.55	47.54	74.00	-26.46	PK
H	17235	39.05	30.33	6.32	24.55	39.59	54.00	-14.41	AV
H	22980	49.27	30.85	7.45	24.69	50.56	74.00	-23.44	PK
H	22980	41.06	30.85	7.45	24.69	42.35	54.00	-11.65	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
High Channel:5785MHz									
V	11570	48.62	30.55	5.77	24.66	48.50	74.00	-25.50	PK
V	11570	36.37	30.55	5.77	24.66	36.25	54.00	-17.75	AV
V	17355	49.30	30.33	6.32	24.55	49.84	74.00	-24.16	PK
V	17355	40.75	30.33	6.32	24.55	41.29	54.00	-12.71	AV
V	23140	49.18	30.85	7.45	24.69	50.47	74.00	-23.53	PK
V	23140	41.13	30.85	7.45	24.69	42.42	54.00	-11.58	AV
H	11570	48.60	30.55	5.77	24.66	48.48	74.00	-25.52	PK
H	11570	38.20	30.55	5.77	24.66	38.08	54.00	-15.92	AV
H	17355	48.71	30.33	6.32	24.55	49.25	74.00	-24.75	PK
H	17355	39.68	30.33	6.32	24.55	40.22	54.00	-13.78	AV
H	23140	51.03	30.85	7.45	24.69	52.32	74.00	-21.68	PK
H	23140	41.33	30.85	7.45	24.69	42.62	54.00	-11.38	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
High Channel:5825MHz									
V	11650	47.69	30.55	5.77	24.66	47.57	74.00	-26.43	PK
V	11650	36.16	30.55	5.77	24.66	36.04	54.00	-17.96	AV
V	17475	48.96	30.33	6.32	24.55	49.50	74.00	-24.50	PK
V	17475	38.88	30.33	6.32	24.55	39.42	54.00	-14.58	AV
V	23300	49.85	30.85	7.45	24.69	51.14	74.00	-22.86	PK
V	23300	38.91	30.85	7.45	24.69	40.20	54.00	-13.80	AV
H	11650	46.90	30.55	5.77	24.66	46.78	74.00	-27.22	PK
H	11650	39.71	30.55	5.77	24.66	39.59	54.00	-14.41	AV
H	17475	47.06	30.33	6.32	24.55	47.60	74.00	-26.40	PK
H	17475	41.58	30.33	6.32	24.55	42.12	54.00	-11.88	AV
H	23300	49.35	30.85	7.45	24.69	50.64	74.00	-23.36	PK
H	23300	40.77	30.85	7.45	24.69	42.06	54.00	-11.94	AV

MIMO-802.11ac40

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detect or Type
Low Channel:5190MHz									
V	10360	48.15	30.55	5.77	24.66	48.03	74.00	-25.97	PK
V	10360	35.21	30.55	5.77	24.66	35.09	54.00	-18.91	AV
V	15540	48.00	30.33	6.32	24.55	48.54	74.00	-25.46	PK
V	15540	40.67	30.33	6.32	24.55	41.21	54.00	-12.79	AV
V	20720	51.66	30.85	7.45	24.69	52.95	74.00	-21.05	PK
V	20720	39.94	30.85	7.45	24.69	41.23	54.00	-12.77	AV
H	10360	47.24	30.55	5.77	24.66	47.12	74.00	-26.88	PK
H	10360	40.08	30.55	5.77	24.66	39.96	54.00	-14.04	AV
H	15540	47.72	30.33	6.32	24.55	48.26	74.00	-25.74	PK
H	15540	40.43	30.33	6.32	24.55	40.97	54.00	-13.03	AV
H	20720	51.65	30.85	7.45	24.69	52.94	74.00	-21.06	PK
H	20720	40.65	30.85	7.45	24.69	41.94	54.00	-12.06	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detect or Type
Middle Channel:5230MHz									
V	10460	47.26	30.55	5.77	24.66	47.14	74.00	-26.86	PK
V	10460	36.47	30.55	5.77	24.66	36.35	54.00	-17.65	AV
V	15690	48.38	30.33	6.32	24.55	48.92	74.00	-25.08	PK
V	15690	41.59	30.33	6.32	24.55	42.13	54.00	-11.87	AV
V	20920	50.46	30.85	7.45	24.69	51.75	74.00	-22.25	PK
V	20920	39.30	30.85	7.45	24.69	40.59	54.00	-13.41	AV
H	10460	47.50	30.55	5.77	24.66	47.38	74.00	-26.62	PK
H	10460	40.50	30.55	5.77	24.66	40.38	54.00	-13.62	AV
H	15690	47.72	30.33	6.32	24.55	48.26	74.00	-25.74	PK
H	15690	41.73	30.33	6.32	24.55	42.27	54.00	-11.73	AV
H	20920	50.48	30.85	7.45	24.69	51.77	74.00	-22.23	PK
H	20920	40.43	30.85	7.45	24.69	41.72	54.00	-12.28	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detect or Type
High Channel:5755MHz									
V	11510	47.85	30.55	5.77	24.66	47.73	74.00	-26.27	PK
V	11510	35.27	30.55	5.77	24.66	35.15	54.00	-18.85	AV
V	17265	48.55	30.33	6.32	24.55	49.09	74.00	-24.91	PK
V	17265	40.19	30.33	6.32	24.55	40.73	54.00	-13.27	AV
V	23020	50.58	30.85	7.45	24.69	51.87	74.00	-22.13	PK
V	23020	39.24	30.85	7.45	24.69	40.53	54.00	-13.47	AV
H	11510	46.19	30.55	5.77	24.66	46.07	74.00	-27.93	PK
H	11510	40.52	30.55	5.77	24.66	40.40	54.00	-13.60	AV
H	17265	48.24	30.33	6.32	24.55	48.78	74.00	-25.22	PK
H	17265	39.33	30.33	6.32	24.55	39.87	54.00	-14.13	AV
H	23020	50.74	30.85	7.45	24.69	52.03	74.00	-21.97	PK
H	23020	41.65	30.85	7.45	24.69	42.94	54.00	-11.06	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detect or Type
High Channel:5795MHz									
V	11510	48.60	30.55	5.77	24.66	48.48	74.00	-25.52	PK
V	11510	36.11	30.55	5.77	24.66	35.99	54.00	-18.01	AV
V	17265	49.26	30.33	6.32	24.55	49.80	74.00	-24.20	PK
V	17265	40.00	30.33	6.32	24.55	40.54	54.00	-13.46	AV
V	23020	49.97	30.85	7.45	24.69	51.26	74.00	-22.74	PK
V	23020	39.64	30.85	7.45	24.69	40.93	54.00	-13.07	AV
H	11510	47.72	30.55	5.77	24.66	47.60	74.00	-26.40	PK
H	11510	39.71	30.55	5.77	24.66	39.59	54.00	-14.41	AV
H	17265	48.11	30.33	6.32	24.55	48.65	74.00	-25.35	PK
H	17265	41.00	30.33	6.32	24.55	41.54	54.00	-12.46	AV
H	23020	51.67	30.85	7.45	24.69	52.96	74.00	-21.04	PK
H	23020	41.64	30.85	7.45	24.69	42.93	54.00	-11.07	AV

MIMO-802.11ac80

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detect or Type
5210MHz									
V	10420	49.17	30.55	5.77	24.66	49.05	74.00	-24.95	PK
V	10420	36.54	30.55	5.77	24.66	36.42	54.00	-17.58	AV
V	15630	49.36	30.33	6.32	24.55	49.90	74.00	-24.10	PK
V	15630	40.31	30.33	6.32	24.55	40.85	54.00	-13.15	AV
V	20840	50.55	30.85	7.45	24.69	51.84	74.00	-22.16	PK
V	20840	41.43	30.85	7.45	24.69	42.72	54.00	-11.28	AV
H	10420	46.77	30.55	5.77	24.66	46.65	74.00	-27.35	PK
H	10420	40.57	30.55	5.77	24.66	40.45	54.00	-13.55	AV
H	15630	47.67	30.33	6.32	24.55	48.21	74.00	-25.79	PK
H	15630	41.54	30.33	6.32	24.55	42.08	54.00	-11.92	AV
H	20840	49.91	30.85	7.45	24.69	51.20	74.00	-22.80	PK
H	20840	39.26	30.85	7.45	24.69	40.55	54.00	-13.45	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detect or Type
High Channel:5775MHz									
V	11550	49.65	30.55	5.77	24.66	49.53	74.00	-24.47	PK
V	11550	34.83	30.55	5.77	24.66	34.71	54.00	-19.29	AV
V	17325	49.15	30.33	6.32	24.55	49.69	74.00	-24.31	PK
V	17325	39.09	30.33	6.32	24.55	39.63	54.00	-14.37	AV
V	23100	48.89	30.85	7.45	24.69	50.18	74.00	-23.82	PK
V	23100	40.29	30.85	7.45	24.69	41.58	54.00	-12.42	AV
H	11550	46.09	30.55	5.77	24.66	45.97	74.00	-28.03	PK
H	11550	39.34	30.55	5.77	24.66	39.22	54.00	-14.78	AV
H	17325	48.76	30.33	6.32	24.55	49.30	74.00	-24.70	PK
H	17325	41.20	30.33	6.32	24.55	41.74	54.00	-12.26	AV
H	23100	50.03	30.85	7.45	24.69	51.32	74.00	-22.68	PK
H	23100	38.92	30.85	7.45	24.69	40.21	54.00	-13.79	AV

Remark: 1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,

Margin= Emission Level - Limit

2. If peak below the average limit, the average emission was no test.

3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

5. POWER SPECTRAL DENSITY TEST

Test Requirement:	FCC 47 CFR Part 15 Subpart E Section 15.407 (a)
Test Method:	KDB 789033 D02 v02r01

5.1 APPLIED PROCEDURES / LIMIT

For client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For the band 5.725-5.850 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.


LIMIT:	U-NII-1	11DBM/MHZ
	U-NII-3	30DBM/500KHZ

5.2 TEST PROCEDURE

1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to 1.5 times the DTS bandwidth.
3. Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
4. Set the VBW $\geq 3 \times \text{RBW}$.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level within the RBW.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

5.3 DEVIATION FROM STANDARD

No deviation.

5.4 TEST SETUP

5.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.1 Unless otherwise a special operating condition is specified in the follows during the testing.

5.6 TEST RESULT

PASS: PLEASE REFER TO APPENDIX: APPENDIX1 FOR DETAILS

6. -26 DB & 6DBM EMISSION BANDWIDTH

Test Requirement:	Part 15 Subpart C Section 15.407 (e)
Test Method:	KDB 789033 D02 v02r01

6.1 APPLIED PROCEDURES / LIMIT

FCC Part15.407 (e)		
Bandwidth		
Limit	U-NII-1	N/A
	U-NII-3	≥ 500 kHz

6.2 TEST PROCEDURE

Place the EUT on the table and set it in the transmitting mode.

Remove the antenna from the EUT and then connect a low-loss RF cable from the antenna port to the spectrum analyzer.

Set the spectrum analyzers RBW = approximately 1% of the emission bandwidth, VBW >RBW, Detector = Peak, Span>26dB bandwidth, and Sweep = auto ,Trace mode = max hold.


Measure the maximum width of the emission that is 26dB down from the maximum of the emission.

Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.

Repeat until all the rest channels were investigated.

6.3 DEVIATION FROM STANDARD

No deviation.

6.4 TEST SETUP**6.5 EUT OPERATION CONDITIONS**

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

6.6 TEST RESULT

PASS: PLEASE REFER TO APPENDIX: APPENDIX1 FOR DETAILS

7. OUTPUT POWER TEST

Test Requirement:	15.407 (a)(1)(2)(3)
Test Method:	KDB 789033 D02 v02r01

7.1 APPLIED PROCEDURES/LIMIT

For client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.


For the band 5.725-5.850 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Test Item	Band	Limit	Result
Max conducted output power	U-NII-1	0.25W / 23.98dbm	Pass
Max conducted output power	U-NII-3	1 W / 30dbm	Pass

7.2 DEVIATION FROM STANDARD

No deviation.

7.3 TEST SETUP



7.4 EUT OPERATION CONDITIONS

PASS: PLEASE REFER TO APPENDIX: APPENDIX1 FOR DETAILS

8. OUT OF BAND EDGE EMISSION

Test Requirement:	15.407 (b)
Test Method:	KDB 789033 D02 v02r01


8.1 TEST PROCEDURE

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW of spectrum analyzer to 1 MHz with a convenient frequency span.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

8.2 DEVIATION FROM STANDARD

No deviation.

8.3 TEST SETUP



8.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

8.5 TEST RESULTS

PASS: PLEASE REFER TO APPENDIX: APPENDIX1 FOR DETAILS

9. FREQUENCY STABILITY MEASUREMENT


9.1 LIMIT

According to §15.407(g), Manufacturers of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the user's manual.

9.2 TESTPROCEDURE

1. To ensure emission at the band edge is maintained within the authorized band, those values shall be measured by radiation emissions at upper and lower frequency points, and finally compensated by frequency deviation as procedures below.
2. The EUT was operated at the maximum output power, and connected to the spectrum analyzer, which is set to maximum hold function and peak detector. The peak value of the power envelope was measured and noted. The upper and lower frequency points were respectively measured relatively 10dB lower than the measured peak value.
3. The frequency deviation was calculated by adding the upper frequency point and the lower frequency point divided by two. Those detailed values of frequency deviation are provided in table below.

9.3 TESTCONFIGURATION



9.4 TEST RESULT

Note: Only the test results of the worst channel are displayed

ANT1-802.11a- CH36

Temperature (°C)	Voltage (AC:V)	Frequency Measure with time Elapsed	
		Freq.Dev(Hz)	(ppm)
50	120	76	0.0146
40	120	79	0.0153
30	120	86	0.0166
20	120	76	0.0146
10	120	96	0.0186
0	120	84	0.0162
-10	120	79	0.0153
-20	120	99	0.0191
-30	120	93	0.0180

ANT1-802.11a-CH165

Temperature (°C)	Voltage (AC:V)	Frequency Measure with time Elapsed	
		Freq.Dev(Hz)	(ppm)
50	120	84	0.0143
40	120	80	0.0137
30	120	95	0.0164
20	120	84	0.0144
10	120	92	0.0158
0	120	100	0.0172
-10	120	85	0.0146
-20	120	95	0.0163
-30	120	80	0.0137

ANT1-802.11n20-CH36

Temperature (°C)	Voltage (AC:V)	Frequency Measure with time Elapsed	
		Freq.Dev(Hz)	(ppm)
50	120	82	0.0159
40	120	71	0.0137
30	120	80	0.0154
20	120	82	0.0158
10	120	93	0.0179
0	120	84	0.0163
-10	120	83	0.0160
-20	120	96	0.0185
-30	120	93	0.0179

ANT1-802.11n20-CH48

Temperature (°C)	Voltage (AC:V)	Frequency Measure with time Elapsed	
		Freq.Dev(Hz)	(ppm)
50	120	91	0.0174
40	120	77	0.0148
30	120	90	0.0172
20	120	80	0.0152
10	120	84	0.0161
0	120	97	0.0184
-10	120	100	0.0190
-20	120	81	0.0154
-30	120	75	0.0144

ANT1-802.11n40-CH38

Temperature (°C)	Voltage (AC:V)	Frequency Measure with time Elapsed	
		Freq.Dev(Hz)	(ppm)
50	120	96	0.0185
40	120	71	0.0137
30	120	93	0.0179
20	120	87	0.0167
10	120	90	0.0173
0	120	81	0.0157
-10	120	96	0.0186
-20	120	97	0.0187
-30	120	88	0.0169

ANT1-802.11n40-CH151

Temperature (°C)	Voltage (AC:V)	Frequency Measure with time Elapsed	
		Freq.Dev(Hz)	(ppm)
50	120	82	0.0142
40	120	83	0.0145
30	120	92	0.0160
20	120	83	0.0145
10	120	95	0.0165

0	120	99	0.0172
-10	120	81	0.0140
-20	120	76	0.0132
-30	120	99	0.0172

ANT1-802.11ac20-CH48

Temperature (°C)	Voltage (AC:V)	Frequency Measure with time Elapsed	
		Freq.Dev(Hz)	(ppm)
50	120	81	0.0154
40	120	100	0.0190
30	120	72	0.0138
20	120	73	0.0139
10	120	76	0.0146
0	120	91	0.0174
-10	120	86	0.0165
-20	120	81	0.0155
-30	120	79	0.0150

ANT2-802.11ac20-CH149

Temperature (°C)	Voltage (AC:V)	Frequency Measure with time Elapsed	
		Freq.Dev(Hz)	(ppm)
50	120	89	0.0156
40	120	90	0.0156
30	120	75	0.0130
20	120	83	0.0145
10	120	80	0.0140
0	120	71	0.0123
-10	120	87	0.0152
-20	120	86	0.0149
-30	120	79	0.0137

ANT2-802.11ac20-CH165

Temperature (°C)	Voltage (AC:V)	Frequency Measure with time Elapsed	
		Freq.Dev(Hz)	(ppm)
50	120	93	0.0160
40	120	98	0.0168
30	120	78	0.0134
20	120	73	0.0126
10	120	87	0.0149
0	120	95	0.0164
-10	120	77	0.0132
-20	120	97	0.0167
-30	120	89	0.0152

ANT2-802.11ac40-CH151

Temperature (°C)	Voltage (AC:V)	Frequency Measure with time Elapsed	
		Freq.Dev(Hz)	(ppm)
50	120	82	0.0142
40	120	81	0.0141
30	120	80	0.0138
20	120	73	0.0127
10	120	99	0.0173
0	120	76	0.0133
-10	120	89	0.0154
-20	120	89	0.0155
-30	120	91	0.0158


ANT2-802.11ac80-CH42

Temperature (°C)	Voltage (AC:V)	Frequency Measure with time Elapsed	
		Freq.Dev(Hz)	(ppm)
50	120	94	0.0181
40	120	93	0.0179
30	120	82	0.0158
20	120	73	0.0141
10	120	81	0.0156
0	120	79	0.0152
-10	120	95	0.0183
-20	120	96	0.0185
-30	120	100	0.0192

ANT2-802.11ac80-CH155

Temperature (°C)	Voltage (AC:V)	Frequency Measure with time Elapsed	
		Freq.Dev(Hz)	(ppm)
50	120	78	0.0135
40	120	89	0.0154
30	120	78	0.0135
20	120	85	0.0147
10	120	73	0.0127
0	120	94	0.0164
-10	120	72	0.0125
-20	120	97	0.0169
-30	120	77	0.0134


10.ANTENNA REQUIREMENT


Standard requirement:	FCC Part15 C Section 15.203 /247(c)
For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247, if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi. Refer to statement below for compliance. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed.	
The antenna is FPC antenna, the best case gain of the 3.46dBi,, reference to the below photo for details 	




11.APPENDIX1---5.2GWIFI**1. -26dB and 99% Emission Bandwidth**




Condition	Antenna	Modulation	Frequency(MHz)	-26dB_Emission_Bandwidth(MHz)	Occupied Bandwidth(MHz)
NVNT	ANT1	802.11a	5180.00	20.24	16.41
NVNT	ANT1	802.11a	5200.00	20.05	16.36
NVNT	ANT1	802.11a	5240.00	19.96	16.42
NVNT	ANT1	802.11n(HT20)	5180.00	21.43	17.63
NVNT	ANT1	802.11n(HT20)	5200.00	20.60	17.58
NVNT	ANT1	802.11n(HT20)	5240.00	22.03	17.62
NVNT	ANT1	802.11ac(VHT20)	5180.00	21.98	17.65
NVNT	ANT1	802.11ac(VHT20)	5200.00	20.43	17.62
NVNT	ANT1	802.11ac(VHT20)	5240.00	21.17	17.65
NVNT	ANT1	802.11n(HT40)	5190.00	40.23	36.10
NVNT	ANT1	802.11n(HT40)	5230.00	39.98	36.21
NVNT	ANT1	802.11ac(VHT40)	5190.00	39.91	36.06
NVNT	ANT1	802.11ac(VHT40)	5230.00	40.38	36.13
NVNT	ANT1	802.11ac(VHT80)	5210.00	146.73	75.58




Condition	Antenna	Modulation	Frequency(MHz)	-26dB_Emission_Bandwidth(MHz)	Occupied Bandwidth(MHz)
NVNT	ANT2	802.11a	5180.00	20.80	16.39
NVNT	ANT2	802.11a	5200.00	19.52	16.38
NVNT	ANT2	802.11a	5240.00	20.38	16.42
NVNT	ANT2	802.11n(HT20)	5180.00	21.51	17.62
NVNT	ANT2	802.11n(HT20)	5200.00	22.09	17.61
NVNT	ANT2	802.11n(HT20)	5240.00	21.37	17.64
NVNT	ANT2	802.11ac(VHT20)	5180.00	21.30	17.63
NVNT	ANT2	802.11ac(VHT20)	5200.00	20.94	17.59
NVNT	ANT2	802.11ac(VHT20)	5240.00	21.27	17.63
NVNT	ANT2	802.11n(HT40)	5190.00	41.60	36.10
NVNT	ANT2	802.11n(HT40)	5230.00	40.04	36.11
NVNT	ANT2	802.11ac(VHT40)	5190.00	40.37	36.04
NVNT	ANT2	802.11ac(VHT40)	5230.00	39.66	36.14
NVNT	ANT2	802.11ac(VHT80)	5210.00	130.76	75.66






-26dB and 99% Emission Bandwidth NVNT ANT1_802_11a_5200_20M**-26dB and 99% Emission Bandwidth NVNT ANT1_802_11a_5240_20M****-26dB and 99% Emission Bandwidth NVNT ANT1_802_11n(HT20)_5180_20M**


-26dB and 99% Emission Bandwidth NVNT_ANT1_802_11n(HT20) 5200 20M**-26dB and 99% Emission Bandwidth NVNT_ANT1_802_11n(HT20) 5240 20M****-26dB and 99% Emission Bandwidth NVNT_ANT1_802_11ac(VHT20) 5180 20M**

-26dB and 99% Emission Bandwidth NVNT_ANT1_802_11ac(VHT20) 5200 20M**-26dB and 99% Emission Bandwidth NVNT_ANT1_802_11ac(VHT20) 5240 20M****-26dB and 99% Emission Bandwidth NVNT_ANT1_802_11n(HT40) 5190 40M**


-26dB and 99% Emission Bandwidth NVNT_ANT1_802_11n(HT40) 5230 40M**-26dB and 99% Emission Bandwidth NVNT_ANT1_802_11ac(VHT40) 5190 40M****-26dB and 99% Emission Bandwidth NVNT_ANT1_802_11ac(VHT40) 5230 40M**

-26dB and 99% Emission Bandwidth NVNT_ANT1_802_11ac(VHT80) 5210 80M**-26dB and 99% Emission Bandwidth NVNT_ANT2_802_11a 5180 20M****-26dB and 99% Emission Bandwidth NVNT_ANT2_802_11a 5200 20M**


-26dB and 99% Emission Bandwidth NVNT_ANT2_802_11a_5240_20M




-26dB and 99% Emission Bandwidth NVNT_ANT2_802_11n(HT20)_5180_20M




-26dB and 99% Emission Bandwidth NVNT_ANT2_802_11n(HT20)_5200_20M




-26dB and 99% Emission Bandwidth NVNT ANT2_802_11n(HT20) 5240 20M




-26dB and 99% Emission Bandwidth NVNT ANT2_802_11ac(VHT20) 5180 20M




-26dB and 99% Emission Bandwidth NVNT ANT2_802_11ac(VHT20) 5200 20M




-26dB and 99% Emission Bandwidth NVNT_ANT2_802_11ac(VHT20) 5240 20M





-26dB and 99% Emission Bandwidth NVNT_ANT2_802_11n(HT40) 5190 40M



-26dB and 99% Emission Bandwidth NVNT_ANT2_802_11n(HT40) 5230 40M



-26dB and 99% Emission Bandwidth NVNT_ANT2_802_11ac(VHT40) 5190 40M**-26dB and 99% Emission Bandwidth NVNT_ANT2_802_11ac(VHT40) 5230 40M****-26dB and 99% Emission Bandwidth NVNT_ANT2_802_11ac(VHT80) 5210 80M**