

TEST REPORT

FCC ID.	2BAMG-IGO3600
Test Report No.	TCT230320E906
Date of issue	Jun. 05, 2023
Testing laboratory	SHENZHEN TONGCE TESTING LAB
Testing location/ address:	2101 & 2201, Zhenchang Factory, Renshan Industrial Zone, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, 518103, People's Republic of China
Applicant's name	Foxtheon Energy Technology (Fujian) Co., Ltd.
Address	Room 409 Building 16, Hi-tech Zone Haixiyuan, Fuzhou, China
Manufacturer's name	Foxtheon Energy Technology (Fujian) Co., Ltd.
Address	Room 409 Building 16, Hi-tech Zone Haixiyuan, Fuzhou, China
Standard(s)	FCC CFR Title 47 Part 2 FCC CFR Title 47 Part22 FCC CFR Title 47 Part24
Product Name	Portable Power Station
Trade Mark	Foxtheon
Model/Type reference	iGo3600
Rating(s)	AC 120V/60Hz Rechargeable Li-ion Battery DC 57.6V
Date of receipt of test item	Mar. 20, 2023
Date (s) of performance of test	Feb. 27, 2023 - Jun. 05, 2023
Tested by (+signature)	Aaron MO
Check by (+signature)	Beryl ZHAO
Approved by (+signature) :	Tomsin



General disclaimer:

This report shall not be reproduced except in full, without the written approval of SHENZHEN TONGCE TESTING LAB. This document may be altered or revised by SHENZHEN TONGCE TESTING LAB personnel only, and shall be noted in the revision section of the document. The test results in the report only apply to the tested sample.

TABLE OF CONTENTS

1. General Product Information	3
1.1. EUT description	3
1.2. Model(s) list.....	3
1.3. Emission Designator	3
1.4. Test Frequency	5
2. Test Result Summary	6
3. General Information.....	7
3.1. Test environment and mode.....	7
3.2. Description of Support Units	9
3.3. Configuration of Tested System	9
3.4. Measurement Results Explanation Example.....	9
4. Facilities and Accreditations	10
4.1. Facilities	10
4.2. Location	10
4.3. Measurement Uncertainty.....	10
5. Test Results and Measurement Data	11
5.1. Effective Radiated Power and Effective Isotropic Radiated Power Measurement	11
5.2. Peak to Average Ratio.....	13
5.3. 99% Occupied Bandwidth and 26dB Bandwidth Measurement	14
5.4. Band Edge and Conducted Spurious Emission Measurement	15
5.5. Field Strength of Spurious Radiation Measurement	16
5.6. Frequency Stability Measurement	24

Appendix A: Photographs of Test Setup**Appendix B: Photographs of EUT****Test Data: Refer to Appendix For LTE Band 2 and Appendix For
LTE Band 5**

1. General Product Information

1.1. EUT description

Product Name	Portable Power Station
Model/Type reference	iGo3600
Sample Number	TCT230227E016-0101
Tx Frequency	LTE Band 2: 1850 MHz ~ 1910 MHz LTE Band 5: 824 MHz ~ 849 MHz
Rx Frequency	LTE Band 2: 1930 MHz ~ 1990 MHz LTE Band 5: 869 MHz ~ 894 MHz
Bandwidth	LTE Band 2: 1.4MHz /3MHz /5MHz /10MHz /15MHz /20MHz LTE Band 5: 1.4MHz /3MHz /5MHz /10MHz
Maximum Output Power to Antenna	LTE Band 2: 23.07dBm LTE Band 5: 22.86dBm
99% Occupied Bandwidth	LTE Band 2: 17M9G7D LTE Band 5: 9M00G7D
Type of Modulation	QPSK/16QAM
Antenna Type	Internal Antenna
Antenna Gain	LTE Band 2: 1.5dBi LTE Band 5: 0.5dBi
Rating(s)	AC 120V/60Hz Rechargeable Li-ion Battery DC 57.6V

Note: The antenna gain listed in this report is provided by applicant, and the test laboratory is not responsible for this parameter.

1.2. Model(s) list

None.

1.3. Emission Designator

LTE Band 2	QPSK		16QAM	
BW(MHz)	Emission Designator (99%OBW)	Maximum EIRP(W)	Emission Designator (99%OBW)	Maximum EIRP(W)
1.4	1M10G7D	0.270	1M10W7D	0.231
3	2M74G7D	0.269	2M74W7D	0.231
5	4M52G7D	0.275	4M52W7D	0.231
10	9M00G7D	0.270	/	/
15	13M5G7D	0.286	/	/
20	17M9G7D	0.278	/	/

LTE Band 5	QPSK		16QAM	
BW(MHz)	Emission Designator (99%OBW)	Maximum ERP(W)	Emission Designator (99%OBW)	Maximum ERP(W)
1.4	1M10G7D	0.129	1M10W7D	0.109
3	2M73G7D	0.129	2M74W7D	0.106
5	4M50G7D	0.131	4M50W7D	0.110
10	9M00G7D	0.132	/	/

1.4. Test Frequency

LTE Band 2(1.4MHz)		LTE Band 2(3MHz)	
Channel	Frequency (MHz)	Channel	Frequency (MHz)
18607	1850.7	18615	1851.5
18900	1880	18900	1880
19193	1909.3	19185	1908.5
LTE Band 2(5MHz)		LTE Band 2(10MHz)	
Channel	Frequency (MHz)	Channel	Frequency (MHz)
18625	1852.5	18650	1855
18900	1880	18900	1880
19175	1907.5	19150	1905
LTE Band 2(15MHz)		LTE Band 2(20MHz)	
Channel	Frequency (MHz)	Channel	Frequency (MHz)
18675	1857.5	18700	1860
18900	1880	18900	1880
19125	1902.5	19100	1900

LTE Band 5(1.4MHz)		LTE Band 5(3MHz)	
Channel	Frequency (MHz)	Channel	Frequency (MHz)
20407	824.7	20415	825.5
20525	836.5	20525	836.5
20643	848.3	20635	847.5
LTE Band 5(5MHz)		LTE Band 5(10MHz)	
Channel	Frequency (MHz)	Channel	Frequency (MHz)
20425	826.5	20450	829
20525	836.5	20525	836.5
20625	846.5	20600	844

2. Test Result Summary

Requirement	CFR 47 Section	Result
Conducted Output Power	§2.1046; §22.913; §24.232(c)	PASS
Peak-to-Average Ratio	§2.1046; §24.232(d)	PASS
Effective Radiated Power	§2.1046; §22.913; §24.232(c)	PASS
Equivalent Isotropic Radiated Power	§2.1046; §22.913; §24.232(c)	PASS
Occupied Bandwidth	§2.1049; §24.238(b)	PASS
Band Edge	§2.1051; §22.917(a); §24.238(a)	PASS
Conducted Spurious Emission	§2.1051; §22.917(a); §24.238(a);	PASS
Field Strength of Spurious Radiation	§2.1053; §22.917(a); §24.238(a)	PASS
Frequency Stability for Temperature & Voltage	§2.1055; §22.355; §24.235	PASS

Note:

1. PASS: Test item meets the requirement.
2. Fail: Test item does not meet the requirement.
3. N/A: Test case does not apply to the test object.
4. The test result judgment is decided by the limit of test standard.
5. This test report was based on FCC ID: 2A986-QX3600; Change applicant, manufacturer, address, product name, product model No., trade mark and external photographs of EUT.

3. General Information

3.1. Test environment and mode

Operating Environment:

Temperature:	25.0 °C
Humidity:	56 % RH
Atmospheric Pressure:	1010 mbar

Remark: This product has a built-in rechargeable battery, so in an independent test, the EUT battery was fully-charged.

Keep the EUT in communication with CMW500 and select channel with modulation
All modes and data rates and positions were investigated.

Test modes are chosen to be reported as the worst case configuration below:

Test Mode		
Band	Radiated TCs	Conducted TCs
LTE Band 2	QPSK Link (1.4MHz / 3MHz / 5MHz / 10MHz / 15MHz / 20MHz)	16QAM Link (1.4MHz / 3MHz / 5MHz)
LTE Band 5	QPSK Link (1.4MHz / 3MHz / 5MHz / 10MHz)	16QAM Link (1.4MHz / 3MHz / 5MHz)

Antenna port conducted and radiated test items were performed according to KDB 971168 D01 Power Meas License Digital Systems v03 with maximum output power. Radiated measurements were performed with rotating EUT in different three orthogonal test planes to find the maximum emission. The sample was placed 0.8m/1.5m above the ground plane of 3m chamber. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating the turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarization. The emissions worst-case are shown in Test Results of the following pages.

Test Items	Band	Bandwidth (MHz)						Modulation		RB #			Test Channel		
		1.4	3	5	10	15	20	QPSK	16QAM	1	Half	Full	L	M	H
Max. Output Power	2	v	v	v	v	v	v	v	v	v	v	v	v	v	v
	5	v	v	v	v	-	-	v	v	v	v	v	v	v	v
Peak-to-Average Ratio	2	v	v	v	v	v	v	v	v	v	v	v	v	v	v
	5	v	v	v	v	-	-	v	v	v	v	v	v	v	v
26dB and 99% Bandwidth	2	v	v	v	v	v	v	v	v	v	v	v	v	v	v
	5	v	v	v	v	-	-	v	v	v	v	v	v	v	v
Conducted Band Edge	2	v	v	v	v	v	v	v	v	v	v	v	v	v	-v
	5	v	v	v	v	-	-	v	v	v	v	v	v	v	-v
Conducted Spurious Emission	2	v	v	v	v	v	v	v	v	v	v	-	-	v	v
	5	v	v	v	v	-	-	v	v	v	v	-	-	v	v
Frequency Stability	2	v	v	v	v	v	v	v	v	v	v	-	-	v	v
	5	v	v	v	v	-	-	v	v	v	v	-	-	v	v
E.R.P./ E.I.R.P.	2	v	v	v	v	v	v	v	v	v	v	v	v	v	v
	5	v	v	v	v	-	-	v	v	v	v	v	v	v	v
Radiated Spurious Emission	2	-	-	-	-	-	v	v	v	v	v	-	-	v	v
	5	-	-	-	v	-	-	v	v	v	v	-	-	v	v
Note	1. The mark "v" means that this configuration is chosen for testing 2. The mark "-" means that this bandwidth is not supported.														

3.2. Description of Support Units


The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Equipment	Model No.	Serial No.	FCC ID	Trade Name
/	/	/	/	/

Note:

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

3.3. Configuration of Tested System



3.4. Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between RF conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level will be exactly the RF output level. The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

$$\text{Offset} = \text{RF cable loss} + \text{attenuator factor}$$

4. Facilities and Accreditations

4.1. Facilities

The test facility is recognized, certified, or accredited by the following organizations:

- FCC - Registration No.: 645098

SHENZHEN TONGCE TESTING LAB

Designation Number: CN1205

The testing lab has been registered and fully described in a report with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files.

- IC - Registration No.: 10668A-1

SHENZHEN TONGCE TESTING LAB

CAB identifier: CN0031

The testing lab has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing.

4.2. Location

SHENZHEN TONGCE TESTING LAB

Address: 2101 & 2201, Zhenchang Factory, Renshan Industrial Zone, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, 518103, People's Republic of China

TEL: 86-755-27673339

4.3. Measurement Uncertainty


The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

No.	Item	MU
1	Conducted Emission	± 3.10 dB
2	RF power, conducted	± 0.12 dB
3	Spurious emissions, conducted	± 0.11 dB
4	All emissions, radiated(<1 GHz)	± 4.56 dB
5	All emissions, radiated(1 GHz - 18 GHz)	± 4.22 dB
6	All emissions, radiated(18 GHz- 40 GHz)	± 4.36 dB

5. Test Results and Measurement Data

5.1. Effective Radiated Power and Effective Isotropic Radiated Power Measurement

5.1.1. Test Specification

Test Requirement:	FCC part 24.232(c), FCC part 22.913;
Test Method:	FCC part 2.1046
Limit:	LTE Band 2: 2W LTE Band 5: 7W
Test Setup:	 <p>System Simulator EUT</p>
Test Procedure:	<ol style="list-style-type: none"> 1. The transmitter output port was connected to the system simulator. 2. Set EUT at maximum power through system simulator. 3. Select lowest, middle, highest channels for each band and different modulation. 4. Measure and record the power level from the system simulator. 5. Calculate the ERP and EIRP <p>The relevant equation for determining the ERP or EIRP from the conducted RF output power measured using the guidance provided above is:</p> $\text{ERP or EIRP} = P_{\text{Meas}} + G_T - L_c$ <p>where:</p> <p>ERP or EIRP = effective radiated power or equivalent isotropically radiated power, respectively (expressed in the same units as P_{Meas}, typically dBW or dBm);</p> <p>P_{Meas} = measured transmitter output power or PSD, in dBm or dBW;</p> <p>G_T = gain of the transmitting antenna, in dBd (ERP) or dBi (EIRP);</p> <p>L_c = signal attenuation in the connecting cable between the transmitter and antenna, in dB.</p> <p><i>Note: For personal/portable radios utilizing an integral antenna, the factor L_c is typically negligible. However, in a fixed station transmit system that utilizes a long cable run between the transmitter and the transmitting antenna, this factor can be significant.</i></p>

Test Result:

PASS

5.1.2. Test Instruments

Equipment	Manufacturer	Model	Serial Number	Calibration Due
Wideband Radio Communication Tester	R&S	CMW500	114220	Jul. 03, 2023
Combiner Box	Ascentest	AT890-RFB	/	/

5.2. Peak to Average Ratio

5.2.1. Test Specification

Test Requirement:	FCC part 2.1046; 22.913; 24.232
Test Method:	FCC KDB 971168 D01v03
Limit:	The peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.
Test Setup:	<p>System Simulator</p> <p>Spectrum Analyzer</p> <p>Power Divider</p> <p>EUT</p>
Test Procedure:	<ol style="list-style-type: none"> 1. The testing follows FCC KDB 971168 D01v03 Section 5.7.1. 2. The EUT was connected to spectrum analyzer and system simulator via a power divider. 3. Set EUT to transmit at maximum output power. 4. Set the CCDF (Complementary Cumulative Distribution Function) option of the spectrum analyzer. Record the maximum PAPR level associated with a probability of 0.1%.
Test Result:	PASS

5.2.2. Test Instruments

Equipment	Manufacturer	Model	Serial Number	Calibration Due
Wideband Radio Communication Tester	R&S	CMW500	114220	Jul. 03, 2023
Spectrum Analyzer	R&S	FSV40-N	102188	Feb. 20, 2024
Combiner Box	Ascentest	AT890-RFB	/	/

5.3. 99% Occupied Bandwidth and 26dB Bandwidth Measurement

5.3.1. Test Specification

Test Requirement:	FCC part 24.238(b)
Test Method:	FCC part 2.1049
Limit:	N/A
Test Setup:	<p>System Simulator</p> <p>Spectrum Analyzer</p> <p>Power Divider</p> <p>EUT</p>
Test Procedure:	<ol style="list-style-type: none"> 1. The testing follows FCC KDB 971168 D01v03 Section 4.2. 2. The EUT was connected to the spectrum analyzer and system simulator via a power divider. 3. The RF output of the EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement. 4. The 99% occupied bandwidth were measured, set RBW= 1% of OBW, VBW= 3*RBW, sample detector, trace maximum hold. 5. The 26dB bandwidth were measured, set RBW= 1% of EBW, VBW= 3*RBW, peak detector, trace maximum hold.
Test Result:	PASS

5.3.2. Test Instruments

Equipment	Manufacturer	Model	Serial Number	Calibration Due
Wideband Radio Communication Tester	R&S	CMW500	114220	Jul. 03, 2023
Spectrum Analyzer	R&S	FSV40-N	102188	Feb. 20, 2024
Combiner Box	Ascentest	AT890-RFB	/	/

5.4. Band Edge and Conducted Spurious Emission Measurement

5.4.1. Test Specification


Test Requirement:	FCC part 24.238(a), 22.917(a)
Test Method:	FCC part2.1051
Limit:	-13dBm
Test Setup:	<p>The diagram illustrates the test setup. A 'System Simulator' (represented by a purple box with a screen and buttons) is connected to a 'Power Divider' (represented by a black rectangle). The 'Power Divider' is connected to a 'Spectrum Analyzer' (represented by a green box with a screen and buttons) and an 'EUT' (Equipment Under Test, represented by a black mobile phone icon).</p>
Test Procedure:	<ol style="list-style-type: none"> 1. The testing follows FCC KDB 971168 D01v03 Section 6.0. 2. The EUT was connected to the spectrum analyzer and system simulator via a power divider. 3. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator. The path loss was compensated to the results for each measurement. 4. The band edges of low and high channels for the highest RF powers were measured. 5. The conducted spurious emission for the whole frequency range was taken. 6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band. 7. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power $P(\text{Watts}) = P(\text{W}) - [43 + 10\log(P)] \text{ (dB)} = [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)} = -13\text{dBm}.$ For Band 17, the limit line is derived from $55 + 10\log(P)$ dB below the transmitter power
Test Result:	PASS

5.4.2. Test Instruments

Equipment	Manufacturer	Model	Serial Number	Calibration Due
Wideband Radio Communication Tester	R&S	CMW500	114220	Jul. 03, 2023
Spectrum Analyzer	R&S	FSV40-N	102188	Feb. 20, 2024
Combiner Box	Ascentest	AT890-RFB	/	/

5.5. Field Strength of Spurious Radiation Measurement

5.5.1. Test Specification

Test Requirement:	FCC part 22.917(a), 24.238(b)
Test Method:	FCC part 2.1053
Limit:	30MHz~20GHz -13dBm
Test setup:	
Test Procedure:	<ol style="list-style-type: none"> 1. The testing follows FCC KDB 971168 D01v03 Section 5.8 and ANSI / TIA-603-D-2010Section 2.2.12. 2. The EUT was placed on a rotatable wooden table 0.8 meters above the ground. 3. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower. 4. The table was rotated 360 degrees to determine the position of the highest spurious emission. 5. The height of the receiving antenna is varied between one meter and four meters to search for the maximum spurious emission for both horizontal and vertical polarizations. 6. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking record of maximum spurious emission. 7. A horn antenna was substituted in place of the EUT and was driven by a signal generator.

	<ol style="list-style-type: none">8. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.9. Taking the record of output power at antenna port.10. Repeat step 7 to step 8 for another polarization.11. $EIRP \text{ (dBm)} = \text{S.G. Power} - \text{Tx Cable Loss} + \text{Tx Antenna Gain}$12. $ERP \text{ (dBm)} = EIRP - 2.15$13. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.14. The limit line is derived from $43 + 10\log(P) \text{ dB}$ below the transmitter power $P(\text{Watts})$ $= P(\text{W}) - [43 + 10\log(P)] \text{ (dB)}$ $= [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)}$ $= -13 \text{ dBm.}$
Test results:	PASS
Remark:	All modulations have been tested, but only the worst modulation show in this test item.

5.5.2. Test Instruments

Radiated Emission Test Site (966)				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Universal Radio Communication Tester	R&S	CMU200	110188	Jul. 04, 2023
Spectrum Analyzer	R&S	FSQ40	200061	Jul. 03, 2023
Signal Generator	HP	83623B	3614A00396	Feb. 24, 2024
Broadband Antenna	Schwarzbeck	VULB9163	340	Jul. 05, 2023
Horn Antenna	Schwarzbeck	BBHA 9120D	631	Jul. 05, 2023
Broadband Antenna	Schwarzbeck	VULB9163	412	Jul. 05, 2023
Horn Antenna	Schwarzbeck	BBHA 9120D	1201	Jul. 05, 2023
Horn Antenna	Schwarzbeck	BBHA 9170	00956	Feb. 24, 2024
Coaxial cable	SKET	RC-18G-N-M	/	Feb. 24, 2024
Coaxial cable	SKET	RC_40G-K-M	/	Feb. 24, 2024
Antenna Mast	Keleto	RE-AM	/	/
EMI Test Software	Shurples Technology	EZ-EMC	/	/

5.5.3. Test Data**Frequency Range (9 kHz-30MHz)**

Frequency (MHz)	Level@3m (dB μ V/m)	Limit@3m (dB μ V/m)
--	--	--
--	--	--
--	--	--
--	--	--

Note: 1. Emission Level=Reading+ Cable loss+Antenna factor-Amp factor

2. The emission levels are 20 dB below the limit value, which are not reported. It is deemed to comply with the requirement

Band	Band 2(QPSK, 20MHz)			Test channel:	Lowest
Test mode:				Temperature :	25°C
				Relative Humidity:	56%

Note: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

Frequency (MHz)	Spurious Emission				Limit (dBm)	Result
	Polarization	Level (dBm)	Correction Factor (dB)	Spurious emissions (dBm)		
3720.00	Vertical	-59.68	23.54	-36.14	-13.00	PASS
5580.00	V	-64.39	23.81	-40.58		
7440.00	V	-81.20	23.96	-57.24		
3720.00	Horizontal	-59.39	23.54	-35.85		
5580.00	H	-65.26	23.81	-41.45		
7440.00	H	-77.62	23.96	-53.66		

Band	Band 2(QPSK, 20MHz)			Test channel:	Middle
Test mode:				Temperature :	25°C
				Relative Humidity:	56%

Note: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

Frequency (MHz)	Spurious Emission				Limit (dBm)	Result
	Polarization	Level (dBm)	Correction Factor (dB)	Spurious emissions (dBm)		
3760.00	Vertical	-60.61	23.58	-37.03	-13.00	PASS
5640.00	V	-72.04	23.85	-48.19		
7520.00	V	-80.35	23.99	-56.36		
3760.00	Horizontal	-59.78	23.58	-36.20		
5640.00	H	-65.46	23.85	-41.61		
7520.00	H	-79.49	23.99	-55.50		

Band	Band 2(QPSK, 20MHz)			Test channel:	Highest
Test mode:				Temperature :	25°C
				Relative Humidity:	56%

Note: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

Frequency (MHz)	Spurious Emission				Limit (dBm)	Result
	Polarization	Level (dBm)	Correction Factor (dB)	Spurious emissions (dBm)		
3800.00	Vertical	-62.36	23.60	-38.76	-13.00	PASS
5700.00	V	-70.41	23.88	-46.53		
7600.00	V	-79.12	24.02	-55.10		
3800.00	Horizontal	-57.63	23.60	-34.03		
5700.00	H	-67.42	23.88	-43.54		
7600.00	H	-81.01	24.02	-56.99		

Band	Band 2(16QAM, 5MHz)			Test channel:	Lowest			
Test mode:				Temperature :	25°C			
				Relative Humidity:	56%			

Note: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

Frequency (MHz)	Spurious Emission				Limit (dBm)	Result
	Polarizati on	Level (dBm)	Correction Factor (dB)	Spurious emissions (dBm)		
3705.00	Vertical	-60.52	23.54	-36.98	-13.00	PASS
5557.50	V	-66.14	23.81	-42.33		
7410.00	V	-79.37	23.96	-55.41		
3705.00	Horizontal	-59.27	23.54	-35.73		
5557.50	H	-65.52	23.81	-41.71		
7410.00	H	-76.74	23.96	-52.78		

Band	Band 2(16QAM, 5MHz)			Test channel:	Middle			
Test mode:				Temperature :	25°C			
				Relative Humidity:	56%			

Note: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

Frequency (MHz)	Spurious Emission				Limit (dBm)	Result
	Polarizati on	Level (dBm)	Correction Factor (dB)	Spurious emissions (dBm)		
3760.00	Vertical	-61.92	23.58	-38.34	-13.00	PASS
5640.00	V	-70.53	23.85	-46.68		
7520.00	V	-78.06	23.99	-54.07		
3760.00	Horizontal	-58.38	23.58	-34.80		
5640.00	H	-66.63	23.85	-42.78		
7520.00	H	-80.11	23.99	-56.12		

Band	Band 2(16QAM, 5MHz)			Test channel:	Highest			
Test mode:				Temperature :	25°C			
				Relative Humidity:	56%			

Note: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

Frequency (MHz)	Spurious Emission				Limit (dBm)	Result
	Polarizati on	Level (dBm)	Correction Factor (dB)	Spurious emissions (dBm)		
3815.00	Vertical	-61.97	23.60	-38.37	-13.00	PASS
5722.50	V	-71.60	23.88	-47.72		
7630.00	V	-80.30	24.02	-56.28		
3815.00	Horizontal	-58.57	23.60	-34.97		
5722.50	H	-66.95	23.88	-43.07		
7630.00	H	-81.58	24.02	-57.56		

Band	Band 5(QPSK, 10MHz)			Test channel:	Lowest
Test mode:				Temperature :	25°C
				Relative Humidity:	56%

Note: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

Frequency (MHz)	Spurious Emission				Limit (dBm)	Result
	Polarization	Level (dBm)	Correction Factor (dB)	Spurious emissions (dBm)		
1658.00	Vertical	-61.26	23.15	-38.11	-13.00	PASS
2487.00	V	-65.09	23.24	-41.85		
3316.00	V	-80.98	23.35	-57.63		
1658.00	Horizontal	-61.32	23.15	-38.17		
2487.00	H	-63.44	23.24	-40.20		
3316.00	H	-77.62	23.35	-54.27		
Band	Band 5(QPSK, 10MHz)				Test channel:	Middle
Test mode:		Temperature :	25°C			
		Relative Humidity:	56%			

Note: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

Frequency (MHz)	Spurious Emission				Limit (dBm)	Result
	Polarization	Level (dBm)	Correction Factor (dB)	Spurious emissions (dBm)		
1673.00	Vertical	-59.83	23.17	-36.66	-13.00	PASS
2509.50	V	-72.61	23.26	-49.35		
3346.00	V	-77.67	23.38	-54.29		
1673.00	Horizontal	-59.38	23.17	-36.21		
2509.50	H	-65.56	23.26	-42.30		
3346.00	H	-79.18	23.38	-55.80		
Band	Band 5(QPSK, 10MHz)				Test channel:	Highest
Test mode:		Temperature :	25°C			
		Relative Humidity:	56%			

Note: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

Frequency (MHz)	Spurious Emission				Limit (dBm)	Result
	Polarization	Level (dBm)	Correction Factor (dB)	Spurious emissions (dBm)		
1688.00	Vertical	-63.55	23.19	-40.36	-13.00	PASS
2532.00	V	-72.18	23.28	-48.90		
3376.00	V	-84.14	23.40	-60.74		
1688.00	Horizontal	-58.57	23.19	-35.38		
2532.00	H	-66.85	23.28	-43.57		
3376.00	H	-81.96	23.40	-58.56		

Band	Band 5(16QAM, 5MHz)			Test channel:	Lowest			
Test mode:				Temperature :	25°C			
				Relative Humidity:	56%			

Note: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

Frequency (MHz)	Spurious Emission				Limit (dBm)	Result				
	Polarization	Level (dBm)	Correction Factor (dB)	Spurious emissions (dBm)						
1653.00	Vertical	-59.98	23.15	-36.83	-13.00	PASS				
2479.50	V	-65.66	23.24	-42.42						
3306.00	V	-82.28	23.35	-58.93						
1653.00	Horizontal	-59.62	23.15	-36.47						
2479.50	H	-65.73	23.24	-42.49						
3306.00	H	-79.19	23.35	-55.84						
Band	Band 5(16QAM, 5MHz)				Test channel:	Middle				
Test mode:					Temperature :	25°C				
					Relative Humidity:	56%				

Note: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

Frequency (MHz)	Spurious Emission				Limit (dBm)	Result				
	Polarization	Level (dBm)	Correction Factor (dB)	Spurious emissions (dBm)						
1673.00	Vertical	-59.76	23.17	-36.59	-13.00	PASS				
2509.50	V	-71.20	23.26	-47.94						
3346.00	V	-77.93	23.38	-54.55						
1673.00	Horizontal	-56.56	23.17	-33.39						
2509.50	H	-67.04	23.26	-43.78						
3346.00	H	-79.34	23.38	-55.96						
Band	Band 5(16QAM, 5MHz)				Test channel:	Highest				
Test mode:					Temperature :	25°C				
					Relative Humidity:	56%				

Note: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

Frequency (MHz)	Spurious Emission				Limit (dBm)	Result
	Polarization	Level (dBm)	Correction Factor (dB)	Spurious emissions (dBm)		
1693.00	Vertical	-61.85	23.19	-38.66	-13.00	PASS
2539.50	V	-71.35	23.28	-48.07		
3386.00	V	-79.57	23.40	-56.17		
1693.00	Horizontal	-58.67	23.19	-35.48		
2539.50	H	-68.59	23.28	-45.31		
3386.00	H	-82.03	23.40	-58.63		

5.6. Frequency Stability Measurement

5.6.1. Test Specification

Test Requirement:	FCC part 22.355, 24.235
Test Method:	FCC Part 2.1055
Limit:	± 2.5 ppm
Test Setup:	
Test Procedure:	<p>Test Procedures for Temperature Variation</p> <ol style="list-style-type: none"> 1. The testing follows FCC KDB 971168 D01v03 Section 9.0. 2. The EUT was set up in the thermal chamber and connected with the system simulator. 3. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute. 4. With power OFF, the temperature was raised in 10°C steps up to 50°C. The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute. <p>Test Procedures for Voltage Variation</p> <ol style="list-style-type: none"> 1. The testing follows FCC KDB 971168 D01v03 Section 9.0. 2. The EUT was placed in a temperature chamber at $25\pm 5^{\circ}\text{C}$ and connected with the system simulator. 3. The power supply voltage to the EUT was varied from BEP to 115% of the nominal value measured at the input to the EUT. 4. The variation in frequency was measured for the worst case. 5. The worst case(worst bandwidth) for frequency stability reported in the Test Data. The worst bandwidth is as follow: 1.4M is for LTE Band 2, 1.4M is for LTE Band 5
Test Result:	PASS

5.6.2. Test Instruments

Equipment	Manufacturer	Model	Serial Number	Calibration Due
Wideband Radio Communication Tester	R&S	CMW500	114220	Jul. 03, 2023
Programable temprature and humidity chamber	JQ	JQ-2000	/	Jul. 04, 2023
DC power supply	Kingrang	KR3005K	/	Jul. 04, 2023
Combiner Box	AT890-RFB	Ascentest	/	/

Appendix A: Photographs of Test Setup

Refer to the test report No. TCT230320E904

Appendix B: Photographs of EUT

Refer to the test report No. TCT230320E904

Test Data for Appendix For LTE Band 2 and Appendix For LTE Band 5

*******END OF REPORT*******