

FCC RF Exposure

Applicant : Nebula Electronic Technology Corporation
Address : Room 1504, No. 8, Lane 777, Gaoke East Road, Pudong New Area, Shanghai
Product Name : Bluetooth module
Brand Mark : N.E.T
Model : BT938-2
Series model : N/A
FCC ID : 2BAMT-BT938-2
Report Number : BLA-EMC-202506-A8002
Date of Receipt : Jun. 19, 2025
Date of Test : Jun. 19, 2025 to Jun. 27, 2025
Test Standard : 47 CFR Part 15, Part1.1307
47 CFR Part 15, Part2.1093
KDB447498D04 General RF Exposure Guidance v01
Test Result : Pass

Compiled by: *Mark Chen* Review by: *Xavier*



BlueAsia of Technical Services(Shenzhen) Co.,Ltd.

Address: Building C, No. 107, Shihuan Road, Shiyan Sub-District, Baoan District, Shenzhen, Guangdong Province, China



The test report is effective only with both signature and specialized stamp and The result(s) shown in this report refer only to the sample(s) tested. Without written approval of BlueAsia, this report can't be reproduced except in full. The results described in this report do not represent the quality or characteristics of the sampled batch, nor do they represent any similar or identical products that are not explicitly stated.

Table of Contents

1 General information	4
1.1 General information	4
1.2 General description of EUT	4
2 RF Exposure Compliance Requirement	5
2.1 Standard Requirement	5
2.2 Limits	5
2.3 Result	6

Revise Record

Version No.	Date	Description
01	Jun. 27, 2025	Original

BlueAsia

1 General information

1.1 General information

Applicant	Nebula Electronic Technology Corporation
Address	Room 1504, No. 8, Lane 777, Gaoke East Road, Pudong New Area, Shanghai
Manufacturer	Nebula Electronic Technology Corporation
Address	Room 1504, No. 8, Lane 777, Gaoke East Road, Pudong New Area, Shanghai
Factory	Nebula Electronic Technology Corporation
Address	Room 1504, No. 8, Lane 777, Gaoke East Road, Pudong New Area, Shanghai

1.2 General description of EUT

Product Name	Bluetooth module
Model No.	BT938-2
Operation Frequency	2402MHz-2480MHz
Modulation Type	GFSK
Rate data	1Mbps, 2Mbps
Channel Spacing	2MHz
Number of Channels	40
Antenna Type	PCB antenna
Antenna Gain	1.2dBi (Provided by customer)
Power supply	DC 3.3V
Hardware Version	V1.0
Software Version	V1.0

Note: For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacturer.

2 RF Exposure Compliance Requirement

2.1 Standard Requirement

According to 447498 D04 Interim General RF Exposure Guidance v01

Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR condition, listed below, is satisfied.

2.2 Limits

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}}(d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases} \quad (\text{B.2})$$

where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right)$$

and f is in GHz, d is the separation distance (cm), and $ERP_{20\text{cm}}$ is per Formula (B.1).

Example values shown in Table B.2 are for illustration only.

Table B.2—Example Power Thresholds (mW)

Frequency (MHz)	Distance (mm)									
	5	10	15	20	25	30	35	40	45	50
300	39	65	88	110	129	148	166	184	201	217
450	22	44	67	89	112	135	158	180	203	226
835	9	25	44	66	90	116	145	175	207	240
1900	3	12	26	44	66	92	122	157	195	236
2450	3	10	22	38	59	83	111	143	179	219
3600	2	8	18	32	49	71	96	125	158	195
5800	1	6	14	25	40	58	80	106	136	169

$$P_{th} \text{ (mW)} = ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases} \quad (\text{B.1})$$

2.3 Result

$$\text{EIRP} = \text{pt} \times \text{gt} = (\text{E} \times \text{d})/30$$

Where:

pt = transmitter output power in watts,

gt = numeric gain of the transmitting antenna (unitless),

E = electric field strength in V/m,

d = measurement distance in meters (m)

$$\text{Spot} = (\text{Exd})/30 \times \text{gt}$$

$$\text{Ant gain} = 1.2\text{dBi}$$

For BLE 2M(Worst case):

$$\text{Max Output power} = 0.164\text{dBm} @ 2442\text{MHz}$$

$$\text{Max Output power} = 1.04\text{mW} < 2.7\text{mW}$$

$$\text{ERP} = 0.164\text{dBm} + 1.2\text{dBi} - 2.15 = -0.786\text{dBm} = 0.834\text{mW} < 2.7\text{mW}$$

Comply with RF exposure exemption limit.

----END OF REPORT----

The test report is effective only with both signature and specialized stamp, the result(s) shown in this report refer only to the sample(s) tested. Without written approval of BlueAsia, this report can't be reproduced except in full.