

SAR Compliance Test Report

Date of Report	16/10/2023	Client's Contact person:	Antje Schladitz
Number of pages:	26	Responsible Test engineer:	Kalle Orava
Testing laboratory:	Verkotan Oy Elektroniikkatie 17 90590 Oulu Finland	Client:	REMS GmbH & Co KG Stuttgarter Strasse 83 71332 Waiblingen Germany
Tested device	REMS Akku-Press 22 V ACC Connected		
Related reports:	-		
Testing has been carried out in accordance with:	47CFR §2.1093 Radiofrequency Radiation Exposure Evaluation: Portable Devices FCC published RF exposure KDB procedures IEC/IEEE 62209-1528, 2020 Measurement procedure for the assessment of specific absorption rate of human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices RSS-102, Issue 5, 2015 Radio Frequency (RF) Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands)		
Documentation:	The test report must always be reproduced in full; reproduction of an excerpt only is subject to written approval of the testing laboratory		
Test Results:	The EUT complies with the requirements in respect of all parameters subject to the test. The test results relate only to devices specified in this document		
Date and signatures:	16.10.2023 Laboratory Manager <i>Miia Nurkkala</i>		

TABLE OF CONTENTS

1. SUMMARY OF SAR TEST REPORT	3
1.1 TEST DETAILS	3
1.2 MAXIMUM RESULTS	4
1.2.1 Standalone SAR	4
1.2.2 Maximum Drift	4
1.2.3 Measurement Uncertainty	4
2. DESCRIPTION OF THE DEVICE UNDER TEST (DUT)	5
2.1 SUPPORTED FREQUENCY BANDS AND OPERATIONAL MODES	6
3. OUTPUT POWER	7
3.1 MAXIMUM SPECIFIED CONDUCTED OUTPUT POWER	7
3.2 TESTED CONDUCTED POWER	7
4. TEST EQUIPMENT	8
4.1 TEST EQUIPMENT LIST	9
4.1.1 Isotropic E-field Probe Type EX3DV4	10
4.2 PHANTOMS	10
4.3 TISSUE SIMULANTS	10
4.4 SYSTEM VALIDATION STATUS	11
4.5 SYSTEM CHECK	11
4.5.1 Tissue Simulant Verification	11
5. TEST PROCEDURE	12
5.1 DEVICE HOLDER	12
5.2 TEST POSITIONS	13
5.2.1 Body-worn Configuration, 0mm separation distance	13
5.3 SCAN PROCEDURES	13
5.4 SAR AVERAGING METHODS	13
6. MEASUREMENT UNCERTAINTY	14
7. TEST RESULTS	15
7.1 SAR RESULTS FOR BODY EXPOSURE CONDITION WITH 0MM SEPARATION	15
7.2 IEC 62209-2 AMD1:2019	15
APPENDIX A: PHOTOS OF THE DUT	16
APPENDIX B: SYSTEM CHECK SCAN	19
APPENDIX C: MEASUREMENT SCANS	20
APPENDIX D: RELEVANT PAGES FROM PROBE CALIBRATION REPORTS	21
APPENDIX E: RELEVANT PAGES FROM DIPOLE CALIBRATION REPORTS	25

1. SUMMARY OF SAR TEST REPORT

1.1 Test Details

Equipment under Test (DUT):

Product:	REMS Akku-Press 22 V ACC Connected
Manufacturer:	REMS GmbH & Co KG
Model:	Pressgun 6 Plus
Serial Number:	918954-2022 (SAR sample), 918952-2022 (conducted sample)
FCC ID Number:	2BAPC-576003
DUT Number:	21049 (SAR sample), 21048 (conducted sample)
Battery Type used in testing:	Li-Ion Battery
State of the Sample:	Production sample

Testing information:

Testing performed:	14.09.2023 – 18.09.2023
Notes:	-
Document history:	-
Document ID:	FCC ISED_SAR report_Pressgun 6 Plus_ID6016_18092023.docx
Temperature °C	22±2 / Controlled
Humidity RH%	30±20 / Controlled
Measurement performed by:	Kalle Orava
FCC Test Firm Designation Number:	FI0005
ISED Company Number:	22218

1.2 Maximum Results

The maximum reported* SAR values for Body-worn for transmitting systems are shown in a table below. The device conforms to the requirements of the standards when the maximum reported SAR value is less than or equal to the limit. The SAR limit specified in FCC 47 CFR part 2 (2.1093) and Health Canada's RF exposure guideline, Safety Code 6 for Head/Body SAR_{1g} is 1.6 W/kg.

1.2.1 Standalone SAR

System	Highest Reported* SAR _{1g} (W/kg) in Body-Worn Exposure Condition, 0mm separation distance	Result
2.4 GHz WLAN	0.19	PASS

* Reported SAR Values are scaled to upper limit of power tuning tolerance.

1.2.2 Maximum Drift

Maximum Drift During Measurements	-0.26 dB*
-----------------------------------	-----------

*Larger than 5% drifts included to scaling factors

1.2.3 Measurement Uncertainty

SAR 1g: 0.3 – 3 GHz:

Expanded Uncertainty (k=2) 95 %	±22.1 %
---------------------------------	---------

2. DESCRIPTION OF THE DEVICE UNDER TEST (DUT)

The DUT is a crimping tool which supports 2.4 GHz WLAN.



Figure 1. Overview of the DUT




Figure 2. Antenna location




Figure 3. View of the internal antenna

Device Category	Portable
Exposure Environment	General population uncontrolled

2.1 Supported Frequency Bands and Operational Modes

TX Frequency bands	Modes of Operation	Transmitter Frequency Range [MHz]
	2.4 GHz WLAN	2412 – 2462

3. OUTPUT POWER

3.1 Maximum specified conducted output power

From the customer, including tune-up tolerances;

WLAN 2.4GHz	Max Output Power [dBm]
802.11b	19.5
802.11g	18
802.11n	18

3.2 Tested conducted power

Measured conducted output power at transmitting antenna connector;

WLAN 2.4 GHz:

Standard	Transmission mode	Data rate [Mbps]	Output power [dBm]		
			CH 1 2412 MHz	CH 6 2437 MHz	CH 11 2462 MHz
802.11b	DSSS	1	18.8	19.03	18.88

4. TEST EQUIPMENT

Dasy52 near field scanning system, manufactured by SPEAG was used for SAR testing. The test system consists of high precision robotics system (Staubli), robot controller, computer, near-field probe, probe alignment sensor, and a phantom containing the tissue equivalent material. The robot is a six-axis industrial robot performing precise movements to position the probe to the location of maximum electromagnetic field.




Figure 4 Schematic Laboratory Picture

4.1 Test Equipment List

Main used test system components are listed below. For full equipment list and calibration intervals, please contact the testing laboratory.

Test Equipment	Model	Serial Number	Calibration Date	Interval [years]
DASY5 Software	52.8.8.1258	-	NA	NA
Amplifier, 800-4200MHz, 50W	5163F	1022	NA	NA
DAE4, converter	DAE4	1332	02/2023	1
Inline Peak Power Sensor	MA24105A	2102058	11/2022	1
Isotropic DOS probe	EX3DV4	3892	04/2023	1
Network Analyzer	E5071C	MY46102812	05/2023	1
System validation dipole	D2450V2	729	07/2022	3

Dipole calibration period supporting data:

Dipole and serial number	Frequency (MHz)	Measured on 09/2023			Calibrated		
		Return loss (dB)	Impedance [Ω]		Return loss [dB]	Impedance [Ω]	
D2450V2-729	2450	-30.1	53.1	0.8	-24.7	54.3	4.3

4.1.1 Isotropic E-field Probe Type EX3DV4

Construction	Symmetrical design with triangular core Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE)
Calibration	Calibration certificate in Appendix D
Frequency	10 MHz to > 6 GHz (dosimetry); Linearity: ± 0.2 dB (30 MHz to 6 GHz)
Directivity	± 0.3 dB in HSL (rotation around probe axis) ± 0.5 dB in tissue material (rotation normal to probe axis)
Dynamic Range	10 μ W/g to > 100 mW/g, Linearity: ± 0.2 dB
Dimensions	Overall length: 330 mm Tip length: 10 mm Body diameter: 12 mm
Application	General dosimetry up to 6 GHz Compliance tests of mobile phones Fast automatic scanning in arbitrary phantoms

4.2 Phantoms

SAM Phantom:

The phantom used in SAR tests was the flat phantom section of the twin-headed "SAM Phantom" manufactured by SPEAG. The phantom conforms to the requirements of IEC/IEEE 62209-1528 and FCC published RF Exposure KDB Procedures.

4.3 Tissue Simulants

Recommended values for the dielectric parameters of the tissue simulants are given in IEC/IEEE 62209-1528 and FCC published RF Exposure KDB Procedures. The dielectric parameters of the used tissue simulants were within $\pm 10\%$ of the recommended values at frequencies under 3GHz and $\pm 5\%$ at frequencies above 3GHz. A liquid compensation algorithm was used in DASY5 with which measured peak average SAR values were corrected for the deviation of used liquid. Depth of the tissue simulant was at least 15.0 cm from the inner surface of the flat phantom.

Tissue simulant liquid Ingredients
Deionized Water, oil, salt, emulsifiers

4.4 System Validation Status

Frequency [MHz]	Dipole Type / SN	Probe Type / SN	Calibrated Signal Type	DAE Unit / SN	Dielectric Constant [ϵ']	Conductivity σ [S/m]	Date
2450	D2450V2 - SN: 758	EX3DV4 - SN: 3852	CW	DAE 4 / 710	40.46	1.75	11/2022

4.5 System Check

Date	Tissue Type	Tissue Temp. [°C]	Frequency [MHz]	Input Power [mW]	Measured SAR _{1g} [W/kg]	1 W Target SAR _{1g} [W/kg]	1 W Normalized SAR _{1g} [W/kg]	Deviation [%]	Plot #
15.09.2023	WB Head	22	2450	250	13.6	52.3	54.4	4.02	1

4.5.1 Tissue Simulant Verification

				Target		Measured		Deviation	
Date	Tissue Type	Tissue Temp [°C]	Frequency [MHz]	Dielectric Constant [ϵ'] Target	Conductivity σ [S/m] Target	Dielectric Constant [ϵ']	Conductivity σ [S/m]	ϵ [%]	σ [%]
14.09.2023	WB Head	21.9	2412.0	39.27	1.76	40.56	1.73	3.3	-2.1
14.09.2023	WB Head	21.9	2437.0	39.23	1.79	40.52	1.75	3.3	-2.2
14.09.2023	WB Head	21.9	2450.0	39.2	1.8	40.51	1.76	3.3	-2.3
14.09.2023	WB Head	21.9	2462.0	39.19	1.81	40.49	1.77	3.3	-2.5

5. TEST PROCEDURE

Testing was carried out in accordance with FCC KDB Publications 447498 D04 Interim General RF Exposure Guidance v01, 248227 D01 802.11 Wi-Fi SAR and RSS-102, Issue 5.

Low, mid and high frequency channels for the configuration with the highest SAR value were tested as per ISED notice 2016-DRS001.

A control software for WLAN was used to set the DUT to transmit at maximum power.

The WLAN transmission modes for testing were selected according to largest channel bandwidth configuration, lowest order modulation and lowest data rate.

WLAN 2.4GHz was tested with 802.11b standard with data rate of 1Mbit/s.

5.1 Device Holder

The device was placed in the device holder (illustrated below) that is supplied by SPEAG as an integral part of the Dasy system.



Device holder supplied by SPEAG

5.2 Test Positions

5.2.1 Body-worn Configuration, 0mm separation distance

Body SAR was tested from the back, left and right sides of the device because the antenna is in the bottom part of the handle. Front side of the device was not tested since the battery blocks access to the DUT casing. The device was lifted towards the phantom until the distance between the phantom and the device was 0mm.

Photos of the test positions are presented in appendix A

5.3 Scan Procedures

First, area scans were used for determination of the field distribution. Next, a zoom scan was performed around the highest E-field value to determine the averaged SAR value. Drift was determined by measuring the same point at the start of the area scan and again at the end of the zoom scan.

5.4 SAR Averaging Methods

The maximum SAR value was averaged over a cube of tissue using interpolation and extrapolation.

The interpolation, extrapolation and maximum search routines within Dasy52 are all based on the modified Quadratic Shepard's method (Robert J. Renka, "Multivariate Interpolation of Large Sets of Scattered Data", University of North Texas ACM Transactions on Mathematical Software, vol. 14, no. 2, June 1988, pp. 139-148).

The interpolation scheme combines a least-square fitted function method with a weighted average method. A trivariate 3-D / bivariate 2-D quadratic function is computed for each measurement point and fitted to neighboring points by a least-square method. For the zoom scan, inverse distance weighting is incorporated to fit distant points more accurately. The interpolating function is finally calculated as a weighted average of the quadratics.

In the zoom scan, the interpolation function is used to extrapolate the Peak SAR from the deepest measurement points to the inner surface of the phantom.

6. MEASUREMENT UNCERTAINTY

DASY5 Uncertainty Budget According to IEC/IEEE 62209-1528 (Frequency band: 300MHz - 3GHz range)								
Symbol	Error Description	Uncert. value	Prob. Dist.	Div.	(c) 1g	(c) 10g	Std. Unc. (1g)	Std. Unc. (10g)
Measurement System Errors								
CF	Probe Calibration	±12.0%	N	√2	1	1	±6.0%	±6.0%
CF _{drift}	Probe Calibration Drift	±1.7%	R	√3	1	1	±1.0%	±1.0%
LIN	Probe Linearity	±4.7%	R	√3	1	1	±2.7%	±2.7%
BBS	Broadband Signal	±3.0%	R	√3	1	1	±1.7%	±1.7%
ISO	Probe Isotropy	±7.6%	R	3	1	1	±4.4%	±4.4%
DAE	Data Acquisition	±0.3%	N	1	1	1	±0.3%	±0.3%
AMB	RF Ambient	±1.8%	N	1	1	1	±1.8%	±1.8%
Δ _{sys}	Probe Positioning	±3.9%	N	1	0.14	0.14	±0.5%	±0.5%
DAT	Data Processing	±1.2%	N	1	1	1	±1.2%	±1.2%
Phantom and Device Errors								
LIQ(σ)	Conductivity (meas.) ^{DAK}	±2.5%	N	√1	0.78	0.71	±2.0%	±1.8%
LIQ(T _a)	Conductivity (temp.) ^{BB}	±3.3%	R	√3	0.78	0.71	±1.5%	±1.4%
EPS	Phantom Permittivity	±14.0%	R	3	0	0	±0%	±0%
DIS	Distance DUT - TSL	±2.0%	N	1	2	2	±4.0%	±4.0%
D _{xyz}	Device Positioning (±0.5mm)	±1.0%	N	1	1	1	±1.0%	±1.0%
H	Device Holder	±3.6%	N	√1	1	1	±3.6%	±3.6%
MOD	DUT Modulation ^m	±2.4%	R	√3	1	1	±1.4%	±1.4%
TAS	Time-average SAR	±2.6%	R	3	1	1	±1.5%	±1.5%
RF _{drift}	DUT drift	±2.5%	N	1	1	1	±2.5%	±2.5%
VAL	Val Antenna Unc. ^{val}	±0.0%	N	1	1	1	±0%	±0%
RF _{in}	Unc. Input Power ^{val}	±0.0%	N	1	1	1	±0%	±0%
Correction to the SAR results								
C(ε, σ)	Deviation to Target	±1.9%	N	√1	1	0.84	±1.9%	±1.6%
C(R)	SAR scaling ^p	±0%	R	3	1	1	±0%	±0%
u(ΔSAR)	Combined Uncertainty						±11.0%	±10.9%
U	Expanded Uncertainty						±22.1%	±21.9%

7. TEST RESULTS

7.1 SAR Results for Body Exposure Condition with 0mm separation

2.4GHz WLAN:

Mode	Data Rate [Mbps]	Frequency [MHz]	Channel	Test position	Maximum Power [dBm]	Conducted Power [dBm]	Measured SAR _{1g} [W/kg]	Power Drift* [dB]	Scaling Factor	Duty Cycle	Reported SAR _{1g} [W/kg]	Plot #
802.11b	1	2437	6	Back, 0mm	19.5	19.03	0.00246	0**	1.11	1:1	0.0027	
802.11b	1	2437	6	Left, 0mm	19.5	19.03	0.141	-0.12	1.11	1:1	0.16	
802.11b	1	2437	6	Right, 0mm	19.5	19.03	0.0195	-0.26	1.18	1:1	0.02	
802.11b	1	2412	1	Left, 0mm	19.5	18.8	0.137	0.14	1.17	1:1	0.16	
802.11b	1	2462	11	Left, 0mm	19.5	18.88	0.161	-0.1	1.15	1:1	0.19	2

*Larger than 5% drifts included to scaling factors

**Due to low e-field generated by DUT at the location of drift measurement, the measurement is not applicable.

7.2 IEC 62209-2 AMD1:2019

According to IEC 62209-2 AMD1:2019, the zoom scan complies if the peak spatial-average SAR is below 0.1 W/kg, or if the following criteria is met:

1. The smallest horizontal distance from the local SAR peaks to all points 3 dB below the SAR peak is larger than the horizontal grid step.
2. Ratio of SAR at the second measured point (M2) to the SAR at the closest measured point (M1) at the x-y location of the measured maximum is at least 30%.

Zoom scan compliance according to IEC 62209-2 AMD1:2019 is automatically verified by DASY5 software and all zoom scans in this test report do pass the criteria. The smallest horizontal distance and Ratio between measurement points M2 and M1 of the highest SAR results is available in Appendix C.

APPENDIX A: PHOTOS OF THE DUT

Size of the DUT is: 300 x 370 x 80 mm



Figure 5. Sides which were measured



Figure 6. Right side of the DUT, 0mm



Figure 7. Left side of the DUT, 0mm



Figure 8. Back side of the DUT, 0mm

APPENDIX B: SYSTEM CHECK SCAN

Plot 1

Date/Time: 15/09/2023 09:02:53

Test Laboratory: Verkotan Oy

DUT: D2450V2 - SN729; Type: D2450V2; Serial: SN729

Communication System: UID 0, CW (0); Communication System Band: D2450 (2450.0 MHz); Frequency: 2450 MHz;
Communication System PAR: 0 dB;
Medium parameters used (interpolated): $f = 2450$ MHz; $\sigma = 1.759$ S/m; $\epsilon_r = 40.51$; $\rho = 1000$ kg/m³
Phantom section: Flat Section
Measurement Standard: DASYS (IEEE/IEC)

DASY Configuration:

- Probe: EX3DV4 - SN3892; ConvF(7.09, 7.31, 6.98) @ 2450 MHz; Calibrated: 20/04/2023
 - Sensor-Surface: 1.4mm (Mechanical Surface Detection), $z = -4.0, 31.0$
 - Electronics: DAE4 Sn1332; Calibrated: 15/02/2023
 - Phantom: SAR2 frontTwin-SAM V4.0 (30deg probe tilt); Type: QD 000 P40 CC;
 - DASY52 52.10.4(1527); SEMCAD X 14.6.12(7450)

Configuration/system check/Area Scan (61x101x1): Interpolated grid: $dx=1.000$ mm, $dy=1.000$ mm

Maximum value of SAR (interpolated) = 20.3 W/kg


Configuration/system check/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 110.8 V/m; Power Drift = -0.07 dB

Peak SAR (extrapolated) = 26.8 W/kg

SAR(1 g) = 13.6 W/kg; SAR(10 g) = 6.34 W/kg (SAR corrected for target medium)

Maximum value of SAR (measured) = 22.1 W/kg



APPENDIX C: MEASUREMENT SCANS

Plot 2

Date/Time: 15/09/2023 16:17:29

Test Laboratory: Verkotan Oy


DUT: Pressgun 6 Plus;

Communication System: UID 0, WLAN 2.4 (0); Communication System Band: WLAN2.4GHz; Frequency: 2462 MHz;
Communication System PAR: 0 dB;
Medium parameters used (interpolated): $f = 2462$ MHz; $\sigma = 1.767$ S/m; $\epsilon_r = 40.484$; $\rho = 1000$ kg/m³
Phantom section: Flat Section
Measurement Standard: DASYS (IEEE/IEC)

DASY Configuration:

- Probe: EX3DV4 - SN3892; ConvF(7.09, 7.31, 6.98) @ 2462 MHz; Calibrated: 20/04/2023
 - Sensor-Surface: 1.4mm (Mechanical Surface Detection), Sensor-Surface: 4mm (Mechanical Surface Detection), $z = 31.0, -4.0$
 - Electronics: DAE4 Sn1332; Calibrated: 15/02/2023
 - Phantom: SAR2 frontTwin-SAM V4.0 (30deg probe tilt); Type: QD 000 P40 CC;
 - DASYS2 52.10.2(1495); SEMCAD X 14.6.12(7450)

Configuration/Pressgun, 2.4 WLAN, CH11, Left, 0mm/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm
Reference Value = 6.732 V/m; Power Drift = -0.10 dB
Peak SAR (extrapolated) = 0.353 W/kg
SAR(1 g) = 0.161 W/kg; SAR(10 g) = 0.067 W/kg (SAR corrected for target medium)
Maximum value of SAR (measured) = 0.285 W/kg
Configuration/Pressgun, 2.4 WLAN, CH11, Left, 0mm/Area Scan (111x121x1): Interpolated grid: $dx=1.000$ mm, $dy=1.000$ mm
Maximum value of SAR (interpolated) = 0.245 W/kg



APPENDIX D: RELEVANT PAGES FROM PROBE CALIBRATION REPORTS

Calibration Laboratory of
Schmid & Partner
Engineering AG
Zeughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
S Servizio svizzero di taratura
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Client **Verkotan**
Oulu, Finland

Certificate No. **EX-3892_Apr23**

CALIBRATION CERTIFICATE

Object **EX3DV4 - SN:3892**

Calibration procedure(s) **QA CAL-01.v10, QA CAL-12.v10, QA CAL-14.v7, QA CAL-23.v6,
QA CAL-25.v8
Calibration procedure for dosimetric E-field probes**

Calibration date **April 20, 2023**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.
All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3) °C and humidity < 70%.
Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID	Cal Date (Certificate No.)	Scheduled Calibration
Power meter NRP2	SN: 104778	30-Mar-23 (No. 217-03804/03805)	Mar-24
Power sensor NRP-Z91	SN: 103244	30-Mar-23 (No. 217-03804)	Mar-24
OCP DAK-3.5 (weighted)	SN: 1249	20-Oct-22 (OCP-DAK3.5-1249_Oct22)	Oct-23
OCP DAK-12	SN: 1016	20-Oct-22 (OCP-DAK12-1016_Oct22)	Oct-23
Reference 20 dB Attenuator	SN: CC2552 (20x)	30-Mar-23 (No. 217-03809)	Mar-24
DAE4	SN: 660	16-Mar-23 (No. DAE4-660_Mar23)	Mar-24
Reference Probe ES3DV2	SN: 3013	06-Jan-23 (No. ES3-3013_Jan23)	Jan-24

Secondary Standards	ID	Check Date (in house)	Scheduled Check
Power meter E4419B	SN: GB41293874	06-Apr-16 (in house check Jun-22)	In house check: Jun-24
Power sensor E4412A	SN: MY41496087	06-Apr-16 (in house check Jun-22)	In house check: Jun-24
Power sensor E4412A	SN: 000110210	06-Apr-16 (in house check Jun-22)	In house check: Jun-24
RF generator HP 8648C	SN: US3642U01700	04-Aug-99 (in house check Jun-22)	In house check: Jun-24
Network Analyzer E8358A	SN: US41080477	31-Mar-14 (in house check Oct-22)	In house check: Oct-24

Calibrated by	Name Jeffrey Katzman	Function Laboratory Technician	Signature
Approved by	Name Sven Kühn	Function Technical Manager	Signature

Issued: April 22, 2023

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

EX3DV4 - SN:3892

April 20, 2023

Parameters of Probe: EX3DV4 - SN:3892

Basic Calibration Parameters

	Sensor X	Sensor Y	Sensor Z	Unc ($k = 2$)
Norm ($\mu V/(V/m)^2$) ^A	0.47	0.39	0.49	$\pm 10.1\%$
DCP (mV) ^B	102.4	105.3	102.6	$\pm 4.7\%$

Calibration Results for Modulation Response

UID	Communication System Name		A dB	B dB $\sqrt{\mu V}$	C	D dB	VR mV	Max dev.	Max Unc ^E $k = 2$
0	CW	X	0.00	0.00	1.00	0.00	120.0	$\pm 1.1\%$	$\pm 4.7\%$
		Y	0.00	0.00	1.00		141.8		
		Z	0.00	0.00	1.00		123.2		

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor $k=2$, which for a normal distribution corresponds to a coverage probability of approximately 95%.

^A The uncertainties of Norm X,Y,Z do not affect the E^2 -field uncertainty inside T-SL (see Page 5).

^B Linearization parameter uncertainty for maximum specified field strength.

^E Uncertainty is determined using the max. deviation from linear response applying rectangular distribution and is expressed for the square of the field value.

EX3DV4 - SN:3892

April 20, 2023

Parameters of Probe: EX3DV4 - SN:3892

Other Probe Parameters

Sensor Arrangement	Triangular
Connector Angle	29.4°
Mechanical Surface Detection Mode	enabled
Optical Surface Detection Mode	disabled
Probe Overall Length	337 mm
Probe Body Diameter	10 mm
Tip Length	9 mm
Tip Diameter	2.5 mm
Probe Tip to Sensor X Calibration Point	1 mm
Probe Tip to Sensor Y Calibration Point	1 mm
Probe Tip to Sensor Z Calibration Point	1 mm
Recommended Measurement Distance from Surface	1.4 mm

Note: Measurement distance from surface can be increased to 3–4 mm for an Area Scan job.

EX3DV4 - SN:3892

April 20, 2023

Parameters of Probe: EX3DV4 - SN:3892

Calibration Parameter Determined in Head Tissue Simulating Media

f (MHz) ^C	Relative Permittivity ^F	Conductivity ^F (S/m)	ConvF X	ConvF Y	ConvF Z	Alpha ^G	Depth ^G (mm)	Unc (k = 2)
450	43.5	0.87	10.79	10.79	10.79	0.16	1.30	±13.3%
600	42.7	0.88	10.21	10.21	10.21	0.10	1.25	±13.3%
750	41.9	0.89	9.64	9.72	9.33	0.37	1.27	±12.0%
900	41.5	0.97	9.30	9.64	8.99	0.35	1.27	±12.0%
1750	40.1	1.37	8.12	8.30	8.01	0.24	1.27	±12.0%
1900	40.0	1.40	7.94	8.14	7.80	0.28	1.27	±12.0%
2450	39.2	1.80	7.09	7.31	6.98	0.26	1.27	±12.0%
2600	39.0	1.96	7.18	7.37	7.04	0.26	1.27	±12.0%
4400	36.9	3.84	6.14	6.32	6.02	0.36	1.27	±14.0%
4800	36.4	4.25	5.96	6.13	5.83	0.36	1.27	±14.0%

^C Frequency validity above 300 MHz of ±100 MHz only applies for DASy v4.4 and higher (see Page 2), else it is restricted to ±50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band. Frequency validity below 300 MHz is ±10, 25, 40, 50 and 70 MHz for ConvF assessments at 30, 64, 128, 150 and 220 MHz respectively. Validity of ConvF assessed at 6 MHz is 4–9 MHz, and ConvF assessed at 13 MHz is 9–19 MHz. Above 5 GHz frequency validity can be extended to ±110 MHz.

^F The probes are calibrated using tissue simulating liquids (TSL) that deviate for ϵ and σ by less than ±5% from the target values (typically better than ±3%) and are valid for TSL with deviations of up to ±10%. If TSL with deviations from the target of less than ±5% are used, the calibration uncertainties are 11.1% for 0.7 - 3 GHz and 13.1% for 3 - 6 GHz.

^G Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ±1% for frequencies below 3 GHz and below ±2% for frequencies between 3–6 GHz at any distance larger than half the probe tip diameter from the boundary.

APPENDIX E: RELEVANT PAGES FROM DIPOLE CALIBRATION REPORTS

Calibration Laboratory of Schmid & Partner Engineering AG
Zeughausstrasse 43, 8004 Zurich, Switzerland

S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
S Servizio svizzero di taratura
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Client: **Verkotan** Certificate No: **D2450V2-729_Jul22**

CALIBRATION CERTIFICATE

Object: **D2450V2 - SN:729**

Calibration procedure(s): **QA CAL-05.v11
Calibration Procedure for SAR Validation Sources between 0.7-3 GHz**

Calibration date: **July 15, 2022**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (Si). The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date (Certificate No.)	Scheduled Calibration
Power meter NRP	SN: 104778	04-Apr-22 (No. 217-03525/03524)	Apr-23
Power sensor NRP-Z91	SN: 103244	04-Apr-22 (No. 217-03524)	Apr-23
Power sensor NRP-Z91	SN: 103245	04-Apr-22 (No. 217-03525)	Apr-23
Reference 20 dB Attenuator	SN: BH9394 (20k)	04-Apr-22 (No. 217-03527)	Apr-23
Type-N mismatch combination	SN: 310982 / 06327	04-Apr-22 (No. 217-03528)	Apr-23
Reference Probe EX3DV4	SN: 7349	31-Dec-21 (No. EX3-7349_Dec21)	Dec-22
DAE4	SN: 601	02-May-22 (No. DAE4-601_May22)	May-23

Secondary Standards	ID #	Check Date (in house)	Scheduled Check
Power meter E4419B	SN: GB39512475	30-Oct-14 (in house check Oct-20)	In house check: Oct-22
Power sensor HP 8481A	SN: US37292783	07-Oct-15 (in house check Oct-20)	In house check: Oct-22
Power sensor HP 8481A	SN: MY41093315	07-Oct-15 (in house check Oct-20)	In house check: Oct-22
RF generator R&S SMT-06	SN: 100972	15-Jun-15 (in house check Oct-20)	In house check: Oct-22
Network Analyzer Agilent E8358A	SN: US41080477	31-Mar-14 (in house check Oct-20)	In house check: Oct-22

Calibrated by: **Aldonis Georgiadou** Function: **Laboratory Technician** Signature: 

Approved by: **Niclas Kuster** Quality Manager

Issued: July 19, 2022

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

Certificate No: D2450V2-729_Jul22

Page 1 of 6

Measurement Conditions

DASY system configuration, as far as not given on page 1.

DASY Version	DASY52	V52.10.4
Extrapolation	Advanced Extrapolation	
Phantom	Modular Flat Phantom	
Distance Dipole Center - TSL	10 mm	with Spacer
Zoom Scan Resolution	dx, dy, dz = 5 mm	
Frequency	2450 MHz $\pm$ 1 MHz	

Head TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	39.2	1.80 mho/m
Measured Head TSL parameters	(22.0 $\pm$ 0.2) °C	37.9 $\pm$ 6 %	1.85 mho/m $\pm$ 6 %
Head TSL temperature change during test	< 0.5 °C		

SAR result with Head TSL

SAR averaged over 1 cm ³ (1 g) of Head TSL	Condition	
SAR measured	250 mW input power	13.4 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	52.3 W/kg $\pm$ 17.0 % (k=2)

SAR averaged over 10 cm ³ (10 g) of Head TSL	condition	
SAR measured	250 mW input power	6.21 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	24.5 W/kg $\pm$ 16.5 % (k=2)