

## FCC ID : 2BAPK-M18

### RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) Radiation as specified in §1.1307(b)

#### Limits for Maximum Permissible Exposure (MPE)

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density(mW/cm <sup>2</sup> )	Average Time
<b>(A) Limits for Occupational/Control Exposures</b>				
300-1500	--	--	F/300	6
1500-100000	--	--	5	6
<b>(B) Limits for General Population/Uncontrol Exposures</b>				
300-1500	--	--	F/1500	6
1500-100000	--	--	1	30

#### 11.1 Friis transmission formula: $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot R^2)$

Where

$P_d$ = Power density in mW/cm<sup>2</sup>

$P_{out}$ =output power to antenna in mW

$G$ = Numeric gain of the antenna relative to isotropic antenna

$\pi=3.1416$

$R$ = distance between observation point and center of the radiator in cm

$P_d$  the limit of MPE, 1mW/cm<sup>2</sup>,If we know the maximum gain of the nd total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

RF Exposure Information: The radiated output power of this device meets the limits of FCC/IC radio frequency exposure limits.This device should be operated with a minimum separation distance of 20cm (8 inches) between the equipment and a person's body.

## 11.2 Measurement Result

BT

Antenna gain: - 0.58 dBi

modulation	Channel Freq. (MHz)	Measured power (dBm)	Tune-up power (dBm)	Max tune-up power (dBm)	Antenna Gain Numeric	Evaluation result (mW/cm2 )	Power density Limits (mW/cm2 )
GFSK	2402	-15.79	±1	-14.79	0.87	0.000006	1
	2441	-16.12	±1	-15.12	0.87	0.000005	1
	2480	-16.76	±1	-15.76	0.87	0.000005	1
pi/4-DQPSK	2402	-14.23	±1	-13.23	0.87	0.000008	1
	2441	-14.72	±1	-13.72	0.87	0.000007	1
	2480	-15.32	±1	-14.32	0.87	0.000006	1
8DPSK	2402	-13.62	±1	-12.62	0.87	0.000010	1
	2441	-14.11	±1	-13.11	0.87	0.000009	1
	2480	-14.73	±1	-13.73	0.87	0.000007	1

Therefore the worst-case situation is 0.000010, which is less than "1",  
 This confirmed that the device comply with FCC 1.1310 MPE limit.

THE END