

# Standalone SAR test exclusion considerations

April 21, 2023

- Device category =  Portable device  Mobile device
- Transmitting mode =  Single Transmitting  Simultaneous Transmitting
- Max. transmitting frequency = 2480 MHz
- Min. test separation distance = 5 mm
- Max. Antenna Gain = -3.98
- Max. power with turn-up tolerance = -3.51 dBm = 0.5 mW ( Typical Power = Max. -3.51 dBm )

Note. Max. power with turn-up tolerance was used the highest value in low/mid/high channels.

## KDB 447498 D01 clause 4.3.1 Step 1) SAR test exclusion thresholds for 100MHz to 6GHz at test separation distances $\leq$ 50 mm

[ ( max. power of channel, including tune-up tolerance, mW ) / ( min. test separation distance, mm ) ]  $\cdot$  [  $\sqrt{f(\text{GHz})}$  ]  $\leq$  3.0 for 1g SAR and  $\leq$  7.5 for 10g extremity SAR

$$= [ ( 1\text{mW} / 5\text{mm} ) ] \times [ \sqrt{2.48\text{GHz}} ] = 0.3$$

Note. The calculation result was rounded to one decimal place for comparison.

→ SAR evaluation for general population exposure conditions by measurement or numerical simulation is not required.