

FCC RF Exposure

EUT Description: Laser engraving machine

ModelNo.:Z40,A40,S40,X40,A60,S60,X60,Z60,A80,S80,X80,Z80

FCC ID: 2BAQ2-Z40

Equipment type: mobile equipment

1. Limits

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

| Frequency range (MHz) | Electric field strength (V/m) | Magnetic field strength (A/m) | Power density (mW/cm ²) | Averaging time (minutes) |
|---|-------------------------------------|----------------------------------|--|-----------------------------|
| (A) Limits for Occupational/Controlled Exposures | | | | |
| 0.3–3.0 | 614 | 1.63 | *(100) | 6 |
| 3.0–30 | 1842/f | 4.89/f | *(900/f ²) | 6 |
| 30–300 | 61.4 | 0.163 | 1.0 | 6 |
| 300–1500 | | | f/300 | 6 |
| 1500–100,000 | | | 5 | 6 |
| (B) Limits for General Population/Uncontrolled Exposure | | | | |
| 0.3–1.34 | 614 | 1.63 | *(100) | 30 |
| 1.34–30 | 824/f | 2.19/f | *(180/f ²) | 30 |
| 30–300 | 27.5 | 0.073 | 0.2 | 30 |
| 300–1500 | | | f/1500 | 30 |
| 1500–100,000 | | | 1.0 | 30 |

F = frequency in MHz

Formula: $P_d = (P_{out} * G) / (4 * \pi * r^2)$

Where :

P_d = power density in mW/cm²,

P_{out} = output power to antenna in mW;

G = gain of antenna in linear scale,

$\pi = 3.14$;

R = distance between observation point and center of the radiator in cm

P_d is the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

2. Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

3. Test Result of RF Exposure Evaluation

| | Output power (dBm/ mW) | Antenna Gain(dBi) | Power Density at R=20cm (mW/cm ²) | Limit (mW/cm ²) | Result |
|----------------|---------------------------|----------------------|---|--------------------------------|--------|
| 802.11b | 8.26/6.6988 | 1.6 | 0.00193 | 1.0 | Pass |
| 802.11g | 7.48/5.5976 | 1.6 | 0.00161 | 1.0 | Pass |
| 802.11n(20MHz) | 6.92/4.9204 | 1.6 | 0.00142 | 1.0 | Pass |
| 802.11n(40MHz) | 6.59/4.5604 | 1.6 | 0.00131 | 1.0 | Pass |

| Turn-up power | |
|---------------|-----------------------|
| Mode | Peak power range(dBm) |
| WIFI | 6.00-9.00 |

| WIFI | Output power (dBm/ mW) | Antenna Gain(dBi) | Power Density at R=20cm (mW/cm ²) | Limit (mW/cm ²) | Result |
|------|---------------------------|----------------------|---|--------------------------------|--------|
| | 9.0/7.9433 | 1.6 | 0.00228 | 1.0 | Pass |