



**Solutions**

## **TEST REPORT**

**Report Number:** R14607588-E5

**Applicant :** AMANTYA TECHNOLOGIES PRIVATE LIMITED  
12TH FLOOR, TOWER B, UNITECH CYBER PARK, SECTOR 39  
GURUGRAM, INDIA 122003

**Model :** 5GTP202SSHCh256677

**FCC ID :** 2BASDAMTBN20233

**EUT Description :** Dual Cell High Capacity Sub6

**Test Standard(s) :** FCC CFR 47 Part 1 Subpart I, Part 2 Subpart J.

**Date Of Issue:**

2023-08-07

**Prepared by:**

UL LLC.

12 Laboratory Drive

Research Triangle Park, 27518, U.S.A.

TEL: (919) 549-1400



Revision History

Rev.	Issue Date	Revisions	Revised By
V1	2023-06-30	Initial Issue	Noah Bennett
V2	2023-08-02	TCB Feedback: -Added Sim Tx Tables -Clarified RF table results.	Noah Bennett
V3	2023-08-04	TCB Feedback: -Updated table 6.2 to be consistent with 6.1 and 6.3. -Added Tolerance value to all power measurements -Clarified naming convention of RF Cards.	Noah Bennett
V4	2023-08-07	Adjustment of power settings in table section 6.2	Noah Bennett

## TABLE OF CONTENTS

1. ATTESTATION OF TEST RESULTS .....	4
2. TEST METHODOLOGY .....	5
3. REFERENCES .....	5
4. FACILITIES AND ACCREDITATION .....	5
5. MAXIMUM PERMISSIBLE RF EXPOSURE .....	6
5.1. FCC RULES .....	6
5.2. EQUATIONS .....	7
6. RF EXPOSURE RESULTS .....	9
6.1. RF1 – N310: .....	9
6.2. RF2 – B210: .....	9
6.3. RF1 + RF2 Simultaneous: .....	9

## 1. ATTESTATION OF TEST RESULTS

**COMPANY NAME:** AMANTYA TECHNOLOGIES PRIVATE LIMITED  
12TH FLOOR, TOWER B,  
UNITECH CYBER PARK, SECTOR 39,  
GURUGRAM, INDIA 122003

**EUT DESCRIPTION:** Dual Cell High Capacity Sub6

**MODEL:** 5GTP202SSHCn256677

**SERIAL NUMBER:** 02SS-5GSS-0001

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
FCC PART 1 SUBPART I & PART 2 SUBPART J	Complies

UL LLC. tested the above equipment in accordance with the requirements set forth in the above standards. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical components. All samples tested were in good operating condition throughout the entire test program. Measurement Uncertainties are published for informational purposes only and were not taken into account unless noted otherwise.

This document may not be altered or revised in any way unless done so by UL LLC. and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL LLC. will constitute fraud and shall nullify the document.

Approved & Released For  
UL LLC. By:



---

Mike Antola  
Staff Engineer  
Consumer Technology Division  
UL LLC.

Prepared By:



---

Noah Bennett  
Engineer  
Consumer Technology Division  
UL LLC.

## 2. TEST METHODOLOGY

All calculations were made in accordance with FCC Parts 1.1310, 2.1091, 2.1093, KDB 447498 D01 v06.

## 3. REFERENCES

This report contains data provided by the customer which can impact the validity of results. UL LLC. is only responsible for the validity of results after the integration of the data provided by the customer. The following is information from the client:

1. Antenna gain data
2. Manufacturing Tolerance.

Output power was retrieved from UL Report R14607588-E1 for RF2 and R14607588-E3 for RF1.

## 4. FACILITIES AND ACCREDITATION

UL LLC is accredited by A2LA, certification # 0751.06, for all testing performed within the scope of this report. Testing was performed at the locations noted below.

	<b>Address</b>	<b>ISED CABID</b>	<b>ISED Company Number</b>	<b>FCC Registration</b>
<input checked="" type="checkbox"/>	Building: 2800 Perimeter Park Dr. Suite B Morrisville, NC 27560, U.S.A	US0067	2180C	825374

## 5. MAXIMUM PERMISSIBLE RF EXPOSURE

### 5.1. FCC RULES

§1.1310 The criteria listed in Table 1 shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in §1.1307(b), except in the case of portable devices which shall be evaluated according to the provisions of §2.1093 of this chapter.

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
<b>(A) Limits for Occupational/Controlled Exposure</b>				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f <sup>2</sup>	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
<b>(B) Limits for General Population/Uncontrolled Exposure</b>				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f <sup>2</sup>	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

f = frequency in MHz

\* = Plane-wave equivalent power density

#### Notes:

- (1) Occupational/controlled exposure limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when a person is transient through a location where occupational/controlled limits apply provided he or she is made aware of the potential for exposure.
- (2) General population/uncontrolled exposure limits apply in situations in which the general public may be exposed, or in which persons who are exposed as a consequence of their employment may not be fully aware of the potential for exposure or cannot exercise control over their exposure

## 5.2. EQUATIONS

### POWER DENSITY

Power density is given by:

$$S = EIRP / (4 * \pi * D^2)$$

Where

S = Power density in mW/cm<sup>2</sup>

EIRP = Equivalent Isotropic Radiated Power in mW

D = Separation distance in cm

Power density in units of mW/cm<sup>2</sup> is converted to units of W/m<sup>2</sup> by multiplying by 10.

### DISTANCE

Distance is given by:

$$D = \sqrt{EIRP / (4 * \pi * S)}$$

Where

D = Separation distance in cm

EIRP = Equivalent Isotropic Radiated Power in mW

S = Power density in mW/cm<sup>2</sup>

### SOURCE-BASED DUTY CYCLE

Where applicable (for example, multi-slot cell phone applications) a duty cycle factor may be applied.

$$\text{Source-based time-averaged EIRP} = (\text{DC} / 100) * \text{EIRP}$$

Where

DC = Duty Cycle in %, as applicable

EIRP = Equivalent Isotropic Radiated Power in mW

### **MIMO AND COLOCATED TRANSMITTERS (IDENTICAL LIMIT FOR ALL TRANSMITTERS)**

For multiple chain devices, and colocated transmitters operating simultaneously in frequency bands where the limit is identical, the total power density is calculated using the total EIRP obtained by summing the EIRP (in linear units) of each transmitter.

$$\text{Total EIRP} = (\text{EIRP1}) + (\text{EIRP2}) + \dots + (\text{EIRPn})$$

where

$\text{EIRPx}$  = Source-based time-averaged EIRP of chain x or transmitter x

The total EIRP is then used to calculate the Power Density or the Distance as applicable.

### **MIMO AND COLOCATED TRANSMITTERS (NON-IDENTICAL LIMIT FOR ALL TRANSMITTERS)**

For multiple colocated transmitters operating simultaneously in frequency bands where different limits apply:

The Power Density at the specified separation distance is calculated for each transmitter chain or transmitter.

The fraction of the exposure limit is calculated for each chain or transmitter as  
(Power Density of chain or transmitter) / (Limit applicable to that chain or transmitter).

The fractions are summed.

Compliance is established if the sum of the fractions is less than or equal to one.

## 6. RF EXPOSURE RESULTS

In the table(s) below, Power and Gain are entered in units of dBm and dBi respectively and conversions to linear forms are used for the calculations.

### 6.1. RF1 – N310:

Non-colocated transmitters										
Band	Mode	Separ. Distance (cm)	Output AVG Power (dBm)	Ant. Gain (dBi)	EIRP (dBm)	Duty Cycle (%)	EIRP (mW)	FCC PD (mW/cm^2)	FCC PD Limit (mW/cm^2)	
5G NR n2	16QAM	20.00	8.49	5.20	13.69	100.0	23.39	0.0047	1.0000	
5G NR n5	16QAM	20.00	-6.69	0.80	-5.89	100.0	0.26	0.0001	0.5793	
5G NR n66	QPSK	20.00	21.70	4.20	25.90	100.0	389.05	0.0774	1.0000	
5G NR n77	16QAM	20.00	15.72	3.92	19.64	100.0	92.04	0.0183	1.0000	

### 6.2. RF2 – B210:

Non-colocated transmitters										
Band	Mode	Separ. Distance (cm)	Output AVG Power (dBm)	Ant. Gain (dBi)	EIRP (dBm)	Duty Cycle (%)	EIRP (mW)	FCC PD (mW/cm^2)	FCC PD Limit (mW/cm^2)	
5G NR n2	16QAM	20.00	3.15	5.20	8.35	100.0	6.84	0.0014	1.0000	
5G NR n5	16QAM	20.00	-0.56	0.80	0.24	100.0	1.06	0.0002	0.5793	
5G NR n66	QPSK	20.00	9.40	4.20	13.60	100.0	22.91	0.0046	1.0000	

### 6.3. RF1 + RF2 Simultaneous:

#### n2 + n2

Multiple chain or colocated transmitters

Band	(MHz)	1900	1900
Mode		5G NR n2	5G NR n2
Transmitter		RF1	RF2
Separation Distance	(cm)	20	20
Output Power	(dBm)	8.49	3.15
Antenna Gain	(dBi)	5.20	5.20
Duty Cycle	(%)	100	100
Source Based EIRP	(mW)	23.39	6.84
FCC Power Density	(mW/cm^2)	0.004655	0.001361
FCC Power Density Limit	(mW/cm^2)	1.0	1.0
FCC Fraction of Limit	(%)	0.47%	0.14%
FCC Sum of Fractions (%)	0.60%		

#### n5 + n5

Multiple chain or colocated transmitters

Band	(GHz)	850MHz	850MHz
Mode		5G NR n5	5G NR n5
Transmitter		RF1	RF2
Separation Distance	(cm)	20	20
Output Power	(dBm)	-6.69	-0.56
Antenna Gain	(dBi)	0.80	0.80
Duty Cycle	(%)	100	100
Source Based EIRP	(mW)	0.26	1.06
FCC Power Density	(mW/cm^2)	0.000051	0.000210
FCC Power Density Limit	(mW/cm^2)	0.579333	0.579333
FCC Fraction of Limit	(%)	0.01%	0.04%
FCC Sum of Fractions (%)	0.05%		

**n66 + n66**

Multiple chain or colocated transmitters

Band	(GHz)	2100	2100
Mode		5G NR n66	5G NR n66
Transmitter		RF1	RF2
Separation Distance	(cm)	20	20
Output Power	(dBm)	21.76	9.40
Antenna Gain	(dBi)	4.20	4.20
Duty Cycle	(%)	100	100
Source Based EIRP	(mW)	394.46	22.91
<hr/>			
FCC Power Density	(mW/cm <sup>2</sup> )	0.078515	0.004560
FCC Power Density Limit	(mW/cm <sup>2</sup> )	1	1
FCC Fraction of Limit	(%)	7.85%	0.46%
FCC Sum of Fractions (%)	8.31%		

**n77 + n5**

Multiple chain or colocated transmitters

Band	(GHz)	850MHz	2100
Mode		5G NR n5	5G NR n66
Transmitter		RF1	RF2
Separation Distance	(cm)	20	20
Output Power	(dBm)	15.72	9.40
Antenna Gain	(dBi)	3.92	4.20
Duty Cycle	(%)	100	100
Source Based EIRP	(mW)	92.04	22.91
<hr/>			
FCC Power Density	(mW/cm <sup>2</sup> )	0.018321	0.004560
FCC Power Density Limit	(mW/cm <sup>2</sup> )	1	1
FCC Fraction of Limit	(%)	1.83%	0.46%
FCC Sum of Fractions (%)	2.29%		

**Notes:**

- 1) The EUT has 2 SDRs, the N310, RF1, and the B210, RF2. RF1 supports n2, n5, n66, and n77 as 4x4 MIMO. RF2 supports n2, n5, n66 as 2x2 MIMO Only.
- 2) In this report, the N310 may also be called RF1, and the B210 may also be called RF2
- 3) The EUT can Simultaneously transmit on the same band, and channel on both RF1 and RF2. Therefore, worst case exposure is reported as if the EUT was transmitting at the highest power mode on each SDR. Since RF2 does not support n77, the band that results in the worst-case exposure was used.
- 4) The manufacturer configures output power so that the maximum power, after accounting for manufacturing tolerances, will never exceed the maximum power level measured. The above is the maximum output power measured +2dBm manufacturer declared tolerance.
- 5) The output power in the tables above is the maximum total power (chain 0 + chain 1 + chain 2 + chain 3) among various channels and various modes within the specific band.
- 6) The antenna gain in the tables above is the maximum antenna gain among various channels within the specified band.
- 7) 100% Duty Cycle was used as worst case.
- 8) For MPE, KDB 447498 requires the calculations to use the maximum rated power; that power should be declared by the manufacturer and should not be lower than the measured power. If the power has a tolerance, then we also need to check that the measured power is within the tolerance.

**END OF REPORT**