



RF Exposure Evaluation

For

WYBOTICS CO., LTD.

ROBOTIC POOL CLEANER

Test Model: WYB0T M2

Additional Model No.: WY320

Prepared for : WYBOTICS CO., LTD.
Address : No.30, 4th Street Zhongnan, West Zone, TEDA, Tianjin, China

Prepared by : Shenzhen LCS Compliance Testing Laboratory Ltd.
Address : 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel : (+86)755-82591330
Fax : (+86)755-82591332
Web : www.LCS-cert.com
Mail : webmaster@LCS-cert.com

Date of receipt of test sample : April 10, 2025
Number of tested samples : 2
Sample No. : A240513088-1, A240513088-2
Serial number : Prototype
Date of Test : April 10, 2025 ~ May 08, 2025
Date of Report : May 09, 2025



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: (+86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



RF Exposure Evaluation	
Report Reference No.	LCSA05244175ED
Date of Issue	May 09, 2025
Testing Laboratory Name	Shenzhen LCS Compliance Testing Laboratory Ltd.
Address	101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China
Testing Location/ Procedure	Full application of Harmonised standards ☒ Partial application of Harmonised standards ☐ Other standard testing method ☐
Applicant's Name	WYBOTICS CO., LTD.
Address	No.30, 4th Street Zhongnan, West Zone, TEDA, Tianjin, China
Test Specification	
Standard	FCC KDB publication 447498 D01 General RF Exposure Guidance v06 FCC CFR 47 part1 1.1310 FCC CFR 47 part2 2.1091
Test Report Form No.	TRF-4-E-215 A/0
TRF Originator	Shenzhen LCS Compliance Testing Laboratory Ltd.
Master TRF	Dated 2011-03
Shenzhen LCS Compliance Testing Laboratory Ltd. All rights reserved. This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen LCS Compliance Testing Laboratory Ltd. is acknowledged as copyright owner and source of the material. Shenzhen LCS Compliance Testing Laboratory Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.	
Test Item Description : ROBOTIC POOL CLEANER	
Trade Mark	N/A
Test Model	WYB0T M2
Ratings	For AC Adapter Input: 100-240V~, 50/60Hz, 2.5A Adapter Output: 29.4V—4.0A, 117.6W Battery capacity: 25.2V, 10000mAh
Result	PASS

Compiled by:

Ling Zhu/ Administrator

Supervised by:

Jack Liu / Technique principal

Approved by:

Gavin Liang/ Manager



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



RF Exposure Evaluation

Test Report No. : LCSA05244175ED	<u>May 09, 2025</u> Date of issue
---	--------------------------------------

EUT.....	: ROBOTIC POOL CLEANER
Test Model.....	: WYB0T M2
Applicant.....	: WYBOTICS CO., LTD.
Address.....	: No.30, 4th Street Zhongnan, West Zone, TEDA, Tianjin, China
Telephone.....	: /
Fax.....	: /
Manufacturer.....	: WYBOTICS CO., LTD.
Address.....	: No.30, 4th Street Zhongnan, West Zone, TEDA, Tianjin, China
Telephone.....	: /
Fax.....	: /
Factory.....	: WYBOTICS CO., LTD.
Address.....	: No.30, 4th Street Zhongnan, West Zone, TEDA, Tianjin, China
Telephone.....	: /
Fax.....	: /

Test Result	PASS
--------------------	-------------

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.





Revision History

Report Version	Issue Date	Revision Content	Revised By
000	May 09, 2025	Initial Issue	---





TABLE OF CONTENTS

Description	Page
1. Product Information	6
2. Evaluation Method	7
3. Limit	7
4. MPE Calculation Method	8
5. Antenna Information	8
6. Conducted Power	9
7. Manufacturing Tolerance	11
8. Measurement Results	12
9. Conclusion	14
10. Description of Test Facility	14
11. Measurement Uncertainty	14





1. Product Information

EUT	: ROBOTIC POOL CLEANER
Test Model	: WYB0T M2
Additional Model No.	: WY320
Model Declaration	: PCB board, structure and internal of these model(s) are the same, So no additional models were tested
Ratings	: For AC Adapter Input: 100-240V~, 50/60Hz, 2.5A Adapter Output: 29.4V—4.0A, 117.6W Battery capacity: 25.2V, 10000mAh
Hardware Version	: /
Software Version	: /
Bluetooth	:
Frequency Range	: 2402MHz~2480MHz
Channel Number	: 79 channels for Bluetooth V5.0 (DSS) 40 channels for Bluetooth V5.0 (DTS)
Channel Spacing	: 1MHz for Bluetooth V5.0 (DSS) 2MHz for Bluetooth V5.0 (DTS)
Modulation Type	: GFSK, $\pi/4$ -DQPSK, 8-DPSK for Bluetooth V5.0 (DSS) GFSK for Bluetooth V5.0 (DTS)
Bluetooth Version	: V5.0
Antenna Description	: PCB Antenna, 4.16dBi(Max.)
WIFI(2.4G Band)	:
Frequency Range	: 2412MHz~2462MHz
Channel Spacing	: 5MHz
Channel Number	: 11 Channels for 20MHz bandwidth (2412~2462MHz) 7 Channels for 40MHz bandwidth (2422~2452MHz)
Modulation Type	: IEEE 802.11b: DSSS (CCK, DQPSK, DBPSK) IEEE 802.11g: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n: OFDM (64QAM, 16QAM, QPSK, BPSK)
Antenna Description	: Ant0: PCB Antenna, 4.16dBi(Max.) Ant1: External Antenna, 4.30dBi(Max.)
Exposure category	: General population/uncontrolled environment
EUT Type	: Production Unit
Device Type	: Mobile Device

Note: For a more detailed antenna description, please refer to the antenna specifications or the antenna report provided by the customer.





2. Evaluation Method

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

In accordance with KDB447498D01 for Simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneous transmitting antennas incorporated in a host device, based on the calculated/estimated, numerically modelled or measured field strengths or power density, is ≤ 1.0 . The MPE ratio of each antenna is determined at the minimum test separation distance required by the operating configurations and exposure conditions of the host device, according to the ratio of field strengths or power density to MPE limit, at the test frequency. Either the maximum peak or spatially averaged results from measurements or numerical simulations may be used to determine the MPE ratios. Spatial averaging does not apply when MPE is estimated using simple calculations based on far-field plane-wave equivalent conditions. The antenna installation and operating requirements for the host device must meet the minimum test separation distances required by all antennas, in both standalone and simultaneous transmission operations, to satisfy compliance.

3. Limit

3.1 Refer Evaluation Method

[ANSI C95.1-2019](#): IEEE Standard for Safety Levels with Respect to Human Exposure to Electric, Magnetic, and Electromagnetic Fields, 0 Hz to 300 GHz

[FCC KDB publication 447498 D01 General 1 RF Exposure Guidance v06](#): Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies.

[FCC CFR 47 part1 1.1310](#): Radiofrequency radiation exposure limits.

[FCC CFR 47 part2 2.1091](#): Radiofrequency radiation exposure evaluation: mobile devices.

3.2 Limit

Limits for Maximum Permissible Exposure (MPE)/Controlled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	6
3.0 – 30	1842/f	4.89/f	(900/f ²)*	6
30 – 300	61.4	0.163	1.0	6
300 – 1500	/	/	f/300	6
1500 – 100,000	/	/	5	6

Limits for Maximum Permissible Exposure (MPE)/Uncontrolled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Uncontrolled Exposure				
0.3 – 3.0	614	1.63	(100) *	30
3.0 – 30	824/f	2.19/f	(180/f ²)*	30
30 – 300	27.5	0.073	0.2	30
300 – 1500	/	/	f/1500	30
1500 – 100,000	/	/	1.0	30

F=frequency in MHz

*=Plane-wave equivalent power density





4. MPE Calculation Method

Predication of MPE limit at a given distance
Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = \frac{PG}{4\pi R^2}$$

Where: S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna

5. Antenna Information

EUT can only use antennas certificated as follows provided by manufacturer;

Internal/ External Identification	Antenna type and antenna number	Operate frequency band	Maximum antenna gain	Notes
Internal	PCB antenna	2400MHz ~ 2500MHz	Bluetooth: 4.16dBi 2.4GWIFI: 4.16dBi	BT/WIFI Antenna
External	External antenna	2400MHz ~ 2500MHz	2.4GWIFI: 4.30dBi	WIFI Antenna



**6. Conducted Power**

[BT]

Mode	Channel	Frequency (MHz)	Peak Conducted Output Power (dBm)
GFSK	0	2402	-0.02
	39	2441	0.49
	78	2480	0.01
$\pi/4$ DQPSK	0	2402	0.48
	39	2441	0.64
	78	2480	-0.37
8DPSK	0	2402	-0.8
	19	2441	0.91
	39	2480	-0.14

[BT LE]

Mode	Channel	Frequency (MHz)	Peak Conducted Output Power (dBm)
GFSK	0	2402	-0.6
	19	2440	-0.24
	39	2480	0.19

[2.4G WIFI Ant0]

Mode	Channel	Frequency (MHz)	Peak Conducted Output Power (dBm)
11B	1	2412	15.76
	6	2437	15.66
	11	2462	15.18
11G	1	2412	14.92
	6	2437	14.94
	11	2462	14.84
11N20 SISO	1	2412	13.67
	6	2437	13
	11	2462	13.11
11N40 SISO	3	2422	12.72
	6	2437	12.07
	9	2452	12.1





[2.4G WIFI Ant1]

Mode	Channel	Frequency (MHz)	Peak Conducted Output Power (dBm)
11B	1	2412	15.41
	6	2437	14.79
	11	2462	14.61
11G	1	2412	14.73
	6	2437	14
	11	2462	13.9
11N20 SISO	1	2412	14.15
	6	2437	13.46
	11	2462	13.4
11N40 SISO	3	2422	13.75
	6	2437	13.64
	9	2452	13.51





7. Manufacturing Tolerance

[BT]

GFSK (Peak)			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	0	0	-1.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
$\pi/4$ -DQPSK (Peak)			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	0	0	0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
8DPSK (Peak)			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	0	0	0
Tolerance $\pm$ (dB)	1.0	1.0	1.0

[BT LE]

BT LE (Peak)			
Channel	Channel 0	Channel 19	Channel 39
Target (dBm)	0	0	0
Tolerance $\pm$ (dB)	1.0	1.0	1.0

[2.4G WIFI Ant0]

11B (Peak)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	15.0	15.0	15.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11G (Peak)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	14.0	14.0	14.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N20 (Peak)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	13.0	13.0	13.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N40 (Peak)			
Channel	Channel 3	Channel 6	Channel 9
Target (dBm)	12.0	12.0	12.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0





[2.4G WIFI Ant1]

11B (Peak)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	15.0	14.0	14.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11G (Peak)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	14.0	14.0	13.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N20 (Peak)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	14.0	13.0	13.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N40 (Peak)			
Channel	Channel 3	Channel 6	Channel 9
Target (dBm)	13.0	13.0	13.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0





8. Measurement Results

8.1 Standalone MPE Evaluation

As declared by the Applicant, the EUT is a wireless device used in a fix application, at least 20 cm from any body part of the user or nearby persons; from the maximum EUT RF output power, the minimum separation distance, $r=20\text{cm}$, as well as the gain of the used antenna refer to antenna information, the RF power density can be obtained.

[BT]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)	MPE ratios1
	dBm	mW					
GFSK	1.0	1.2589	4.16	2.6062	0.0007	1.0000	0.0007
$\pi/4$ -DQPSK	1.0	1.2589	4.16	2.6062	0.0007	1.0000	0.0007
8-DPSK	1.0	1.2589	4.16	2.6062	0.0007	1.0000	0.0007

[BT LE]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)	MPE ratios1
	dBm	mW					
GFSK	1.0	1.2589	4.16	2.6062	0.0007	1.0000	0.0007

[2.4G WIFI Ant0]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)	MPE ratios1
	dBm	mW					
IEEE 802.11b	16.0	39.8107	4.16	2.6062	0.0207	1.0000	0.0207
IEEE 802.11g	15.0	31.6228	4.16	2.6062	0.0164	1.0000	0.0164
IEEE 802.11n HT20	14.0	25.1189	4.16	2.6062	0.0130	1.0000	0.0130
IEEE 802.11n HT40	13.0	19.9526	4.16	2.6062	0.0104	1.0000	0.0104

[2.4G WIFI Ant1]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)	MPE ratios2
	dBm	mW					
IEEE 802.11b	16.0	39.8107	4.30	2.6915	0.0213	1.0000	0.0079
IEEE 802.11g	15.0	31.6228	4.30	2.6915	0.0169	1.0000	0.0063
IEEE 802.11n HT20	15.0	31.6228	4.30	2.6915	0.0169	1.0000	0.0063
IEEE 802.11n HT40	14.0	25.1189	4.30	2.6915	0.0135	1.0000	0.0050

Remark:

1. Output power including tune-up tolerance;
2. Output power was adjusted to duty cycle at 100% if measured duty cycle less than 98%;
3. MPE evaluate distance is 20cm from user manual provide by manufacturer.





8.2 Simultaneous Transmission MPE Evaluation

The sample support one Bluetooth/2.4G WIFI antenna, another one 2.4G WIFI antenna antenna, so need consider simultaneous transmission;

Simultaneous transmission MPE

According to KDB447498 for Transmitters used in mobile exposure conditions for simultaneous transmission operations;

$$TER = \sum_{k=1}^{N_s} \left(\frac{SAR_k}{SAR_{lim}} \right) + \sum_{k=1}^{N_f} \left(\frac{MPE_{field, k}}{MPE_{field, lim}} \right)^2 + \sum_{k=1}^{N_{PD}} \left(\frac{MPE_{PD, k}}{MPE_{PD, lim}} \right)$$

$\sum$ of MPE ratios ≤ 1.0

Mode	$\sum$ MPE ratios	Limit	Results
MPE ratios1+ MPE ratios2	0.0420=0.0207+0.0213	1.000	Pass

9. Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.

10. Description of Test Facility

NVLAP Accreditation Code is 600167-0.

FCC Designation Number is CN5024.

CAB identifier is CN0071.

CNAS Registration Number is L4595.

Test Firm Registration Number: 254912.

11. Measurement Uncertainty

BT/BLE/2.4GWIFI:

Test Item	Frequency Range	Uncertainty	Note
Output power	1GHz-40GHz	± 0.57 dB	(1)

(1). This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

-----THE END OF REPORT-----

