



深圳自由行通信技术有限公司

Shenzhen Free Walk Communication Technology Co. LTD

ADD: 深圳市宝安西乡鹤洲西区工业园 2 栋 3 楼

3rd Floor, Building 2, Industrial Park, Hezhou West District, Bao'an West Township,
Shenzhen

Email: zyx_sz@yeah.net

TEL: 86-0755-29955983

FAX: 86-0755-29955983

产品 (**Product**) : 2.4G antenna (L=215mm)


型号 (**Model**) : D50 home

料号 (**Part Number**) : Z02-10359-R01

The basic parameters

A. Electrical Characteristics	
Frequency	2400 MHz ~2500MHz
VSWR	≤ 2
Efficiency	>60%
Impedance	50 Ohm
Polarization	Linear
Gain	4.16dBi
B. Material & Mechanical Characteristics	
Material of Radiator	
Cable Type	2.4G Φ 1.13mm Gray
Connector Type	IPEX
Dimension	
C. Environmental	
Operation Temperature	- 20 °C ~ + 60 °C
Storage Temperature	- 40 °C ~ + 80 °C

Product Drawing:



Test Equipment & Conditions


1. Network Analyzers :

Agilent 8753D 5071C


2. Communications Test Set:

Agilent 8960 CMW500

3. 3D Chamber Test System




(Testing by 3D anechoic chamber)




(2.4G)

SWR



Smith





效率&增益: Efficiency&Gain


Freq (MHz)	Effi (%)	Gain(dBi)
2400	63.61	3.46
2410	60.72	3.24
2420	61.21	3.22
2430	61.75	3.63
2440	65.53	5.00
2450	65.12	3.92
2460	63.48	3.95
2470	69.27	4.10
2480	69.14	4.34
2490	66.38	4.30
2500	62.15	3.99

方向图


Patten

3D

2400MHz



2450MHz



2500MHz

