



TEST REPORT

Applicant Name : Xunison Inc
Address : 11720 Amber Park Dr.Suite 160 Atlanta, GA 30009 United State
Report Number : RA230206-05020E-RF-00
FCC ID: 2BAT3D60

Test Standard (s)

FCC PART 15.407

Samp Sample Description

Product Type: Xunison Hub
Model No.: D60 5G
Multiple Model(s) No.: N/A
Trade Mark: XUNISON
Date Received: 2023/02/06
Report Date: 2023/06/12

Test Result:	Pass*
--------------	-------

* In the configuration tested, the EUT complied with the standards above.

Prepared and Checked By:

Andy Yu

Andy Yu
EMC Engineer

Approved By:

Candy Li

Candy Li
EMC Engineer

Note: This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk "★".

Shenzhen Accurate Technology Co., Ltd. is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with an asterisk "*". Customer model name, addresses, names, trademarks etc. are not considered data.

This report cannot be reproduced except in full, without prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

Shenzhen Accurate Technology Co., Ltd.

1/F., Building A, Changyuan New Material Port, Science & Industry Park, Nanshan District, Shenzhen, Guangdong, P.R. China

Tel: +86 755-26503290 Fax: +86 755-26503290 Web: www.atc-lab.com

TABLE OF CONTENTS

DOCUMENT REVISION HISTORY	4
GENERAL INFORMATION.....	5
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	5
OBJECTIVE	5
TEST METHODOLOGY	5
TEST FACILITY	6
SYSTEM TEST CONFIGURATION.....	7
DESCRIPTION OF TEST CONFIGURATION	7
EUT EXERCISE SOFTWARE	7
EQUIPMENT MODIFICATIONS	7
SUPPORT EQUIPMENT LIST AND DETAILS	7
EXTERNAL I/O CABLE.....	7
SUMMARY OF TEST RESULTS.....	8
TEST EQUIPMENT LIST	9
APPLICABLE STANDARDS.....	10
DFS REQUIREMENT	10
DFS MEASUREMENT SYSTEM.....	14
SYSTEM BLOCK DIAGRAM	14
CONDUCTED METHOD	15
RADIATED METHOD.....	16
TEST PROCEDURE	16
TEST RESULTS.....	17
DESCRIPTION OF EUT	17
RADAR WAVEFORM CALIBRATION	17
TEST DATA	17
CHANNEL AVAILABILITY CHECK TIME(CAC)	18
TEST PROCEDURE	18
TEST DATA	18
CHANNEL MOVE TIME AND CHANNEL CLOSING TRANSMISSION TIME	19
TEST PROCEDURE	19
TEST DATA	19
NON-OCCUPANCY PERIOD.....	20
TEST PROCEDURE	20
TEST DATA	20
DETECTION BANDWIDTH.....	21
TEST PROCEDURE	21
TEST DATA	21
STATISTICAL PERFORMANCE CHECK	22
TEST PROCEDURE	22
TEST DATA	22

BRIDGE AND/OR MESH MODE	23
TEST PROCEDURE	23
TEST DATA	23
APPENDIX	24
APPENDIX A:DFS DETECTION THRESHOLDS	24
APPENDIX B: CHANNEL LOADING.....	39
APPENDIX C: CHANNEL AVAILABILITY CHECK TIME	41
APPENDIX D:CHANNEL MOVE TIME AND CHANNEL CLOSING TRANSMISSION TIME	44
APPENDIX E:NON-OCCUPANCY PERIOD	45
APPENDIX F: U-NII DETECTION BANDWIDTH.....	46
APPENDIX G:STATISTICAL PERFORMANCE CHECK.....	48

DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
0	RA230206-05020E-RF-00	Original Report	2023/05/12
1	RA230206-05020E-RF-00	Update the report format	2023/05/25
2	RA230206-05020E-RF-00	Update Detection Bandwidth to 160MHz in page 46 (Typo)	2023/06/12

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Frequency Range	5GHz Wi-Fi: 5250-5350 MHz; 5470-5725MHz
Mode	802.11a/n20/n40/ac20/ac40/ac80/ax20 /ax 40/ ax 80
Maximum Conducted Average Output Power	5250-5350MHz: 19.82dBm 5470-5725MHz: 21.79dBm
Maximum EIRP	5250-5350MHz: 25.35dBm 5470-5725MHz: 28.53dBm
Modulation Technique	OFDM, OFDMA
Voltage Range	DC 12V from adapter
Sample serial number	2OKI (Assigned by ATC)
Sample/EUT Status	Good condition
Adapter 1 Information	Model: RD1202000-C55-154MG Input: AC 100-240V, 50/60Hz, 1.0A MAX Output: DC 12.0V, 2.0A
Adapter 2 Information	Model: AS2406A-1202000US Input: AC 100-240V, 50/60Hz, 0.8A MAX Output: DC 12.0V, 2000mA
Adapter 3 Information	Model: AS2406A-1202000DM Input: AC 100-240V, 50/60Hz, 0.8A MAX Output: DC 12.0V, 2.0A, 24.0W

Objective

This test report is in accordance with Part 2-Subpart J, Part 15-Subparts E of the Federal Communications Commission's rules.

The objective is to determine compliance with FCC Part 15, Subpart E, section 15.407 Dynamic Frequency Selection (DFS) for devices operating in the bands 5250-5350 MHz, 5470-5725 MHz.

Test Methodology

FCC KDB 905462 D02 UNII DFS Compliance Procedures New Rules v02.

Each test item follows test standards and with no deviation.

Test Facility

The test site used by Shenzhen Accurate Technology Co., Ltd. to collect test data is located on the Floor 1, KuMaKe Building, Dongzhou Community, Guangming Street, Guangming District, Shenzhen, Guangdong, China.

The test site has been approved by the FCC under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No.: 30241, the FCC Designation No.: CN1189. Accredited by American Association for Laboratory Accreditation (A2LA) The Certificate Number is 4297.01.

The lab has been recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements, the CAB identifier: CN0016. The Registration Number is 30241.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The EUT was configured for testing in an engineering mode which was provided by the manufacturer.

EUT Exercise Software

N/A

Equipment Modifications

N/A

Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
DELL	PC	Vostro 3690	E569659A9981
DELL	LED display	E2423H	CN-OPTM1T
DELL	Keyboard	KB1421	E134780
DELL	Mouse	WM-100	/
Winner	WiFi dongle	EZC-5201BS	/
DELL	Notebook	Latitude E6410	11429208685

External I/O Cable

Cable Description	Length (m)	From Port	To
Un-Shielding Detachable RJ45 Cable	1.5	EUT	PC
Shielding Detachable RF Cable	0.4	EUT	Open Switch and Control Unit

SUMMARY OF TEST RESULTS

The following result table represents the list of measurements required under the CFR §47 Part 15.407(h), and KDB: 905462 D02 UNII DFS Compliance Procedures New Rules v02

Items	Description of Test	Result
Detection Bandwidth	UNII Detection Bandwidth	Compliant
Performance Requirements Check	Initial Channel Availability Check Time (CAC)	Compliant
	Radar Burst at the Beginning of the CAC	Compliant
	Radar Burst at the End of the CAC	Compliant
In-Service Monitoring	Channel Move Time	Compliant
	Channel Closing Transmission Time	Compliant
	Non-Occupancy Period	Compliant
Radar Detection	Statistical Performance Check	Compliant

Note: This device does not support “802.11ax Channel Puncturing” function.

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Open Switch and Control Unit	OSP120 + OSP-B157	101244 + 100866	2022/11/25	2023/11/24
Rohde & Schwarz	Signal and Spectrum Analyzer	FSV40	101473	2023/02/08	2024/02/07
AGILENT	Vector Signal Generator	N5182B	MY53052129	2022/11/25	2023/11/24

*** Statement of Traceability:** Shenzhen Accurate Technology Co., Ltd. attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

APPLICABLE STANDARDS

DFS Requirement

CFR §47 Part 15.407(h)

FCC KDB 905462 D02 UNII DFS Compliance Procedures New Rules v02

Table 1: Applicability of DFS Requirements Prior to Use of a Channel

Requirement	Operational Mode		
	Master	Client Without Radar Detection	Client With Radar Detection
<i>Non-Occupancy Period</i>	Yes	Not required	Yes
<i>DFS Detection Threshold</i>	Yes	Not required	Yes
<i>Channel Availability Check Time</i>	Yes	Not required	Not required
<i>U-NII Detection Bandwidth</i>	Yes	Not required	Yes

Table 2: Applicability of DFS requirements during normal operation

Requirement	Operational Mode	
	Master Device or Client with Radar Detection	Client Without Radar Detection
<i>DFS Detection Threshold</i>	Yes	Not required
<i>Channel Closing Transmission Time</i>	Yes	Yes
<i>Channel Move Time</i>	Yes	Yes
<i>U-NII Detection Bandwidth</i>	Yes	Not required

Additional requirements for devices with multiple bandwidth modes	Master Device or Client with Radar Detection	Client Without Radar Detection
<i>U-NII Detection Bandwidth and Statistical Performance Check</i>	All BW modes must be tested	Not required
<i>Channel Move Time and Channel Closing Transmission Time</i>	Test using widest BW mode available	Test using the widest BW mode available for the link
<i>All other tests</i>	Any single BW mode	Not required
Note: Frequencies selected for statistical performance check (Section 7.8.4) should include several frequencies within the radar detection bandwidth and frequencies near the edge of the radar detection bandwidth. For 802.11 devices it is suggested to select frequencies in each of the bonded 20 MHz channels and the channel center frequency.		

Table 3: DFS Detection Thresholds for Master Devices and Client Devices With Radar Detection

Maximum Transmit Power	Value (See Notes 1, 2, and 3)
EIRP $\geq$ 200 milliwatt	-64 dBm
EIRP < 200 milliwatt and power spectral density < 10 dBm/MHz	-62 dBm
EIRP < 200 milliwatt that do not meet the power spectral density requirement	-64 dBm
Note 1: This is the level at the input of the receiver assuming a 0 dBi receive antenna. Note 2: Throughout these test procedures an additional 1 dB has been added to the amplitude of the test transmission waveforms to account for variations in measurement equipment. This will ensure that the test signal is at or above the detection threshold level to trigger a DFS response. Note3: EIRP is based on the highest antenna gain. For MIMO devices refer to KDB Publication 662911 D01.	

Table 4: DFS Response Requirement Values

Parameter	Value
<i>Non-occupancy period</i>	Minimum 30 minutes
<i>Channel Availability Check Time</i>	60 seconds
<i>Channel Move Time</i>	10 seconds See Note 1.
<i>Channel Closing Transmission Time</i>	200 milliseconds + an aggregate of 60 milliseconds over remaining 10 second period. See Notes 1 and 2.
<i>U-NII Detection Bandwidth</i>	Minimum 100% of the U-NII 99% transmission power bandwidth. See Note 3.
Note 1: <i>Channel Move Time</i> and the <i>Channel Closing Transmission Time</i> should be performed with Radar Type 0. The measurement timing begins at the end of the Radar Type 0 burst. Note 2: The <i>Channel Closing Transmission Time</i> is comprised of 200 milliseconds starting at the beginning of the <i>Channel Move Time</i> plus any additional intermittent control signals required to facilitate a <i>Channel move</i> (an aggregate of 60 milliseconds) during the remainder of the 10 second period. The aggregate duration of control signals will not count quiet periods in between transmissions. Note 3: During the <i>U-NII Detection Bandwidth</i> detection test, radar type 0 should be used. For each frequency step the minimum percentage of detection is 90 percent. Measurements are performed with no data traffic.	

Table 5 – Short Pulse Radar Test Waveforms

Radar Type	Pulse Width (μsec)	PRI (μsec)	Number of Pulses	Minimum Percentage of Successful Detection	Minimum Number of Trials
0	1	1428	18	See Note 1	See Note 1
1	1	Test A: 15 unique PRI values randomly selected from the list of 23 PRI values in Table 5a	Roundup $\left\{ \left(\frac{1}{360} \right) \cdot \left(\frac{19 \cdot 10^6}{\text{PRI}_{\mu\text{sec}}} \right) \right\}$	60%	30
		Test B: 15 unique PRI values randomly selected within the range of 518-3066 μsec, with a minimum increment of 1 μsec, excluding PRI values selected in Test A			
2	1-5	150-230	23-29	60%	30
3	6-10	200-500	16-18	60%	30
4	11-20	200-500	12-16	60%	30
Aggregate (Radar Types 1-4)				80%	120
Note 1: Short Pulse Radar Type 0 should be used for the detection bandwidth test, channel move time, and channel closing time tests.					

A minimum of 30 unique waveforms are required for each of the Short Pulse Radar Types 2 through 4. If more than 30 waveforms are used for Short Pulse Radar Types 2 through 4, then each additional waveform must also be unique and not repeated from the previous waveforms. If more than 30 waveforms are used for Short Pulse Radar Type 1, then each additional waveform is generated with Test B and must also be unique and not repeated from the previous waveforms in Tests A or B.

For example if in Short Pulse Radar Type 1 Test B a PRI of 3066 usec is selected, the number of pulses

would be $\text{Roundup} \left\{ \left(\frac{1}{360} \right) \cdot \left(\frac{19 \cdot 10^6}{3066} \right) \right\} = \text{Roundup} \{17.2\} = 18$.

Table 5a - Pulse Repetition Intervals Values for Test A

Pulse Repetition Frequency Number	Pulse Repetition Frequency (Pulses Per Second)	Pulse Repetition Interval (Microseconds)
1	1930.5	518
2	1858.7	538
3	1792.1	558
4	1730.1	578
5	1672.2	598
6	1618.1	618
7	1567.4	638
8	1519.8	658
9	1474.9	678
10	1432.7	698
11	1392.8	718
12	1355	738
13	1319.3	758
14	1285.3	778
15	1253.1	798
16	1222.5	818
17	1193.3	838
18	1165.6	858
19	1139	878
20	1113.6	898
21	1089.3	918
22	1066.1	938
23	326.2	3066

The aggregate is the average of the percentage of successful detections of Short Pulse Radar Types 1-4. For example, the following table indicates how to compute the aggregate of percentage of successful detections.

Radar Type	Number of Trials	Number of Successful Detections	Minimum Percentage of Successful Detection
1	35	29	82.9%
2	30	18	60%
3	30	27	90%
4	50	44	88%
Aggregate $(82.9\% + 60\% + 90\% + 88\%)/4 = 80.2\%$			

Table 6 – Long Pulse Radar Test Waveform

Radar Type	Pulse Width (μsec)	Chirp Width (MHz)	PRI (μsec)	Number of Pulses per <i>Burst</i>	Number of <i>Bursts</i>	Minimum Percentage of Successful Detection	Minimum Number of Trials
5	50-100	5-20	1000-2000	1-3	8-20	80%	30


Table 7 – Frequency Hopping Radar Test Waveform



Radar Type	Pulse Width (μsec)	PRI (μsec)	Pulses per Hop	Hopping Rate (kHz)	Hopping Sequence Length (msec)	Minimum Percentage of Successful Detection	Minimum Number of Trials
6	1	333	9	0.333	300	70%	30


DFS Measurement System

DFS measurement system consists of two subsystems: (1) The radar signal generating subsystem and (2) the traffic monitoring subsystem.

System Block Diagram




Conducted Method**Setup for Master with injection at the Master****Setup for Client with injection at the Master**



Setup for Client with injection at the Client

Radiated Method



Test Procedure


A spectrum analyzer is used as a monitor verifies that the EUT status including Channel Closing Transmission Time and Channel Move Time, and does not transmit on a Channel during the Non-Occupancy Period after the diction and Channel move. It is also used to monitor EUT transmissions during the Channel Availability Check Time.

TEST RESULTS

Description of EUT

The maximum EIRP is more than 200mW. The calibrated radiated DFS detection threshold level is set to -64 dBm.

Radar Waveform Calibration



The DFS detection threshold level = SG level - Cable loss - Attenuator + Antenna gain

Test Data

Environmental Conditions

Temperature:	25.8~27 °C
Relative Humidity:	51~54 %
ATM Pressure:	101.0 kPa

The testing was performed by Roger Ling from 2023-05-06 to 2023-05-08.

EUT operation mode: Transmitting

Test Result: Pass

Please refer to the Appendix.

CHANNEL AVAILABILITY CHECK TIME(CAC)

Test Procedure

1. Initial Channel Availability Check Time

The U-NII devices will be powered on and be instructed to operate on the appropriate U-NII Channel that must incorporate DFS functions. At the same time the UUT is powered on, the spectrum analyzer will be set to zero span and the spectrum analyzer's sweep will be started at the same time power is applied to the U-NII device.

The UUT should not transmit any beacon or data transmissions until at least 1 minute after the completion of the power-on cycle.

Confirm that the UUT initiates transmission on the channel

2. Radar Burst at the Beginning of the Channel Availability Check Time

A single Burst of one of the Short Pulse Radar Types 0-4 will commence within a 6 second window at the beginning of CAC time. Visual indication or measured results on the UUT of successful detection of the radar Burst will be recorded and reported.

3. Radar Burst at the End of the Channel Availability Check Time

A single Burst of one of the Short Pulse Radar Types 0-4 will commence within a 6 second window at the end of CAC time. Visual indication or measured results on the UUT of successful detection of the radar Burst will be recorded and reported.

Test Data

Environmental Conditions

Temperature:	25.8~27 °C
Relative Humidity:	51~54 %
ATM Pressure:	101.0 kPa

The testing was performed by Roger Ling from 2023-05-06 to 2023-05-08.

EUT operation mode: Transmitting

Test Result: Pass

Please refer to the Appendix.

CHANNEL MOVE TIME AND CHANNEL CLOSING TRANSMISSION TIME

Test Procedure

Channel Move Time and the Channel Closing Transmission Time should be performed with Radar Type 0. The measurement timing begins at the end of the Radar Type 0 burst. repeat using a long pulse radar type5 waveform.

The Channel Closing Transmission Time is comprised of 200 milliseconds starting at the beginning of the Channel Move Time plus any additional intermittent control signals required to facilitate a Channel move (an aggregate of 60 milliseconds) during the remainder of the 10 second period. The aggregate duration of control signals will not count quiet periods in between transmissions.

The aggregate channel closing transmission time is calculated as follows:

Aggregate Transmission Time = $N \times \text{Dwell Time}$

N is the number of spectrum analyzer bins showing a device transmission Dwell Time is the dwell time per bin (i.e. $\text{Dwell Time} = S/B$, S is the sweep time and B is the number of bin, i.e. 8192)

Test Data

Environmental Conditions

Temperature:	25.8~27 °C
Relative Humidity:	51~54 %
ATM Pressure:	101.0 kPa

The testing was performed by Roger Ling from 2023-05-06 to 2023-05-08.

EUT operation mode: Transmitting

Test Result: Pass

Please refer to the Appendix.

NON-OCCUPANCY PERIOD

Test Procedure

Measure the EUT for more than 30 minutes following the channel close/move time to verify that the EUT does not resume any transmissions on this channel. Provide one plot to demonstrate no transmission on the channel for the non-occupancy period (30 minutes observation time)

Test Data

Environmental Conditions

Temperature:	25.8~27 °C
Relative Humidity:	51~54 %
ATM Pressure:	101.0 kPa

The testing was performed by Roger Ling from 2023-05-06 to 2023-05-08.

EUT operation mode: Transmitting

Test Result: Pass

Please refer to the Appendix.

DETECTION BANDWIDTH

Test Procedure

Performed with Type 0 radar waveforms

Starting at the center frequency of the UUT operating Channel, increase the radar frequency in 5 MHz steps, repeating the above test sequence, until the detection rate falls below the *U-NII Detection Bandwidth* criterion specified in Table 4. Repeat this measurement in 1MHz steps at frequencies 5 MHz below where the detection rate begins to fall. Record the highest frequency (denote as F_H) at which detection is greater than or equal to the *U-NII Detection Bandwidth* criterion. Recording the detection rate at frequencies above F_H is not required to demonstrate compliance.

Starting at the center frequency of the UUT operating Channel, decrease the radar frequency in 5 MHz steps, repeating the above test sequence, until the detection rate falls below the *U-NII Detection Bandwidth* criterion specified in Table 4. Repeat this measurement in 1MHz steps at frequencies 5 MHz above where the detection rate begins to fall. Record the lowest frequency (denote as F_L) at which detection is greater than or equal to the *U-NII Detection Bandwidth* criterion. Recording the detection rate at frequencies below F_L is not required to demonstrate compliance

The *U-NII Detection Bandwidth* is calculated as follows: $U-NII\ Detection\ Bandwidth = F_H - F_L$

The *U-NII Detection Bandwidth* must meet the *U-NII Detection Bandwidth* criterion specified in Table 4. Otherwise, the UUT does not comply with DFS requirements. This is essential to ensure that the UUT is capable of detecting *Radar Waveforms* across the same frequency spectrum that contains the significant energy from the system. In the case that the *U-NII Detection Bandwidth* is greater than or equal to the 99 percent power bandwidth for the measured F_H and F_L , the test can be truncated and the *U-NII Detection Bandwidth* can be reported as the measured F_H and F_L .

Test Data

Environmental Conditions

Temperature:	25.8~27 °C
Relative Humidity:	51~54 %
ATM Pressure:	101.0 kPa

The testing was performed by Roger Ling from 2023-05-06 to 2023-05-08.

EUT operation mode: Transmitting

Test Result: Pass

Please refer to the Appendix.

STATISTICAL PERFORMANCE CHECK

Test Procedure

The steps below define the procedure to determine the minimum percentage of successful detection requirements found in **Tables 5-7** when a radar burst with a level equal to the *DFS Detection Threshold* + 1dB is generated on the *Operating Channel* of the U-NII device (*In-Service Monitoring*).

a) One frequency will be chosen from the *Operating Channels* of the UUT within the 5250-5350 MHz or 5470-5725 MHz bands.

b) In case the UUT is a U-NII device operating as a *Client Device* (with or without Radar Detection), a U-NII device operating as a *Master Device* will be used to allow the UUT (Client device) to *Associate* with the *Master Device*. In case the UUT is a *Master Device*, a U-NII device operating as a *Client Device* will be used and it is assumed that the Client will *Associate* with the UUT (Master). In both cases for conducted tests, the *Radar Waveform* generator will be connected to the *Master Device*. For radiated tests, the emissions of the *Radar Waveform* generator will be directed towards the *Master Device*. If the *Master Device* has antenna gain, the main beam of the antenna will be directed toward the radar emitter. Vertical polarization is used for testing.

c) Stream the channel loading test file from the *Master Device* to the Client Device on the test *Channel* for the entire period of the test.

d) At time T_0 the *Radar Waveform* generator sends the individual waveform for each of the Radar Types 1-6 in **Tables 5-7**, at levels defined in **Table 3**, on the *Operating Channel*. An additional 1 dB is added to the radar test signal to ensure it is at or above the *DFS Detection Threshold*, accounting for equipment variations/errors.

e) Observe the transmissions of the UUT at the end of the Burst on the *Operating Channel* for duration greater than 10 seconds for Radar Type 0 to ensure detection occurs.

f) Observe the transmissions of the UUT at the end of the Burst on the *Operating Channel* for duration greater than 22 seconds for Long Pulse Radar Type 5 to ensure detection occurs.

g) In case the UUT is a U-NII device operating as a *Client Device* with *In-Service Monitoring*, perform steps a) to f).

Test Data

Environmental Conditions

Temperature:	25.8~27 °C
Relative Humidity:	51~54 %
ATM Pressure:	101.0 kPa

The testing was performed by Roger Ling from 2023-05-06 to 2023-05-08.

EUT operation mode: Transmitting

Test Result: Pass

Please refer to the Appendix.

BRIDGE AND/OR MESH MODE

Test Procedure

Networks Access Points with Bridge and/or MESH modes of operation are permitted to operate in the DFS bands but must employ a DFS function. The functionality of the Bridge mode as specified in ?15.403(a) must be validated in the DFS test report. Devices operating as relays where they act as master and client must also employ DFS function for the master. The method used to validate the functionality must be documented and validation data must be documented. Bridge mode can be validated by performing a test statistical performance check (Section 7.8.4) on any one of the radar types. This is an abbreviated test to verify DFS functionality. MESH mode operational methodology must be submitted in the application for certification for evaluation by the FCC.

Test Data

Environmental Conditions

Temperature:	25.8~27 °C
Relative Humidity:	51~54 %
ATM Pressure:	101.0 kPa

The testing was performed by Roger Ling from 2023-05-06 to 2023-05-08.

EUT operation mode: Transmitting

Test Result: Pass


Please refer to the Appendix.

APPENDIX


AppendixA:DFS Detection Thresholds Test Result

Test Mode	Frequency [MHz]	Radar Type	Result [dBm]	Limit [dBm]	Verdict
20M	5260	Type0	-64.13	-64.00	PASS
		Type1	-64.44	-64.00	PASS
		Type2	-64.45	-64.00	PASS
		Type3	-64.07	-64.00	PASS
		Type4	-64.39	-64.00	PASS
		Type5	-64.40	-64.00	PASS
		Type6	-64.09	-64.00	PASS
40M	5270	Type0	-64.41	-64.00	PASS
		Type1	-64.06	-64.00	PASS
		Type2	-64.09	-64.00	PASS
		Type3	-64.02	-64.00	PASS
		Type4	-64.07	-64.00	PASS
		Type5	-64.37	-64.00	PASS
		Type6	-64.03	-64.00	PASS
80M	5290	Type0	-64.22	-64.00	PASS
		Type1	-64.40	-64.00	PASS
		Type2	-64.22	-64.00	PASS
		Type3	-64.24	-64.00	PASS
		Type4	-64.14	-64.00	PASS
		Type5	-64.48	-64.00	PASS
		Type6	-64.50	-64.00	PASS
160M	5250	Type0	-64.06	-64.00	PASS
		Type1	-64.33	-64.00	PASS
		Type2	-64.41	-64.00	PASS
		Type3	-64.07	-64.00	PASS
		Type4	-64.03	-64.00	PASS
		Type5	-64.39	-64.00	PASS
		Type6	-64.44	-64.00	PASS


Test Graphs




20M 5260 Type2




20M 5260 Type3




20M_5260_Type4




20M_5260_Type5




20M 5260 Type6




40M 5270 Type0




40M_5270_Type1




40M_5270_Type2




40M_5270_Type3




40M_5270_Type4




40M_5270_Type5




40M_5270_Type6




80M_5290_Type0




80M_5290_Type1




80M_5290_Type2




80M_5290_Type3




80M_5290_Type4




80M_5290_Type5




80M_5290_Type6




160M_5250_Type0




160M_5250_Type1




160M_5250_Type2




160M_5250_Type3




160M_5250_Type4



160M_5250_Type5




160M_5250_Type6



**Appendix B: Channel Loading
Test Result**

Test Mode	Frequency[MHz]	Result	Limit [%]	Verdict
11AX160MIMO	5250	20.24	17	PASS

Test Graphs



Appendix C: Channel Availability Check Time Test Result

Initial Channel Availability Check Time

Test Mode	Frequency[MHz]	Result	Verdict
11AX160MIMO	5250	See test Graph	PASS

Beginning of Channel Availability Check Time

Test Mode	Frequency[MHz]	Result	Verdict
11AX160MIMO	5250	See test Graph	PASS

End of Channel Availability Check Time


Test Mode	Frequency[MHz]	Result	Verdict
11AX160MIMO	5250	See test Graph	PASS

Note: the power-up cycle time of EUT is 87s.

Test Graphs


Initial Channel Availability Check Time

11AX160MIMO 5250




Beginning of Channel Availability Check Time

11AX160MIMO 5250



End of Channel Availability Check Time


11AX160MIMO_5250



Appendix D: Channel Move Time and Channel Closing Transmission Time Test Result

Test Mode	Frequency[MHz]	CCTT[ms]	Limit[ms]	CMT[ms]	Limit[ms]	Verdict
11AX160MIMO	5250	200+6.5	200+60	465.1	10000	PASS

Test Graphs




Appendix E:Non-Occupancy Period

Test Result

Test Mode	Frequency[MHz]	Result	Limit[s]	Verdict
11AX160MIMO	5250	see test graph	≥1800	PASS

Test Graphs



Appendix F: U-NII Detection Bandwidth**Test Result**

Test Mode	Frequency[MHz]	FL[MHz]	FH[MHz]	Detection Bandwidth [MHz]	OCB [MHz]	Limit	Verdict
11AX20MIMO	5260	5250	5270	20	19.231	≥OCB	PASS
11AX40MIMO	5270	5250	5290	40	37.949	≥OCB	PASS
11AX80MIMO	5290	5250	5330	80	77.436	≥OCB	PASS
11AX160MIMO	5250	5250	5330	160	155.385	≥OCB*	PASS
11AX160MIMO	5570	5490	5650	160	155.385	≥OCB	PASS

Note*: the detection bandwidth covered the OBW fall within 5250-5350MHz range.

Test Mode	Frequency [MHz]	Radar Freq.	Trial 1	Trial 2	Trial 3	Trial 4	Trial 5	Trial 6	Trial 7	Trial 8	Trial 9	Trial 10	Ratio (%)
11AX20MIMO	5260	5250	1	1	1	1	1	1	1	1	1	1	100
		5255	1	1	1	1	1	1	1	1	1	1	100
		5260	1	1	1	1	1	1	1	1	1	1	100
		5265	1	1	1	1	1	1	1	1	1	0	90
		5266	1	1	1	1	1	1	1	1	1	1	100
		5267	1	1	1	1	1	1	1	1	1	1	100
		5268	1	1	1	1	1	1	1	1	1	1	100
		5269	1	1	1	1	1	1	1	1	1	1	100
		5270	1	1	1	1	1	1	1	1	1	1	100
11AX40MIMO	5270	5250	1	1	1	1	1	1	1	1	1	1	100
		5255	1	1	1	1	1	1	1	1	1	1	100
		5260	1	1	1	1	1	1	1	1	1	1	100
		5265	1	1	1	1	1	1	1	1	1	1	100
		5270	1	1	1	1	1	1	1	1	1	1	100
		5275	1	1	1	1	1	1	1	1	1	1	100
		5280	1	1	1	1	1	1	1	1	1	1	100
		5285	1	1	1	1	1	1	1	1	1	1	100
		5290	1	1	1	1	1	1	1	1	1	1	100
11AX80MIMO	5290	5250	1	1	1	1	1	1	1	1	1	1	100
		5255	1	1	1	1	1	1	1	1	1	1	100
		5260	1	1	1	1	1	1	1	1	1	1	100
		5265	1	1	1	1	1	1	1	1	1	1	100
		5270	1	1	1	1	1	1	1	1	1	1	100
		5275	1	1	1	1	1	1	1	1	1	1	100
		5280	1	1	1	1	1	1	1	1	1	1	100
		5285	1	1	1	1	1	1	1	1	1	1	100
		5290	1	1	1	1	1	1	1	1	1	1	100
		5295	1	1	1	1	1	1	1	1	1	1	100
		5300	1	1	1	1	1	1	1	1	1	1	100
		5305	1	1	1	1	1	1	1	1	1	1	100
		5310	1	1	1	1	1	1	1	1	1	1	100
		5315	1	1	1	1	1	1	1	1	1	1	100
		5320	1	1	1	1	1	1	1	1	1	1	100
		5325	1	1	1	1	1	1	1	1	1	1	100
		5330	1	1	1	1	1	1	1	1	1	0	90
11AX160MIMO	5250	5250	1	1	1	1	1	1	1	1	1	1	100
		5255	1	1	1	1	1	1	1	1	1	1	100
		5260	1	1	1	1	1	1	1	1	1	1	100
		5265	1	1	1	1	1	1	1	1	1	1	100
		5270	1	1	1	1	1	1	1	1	1	1	100
		5275	1	1	1	1	1	1	1	1	1	1	100
		5280	1	1	1	1	1	1	1	1	1	1	100
		5285	1	1	1	1	1	1	1	1	1	1	100
		5290	1	1	1	1	1	1	1	1	1	1	100

		5295	1	1	1	1	1	1	1	1	1	1	100
		5300	1	1	1	1	1	1	1	1	1	1	100
		5305	1	1	1	1	1	1	1	1	1	1	100
		5310	1	1	1	1	1	1	1	1	1	1	100
		5315	1	1	1	1	1	1	1	1	1	1	100
		5320	1	1	1	1	1	1	1	1	1	1	100
		5325	1	1	1	1	1	1	1	1	1	1	100
11AX160 MIMO	5570	5330	1	1	1	1	1	1	1	1	1	1	100
		5490	1	1	1	1	1	1	1	1	1	1	100
		5495	1	1	1	1	1	1	1	1	1	1	100
		5500	1	1	1	1	1	1	1	1	1	1	100
		5505	1	1	1	1	1	1	1	1	1	1	100
		5510	1	1	1	1	1	1	1	1	1	1	100
		5515	1	1	1	1	1	1	1	1	1	1	100
		5520	1	1	1	1	1	1	1	1	1	1	100
		5525	1	1	1	1	1	1	1	1	1	1	100
		5530	1	1	1	1	1	1	1	1	1	1	100
		5535	1	1	1	1	1	1	1	1	1	1	100
		5540	1	1	1	1	1	1	1	1	1	1	100
		5545	1	1	1	1	1	1	1	1	1	1	100
		5550	1	1	1	1	1	1	1	1	1	1	100
		5555	1	1	1	1	1	1	1	1	1	1	100
		5560	1	1	1	1	1	1	1	1	1	1	100
		5565	1	1	1	1	1	1	1	1	1	1	100
		5570	1	1	1	1	1	1	1	1	1	1	100
		5575	1	1	1	1	1	1	1	1	1	1	100
		5580	1	1	1	1	1	1	1	1	1	1	100
		5585	1	1	1	1	1	1	1	1	1	1	100
		5590	1	1	1	1	1	1	1	1	1	1	100
		5595	1	1	1	1	1	1	1	1	1	1	100
		5600	1	1	1	1	1	1	1	1	1	1	100
		5605	1	1	1	1	1	1	1	1	1	1	100
		5610	1	1	1	1	1	1	1	1	1	1	100
		5615	1	1	1	1	1	1	1	1	1	1	100
		5620	1	1	1	1	1	1	1	1	1	1	100
		5625	1	1	1	1	1	1	1	1	1	1	100
		5630	1	1	1	1	1	1	1	1	1	1	100
		5635	1	1	1	1	1	1	1	1	1	1	100
		5640	1	1	1	1	1	1	1	1	1	1	100
		5645	1	1	1	1	1	1	1	1	1	1	100
		5650	1	1	1	1	1	1	1	1	1	1	100

Appendix G:Statistical Performance check**Test Result**

Test Mode	Frequency[MHz]	Radar Type	Pass Times	Fail Times	Probability (%)	Limit (%)	Verdict
11AX20MIMO	5260	Type1	30	0	100.00	60	PASS
		Type2	30	0	100.00	60	PASS
		Type3	30	0	100.00	60	PASS
		Type4	30	0	100.00	60	PASS
		Type 1-4	120	0	100.00	80	PASS
		Type5	30	0	100.00	80	PASS
		Type6	30	0	100.00	70	PASS
11AX40MIMO	5270	Type1	30	0	100.00	60	PASS
		Type2	30	0	100.00	60	PASS
		Type3	30	0	100.00	60	PASS
		Type4	30	0	100.00	60	PASS
		Type 1-4	120	0	100.00	80	PASS
		Type5	30	0	100.00	80	PASS
		Type6	30	0	100.00	70	PASS
11AX80MIMO	5290	Type1	30	0	100.00	60	PASS
		Type2	30	0	100.00	60	PASS
		Type3	30	0	100.00	60	PASS
		Type4	30	0	100.00	60	PASS
		Type 1-4	120	0	100.00	80	PASS
		Type5	30	0	100.00	80	PASS
		Type6	30	0	100.00	70	PASS
11AX160MIMO	5250	Type1	30	0	100.00	60	PASS
		Type2	30	0	100.00	60	PASS
		Type3	30	0	100.00	60	PASS
		Type4	30	0	100.00	60	PASS
		Type 1-4	120	0	100.00	80	PASS
		Type5	30	0	100.00	80	PASS
		Type6	30	0	100.00	70	PASS

Bridge mode:

Test Mode	Channel	Radar Type	Pass Times	Fail Times	Probability(%)	Limit(%)	Verdict
11AX40MIMO	5270	Type4	30	0	100.00	60	PASS

TestMode	Frequency[MHz]	Radar Type	Trial ID	Pulse width(μs)	PRI(μs)	Pulses per Burst	Detection (1: Yes; 0: No)
11AX20MI MO	5260	Type1	0	1.0	938.0	57	1
		Type1	1	1.0	698.0	76	1
		Type1	2	1.0	618.0	86	1
		Type1	3	1.0	538.0	99	1
		Type1	4	1.0	878.0	61	1
		Type1	5	1.0	3066.0	18	1
		Type1	6	1.0	638.0	83	1
		Type1	7	1.0	918.0	58	1
		Type1	8	1.0	838.0	63	1
		Type1	9	1.0	858.0	62	1
		Type1	10	1.0	798.0	67	1
		Type1	11	1.0	718.0	74	1
		Type1	12	1.0	578.0	92	1
		Type1	13	1.0	598.0	89	1
		Type1	14	1.0	558.0	95	1
		Type1	15	1.0	2536.0	21	1
		Type1	16	1.0	966.0	55	1
		Type1	17	1.0	827.0	64	1
		Type1	18	1.0	2501.0	22	1
		Type1	19	1.0	2595.0	21	1
		Type1	20	1.0	1114.0	48	1
		Type1	21	1.0	1302.0	41	1
		Type1	22	1.0	3045.0	18	1
		Type1	23	1.0	1624.0	33	1
		Type1	24	1.0	2878.0	19	1
		Type1	25	1.0	1027.0	52	1
		Type1	26	1.0	2485.0	22	1
		Type1	27	1.0	1600.0	33	1
		Type1	28	1.0	1172.0	46	1
		Type1	29	1.0	1177.0	45	1
		Type2	0	3.4	179.0	26	1
		Type2	1	4.5	207.0	23	1
		Type2	2	2.1	230.0	24	1
		Type2	3	2.8	200.0	29	1
		Type2	4	3.2	214.0	28	1
		Type2	5	3.8	222.0	26	1
		Type2	6	3.0	204.0	26	1
		Type2	7	1.5	192.0	25	1
		Type2	8	3.0	164.0	26	1
		Type2	9	1.1	156.0	23	1
		Type2	10	1.2	210.0	27	1
		Type2	11	5.0	201.0	29	1
		Type2	12	1.6	162.0	26	1
		Type2	13	3.6	197.0	25	1
		Type2	14	2.8	163.0	29	1
		Type2	15	1.7	203.0	26	1
		Type2	16	2.9	168.0	29	1
		Type2	17	2.5	217.0	25	1
		Type2	18	1.3	191.0	26	1
		Type2	19	3.6	166.0	25	1
		Type2	20	4.2	150.0	27	1
		Type2	21	3.5	176.0	25	1
		Type2	22	3.6	195.0	29	1
		Type2	23	3.3	202.0	26	1
		Type2	24	4.8	178.0	25	1

	Type2	25	3.4	206.0	23	1
	Type2	26	3.8	155.0	27	1
	Type2	27	1.3	157.0	29	1
	Type2	28	4.5	224.0	25	1
	Type2	29	2.3	159.0	28	1
	Type3	0	8.2	355.0	17	1
	Type3	1	6.1	487.0	16	1
	Type3	2	7.1	344.0	16	1
	Type3	3	9.8	288.0	18	1
	Type3	4	8.9	230.0	18	1
	Type3	5	7.9	432.0	17	1
	Type3	6	8.2	207.0	17	1
	Type3	7	7.5	443.0	17	1
	Type3	8	8.1	439.0	17	1
	Type3	9	6.2	223.0	16	1
	Type3	10	8.9	208.0	18	1
	Type3	11	9.6	463.0	18	1
	Type3	12	8.2	441.0	17	1
	Type3	13	7.2	323.0	16	1
	Type3	14	9.5	297.0	18	1
	Type3	15	8.0	412.0	17	1
	Type3	16	10.0	324.0	18	1
	Type3	17	7.4	271.0	17	1
	Type3	18	7.9	349.0	17	1
	Type3	19	7.3	409.0	16	1
	Type3	20	8.7	373.0	18	1
	Type3	21	7.2	254.0	16	1
	Type3	22	9.9	274.0	18	1
	Type3	23	7.9	278.0	17	1
	Type3	24	7.5	317.0	17	1
	Type3	25	6.1	260.0	16	1
	Type3	26	8.8	211.0	18	1
	Type3	27	9.7	272.0	18	1
	Type3	28	7.4	264.0	17	1
	Type3	29	9.2	284.0	18	1
	Type4	0	16.0	355.0	14	1
	Type4	1	11.3	487.0	12	1
	Type4	2	13.5	344.0	13	1
	Type4	3	19.4	288.0	16	1
	Type4	4	17.5	230.0	15	1
	Type4	5	15.3	432.0	14	1
	Type4	6	15.9	207.0	14	1
	Type4	7	14.3	443.0	13	1
	Type4	8	15.8	439.0	14	1
	Type4	9	11.5	223.0	12	1
	Type4	10	17.4	208.0	15	1
	Type4	11	19.0	463.0	16	1
	Type4	12	16.0	441.0	14	1
	Type4	13	13.8	323.0	13	1
	Type4	14	18.9	297.0	16	1
	Type4	15	15.5	412.0	14	1
	Type4	16	19.9	324.0	16	1
	Type4	17	14.1	271.0	13	1
	Type4	18	15.2	349.0	14	1
	Type4	19	13.8	409.0	13	1
	Type4	20	17.1	373.0	15	1
	Type4	21	13.8	254.0	13	1
	Type4	22	19.8	274.0	16	1

		Type4	23	15.3	278.0	14	1
		Type4	24	14.5	317.0	13	1
		Type4	25	11.3	260.0	12	1
		Type4	26	17.3	211.0	15	1
		Type4	27	19.2	272.0	16	1
		Type4	28	14.2	264.0	13	1
		Type4	29	18.2	284.0	15	1
11AX40MI MO	5270	Type1	0	1.0	938.0	57	1
		Type1	1	1.0	698.0	76	1
		Type1	2	1.0	618.0	86	1
		Type1	3	1.0	538.0	99	1
		Type1	4	1.0	878.0	61	1
		Type1	5	1.0	3066.0	18	1
		Type1	6	1.0	638.0	83	1
		Type1	7	1.0	918.0	58	1
		Type1	8	1.0	838.0	63	1
		Type1	9	1.0	858.0	62	1
		Type1	10	1.0	798.0	67	1
		Type1	11	1.0	718.0	74	1
		Type1	12	1.0	578.0	92	1
		Type1	13	1.0	598.0	89	1
		Type1	14	1.0	558.0	95	1
		Type1	15	1.0	2536.0	21	1
		Type1	16	1.0	966.0	55	1
		Type1	17	1.0	827.0	64	1
		Type1	18	1.0	2501.0	22	1
		Type1	19	1.0	2595.0	21	1
		Type1	20	1.0	1114.0	48	1
		Type1	21	1.0	1302.0	41	1
		Type1	22	1.0	3045.0	18	1
		Type1	23	1.0	1624.0	33	1
		Type1	24	1.0	2878.0	19	1
		Type1	25	1.0	1027.0	52	1
		Type1	26	1.0	2485.0	22	1
		Type1	27	1.0	1600.0	33	1
		Type1	28	1.0	1172.0	46	1
		Type1	29	1.0	1177.0	45	1
		Type2	0	3.2	179.0	26	1
		Type2	1	1.1	207.0	23	1
		Type2	2	2.1	230.0	24	1
		Type2	3	4.8	200.0	29	1
		Type2	4	3.9	214.0	28	1
		Type2	5	2.9	222.0	26	1
		Type2	6	3.2	204.0	26	1
		Type2	7	2.5	192.0	25	1
		Type2	8	3.1	164.0	26	1
		Type2	9	1.2	156.0	23	1
		Type2	10	3.9	210.0	27	1
		Type2	11	4.6	201.0	29	1
		Type2	12	3.2	162.0	26	1
		Type2	13	2.2	197.0	25	1
		Type2	14	4.5	163.0	29	1
		Type2	15	3.0	203.0	26	1
		Type2	16	5.0	168.0	29	1
		Type2	17	2.4	217.0	25	1
		Type2	18	2.9	191.0	26	1
		Type2	19	2.3	166.0	25	1
		Type2	20	3.7	150.0	27	1

	Type2	21	2.2	176.0	25	1
	Type2	22	4.9	195.0	29	1
	Type2	23	2.9	202.0	26	1
	Type2	24	2.5	178.0	25	1
	Type2	25	1.1	206.0	23	1
	Type2	26	3.8	155.0	27	1
	Type2	27	4.7	157.0	29	1
	Type2	28	2.4	224.0	25	1
	Type2	29	4.2	159.0	28	1
	Type3	0	8.2	355.0	17	1
	Type3	1	6.1	487.0	16	1
	Type3	2	7.1	344.0	16	1
	Type3	3	9.8	288.0	18	1
	Type3	4	8.9	230.0	18	1
	Type3	5	7.9	432.0	17	1
	Type3	6	8.2	207.0	17	1
	Type3	7	7.5	443.0	17	1
	Type3	8	8.1	439.0	17	1
	Type3	9	6.2	223.0	16	1
	Type3	10	8.9	208.0	18	1
	Type3	11	9.6	463.0	18	1
	Type3	12	8.2	441.0	17	1
	Type3	13	7.2	323.0	16	1
	Type3	14	9.5	297.0	18	1
	Type3	15	8.0	412.0	17	1
	Type3	16	10.0	324.0	18	1
	Type3	17	7.4	271.0	17	1
	Type3	18	7.9	349.0	17	1
	Type3	19	7.3	409.0	16	1
	Type3	20	8.7	373.0	18	1
	Type3	21	7.2	254.0	16	1
	Type3	22	9.9	274.0	18	1
	Type3	23	7.9	278.0	17	1
	Type3	24	7.5	317.0	17	1
	Type3	25	6.1	260.0	16	1
	Type3	26	8.8	211.0	18	1
	Type3	27	9.7	272.0	18	1
	Type3	28	7.4	264.0	17	1
	Type3	29	9.2	284.0	18	1
	Type4	0	16.0	355.0	14	1
	Type4	1	11.3	487.0	12	1
	Type4	2	13.5	344.0	13	1
	Type4	3	19.4	288.0	16	1
	Type4	4	17.5	230.0	15	1
	Type4	5	15.3	432.0	14	1
	Type4	6	15.9	207.0	14	1
	Type4	7	14.3	443.0	13	1
	Type4	8	15.8	439.0	14	1
	Type4	9	11.5	223.0	12	1
	Type4	10	17.4	208.0	15	1
	Type4	11	19.0	463.0	16	1
	Type4	12	16.0	441.0	14	1
	Type4	13	13.8	323.0	13	1
	Type4	14	18.9	297.0	16	1
	Type4	15	15.5	412.0	14	1
	Type4	16	19.9	324.0	16	1
	Type4	17	14.1	271.0	13	1
	Type4	18	15.2	349.0	14	1

		Type4	19	13.8	409.0	13	1
		Type4	20	17.1	373.0	15	1
		Type4	21	13.8	254.0	13	1
		Type4	22	19.8	274.0	16	1
		Type4	23	15.3	278.0	14	1
		Type4	24	14.5	317.0	13	1
		Type4	25	11.3	260.0	12	1
		Type4	26	17.3	211.0	15	1
		Type4	27	19.2	272.0	16	1
		Type4	28	14.2	264.0	13	1
11AX80MI MO	5290	Type4	29	18.2	284.0	15	1
		Type1	0	1.0	938.0	57	1
		Type1	1	1.0	698.0	76	1
		Type1	2	1.0	618.0	86	1
		Type1	3	1.0	538.0	99	1
		Type1	4	1.0	878.0	61	1
		Type1	5	1.0	3066.0	18	1
		Type1	6	1.0	638.0	83	1
		Type1	7	1.0	918.0	58	1
		Type1	8	1.0	838.0	63	1
		Type1	9	1.0	858.0	62	1
		Type1	10	1.0	798.0	67	1
		Type1	11	1.0	718.0	74	1
		Type1	12	1.0	578.0	92	1
		Type1	13	1.0	598.0	89	1
		Type1	14	1.0	558.0	95	1
		Type1	15	1.0	2536.0	21	1
		Type1	16	1.0	966.0	55	1
		Type1	17	1.0	827.0	64	1
		Type1	18	1.0	2501.0	22	1
		Type1	19	1.0	2595.0	21	1
		Type1	20	1.0	1114.0	48	1
		Type1	21	1.0	1302.0	41	1
		Type1	22	1.0	3045.0	18	1
		Type1	23	1.0	1624.0	33	1
		Type1	24	1.0	2878.0	19	1
		Type1	25	1.0	1027.0	52	1
		Type1	26	1.0	2485.0	22	1
		Type1	27	1.0	1600.0	33	1
		Type1	28	1.0	1172.0	46	1
		Type1	29	1.0	1177.0	45	1
		Type2	0	3.2	179.0	26	1
		Type2	1	1.1	207.0	23	1
		Type2	2	2.1	230.0	24	1
		Type2	3	4.8	200.0	29	1
		Type2	4	3.9	214.0	28	1
		Type2	5	2.9	222.0	26	1
		Type2	6	3.2	204.0	26	1
		Type2	7	2.5	192.0	25	1
		Type2	8	3.1	164.0	26	1
		Type2	9	1.2	156.0	23	1
		Type2	10	3.9	210.0	27	1
		Type2	11	4.6	201.0	29	1
		Type2	12	3.2	162.0	26	1
		Type2	13	2.2	197.0	25	1
		Type2	14	4.5	163.0	29	1
		Type2	15	3.0	203.0	26	1
		Type2	16	5.0	168.0	29	1

	Type2	17	2.4	217.0	25	1
	Type2	18	2.9	191.0	26	1
	Type2	19	2.3	166.0	25	1
	Type2	20	3.7	150.0	27	1
	Type2	21	2.2	176.0	25	1
	Type2	22	4.9	195.0	29	1
	Type2	23	2.9	202.0	26	1
	Type2	24	2.5	178.0	25	1
	Type2	25	1.1	206.0	23	1
	Type2	26	3.8	155.0	27	1
	Type2	27	4.7	157.0	29	1
	Type2	28	2.4	224.0	25	1
	Type2	29	4.2	159.0	28	1
	Type3	0	8.2	355.0	17	1
	Type3	1	6.1	487.0	16	1
	Type3	2	7.1	344.0	16	1
	Type3	3	9.8	288.0	18	1
	Type3	4	8.9	230.0	18	1
	Type3	5	7.9	432.0	17	1
	Type3	6	8.2	207.0	17	1
	Type3	7	7.5	443.0	17	1
	Type3	8	8.1	439.0	17	1
	Type3	9	6.2	223.0	16	1
	Type3	10	8.9	208.0	18	1
	Type3	11	9.6	463.0	18	1
	Type3	12	8.2	441.0	17	1
	Type3	13	7.2	323.0	16	1
	Type3	14	9.5	297.0	18	1
	Type3	15	8.0	412.0	17	1
	Type3	16	10.0	324.0	18	1
	Type3	17	7.4	271.0	17	1
	Type3	18	7.9	349.0	17	1
	Type3	19	7.3	409.0	16	1
	Type3	20	8.7	373.0	18	1
	Type3	21	7.2	254.0	16	1
	Type3	22	9.9	274.0	18	1
	Type3	23	7.9	278.0	17	1
	Type3	24	7.5	317.0	17	1
	Type3	25	6.1	260.0	16	1
	Type3	26	8.8	211.0	18	1
	Type3	27	9.7	272.0	18	1
	Type3	28	7.4	264.0	17	1
	Type3	29	9.2	284.0	18	1
	Type4	0	16.0	355.0	14	1
	Type4	1	11.3	487.0	12	1
	Type4	2	13.5	344.0	13	1
	Type4	3	19.4	288.0	16	1
	Type4	4	17.5	230.0	15	1
	Type4	5	15.3	432.0	14	1
	Type4	6	15.9	207.0	14	1
	Type4	7	14.3	443.0	13	1
	Type4	8	15.8	439.0	14	1
	Type4	9	11.5	223.0	12	1
	Type4	10	17.4	208.0	15	1
	Type4	11	19.0	463.0	16	1
	Type4	12	16.0	441.0	14	1
	Type4	13	13.8	323.0	13	1
	Type4	14	18.9	297.0	16	1

11AX160MI MO	5250	Type4	15	15.5	412.0	14	1
		Type4	16	19.9	324.0	16	1
		Type4	17	14.1	271.0	13	1
		Type4	18	15.2	349.0	14	1
		Type4	19	13.8	409.0	13	1
		Type4	20	17.1	373.0	15	1
		Type4	21	13.8	254.0	13	1
		Type4	22	19.8	274.0	16	1
		Type4	23	15.3	278.0	14	1
		Type4	24	14.5	317.0	13	1
		Type4	25	11.3	260.0	12	1
		Type4	26	17.3	211.0	15	1
		Type4	27	19.2	272.0	16	1
		Type4	28	14.2	264.0	13	1
		Type4	29	18.2	284.0	15	1
		Type1	0	1.0	938.0	57	1
		Type1	1	1.0	698.0	76	1
		Type1	2	1.0	618.0	86	1
		Type1	3	1.0	538.0	99	1
		Type1	4	1.0	878.0	61	1
		Type1	5	1.0	3066.0	18	1
		Type1	6	1.0	638.0	83	1
		Type1	7	1.0	918.0	58	1
		Type1	8	1.0	838.0	63	1
		Type1	9	1.0	858.0	62	1
		Type1	10	1.0	798.0	67	1
		Type1	11	1.0	718.0	74	1
		Type1	12	1.0	578.0	92	1
		Type1	13	1.0	598.0	89	1
		Type1	14	1.0	558.0	95	1
		Type1	15	1.0	2536.0	21	1
		Type1	16	1.0	966.0	55	1
		Type1	17	1.0	827.0	64	1
		Type1	18	1.0	2501.0	22	1
		Type1	19	1.0	2595.0	21	1
		Type1	20	1.0	1114.0	48	1
		Type1	21	1.0	1302.0	41	1
		Type1	22	1.0	3045.0	18	1
		Type1	23	1.0	1624.0	33	1
		Type1	24	1.0	2878.0	19	1
		Type1	25	1.0	1027.0	52	1
		Type1	26	1.0	2485.0	22	1
		Type1	27	1.0	1600.0	33	1
		Type1	28	1.0	1172.0	46	1
		Type1	29	1.0	1177.0	45	1
		Type2	0	3.2	179.0	26	1
		Type2	1	1.1	207.0	23	1
		Type2	2	2.1	230.0	24	1
		Type2	3	4.8	200.0	29	1
		Type2	4	3.9	214.0	28	1
		Type2	5	2.9	222.0	26	1
		Type2	6	3.2	204.0	26	1
		Type2	7	2.5	192.0	25	1
		Type2	8	3.1	164.0	26	1
		Type2	9	1.2	156.0	23	1
		Type2	10	3.9	210.0	27	1
		Type2	11	4.6	201.0	29	1
		Type2	12	3.2	162.0	26	1

	Type2	13	2.2	197.0	25	1
	Type2	14	4.5	163.0	29	1
	Type2	15	3.0	203.0	26	1
	Type2	16	5.0	168.0	29	1
	Type2	17	2.4	217.0	25	1
	Type2	18	2.9	191.0	26	1
	Type2	19	2.3	166.0	25	1
	Type2	20	3.7	150.0	27	1
	Type2	21	2.2	176.0	25	1
	Type2	22	4.9	195.0	29	1
	Type2	23	2.9	202.0	26	1
	Type2	24	2.5	178.0	25	1
	Type2	25	1.1	206.0	23	1
	Type2	26	3.8	155.0	27	1
	Type2	27	4.7	157.0	29	1
	Type2	28	2.4	224.0	25	1
	Type2	29	4.2	159.0	28	1
	Type3	0	8.2	355.0	17	1
	Type3	1	6.1	487.0	16	1
	Type3	2	7.1	344.0	16	1
	Type3	3	9.8	288.0	18	1
	Type3	4	8.9	230.0	18	1
	Type3	5	7.9	432.0	17	1
	Type3	6	8.2	207.0	17	1
	Type3	7	7.5	443.0	17	1
	Type3	8	8.1	439.0	17	1
	Type3	9	6.2	223.0	16	1
	Type3	10	8.9	208.0	18	1
	Type3	11	9.6	463.0	18	1
	Type3	12	8.2	441.0	17	1
	Type3	13	7.2	323.0	16	1
	Type3	14	9.5	297.0	18	1
	Type3	15	8.0	412.0	17	1
	Type3	16	10.0	324.0	18	1
	Type3	17	7.4	271.0	17	1
	Type3	18	7.9	349.0	17	1
	Type3	19	7.3	409.0	16	1
	Type3	20	8.7	373.0	18	1
	Type3	21	7.2	254.0	16	1
	Type3	22	9.9	274.0	18	1
	Type3	23	7.9	278.0	17	1
	Type3	24	7.5	317.0	17	1
	Type3	25	6.1	260.0	16	1
	Type3	26	8.8	211.0	18	1
	Type3	27	9.7	272.0	18	1
	Type3	28	7.4	264.0	17	1
	Type3	29	9.2	284.0	18	1
	Type4	0	16.0	355.0	14	1
	Type4	1	11.3	487.0	12	1
	Type4	2	13.5	344.0	13	1
	Type4	3	19.4	288.0	16	1
	Type4	4	17.5	230.0	15	1
	Type4	5	15.3	432.0	14	1
	Type4	6	15.9	207.0	14	1
	Type4	7	14.3	443.0	13	1
	Type4	8	15.8	439.0	14	1
	Type4	9	11.5	223.0	12	1
	Type4	10	17.4	208.0	15	1

	Type4	11	19.0	463.0	16	1
	Type4	12	16.0	441.0	14	1
	Type4	13	13.8	323.0	13	1
	Type4	14	18.9	297.0	16	1
	Type4	15	15.5	412.0	14	1
	Type4	16	19.9	324.0	16	1
	Type4	17	14.1	271.0	13	1
	Type4	18	15.2	349.0	14	1
	Type4	19	13.8	409.0	13	1
	Type4	20	17.1	373.0	15	1
	Type4	21	13.8	254.0	13	1
	Type4	22	19.8	274.0	16	1
	Type4	23	15.3	278.0	14	1
	Type4	24	14.5	317.0	13	1
	Type4	25	11.3	260.0	12	1
	Type4	26	17.3	211.0	15	1
	Type4	27	19.2	272.0	16	1
	Type4	28	14.2	264.0	13	1
	Type4	29	18.2	284.0	15	1

Test Mode	Frequency [MHz]	Radar Type	Trial ID	Number Of Bursts	Waveform Length (s)	Radar Frequency	Detection (1: Yes; 0: No)
11AX20MI MO	5260	Type5	0	15	12	5260	1
		Type5	1	8	12	5260	1
		Type5	2	11	12	5260	1
		Type5	3	20	12	5260	1
		Type5	4	17	12	5260	1
		Type5	5	14	12	5260	1
		Type5	6	15	12	5260	1
		Type5	7	12	12	5260	1
		Type5	8	14	12	5260	1
		Type5	9	8	12	5260	1
		Type5	10	17	12	5257.4	1
		Type5	11	19	12	5258.6	1
		Type5	12	15	12	5256.2	1
		Type5	13	12	12	5255	1
		Type5	14	19	12	5258.2	1
		Type5	15	14	12	5255.8	1
		Type5	16	20	12	5259	1
		Type5	17	12	12	5255	1
		Type5	18	14	12	5255.8	1
		Type5	19	12	12	5255	1
		Type5	20	16	12	5263	1
		Type5	21	12	12	5265.4	1
		Type5	22	20	12	5261	1
		Type5	23	14	12	5264.2	1
		Type5	24	13	12	5264.6	1
		Type5	25	8	12	5267	1
		Type5	26	17	12	5262.6	1
		Type5	27	19	12	5261.4	1
		Type5	28	12	12	5265	1
		Type5	29	18	12	5262.2	1
11AX40MI MO	5270	Type5	0	15	12	5270	1
		Type5	1	8	12	5270	1
		Type5	2	11	12	5270	1
		Type5	3	20	12	5270	1
		Type5	4	17	12	5270	1
		Type5	5	14	12	5270	1
		Type5	6	15	12	5270	1
		Type5	7	12	12	5270	1
		Type5	8	14	12	5270	1
		Type5	9	8	12	5270	1
		Type5	10	17	12	5257.9	1
		Type5	11	19	12	5259.1	1
		Type5	12	15	12	5256.7	1
		Type5	13	12	12	5255.5	1
		Type5	14	19	12	5258.7	1
		Type5	15	14	12	5256.3	1
		Type5	16	20	12	5259.5	1
		Type5	17	12	12	5255.5	1
		Type5	18	14	12	5256.3	1
		Type5	19	12	12	5255.5	1
		Type5	20	16	12	5282.5	1
		Type5	21	12	12	5284.9	1
		Type5	22	20	12	5280.5	1
		Type5	23	14	12	5283.7	1
		Type5	24	13	12	5284.1	1
		Type5	25	8	12	5286.5	1
		Type5	26	17	12	5282.1	1

		Type5	27	19	12	5280.9	1
		Type5	28	12	12	5284.5	1
		Type5	29	18	12	5281.7	1
11AX80MI MO	5290	Type5	0	15	12	5290	1
		Type5	1	8	12	5290	1
		Type5	2	11	12	5290	1
		Type5	3	20	12	5290	1
		Type5	4	17	12	5290	1
		Type5	5	14	12	5290	1
		Type5	6	15	12	5290	1
		Type5	7	12	12	5290	1
		Type5	8	14	12	5290	1
		Type5	9	8	12	5290	1
		Type5	10	17	12	5257.4	1
		Type5	11	19	12	5258.6	1
		Type5	12	15	12	5256.2	1
		Type5	13	12	12	5255	1
		Type5	14	19	12	5258.2	1
		Type5	15	14	12	5255.8	1
		Type5	16	20	12	5259	1
		Type5	17	12	12	5255	1
		Type5	18	14	12	5255.8	1
		Type5	19	12	12	5255	1
		Type5	20	16	12	5323	1
		Type5	21	12	12	5325.4	1
		Type5	22	20	12	5321	1
		Type5	23	14	12	5324.2	1
		Type5	24	13	12	5324.6	1
		Type5	25	8	12	5327	1
		Type5	26	17	12	5322.6	1
		Type5	27	19	12	5321.4	1
		Type5	28	12	12	5325	1
		Type5	29	18	12	5322.2	1
11AX160 MIMO	5250	Type5	0	15	12	5250	1
		Type5	1	8	12	5250	1
		Type5	2	11	12	5250	1
		Type5	3	20	12	5250	1
		Type5	4	17	12	5250	1
		Type5	5	14	12	5250	1
		Type5	6	15	12	5250	1
		Type5	7	12	12	5250	1
		Type5	8	14	12	5250	1
		Type5	9	8	12	5290	1
		Type5	10	17	12	5257.4	1
		Type5	11	19	12	5258.6	1
		Type5	12	15	12	5256.2	1
		Type5	13	12	12	5255	1
		Type5	14	19	12	5258.2	1
		Type5	15	14	12	5255.8	1
		Type5	16	20	12	5259	1
		Type5	17	12	12	5255	1
		Type5	18	14	12	5255.8	1
		Type5	19	12	12	5255	1
		Type5	20	16	12	5323	1
		Type5	21	12	12	5325.4	1
		Type5	22	20	12	5321	1
		Type5	23	14	12	5324.2	1
		Type5	24	13	12	5324.6	1
		Type5	25	8	12	5327	1
		Type5	26	17	12	5322.6	1
		Type5	27	19	12	5321.4	1

		Type5	28	12	12	5325	1
		Type5	29	18	12	5322.2	1

Test Mode	Channel	Radar Type	Trial ID	Burst ID	Burst Offset (μs)	Chirp Width (MHz)	Number Of Pulses	Pulse Width (μs)	PRI1 (μs)	PRI2 (μs)	PRI3 (μs)
11AX20MI MO	5260	Type5	0	0	636184.0	13	2	54.1	1507.0	1536.0	---
		Type5	0	1	32644.0	13	1	98.1	1657.0	---	---
		Type5	0	2	226266.0	13	2	81.5	1391.0	---	---
		Type5	0	3	417977.0	13	1	78.3	1110.0	1291.0	1906.0
		Type5	0	4	616112.0	13	2	98.4	1976.0	1737.0	1975.0
		Type5	0	5	8777.0	13	2	63.0	1122.0	1778.0	---
		Type5	0	6	201111.0	13	2	64.9	1863.0	1022.0	---
		Type5	0	7	395566.0	13	3	83.8	1484.0	1232.0	---
		Type5	0	8	588566.0	13	1	73.3	1189.0	1172.0	---
		Type5	0	9	787799.0	13	3	69.7	1635.0	---	---
		Type5	0	10	188864.0	13	1	88.3	1141.0	1679.0	1251.0
		Type5	0	11	370566.0	13	2	86.3	1164.0	1205.0	1782.0
		Type5	0	12	564655.0	13	2	96.2	1505.0	1867.0	---
		Type5	0	13	759666.0	13	2	96.9	1955.0	---	---
		Type5	0	14	154652.0	13	1	54.5	1110.0	1548.0	1883.0
11AX40MI MO	5270	Type5	0	0	636184.0	13	2	54.1	1507.0	1536.0	---
		Type5	0	1	32644.0	13	1	98.1	1657.0	---	---
		Type5	0	2	226266.0	13	2	81.5	1391.0	---	---
		Type5	0	3	417977.0	13	1	78.3	1110.0	1291.0	1906.0
		Type5	0	4	616112.0	13	2	98.4	1976.0	1737.0	1975.0
		Type5	0	5	8777.0	13	2	63.0	1122.0	1778.0	---
		Type5	0	6	201111.0	13	2	64.9	1863.0	1022.0	---
		Type5	0	7	395566.0	13	3	83.8	1484.0	1232.0	---
		Type5	0	8	588566.0	13	1	73.3	1189.0	1172.0	---
		Type5	0	9	787799.0	13	3	69.7	1635.0	---	---
		Type5	0	10	188864.0	13	1	88.3	1141.0	1679.0	1251.0
		Type5	0	11	370566.0	13	2	86.3	1164.0	1205.0	1782.0
		Type5	0	12	564655.0	13	2	96.2	1505.0	1867.0	---
		Type5	0	13	759666.0	13	2	96.9	1955.0	---	---
		Type5	0	14	154652.0	13	1	54.5	1110.0	1548.0	1883.0
11AX80MI MO	5290	Type5	0	0	636184.0	13	2	54.1	1507.0	1536.0	---
		Type5	0	1	32644.0	13	1	98.1	1657.0	---	---
		Type5	0	2	226266.0	13	2	81.5	1391.0	---	---
		Type5	0	3	417977.0	13	1	78.3	1110.0	1291.0	1906.0
		Type5	0	4	616112.0	13	2	98.4	1976.0	1737.0	1975.0
		Type5	0	5	8777.0	13	2	63.0	1122.0	1778.0	---
		Type5	0	6	201111.0	13	2	64.9	1863.0	1022.0	---
		Type5	0	7	395566.0	13	3	83.8	1484.0	1232.0	---
		Type5	0	8	588566.0	13	1	73.3	1189.0	1172.0	---
		Type5	0	9	787799.0	13	3	69.7	1635.0	---	---
		Type5	0	10	188864.0	13	1	88.3	1141.0	1679.0	1251.0
		Type5	0	11	370566.0	13	2	86.3	1164.0	1205.0	1782.0
		Type5	0	12	564655.0	13	2	96.2	1505.0	1867.0	---
		Type5	0	13	759666.0	13	2	96.9	1955.0	---	---
		Type5	0	14	154652.0	13	1	54.5	1110.0	1548.0	1883.0
11AX160MI MO	5250	Type5	0	0	636184.0	13	2	54.1	1507.0	1536.0	---
		Type5	0	1	32644.0	13	1	98.1	1657.0	---	---
		Type5	0	2	226266.0	13	2	81.5	1391.0	---	---
		Type5	0	3	417977.0	13	1	78.3	1110.0	1291.0	1906.0
		Type5	0	4	616112.0	13	2	98.4	1976.0	1737.0	1975.0
		Type5	0	5	8777.0	13	2	63.0	1122.0	1778.0	---
		Type5	0	6	201111.0	13	2	64.9	1863.0	1022.0	---
		Type5	0	7	395566.0	13	3	83.8	1484.0	1232.0	---

	Type5	0	8	588566.0	13	1	73.3	1189.0	1172.0	---
	Type5	0	9	787799.0	13	3	69.7	1635.0	---	---
	Type5	0	10	188864.0	13	1	88.3	1141.0	1679.0	1251.0
	Type5	0	11	370566.0	13	2	86.3	1164.0	1205.0	1782.0
	Type5	0	12	564655.0	13	2	96.2	1505.0	1867.0	---
	Type5	0	13	759666.0	13	2	96.9	1955.0	---	---
	Type5	0	14	154652.0	13	1	54.5	1110.0	1548.0	1883.0

Test Mode	Channel	Radar Type	Trial ID	Burst ID	Burst Offset (μs)	Chirp Width (MHz)	Number Of Pulses	Pulse Width (μs)	PRI1 (μs)	PRI2 (μs)	PRI3 (μs)
11AX20MI MO	5260	Type5	1	0	643020.0	5	2	72.0	1780.0	1524.0	---
		Type5	1	1	1115643.0	5	3	95.4	1301.0	1252.0	1244.0
		Type5	1	2	1579398.0	5	2	66.4	1431.0	1453.0	---
		Type5	1	3	235489.0	5	2	76.6	1249.0	1034.0	---
		Type5	1	4	609513.0	5	1	64.9	1462.0	---	---
		Type5	1	5	970652.0	5	3	84.5	1346.0	1278.0	1399.0
		Type5	1	6	1335713.0	5	1	65.9	1542.0	---	---
		Type5	1	7	200906.0	5	3	97.5	1543.0	1791.0	1658.0
11AX40MI MO	5270	Type5	1	0	643020.0	5	2	72.0	1780.0	1524.0	---
		Type5	1	1	1115643.0	5	3	95.4	1301.0	1252.0	1244.0
		Type5	1	2	1579398.0	5	2	66.4	1431.0	1453.0	---
		Type5	1	3	235489.0	5	2	76.6	1249.0	1034.0	---
		Type5	1	4	609513.0	5	1	64.9	1462.0	---	---
		Type5	1	5	970652.0	5	3	84.5	1346.0	1278.0	1399.0
		Type5	1	6	1335713.0	5	1	65.9	1542.0	---	---
		Type5	1	7	200906.0	5	3	97.5	1543.0	1791.0	1658.0
11AX80MI MO	5290	Type5	1	0	643020.0	5	2	72.0	1780.0	1524.0	---
		Type5	1	1	1115643.0	5	3	95.4	1301.0	1252.0	1244.0
		Type5	1	2	1579398.0	5	2	66.4	1431.0	1453.0	---
		Type5	1	3	235489.0	5	2	76.6	1249.0	1034.0	---
		Type5	1	4	609513.0	5	1	64.9	1462.0	---	---
		Type5	1	5	970652.0	5	3	84.5	1346.0	1278.0	1399.0
		Type5	1	6	1335713.0	5	1	65.9	1542.0	---	---
		Type5	1	7	200906.0	5	3	97.5	1543.0	1791.0	1658.0
11AX160 MIMO	5250	Type5	1	0	643020.0	5	2	72.0	1780.0	1524.0	---
		Type5	1	1	1115643.0	5	3	95.4	1301.0	1252.0	1244.0
		Type5	1	2	1579398.0	5	2	66.4	1431.0	1453.0	---
		Type5	1	3	235489.0	5	2	76.6	1249.0	1034.0	---
		Type5	1	4	609513.0	5	1	64.9	1462.0	---	---
		Type5	1	5	970652.0	5	3	84.5	1346.0	1278.0	1399.0
		Type5	1	6	1335713.0	5	1	65.9	1542.0	---	---
		Type5	1	7	200906.0	5	3	97.5	1543.0	1791.0	1658.0

Test Mode	Channel	Radar Type	Trial ID	Burst ID	Burst Offset (μs)	Chirp Width (MHz)	Number Of Pulses	Pulse Width (μs)	PRI1 (μs)	PRI2 (μs)	PRI3 (μs)
11AX20MI MO	5260	Type5	2	0	525323.0	9	2	74.0	1126.0	1538.0	---
		Type5	2	1	218866.0	9	2	96.0	1113.0	1649.0	---
		Type5	2	2	754424.0	9	1	93.0	1817.0	---	---
		Type5	2	3	564916.0	9	3	57.0	1296.0	1032.0	1321.0
		Type5	2	4	130135.0	9	3	78.0	1483.0	1903.0	1233.0
		Type5	2	5	464485.0	9	2	75.0	1197.0	1351.0	---
		Type5	2	6	901284.0	9	3	93.0	1714.0	1514.0	1466.0
		Type5	2	7	762593.0	9	2	83.0	1222.0	1689.0	---
		Type5	2	8	919703.0	9	3	56.0	1393.0	1330.0	1688.0
		Type5	2	9	81991.0	9	1	62.0	1811.0	---	---
		Type5	2	10	746832.0	9	3	87.0	1282.0	1106.0	1011.0
11AX40MI MO	5270	Type5	2	0	525323.0	9	2	74.0	1126.0	1538.0	---
		Type5	2	1	218866.0	9	2	96.0	1113.0	1649.0	---
		Type5	2	2	754424.0	9	1	93.0	1817.0	---	---
		Type5	2	3	564916.0	9	3	57.0	1296.0	1032.0	1321.0
		Type5	2	4	130135.0	9	3	78.0	1483.0	1903.0	1233.0
		Type5	2	5	464485.0	9	2	75.0	1197.0	1351.0	---
		Type5	2	6	901284.0	9	3	93.0	1714.0	1514.0	1466.0
		Type5	2	7	762593.0	9	2	83.0	1222.0	1689.0	---
		Type5	2	8	919703.0	9	3	56.0	1393.0	1330.0	1688.0
		Type5	2	9	81991.0	9	1	62.0	1811.0	---	---
		Type5	2	10	746832.0	9	3	87.0	1282.0	1106.0	1011.0
11AX80MI MO	5290	Type5	2	0	525323.0	9	2	74.0	1126.0	1538.0	---
		Type5	2	1	218866.0	9	2	96.0	1113.0	1649.0	---
		Type5	2	2	754424.0	9	1	93.0	1817.0	---	---
		Type5	2	3	564916.0	9	3	57.0	1296.0	1032.0	1321.0
		Type5	2	4	130135.0	9	3	78.0	1483.0	1903.0	1233.0
		Type5	2	5	464485.0	9	2	75.0	1197.0	1351.0	---
		Type5	2	6	901284.0	9	3	93.0	1714.0	1514.0	1466.0
		Type5	2	7	762593.0	9	2	83.0	1222.0	1689.0	---
		Type5	2	8	919703.0	9	3	56.0	1393.0	1330.0	1688.0
		Type5	2	9	81991.0	9	1	62.0	1811.0	---	---
		Type5	2	10	746832.0	9	3	87.0	1282.0	1106.0	1011.0
11AX160MI MO	5250	Type5	2	0	525323.0	9	2	74.0	1126.0	1538.0	---
		Type5	2	1	218866.0	9	2	96.0	1113.0	1649.0	---
		Type5	2	2	754424.0	9	1	93.0	1817.0	---	---
		Type5	2	3	564916.0	9	3	57.0	1296.0	1032.0	1321.0
		Type5	2	4	130135.0	9	3	78.0	1483.0	1903.0	1233.0
		Type5	2	5	464485.0	9	2	75.0	1197.0	1351.0	---
		Type5	2	6	901284.0	9	3	93.0	1714.0	1514.0	1466.0
		Type5	2	7	762593.0	9	2	83.0	1222.0	1689.0	---
		Type5	2	8	919703.0	9	3	56.0	1393.0	1330.0	1688.0
		Type5	2	9	81991.0	9	1	62.0	1811.0	---	---
		Type5	2	10	746832.0	9	3	87.0	1282.0	1106.0	1011.0

Test Mode	Channel	Radar Type	Trial ID	Burst ID	Burst Offset (μs)	Chirp Width (MHz)	Number Of Pulses	Pulse Width (μs)	PRI1 (μs)	PRI2 (μs)	PRI3 (μs)
11AX20MI MO	5260	Type5	3	0	26541.0	19	2	68.1	1339.0	1355.0	---
		Type5	3	1	171821.0	19	1	58.7	1251.0	---	---
		Type5	3	2	316229.0	19	2	75.3	1136.0	1640.0	---
		Type5	3	3	461864.0	19	1	56.4	1753.0	---	---
		Type5	3	4	8677.0	19	3	99.7	1196.0	1708.0	1159.0
		Type5	3	5	153995.0	19	1	57.7	1013.0	---	---
		Type5	3	6	299238.0	19	1	59.5	1072.0	---	---
		Type5	3	7	443177.0	19	2	80.0	1482.0	1369.0	---
		Type5	3	8	587671.0	19	2	82.0	1993.0	1197.0	---
		Type5	3	9	135674.0	19	2	82.8	1883.0	1005.0	---
		Type5	3	10	279928.0	19	3	88.0	1061.0	1928.0	1101.0
		Type5	3	11	424279.0	19	3	93.2	1207.0	1907.0	1223.0
		Type5	3	12	570132.0	19	2	70.4	1526.0	1360.0	---
		Type5	3	13	117439.0	19	3	95.3	1171.0	1955.0	1775.0
		Type5	3	14	262502.0	19	2	81.9	1690.0	1545.0	---
		Type5	3	15	406573.0	19	3	98.5	1975.0	1169.0	1062.0
		Type5	3	16	553328.0	19	1	65.0	1767.0	---	---
		Type5	3	17	99799.0	19	3	85.4	1011.0	1637.0	1425.0
		Type5	3	18	244095.0	19	3	91.6	1878.0	1445.0	1325.0
		Type5	3	19	390012.0	19	2	67.3	1091.0	1218.0	---
11AX40MI MO	5270	Type5	3	0	26541.0	19	2	68.1	1339.0	1355.0	---
		Type5	3	1	171821.0	19	1	58.7	1251.0	---	---
		Type5	3	2	316229.0	19	2	75.3	1136.0	1640.0	---
		Type5	3	3	461864.0	19	1	56.4	1753.0	---	---
		Type5	3	4	8677.0	19	3	99.7	1196.0	1708.0	1159.0
		Type5	3	5	153995.0	19	1	57.7	1013.0	---	---
		Type5	3	6	299238.0	19	1	59.5	1072.0	---	---
		Type5	3	7	443177.0	19	2	80.0	1482.0	1369.0	---
		Type5	3	8	587671.0	19	2	82.0	1993.0	1197.0	---
		Type5	3	9	135674.0	19	2	82.8	1883.0	1005.0	---
		Type5	3	10	279928.0	19	3	88.0	1061.0	1928.0	1101.0
		Type5	3	11	424279.0	19	3	93.2	1207.0	1907.0	1223.0
		Type5	3	12	570132.0	19	2	70.4	1526.0	1360.0	---
		Type5	3	13	117439.0	19	3	95.3	1171.0	1955.0	1775.0
		Type5	3	14	262502.0	19	2	81.9	1690.0	1545.0	---
		Type5	3	15	406573.0	19	3	98.5	1975.0	1169.0	1062.0
		Type5	3	16	553328.0	19	1	65.0	1767.0	---	---
		Type5	3	17	99799.0	19	3	85.4	1011.0	1637.0	1425.0
		Type5	3	18	244095.0	19	3	91.6	1878.0	1445.0	1325.0
		Type5	3	19	390012.0	19	2	67.3	1091.0	1218.0	---
11AX80MI MO	5290	Type5	3	0	26541.0	19	2	68.1	1339.0	1355.0	---
		Type5	3	1	171821.0	19	1	58.7	1251.0	---	---
		Type5	3	2	316229.0	19	2	75.3	1136.0	1640.0	---
		Type5	3	3	461864.0	19	1	56.4	1753.0	---	---
		Type5	3	4	8677.0	19	3	99.7	1196.0	1708.0	1159.0
		Type5	3	5	153995.0	19	1	57.7	1013.0	---	---
		Type5	3	6	299238.0	19	1	59.5	1072.0	---	---
		Type5	3	7	443177.0	19	2	80.0	1482.0	1369.0	---
		Type5	3	8	587671.0	19	2	82.0	1993.0	1197.0	---
		Type5	3	9	135674.0	19	2	82.8	1883.0	1005.0	---
		Type5	3	10	279928.0	19	3	88.0	1061.0	1928.0	1101.0
		Type5	3	11	424279.0	19	3	93.2	1207.0	1907.0	1223.0
		Type5	3	12	570132.0	19	2	70.4	1526.0	1360.0	---
		Type5	3	13	117439.0	19	3	95.3	1171.0	1955.0	1775.0
		Type5	3	14	262502.0	19	2	81.9	1690.0	1545.0	---
		Type5	3	15	406573.0	19	3	98.5	1975.0	1169.0	1062.0
		Type5	3	16	553328.0	19	1	65.0	1767.0	---	---

		Type5	3	17	99799.0	19	3	85.4	1011.0	1637.0	1425.0
		Type5	3	18	244095.0	19	3	91.6	1878.0	1445.0	1325.0
11AX160MI MO	5250	Type5	3	19	390012.0	19	2	67.3	1091.0	1218.0	---
		Type5	3	0	26541.0	19	2	68.1	1339.0	1355.0	---
		Type5	3	1	171821.0	19	1	58.7	1251.0	---	---
		Type5	3	2	316229.0	19	2	75.3	1136.0	1640.0	---
		Type5	3	3	461864.0	19	1	56.4	1753.0	---	---
		Type5	3	4	8677.0	19	3	99.7	1196.0	1708.0	1159.0
		Type5	3	5	153995.0	19	1	57.7	1013.0	---	---
		Type5	3	6	299238.0	19	1	59.5	1072.0	---	---
		Type5	3	7	443177.0	19	2	80.0	1482.0	1369.0	---
		Type5	3	8	587671.0	19	2	82.0	1993.0	1197.0	---
		Type5	3	9	135674.0	19	2	82.8	1883.0	1005.0	---
		Type5	3	10	279928.0	19	3	88.0	1061.0	1928.0	1101.0
		Type5	3	11	424279.0	19	3	93.2	1207.0	1907.0	1223.0
		Type5	3	12	570132.0	19	2	70.4	1526.0	1360.0	---
		Type5	3	13	117439.0	19	3	95.3	1171.0	1955.0	1775.0
		Type5	3	14	262502.0	19	2	81.9	1690.0	1545.0	---
		Type5	3	15	406573.0	19	3	98.5	1975.0	1169.0	1062.0
		Type5	3	16	553328.0	19	1	65.0	1767.0	---	---
		Type5	3	17	99799.0	19	3	85.4	1011.0	1637.0	1425.0
		Type5	3	18	244095.0	19	3	91.6	1878.0	1445.0	1325.0
		Type5	3	19	390012.0	19	2	67.3	1091.0	1218.0	---

Test Mode	Channel	Radar Type	Trial ID	Burst ID	Burst Offset (μs)	Chirp Width (MHz)	Number Of Pulses	Pulse Width (μs)	PRI1 (μs)	PRI2 (μs)	PRI3 (μs)
11AX20MI MO	5260	Type5	4	0	582158.0	16	2	61.0	1872.0	1323.0	---
		Type5	4	1	152159.0	16	1	74.0	1847.0	---	---
		Type5	4	2	36680.0	16	1	78.0	1160.0	---	---
		Type5	4	3	502542.0	16	3	86.0	1495.0	1233.0	1436.0
		Type5	4	4	100348.0	16	2	67.0	1881.0	1876.0	---
		Type5	4	5	213387.0	16	3	79.0	1359.0	1352.0	1239.0
		Type5	4	6	96672.0	16	3	66.0	1099.0	1964.0	1239.0
		Type5	4	7	123456.0	16	2	84.0	1135.0	1556.0	---
		Type5	4	8	303939.0	16	1	54.0	1514.0	---	---
		Type5	4	9	560291.0	16	3	89.0	1058.0	1236.0	1756.0
		Type5	4	10	81912.0	16	2	81.0	1346.0	1785.0	---
		Type5	4	11	356653.0	16	3	79.0	1110.0	1335.0	1212.0
		Type5	4	12	409928.0	16	3	92.0	1471.0	1140.0	1644.0
		Type5	4	13	402432.0	16	3	57.0	1803.0	1233.0	1682.0
		Type5	4	14	340660.0	16	3	89.0	1807.0	1473.0	1551.0
		Type5	4	15	385402.0	16	3	76.0	1289.0	1318.0	1154.0
		Type5	4	16	36742.0	16	3	65.0	1505.0	1324.0	1328.0
11AX40MI MO	5270	Type5	4	0	582158.0	16	2	61.0	1872.0	1323.0	---
		Type5	4	1	152159.0	16	1	74.0	1847.0	---	---
		Type5	4	2	36680.0	16	1	78.0	1160.0	---	---
		Type5	4	3	502542.0	16	3	86.0	1495.0	1233.0	1436.0
		Type5	4	4	100348.0	16	2	67.0	1881.0	1876.0	---
		Type5	4	5	213387.0	16	3	79.0	1359.0	1352.0	1239.0
		Type5	4	6	96672.0	16	3	66.0	1099.0	1964.0	1239.0
		Type5	4	7	123456.0	16	2	84.0	1135.0	1556.0	---
		Type5	4	8	303939.0	16	1	54.0	1514.0	---	---
		Type5	4	9	560291.0	16	3	89.0	1058.0	1236.0	1756.0
		Type5	4	10	81912.0	16	2	81.0	1346.0	1785.0	---
		Type5	4	11	356653.0	16	3	79.0	1110.0	1335.0	1212.0
		Type5	4	12	409928.0	16	3	92.0	1471.0	1140.0	1644.0
		Type5	4	13	402432.0	16	3	57.0	1803.0	1233.0	1682.0
		Type5	4	14	340660.0	16	3	89.0	1807.0	1473.0	1551.0
		Type5	4	15	385402.0	16	3	76.0	1289.0	1318.0	1154.0
		Type5	4	16	36742.0	16	3	65.0	1505.0	1324.0	1328.0
11AX80MI MO	5290	Type5	4	0	582158.0	16	2	61.0	1872.0	1323.0	---
		Type5	4	1	152159.0	16	1	74.0	1847.0	---	---
		Type5	4	2	36680.0	16	1	78.0	1160.0	---	---
		Type5	4	3	502542.0	16	3	86.0	1495.0	1233.0	1436.0
		Type5	4	4	100348.0	16	2	67.0	1881.0	1876.0	---
		Type5	4	5	213387.0	16	3	79.0	1359.0	1352.0	1239.0
		Type5	4	6	96672.0	16	3	66.0	1099.0	1964.0	1239.0
		Type5	4	7	123456.0	16	2	84.0	1135.0	1556.0	---
		Type5	4	8	303939.0	16	1	54.0	1514.0	---	---
		Type5	4	9	560291.0	16	3	89.0	1058.0	1236.0	1756.0
		Type5	4	10	81912.0	16	2	81.0	1346.0	1785.0	---
		Type5	4	11	356653.0	16	3	79.0	1110.0	1335.0	1212.0
		Type5	4	12	409928.0	16	3	92.0	1471.0	1140.0	1644.0
		Type5	4	13	402432.0	16	3	57.0	1803.0	1233.0	1682.0
		Type5	4	14	340660.0	16	3	89.0	1807.0	1473.0	1551.0
		Type5	4	15	385402.0	16	3	76.0	1289.0	1318.0	1154.0
		Type5	4	16	36742.0	16	3	65.0	1505.0	1324.0	1328.0
11AX160MI MO	5250	Type5	4	0	582158.0	16	2	61.0	1872.0	1323.0	---
		Type5	4	1	152159.0	16	1	74.0	1847.0	---	---
		Type5	4	2	36680.0	16	1	78.0	1160.0	---	---
		Type5	4	3	502542.0	16	3	86.0	1495.0	1233.0	1436.0
		Type5	4	4	100348.0	16	2	67.0	1881.0	1876.0	---
		Type5	4	5	213387.0	16	3	79.0	1359.0	1352.0	1239.0

	Type5	4	6	96672.0	16	3	66.0	1099.0	1964.0	1239.0
	Type5	4	7	123456.0	16	2	84.0	1135.0	1556.0	---
	Type5	4	8	303939.0	16	1	54.0	1514.0	---	---
	Type5	4	9	560291.0	16	3	89.0	1058.0	1236.0	1756.0
	Type5	4	10	81912.0	16	2	81.0	1346.0	1785.0	---
	Type5	4	11	356653.0	16	3	79.0	1110.0	1335.0	1212.0
	Type5	4	12	409928.0	16	3	92.0	1471.0	1140.0	1644.0
	Type5	4	13	402432.0	16	3	57.0	1803.0	1233.0	1682.0
	Type5	4	14	340660.0	16	3	89.0	1807.0	1473.0	1551.0
	Type5	4	15	385402.0	16	3	76.0	1289.0	1318.0	1154.0
	Type5	4	16	36742.0	16	3	65.0	1505.0	1324.0	1328.0

Test Mode	Channel	Radar Type	Trial ID	Burst ID	Burst Offset (μs)	Chirp Width (MHz)	Number Of Pulses	Pulse Width (μs)	PRI1 (μs)	PRI2 (μs)	PRI3 (μs)
11AX20MI MO	5260	Type5	5	0	33196.0	12	3	67.0	1032.0	1654.0	1466.0
		Type5	5	1	327526.0	12	2	59.0	1481.0	1447.0	---
		Type5	5	2	427894.0	12	1	59.0	1472.0	---	---
		Type5	5	3	173576.0	12	1	59.0	1048.0	---	---
		Type5	5	4	174486.0	12	1	74.0	1363.0	---	---
		Type5	5	5	458781.0	12	3	54.0	1373.0	1730.0	1965.0
		Type5	5	6	216715.0	12	1	95.0	1061.0	---	---
		Type5	5	7	574313.0	12	3	81.0	1110.0	1364.0	1468.0
		Type5	5	8	227142.0	12	2	83.0	1300.0	1746.0	---
		Type5	5	9	506930.0	12	2	60.0	1324.0	1644.0	---
		Type5	5	10	332900.0	12	3	68.0	1300.0	1444.0	1877.0
		Type5	5	11	120743.0	12	1	85.0	1636.0	---	---
		Type5	5	12	417794.0	12	2	97.0	1254.0	1625.0	---
11AX40MI MO	5270	Type5	5	0	33196.0	12	3	67.0	1032.0	1654.0	1466.0
		Type5	5	1	327526.0	12	2	59.0	1481.0	1447.0	---
		Type5	5	2	427894.0	12	1	59.0	1472.0	---	---
		Type5	5	3	173576.0	12	1	59.0	1048.0	---	---
		Type5	5	4	174486.0	12	1	74.0	1363.0	---	---
		Type5	5	5	458781.0	12	3	54.0	1373.0	1730.0	1965.0
		Type5	5	6	216715.0	12	1	95.0	1061.0	---	---
		Type5	5	7	574313.0	12	3	81.0	1110.0	1364.0	1468.0
		Type5	5	8	227142.0	12	2	83.0	1300.0	1746.0	---
		Type5	5	9	506930.0	12	2	60.0	1324.0	1644.0	---
		Type5	5	10	332900.0	12	3	68.0	1300.0	1444.0	1877.0
		Type5	5	11	120743.0	12	1	85.0	1636.0	---	---
		Type5	5	12	417794.0	12	2	97.0	1254.0	1625.0	---
11AX80MI MO	5290	Type5	5	0	33196.0	12	3	67.0	1032.0	1654.0	1466.0
		Type5	5	1	327526.0	12	2	59.0	1481.0	1447.0	---
		Type5	5	2	427894.0	12	1	59.0	1472.0	---	---
		Type5	5	3	173576.0	12	1	59.0	1048.0	---	---
		Type5	5	4	174486.0	12	1	74.0	1363.0	---	---
		Type5	5	5	458781.0	12	3	54.0	1373.0	1730.0	1965.0
		Type5	5	6	216715.0	12	1	95.0	1061.0	---	---
		Type5	5	7	574313.0	12	3	81.0	1110.0	1364.0	1468.0
		Type5	5	8	227142.0	12	2	83.0	1300.0	1746.0	---
		Type5	5	9	506930.0	12	2	60.0	1324.0	1644.0	---
		Type5	5	10	332900.0	12	3	68.0	1300.0	1444.0	1877.0
		Type5	5	11	120743.0	12	1	85.0	1636.0	---	---
		Type5	5	12	417794.0	12	2	97.0	1254.0	1625.0	---

11AX160MI MO	5250	Type5	5	13	296740.0	12	2	54.0	1927.0	1846.0	---
		Type5	5	0	33196.0	12	3	67.0	1032.0	1654.0	1466.0
		Type5	5	1	327526.0	12	2	59.0	1481.0	1447.0	---
		Type5	5	2	427894.0	12	1	59.0	1472.0	---	---
		Type5	5	3	173576.0	12	1	59.0	1048.0	---	---
		Type5	5	4	174486.0	12	1	74.0	1363.0	---	---
		Type5	5	5	458781.0	12	3	54.0	1373.0	1730.0	1965.0
		Type5	5	6	216715.0	12	1	95.0	1061.0	---	---
		Type5	5	7	574313.0	12	3	81.0	1110.0	1364.0	1468.0
		Type5	5	8	227142.0	12	2	83.0	1300.0	1746.0	---
		Type5	5	9	506930.0	12	2	60.0	1324.0	1644.0	---
		Type5	5	10	332900.0	12	3	68.0	1300.0	1444.0	1877.0
		Type5	5	11	120743.0	12	1	85.0	1636.0	---	---
		Type5	5	12	417794.0	12	2	97.0	1254.0	1625.0	---
		Type5	5	13	296740.0	12	2	54.0	1927.0	1846.0	---

Test Mode	Channel	Radar Type	Trial ID	Burst ID	Burst Offset (μs)	Chirp Width (MHz)	Number Of Pulses	Pulse Width (μs)	PRI1 (μs)	PRI2 (μs)	PRI3 (μs)
11AX20MI MO	5260	Type5	6	0	446104.0	13	3	58.0	1125.0	1659.0	1351.0
		Type5	6	1	478298.0	13	3	73.0	1653.0	1779.0	1754.0
		Type5	6	2	99392.0	13	3	74.0	1924.0	1296.0	1355.0
		Type5	6	3	132638.0	13	2	92.0	1280.0	1658.0	---
		Type5	6	4	375546.0	13	1	90.0	1248.0	---	---
		Type5	6	5	168317.0	13	1	73.0	1249.0	---	---
		Type5	6	6	303142.0	13	3	73.0	1945.0	1424.0	1230.0
		Type5	6	7	208009.0	13	2	98.0	1397.0	1663.0	---
		Type5	6	8	225405.0	13	1	90.0	1508.0	---	---
		Type5	6	9	49240.0	13	2	81.0	1168.0	1568.0	---
		Type5	6	10	356481.0	13	2	61.0	1527.0	1115.0	---
		Type5	6	11	599705.0	13	2	55.0	1864.0	1631.0	---
		Type5	6	12	564909.0	13	3	64.0	1030.0	1130.0	1239.0
		Type5	6	13	558428.0	13	1	70.0	1315.0	---	---
		Type5	6	14	438060.0	13	3	55.0	1149.0	1762.0	1567.0
11AX40MI MO	5270	Type5	6	0	446104.0	13	3	58.0	1125.0	1659.0	1351.0
		Type5	6	1	478298.0	13	3	73.0	1653.0	1779.0	1754.0
		Type5	6	2	99392.0	13	3	74.0	1924.0	1296.0	1355.0
		Type5	6	3	132638.0	13	2	92.0	1280.0	1658.0	---
		Type5	6	4	375546.0	13	1	90.0	1248.0	---	---
		Type5	6	5	168317.0	13	1	73.0	1249.0	---	---
		Type5	6	6	303142.0	13	3	73.0	1945.0	1424.0	1230.0
		Type5	6	7	208009.0	13	2	98.0	1397.0	1663.0	---
		Type5	6	8	225405.0	13	1	90.0	1508.0	---	---
		Type5	6	9	49240.0	13	2	81.0	1168.0	1568.0	---
		Type5	6	10	356481.0	13	2	61.0	1527.0	1115.0	---
		Type5	6	11	599705.0	13	2	55.0	1864.0	1631.0	---
		Type5	6	12	564909.0	13	3	64.0	1030.0	1130.0	1239.0
		Type5	6	13	558428.0	13	1	70.0	1315.0	---	---
		Type5	6	14	438060.0	13	3	55.0	1149.0	1762.0	1567.0
11AX80MI MO	5290	Type5	6	0	446104.0	13	3	58.0	1125.0	1659.0	1351.0
		Type5	6	1	478298.0	13	3	73.0	1653.0	1779.0	1754.0
		Type5	6	2	99392.0	13	3	74.0	1924.0	1296.0	1355.0
		Type5	6	3	132638.0	13	2	92.0	1280.0	1658.0	---
		Type5	6	4	375546.0	13	1	90.0	1248.0	---	---
		Type5	6	5	168317.0	13	1	73.0	1249.0	---	---

		Type5	6	6	303142.0	13	3	73.0	1945.0	1424.0	1230.0
		Type5	6	7	208009.0	13	2	98.0	1397.0	1663.0	---
		Type5	6	8	225405.0	13	1	90.0	1508.0	---	---
		Type5	6	9	49240.0	13	2	81.0	1168.0	1568.0	---
		Type5	6	10	356481.0	13	2	61.0	1527.0	1115.0	---
		Type5	6	11	599705.0	13	2	55.0	1864.0	1631.0	---
		Type5	6	12	564909.0	13	3	64.0	1030.0	1130.0	1239.0
		Type5	6	13	558428.0	13	1	70.0	1315.0	---	---
11AX160MI MO	5250	Type5	6	14	438060.0	13	3	55.0	1149.0	1762.0	1567.0
		Type5	6	0	446104.0	13	3	58.0	1125.0	1659.0	1351.0
		Type5	6	1	478298.0	13	3	73.0	1653.0	1779.0	1754.0
		Type5	6	2	99392.0	13	3	74.0	1924.0	1296.0	1355.0
		Type5	6	3	132638.0	13	2	92.0	1280.0	1658.0	---
		Type5	6	4	375546.0	13	1	90.0	1248.0	---	---
		Type5	6	5	168317.0	13	1	73.0	1249.0	---	---
		Type5	6	6	303142.0	13	3	73.0	1945.0	1424.0	1230.0
		Type5	6	7	208009.0	13	2	98.0	1397.0	1663.0	---
		Type5	6	8	225405.0	13	1	90.0	1508.0	---	---
		Type5	6	9	49240.0	13	2	81.0	1168.0	1568.0	---
		Type5	6	10	356481.0	13	2	61.0	1527.0	1115.0	---
		Type5	6	11	599705.0	13	2	55.0	1864.0	1631.0	---
		Type5	6	12	564909.0	13	3	64.0	1030.0	1130.0	1239.0
		Type5	6	13	558428.0	13	1	70.0	1315.0	---	---
		Type5	6	14	438060.0	13	3	55.0	1149.0	1762.0	1567.0

Test Mode	Channel	Radar Type	Trial ID	Burst ID	Burst Offset (μs)	Chirp Width (MHz)	Number Of Pulses	Pulse Width (μs)	PRI1 (μs)	PRI2 (μs)	PRI3 (μs)
11AX20MI MO	5260	Type5	7	0	482736.0	10	1	48.0	1971.0	---	---
		Type5	7	1	547771.0	10	3	77.0	1211.0	1625.0	1129.0
		Type5	7	2	175579.0	10	3	34.0	1288.0	1768.0	1905.0
		Type5	7	3	204708.0	10	3	61.0	1566.0	1346.0	1755.0
		Type5	7	4	350287.0	10	3	33.0	1769.0	1786.0	1602.0
		Type5	7	5	369969.0	10	2	89.0	1283.0	1284.0	---
		Type5	7	6	155041.0	10	2	63.0	1758.0	1427.0	---
		Type5	7	7	308104.0	10	2	49.0	1381.0	1861.0	---
		Type5	7	8	127043.0	10	1	28.0	1755.0	---	---
		Type5	7	9	193078.0	10	1	69.0	1690.0	---	---
		Type5	7	10	178577.0	10	2	29.0	1377.0	1504.0	---
11AX40MI MO	5270	Type5	7	11	526319.0	10	3	65.0	1309.0	1112.0	1583.0
		Type5	7	0	482736.0	10	1	48.0	1971.0	---	---
		Type5	7	1	547771.0	10	3	77.0	1211.0	1625.0	1129.0
		Type5	7	2	175579.0	10	3	34.0	1288.0	1768.0	1905.0
		Type5	7	3	204708.0	10	3	61.0	1566.0	1346.0	1755.0
		Type5	7	4	350287.0	10	3	33.0	1769.0	1786.0	1602.0
		Type5	7	5	369969.0	10	2	89.0	1283.0	1284.0	---
		Type5	7	6	155041.0	10	2	63.0	1758.0	1427.0	---
		Type5	7	7	308104.0	10	2	49.0	1381.0	1861.0	---
		Type5	7	8	127043.0	10	1	28.0	1755.0	---	---
		Type5	7	9	193078.0	10	1	69.0	1690.0	---	---
11AX80MI MO	5290	Type5	7	10	178577.0	10	2	29.0	1377.0	1504.0	---
		Type5	7	11	526319.0	10	3	65.0	1309.0	1112.0	1583.0
		Type5	7	0	482736.0	10	1	48.0	1971.0	---	---
		Type5	7	1	547771.0	10	3	77.0	1211.0	1625.0	1129.0
		Type5	7	2	175579.0	10	3	34.0	1288.0	1768.0	1905.0

		Type5	7	3	204708.0	10	3	61.0	1566.0	1346.0	1755.0
		Type5	7	4	350287.0	10	3	33.0	1769.0	1786.0	1602.0
		Type5	7	5	369969.0	10	2	89.0	1283.0	1284.0	---
		Type5	7	6	155041.0	10	2	63.0	1758.0	1427.0	---
		Type5	7	7	308104.0	10	2	49.0	1381.0	1861.0	---
		Type5	7	8	127043.0	10	1	28.0	1755.0	---	---
		Type5	7	9	193078.0	10	1	69.0	1690.0	---	---
		Type5	7	10	178577.0	10	2	29.0	1377.0	1504.0	---
11AX160MI MO	5250	Type5	7	11	526319.0	10	3	65.0	1309.0	1112.0	1583.0
		Type5	7	0	482736.0	10	1	48.0	1971.0	---	---
		Type5	7	1	547771.0	10	3	77.0	1211.0	1625.0	1129.0
		Type5	7	2	175579.0	10	3	34.0	1288.0	1768.0	1905.0
		Type5	7	3	204708.0	10	3	61.0	1566.0	1346.0	1755.0
		Type5	7	4	350287.0	10	3	33.0	1769.0	1786.0	1602.0
		Type5	7	5	369969.0	10	2	89.0	1283.0	1284.0	---
		Type5	7	6	155041.0	10	2	63.0	1758.0	1427.0	---
		Type5	7	7	308104.0	10	2	49.0	1381.0	1861.0	---
		Type5	7	8	127043.0	10	1	28.0	1755.0	---	---
		Type5	7	9	193078.0	10	1	69.0	1690.0	---	---
		Type5	7	10	178577.0	10	2	29.0	1377.0	1504.0	---
		Type5	7	11	526319.0	10	3	65.0	1309.0	1112.0	1583.0

Test Mode	Channel	Radar Type	Trial ID	Burst ID	Burst Offset (μs)	Chirp Width (MHz)	Number Of Pulses	Pulse Width (μs)	PRI1 (μs)	PRI2 (μs)	PRI3 (μs)
11AX20MI MO	5260	Type5	8	0	622605.0	13	1	81.0	1331.0	---	---
		Type5	8	1	585994.0	13	1	85.0	1840.0	---	---
		Type5	8	2	327287.0	13	1	64.0	1573.0	---	---
		Type5	8	3	210430.0	13	3	54.0	1682.0	1466.0	1949.0
		Type5	8	4	577806.0	13	2	83.0	1529.0	1129.0	---
		Type5	8	5	289309.0	13	2	23.0	1955.0	1755.0	---
		Type5	8	6	672361.0	13	1	20.0	1867.0	---	---
		Type5	8	7	296337.0	13	2	23.0	1745.0	1334.0	---
		Type5	8	8	636533.0	13	1	79.0	1393.0	---	---
		Type5	8	9	234095.0	13	1	79.0	1988.0	---	---
		Type5	8	10	376503.0	13	1	63.0	1860.0	---	---
		Type5	8	11	472072.0	13	3	48.0	1791.0	1650.0	1347.0
		Type5	8	12	690663.0	13	2	28.0	1613.0	1742.0	---
		Type5	8	13	178273.0	13	1	78.0	1611.0	---	---
11AX40MI MO	5270	Type5	8	0	622605.0	13	1	81.0	1331.0	---	---
		Type5	8	1	585994.0	13	1	85.0	1840.0	---	---
		Type5	8	2	327287.0	13	1	64.0	1573.0	---	---
		Type5	8	3	210430.0	13	3	54.0	1682.0	1466.0	1949.0
		Type5	8	4	577806.0	13	2	83.0	1529.0	1129.0	---
		Type5	8	5	289309.0	13	2	23.0	1955.0	1755.0	---
		Type5	8	6	672361.0	13	1	20.0	1867.0	---	---
		Type5	8	7	296337.0	13	2	23.0	1745.0	1334.0	---
		Type5	8	8	636533.0	13	1	79.0	1393.0	---	---
		Type5	8	9	234095.0	13	1	79.0	1988.0	---	---
		Type5	8	10	376503.0	13	1	63.0	1860.0	---	---
		Type5	8	11	472072.0	13	3	48.0	1791.0	1650.0	1347.0
		Type5	8	12	690663.0	13	2	28.0	1613.0	1742.0	---
		Type5	8	13	178273.0	13	1	78.0	1611.0	---	---
11AX80MI MO	5290	Type5	8	0	622605.0	13	1	81.0	1331.0	---	---
		Type5	8	1	585994.0	13	1	85.0	1840.0	---	---

		Type5	8	2	327287.0	13	1	64.0	1573.0	---	---
		Type5	8	3	210430.0	13	3	54.0	1682.0	1466.0	1949.0
		Type5	8	4	577806.0	13	2	83.0	1529.0	1129.0	---
		Type5	8	5	289309.0	13	2	23.0	1955.0	1755.0	---
		Type5	8	6	672361.0	13	1	20.0	1867.0	---	---
		Type5	8	7	296337.0	13	2	23.0	1745.0	1334.0	---
		Type5	8	8	636533.0	13	1	79.0	1393.0	---	---
		Type5	8	9	234095.0	13	1	79.0	1988.0	---	---
		Type5	8	10	376503.0	13	1	63.0	1860.0	---	---
		Type5	8	11	472072.0	13	3	48.0	1791.0	1650.0	1347.0
		Type5	8	12	690663.0	13	2	28.0	1613.0	1742.0	---
		Type5	8	13	178273.0	13	1	78.0	1611.0	---	---
11AX160MI MO	5250	Type5	8	0	622605.0	13	1	81.0	1331.0	---	---
		Type5	8	1	585994.0	13	1	85.0	1840.0	---	---
		Type5	8	2	327287.0	13	1	64.0	1573.0	---	---
		Type5	8	3	210430.0	13	3	54.0	1682.0	1466.0	1949.0
		Type5	8	4	577806.0	13	2	83.0	1529.0	1129.0	---
		Type5	8	5	289309.0	13	2	23.0	1955.0	1755.0	---
		Type5	8	6	672361.0	13	1	20.0	1867.0	---	---
		Type5	8	7	296337.0	13	2	23.0	1745.0	1334.0	---
		Type5	8	8	636533.0	13	1	79.0	1393.0	---	---
		Type5	8	9	234095.0	13	1	79.0	1988.0	---	---
		Type5	8	10	376503.0	13	1	63.0	1860.0	---	---
		Type5	8	11	472072.0	13	3	48.0	1791.0	1650.0	1347.0
		Type5	8	12	690663.0	13	2	28.0	1613.0	1742.0	---
		Type5	8	13	178273.0	13	1	78.0	1611.0	---	---

Test Mode	Channel	Radar Type	Trial ID	Burst ID	Burst Offset (μs)	Chirp Width (MHz)	Number Of Pulses	Pulse Width (μs)	PRI1 (μs)	PRI2 (μs)	PRI3 (μs)
11AX20MI MO	5260	Type5	9	0	65475.0	6	1	72.0	1367.0	---	---
		Type5	9	1	725425.0	6	1	79.0	1489.0	---	---
		Type5	9	2	670248.0	6	3	49.0	1731.0	1555.0	1383.0
		Type5	9	3	726276.0	6	2	64.0	1976.0	1463.0	---
		Type5	9	4	303641.0	6	2	84.0	1658.0	1332.0	---
		Type5	9	5	219404.0	6	3	61.0	1433.0	1564.0	1583.0
		Type5	9	6	504870.0	6	1	51.0	1335.0	---	---
11AX40MI MO	5270	Type5	9	7	263373.0	6	3	87.0	1276.0	1655.0	1361.0
		Type5	9	0	65475.0	6	1	72.0	1367.0	---	---
		Type5	9	1	725425.0	6	1	79.0	1489.0	---	---
		Type5	9	2	670248.0	6	3	49.0	1731.0	1555.0	1383.0
		Type5	9	3	726276.0	6	2	64.0	1976.0	1463.0	---
		Type5	9	4	303641.0	6	2	84.0	1658.0	1332.0	---
		Type5	9	5	219404.0	6	3	61.0	1433.0	1564.0	1583.0
11AX80MI MO	5290	Type5	9	6	504870.0	6	1	51.0	1335.0	---	---
		Type5	9	7	263373.0	6	3	87.0	1276.0	1655.0	1361.0
		Type5	9	0	65475.0	6	1	72.0	1367.0	---	---
		Type5	9	1	725425.0	6	1	79.0	1489.0	---	---
		Type5	9	2	670248.0	6	3	49.0	1731.0	1555.0	1383.0
		Type5	9	3	726276.0	6	2	64.0	1976.0	1463.0	---
		Type5	9	4	303641.0	6	2	84.0	1658.0	1332.0	---
11AX160MI MO	5250	Type5	9	5	219404.0	6	3	61.0	1433.0	1564.0	1583.0
		Type5	9	6	504870.0	6	1	51.0	1335.0	---	---
		Type5	9	7	263373.0	6	3	87.0	1276.0	1655.0	1361.0
		Type5	9	0	65475.0	6	1	72.0	1367.0	---	---
		Type5	9	1	725425.0	6	1	79.0	1489.0	---	---
		Type5	9	2	670248.0	6	3	49.0	1731.0	1555.0	1383.0
		Type5	9	3	726276.0	6	2	64.0	1976.0	1463.0	---
		Type5	9	4	303641.0	6	2	84.0	1658.0	1332.0	---
		Type5	9	5	219404.0	6	3	61.0	1433.0	1564.0	1583.0
		Type5	9	6	504870.0	6	1	51.0	1335.0	---	---
		Type5	9	7	263373.0	6	3	87.0	1276.0	1655.0	1361.0
		Type5	9	0	65475.0	6	1	72.0	1367.0	---	---
		Type5	9	1	725425.0	6	1	79.0	1489.0	---	---
		Type5	9	2	670248.0	6	3	49.0	1731.0	1555.0	1383.0
		Type5	9	3	726276.0	6	2	64.0	1976.0	1463.0	---
		Type5	9	4	303641.0	6	2	84.0	1658.0	1332.0	---
		Type5	9	5	219404.0	6	3	61.0	1433.0	1564.0	1583.0
		Type5	9	6	504870.0	6	1	51.0	1335.0	---	---
		Type5	9	7	263373.0	6	3	87.0	1276.0	1655.0	1361.0
		Type5	9	0	65475.0	6	1	72.0	1367.0	---	---
		Type5	9	1	725425.0	6	1	79.0	1489.0	---	---
		Type5	9	2	670248.0	6	3	49.0	1731.0	1555.0	1383.0
		Type5	9	3	726276.0	6	2	64.0	1976.0	1463.0	---
		Type5	9	4	303641.0	6	2	84.0	1658.0	1332.0	---
		Type5	9	5	219404.0	6	3	61.0	1433.0	1564.0	1583.0
		Type5	9	6	504870.0	6	1	51.0	1335.0	---	---
		Type5	9	7	263373.0	6	3	87.0	1276.0	1655.0	1361.0
		Type5	9	0	65475.0	6	1	72.0	1367.0	---	---
		Type5	9	1	725425.0	6	1	79.0	1489.0	---	---
		Type5	9	2	670248.0	6	3	49.0	1731.0	1555.0	1383.0
		Type5	9	3	726276.0	6	2	64.0	1976.0	1463.0	---
		Type5	9	4	303641.0	6	2	84.0	1658.0	1332.0	---
		Type5	9	5	219404.0	6	3	61.0	1433.0	1564.0	1583.0
		Type5	9	6	504870.0	6	1	51.0	1335.0	---	---
		Type5	9	7	263373.0	6	3	87.0	1276.0	1655.0	1361.0
		Type5	9	0	65475.0	6	1	72.0	1367.0	---	---
		Type5	9	1	725425.0	6	1	79.0	1489.0	---	---
		Type5	9	2	670248.0	6	3	49.0	1731.0	1555.0	1383.0
		Type5	9	3	726276.0	6	2	64.0	1976.0	1463.0	---
		Type5	9	4	303641.0	6	2	84.0	1658.0	1332.0	---
		Type5	9	5	219404.0	6	3	61.0	1433.0	1564.0	1583.0
		Type5	9	6	504870.0	6	1	51.0	1335.0	---	---
		Type5	9	7	263373.0	6	3	87.0	1276.0	1655.0	1361.0
		Type5	9	0	65475.0	6	1	72.0	1367.0	---	---
		Type5	9	1	725425.0	6	1	79.0	1489.0	---	---
		Type5	9	2	670248.0	6	3	49.0	1731.0	1555.0	1383.0
		Type5	9	3	726276.0	6	2	64.0	1976.0	1463.0	---
		Type5	9	4	303641.0	6	2	84.0	1658.0	1332.0	---
		Type5	9	5	219404.0	6	3	61.0	1433.0	1564.0	1583.0
		Type5	9	6	504870.0	6	1	51.0	1335.0	---	---
		Type5	9	7	263373.0	6	3	87.0	1276.0	1655.0	1361.0
		Type5	9	0	65475.0	6	1	72.0	1367.0	---	---
		Type5	9	1	725425.0	6	1	79.0	1489.0	---	---
		Type5	9	2	670248.0	6	3	49.0	1731.0	1555.0	1383.0
		Type5	9	3	726276.0	6	2	64.0	1976.0	1463.0	---
		Type5	9	4	303641.0	6	2	84.0	1658.0	1332.0	---
		Type5	9	5	219404.0	6	3	61.0	1433.0	1564.0	1583.0
		Type5	9	6	504870.0	6	1	51.0	1335.0	---	---
		Type5	9	7	263373.0	6	3	87.0	1276.0	1655.0	1361.0
		Type5	9	0	65475.0	6	1	72.0	1367.0	---	---
		Type5	9	1	725425.0	6	1	79.0	1489.0	---	---
		Type5	9	2	670248.0	6	3	49.0	1731.0	1555.0	1383.0
		Type5	9	3	726276.0	6	2	64.0	1976.0	1463.0	---
		Type5	9	4	303641.0	6	2	84.0	1658.0	1332.0	---
		Type5	9	5	219404.0	6	3	61.0	1433.0	1564.0	1583.0
		Type5	9	6	504870.0	6	1	51.0	1335.0	---	---
		Type5	9	7	263373.0	6	3	87.0	1276.0	1655.0	1361.0
		Type5	9	0	65475.0	6	1	72.0	1367.0	---	---

	Type5	9	2	670248.0	6	3	49.0	1731.0	1555.0	1383.0
	Type5	9	3	726276.0	6	2	64.0	1976.0	1463.0	---
	Type5	9	4	303641.0	6	2	84.0	1658.0	1332.0	---
	Type5	9	5	219404.0	6	3	61.0	1433.0	1564.0	1583.0
	Type5	9	6	504870.0	6	1	51.0	1335.0	---	---
	Type5	9	7	263373.0	6	3	87.0	1276.0	1655.0	1361.0

Test Mode	Channel	Radar Type	Trial ID	Burst ID	Burst Offset (μs)	Chirp Width (MHz)	Number Of Pulses	Pulse Width (μs)	PRI1 (μs)	PRI2 (μs)	PRI3 (μs)
11AX20MI MO	5260	Type5	10	0	572708.0	16	2	47.0	1412.0	1327.0	---
		Type5	10	1	421625.0	16	3	41.0	1945.0	1454.0	1613.0
		Type5	10	2	250949.0	16	3	73.0	1893.0	1662.0	1462.0
		Type5	10	3	681692.0	16	1	67.0	1875.0	---	---
		Type5	10	4	293667.0	16	2	28.0	1247.0	1781.0	---
		Type5	10	5	325390.0	16	1	83.0	1747.0	---	---
		Type5	10	6	679238.0	16	2	23.0	1444.0	1654.0	---
		Type5	10	7	153968.0	16	2	83.0	1210.0	1258.0	---
		Type5	10	8	167955.0	16	2	60.0	1493.0	1454.0	---
		Type5	10	9	356028.0	16	1	63.0	1372.0	---	---
		Type5	10	10	618765.0	16	2	70.0	1319.0	1544.0	---
		Type5	10	11	695440.0	16	2	42.0	1352.0	1653.0	---
		Type5	10	12	477340.0	16	2	35.0	1845.0	1352.0	---
		Type5	10	13	456510.0	16	2	32.0	1834.0	1471.0	---
		Type5	10	14	146421.0	16	1	31.0	1220.0	---	---
		Type5	10	15	87977.0	16	2	75.0	1317.0	1653.0	---
		Type5	10	16	158238.0	16	1	56.0	1703.0	---	---
11AX40MI MO	5270	Type5	10	0	572708.0	16	2	47.0	1412.0	1327.0	---
		Type5	10	1	421625.0	16	3	41.0	1945.0	1454.0	1613.0
		Type5	10	2	250949.0	16	3	73.0	1893.0	1662.0	1462.0
		Type5	10	3	681692.0	16	1	67.0	1875.0	---	---
		Type5	10	4	293667.0	16	2	28.0	1247.0	1781.0	---
		Type5	10	5	325390.0	16	1	83.0	1747.0	---	---
		Type5	10	6	679238.0	16	2	23.0	1444.0	1654.0	---
		Type5	10	7	153968.0	16	2	83.0	1210.0	1258.0	---
		Type5	10	8	167955.0	16	2	60.0	1493.0	1454.0	---
		Type5	10	9	356028.0	16	1	63.0	1372.0	---	---
		Type5	10	10	618765.0	16	2	70.0	1319.0	1544.0	---
		Type5	10	11	695440.0	16	2	42.0	1352.0	1653.0	---
		Type5	10	12	477340.0	16	2	35.0	1845.0	1352.0	---
		Type5	10	13	456510.0	16	2	32.0	1834.0	1471.0	---
		Type5	10	14	146421.0	16	1	31.0	1220.0	---	---
		Type5	10	15	87977.0	16	2	75.0	1317.0	1653.0	---
		Type5	10	16	158238.0	16	1	56.0	1703.0	---	---
11AX80MI MO	5290	Type5	10	0	572708.0	16	2	47.0	1412.0	1327.0	---
		Type5	10	1	421625.0	16	3	41.0	1945.0	1454.0	1613.0
		Type5	10	2	250949.0	16	3	73.0	1893.0	1662.0	1462.0
		Type5	10	3	681692.0	16	1	67.0	1875.0	---	---
		Type5	10	4	293667.0	16	2	28.0	1247.0	1781.0	---
		Type5	10	5	325390.0	16	1	83.0	1747.0	---	---
		Type5	10	6	679238.0	16	2	23.0	1444.0	1654.0	---
		Type5	10	7	153968.0	16	2	83.0	1210.0	1258.0	---
		Type5	10	8	167955.0	16	2	60.0	1493.0	1454.0	---
		Type5	10	9	356028.0	16	1	63.0	1372.0	---	---
		Type5	10	10	618765.0	16	2	70.0	1319.0	1544.0	---
		Type5	10	11	695440.0	16	2	42.0	1352.0	1653.0	---

		Type5	10	12	477340.0	16	2	35.0	1845.0	1352.0	---
		Type5	10	13	456510.0	16	2	32.0	1834.0	1471.0	---
		Type5	10	14	146421.0	16	1	31.0	1220.0	---	---
		Type5	10	15	87977.0	16	2	75.0	1317.0	1653.0	---
		Type5	10	16	158238.0	16	1	56.0	1703.0	---	---
11AX80MI MO	5290	Type5	10	0	572708.0	16	2	47.0	1412.0	1327.0	---
		Type5	10	1	421625.0	16	3	41.0	1945.0	1454.0	1613.0
		Type5	10	2	250949.0	16	3	73.0	1893.0	1662.0	1462.0
		Type5	10	3	681692.0	16	1	67.0	1875.0	---	---
		Type5	10	4	293667.0	16	2	28.0	1247.0	1781.0	---
		Type5	10	5	325390.0	16	1	83.0	1747.0	---	---
		Type5	10	6	679238.0	16	2	23.0	1444.0	1654.0	---
		Type5	10	7	153968.0	16	2	83.0	1210.0	1258.0	---
		Type5	10	8	167955.0	16	2	60.0	1493.0	1454.0	---
		Type5	10	9	356028.0	16	1	63.0	1372.0	---	---
		Type5	10	10	618765.0	16	2	70.0	1319.0	1544.0	---
		Type5	10	11	695440.0	16	2	42.0	1352.0	1653.0	---
		Type5	10	12	477340.0	16	2	35.0	1845.0	1352.0	---
		Type5	10	13	456510.0	16	2	32.0	1834.0	1471.0	---
		Type5	10	14	146421.0	16	1	31.0	1220.0	---	---
		Type5	10	15	87977.0	16	2	75.0	1317.0	1653.0	---
		Type5	10	16	158238.0	16	1	56.0	1703.0	---	---
11AX160MI MO	5250	Type5	10	0	572708.0	16	2	47.0	1412.0	1327.0	---
		Type5	10	1	421625.0	16	3	41.0	1945.0	1454.0	1613.0
		Type5	10	2	250949.0	16	3	73.0	1893.0	1662.0	1462.0
		Type5	10	3	681692.0	16	1	67.0	1875.0	---	---
		Type5	10	4	293667.0	16	2	28.0	1247.0	1781.0	---
		Type5	10	5	325390.0	16	1	83.0	1747.0	---	---
		Type5	10	6	679238.0	16	2	23.0	1444.0	1654.0	---
		Type5	10	7	153968.0	16	2	83.0	1210.0	1258.0	---
		Type5	10	8	167955.0	16	2	60.0	1493.0	1454.0	---
		Type5	10	9	356028.0	16	1	63.0	1372.0	---	---
		Type5	10	10	618765.0	16	2	70.0	1319.0	1544.0	---
		Type5	10	11	695440.0	16	2	42.0	1352.0	1653.0	---
		Type5	10	12	477340.0	16	2	35.0	1845.0	1352.0	---
		Type5	10	13	456510.0	16	2	32.0	1834.0	1471.0	---
		Type5	10	14	146421.0	16	1	31.0	1220.0	---	---
		Type5	10	15	87977.0	16	2	75.0	1317.0	1653.0	---
		Type5	10	16	158238.0	16	1	56.0	1703.0	---	---

Test Mode	Channel	Radar Type	Trial ID	Burst ID	Burst Offset (μs)	Chirp Width (MHz)	Number Of Pulses	Pulse Width (μs)	PRI1 (μs)	PRI2 (μs)	PRI3 (μs)
11AX20MI MO	5260	Type5	11	0	174455.0	19	3	61.0	1745.0	1740.0	1788.0
		Type5	11	1	443967.0	19	2	55.0	1912.0	1855.0	---
		Type5	11	2	356583.0	19	3	27.0	1650.0	1350.0	1519.0
		Type5	11	3	176339.0	19	3	74.0	1301.0	1448.0	1682.0
		Type5	11	4	303712.0	19	3	74.0	1747.0	1654.0	1761.0
		Type5	11	5	385912.0	19	2	87.0	1826.0	1779.0	---
		Type5	11	6	429166.0	19	1	62.0	1787.0	---	---
		Type5	11	7	489362.0	19	2	40.0	1447.0	1992.0	---
		Type5	11	8	122752.0	19	3	76.0	1510.0	1877.0	1143.0
		Type5	11	9	338360.0	19	1	59.0	1440.0	---	---
		Type5	11	10	336067.0	19	1	56.0	1935.0	---	---
		Type5	11	11	460092.0	19	2	25.0	1898.0	1794.0	---

		Type5	11	12	203203.0	19	2	86.0	1351.0	1456.0	---
		Type5	11	13	311549.0	19	3	57.0	1690.0	1661.0	1266.0
		Type5	11	14	297253.0	19	3	89.0	1413.0	1659.0	1950.0
		Type5	11	15	336918.0	19	2	40.0	1533.0	1421.0	---
		Type5	11	16	127877.0	19	1	66.0	1591.0	---	---
		Type5	11	17	326091.0	19	2	60.0	1342.0	1667.0	---
11AX40MI MO	5270	Type5	11	18	458410.0	19	1	83.0	1357.0	---	---
		Type5	11	0	174455.0	19	3	61.0	1745.0	1740.0	1788.0
		Type5	11	1	443967.0	19	2	55.0	1912.0	1855.0	---
		Type5	11	2	356583.0	19	3	27.0	1650.0	1350.0	1519.0
		Type5	11	3	176339.0	19	3	74.0	1301.0	1448.0	1682.0
		Type5	11	4	303712.0	19	3	74.0	1747.0	1654.0	1761.0
		Type5	11	5	385912.0	19	2	87.0	1826.0	1779.0	---
		Type5	11	6	429166.0	19	1	62.0	1787.0	---	---
		Type5	11	7	489362.0	19	2	40.0	1447.0	1992.0	---
		Type5	11	8	122752.0	19	3	76.0	1510.0	1877.0	1143.0
		Type5	11	9	338360.0	19	1	59.0	1440.0	---	---
		Type5	11	10	336067.0	19	1	56.0	1935.0	---	---
		Type5	11	11	460092.0	19	2	25.0	1898.0	1794.0	---
		Type5	11	12	203203.0	19	2	86.0	1351.0	1456.0	---
		Type5	11	13	311549.0	19	3	57.0	1690.0	1661.0	1266.0
		Type5	11	14	297253.0	19	3	89.0	1413.0	1659.0	1950.0
		Type5	11	15	336918.0	19	2	40.0	1533.0	1421.0	---
		Type5	11	16	127877.0	19	1	66.0	1591.0	---	---
		Type5	11	17	326091.0	19	2	60.0	1342.0	1667.0	---
		Type5	11	18	458410.0	19	1	83.0	1357.0	---	---
11AX80MI MO	5290	Type5	11	0	174455.0	19	3	61.0	1745.0	1740.0	1788.0
		Type5	11	1	443967.0	19	2	55.0	1912.0	1855.0	---
		Type5	11	2	356583.0	19	3	27.0	1650.0	1350.0	1519.0
		Type5	11	3	176339.0	19	3	74.0	1301.0	1448.0	1682.0
		Type5	11	4	303712.0	19	3	74.0	1747.0	1654.0	1761.0
		Type5	11	5	385912.0	19	2	87.0	1826.0	1779.0	---
		Type5	11	6	429166.0	19	1	62.0	1787.0	---	---
		Type5	11	7	489362.0	19	2	40.0	1447.0	1992.0	---
		Type5	11	8	122752.0	19	3	76.0	1510.0	1877.0	1143.0
		Type5	11	9	338360.0	19	1	59.0	1440.0	---	---
		Type5	11	10	336067.0	19	1	56.0	1935.0	---	---
		Type5	11	11	460092.0	19	2	25.0	1898.0	1794.0	---
		Type5	11	12	203203.0	19	2	86.0	1351.0	1456.0	---
		Type5	11	13	311549.0	19	3	57.0	1690.0	1661.0	1266.0
		Type5	11	14	297253.0	19	3	89.0	1413.0	1659.0	1950.0
		Type5	11	15	336918.0	19	2	40.0	1533.0	1421.0	---
		Type5	11	16	127877.0	19	1	66.0	1591.0	---	---
		Type5	11	17	326091.0	19	2	60.0	1342.0	1667.0	---
		Type5	11	18	458410.0	19	1	83.0	1357.0	---	---
11AX160MI MO	5250	Type5	11	0	174455.0	19	3	61.0	1745.0	1740.0	1788.0
		Type5	11	1	443967.0	19	2	55.0	1912.0	1855.0	---
		Type5	11	2	356583.0	19	3	27.0	1650.0	1350.0	1519.0
		Type5	11	3	176339.0	19	3	74.0	1301.0	1448.0	1682.0
		Type5	11	4	303712.0	19	3	74.0	1747.0	1654.0	1761.0
		Type5	11	5	385912.0	19	2	87.0	1826.0	1779.0	---
		Type5	11	6	429166.0	19	1	62.0	1787.0	---	---
		Type5	11	7	489362.0	19	2	40.0	1447.0	1992.0	---
		Type5	11	8	122752.0	19	3	76.0	1510.0	1877.0	1143.0
		Type5	11	9	338360.0	19	1	59.0	1440.0	---	---
		Type5	11	10	336067.0	19	1	56.0	1935.0	---	---
		Type5	11	11	460092.0	19	2	25.0	1898.0	1794.0	---
		Type5	11	12	203203.0	19	2	86.0	1351.0	1456.0	---
		Type5	11	13	311549.0	19	3	57.0	1690.0	1661.0	1266.0
		Type5	11	14	297253.0	19	3	89.0	1413.0	1659.0	1950.0
		Type5	11	15	336918.0	19	2	40.0	1533.0	1421.0	---

	Type5	11	16	127877.0	19	1	66.0	1591.0	---	---
	Type5	11	17	326091.0	19	2	60.0	1342.0	1667.0	---
	Type5	11	18	458410.0	19	1	83.0	1357.0	---	---

Test Mode	Channel	Radar Type	Trial ID	Burst ID	Burst Offset (μs)	Chirp Width (MHz)	Number Of Pulses	Pulse Width (μs)	PRI1 (μs)	PRI2 (μs)	PRI3 (μs)
11AX20MI MO	5260	Type5	12	0	22911.0	13	1	58.1	1929.0	---	---
		Type5	12	1	216473.0	13	1	52.1	1910.0	---	---
		Type5	12	2	410004.0	13	1	59.9	1971.0	---	---
		Type5	12	3	603671.0	13	1	60.2	1812.0	---	---
		Type5	12	4	794160.0	13	3	95.9	1399.0	1906.0	1608.0
		Type5	12	5	192251.0	13	2	79.9	1626.0	1859.0	---
		Type5	12	6	385590.0	13	2	78.5	1238.0	1917.0	---
		Type5	12	7	579862.0	13	1	53.8	1763.0	---	---
		Type5	12	8	773423.0	13	1	64.7	1800.0	---	---
		Type5	12	9	168898.0	13	1	61.4	1390.0	---	---
		Type5	12	10	361606.0	13	2	83.2	1692.0	1858.0	---
		Type5	12	11	553866.0	13	3	84.7	1533.0	1677.0	1638.0
		Type5	12	12	747241.0	13	3	88.7	1703.0	1528.0	1058.0
		Type5	12	13	144710.0	13	2	78.3	1258.0	1951.0	---
		Type5	12	14	337856.0	13	2	69.3	1731.0	1717.0	---
11AX40MI MO	5270	Type5	12	0	22911.0	13	1	58.1	1929.0	---	---
		Type5	12	1	216473.0	13	1	52.1	1910.0	---	---
		Type5	12	2	410004.0	13	1	59.9	1971.0	---	---
		Type5	12	3	603671.0	13	1	60.2	1812.0	---	---
		Type5	12	4	794160.0	13	3	95.9	1399.0	1906.0	1608.0
		Type5	12	5	192251.0	13	2	79.9	1626.0	1859.0	---
		Type5	12	6	385590.0	13	2	78.5	1238.0	1917.0	---
		Type5	12	7	579862.0	13	1	53.8	1763.0	---	---
		Type5	12	8	773423.0	13	1	64.7	1800.0	---	---
		Type5	12	9	168898.0	13	1	61.4	1390.0	---	---
		Type5	12	10	361606.0	13	2	83.2	1692.0	1858.0	---
		Type5	12	11	553866.0	13	3	84.7	1533.0	1677.0	1638.0
		Type5	12	12	747241.0	13	3	88.7	1703.0	1528.0	1058.0
		Type5	12	13	144710.0	13	2	78.3	1258.0	1951.0	---
		Type5	12	14	337856.0	13	2	69.3	1731.0	1717.0	---
11AX80MI MO	5290	Type5	12	0	22911.0	13	1	58.1	1929.0	---	---
		Type5	12	1	216473.0	13	1	52.1	1910.0	---	---
		Type5	12	2	410004.0	13	1	59.9	1971.0	---	---
		Type5	12	3	603671.0	13	1	60.2	1812.0	---	---
		Type5	12	4	794160.0	13	3	95.9	1399.0	1906.0	1608.0
		Type5	12	5	192251.0	13	2	79.9	1626.0	1859.0	---
		Type5	12	6	385590.0	13	2	78.5	1238.0	1917.0	---
		Type5	12	7	579862.0	13	1	53.8	1763.0	---	---
		Type5	12	8	773423.0	13	1	64.7	1800.0	---	---
		Type5	12	9	168898.0	13	1	61.4	1390.0	---	---
		Type5	12	10	361606.0	13	2	83.2	1692.0	1858.0	---
		Type5	12	11	553866.0	13	3	84.7	1533.0	1677.0	1638.0
		Type5	12	12	747241.0	13	3	88.7	1703.0	1528.0	1058.0
		Type5	12	13	144710.0	13	2	78.3	1258.0	1951.0	---
		Type5	12	14	337856.0	13	2	69.3	1731.0	1717.0	---
11AX160MI MO	5250	Type5	12	0	22911.0	13	1	58.1	1929.0	---	---
		Type5	12	1	216473.0	13	1	52.1	1910.0	---	---
		Type5	12	2	410004.0	13	1	59.9	1971.0	---	---
		Type5	12	3	603671.0	13	1	60.2	1812.0	---	---
		Type5	12	4	794160.0	13	3	95.9	1399.0	1906.0	1608.0
		Type5	12	5	192251.0	13	2	79.9	1626.0	1859.0	---
		Type5	12	6	385590.0	13	2	78.5	1238.0	1917.0	---
		Type5	12	7	579862.0	13	1	53.8	1763.0	---	---

	Type5	12	8	773423.0	13	1	64.7	1800.0	---	---
	Type5	12	9	168898.0	13	1	61.4	1390.0	---	---
	Type5	12	10	361606.0	13	2	83.2	1692.0	1858.0	---
	Type5	12	11	553866.0	13	3	84.7	1533.0	1677.0	1638.0
	Type5	12	12	747241.0	13	3	88.7	1703.0	1528.0	1058.0
	Type5	12	13	144710.0	13	2	78.3	1258.0	1951.0	---
	Type5	12	14	337856.0	13	2	69.3	1731.0	1717.0	---

Test Mode	Channel	Radar Type	Trial ID	Burst ID	Burst Offset (μs)	Chirp Width (MHz)	Number Of Pulses	Pulse Width (μs)	PRI1 (μs)	PRI2 (μs)	PRI3 (μs)
11AX20MI MO	5260	Type5	13	0	664275.0	10	2	75.3	1994.0	1612.0	---
		Type5	13	1	907886.0	10	1	56.3	1456.0	---	---
		Type5	13	2	151316.0	10	2	67.7	1617.0	1185.0	---
		Type5	13	3	393746.0	10	1	55.6	1337.0	---	---
		Type5	13	4	635093.0	10	2	75.2	1421.0	1267.0	---
		Type5	13	5	876993.0	10	2	76.3	1359.0	1305.0	---
		Type5	13	6	121278.0	10	3	85.7	1547.0	1362.0	1924.0
		Type5	13	7	362696.0	10	3	98.4	1873.0	1550.0	1249.0
		Type5	13	8	604342.0	10	3	86.4	1779.0	1439.0	1046.0
		Type5	13	9	846453.0	10	3	93.6	1059.0	1031.0	1452.0
		Type5	13	10	91871.0	10	1	63.3	1328.0	---	---
		Type5	13	11	333050.0	10	3	92.4	1412.0	1673.0	1322.0
11AX40MI MO	5270	Type5	13	0	664275.0	10	2	75.3	1994.0	1612.0	---
		Type5	13	1	907886.0	10	1	56.3	1456.0	---	---
		Type5	13	2	151316.0	10	2	67.7	1617.0	1185.0	---
		Type5	13	3	393746.0	10	1	55.6	1337.0	---	---
		Type5	13	4	635093.0	10	2	75.2	1421.0	1267.0	---
		Type5	13	5	876993.0	10	2	76.3	1359.0	1305.0	---
		Type5	13	6	121278.0	10	3	85.7	1547.0	1362.0	1924.0
		Type5	13	7	362696.0	10	3	98.4	1873.0	1550.0	1249.0
		Type5	13	8	604342.0	10	3	86.4	1779.0	1439.0	1046.0
		Type5	13	9	846453.0	10	3	93.6	1059.0	1031.0	1452.0
		Type5	13	10	91871.0	10	1	63.3	1328.0	---	---
		Type5	13	11	333050.0	10	3	92.4	1412.0	1673.0	1322.0
11AX80MI MO	5290	Type5	13	0	664275.0	10	2	75.3	1994.0	1612.0	---
		Type5	13	1	907886.0	10	1	56.3	1456.0	---	---
		Type5	13	2	151316.0	10	2	67.7	1617.0	1185.0	---
		Type5	13	3	393746.0	10	1	55.6	1337.0	---	---
		Type5	13	4	635093.0	10	2	75.2	1421.0	1267.0	---
		Type5	13	5	876993.0	10	2	76.3	1359.0	1305.0	---
		Type5	13	6	121278.0	10	3	85.7	1547.0	1362.0	1924.0
		Type5	13	7	362696.0	10	3	98.4	1873.0	1550.0	1249.0
		Type5	13	8	604342.0	10	3	86.4	1779.0	1439.0	1046.0
		Type5	13	9	846453.0	10	3	93.6	1059.0	1031.0	1452.0
		Type5	13	10	91871.0	10	1	63.3	1328.0	---	---
		Type5	13	11	333050.0	10	3	92.4	1412.0	1673.0	1322.0
11AX160MI MO	5250	Type5	13	0	664275.0	10	2	75.3	1994.0	1612.0	---
		Type5	13	1	907886.0	10	1	56.3	1456.0	---	---
		Type5	13	2	151316.0	10	2	67.7	1617.0	1185.0	---
		Type5	13	3	393746.0	10	1	55.6	1337.0	---	---
		Type5	13	4	635093.0	10	2	75.2	1421.0	1267.0	---
		Type5	13	5	876993.0	10	2	76.3	1359.0	1305.0	---
		Type5	13	6	121278.0	10	3	85.7	1547.0	1362.0	1924.0
		Type5	13	7	362696.0	10	3	98.4	1873.0	1550.0	1249.0
		Type5	13	8	604342.0	10	3	86.4	1779.0	1439.0	1046.0
		Type5	13	9	846453.0	10	3	93.6	1059.0	1031.0	1452.0
		Type5	13	10	91871.0	10	1	63.3	1328.0	---	---
		Type5	13	11	333050.0	10	3	92.4	1412.0	1673.0	1322.0

Test Mode	Channel	Radar Type	Trial ID	Burst ID	Burst Offset (μs)	Chirp Width (MHz)	Number Of Pulses	Pulse Width (μs)	PRI1 (μs)	PRI2 (μs)	PRI3 (μs)
11AX20MI MO	5260	Type5	14	0	361323.0	18	3	93.3	1983.0	1912.0	1535.0
		Type5	14	1	515261.0	18	2	69.1	1102.0	1794.0	---
		Type5	14	2	39025.0	18	3	86.9	1044.0	1152.0	1148.0
		Type5	14	3	190900.0	18	3	84.9	1894.0	1948.0	1118.0
		Type5	14	4	343941.0	18	2	72.3	1094.0	1916.0	---
		Type5	14	5	497624.0	18	1	51.7	1447.0	---	---
		Type5	14	6	20319.0	18	1	58.3	1429.0	---	---
		Type5	14	7	172999.0	18	1	60.8	1979.0	---	---
		Type5	14	8	325872.0	18	1	57.1	1641.0	---	---
		Type5	14	9	475841.0	18	3	88.9	1886.0	1964.0	1489.0
		Type5	14	10	1489.0	18	2	72.0	1909.0	1297.0	---
		Type5	14	11	153647.0	18	3	90.9	1261.0	1566.0	1370.0
		Type5	14	12	307096.0	18	1	59.8	1552.0	---	---
		Type5	14	13	458804.0	18	2	70.0	1759.0	1291.0	---
		Type5	14	14	610798.0	18	2	67.2	1625.0	1881.0	---
		Type5	14	15	134759.0	18	3	91.2	1382.0	1832.0	1661.0
		Type5	14	16	288306.0	18	1	56.5	1483.0	---	---
		Type5	14	17	441296.0	18	1	51.2	1237.0	---	---
		Type5	14	18	592780.0	18	2	74.1	1471.0	1245.0	---
11AX40MI MO	5270	Type5	14	0	361323.0	18	3	93.3	1983.0	1912.0	1535.0
		Type5	14	1	515261.0	18	2	69.1	1102.0	1794.0	---
		Type5	14	2	39025.0	18	3	86.9	1044.0	1152.0	1148.0
		Type5	14	3	190900.0	18	3	84.9	1894.0	1948.0	1118.0
		Type5	14	4	343941.0	18	2	72.3	1094.0	1916.0	---
		Type5	14	5	497624.0	18	1	51.7	1447.0	---	---
		Type5	14	6	20319.0	18	1	58.3	1429.0	---	---
		Type5	14	7	172999.0	18	1	60.8	1979.0	---	---
		Type5	14	8	325872.0	18	1	57.1	1641.0	---	---
		Type5	14	9	475841.0	18	3	88.9	1886.0	1964.0	1489.0
		Type5	14	10	1489.0	18	2	72.0	1909.0	1297.0	---
		Type5	14	11	153647.0	18	3	90.9	1261.0	1566.0	1370.0
		Type5	14	12	307096.0	18	1	59.8	1552.0	---	---
		Type5	14	13	458804.0	18	2	70.0	1759.0	1291.0	---
		Type5	14	14	610798.0	18	2	67.2	1625.0	1881.0	---
		Type5	14	15	134759.0	18	3	91.2	1382.0	1832.0	1661.0
		Type5	14	16	288306.0	18	1	56.5	1483.0	---	---
		Type5	14	17	441296.0	18	1	51.2	1237.0	---	---
		Type5	14	18	592780.0	18	2	74.1	1471.0	1245.0	---
11AX80MI MO	5290	Type5	14	0	361323.0	18	3	93.3	1983.0	1912.0	1535.0
		Type5	14	1	515261.0	18	2	69.1	1102.0	1794.0	---
		Type5	14	2	39025.0	18	3	86.9	1044.0	1152.0	1148.0
		Type5	14	3	190900.0	18	3	84.9	1894.0	1948.0	1118.0
		Type5	14	4	343941.0	18	2	72.3	1094.0	1916.0	---
		Type5	14	5	497624.0	18	1	51.7	1447.0	---	---
		Type5	14	6	20319.0	18	1	58.3	1429.0	---	---
		Type5	14	7	172999.0	18	1	60.8	1979.0	---	---
		Type5	14	8	325872.0	18	1	57.1	1641.0	---	---
		Type5	14	9	475841.0	18	3	88.9	1886.0	1964.0	1489.0
		Type5	14	10	1489.0	18	2	72.0	1909.0	1297.0	---
		Type5	14	11	153647.0	18	3	90.9	1261.0	1566.0	1370.0
		Type5	14	12	307096.0	18	1	59.8	1552.0	---	---
		Type5	14	13	458804.0	18	2	70.0	1759.0	1291.0	---
		Type5	14	14	610798.0	18	2	67.2	1625.0	1881.0	---
		Type5	14	15	134759.0	18	3	91.2	1382.0	1832.0	1661.0
		Type5	14	16	288306.0	18	1	56.5	1483.0	---	---
		Type5	14	17	441296.0	18	1	51.2	1237.0	---	---
		Type5	14	18	592780.0	18	2	74.1	1471.0	1245.0	---

11AX160MI MO	5250	Type5	14	0	361323.0	18	3	93.3	1983.0	1912.0	1535.0
		Type5	14	1	515261.0	18	2	69.1	1102.0	1794.0	---
		Type5	14	2	39025.0	18	3	86.9	1044.0	1152.0	1148.0
		Type5	14	3	190900.0	18	3	84.9	1894.0	1948.0	1118.0
		Type5	14	4	343941.0	18	2	72.3	1094.0	1916.0	---
		Type5	14	5	497624.0	18	1	51.7	1447.0	---	---
		Type5	14	6	20319.0	18	1	58.3	1429.0	---	---
		Type5	14	7	172999.0	18	1	60.8	1979.0	---	---
		Type5	14	8	325872.0	18	1	57.1	1641.0	---	---
		Type5	14	9	475841.0	18	3	88.9	1886.0	1964.0	1489.0
		Type5	14	10	1489.0	18	2	72.0	1909.0	1297.0	---
		Type5	14	11	153647.0	18	3	90.9	1261.0	1566.0	1370.0
		Type5	14	12	307096.0	18	1	59.8	1552.0	---	---
		Type5	14	13	458804.0	18	2	70.0	1759.0	1291.0	---
		Type5	14	14	610798.0	18	2	67.2	1625.0	1881.0	---
		Type5	14	15	134759.0	18	3	91.2	1382.0	1832.0	1661.0
		Type5	14	16	288306.0	18	1	56.5	1483.0	---	---
		Type5	14	17	441296.0	18	1	51.2	1237.0	---	---
		Type5	14	18	592780.0	18	2	74.1	1471.0	1245.0	---

Test Mode	Channel	Radar Type	Trial ID	Burst ID	Burst Offset (μs)	Chirp Width (MHz)	Number Of Pulses	Pulse Width (μs)	PRI1 (μs)	PRI2 (μs)	PRI3 (μs)
11AX20MI MO	5260	Type5	15	0	158286.0	12	2	76.9	1110.0	1140.0	---
		Type5	15	1	366024.0	12	1	50.2	1316.0	---	---
		Type5	15	2	573452.0	12	1	62.9	1520.0	---	---
		Type5	15	3	780619.0	12	1	64.7	1902.0	---	---
		Type5	15	4	132455.0	12	3	83.8	1410.0	1097.0	1611.0
		Type5	15	5	340207.0	12	1	65.4	1944.0	---	---
		Type5	15	6	548208.0	12	1	53.2	1024.0	---	---
		Type5	15	7	755333.0	12	1	51.7	1603.0	---	---
		Type5	15	8	107117.0	12	2	78.7	1804.0	1168.0	---
		Type5	15	9	314500.0	12	2	72.4	1030.0	1343.0	---
		Type5	15	10	522447.0	12	1	53.8	1327.0	---	---
		Type5	15	11	728517.0	12	2	73.6	1524.0	1553.0	---
		Type5	15	12	81611.0	12	2	66.7	1722.0	1122.0	---
11AX40MI MO	5270	Type5	15	13	288948.0	12	2	82.5	1404.0	1019.0	---
		Type5	15	0	158286.0	12	2	76.9	1110.0	1140.0	---
		Type5	15	1	366024.0	12	1	50.2	1316.0	---	---
		Type5	15	2	573452.0	12	1	62.9	1520.0	---	---
		Type5	15	3	780619.0	12	1	64.7	1902.0	---	---
		Type5	15	4	132455.0	12	3	83.8	1410.0	1097.0	1611.0
		Type5	15	5	340207.0	12	1	65.4	1944.0	---	---
		Type5	15	6	548208.0	12	1	53.2	1024.0	---	---
		Type5	15	7	755333.0	12	1	51.7	1603.0	---	---
		Type5	15	8	107117.0	12	2	78.7	1804.0	1168.0	---
		Type5	15	9	314500.0	12	2	72.4	1030.0	1343.0	---
		Type5	15	10	522447.0	12	1	53.8	1327.0	---	---
		Type5	15	11	728517.0	12	2	73.6	1524.0	1553.0	---
11AX80MI MO	5290	Type5	15	12	81611.0	12	2	66.7	1722.0	1122.0	---
		Type5	15	13	288948.0	12	2	82.5	1404.0	1019.0	---
		Type5	15	0	158286.0	12	2	76.9	1110.0	1140.0	---
		Type5	15	1	366024.0	12	1	50.2	1316.0	---	---
		Type5	15	2	573452.0	12	1	62.9	1520.0	---	---
		Type5	15	3	780619.0	12	1	64.7	1902.0	---	---
		Type5	15	4	132455.0	12	3	83.8	1410.0	1097.0	1611.0
		Type5	15	5	340207.0	12	1	65.4	1944.0	---	---
		Type5	15	6	548208.0	12	1	53.2	1024.0	---	---

		Type5	15	7	755333.0	12	1	51.7	1603.0	---	---
		Type5	15	8	107117.0	12	2	78.7	1804.0	1168.0	---
		Type5	15	9	314500.0	12	2	72.4	1030.0	1343.0	---
		Type5	15	10	522447.0	12	1	53.8	1327.0	---	---
		Type5	15	11	728517.0	12	2	73.6	1524.0	1553.0	---
		Type5	15	12	81611.0	12	2	66.7	1722.0	1122.0	---
11AX160MI MO	5250	Type5	15	13	288948.0	12	2	82.5	1404.0	1019.0	---
		Type5	15	0	158286.0	12	2	76.9	1110.0	1140.0	---
		Type5	15	1	366024.0	12	1	50.2	1316.0	---	---
		Type5	15	2	573452.0	12	1	62.9	1520.0	---	---
		Type5	15	3	780619.0	12	1	64.7	1902.0	---	---
		Type5	15	4	132455.0	12	3	83.8	1410.0	1097.0	1611.0
		Type5	15	5	340207.0	12	1	65.4	1944.0	---	---
		Type5	15	6	548208.0	12	1	53.2	1024.0	---	---
		Type5	15	7	755333.0	12	1	51.7	1603.0	---	---
		Type5	15	8	107117.0	12	2	78.7	1804.0	1168.0	---
		Type5	15	9	314500.0	12	2	72.4	1030.0	1343.0	---
		Type5	15	10	522447.0	12	1	53.8	1327.0	---	---
		Type5	15	11	728517.0	12	2	73.6	1524.0	1553.0	---
		Type5	15	12	81611.0	12	2	66.7	1722.0	1122.0	---
		Type5	15	13	288948.0	12	2	82.5	1404.0	1019.0	---

Test Mode	Channel	Radar Type	Trial ID	Burst ID	Burst Offset (μs)	Chirp Width (MHz)	Number Of Pulses	Pulse Width (μs)	PRI1 (μs)	PRI2 (μs)	PRI3 (μs)
11AX20MI MO	5260	Type5	16	0	345766.0	20	3	87.6	1565.0	1055.0	1240.0
		Type5	16	1	490019.0	20	3	85.2	1735.0	1541.0	1408.0
		Type5	16	2	39073.0	20	3	84.8	1534.0	1889.0	1463.0
		Type5	16	3	183923.0	20	2	77.9	1749.0	1460.0	---
		Type5	16	4	328777.0	20	2	76.5	1518.0	1485.0	---
		Type5	16	5	474728.0	20	1	60.9	1540.0	---	---
		Type5	16	6	21394.0	20	2	83.0	1080.0	1010.0	---
		Type5	16	7	165992.0	20	2	80.4	1824.0	1752.0	---
		Type5	16	8	310973.0	20	2	67.5	1764.0	1181.0	---
		Type5	16	9	456884.0	20	1	62.1	1495.0	---	---
		Type5	16	10	3515.0	20	3	86.4	1773.0	1966.0	1263.0
		Type5	16	11	147928.0	20	3	84.3	1593.0	1188.0	1788.0
		Type5	16	12	293225.0	20	2	76.9	1226.0	1537.0	---
		Type5	16	13	436922.0	20	3	95.8	1192.0	1298.0	1844.0
		Type5	16	14	584015.0	20	1	55.2	1644.0	---	---
		Type5	16	15	130832.0	20	1	59.0	1402.0	---	---
		Type5	16	16	274684.0	20	3	94.5	1296.0	1700.0	1283.0
		Type5	16	17	418579.0	20	3	91.9	1970.0	1978.0	1165.0
		Type5	16	18	563464.0	20	3	85.2	1732.0	1551.0	1189.0
		Type5	16	19	112787.0	20	2	69.5	1038.0	1224.0	---
11AX40MI MO	5270	Type5	16	0	345766.0	20	3	87.6	1565.0	1055.0	1240.0
		Type5	16	1	490019.0	20	3	85.2	1735.0	1541.0	1408.0
		Type5	16	2	39073.0	20	3	84.8	1534.0	1889.0	1463.0
		Type5	16	3	183923.0	20	2	77.9	1749.0	1460.0	---
		Type5	16	4	328777.0	20	2	76.5	1518.0	1485.0	---
		Type5	16	5	474728.0	20	1	60.9	1540.0	---	---
		Type5	16	6	21394.0	20	2	83.0	1080.0	1010.0	---
		Type5	16	7	165992.0	20	2	80.4	1824.0	1752.0	---
		Type5	16	8	310973.0	20	2	67.5	1764.0	1181.0	---
		Type5	16	9	456884.0	20	1	62.1	1495.0	---	---
		Type5	16	10	3515.0	20	3	86.4	1773.0	1966.0	1263.0
		Type5	16	11	147928.0	20	3	84.3	1593.0	1188.0	1788.0
		Type5	16	12	293225.0	20	2	76.9	1226.0	1537.0	---

		Type5	16	13	436922.0	20	3	95.8	1192.0	1298.0	1844.0
		Type5	16	14	584015.0	20	1	55.2	1644.0	---	---
		Type5	16	15	130832.0	20	1	59.0	1402.0	---	---
		Type5	16	16	274684.0	20	3	94.5	1296.0	1700.0	1283.0
		Type5	16	17	418579.0	20	3	91.9	1970.0	1978.0	1165.0
		Type5	16	18	563464.0	20	3	85.2	1732.0	1551.0	1189.0
		Type5	16	19	112787.0	20	2	69.5	1038.0	1224.0	---
11AX80MI MO	5290	Type5	16	0	345766.0	20	3	87.6	1565.0	1055.0	1240.0
		Type5	16	1	490019.0	20	3	85.2	1735.0	1541.0	1408.0
		Type5	16	2	39073.0	20	3	84.8	1534.0	1889.0	1463.0
		Type5	16	3	183923.0	20	2	77.9	1749.0	1460.0	---
		Type5	16	4	328777.0	20	2	76.5	1518.0	1485.0	---
		Type5	16	5	474728.0	20	1	60.9	1540.0	---	---
		Type5	16	6	21394.0	20	2	83.0	1080.0	1010.0	---
		Type5	16	7	165992.0	20	2	80.4	1824.0	1752.0	---
		Type5	16	8	310973.0	20	2	67.5	1764.0	1181.0	---
		Type5	16	9	456884.0	20	1	62.1	1495.0	---	---
		Type5	16	10	3515.0	20	3	86.4	1773.0	1966.0	1263.0
		Type5	16	11	147928.0	20	3	84.3	1593.0	1188.0	1788.0
		Type5	16	12	293225.0	20	2	76.9	1226.0	1537.0	---
		Type5	16	13	436922.0	20	3	95.8	1192.0	1298.0	1844.0
		Type5	16	14	584015.0	20	1	55.2	1644.0	---	---
		Type5	16	15	130832.0	20	1	59.0	1402.0	---	---
		Type5	16	16	274684.0	20	3	94.5	1296.0	1700.0	1283.0
		Type5	16	17	418579.0	20	3	91.9	1970.0	1978.0	1165.0
		Type5	16	18	563464.0	20	3	85.2	1732.0	1551.0	1189.0
		Type5	16	19	112787.0	20	2	69.5	1038.0	1224.0	---
11AX160MI MO	5250	Type5	16	0	345766.0	20	3	87.6	1565.0	1055.0	1240.0
		Type5	16	1	490019.0	20	3	85.2	1735.0	1541.0	1408.0
		Type5	16	2	39073.0	20	3	84.8	1534.0	1889.0	1463.0
		Type5	16	3	183923.0	20	2	77.9	1749.0	1460.0	---
		Type5	16	4	328777.0	20	2	76.5	1518.0	1485.0	---
		Type5	16	5	474728.0	20	1	60.9	1540.0	---	---
		Type5	16	6	21394.0	20	2	83.0	1080.0	1010.0	---
		Type5	16	7	165992.0	20	2	80.4	1824.0	1752.0	---
		Type5	16	8	310973.0	20	2	67.5	1764.0	1181.0	---
		Type5	16	9	456884.0	20	1	62.1	1495.0	---	---
		Type5	16	10	3515.0	20	3	86.4	1773.0	1966.0	1263.0
		Type5	16	11	147928.0	20	3	84.3	1593.0	1188.0	1788.0
		Type5	16	12	293225.0	20	2	76.9	1226.0	1537.0	---
		Type5	16	13	436922.0	20	3	95.8	1192.0	1298.0	1844.0
		Type5	16	14	584015.0	20	1	55.2	1644.0	---	---
		Type5	16	15	130832.0	20	1	59.0	1402.0	---	---
		Type5	16	16	274684.0	20	3	94.5	1296.0	1700.0	1283.0
		Type5	16	17	418579.0	20	3	91.9	1970.0	1978.0	1165.0
		Type5	16	18	563464.0	20	3	85.2	1732.0	1551.0	1189.0
		Type5	16	19	112787.0	20	2	69.5	1038.0	1224.0	---

Test Mode	Channel	Radar Type	Trial ID	Burst ID	Burst Offset (μs)	Chirp Width (MHz)	Number Of Pulses	Pulse Width (μs)	PRI1 (μs)	PRI2 (μs)	PRI3 (μs)
11AX20MI MO	5260	Type5	17	0	429224.0	10	3	86.4	1259.0	1918.0	1355.0
		Type5	17	1	670241.0	10	3	92.2	1598.0	1719.0	1295.0
		Type5	17	2	912880.0	10	2	80.4	1816.0	1899.0	---
		Type5	17	3	158603.0	10	1	54.3	1335.0	---	---
		Type5	17	4	400824.0	10	1	53.1	1303.0	---	---
		Type5	17	5	641915.0	10	2	69.4	1503.0	1546.0	---
		Type5	17	6	883823.0	10	2	69.1	1279.0	1639.0	---
		Type5	17	7	128373.0	10	3	100.0	1375.0	1438.0	1595.0
		Type5	17	8	370379.0	10	2	79.6	1239.0	1705.0	---
		Type5	17	9	611194.0	10	3	88.4	1374.0	1579.0	1623.0
		Type5	17	10	855665.0	10	1	53.3	1016.0	---	---
11AX40MI MO	5270	Type5	17	11	98897.0	10	1	65.3	1709.0	---	---
		Type5	17	0	429224.0	10	3	86.4	1259.0	1918.0	1355.0
		Type5	17	1	670241.0	10	3	92.2	1598.0	1719.0	1295.0
		Type5	17	2	912880.0	10	2	80.4	1816.0	1899.0	---
		Type5	17	3	158603.0	10	1	54.3	1335.0	---	---
		Type5	17	4	400824.0	10	1	53.1	1303.0	---	---
		Type5	17	5	641915.0	10	2	69.4	1503.0	1546.0	---
		Type5	17	6	883823.0	10	2	69.1	1279.0	1639.0	---
		Type5	17	7	128373.0	10	3	100.0	1375.0	1438.0	1595.0
		Type5	17	8	370379.0	10	2	79.6	1239.0	1705.0	---
		Type5	17	9	611194.0	10	3	88.4	1374.0	1579.0	1623.0
11AX80MI MO	5290	Type5	17	10	855665.0	10	1	53.3	1016.0	---	---
		Type5	17	11	98897.0	10	1	65.3	1709.0	---	---
		Type5	17	0	429224.0	10	3	86.4	1259.0	1918.0	1355.0
		Type5	17	1	670241.0	10	3	92.2	1598.0	1719.0	1295.0
		Type5	17	2	912880.0	10	2	80.4	1816.0	1899.0	---
		Type5	17	3	158603.0	10	1	54.3	1335.0	---	---
		Type5	17	4	400824.0	10	1	53.1	1303.0	---	---
		Type5	17	5	641915.0	10	2	69.4	1503.0	1546.0	---
		Type5	17	6	883823.0	10	2	69.1	1279.0	1639.0	---
		Type5	17	7	128373.0	10	3	100.0	1375.0	1438.0	1595.0
		Type5	17	8	370379.0	10	2	79.6	1239.0	1705.0	---
11AX160MI MO	5250	Type5	17	9	611194.0	10	3	88.4	1374.0	1579.0	1623.0
		Type5	17	10	855665.0	10	1	53.3	1016.0	---	---
		Type5	17	11	98897.0	10	1	65.3	1709.0	---	---
		Type5	17	0	429224.0	10	3	86.4	1259.0	1918.0	1355.0
		Type5	17	1	670241.0	10	3	92.2	1598.0	1719.0	1295.0
		Type5	17	2	912880.0	10	2	80.4	1816.0	1899.0	---
		Type5	17	3	158603.0	10	1	54.3	1335.0	---	---
		Type5	17	4	400824.0	10	1	53.1	1303.0	---	---
		Type5	17	5	641915.0	10	2	69.4	1503.0	1546.0	---
		Type5	17	6	883823.0	10	2	69.1	1279.0	1639.0	---
		Type5	17	7	128373.0	10	3	100.0	1375.0	1438.0	1595.0

Test Mode	Channel	Radar Type	Trial ID	Burst ID	Burst Offset (μs)	Chirp Width (MHz)	Number Of Pulses	Pulse Width (μs)	PRI1 (μs)	PRI2 (μs)	PRI3 (μs)
11AX20MI MO	5260	Type5	18	0	292143.0	12	1	55.3	1920.0	---	---
		Type5	18	1	499633.0	12	1	58.3	1797.0	---	---
		Type5	18	2	706377.0	12	2	72.3	1610.0	1139.0	---
		Type5	18	3	58989.0	12	3	84.8	1131.0	1761.0	1621.0
		Type5	18	4	266161.0	12	2	82.5	1875.0	1431.0	---
		Type5	18	5	474469.0	12	1	63.3	1095.0	---	---
		Type5	18	6	680544.0	12	2	80.0	1119.0	1913.0	---
		Type5	18	7	33519.0	12	3	90.3	1660.0	1853.0	1123.0
		Type5	18	8	240319.0	12	3	91.1	1539.0	1783.0	1172.0
		Type5	18	9	447400.0	12	3	96.6	1525.0	1036.0	1385.0
		Type5	18	10	654516.0	12	2	82.7	1710.0	1990.0	---
		Type5	18	11	8083.0	12	1	50.7	1234.0	---	---
		Type5	18	12	215435.0	12	2	78.4	1047.0	1109.0	---
		Type5	18	13	421325.0	12	3	99.5	1299.0	1965.0	1869.0
11AX40MI MO	5270	Type5	18	0	292143.0	12	1	55.3	1920.0	---	---
		Type5	18	1	499633.0	12	1	58.3	1797.0	---	---
		Type5	18	2	706377.0	12	2	72.3	1610.0	1139.0	---
		Type5	18	3	58989.0	12	3	84.8	1131.0	1761.0	1621.0
		Type5	18	4	266161.0	12	2	82.5	1875.0	1431.0	---
		Type5	18	5	474469.0	12	1	63.3	1095.0	---	---
		Type5	18	6	680544.0	12	2	80.0	1119.0	1913.0	---
		Type5	18	7	33519.0	12	3	90.3	1660.0	1853.0	1123.0
		Type5	18	8	240319.0	12	3	91.1	1539.0	1783.0	1172.0
		Type5	18	9	447400.0	12	3	96.6	1525.0	1036.0	1385.0
		Type5	18	10	654516.0	12	2	82.7	1710.0	1990.0	---
		Type5	18	11	8083.0	12	1	50.7	1234.0	---	---
		Type5	18	12	215435.0	12	2	78.4	1047.0	1109.0	---
		Type5	18	13	421325.0	12	3	99.5	1299.0	1965.0	1869.0
11AX80MI MO	5290	Type5	18	0	292143.0	12	1	55.3	1920.0	---	---
		Type5	18	1	499633.0	12	1	58.3	1797.0	---	---
		Type5	18	2	706377.0	12	2	72.3	1610.0	1139.0	---
		Type5	18	3	58989.0	12	3	84.8	1131.0	1761.0	1621.0
		Type5	18	4	266161.0	12	2	82.5	1875.0	1431.0	---
		Type5	18	5	474469.0	12	1	63.3	1095.0	---	---
		Type5	18	6	680544.0	12	2	80.0	1119.0	1913.0	---
		Type5	18	7	33519.0	12	3	90.3	1660.0	1853.0	1123.0
		Type5	18	8	240319.0	12	3	91.1	1539.0	1783.0	1172.0
		Type5	18	9	447400.0	12	3	96.6	1525.0	1036.0	1385.0
		Type5	18	10	654516.0	12	2	82.7	1710.0	1990.0	---
		Type5	18	11	8083.0	12	1	50.7	1234.0	---	---
		Type5	18	12	215435.0	12	2	78.4	1047.0	1109.0	---
		Type5	18	13	421325.0	12	3	99.5	1299.0	1965.0	1869.0
11AX160MI MO	5250	Type5	18	0	292143.0	12	1	55.3	1920.0	---	---
		Type5	18	1	499633.0	12	1	58.3	1797.0	---	---
		Type5	18	2	706377.0	12	2	72.3	1610.0	1139.0	---
		Type5	18	3	58989.0	12	3	84.8	1131.0	1761.0	1621.0
		Type5	18	4	266161.0	12	2	82.5	1875.0	1431.0	---
		Type5	18	5	474469.0	12	1	63.3	1095.0	---	---
		Type5	18	6	680544.0	12	2	80.0	1119.0	1913.0	---
		Type5	18	7	33519.0	12	3	90.3	1660.0	1853.0	1123.0
		Type5	18	8	240319.0	12	3	91.1	1539.0	1783.0	1172.0
		Type5	18	9	447400.0	12	3	96.6	1525.0	1036.0	1385.0
		Type5	18	10	654516.0	12	2	82.7	1710.0	1990.0	---
		Type5	18	11	8083.0	12	1	50.7	1234.0	---	---
		Type5	18	12	215435.0	12	2	78.4	1047.0	1109.0	---
		Type5	18	13	421325.0	12	3	99.5	1299.0	1965.0	1869.0

Test Mode	Channel	Radar Type	Trial ID	Burst ID	Burst Offset (μs)	Chirp Width (MHz)	Number Of Pulses	Pulse Width (μs)	PRI1 (μs)	PRI2 (μs)	PRI3 (μs)
11AX20MI MO	5260	Type5	19	0	733725.0	10	3	88.6	1501.0	1267.0	1227.0
		Type5	19	1	977882.0	10	1	57.4	1723.0	---	---
		Type5	19	2	221197.0	10	3	96.6	1086.0	1658.0	1324.0
		Type5	19	3	462915.0	10	2	69.7	1751.0	1945.0	---
		Type5	19	4	705071.0	10	2	77.9	1642.0	1317.0	---
		Type5	19	5	947923.0	10	1	62.0	1866.0	---	---
		Type5	19	6	191373.0	10	3	88.4	1997.0	1077.0	1366.0
		Type5	19	7	432561.0	10	3	97.3	1790.0	1896.0	1367.0
		Type5	19	8	674004.0	10	3	96.2	1391.0	1787.0	1672.0
		Type5	19	9	915842.0	10	3	95.4	1020.0	1892.0	1414.0
		Type5	19	10	162176.0	10	1	54.8	1084.0	---	---
11AX40MI MO	5270	Type5	19	11	403553.0	10	2	80.4	1850.0	1436.0	---
		Type5	19	0	733725.0	10	3	88.6	1501.0	1267.0	1227.0
		Type5	19	1	977882.0	10	1	57.4	1723.0	---	---
		Type5	19	2	221197.0	10	3	96.6	1086.0	1658.0	1324.0
		Type5	19	3	462915.0	10	2	69.7	1751.0	1945.0	---
		Type5	19	4	705071.0	10	2	77.9	1642.0	1317.0	---
		Type5	19	5	947923.0	10	1	62.0	1866.0	---	---
		Type5	19	6	191373.0	10	3	88.4	1997.0	1077.0	1366.0
		Type5	19	7	432561.0	10	3	97.3	1790.0	1896.0	1367.0
		Type5	19	8	674004.0	10	3	96.2	1391.0	1787.0	1672.0
		Type5	19	9	915842.0	10	3	95.4	1020.0	1892.0	1414.0
11AX80MI MO	5290	Type5	19	10	162176.0	10	1	54.8	1084.0	---	---
		Type5	19	11	403553.0	10	2	80.4	1850.0	1436.0	---
		Type5	19	0	733725.0	10	3	88.6	1501.0	1267.0	1227.0
		Type5	19	1	977882.0	10	1	57.4	1723.0	---	---
		Type5	19	2	221197.0	10	3	96.6	1086.0	1658.0	1324.0
		Type5	19	3	462915.0	10	2	69.7	1751.0	1945.0	---
		Type5	19	4	705071.0	10	2	77.9	1642.0	1317.0	---
		Type5	19	5	947923.0	10	1	62.0	1866.0	---	---
		Type5	19	6	191373.0	10	3	88.4	1997.0	1077.0	1366.0
		Type5	19	7	432561.0	10	3	97.3	1790.0	1896.0	1367.0
		Type5	19	8	674004.0	10	3	96.2	1391.0	1787.0	1672.0
11AX160MI MO	5250	Type5	19	9	915842.0	10	3	95.4	1020.0	1892.0	1414.0
		Type5	19	10	162176.0	10	1	54.8	1084.0	---	---
		Type5	19	11	403553.0	10	2	80.4	1850.0	1436.0	---
		Type5	19	0	733725.0	10	3	88.6	1501.0	1267.0	1227.0
		Type5	19	1	977882.0	10	1	57.4	1723.0	---	---
		Type5	19	2	221197.0	10	3	96.6	1086.0	1658.0	1324.0
		Type5	19	3	462915.0	10	2	69.7	1751.0	1945.0	---
		Type5	19	4	705071.0	10	2	77.9	1642.0	1317.0	---
		Type5	19	5	947923.0	10	1	62.0	1866.0	---	---
		Type5	19	6	191373.0	10	3	88.4	1997.0	1077.0	1366.0
		Type5	19	7	432561.0	10	3	97.3	1790.0	1896.0	1367.0
		Type5	19	8	674004.0	10	3	96.2	1391.0	1787.0	1672.0
		Type5	19	9	915842.0	10	3	95.4	1020.0	1892.0	1414.0
		Type5	19	10	162176.0	10	1	54.8	1084.0	---	---
		Type5	19	11	403553.0	10	2	80.4	1850.0	1436.0	---

Test Mode	Channel	Radar Type	Trial ID	Burst ID	Burst Offset (μs)	Chirp Width (MHz)	Number Of Pulses	Pulse Width (μs)	PRI1 (μs)	PRI2 (μs)	PRI3 (μs)
11AX20MI MO	5260	Type5	20	0	483470.0	15	2	74.7	1619.0	1611.0	---
		Type5	20	1	666072.0	15	1	57.1	1560.0	---	---
		Type5	20	2	98810.0	15	3	91.9	1392.0	1475.0	1376.0
		Type5	20	3	279914.0	15	2	83.1	1809.0	1772.0	---
		Type5	20	4	462536.0	15	1	50.7	1003.0	---	---
		Type5	20	5	642324.0	15	2	79.2	1574.0	1600.0	---
		Type5	20	6	76831.0	15	1	58.7	1186.0	---	---
		Type5	20	7	257785.0	15	2	71.0	1521.0	1567.0	---
		Type5	20	8	438554.0	15	2	79.0	1777.0	1960.0	---
		Type5	20	9	620397.0	15	2	68.5	1284.0	1428.0	---
		Type5	20	10	54310.0	15	2	73.5	1904.0	1352.0	---
		Type5	20	11	235506.0	15	2	70.5	1864.0	1115.0	---
		Type5	20	12	417036.0	15	2	76.6	1045.0	1300.0	---
		Type5	20	13	597974.0	15	2	81.2	1160.0	1675.0	---
		Type5	20	14	32086.0	15	1	61.8	1277.0	---	---
11AX40MI MO	5270	Type5	20	0	483470.0	15	2	74.7	1619.0	1611.0	---
		Type5	20	1	666072.0	15	1	57.1	1560.0	---	---
		Type5	20	2	98810.0	15	3	91.9	1392.0	1475.0	1376.0
		Type5	20	3	279914.0	15	2	83.1	1809.0	1772.0	---
		Type5	20	4	462536.0	15	1	50.7	1003.0	---	---
		Type5	20	5	642324.0	15	2	79.2	1574.0	1600.0	---
		Type5	20	6	76831.0	15	1	58.7	1186.0	---	---
		Type5	20	7	257785.0	15	2	71.0	1521.0	1567.0	---
		Type5	20	8	438554.0	15	2	79.0	1777.0	1960.0	---
		Type5	20	9	620397.0	15	2	68.5	1284.0	1428.0	---
		Type5	20	10	54310.0	15	2	73.5	1904.0	1352.0	---
		Type5	20	11	235506.0	15	2	70.5	1864.0	1115.0	---
		Type5	20	12	417036.0	15	2	76.6	1045.0	1300.0	---
		Type5	20	13	597974.0	15	2	81.2	1160.0	1675.0	---
		Type5	20	14	32086.0	15	1	61.8	1277.0	---	---
		Type5	20	15	212751.0	15	3	94.9	1450.0	1206.0	1860.0
11AX80MI MO	5290	Type5	20	0	483470.0	15	2	74.7	1619.0	1611.0	---
		Type5	20	1	666072.0	15	1	57.1	1560.0	---	---
		Type5	20	2	98810.0	15	3	91.9	1392.0	1475.0	1376.0
		Type5	20	3	279914.0	15	2	83.1	1809.0	1772.0	---
		Type5	20	4	462536.0	15	1	50.7	1003.0	---	---
		Type5	20	5	642324.0	15	2	79.2	1574.0	1600.0	---
		Type5	20	6	76831.0	15	1	58.7	1186.0	---	---
		Type5	20	7	257785.0	15	2	71.0	1521.0	1567.0	---
		Type5	20	8	438554.0	15	2	79.0	1777.0	1960.0	---
		Type5	20	9	620397.0	15	2	68.5	1284.0	1428.0	---
		Type5	20	10	54310.0	15	2	73.5	1904.0	1352.0	---
		Type5	20	11	235506.0	15	2	70.5	1864.0	1115.0	---
		Type5	20	12	417036.0	15	2	76.6	1045.0	1300.0	---
		Type5	20	13	597974.0	15	2	81.2	1160.0	1675.0	---
		Type5	20	14	32086.0	15	1	61.8	1277.0	---	---
		Type5	20	15	212751.0	15	3	94.9	1450.0	1206.0	1860.0
11AX160MI MO	5250	Type5	20	0	483470.0	15	2	74.7	1619.0	1611.0	---
		Type5	20	1	666072.0	15	1	57.1	1560.0	---	---
		Type5	20	2	98810.0	15	3	91.9	1392.0	1475.0	1376.0
		Type5	20	3	279914.0	15	2	83.1	1809.0	1772.0	---
		Type5	20	4	462536.0	15	1	50.7	1003.0	---	---
		Type5	20	5	642324.0	15	2	79.2	1574.0	1600.0	---
		Type5	20	6	76831.0	15	1	58.7	1186.0	---	---
		Type5	20	7	257785.0	15	2	71.0	1521.0	1567.0	---
		Type5	20	8	438554.0	15	2	79.0	1777.0	1960.0	---

	Type5	20	9	620397.0	15	2	68.5	1284.0	1428.0	---
	Type5	20	10	54310.0	15	2	73.5	1904.0	1352.0	---
	Type5	20	11	235506.0	15	2	70.5	1864.0	1115.0	---
	Type5	20	12	417036.0	15	2	76.6	1045.0	1300.0	---
	Type5	20	13	597974.0	15	2	81.2	1160.0	1675.0	---
	Type5	20	14	32086.0	15	1	61.8	1277.0	---	---
	Type5	20	15	212751.0	15	3	94.9	1450.0	1206.0	1860.0

Test Mode	Channel	Radar Type	Trial ID	Burst ID	Burst Offset (μs)	Chirp Width (MHz)	Number Of Pulses	Pulse Width (μs)	PRI1 (μs)	PRI2 (μs)	PRI3 (μs)
11AX20MI MO	5260	Type5	21	0	696739.0	9	2	92.0	1859.0	1298.0	---
		Type5	21	1	329165.0	9	3	95.0	1923.0	1256.0	1227.0
		Type5	21	2	141229.0	9	1	73.0	1249.0	---	---
		Type5	21	3	377186.0	9	2	73.0	1628.0	1540.0	---
		Type5	21	4	228136.0	9	2	73.0	1330.0	1541.0	---
		Type5	21	5	13553.0	9	1	71.0	1651.0	---	---
		Type5	21	6	486207.0	9	2	70.0	1242.0	1123.0	---
		Type5	21	7	785190.0	9	1	82.0	1840.0	---	---
		Type5	21	8	484793.0	9	1	95.0	1433.0	---	---
		Type5	21	9	575042.0	9	1	87.0	1381.0	---	---
		Type5	21	10	38442.0	9	1	60.0	1401.0	---	---
11AX40MI MO	5270	Type5	21	11	937241.0	9	3	83.0	1417.0	1321.0	1227.0
		Type5	21	0	696739.0	9	2	92.0	1859.0	1298.0	---
		Type5	21	1	329165.0	9	3	95.0	1923.0	1256.0	1227.0
		Type5	21	2	141229.0	9	1	73.0	1249.0	---	---
		Type5	21	3	377186.0	9	2	73.0	1628.0	1540.0	---
		Type5	21	4	228136.0	9	2	73.0	1330.0	1541.0	---
		Type5	21	5	13553.0	9	1	71.0	1651.0	---	---
		Type5	21	6	486207.0	9	2	70.0	1242.0	1123.0	---
		Type5	21	7	785190.0	9	1	82.0	1840.0	---	---
		Type5	21	8	484793.0	9	1	95.0	1433.0	---	---
		Type5	21	9	575042.0	9	1	87.0	1381.0	---	---
11AX80MI MO	5290	Type5	21	10	38442.0	9	1	60.0	1401.0	---	---
		Type5	21	11	937241.0	9	3	83.0	1417.0	1321.0	1227.0
		Type5	21	0	696739.0	9	2	92.0	1859.0	1298.0	---
		Type5	21	1	329165.0	9	3	95.0	1923.0	1256.0	1227.0
		Type5	21	2	141229.0	9	1	73.0	1249.0	---	---
		Type5	21	3	377186.0	9	2	73.0	1628.0	1540.0	---
		Type5	21	4	228136.0	9	2	73.0	1330.0	1541.0	---
		Type5	21	5	13553.0	9	1	71.0	1651.0	---	---
		Type5	21	6	486207.0	9	2	70.0	1242.0	1123.0	---
		Type5	21	7	785190.0	9	1	82.0	1840.0	---	---
		Type5	21	8	484793.0	9	1	95.0	1433.0	---	---
11AX16MI MO	5290	Type5	21	9	575042.0	9	1	87.0	1381.0	---	---
		Type5	21	10	38442.0	9	1	60.0	1401.0	---	---
		Type5	21	11	937241.0	9	3	83.0	1417.0	1321.0	1227.0
		Type5	21	0	696739.0	9	2	92.0	1859.0	1298.0	---
		Type5	21	1	329165.0	9	3	95.0	1923.0	1256.0	1227.0
		Type5	21	2	141229.0	9	1	73.0	1249.0	---	---
		Type5	21	3	377186.0	9	2	73.0	1628.0	1540.0	---

	Type5	21	8	484793.0	9	1	95.0	1433.0	---	---
	Type5	21	9	575042.0	9	1	87.0	1381.0	---	---
	Type5	21	10	38442.0	9	1	60.0	1401.0	---	---
	Type5	21	11	937241.0	9	3	83.0	1417.0	1321.0	1227.0

Test Mode	Channel	Radar Type	Trial ID	Burst ID	Burst Offset (μs)	Chirp Width (MHz)	Number Of Pulses	Pulse Width (μs)	PRI1 (μs)	PRI2 (μs)	PRI3 (μs)
11AX20MI MO	5260	Type5	22	0	290679.0	20	2	52.0	1779.0	1323.0	---
		Type5	22	1	109024.0	20	1	83.0	1570.0	---	---
		Type5	22	2	421424.0	20	1	72.0	1241.0	---	---
		Type5	22	3	758698.0	20	2	84.0	1740.0	1211.0	---
		Type5	22	4	91818.0	20	2	77.0	1549.0	1442.0	---
		Type5	22	5	927127.0	20	1	52.0	1365.0	---	---
		Type5	22	6	236416.0	20	3	71.0	1979.0	1446.0	1505.0
		Type5	22	7	701958.0	20	2	69.0	1134.0	1137.0	---
		Type5	22	8	905111.0	20	3	77.0	1206.0	1565.0	1358.0
		Type5	22	9	772244.0	20	1	75.0	1902.0	---	---
		Type5	22	10	762629.0	20	3	60.0	1295.0	1460.0	1566.0
		Type5	22	11	397683.0	20	1	96.0	1238.0	---	---
		Type5	22	12	792255.0	20	3	83.0	1625.0	1357.0	1938.0
		Type5	22	13	500693.0	20	1	54.0	1624.0	---	---
		Type5	22	14	680849.0	20	2	79.0	1937.0	1586.0	---
		Type5	22	15	834416.0	20	2	75.0	1837.0	1664.0	---
		Type5	22	16	748306.0	20	3	88.0	1958.0	1630.0	1176.0
		Type5	22	17	693060.0	20	2	95.0	1937.0	1057.0	---
		Type5	22	18	791588.0	20	3	88.0	1575.0	1018.0	1340.0
		Type5	22	19	712034.0	20	3	64.0	1791.0	1614.0	1817.0
11AX40MI MO	5270	Type5	22	0	290679.0	20	2	52.0	1779.0	1323.0	---
		Type5	22	1	109024.0	20	1	83.0	1570.0	---	---
		Type5	22	2	421424.0	20	1	72.0	1241.0	---	---
		Type5	22	3	758698.0	20	2	84.0	1740.0	1211.0	---
		Type5	22	4	91818.0	20	2	77.0	1549.0	1442.0	---
		Type5	22	5	927127.0	20	1	52.0	1365.0	---	---
		Type5	22	6	236416.0	20	3	71.0	1979.0	1446.0	1505.0
		Type5	22	7	701958.0	20	2	69.0	1134.0	1137.0	---
		Type5	22	8	905111.0	20	3	77.0	1206.0	1565.0	1358.0
		Type5	22	9	772244.0	20	1	75.0	1902.0	---	---
		Type5	22	10	762629.0	20	3	60.0	1295.0	1460.0	1566.0
		Type5	22	11	397683.0	20	1	96.0	1238.0	---	---
		Type5	22	12	792255.0	20	3	83.0	1625.0	1357.0	1938.0
		Type5	22	13	500693.0	20	1	54.0	1624.0	---	---
		Type5	22	14	680849.0	20	2	79.0	1937.0	1586.0	---
		Type5	22	15	834416.0	20	2	75.0	1837.0	1664.0	---
		Type5	22	16	748306.0	20	3	88.0	1958.0	1630.0	1176.0
		Type5	22	17	693060.0	20	2	95.0	1937.0	1057.0	---
		Type5	22	18	791588.0	20	3	88.0	1575.0	1018.0	1340.0
		Type5	22	19	712034.0	20	3	64.0	1791.0	1614.0	1817.0
11AX80MI MO	5290	Type5	22	0	290679.0	20	2	52.0	1779.0	1323.0	---
		Type5	22	1	109024.0	20	1	83.0	1570.0	---	---
		Type5	22	2	421424.0	20	1	72.0	1241.0	---	---
		Type5	22	3	758698.0	20	2	84.0	1740.0	1211.0	---
		Type5	22	4	91818.0	20	2	77.0	1549.0	1442.0	---
		Type5	22	5	927127.0	20	1	52.0	1365.0	---	---
		Type5	22	6	236416.0	20	3	71.0	1979.0	1446.0	1505.0
		Type5	22	7	701958.0	20	2	69.0	1134.0	1137.0	---
		Type5	22	8	905111.0	20	3	77.0	1206.0	1565.0	1358.0
		Type5	22	9	772244.0	20	1	75.0	1902.0	---	---

11AX160MI MO	5290	Type5	22	10	762629.0	20	3	60.0	1295.0	1460.0	1566.0
		Type5	22	11	397683.0	20	1	96.0	1238.0	---	---
		Type5	22	12	792255.0	20	3	83.0	1625.0	1357.0	1938.0
		Type5	22	13	500693.0	20	1	54.0	1624.0	---	---
		Type5	22	14	680849.0	20	2	79.0	1937.0	1586.0	---
		Type5	22	15	834416.0	20	2	75.0	1837.0	1664.0	---
		Type5	22	16	748306.0	20	3	88.0	1958.0	1630.0	1176.0
		Type5	22	17	693060.0	20	2	95.0	1937.0	1057.0	---
		Type5	22	18	791588.0	20	3	88.0	1575.0	1018.0	1340.0
		Type5	22	19	712034.0	20	3	64.0	1791.0	1614.0	1817.0
		Type5	22	0	290679.0	20	2	52.0	1779.0	1323.0	---
		Type5	22	1	109024.0	20	1	83.0	1570.0	---	---
		Type5	22	2	421424.0	20	1	72.0	1241.0	---	---
		Type5	22	3	758698.0	20	2	84.0	1740.0	1211.0	---
		Type5	22	4	91818.0	20	2	77.0	1549.0	1442.0	---
		Type5	22	5	927127.0	20	1	52.0	1365.0	---	---
		Type5	22	6	236416.0	20	3	71.0	1979.0	1446.0	1505.0
		Type5	22	7	701958.0	20	2	69.0	1134.0	1137.0	---
		Type5	22	8	905111.0	20	3	77.0	1206.0	1565.0	1358.0
		Type5	22	9	772244.0	20	1	75.0	1902.0	---	---
11AX160MI MO	5290	Type5	22	10	762629.0	20	3	60.0	1295.0	1460.0	1566.0
		Type5	22	11	397683.0	20	1	96.0	1238.0	---	---
		Type5	22	12	792255.0	20	3	83.0	1625.0	1357.0	1938.0
		Type5	22	13	500693.0	20	1	54.0	1624.0	---	---
		Type5	22	14	680849.0	20	2	79.0	1937.0	1586.0	---
		Type5	22	15	834416.0	20	2	75.0	1837.0	1664.0	---
		Type5	22	16	748306.0	20	3	88.0	1958.0	1630.0	1176.0
		Type5	22	17	693060.0	20	2	95.0	1937.0	1057.0	---
		Type5	22	18	791588.0	20	3	88.0	1575.0	1018.0	1340.0
		Type5	22	19	712034.0	20	3	64.0	1791.0	1614.0	1817.0

Test Mode	Channel	Radar Type	Trial ID	Burst ID	Burst Offset (μs)	Chirp Width (MHz)	Number Of Pulses	Pulse Width (μs)	PRI1 (μs)	PRI2 (μs)	PRI3 (μs)
11AX20MI MO	5260	Type5	23	0	794426.0	12	1	92.0	1237.0	---	---
		Type5	23	1	691107.0	12	3	85.0	1604.0	1181.0	1413.0
		Type5	23	2	386985.0	12	2	70.0	1464.0	1353.0	---
		Type5	23	3	208723.0	12	1	77.0	1805.0	---	---
		Type5	23	4	132614.0	12	3	63.0	1108.0	1354.0	1987.0
		Type5	23	5	789770.0	12	2	84.0	1712.0	1119.0	---
		Type5	23	6	413900.0	12	1	56.0	1569.0	---	---
		Type5	23	7	806629.0	12	2	85.0	1857.0	1354.0	---
		Type5	23	8	403314.0	12	2	75.0	1236.0	1451.0	---
		Type5	23	9	492442.0	12	2	83.0	1738.0	1547.0	---
		Type5	23	10	792718.0	12	2	89.0	1238.0	1274.0	---
		Type5	23	11	519771.0	12	3	75.0	1532.0	1652.0	1601.0
		Type5	23	12	405718.0	12	2	70.0	1572.0	1421.0	---
11AX40MI MO	5270	Type5	23	13	234028.0	12	2	56.0	1167.0	1233.0	---
		Type5	23	0	794426.0	12	1	92.0	1237.0	---	---
		Type5	23	1	691107.0	12	3	85.0	1604.0	1181.0	1413.0
		Type5	23	2	386985.0	12	2	70.0	1464.0	1353.0	---
		Type5	23	3	208723.0	12	1	77.0	1805.0	---	---
		Type5	23	4	132614.0	12	3	63.0	1108.0	1354.0	1987.0
		Type5	23	5	789770.0	12	2	84.0	1712.0	1119.0	---
11AX40MI MO	5270	Type5	23	6	413900.0	12	1	56.0	1569.0	---	---
		Type5	23	7	806629.0	12	2	85.0	1857.0	1354.0	---

		Type5	23	8	403314.0	12	2	75.0	1236.0	1451.0	---
		Type5	23	9	492442.0	12	2	83.0	1738.0	1547.0	---
		Type5	23	10	792718.0	12	2	89.0	1238.0	1274.0	---
		Type5	23	11	519771.0	12	3	75.0	1532.0	1652.0	1601.0
		Type5	23	12	405718.0	12	2	70.0	1572.0	1421.0	---
		Type5	23	13	234028.0	12	2	56.0	1167.0	1233.0	---
11AX80MI MO	5290	Type5	23	0	794426.0	12	1	92.0	1237.0	---	---
		Type5	23	1	691107.0	12	3	85.0	1604.0	1181.0	1413.0
		Type5	23	2	386985.0	12	2	70.0	1464.0	1353.0	---
		Type5	23	3	208723.0	12	1	77.0	1805.0	---	---
		Type5	23	4	132614.0	12	3	63.0	1108.0	1354.0	1987.0
		Type5	23	5	789770.0	12	2	84.0	1712.0	1119.0	---
		Type5	23	6	413900.0	12	1	56.0	1569.0	---	---
		Type5	23	7	806629.0	12	2	85.0	1857.0	1354.0	---
		Type5	23	8	403314.0	12	2	75.0	1236.0	1451.0	---
		Type5	23	9	492442.0	12	2	83.0	1738.0	1547.0	---
		Type5	23	10	792718.0	12	2	89.0	1238.0	1274.0	---
		Type5	23	11	519771.0	12	3	75.0	1532.0	1652.0	1601.0
		Type5	23	12	405718.0	12	2	70.0	1572.0	1421.0	---
		Type5	23	13	234028.0	12	2	56.0	1167.0	1233.0	---
11AX160MI MO	5250	Type5	23	0	794426.0	12	1	92.0	1237.0	---	---
		Type5	23	1	691107.0	12	3	85.0	1604.0	1181.0	1413.0
		Type5	23	2	386985.0	12	2	70.0	1464.0	1353.0	---
		Type5	23	3	208723.0	12	1	77.0	1805.0	---	---
		Type5	23	4	132614.0	12	3	63.0	1108.0	1354.0	1987.0
		Type5	23	5	789770.0	12	2	84.0	1712.0	1119.0	---
		Type5	23	6	413900.0	12	1	56.0	1569.0	---	---
		Type5	23	7	806629.0	12	2	85.0	1857.0	1354.0	---
		Type5	23	8	403314.0	12	2	75.0	1236.0	1451.0	---
		Type5	23	9	492442.0	12	2	83.0	1738.0	1547.0	---
		Type5	23	10	792718.0	12	2	89.0	1238.0	1274.0	---
		Type5	23	11	519771.0	12	3	75.0	1532.0	1652.0	1601.0
		Type5	23	12	405718.0	12	2	70.0	1572.0	1421.0	---
		Type5	23	13	234028.0	12	2	56.0	1167.0	1233.0	---

Test Mode	Channel	Radar Type	Trial ID	Burst ID	Burst Offset (μs)	Chirp Width (MHz)	Number Of Pulses	Pulse Width (μs)	PRI1 (μs)	PRI2 (μs)	PRI3 (μs)
11AX20MI MO	5260	Type5	24	0	512767.0	11	3	71.0	1946.0	1468.0	1941.0
		Type5	24	1	244307.0	11	2	75.0	1504.0	1265.0	---
		Type5	24	2	288713.0	11	1	64.0	1534.0	---	---
		Type5	24	3	887306.0	11	3	88.0	1990.0	1336.0	1332.0
		Type5	24	4	625409.0	11	3	60.0	1297.0	1456.0	1498.0
		Type5	24	5	664827.0	11	2	76.0	1737.0	1329.0	---
		Type5	24	6	265675.0	11	3	56.0	1533.0	1646.0	1222.0
		Type5	24	7	482739.0	11	3	77.0	1351.0	1565.0	1380.0
		Type5	24	8	500439.0	11	3	86.0	1809.0	1234.0	1602.0
		Type5	24	9	293001.0	11	2	77.0	1728.0	1178.0	---
		Type5	24	10	799572.0	11	3	73.0	1572.0	1629.0	1956.0
		Type5	24	11	403381.0	11	1	58.0	1957.0	---	---
		Type5	24	12	658295.0	11	3	66.0	1924.0	1963.0	1164.0
11AX40MI MO	5270	Type5	24	0	512767.0	11	3	71.0	1946.0	1468.0	1941.0
		Type5	24	1	244307.0	11	2	75.0	1504.0	1265.0	---
		Type5	24	2	288713.0	11	1	64.0	1534.0	---	---
		Type5	24	3	887306.0	11	3	88.0	1990.0	1336.0	1332.0
		Type5	24	4	625409.0	11	3	60.0	1297.0	1456.0	1498.0

		Type5	24	5	664827.0	11	2	76.0	1737.0	1329.0	---
		Type5	24	6	265675.0	11	3	56.0	1533.0	1646.0	1222.0
		Type5	24	7	482739.0	11	3	77.0	1351.0	1565.0	1380.0
		Type5	24	8	500439.0	11	3	86.0	1809.0	1234.0	1602.0
		Type5	24	9	293001.0	11	2	77.0	1728.0	1178.0	---
		Type5	24	10	799572.0	11	3	73.0	1572.0	1629.0	1956.0
		Type5	24	11	403381.0	11	1	58.0	1957.0	---	---
11AX80MI MO	5290	Type5	24	12	658295.0	11	3	66.0	1924.0	1963.0	1164.0
		Type5	24	0	512767.0	11	3	71.0	1946.0	1468.0	1941.0
		Type5	24	1	244307.0	11	2	75.0	1504.0	1265.0	---
		Type5	24	2	288713.0	11	1	64.0	1534.0	---	---
		Type5	24	3	887306.0	11	3	88.0	1990.0	1336.0	1332.0
		Type5	24	4	625409.0	11	3	60.0	1297.0	1456.0	1498.0
		Type5	24	5	664827.0	11	2	76.0	1737.0	1329.0	---
		Type5	24	6	265675.0	11	3	56.0	1533.0	1646.0	1222.0
		Type5	24	7	482739.0	11	3	77.0	1351.0	1565.0	1380.0
		Type5	24	8	500439.0	11	3	86.0	1809.0	1234.0	1602.0
		Type5	24	9	293001.0	11	2	77.0	1728.0	1178.0	---
		Type5	24	10	799572.0	11	3	73.0	1572.0	1629.0	1956.0
11AX160MI MO	5250	Type5	24	11	403381.0	11	1	58.0	1957.0	---	---
		Type5	24	12	658295.0	11	3	66.0	1924.0	1963.0	1164.0
		Type5	24	0	512767.0	11	3	71.0	1946.0	1468.0	1941.0
		Type5	24	1	244307.0	11	2	75.0	1504.0	1265.0	---
		Type5	24	2	288713.0	11	1	64.0	1534.0	---	---
		Type5	24	3	887306.0	11	3	88.0	1990.0	1336.0	1332.0
		Type5	24	4	625409.0	11	3	60.0	1297.0	1456.0	1498.0
		Type5	24	5	664827.0	11	2	76.0	1737.0	1329.0	---
		Type5	24	6	265675.0	11	3	56.0	1533.0	1646.0	1222.0
		Type5	24	7	482739.0	11	3	77.0	1351.0	1565.0	1380.0
		Type5	24	8	500439.0	11	3	86.0	1809.0	1234.0	1602.0
		Type5	24	9	293001.0	11	2	77.0	1728.0	1178.0	---
		Type5	24	10	799572.0	11	3	73.0	1572.0	1629.0	1956.0
		Type5	24	11	403381.0	11	1	58.0	1957.0	---	---
		Type5	24	12	658295.0	11	3	66.0	1924.0	1963.0	1164.0

Test Mode	Channel	Radar Type	Trial ID	Burst ID	Burst Offset (μs)	Chirp Width (MHz)	Number Of Pulses	Pulse Width (μs)	PRI1 (μs)	PRI2 (μs)	PRI3 (μs)
11AX20MI MO	5260	Type5	25	0	291202.0	5	2	68.6	1116.0	1171.0	---
		Type5	25	1	191464.0	5	2	83.1	1320.0	1315.0	---
		Type5	25	2	794839.0	5	1	60.9	1564.0	---	---
		Type5	25	3	1002174.0	5	2	77.7	1696.0	1358.0	---
		Type5	25	4	100851.0	5	2	77.4	1793.0	1110.0	---
		Type5	25	5	146185.0	5	2	66.8	1576.0	1423.0	---
		Type5	25	6	1102402.0	5	1	63.7	1333.0	---	---
		Type5	25	7	1104601.0	5	3	91.2	1409.0	1681.0	1275.0
11AX40MI MO	5270	Type5	25	0	291202.0	5	2	68.6	1116.0	1171.0	---
		Type5	25	1	191464.0	5	2	83.1	1320.0	1315.0	---
		Type5	25	2	794839.0	5	1	60.9	1564.0	---	---
		Type5	25	3	1002174.0	5	2	77.7	1696.0	1358.0	---
		Type5	25	4	100851.0	5	2	77.4	1793.0	1110.0	---
		Type5	25	5	146185.0	5	2	66.8	1576.0	1423.0	---
		Type5	25	6	1102402.0	5	1	63.7	1333.0	---	---
11AX80MI MO	5290	Type5	25	7	1104601.0	5	3	91.2	1409.0	1681.0	1275.0
		Type5	25	0	291202.0	5	2	68.6	1116.0	1171.0	---
		Type5	25	1	191464.0	5	2	83.1	1320.0	1315.0	---
		Type5	25	2	794839.0	5	1	60.9	1564.0	---	---
		Type5	25	3	1002174.0	5	2	77.7	1696.0	1358.0	---

		Type5	25	4	100851.0	5	2	77.4	1793.0	1110.0	---
		Type5	25	5	146185.0	5	2	66.8	1576.0	1423.0	---
		Type5	25	6	1102402.0	5	1	63.7	1333.0	---	---
		Type5	25	7	1104601.0	5	3	91.2	1409.0	1681.0	1275.0
11AX160MI MO	5250	Type5	25	0	291202.0	5	2	68.6	1116.0	1171.0	---
		Type5	25	1	191464.0	5	2	83.1	1320.0	1315.0	---
		Type5	25	2	794839.0	5	1	60.9	1564.0	---	---
		Type5	25	3	1002174.0	5	2	77.7	1696.0	1358.0	---
		Type5	25	4	100851.0	5	2	77.4	1793.0	1110.0	---
		Type5	25	5	146185.0	5	2	66.8	1576.0	1423.0	---
		Type5	25	6	1102402.0	5	1	63.7	1333.0	---	---
		Type5	25	7	1104601.0	5	3	91.2	1409.0	1681.0	1275.0

Test Mode	Channel	Radar Type	Trial ID	Burst ID	Burst Offset (μs)	Chirp Width (MHz)	Number Of Pulses	Pulse Width (μs)	PRI1 (μs)	PRI2 (μs)	PRI3 (μs)
11AX20MI MO	5260	Type5	26	0	176610.0	16	3	88.0	1282.0	1295.0	1165.0
		Type5	26	1	17411.0	16	3	74.0	1926.0	1666.0	1387.0
		Type5	26	2	354336.0	16	1	85.0	1281.0	---	---
		Type5	26	3	510078.0	16	3	85.0	1353.0	1964.0	1631.0
		Type5	26	4	46686.0	16	1	90.0	1267.0	---	---
		Type5	26	5	334144.0	16	3	80.0	1304.0	1113.0	1690.0
		Type5	26	6	386344.0	16	2	65.0	1508.0	1943.0	---
		Type5	26	7	280687.0	16	3	58.0	1397.0	1413.0	1326.0
		Type5	26	8	315397.0	16	2	83.0	1237.0	1124.0	---
		Type5	26	9	209001.0	16	2	90.0	1846.0	1312.0	---
		Type5	26	10	511553.0	16	1	90.0	1685.0	---	---
		Type5	26	11	322303.0	16	3	68.0	1449.0	1166.0	1989.0
		Type5	26	12	629865.0	16	2	81.0	1386.0	1866.0	---
		Type5	26	13	414588.0	16	1	82.0	1958.0	---	---
		Type5	26	14	249199.0	16	3	64.0	1660.0	1115.0	1300.0
		Type5	26	15	362815.0	16	1	63.0	1982.0	---	---
11AX40MI MO	5270	Type5	26	0	176610.0	16	3	88.0	1282.0	1295.0	1165.0
		Type5	26	1	17411.0	16	3	74.0	1926.0	1666.0	1387.0
		Type5	26	2	354336.0	16	1	85.0	1281.0	---	---
		Type5	26	3	510078.0	16	3	85.0	1353.0	1964.0	1631.0
		Type5	26	4	46686.0	16	1	90.0	1267.0	---	---
		Type5	26	5	334144.0	16	3	80.0	1304.0	1113.0	1690.0
		Type5	26	6	386344.0	16	2	65.0	1508.0	1943.0	---
		Type5	26	7	280687.0	16	3	58.0	1397.0	1413.0	1326.0
		Type5	26	8	315397.0	16	2	83.0	1237.0	1124.0	---
		Type5	26	9	209001.0	16	2	90.0	1846.0	1312.0	---
		Type5	26	10	511553.0	16	1	90.0	1685.0	---	---
		Type5	26	11	322303.0	16	3	68.0	1449.0	1166.0	1989.0
		Type5	26	12	629865.0	16	2	81.0	1386.0	1866.0	---
		Type5	26	13	414588.0	16	1	82.0	1958.0	---	---
		Type5	26	14	249199.0	16	3	64.0	1660.0	1115.0	1300.0
		Type5	26	15	362815.0	16	1	63.0	1982.0	---	---
11AX80 MIMO	5290	Type5	26	0	176610.0	16	3	88.0	1282.0	1295.0	1165.0
		Type5	26	1	17411.0	16	3	74.0	1926.0	1666.0	1387.0
		Type5	26	2	354336.0	16	1	85.0	1281.0	---	---
		Type5	26	3	510078.0	16	3	85.0	1353.0	1964.0	1631.0
		Type5	26	4	46686.0	16	1	90.0	1267.0	---	---
		Type5	26	5	334144.0	16	3	80.0	1304.0	1113.0	1690.0

		Type5	26	6	386344.0	16	2	65.0	1508.0	1943.0	---
		Type5	26	7	280687.0	16	3	58.0	1397.0	1413.0	1326.0
		Type5	26	8	315397.0	16	2	83.0	1237.0	1124.0	---
		Type5	26	9	209001.0	16	2	90.0	1846.0	1312.0	---
		Type5	26	10	511553.0	16	1	90.0	1685.0	---	---
		Type5	26	11	322303.0	16	3	68.0	1449.0	1166.0	1989.0
		Type5	26	12	629865.0	16	2	81.0	1386.0	1866.0	---
		Type5	26	13	414588.0	16	1	82.0	1958.0	---	---
		Type5	26	14	249199.0	16	3	64.0	1660.0	1115.0	1300.0
		Type5	26	15	362815.0	16	1	63.0	1982.0	---	---
		Type5	26	16	376201.0	16	3	87.0	1402.0	1051.0	1831.0
11AX160 MIMO	5250	Type5	26	0	176610.0	16	3	88.0	1282.0	1295.0	1165.0
		Type5	26	1	17411.0	16	3	74.0	1926.0	1666.0	1387.0
		Type5	26	2	354336.0	16	1	85.0	1281.0	---	---
		Type5	26	3	510078.0	16	3	85.0	1353.0	1964.0	1631.0
		Type5	26	4	46686.0	16	1	90.0	1267.0	---	---
		Type5	26	5	334144.0	16	3	80.0	1304.0	1113.0	1690.0
		Type5	26	6	386344.0	16	2	65.0	1508.0	1943.0	---
		Type5	26	7	280687.0	16	3	58.0	1397.0	1413.0	1326.0
		Type5	26	8	315397.0	16	2	83.0	1237.0	1124.0	---
		Type5	26	9	209001.0	16	2	90.0	1846.0	1312.0	---
		Type5	26	10	511553.0	16	1	90.0	1685.0	---	---
		Type5	26	11	322303.0	16	3	68.0	1449.0	1166.0	1989.0
		Type5	26	12	629865.0	16	2	81.0	1386.0	1866.0	---
		Type5	26	13	414588.0	16	1	82.0	1958.0	---	---
		Type5	26	14	249199.0	16	3	64.0	1660.0	1115.0	1300.0
		Type5	26	15	362815.0	16	1	63.0	1982.0	---	---
		Type5	26	16	376201.0	16	3	87.0	1402.0	1051.0	1831.0

Test Mode	Channel	Radar Type	Trial ID	Burst ID	Burst Offset (μs)	Chirp Width (MHz)	Number Of Pulses	Pulse Width (μs)	PRI1 (μs)	PRI2 (μs)	PRI3 (μs)
11AX20MI MO	5260	Type5	27	0	127235.0	19	3	86.0	1261.0	1178.0	1125.0
		Type5	27	1	405203.0	19	2	79.0	1604.0	1320.0	---
		Type5	27	2	409964.0	19	1	67.0	1966.0	---	---
		Type5	27	3	415010.0	19	1	79.0	1566.0	---	---
		Type5	27	4	501282.0	19	3	72.0	1864.0	1799.0	1650.0
		Type5	27	5	450861.0	19	3	79.0	1690.0	1469.0	1882.0
		Type5	27	6	430779.0	19	1	86.0	1939.0	---	---
		Type5	27	7	228511.0	19	2	68.0	1291.0	1319.0	---
		Type5	27	8	486234.0	19	3	85.0	1949.0	1558.0	1279.0
		Type5	27	9	245076.0	19	3	80.0	1582.0	1348.0	1472.0
		Type5	27	10	171719.0	19	3	70.0	1819.0	1124.0	1631.0
		Type5	27	11	230250.0	19	1	83.0	1946.0	---	---
		Type5	27	12	480954.0	19	1	74.0	1206.0	---	---
		Type5	27	13	405048.0	19	1	61.0	1285.0	---	---
		Type5	27	14	327282.0	19	2	74.0	1777.0	1200.0	---
		Type5	27	15	222378.0	19	1	85.0	1621.0	---	---
		Type5	27	16	215142.0	19	2	71.0	1960.0	1502.0	---
		Type5	27	17	274277.0	19	1	88.0	1249.0	---	---
		Type5	27	18	463540.0	19	2	80.0	1658.0	1103.0	---
11AX40MI MO	5270	Type5	27	0	127235.0	19	3	86.0	1261.0	1178.0	1125.0
		Type5	27	1	405203.0	19	2	79.0	1604.0	1320.0	---
		Type5	27	2	409964.0	19	1	67.0	1966.0	---	---
		Type5	27	3	415010.0	19	1	79.0	1566.0	---	---
		Type5	27	4	501282.0	19	3	72.0	1864.0	1799.0	1650.0

		Type5	27	5	450861.0	19	3	79.0	1690.0	1469.0	1882.0
		Type5	27	6	430779.0	19	1	86.0	1939.0	---	---
		Type5	27	7	228511.0	19	2	68.0	1291.0	1319.0	---
		Type5	27	8	486234.0	19	3	85.0	1949.0	1558.0	1279.0
		Type5	27	9	245076.0	19	3	80.0	1582.0	1348.0	1472.0
		Type5	27	10	171719.0	19	3	70.0	1819.0	1124.0	1631.0
		Type5	27	11	230250.0	19	1	83.0	1946.0	---	---
		Type5	27	12	480954.0	19	1	74.0	1206.0	---	---
		Type5	27	13	405048.0	19	1	61.0	1285.0	---	---
		Type5	27	14	327282.0	19	2	74.0	1777.0	1200.0	---
		Type5	27	15	222378.0	19	1	85.0	1621.0	---	---
		Type5	27	16	215142.0	19	2	71.0	1960.0	1502.0	---
		Type5	27	17	274277.0	19	1	88.0	1249.0	---	---
		Type5	27	18	463540.0	19	2	80.0	1658.0	1103.0	---
11AX80MI MO	5290	Type5	27	0	127235.0	19	3	86.0	1261.0	1178.0	1125.0
		Type5	27	1	405203.0	19	2	79.0	1604.0	1320.0	---
		Type5	27	2	409964.0	19	1	67.0	1966.0	---	---
		Type5	27	3	415010.0	19	1	79.0	1566.0	---	---
		Type5	27	4	501282.0	19	3	72.0	1864.0	1799.0	1650.0
		Type5	27	5	450861.0	19	3	79.0	1690.0	1469.0	1882.0
		Type5	27	6	430779.0	19	1	86.0	1939.0	---	---
		Type5	27	7	228511.0	19	2	68.0	1291.0	1319.0	---
		Type5	27	8	486234.0	19	3	85.0	1949.0	1558.0	1279.0
		Type5	27	9	245076.0	19	3	80.0	1582.0	1348.0	1472.0
		Type5	27	10	171719.0	19	3	70.0	1819.0	1124.0	1631.0
		Type5	27	11	230250.0	19	1	83.0	1946.0	---	---
		Type5	27	12	480954.0	19	1	74.0	1206.0	---	---
		Type5	27	13	405048.0	19	1	61.0	1285.0	---	---
		Type5	27	14	327282.0	19	2	74.0	1777.0	1200.0	---
		Type5	27	15	222378.0	19	1	85.0	1621.0	---	---
		Type5	27	16	215142.0	19	2	71.0	1960.0	1502.0	---
		Type5	27	17	274277.0	19	1	88.0	1249.0	---	---
11AX160MI MO	5250	Type5	27	18	463540.0	19	2	80.0	1658.0	1103.0	---
		Type5	27	0	127235.0	19	3	86.0	1261.0	1178.0	1125.0
		Type5	27	1	405203.0	19	2	79.0	1604.0	1320.0	---
		Type5	27	2	409964.0	19	1	67.0	1966.0	---	---
		Type5	27	3	415010.0	19	1	79.0	1566.0	---	---
		Type5	27	4	501282.0	19	3	72.0	1864.0	1799.0	1650.0
		Type5	27	5	450861.0	19	3	79.0	1690.0	1469.0	1882.0
		Type5	27	6	430779.0	19	1	86.0	1939.0	---	---
		Type5	27	7	228511.0	19	2	68.0	1291.0	1319.0	---
		Type5	27	8	486234.0	19	3	85.0	1949.0	1558.0	1279.0
		Type5	27	9	245076.0	19	3	80.0	1582.0	1348.0	1472.0
		Type5	27	10	171719.0	19	3	70.0	1819.0	1124.0	1631.0
		Type5	27	11	230250.0	19	1	83.0	1946.0	---	---
		Type5	27	12	480954.0	19	1	74.0	1206.0	---	---
		Type5	27	13	405048.0	19	1	61.0	1285.0	---	---
		Type5	27	14	327282.0	19	2	74.0	1777.0	1200.0	---
		Type5	27	15	222378.0	19	1	85.0	1621.0	---	---
		Type5	27	16	215142.0	19	2	71.0	1960.0	1502.0	---
		Type5	27	17	274277.0	19	1	88.0	1249.0	---	---
		Type5	27	18	463540.0	19	2	80.0	1658.0	1103.0	---

Test Mode	Channel	Radar Type	Trial ID	Burst ID	Burst Offset (μs)	Chirp Width (MHz)	Number Of Pulses	Pulse Width (μs)	PRI1 (μs)	PRI2 (μs)	PRI3 (μs)
11AX20MI MO	5260	Type5	28	0	306103.0	10	1	83.0	1812.0	---	---
		Type5	28	1	508105.0	10	1	84.0	1472.0	---	---
		Type5	28	2	539450.0	10	3	50.0	1217.0	1552.0	1984.0
		Type5	28	3	327643.0	10	2	79.0	1841.0	1634.0	---
		Type5	28	4	516046.0	10	2	58.0	1485.0	1692.0	---
		Type5	28	5	828741.0	10	3	53.0	1253.0	1746.0	1562.0
		Type5	28	6	558224.0	10	2	50.0	1336.0	1327.0	---
		Type5	28	7	296916.0	10	3	82.0	1210.0	1252.0	1123.0
		Type5	28	8	314875.0	10	3	59.0	1283.0	1706.0	1411.0
		Type5	28	9	431902.0	10	2	65.0	1681.0	1620.0	---
		Type5	28	10	420211.0	10	1	85.0	1804.0	---	---
11AX40MI MO	5270	Type5	28	11	634171.0	10	1	81.0	1729.0	---	---
		Type5	28	0	306103.0	10	1	83.0	1812.0	---	---
		Type5	28	1	508105.0	10	1	84.0	1472.0	---	---
		Type5	28	2	539450.0	10	3	50.0	1217.0	1552.0	1984.0
		Type5	28	3	327643.0	10	2	79.0	1841.0	1634.0	---
		Type5	28	4	516046.0	10	2	58.0	1485.0	1692.0	---
		Type5	28	5	828741.0	10	3	53.0	1253.0	1746.0	1562.0
		Type5	28	6	558224.0	10	2	50.0	1336.0	1327.0	---
		Type5	28	7	296916.0	10	3	82.0	1210.0	1252.0	1123.0
		Type5	28	8	314875.0	10	3	59.0	1283.0	1706.0	1411.0
		Type5	28	9	431902.0	10	2	65.0	1681.0	1620.0	---
11AX80MI MO	5290	Type5	28	10	420211.0	10	1	85.0	1804.0	---	---
		Type5	28	11	634171.0	10	1	81.0	1729.0	---	---
		Type5	28	0	306103.0	10	1	83.0	1812.0	---	---
		Type5	28	1	508105.0	10	1	84.0	1472.0	---	---
		Type5	28	2	539450.0	10	3	50.0	1217.0	1552.0	1984.0
		Type5	28	3	327643.0	10	2	79.0	1841.0	1634.0	---
		Type5	28	4	516046.0	10	2	58.0	1485.0	1692.0	---
		Type5	28	5	828741.0	10	3	53.0	1253.0	1746.0	1562.0
		Type5	28	6	558224.0	10	2	50.0	1336.0	1327.0	---
		Type5	28	7	296916.0	10	3	82.0	1210.0	1252.0	1123.0
		Type5	28	8	314875.0	10	3	59.0	1283.0	1706.0	1411.0
11AX160MI MO	5250	Type5	28	9	431902.0	10	2	65.0	1681.0	1620.0	---
		Type5	28	10	420211.0	10	1	85.0	1804.0	---	---
		Type5	28	11	634171.0	10	1	81.0	1729.0	---	---
		Type5	28	0	306103.0	10	1	83.0	1812.0	---	---
		Type5	28	1	508105.0	10	1	84.0	1472.0	---	---
		Type5	28	2	539450.0	10	3	50.0	1217.0	1552.0	1984.0
		Type5	28	3	327643.0	10	2	79.0	1841.0	1634.0	---
		Type5	28	4	516046.0	10	2	58.0	1485.0	1692.0	---
		Type5	28	5	828741.0	10	3	53.0	1253.0	1746.0	1562.0
		Type5	28	6	558224.0	10	2	50.0	1336.0	1327.0	---
		Type5	28	7	296916.0	10	3	82.0	1210.0	1252.0	1123.0
		Type5	28	8	314875.0	10	3	59.0	1283.0	1706.0	1411.0
		Type5	28	9	431902.0	10	2	65.0	1681.0	1620.0	---
		Type5	28	10	420211.0	10	1	85.0	1804.0	---	---
		Type5	28	11	634171.0	10	1	81.0	1729.0	---	---

Test Mode	Channel	Radar Type	Trial ID	Burst ID	Burst Offset (μs)	Chirp Width (MHz)	Number Of Pulses	Pulse Width (μs)	PRI1 (μs)	PRI2 (μs)	PRI3 (μs)
11AX20MI MO	5260	Type5	29	0	565749.0	17	3	69.0	1824.0	1395.0	1881.0
		Type5	29	1	263479.0	17	3	68.0	1231.0	1654.0	1635.0
		Type5	29	2	190890.0	17	3	85.0	1729.0	1216.0	1624.0
		Type5	29	3	584648.0	17	3	78.0	1273.0	1345.0	1802.0
		Type5	29	4	242495.0	17	3	69.0	1721.0	1123.0	1766.0
		Type5	29	5	587369.0	17	1	65.0	1787.0	---	---
		Type5	29	6	261172.0	17	2	65.0	1772.0	1137.0	---
		Type5	29	7	450000.0	17	3	84.0	1501.0	1128.0	1828.0
		Type5	29	8	192068.0	17	3	77.0	1563.0	1599.0	1442.0
		Type5	29	9	160660.0	17	3	77.0	1457.0	1373.0	1087.0
		Type5	29	10	310337.0	17	1	67.0	1684.0	---	---
		Type5	29	11	568802.0	17	2	89.0	1490.0	1405.0	---
		Type5	29	12	558173.0	17	1	80.0	1618.0	---	---
		Type5	29	13	460266.0	17	2	74.0	1763.0	1456.0	---
		Type5	29	14	383361.0	17	2	67.0	1667.0	1112.0	---
		Type5	29	15	212766.0	17	1	89.0	1860.0	---	---
		Type5	29	16	370314.0	17	2	69.0	1623.0	1786.0	---
11AX40MI MO	5270	Type5	29	0	565749.0	17	3	69.0	1824.0	1395.0	1881.0
		Type5	29	1	263479.0	17	3	68.0	1231.0	1654.0	1635.0
		Type5	29	2	190890.0	17	3	85.0	1729.0	1216.0	1624.0
		Type5	29	3	584648.0	17	3	78.0	1273.0	1345.0	1802.0
		Type5	29	4	242495.0	17	3	69.0	1721.0	1123.0	1766.0
		Type5	29	5	587369.0	17	1	65.0	1787.0	---	---
		Type5	29	6	261172.0	17	2	65.0	1772.0	1137.0	---
		Type5	29	7	450000.0	17	3	84.0	1501.0	1128.0	1828.0
		Type5	29	8	192068.0	17	3	77.0	1563.0	1599.0	1442.0
		Type5	29	9	160660.0	17	3	77.0	1457.0	1373.0	1087.0
		Type5	29	10	310337.0	17	1	67.0	1684.0	---	---
		Type5	29	11	568802.0	17	2	89.0	1490.0	1405.0	---
		Type5	29	12	558173.0	17	1	80.0	1618.0	---	---
		Type5	29	13	460266.0	17	2	74.0	1763.0	1456.0	---
		Type5	29	14	383361.0	17	2	67.0	1667.0	1112.0	---
		Type5	29	15	212766.0	17	1	89.0	1860.0	---	---
		Type5	29	16	370314.0	17	2	69.0	1623.0	1786.0	---
11AX80MI MO	5290	Type5	29	0	565749.0	17	3	69.0	1824.0	1395.0	1881.0
		Type5	29	1	263479.0	17	3	68.0	1231.0	1654.0	1635.0
		Type5	29	2	190890.0	17	3	85.0	1729.0	1216.0	1624.0
		Type5	29	3	584648.0	17	3	78.0	1273.0	1345.0	1802.0
		Type5	29	4	242495.0	17	3	69.0	1721.0	1123.0	1766.0
		Type5	29	5	587369.0	17	1	65.0	1787.0	---	---
		Type5	29	6	261172.0	17	2	65.0	1772.0	1137.0	---
		Type5	29	7	450000.0	17	3	84.0	1501.0	1128.0	1828.0
		Type5	29	8	192068.0	17	3	77.0	1563.0	1599.0	1442.0
		Type5	29	9	160660.0	17	3	77.0	1457.0	1373.0	1087.0
		Type5	29	10	310337.0	17	1	67.0	1684.0	---	---
		Type5	29	11	568802.0	17	2	89.0	1490.0	1405.0	---
		Type5	29	12	558173.0	17	1	80.0	1618.0	---	---
		Type5	29	13	460266.0	17	2	74.0	1763.0	1456.0	---
		Type5	29	14	383361.0	17	2	67.0	1667.0	1112.0	---
		Type5	29	15	212766.0	17	1	89.0	1860.0	---	---
		Type5	29	16	370314.0	17	2	69.0	1623.0	1786.0	---
11AX160MI MO	5250	Type5	29	0	565749.0	17	3	69.0	1824.0	1395.0	1881.0
		Type5	29	1	263479.0	17	3	68.0	1231.0	1654.0	1635.0

	Type5	29	2	190890.0	17	3	85.0	1729.0	1216.0	1624.0
	Type5	29	3	584648.0	17	3	78.0	1273.0	1345.0	1802.0
	Type5	29	4	242495.0	17	3	69.0	1721.0	1123.0	1766.0
	Type5	29	5	587369.0	17	1	65.0	1787.0	---	---
	Type5	29	6	261172.0	17	2	65.0	1772.0	1137.0	---
	Type5	29	7	450000.0	17	3	84.0	1501.0	1128.0	1828.0
	Type5	29	8	192068.0	17	3	77.0	1563.0	1599.0	1442.0
	Type5	29	9	160660.0	17	3	77.0	1457.0	1373.0	1087.0
	Type5	29	10	310337.0	17	1	67.0	1684.0	---	---
	Type5	29	11	568802.0	17	2	89.0	1490.0	1405.0	---
	Type5	29	12	558173.0	17	1	80.0	1618.0	---	---
	Type5	29	13	460266.0	17	2	74.0	1763.0	1456.0	---
	Type5	29	14	383361.0	17	2	67.0	1667.0	1112.0	---
	Type5	29	15	212766.0	17	1	89.0	1860.0	---	---
	Type5	29	16	370314.0	17	2	69.0	1623.0	1786.0	---
	Type5	29	17	427878.0	17	2	86.0	1658.0	1668.0	---

Test Mode	Frequen cy[MHz]	Radar Type	Trial ID	Pulse width (μs)	PRI (μs)	Pulses per Hop	Detection (1: Yes; 0: No)
11AX20 MIMO	5260	Type6	0	1	333.3	9	1
		Type6	1	1	333.3	9	1
		Type6	2	1	333.3	9	1
		Type6	3	1	333.3	9	1
		Type6	4	1	333.3	9	1
		Type6	5	1	333.3	9	1
		Type6	6	1	333.3	9	1
		Type6	7	1	333.3	9	1
		Type6	8	1	333.3	9	1
		Type6	9	1	333.3	9	1
		Type6	10	1	333.3	9	1
		Type6	11	1	333.3	9	1
		Type6	12	1	333.3	9	1
		Type6	13	1	333.3	9	1
		Type6	14	1	333.3	9	1
		Type6	15	1	333.3	9	1
		Type6	16	1	333.3	9	1
		Type6	17	1	333.3	9	1
		Type6	18	1	333.3	9	1
		Type6	19	1	333.3	9	1
		Type6	20	1	333.3	9	1
		Type6	21	1	333.3	9	1
		Type6	22	1	333.3	9	1
		Type6	23	1	333.3	9	1
		Type6	24	1	333.3	9	1
		Type6	25	1	333.3	9	1
		Type6	26	1	333.3	9	1
		Type6	27	1	333.3	9	1
		Type6	28	1	333.3	9	1
		Type6	29	1	333.3	9	1
11AX40 MIMO	5270	Type6	0	1	333.3	9	1
		Type6	1	1	333.3	9	1
		Type6	2	1	333.3	9	1
		Type6	3	1	333.3	9	1
		Type6	4	1	333.3	9	1
		Type6	5	1	333.3	9	1
		Type6	6	1	333.3	9	1
		Type6	7	1	333.3	9	1

		Type6	8	1	333.3	9	1
		Type6	9	1	333.3	9	1
		Type6	10	1	333.3	9	1
		Type6	11	1	333.3	9	1
		Type6	12	1	333.3	9	1
		Type6	13	1	333.3	9	1
		Type6	14	1	333.3	9	1
		Type6	15	1	333.3	9	1
		Type6	16	1	333.3	9	1
		Type6	17	1	333.3	9	1
		Type6	18	1	333.3	9	1
		Type6	19	1	333.3	9	1
		Type6	20	1	333.3	9	1
		Type6	21	1	333.3	9	1
		Type6	22	1	333.3	9	1
		Type6	23	1	333.3	9	1
		Type6	24	1	333.3	9	1
		Type6	25	1	333.3	9	1
		Type6	26	1	333.3	9	1
		Type6	27	1	333.3	9	1
		Type6	28	1	333.3	9	1
		Type6	29	1	333.3	9	1
11AX80 MIMO	5290	Type6	0	1	333.3	9	1
		Type6	1	1	333.3	9	1
		Type6	2	1	333.3	9	1
		Type6	3	1	333.3	9	1
		Type6	4	1	333.3	9	1
		Type6	5	1	333.3	9	1
		Type6	6	1	333.3	9	1
		Type6	7	1	333.3	9	1
		Type6	8	1	333.3	9	1
		Type6	9	1	333.3	9	1
		Type6	10	1	333.3	9	1
		Type6	11	1	333.3	9	1
		Type6	12	1	333.3	9	1
		Type6	13	1	333.3	9	1
		Type6	14	1	333.3	9	1
		Type6	15	1	333.3	9	1
		Type6	16	1	333.3	9	1
		Type6	17	1	333.3	9	1
		Type6	18	1	333.3	9	1
		Type6	19	1	333.3	9	1
		Type6	20	1	333.3	9	1
		Type6	21	1	333.3	9	1
		Type6	22	1	333.3	9	1
		Type6	23	1	333.3	9	1
		Type6	24	1	333.3	9	1
		Type6	25	1	333.3	9	1
		Type6	26	1	333.3	9	1
		Type6	27	1	333.3	9	1
		Type6	28	1	333.3	9	1
		Type6	29	1	333.3	9	1
11AX160 MIMO	5250	Type6	0	1	333.3	9	1
		Type6	1	1	333.3	9	1
		Type6	2	1	333.3	9	1
		Type6	3	1	333.3	9	1
		Type6	4	1	333.3	9	1
		Type6	5	1	333.3	9	1
		Type6	6	1	333.3	9	1
		Type6	7	1	333.3	9	1
		Type6	8	1	333.3	9	1

		Type6	9	1	333.3	9	1
		Type6	10	1	333.3	9	1
		Type6	11	1	333.3	9	1
		Type6	12	1	333.3	9	1
		Type6	13	1	333.3	9	1
		Type6	14	1	333.3	9	1
		Type6	15	1	333.3	9	1
		Type6	16	1	333.3	9	1
		Type6	17	1	333.3	9	1
		Type6	18	1	333.3	9	1
		Type6	19	1	333.3	9	1
		Type6	20	1	333.3	9	1
		Type6	21	1	333.3	9	1
		Type6	22	1	333.3	9	1
		Type6	23	1	333.3	9	1
		Type6	24	1	333.3	9	1
		Type6	25	1	333.3	9	1
		Type6	26	1	333.3	9	1
		Type6	27	1	333.3	9	1
		Type6	28	1	333.3	9	1
		Type6	29	1	333.3	9	1

Bridge mode:

Test Mode	Frequency [MHz]	Radar Type	Trial ID	Pulse width(μs)	PRI(μs)	Pulses per Burst	Detection (1: Yes; 0: No)
11AX40MI MO	5270	Type4	0	16.0	355.0	14	1
		Type4	1	11.3	487.0	12	1
		Type4	2	13.5	344.0	13	1
		Type4	3	19.4	288.0	16	1
		Type4	4	17.5	230.0	15	1
		Type4	5	15.3	432.0	14	1
		Type4	6	15.9	207.0	14	1
		Type4	7	14.3	443.0	13	1
		Type4	8	15.8	439.0	14	1
		Type4	9	11.5	223.0	12	1
		Type4	10	17.4	208.0	15	1
		Type4	11	19.0	463.0	16	1
		Type4	12	16.0	441.0	14	1
		Type4	13	13.8	323.0	13	1
		Type4	14	18.9	297.0	16	1
		Type4	15	15.5	412.0	14	1
		Type4	16	19.9	324.0	16	1
		Type4	17	14.1	271.0	13	1
		Type4	18	15.2	349.0	14	1
		Type4	19	13.8	409.0	13	1
		Type4	20	17.1	373.0	15	1
		Type4	21	13.8	254.0	13	1
		Type4	22	19.8	274.0	16	1
		Type4	23	15.3	278.0	14	1
		Type4	24	14.5	317.0	13	1
		Type4	25	11.3	260.0	12	1
		Type4	26	17.3	211.0	15	1
		Type4	27	19.2	272.0	16	1
		Type4	28	14.2	264.0	13	1
		Type4	29	18.2	284.0	15	1

***** END OF REPORT *****