

# Test Report TR3609C

---

<b>Equipment Under Test:</b>	Latch PCB
<b>Requirement(s):</b>	FCC 1.1310
<b>Test Date(s):</b>	4/10/2023 - 4/13/2023
<b>Prepared for:</b>	Eberhard Attn: Rob Pliml 21944 Drake Road Strongsville, OH 44149

---

**Report Issued by:** Anthony Smith, EMC Engineering Specialist

Signature: 

Date: 12/11/2023

**Report Reviewed by:** Adam Alger, Laboratory Manager

Signature: 

Date: 12/11/2023

**Report Constructed by:** Anthony Smith, EMC Engineering Specialist

Signature: 

Date: 12/5/2023

*This test report may not be reproduced, except in full, without approval of Laird Connectivity LLC*

Company: Eberhard	Page 1 of 12	Name: Latch PCB
Report: TR3609C		Model: 17240-25
Quote: NBO-04-2022-004907		Serial: Engineering Sample

## CONTENTS

Contents.....	2
Laird Connectivity Test Services in Review .....	3
1    Test Report Summary .....	4
2    Client Information.....	5
2.1    Equipment Under Test (EUT) Information .....	5
2.2    Product Description .....	5
2.3    Modifications Incorporated for Compliance.....	5
2.4    Deviations and Exclusions from Test Specifications .....	5
2.5    Additional Information.....	5
3    References .....	6
4    Uncertainty Summary .....	7
5    Test Data .....	8
5.1    Antenna Port Conducted Emissions.....	8
6    FCC 1-G SAR Test Exclusion Calculations .....	11
7    Revision History .....	12

Company: Eberhard	Page 2 of 12	Name: Latch PCB
Report: TR3609C		Model: 17240-25
Quote: NBO-04-2022-004907		Serial: Engineering Sample

## Laird Connectivity Test Services in Review

The Laird Connectivity LLC laboratory located at W66 N220 Commerce Court Cedarburg, Wisconsin, 53012 USA is recognized through the following organizations:



### A2LA – American Association for Laboratory Accreditation

*Accreditation based on ISO/IEC 17025:2017 with Electrical (EMC) Scope*

*A2LA Certificate Number: 1255.01*

*Scope of accreditation includes all test methods listed herein unless otherwise noted*

---



### Federal Communications Commission (FCC) – USA

*Accredited Test Firm Registration Number: 953492*

*Recognition of two 3 meter Semi-Anechoic Chambers*

---



Government  
of Canada

### Innovation, Science and Economic Development Canada

*Accredited U.S. Identification Number: US0218*

*Recognition of two 3 meter Semi-Anechoic Chambers*

Company: Eberhard	Page 3 of 12	Name: Latch PCB
Report: TR3609C		Model: 17240-25
Quote: NBO-04-2022-004907		Serial: Engineering Sample

## 1 TEST REPORT SUMMARY

During **April 10<sup>th</sup>, 2023 to April 13<sup>th</sup>, 2023** the Equipment Under Test (EUT), **Latch PCB**, as provided by **Eberhard** was tested to the following requirements:

Requirements	Description	Method	Result
FCC: 1.1310	Radiofrequency Radiation Exposure Limits	Distance ≤ 5 mm 1g-SAR	Reported

### Notice:

The results relate only to the item tested as configured and described in this report. Any additional configurations, modes of operation, or modifications made to the equipment under test after the specified test date(s) are at the decision of the client and may not apply to the data seen in this test report.

The decision rule for Pass / Fail assessment to the specification or standard listed in this test report has been agreed upon by the client and laboratory to be as follows:

Measurement Type	Rule
Emissions – Amplitude	1 dB below specified limit
Emissions – Frequency	1% less than the specification
Immunity	Tested at specified level

Company: Eberhard	Page 4 of 12	Name: Latch PCB
Report: TR3609C		Model: 17240-25
Quote: NBO-04-2022-004907		Serial: Engineering Sample

## 2 CLIENT INFORMATION

Company Name	Eberhard
Contact Person	Rob Pliml
Address	21944 Drake Road Strongsville, OH 44149

### 2.1 Equipment Under Test (EUT) Information

*The following information has been supplied by the client*

Product Name	Latch PCB
Model Number	17240-25
Serial Number	Engineering Sample
FCC ID	2BATJ-1724058

### 2.2 Product Description

Latch PCB

### 2.3 Modifications Incorporated for Compliance

None noted at time of test

### 2.4 Deviations and Exclusions from Test Specifications

None noted at time of test

### 2.5 Additional Information

Device programmed via USB micro to UART board to UART serial connection to PCB utilizing "YAT" terminal emulation software version 2.5.0. Device powered via 12V Battery. Device uses Bluetooth Low Energy with 1M data rate. Power Setting 2 used for final compliance.

Antenna is an "Inverted F" trace antenna with a peak gain of 3.2 dBi (see TR3609D).

Company: Eberhard	Page 5 of 12	Name: Latch PCB
Report: TR3609C		Model: 17240-25
Quote: NBO-04-2022-004907		Serial: Engineering Sample

### 3 REFERENCES

Publication	Edition	Date
FCC eCFR	-	2023
KDB 447498	-	2015

Company: Eberhard	Page 6 of 12	Name: Latch PCB
Report: TR3609C		Model: 17240-25
Quote: NBO-04-2022-004907		Serial: Engineering Sample

## 4 UNCERTAINTY SUMMARY

Using the guidance of the following publications the calculated measurement uncertainty represents an expanded uncertainty expressed at approximately the 95 % confidence level, using a coverage factor of  $k = 2$ .

References
CISPR 16-4-1
CISPR 16-4-2
CISPR 32
ANSI C63.23
A2LA P103
A2LA P103c
ETSI TR 100-028

Measurement Type	Configuration	Uncertainty $\pm$
Radiated Emissions	Biconical Antenna	5.0 dB
Radiated Emissions	Log Periodic Antenna	5.3 dB
Radiated Emissions	Horn Antenna	4.7 dB
AC Line Conducted Emissions	Artificial Mains Network	3.4 dB
Telecom Conducted Emissions	Asymmetric Artificial Network	4.9 dB
Disturbance Power Emissions	Absorbing Clamp	4.1 dB
Radiated Immunity	3 Volts/meter	2.2 dB
Conducted Immunity	CDN/EM/BCI	2.4/3.5/3.4 dB
EFT Burst/Surge	Peak pulse voltage	164 volts
ESD Immunity	15 kV level	1377 Volts

Parameter	ETSI U.C. $\pm$	U.C. $\pm$
Radio Frequency, from F0	$1 \times 10^{-7}$	$0.55 \times 10^{-7}$
Occupied Channel Bandwidth	5 %	2 %
RF conducted Power (Power Meter)	1.5 dB	1.2 dB
RF conducted emissions (Spectrum Analyzer)	3.0 dB	1.7 dB
All emissions, radiated	6.0 dB	5.3 dB
Temperature	1° C	0.65° C
Humidity	5 %	2.9 %
Supply voltages	3 %	1 %


Company: Eberhard	Page 7 of 12	Name: Latch PCB
Report: TR3609C		Model: 17240-25
Quote: NBO-04-2022-004907		Serial: Engineering Sample

## 5 TEST DATA

### 5.1 Antenna Port Conducted Emissions

<b>Description of Measurement</b>	<p>The direct measurement of emissions at the antenna port of the EUT is achieved by use of a RF connection to a spectrum analyzer or power meter.</p> <p>The cable and attenuator factors are loaded into the analyzer or power meter allowing for direct measurement readings without the need for further corrections.</p>
<b>Example Calculations</b>	<p>Measurement (dBm) + Cable factor (dB) + External Attenuator (dB) = Corrected Reading (dBm)</p> <p>Margin (dB) = Limit (dBm) – Corrected Reading (dBm)</p>

#### Block Diagram



#### Instrumentation

Asset #	Description	Manufacturer	Model #	Serial #	Date	Due Date	Status
AA 960172	Cable	A.H. Systems, Inc.	SAC-26G-1	387	3/22/2023	3/22/2024	Active Verification
EE 960085	Analyzer - EMI Receiver	Agilent	N9038A	MY51210148	4/11/2023	4/11/2024	Active Calibration
EE 960203	Analyzer - EMI Receiver	Keysight	N9038A	MY56400072	4/13/2023	4/13/2024	Active Calibration

Company: Eberhard	Page 8 of 12	Name: Latch PCB
Report: TR3609C		Model: 17240-25
Quote: NBO-04-2022-004907		Serial: Engineering Sample

### 5.1.1 Antenna Port Conducted Emissions – Max Conducted Output Power

<b>Operator</b>	Anthony Smith	<b>QA</b>	Adam Alger
<b>Temperature</b>	21.9, 22.5, 22.9°C	<b>R.H. %</b>	31.8, 34.3, 39.9%
<b>Test Date</b>	4/10/2023, 4/12/2023, 4/13/2023	<b>Location</b>	Chamber 3
<b>Requirement</b>	FCC: 15.247 (b)(3)	<b>Method</b>	ANSI C63.10 §11.9

**Limits:** <30 dBm

#### Test Parameters

<b>Frequency</b>	2402, 2440, 2480 MHz	<b>Setup</b>	Conducted
<b>RBW</b>	3 MHz	<b>VBW</b>	50 MHz
<b>Detector(s)</b>	Max Peak Hold	<b>Sweep Time</b>	Auto

#### EUT Parameters

<b>Input Power</b>	12VDC (Battery)	<b>Mode</b>	BLE Transmit
<b>Frequency</b>	2402, 2440, 2480 MHz	<b>Channel</b>	37, 17, 39
<b>Data Rate / Modulation</b>	BLE 1Mbps	<b>Transmit Power Setting</b>	2


#### Data

#### Table

Channel	Data Rate	Transmit Power Setting	Peak Output Power (dBm)	Limit (dBm)	Margin (dB)
37	BLE 1Mbps	2	-0.4	30.0	30.4
17	BLE 1Mbps	2	-0.1	30.0	30.1
39	BLE 1Mbps	2	0.1	30.0	29.9

Company: Eberhard	Page 9 of 12	Name: Latch PCB
Report: TR3609C		Model: 17240-25
Quote: NBO-04-2022-004907		Serial: Engineering Sample

## Plots



## 6 FCC 1-G SAR TEST EXCLUSION CALCULATIONS

### 6.1 Power Calculations

Max Power of Channel = 0.1 dBm

Tune Up Tolerance = 1 dB

Total Channel Power = 1.1 dBm = 1.3 mW = 1 mW

### 6.2 Distance

$\leq 5$  mm

### 6.3 SAR Test Exclusion Calculation

$[(\text{Maximum power of channel, including tune-up tolerance, mW}) / (\text{Minimum test separation distance, mm})] * [\sqrt{f(\text{GHz})}] \leq 3$  for 1-g SAR

Where:

- $F(\text{GHz})$  is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- The value 3.0 is referred to as numeric thresholds

$$\left(\frac{1\text{mW}}{5\text{mm}}\right) \times (\sqrt{2.48}) \leq 3.0$$

$$0.2 \times 1.575 \leq 3.0$$

$$0.3 \leq 3.0$$

### 6.4 Result

The EUT is excluded from routine SAR testing as 0.3 is less than 3.0.

Company: Eberhard	Page 11 of 12	Name: Latch PCB
Report: TR3609C		Model: 17240-25
Quote: NBO-04-2022-004907		Serial: Engineering Sample

## 7 REVISION HISTORY

Version	Date	Notes	Person
0	5/10/2023	Initial Draft	Anthony Smith
1	8/2/2023	Revised Draft	Anthony Smith
2	8/17/2023	Revised Draft	Anthony Smith
3	12/5/2023	Revised Draft	Anthony Smith

**END OF REPORT**

Company: Eberhard	Page 12 of 12	Name: Latch PCB
Report: TR3609C		Model: 17240-25
Quote: NBO-04-2022-004907		Serial: Engineering Sample