




WCDMA Band4 Channel=1312




WCDMA Band4 Channel=1450




WCDMA Band4 Channel=1513




WCDMA Band5 Channel=4132



WCDMA Band5 Channel=4182



WCDMA Band5 Channel=4233



Band edge

Band	Channel	Frequency (MHz)	Spur Freq (MHz)	Spur Level (dBm)	Limit (dBm)	Verdict
WCDMA Band2	9262	1852.4	1850.00	-25.31	-13	PASS
WCDMA Band2	9538	1907.6	1910.00	-25.50	-13	PASS
WCDMA Band4	1312	1712.4	1710.00	-23.79	-13	PASS
WCDMA Band4	1513	1752.6	1755.00	-22.25	-13	PASS
WCDMA Band5	4132	826.4	824.00	-23.60	-13	PASS
WCDMA Band5	4233	846.6	849.00	-24.47	-13	PASS

WCDMA Band2 Channel=9262



WCDMA Band2 Channel=9538




WCDMA Band4 Channel=1312



WCDMA Band4 Channel=1513



WCDMA Band5 Channel=4132




WCDMA Band5 Channel=4233




Out-of-band emissions

Band	Channel	Frequency (MHz)	Spur Freq (MHz)	Spur Level (dBm)	Limit (dBm)	Verdict
WCDMA Band2	9262	1852.4	16434.36	-22.55	-13	PASS
WCDMA Band2	9400	1880	19638.04	-21.58	-13	PASS
WCDMA Band2	9538	1907.6	19447.83	-22.30	-13	PASS
WCDMA Band4	1312	1712.4	19008.99	-22.72	-13	PASS
WCDMA Band4	1450	1740	19889.67	-22.87	-13	PASS
WCDMA Band4	1513	1752.6	18942.59	-23.19	-13	PASS
WCDMA Band5	4132	826.4	6014.49	-29.80	-13	PASS
WCDMA Band5	4182	836.4	7322.31	-29.20	-13	PASS
WCDMA Band5	4233	846.6	7505.76	-29.85	-13	PASS


WCDMA Band2 Channel=9262




WCDMA Band2 Channel=9400




WCDMA Band2 Channel=9538



WCDMA Band4 Channel=1312




WCDMA Band4 Channel=1450




WCDMA Band4 Channel=1513




WCDMA Band5 Channel=4132



WCDMA Band5 Channel=4182



WCDMA Band5 Channel=4233



RADIATED SPURIOUS EMISSION

Note: (1) Spurious emissions which are attenuated by more than 20dB below the permissible value for frequency below 1000MHz.

(2) Test is divided into three directions, X/Y/Z. X pattern for the worst.

WCDMA Band 2: (30-20000)MHz							
The Worst Test Results for Channel 9262/1852.4MHz							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea	Limit	Margin	Polarity
				(dBm)	(dBm)	(dBm)	
3703.99	-25.77	7.00	12.93	-31.70	-13.00	-18.70	H
5557.38	-25.97	8.20	17.11	-34.88	-13.00	-21.88	H
7409.52	-27.24	8.10	22.20	-41.34	-13.00	-28.34	H
3704.40	-29.08	7.00	12.93	-35.01	-13.00	-22.01	V
5557.55	-25.86	8.20	17.11	-34.77	-13.00	-21.77	V
7409.75	-28.12	8.10	22.20	-42.22	-13.00	-29.22	V
The Worst Test Results for Channel 9400/1880MHz							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea	Limit	Margin	Polarity
				(dBm)	(dBm)	(dBm)	
3760.11	-27.67	7.00	12.93	-33.60	-13.00	-20.60	H
5640.03	-26.96	8.20	17.11	-35.87	-13.00	-22.87	H
7520.16	-28.48	8.10	22.20	-42.58	-13.00	-29.58	H
3760.24	-26.65	7.00	12.93	-32.58	-13.00	-19.58	V
5640.32	-26.62	8.20	17.11	-35.53	-13.00	-22.53	V
7520.18	-26.33	8.10	22.20	-40.43	-13.00	-27.43	V
The Worst Test Results for Channel 9538/1907.6MHz							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea	Limit	Margin	Polarity
				(dBm)	(dBm)	(dBm)	
3815.71	-29.52	7.00	12.93	-35.45	-13.00	-22.45	H
5722.49	-25.56	8.20	17.11	-34.47	-13.00	-21.47	H
7629.93	-24.84	8.10	22.20	-38.94	-13.00	-25.94	H
3815.58	-27.92	7.00	12.93	-33.85	-13.00	-20.85	V
5722.26	-30.02	8.20	17.11	-38.93	-13.00	-25.93	V
7629.97	-27.34	8.10	22.20	-41.44	-13.00	-28.44	V

HSUPA Band 2: (30-20000)MHz							
The Worst Test Results for Channel 9262/1852.4MHz							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea	Limit	Margin	Polarity
				(dBm)	(dBm)	(dBm)	
3704.22	-27.11	7.00	12.93	-33.04	-13.00	-20.04	H
5557.66	-26.83	8.20	17.11	-35.74	-13.00	-22.74	H
7409.58	-23.91	8.10	22.20	-38.01	-13.00	-25.01	H
3704.28	-25.37	7.00	12.93	-31.30	-13.00	-18.30	V
5557.50	-29.29	8.20	17.11	-38.20	-13.00	-25.20	V
7409.83	-24.64	8.10	22.20	-38.74	-13.00	-25.74	V
The Worst Test Results for Channel 9400/1880MHz							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea	Limit	Margin	Polarity
				(dBm)	(dBm)	(dBm)	
3760.22	-28.59	7.00	12.93	-34.52	-13.00	-21.52	H
5639.82	-27.05	8.20	17.11	-35.96	-13.00	-22.96	H
7520.00	-26.53	8.10	22.20	-40.63	-13.00	-27.63	H
3759.85	-25.78	7.00	12.93	-31.71	-13.00	-18.71	V
5640.21	-27.40	8.20	17.11	-36.31	-13.00	-23.31	V
7519.82	-25.19	8.10	22.20	-39.29	-13.00	-26.29	V
The Worst Test Results for Channel 9538/1907.6MHz							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea	Limit	Margin	Polarity
				(dBm)	(dBm)	(dBm)	
3815.65	-29.18	7.00	12.93	-35.11	-13.00	-22.11	H
5722.22	-27.34	8.20	17.11	-36.25	-13.00	-23.25	H
7630.31	-26.87	8.10	22.20	-40.97	-13.00	-27.97	H
3815.52	-27.19	7.00	12.93	-33.12	-13.00	-20.12	V
5722.48	-29.77	8.20	17.11	-38.68	-13.00	-25.68	V
7630.01	-25.32	8.10	22.20	-39.42	-13.00	-26.42	V

HSDPA Band 2: (30-20000)MHz							
The Worst Test Results for Channel 9262/1852.4MHz							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea	Limit	Margin	Polarity
				(dBm)	(dBm)	(dBm)	
3704.23	-25.35	7.00	12.93	-31.28	-13.00	-18.28	H
5557.23	-26.50	8.20	17.11	-35.41	-13.00	-22.41	H
7409.77	-28.49	8.10	22.20	-42.59	-13.00	-29.59	H
3704.35	-27.06	7.00	12.93	-32.99	-13.00	-19.99	V
5557.43	-29.94	8.20	17.11	-38.85	-13.00	-25.85	V
7409.62	-26.27	8.10	22.20	-40.37	-13.00	-27.37	V
The Worst Test Results for Channel 9400/1880MHz							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea	Limit	Margin	Polarity
				(dBm)	(dBm)	(dBm)	
3759.77	-28.48	7.00	12.93	-34.41	-13.00	-21.41	H
5640.24	-28.96	8.20	17.11	-37.87	-13.00	-24.87	H
7520.26	-26.50	8.10	22.20	-40.60	-13.00	-27.60	H
3760.00	-26.55	7.00	12.93	-32.48	-13.00	-19.48	V
5640.01	-26.48	8.20	17.11	-35.39	-13.00	-22.39	V
7520.23	-26.95	8.10	22.20	-41.05	-13.00	-28.05	V
The Worst Test Results for Channel 9538/1907.6MHz							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea	Limit	Margin	Polarity
				(dBm)	(dBm)	(dBm)	
3815.34	-25.62	7.00	12.93	-31.55	-13.00	-18.55	H
5722.02	-28.02	8.20	17.11	-36.93	-13.00	-23.93	H
7629.91	-24.74	8.10	22.20	-38.84	-13.00	-25.84	H
3815.57	-28.56	7.00	12.93	-34.49	-13.00	-21.49	V
5722.22	-27.10	8.20	17.11	-36.01	-13.00	-23.01	V
7630.24	-24.04	8.10	22.20	-38.14	-13.00	-25.14	V

WCDMA Band 4: (30-18000)MHz							
The Worst Test Results for Channel 1313/1712.6MHz							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea	Limit	Margin	Polarity
				(dBm)	(dBm)	(dBm)	
3424.91	-31.84	7.20	12.05	-36.69	-13.00	-23.69	H
5137.31	-33.45	7.90	16.27	-41.82	-13.00	-28.82	H
6850.06	-31.94	8.30	20.13	-43.77	-13.00	-30.77	H
3425.19	-35.07	7.20	12.05	-39.92	-13.00	-26.92	V
5137.65	-35.17	7.90	16.27	-43.54	-13.00	-30.54	V
6850.03	-28.89	8.30	20.13	-40.72	-13.00	-27.72	V
The Worst Test Results for Channel 1450/1740.0MHz							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea	Limit	Margin	Polarity
				(dBm)	(dBm)	(dBm)	
3479.99	-31.72	7.20	12.05	-36.57	-13.00	-23.57	H
5219.61	-34.01	7.90	16.27	-42.38	-13.00	-29.38	H
6959.55	-31.24	8.30	20.13	-43.07	-13.00	-30.07	H
3479.84	-35.33	7.20	12.05	-40.18	-13.00	-27.18	V
5219.74	-31.91	7.90	16.27	-40.28	-13.00	-27.28	V
6959.62	-32.90	8.30	20.13	-44.73	-13.00	-31.73	V
The Worst Test Results for Channel 1512/1752.4MHz							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea	Limit	Margin	Polarity
				(dBm)	(dBm)	(dBm)	
3504.32	-32.71	7.20	12.05	-37.56	-13.00	-24.56	H
5257.18	-33.23	7.90	16.27	-41.60	-13.00	-28.60	H
7009.59	-33.46	8.30	20.13	-45.29	-13.00	-32.29	H
3504.30	-33.87	7.20	12.05	-38.72	-13.00	-25.72	V
5257.08	-34.90	7.90	16.27	-43.27	-13.00	-30.27	V
7009.39	-30.40	8.30	20.13	-42.23	-13.00	-29.23	V

HSUPA Band 4: (30-18000)MHz							
The Worst Test Results for Channel 1313/1712.6MHz							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea	Limit	Margin	Polarity
				(dBm)	(dBm)	(dBm)	
3424.95	-33.74	7.20	12.05	-38.59	-13.00	-25.59	H
5137.65	-32.15	7.90	16.27	-40.52	-13.00	-27.52	H
6850.05	-31.37	8.30	20.13	-43.20	-13.00	-30.20	H
3425.11	-33.70	7.20	12.05	-38.55	-13.00	-25.55	V
5137.49	-31.26	7.90	16.27	-39.63	-13.00	-26.63	V
6850.14	-29.28	8.30	20.13	-41.11	-13.00	-28.11	V
The Worst Test Results for Channel 1450/1740.0MHz							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea	Limit	Margin	Polarity
				(dBm)	(dBm)	(dBm)	
3479.64	-32.03	7.20	12.05	-36.88	-13.00	-23.88	H
5219.61	-35.32	7.90	16.27	-43.69	-13.00	-30.69	H
6959.68	-28.66	8.30	20.13	-40.49	-13.00	-27.49	H
3479.86	-35.75	7.20	12.05	-40.60	-13.00	-27.60	V
5219.79	-32.41	7.90	16.27	-40.78	-13.00	-27.78	V
6959.86	-30.67	8.30	20.13	-42.50	-13.00	-29.50	V
The Worst Test Results for Channel 1512/1752.4MHz							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea	Limit	Margin	Polarity
				(dBm)	(dBm)	(dBm)	
3504.60	-33.87	7.20	12.05	-38.72	-13.00	-25.72	H
5257.09	-34.21	7.90	16.27	-42.58	-13.00	-29.58	H
7009.40	-33.26	8.30	20.13	-45.09	-13.00	-32.09	H
3504.71	-31.75	7.20	12.05	-36.60	-13.00	-23.60	V
5257.07	-35.22	7.90	16.27	-43.59	-13.00	-30.59	V
7009.46	-30.53	8.30	20.13	-42.36	-13.00	-29.36	V

HSDPA Band 4: (30-18000)MHz							
The Worst Test Results for Channel 1313/1712.6MHz							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea	Limit	Margin	Polarity
				(dBm)	(dBm)	(dBm)	
3424.92	-34.60	7.20	12.05	-39.45	-13.00	-26.45	H
5137.35	-32.95	7.90	16.27	-41.32	-13.00	-28.32	H
6850.21	-33.48	8.30	20.13	-45.31	-13.00	-32.31	H
3424.83	-35.86	7.20	12.05	-40.71	-13.00	-27.71	V
5137.61	-30.65	7.90	16.27	-39.02	-13.00	-26.02	V
6850.15	-30.58	8.30	20.13	-42.41	-13.00	-29.41	V
The Worst Test Results for Channel 1450/1740.0MHz							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea	Limit	Margin	Polarity
				(dBm)	(dBm)	(dBm)	
3479.85	-30.12	7.20	12.05	-34.97	-13.00	-21.97	H
5219.56	-30.52	7.90	16.27	-38.89	-13.00	-25.89	H
6959.67	-30.08	8.30	20.13	-41.91	-13.00	-28.91	H
3479.61	-31.14	7.20	12.05	-35.99	-13.00	-22.99	V
5219.56	-32.48	7.90	16.27	-40.85	-13.00	-27.85	V
6959.57	-32.24	8.30	20.13	-44.07	-13.00	-31.07	V
The Worst Test Results for Channel 1512/1752.4MHz							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea	Limit	Margin	Polarity
				(dBm)	(dBm)	(dBm)	
3504.35	-33.35	7.20	12.05	-38.20	-13.00	-25.20	H
5257.07	-34.16	7.90	16.27	-42.53	-13.00	-29.53	H
7009.11	-31.08	8.30	20.13	-42.91	-13.00	-29.91	H
3504.30	-34.32	7.20	12.05	-39.17	-13.00	-26.17	V
5257.01	-34.32	7.90	16.27	-42.69	-13.00	-29.69	V
7009.49	-31.00	8.30	20.13	-42.83	-13.00	-29.83	V

WCDMA Band 5: (30-9000)MHz							
The worst testresults channel 4132/826.4MHz							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea	Limit	Margin	Polarity
				(dBm)	(dBm)	(dBm)	
1652.31	-32.89	7.40	4.75	-30.24	-13.00	-17.24	H
2479.53	-33.77	8.30	8.39	-33.86	-13.00	-20.86	H
3305.68	-24.08	7.20	11.79	-28.67	-13.00	-15.67	H
1652.30	-37.59	7.40	4.75	-34.94	-13.00	-21.94	V
2479.51	-34.59	8.30	8.39	-34.68	-13.00	-21.68	V
3305.51	-28.99	7.20	11.79	-33.58	-13.00	-20.58	V
The Worst Test Results Channel 4183/836.6MHz							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea	Limit	Margin	Polarity
				(dBm)	(dBm)	(dBm)	
1673.09	-32.93	7.40	4.75	-30.28	-13.00	-17.28	H
2509.84	-33.50	8.30	8.39	-33.59	-13.00	-20.59	H
3346.30	-24.76	7.20	11.79	-29.35	-13.00	-16.35	H
1673.14	-37.38	7.40	4.75	-34.73	-13.00	-21.73	V
2509.80	-33.25	8.30	8.39	-33.34	-13.00	-20.34	V
3345.97	-30.52	7.20	11.79	-35.11	-13.00	-22.11	V
The Worst Test Results Channel 4233/846.6MHz							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea	Limit	Margin	Polarity
				(dBm)	(dBm)	(dBm)	
1693.37	-33.34	7.40	4.75	-30.69	-13.00	-17.69	H
2539.19	-34.00	8.30	8.39	-34.09	-13.00	-21.09	H
3385.92	-25.93	7.20	11.79	-30.52	-13.00	-17.52	H
1693.60	-35.54	7.40	4.75	-32.89	-13.00	-19.89	V
2539.54	-34.15	8.30	8.39	-34.24	-13.00	-21.24	V
3386.26	-33.39	7.20	11.79	-37.98	-13.00	-24.98	V

HSUPA Band 5: (30-9000)MHz							
The worst testresults channel 4132/826.4MHz							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea	Limit	Margin	Polarity
				(dBm)	(dBm)	(dBm)	
1652.20	-33.69	7.40	4.75	-31.04	-13.00	-18.04	H
2479.38	-33.48	8.30	8.39	-33.57	-13.00	-20.57	H
3305.46	-23.72	7.20	11.79	-28.31	-13.00	-15.31	H
1652.28	-33.95	7.40	4.75	-31.30	-13.00	-18.30	V
2479.26	-34.41	8.30	8.39	-34.50	-13.00	-21.50	V
3305.47	-29.99	7.20	11.79	-34.58	-13.00	-21.58	V
The Worst Test Results Channel 4183/836.6MHz							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea	Limit	Margin	Polarity
				(dBm)	(dBm)	(dBm)	
1673.18	-32.95	7.40	4.75	-30.30	-13.00	-17.30	H
2509.48	-30.58	8.30	8.39	-30.67	-13.00	-17.67	H
3346.25	-23.70	7.20	11.79	-28.29	-13.00	-15.29	H
1672.93	-35.91	7.40	4.75	-33.26	-13.00	-20.26	V
2509.69	-32.23	8.30	8.39	-32.32	-13.00	-19.32	V
3346.43	-29.76	7.20	11.79	-34.35	-13.00	-21.35	V
The Worst Test Results Channel 4233/846.6MHz							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea	Limit	Margin	Polarity
				(dBm)	(dBm)	(dBm)	
1693.18	-32.74	7.40	4.75	-30.09	-13.00	-17.09	H
2539.51	-29.93	8.30	8.39	-30.02	-13.00	-17.02	H
3385.98	-27.01	7.20	11.79	-31.60	-13.00	-18.60	H
1693.20	-36.56	7.40	4.75	-33.91	-13.00	-20.91	V
2539.30	-31.67	8.30	8.39	-31.76	-13.00	-18.76	V
3385.84	-33.43	7.20	11.79	-38.02	-13.00	-25.02	V

HSDPA Band 5: (30-9000)MHz							
The worst testresults channel 4132/826.4MHz							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea	Limit	Margin	Polarity
				(dBm)	(dBm)	(dBm)	
1652.02	-36.24	7.40	4.75	-33.59	-13.00	-20.59	H
2479.26	-30.43	8.30	8.39	-30.52	-13.00	-17.52	H
3305.77	-27.20	7.20	11.79	-31.79	-13.00	-18.79	H
1652.05	-33.84	7.40	4.75	-31.19	-13.00	-18.19	V
2479.43	-35.23	8.30	8.39	-35.32	-13.00	-22.32	V
3305.60	-33.87	7.20	11.79	-38.46	-13.00	-25.46	V
The Worst Test Results Channel 4183/836.6MHz							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea	Limit	Margin	Polarity
				(dBm)	(dBm)	(dBm)	
1672.93	-31.74	7.40	4.75	-29.09	-13.00	-16.09	H
2509.78	-30.61	8.30	8.39	-30.70	-13.00	-17.70	H
3346.19	-25.77	7.20	11.79	-30.36	-13.00	-17.36	H
1672.99	-33.97	7.40	4.75	-31.32	-13.00	-18.32	V
2509.48	-33.32	8.30	8.39	-33.41	-13.00	-20.41	V
3346.16	-31.08	7.20	11.79	-35.67	-13.00	-22.67	V
The Worst Test Results Channel 4233/846.6MHz							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea	Limit	Margin	Polarity
				(dBm)	(dBm)	(dBm)	
1693.48	-32.95	7.40	4.75	-30.30	-13.00	-17.30	H
2539.13	-30.40	8.30	8.39	-30.49	-13.00	-17.49	H
3386.30	-23.95	7.20	11.79	-28.54	-13.00	-15.54	H
1693.57	-35.96	7.40	4.75	-33.31	-13.00	-20.31	V
2539.25	-32.58	8.30	8.39	-32.67	-13.00	-19.67	V
3386.00	-29.05	7.20	11.79	-33.64	-13.00	-20.64	V

CDMA

Conducted output power

CDMA BC0							
Mode	Frequency (MHz)	Conduction AVG Power(dBm)	Ant Gain (dBi)	ERP (dBm)	ERP Limit (W)	ERP Limit (dBm)	Conclusion
CDMA BC0	824.70	23.56	-2.10	19.31	7.00	38.45	PASS
	836.52	23.30	-2.10	19.05	7.00	38.45	PASS
	848.31	23.42	-2.10	19.17	7.00	38.45	PASS
EVDO BC0	824.70	23.47	-2.10	19.22	7.00	38.45	PASS
	836.52	23.27	-2.10	19.02	7.00	38.45	PASS
	848.31	23.36	-2.10	19.11	7.00	38.45	PASS

CDMA BC1							
Mode	Frequency (MHz)	Conduction AVG Power(dBm)	Ant Gain (dBi)	EIRP (dBm)	EIRP Limit(W)	EIRP Limit(dBm)	Conclusion
CDMA BC1	1851.25	23.26	-0.20	23.06	2.00	33.01	PASS
	1880.00	23.43	-0.20	23.23	2.00	33.01	PASS
	1908.75	23.47	-0.20	23.27	2.00	33.01	PASS
EVDO BC1	1851.25	23.23	-0.20	23.03	2.00	33.01	PASS
	1880.00	23.39	-0.20	23.19	2.00	33.01	PASS
	1908.75	23.42	-0.20	23.22	2.00	33.01	PASS

Frequency stability

CDMA BC0					
Temperature (°C)	Voltage	Freq. Dev.	Freq. Dev.	Limit	Result
	(Volt)	(Hz)	(ppm)		
50	Normal Voltage	4.42	0.002	2.5ppm	PASS
40		4.81	0.003		
30		4.41	0.002		
20		7.53	0.004		
10		4.66	0.002		
0		-4.51	-0.002		
-10		4.44	0.002		
-20		4.42	0.002		
-30		4.57	0.002		
20	Maximum Voltage	4.31	0.002		
20	BEP	-4.83	-0.003		

EVDO BC0					
Temperature (°C)	Voltage	Freq. Dev.	Freq. Dev.	Limit	Result
	(Volt)	(Hz)	(ppm)		
50	Normal Voltage	-0.34	0.000	2.5ppm	PASS
40		0.38	0.000		
30		0.00	0.000		
20		-1.38	-0.001		
10		0.13	0.000		
0		-0.43	0.000		
-10		-0.28	0.000		
-20		-0.37	0.000		
-30		-0.10	0.000		
20	Maximum Voltage	-0.33	0.000		
20	BEP	0.35	0.000		

CDMA BC1					
Temperature (°C)	Voltage	Freq. Dev.	Freq. Dev.	Limit	Result
	(Volt)	(Hz)	(ppm)		
50	Normal Voltage	1.27	0.001	Within Authorized Band	PASS
40		1.69	0.001		
30		1.72	0.001		
20		-4.56	-0.002		
10		-1.32	-0.001		
0		-1.69	-0.001		
-10		1.24	0.001		
-20		-1.47	-0.001		
-30		1.63	0.001		
20	Maximum Voltage	1.19	0.001		
20	BEP	-1.70	-0.001		


EVDO BC1					
Temperature (°C)	Voltage	Freq. Dev.	Freq. Dev.	Limit	Result
	(Volt)	(Hz)	(ppm)		
50	Normal Voltage	2.38	0.001	Within Authorized Band	PASS
40		-2.30	-0.001		
30		-1.93	-0.001		
20		2.71	0.001		
10		2.48	0.001		
0		2.48	0.001		
-10		-2.10	-0.001		
-20		1.96	0.001		
-30		-2.28	-0.001		
20	Maximum Voltage	-2.18	-0.001		
20	BEP	2.39	0.001		

Peak-to-Average Ratio


CDMA BC0		
Mode	Frequency (MHz)	PAR
CDMA BC0	824.70	6.57
	836.52	6.57
	848.31	6.58
EVDO BC0	824.70	6.57
	836.52	6.65
	848.31	6.57

CDMA BC1		
Mode	Frequency (MHz)	PAR
CDMA BC1	1851.25	6.65
	1880.00	6.72
	1908.75	6.74
EVDO BC1	1851.25	6.71
	1880.00	6.71
	1908.75	6.80


CDMA BC0 824.7MHz




CDMA BC0 836.5MHz




CDMA BC0 848.3MHz




EVDO BC0 824.7MHz




EVDO BC0 836.5MHz




EVDO BC0 824.7MHz




CDMA BC1 1851.25MHz




CDMA BC1 1880MHz




CDMA BC1 1908.75MHz




EVDO BC1 1851.25MHz



EVDO BC1 1880MHz




EVDO BC1 1908.75MHz




Occupied Bandwidth (99% Occupied Bandwidth/26dB Bandwidth)

CDMA Bandwidth [MHz]						
Mode	Lowest		Middle		Highest	
	99% BW	26dB BW	99% BW	26dB BW	99% BW	26dB BW
CDMA BC0	1.2755	1.43	1.2696	1.434	1.2743	1.43
EVDO BC0	1.2765	1.424	1.2734	1.427	1.2761	1.424
CDMA BC1	1.272	1.438	1.2811	1.447	1.2766	1.45
EVDO BC1	1.2766	1.444	1.2738	1.434	1.2858	1.445


BC0_CDMA_Lower




BC0_CDMA_Middle




BC0_CDMA_Higher




BC0_EVDO_Lower




BC0_EVDO_Middle




BC0_EVDO_Higher




BC1_CDMA_Lower




BC1_CDMA_Middle




BC1_CDMA_Higher




BC1_EVDO_Lower



BC1_EVDO_Middle





BC1_EVDO_Higher





Band edge



CDMA_BC0_Low_Band edge





CDMA_BC0_High_Band edge





EVDO_BC0_Low_Band edge





EVDO_BC0_High_Band edge





CDMA_BC1_Low_Band edge




CDMA_BC1_High_Band edge



EVDO_BC1_Low_Band edge




EVDO_BC1_High_Band edge




SPURIOUS EMISSIONS AT ANTENNA TERMINALS


CDMA BC0_Low




CDMA BC0_Middle




CDMA BC0_Higher




CDMA BC1_Low




CDMA BC1_Middle




CDMA BC1_Higher




EVDO BC0_Low




EVDO BC0_Middle




EVDO BC0_Higher




EVDO BC1_Low



EVDO BC1_Middle



EVDO BC1_High



RADIATED SPURIOUS EMISSION

Note:

(1) Spurious emissions which are attenuated by more than 20dB below the permissible value for frequency below 1000MHz.

(2) Test is divided into three directions, X/Y/Z. X pattern for the worst.

CDMA BC0: (30-9000)MHz							
The Worst Test Results for Channel 1013/824.7MHz							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea	Limit	Margin	Polarity
				(dBm)	(dBm)	(dBm)	
1649.54	-30.35	7.40	4.75	-27.70	-13.00	-14.70	H
2474.27	-29.57	8.30	8.39	-29.66	-13.00	-16.66	H
3297.91	-27.94	7.20	11.79	-32.53	-13.00	-19.53	H
1649.54	-30.05	7.40	4.75	-27.40	-13.00	-14.40	V
2474.27	-28.10	8.30	8.39	-28.19	-13.00	-15.19	V
3297.91	-27.92	7.20	11.79	-32.51	-13.00	-19.51	V
The Worst Test Results for Channel 384/836.52MHz							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea	Limit	Margin	Polarity
				(dBm)	(dBm)	(dBm)	
1673.61	-28.50	7.40	4.75	-25.85	-13.00	-12.85	H
2509.75	-28.04	8.30	8.39	-28.13	-13.00	-15.13	H
3346.34	-26.09	7.20	11.79	-30.68	-13.00	-17.68	H
1673.61	-29.26	7.40	4.75	-26.61	-13.00	-13.61	V
2509.75	-32.10	8.30	8.39	-32.19	-13.00	-19.19	V
3346.34	-25.83	7.20	11.79	-30.42	-13.00	-17.42	V
The Worst Test Results for Channel 1175/848.31MHz							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea	Limit	Margin	Polarity
				(dBm)	(dBm)	(dBm)	
1696.39	-29.04	7.40	4.75	-26.39	-13.00	-13.39	H
2544.52	-28.97	8.30	8.39	-29.06	-13.00	-16.06	H
3393.65	-28.17	7.20	11.79	-32.76	-13.00	-19.76	H
1696.39	-30.44	7.40	4.75	-27.79	-13.00	-14.79	V
2544.52	-32.03	8.30	8.39	-32.12	-13.00	-19.12	V
3393.65	-27.85	7.20	11.79	-32.44	-13.00	-19.44	V

EVDO BC0: (30-9000)MHz							
The Worst Test Results for Channel 1013/824.7MHz							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea	Limit	Margin	Polarity
				(dBm)	(dBm)	(dBm)	
1649.39	-30.96	7.40	4.75	-28.31	-13.00	-15.31	H
2474.37	-29.55	8.30	8.39	-29.64	-13.00	-16.64	H
3298.01	-30.46	7.20	11.79	-35.05	-13.00	-22.05	H
1649.39	-30.41	7.40	4.75	-27.76	-13.00	-14.76	V
2474.37	-29.17	8.30	8.39	-29.26	-13.00	-16.26	V
3298.01	-25.84	7.20	11.79	-30.43	-13.00	-17.43	V
The Worst Test Results for Channel 384/836.52MHz							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea	Limit	Margin	Polarity
				(dBm)	(dBm)	(dBm)	
1673.40	-31.14	7.40	4.75	-28.49	-13.00	-15.49	H
2509.55	-28.75	8.30	8.39	-28.84	-13.00	-15.84	H
3346.10	-25.66	7.20	11.79	-30.25	-13.00	-17.25	H
1673.40	-32.37	7.40	4.75	-29.72	-13.00	-16.72	V
2509.55	-32.22	8.30	8.39	-32.31	-13.00	-19.31	V
3346.10	-26.35	7.20	11.79	-30.94	-13.00	-17.94	V
The Worst Test Results for Channel 1175/848.31MHz							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea	Limit	Margin	Polarity
				(dBm)	(dBm)	(dBm)	
1696.33	-31.46	7.40	4.75	-28.81	-13.00	-15.81	H
2544.28	-27.92	8.30	8.39	-28.01	-13.00	-15.01	H
3393.67	-29.90	7.20	11.79	-34.49	-13.00	-21.49	H
1696.33	-29.54	7.40	4.75	-26.89	-13.00	-13.89	V
2544.28	-27.64	8.30	8.39	-27.73	-13.00	-14.73	V
3393.67	-28.07	7.20	11.79	-32.66	-13.00	-19.66	V

CDMA BC1: (30-20000)MHz							
The Worst Test Results for Channel 25/1851.25MHz							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea	Limit	Margin	Polarity
				(dBm)	(dBm)	(dBm)	
3702.50	-30.00	7.00	12.93	-35.93	-13.00	-22.93	H
5553.51	-27.66	8.20	17.11	-36.57	-13.00	-23.57	H
7405.87	-25.72	8.10	22.20	-39.82	-13.00	-26.82	H
3702.50	-32.24	7.00	12.93	-38.17	-13.00	-25.17	V
5553.51	-28.03	8.20	17.11	-36.94	-13.00	-23.94	V
7405.87	-29.73	8.10	22.20	-43.83	-13.00	-30.83	V
The Worst Test Results for Channel 600/1880MHz							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea	Limit	Margin	Polarity
				(dBm)	(dBm)	(dBm)	
3759.87	-29.64	7.00	12.93	-35.57	-13.00	-22.57	H
5639.86	-27.72	8.20	17.11	-36.63	-13.00	-23.63	H
7519.85	-27.33	8.10	22.20	-41.43	-13.00	-28.43	H
3759.87	-30.09	7.00	12.93	-36.02	-13.00	-23.02	V
5639.86	-30.99	8.20	17.11	-39.90	-13.00	-26.90	V
7519.85	-26.18	8.10	22.20	-40.28	-13.00	-27.28	V
The Worst Test Results for Channel 1175/1908.75MHz							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea	Limit	Margin	Polarity
				(dBm)	(dBm)	(dBm)	
3817.40	-30.18	7.00	12.93	-36.11	-13.00	-23.11	H
5725.98	-28.77	8.20	17.11	-37.68	-13.00	-24.68	H
7634.87	-27.19	8.10	22.20	-41.29	-13.00	-28.29	H
3817.40	-31.28	7.00	12.93	-37.21	-13.00	-24.21	V
5725.98	-30.02	8.20	17.11	-38.93	-13.00	-25.93	V
7634.87	-25.99	8.10	22.20	-40.09	-13.00	-27.09	V

EVDO BC1: (30-20000)MHz							
The Worst Test Results for Channel 25/1851.25MHz							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea	Limit	Margin	Polarity
				(dBm)	(dBm)	(dBm)	
3702.28	-28.85	7.00	12.93	-34.78	-13.00	-21.78	H
5553.41	-32.10	8.20	17.11	-41.01	-13.00	-28.01	H
7405.55	-27.40	8.10	22.20	-41.50	-13.00	-28.50	H
3702.28	-29.79	7.00	12.93	-35.72	-13.00	-22.72	V
5553.41	-30.44	8.20	17.11	-39.35	-13.00	-26.35	V
7405.55	-26.10	8.10	22.20	-40.20	-13.00	-27.20	V
The Worst Test Results for Channel 600/1880MHz							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea	Limit	Margin	Polarity
				(dBm)	(dBm)	(dBm)	
3759.87	-31.88	7.00	12.93	-37.81	-13.00	-24.81	H
5639.88	-28.67	8.20	17.11	-37.58	-13.00	-24.58	H
7519.92	-26.00	8.10	22.20	-40.10	-13.00	-27.10	H
3759.87	-32.56	7.00	12.93	-38.49	-13.00	-25.49	V
5639.88	-28.73	8.20	17.11	-37.64	-13.00	-24.64	V
7519.92	-27.92	8.10	22.20	-42.02	-13.00	-29.02	V
The Worst Test Results for Channel 1175/1908.75MHz							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea	Limit	Margin	Polarity
				(dBm)	(dBm)	(dBm)	
3817.36	-31.08	7.00	12.93	-37.01	-13.00	-24.01	H
5725.82	-31.46	8.20	17.11	-40.37	-13.00	-27.37	H
7635.23	-26.11	8.10	22.20	-40.21	-13.00	-27.21	H
3817.36	-30.91	7.00	12.93	-36.84	-13.00	-23.84	V
5725.82	-27.46	8.20	17.11	-36.37	-13.00	-23.37	V
7635.23	-28.24	8.10	22.20	-42.34	-13.00	-29.34	V

APPENDIX II - PHOTOS OF TEST SETUP

Note: See test photos in setup photo document for the actual connections between Product and support equipment.

APPENDIX III - PHOTOGRAPHS OF EUT CONSTRUCTIONAL DETAILS

Note: Please see the attached OB-P10_EUT Photos.

※※※※※END OF THE REPORT※※※※※