

MPE Calculation

Regulation(s): Part 1.1310, Part 2.1091

Method: KDB447498 D01v06

RF feature(Mode)	Frequency range (MHz)			Max Target Power (dBm)	ANT Gain (dBi)	Maximum EIRP (dBm)	Maximum EIRP (mW)	Maximum power density (mW/cm ²)	Requirement (mW/cm ²)
LTE Band 12	699.00	~	716.00	25.00	0.00	25.00	316.228	0.063 0	0.466 0
LTE Band 13	777.00	~	787.00	25.00	0.00	25.00	316.228	0.063 0	0.518 0
LTE Band 26	814.00	~	824.00	25.00	0.00	25.00	316.228	0.063 0	0.542 0
LTE Band 26(5)	824.00	~	849.00	25.00	0.00	25.00	316.228	0.063 0	0.549 0
LTE Band 66(4)	1 710.00	~	1 780.00	25.00	0.00	25.00	316.228	0.063 0	1.000 0
LTE Band 25(2)	1 850.00	~	1 915.00	25.00	0.00	25.00	316.228	0.063 0	1.000 0
		~							
		~							

Note: Please refer to the Tune-up proceduer for Max tune-up power.

The EUT will only be used with a separation of 20 centimeters or greater between the antenna and the body of the user.

The MPE sample calculation for this exposure is shown below.

$$\begin{aligned}
 S &= \text{EIRP} / (4 R^2 \pi) \\
 &= 316.228 / (4 \times 20^2 \times \pi) \\
 &= 0.063 \text{ mW/cm}^2
 \end{aligned}$$

- Note

S= Maximum power density(mW/cm²)

EIRP= Equivalent Isotropic Radiated Power(mW)

R= Distance to the center of the radiation of the antenna(20cm)

Part 1.1310

▪ Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric Field strength (V/m)	Magnetic field strength (A/m)	Power Density (mW/cm ²)	Averaging time (minutes)
0.3 ~ 1.34	614	1.63	*100	30
1.34 ~ 30	824/f	2.19 / f	*180 / f ²	30
30 ~ 300	27.5	0.073	0.2	30
300 ~ 1,500			f / 1500	30
1,500 ~ 100,000			1.0	30

Conclusion : The exposure condition of this device is compliant with FCC