

SPECIFICATION FOR APPROVAL

SUPPLIER: Postek Electronics Co., Ltd

PRODUCT MODEL: FYT-01-5

PRODUCT NAME: 2.4G Antenna

PRODUCT CODE: M01-0601310R0A

PREPARED BY:

PengCheng.Gao

DATE:

2023.08.30

ADDRESS:

Wisdom Plaza, Block B, Tower 2, 18th
Floor,Nanshan District, Shen Zhen

TEL:

0755-83240988

PERFORMANCE PARAMETER

1. Electrical Characteristics

1	Frequency Range	2400-2500MHz
2	V. S. W. R	≤ 3
3	Gain	3.77dBi
4	Efficiency	41.06%
5	Impedence	50 Ω
6	Polarization	Linear
7	Interface type	Ipex

2.Mechanical parameters

1	Measure	FPC:50.85*8.5mm/ Cable: 550.0mm* Φ 1.13mm
2	Colour	Black


3.Environment Condition

1	Working Temp	-30℃~80℃
---	--------------	----------

TESTING CURVE

1. Performance test

1.1 V.S.W.R





Data list

Freq	2.4	2.45	2.5
VSWR	1.35	1.08	1.22

TESTING CURVE

2. Passive testing

2.1 Efficiency and Gain




TESTING CURVE

Efficiency and Gain Data list

Freq(MHz)	Efficiency(%)	Gain (dBi)
2400	37.53	2.73
2410	40.59	3.15
2420	40.21	3.15
2430	39.68	3.26
2440	40.37	3.52
2450	41.06	3.77
2460	39.33	3.72
2470	38.75	3.69
2480	38.15	3.7
2490	37.81	3.66
2500	38.61	3.58


TESTING CURVE

2.2 3D Map




2420MHz

Gain=3.15dBi



2450MHz




Gain=3.77dBi



2480MHz




Gain=3.70dBi

2.3 2D Figure






2420MHz

Gain=3.15dBi



2450MHz

Gain=3.77dBi



2480MHz

Gain=3.70dBi

ANTENNA PHYSICAL DIAGRAM

