

FCC RF Exposure

EUT Description: Dog Training Collar

Model No.: FF08

FCC ID: 2BAWZ-FF08

1. Limits

According to KDB 447498 D04 General RF Exposure Guidance v01 The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances \leq 50 mm are determined by:

$[(\text{max power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR,}$

Where:

$$\text{Result} = P/D \cdot \sqrt{f}$$

F= the RF channel transmit frequency in GHz

P=Maximum turn-up power in mw

D=Min. test separation distance in mm

2. Test Result of RF Exposure Evaluation

433.92MHz:

$$\text{EIRP(dBm)} = 67.49(\text{dBuV/m}) - 95.2 = -27.71(\text{dBm})$$

	Output power (dBm)	Tune Up Power (dBm)	Max Tune Up power dBm/mW	Min test separation distance mm	Result	Limit	SAR Test Exclusion
433.92	-27.71	-27±1(-26)	0.003	5	0.0003	3.0	Pass

Note:

PK Output power= conducted power.

Conducted power see the test report **HK2312045869-E**, antenna gain=1dBi

Per KDB 447498 D04, when the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion. The test exclusion threshold is 0.0003 which is ≤ 3 , SAR testing is not required.

Note: Exclusion Thresholds Results = $[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}]$

$f(\text{GHz})$ is the RF channel transmit frequency in GHz

Distance=5mm