

TEST REPORT

Report No.: **BCTC2506974944-1E**

Applicant: **Shenzhen Xiaodi Network Technology Co.,Ltd.**

Product Name: **Power bank**

Test Model.: **B697**

Tested Date: **2025-06-27 to 2025-07-04**

Issued Date: **2025-07-21**

Shenzhen BCTC Testing Co., Ltd.



FCC ID:2BAX5-45188

Product Name: Power bank

Trademark: N/A

Model/Type Ref.: B697,B739,B743,B758,B759,B708,B832,B729,B735,B738,B750,B728,B784,B695,B803,B805,B806,B807,B808,B809,B810,B819,B820,B821,B822,B823,B824,B850,B851,B852,B860,B861,B862,B865,B866,B697C

Prepared For: Shenzhen Xiaodi Network Technology Co.,Ltd.

Address: RM 305, 3F, BLDG No. 4, Demei Industrial CTR,Fukang Community, Longhua St., Longhua District,Shenzhen,China

Manufacturer: Shenzhen Xiaodi Network Technology Co.,Ltd.

Address: RM 305, 3F, BLDG No. 4, Demei Industrial CTR,Fukang Community, Longhua St., Longhua District,Shenzhen,China

Prepared By: Shenzhen BCTC Testing Co., Ltd.

Address: 1-2/F., Building B, Pengzhou Industrial Park, No.158, Fuyuan 1st Road, Zhancheng, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, China

Sample Received Date: 2025-06-27


Sample tested Date: 2025-06-27 to 2025-07-04

Report No.: BCTC2506974944-1E

Test Standards: FCC Part15.209
ANSI C63.10-2020

Test Results: PASS

Tested by:



Shanshan. Zhang / Project Handler

Approved by:



Zero Zhou/Reviewer

The test report is effective only with both signature and specialized stamp. This result(s) shown in this report refer only to the sample(s) tested. Without written approval of Shenzhen BCTC Testing Co., Ltd, this report can't be reproduced except in full. The tested sample(s) and the sample information are provided by the client.

Table of Content

Test Report Declaration	Page
1. Version	4
2. Test Summary	5
3. Measurement Uncertainty	6
4. Product Information and Test Setup.....	7
4.1 Product Information	7
4.2 Test Setup Configuration.....	7
4.3 Support Equipment	8
4.4 Test Mode	8
5. Test Facility and Test Instrument Used	8
5.1 Test Facility	9
5.2 Test Instrument Used.....	9
6. Conducted Emissions.....	11
6.1 Block Diagram Of Test Setup	11
6.2 Limit	11
6.3 Test Procedure	11
6.4 EUT Operating Conditions.....	12
6.5 Test Result	13
7. Radiated Emissions.....	15
7.1 Block Diagram Of Test Setup	15
7.2 Limit.....	16
7.3 Test Procedure	16
7.4 Test Result.....	17
8. Bandwidth Test.....	23
9. Antenna Requirements.....	26
10. EUT Test Setup Photographs.....	27

1. Version

Report No.	Issue Date	Description	Approved
BCTC2506974944-1E	2025-07-21	Original	Valid

2. Test Summary

The Product has been tested according to the following specifications:

No.	Test Parameter	Clause No	Results
1	Conducted Emission	15.207	PASS
2	Radiated Emission	15.209	PASS
3	20dB Bandwidth	15.215	PASS
4	Antenna Requirement	15.203	PASS



3. Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the Product as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

No.	Item	Uncertainty
1	3m chamber Radiated spurious emission(9kHz-30MHz)	U=3.7dB
2	3m chamber Radiated spurious emission(30MHz-1GHz)	U=4.3dB
3	3m chamber Radiated spurious emission(1GHz-18GHz)	U=4.5dB
4	3m chamber Radiated spurious emission(18GHz-40GHz)	U=3.34dB
5	Conducted Emission(150kHz-30MHz)	U=3.20dB
6	Conducted Adjacent channel power	U=1.38dB
7	Conducted output power uncertainty Above 1G	U=1.576dB
8	Conducted output power uncertainty below 1G	U=1.28dB
9	humidity uncertainty	U=5.3%
10	Temperature uncertainty	U=0.59°C

4. Product Information and Test Setup


4.1 Product Information

Model/Type reference:	B697,B739,B743,B758,B759,B708,B832,B729,B735,B738,B750,B728,B784,B695,B803,B805,B806,B807,B808,B809,B810,B819,B820,B821,B822,B823,B824,B850,B851,B852,B860,B861,B862,B865,B866,B697C
Model differences:	The following models of units we produce are identical in electrical, mechanical and physical structure; The difference is only in the model name, we finally have B697as test model.
Hardware Version:	N/A
Software Version:	N/A
Type of Modulation:	ASK
Operation Frequency:	112-205KHz 300-350KHz
Antenna installation:	Loop coil antenna
Ratings:	Input: Type-c:5V/3A, 9V/2A, 12V/1.5A PD18w Output: Type-C: DC5V=3A 9V=2.22A 10V=2.25A (22.5W Max) USB-A: 5V/2A,10W Cable output: type-c1/c2: DC5V=3A 9V=2.22A 10V=2.25A (SCP) 12V=1.67A (PD20W/22.5W Max) Mobile magnetic output: 15W max Apple watch output: 2.5W max
Battery:	DC 3.85V/10000mAh


4.2 Test Setup Configuration

See test photographs attached in EUT TEST SETUP Photographs for the actual connections between Product and support equipment.

Conducted Emission



Radiated Spurious Emission:



4.3 Support Equipment

No.	Device Type	Brand	Model	Series No.	Note
E-1	Power bank	N/A	B697	N/A	EUT
E-2	Dummy load	N/A	DL01	N/A	Dummy load
E-3	Adapter	N/A	KA3601A-1252880 US	N/A	Auxiliary

Notes:

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

4.4 Test Mode

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configit

Test Mode 1	Wireless :15W
Test Mode 2	Watch:2.5W
Test Mode 3	Charging

5. Test Facility and Test Instrument Used

5.1 Test Facility

All measurement facilities used to collect the measurement data are located at Shenzhen BCTC Testing Co., Ltd. Address: 1-2/F., Building B, Pengzhou Industrial Park, No.158, Fuyuan 1st Road, Zhancheng, Fuhe Subdistrict, Bao'an District, Shenzhen, Guangdong, China. The site and apparatus are constructed in conformance with the requirements of ANSI C63.4 and CISPR 16-1-1 other equivalent standards.

FCC Test Firm Registration Number: 712850

A2LA certificate registration number is: CN1212

ISED Registered No.: 23583

ISED CAB identifier: CN0017

5.2 Test Instrument Used


Conducted Emissions Test					
Equipment	Manufacturer	Model#	Serial#	Last Cal.	Next Cal.
Receiver	R&S	ESR3	102075	May 08 2025	May 07, 2026
LISN	R&S	ENV216	101375	May 14, 2025	May 13, 2026
Software	Frad	EZ-EMC	EMC-CON 3A1	\	\
Pulse limiter	Schwarzbeck	VTSD9561-F	01323	May 14, 2025	May 13, 2026

RF Conducted Test					
Equipment	Manufacturer	Model#	Serial#	Last Cal.	Next Cal.
Power meter	Keysight	E4419	\	May 14, 2025	May 13, 2026
Power Sensor (AV)	Keysight	E9300A	\	May 14, 2025	May 13, 2026
Signal Analyzer20kH z-26.5GHz	Keysight	N9020A	MY49100060	May 14, 2025	May 13, 2026
Spectrum Analyzer9kHz-40GHz	R&S	FSP40	100363	May 14, 2025	May 13, 2026

Radiated Emissions Test (966 Chamber)					
Equipment	Manufacturer	Model#	Serial#	Last Cal.	Next Cal.
966 chamber	ChengYu	966 Room	966	Oct. 31. 2024	Oct. 30. 2027
Receiver	R&S	ESR3	102075	May 08, 2025	May 07, 2026
Receiver	R&S	ESRP	101154	Oct. 31. 2024	Oct. 30. 2025
Amplifier	Schwarzbeck	BBV9744	9744-0037	Oct. 31. 2024	Oct. 30. 2025
TRILOG Broadband Antenna	Schwarzbeck	VULB9163	942	May 24, 2025	May 23, 2026
Loop Antenna(9KHz -30MHz)	Schwarzbeck	FMZB1519B	00014	May 24, 2025	May 23, 2026
Amplifier	SKET	LAPA_01G1 8G-45dB	SK202104090 1	May 14, 2025	May 13, 2026
Horn Antenna	Schwarzbeck	BBHA9120D	1541	May 24, 2025	May 23, 2026
Amplifier(18G Hz-40GHz)	MITEQ	TTA1840-35- HG	2034381	May 14, 2025	May 13, 2026
Horn Antenn(18GH z-40GHz)	Schwarzbeck	BBHA9170	00822	May 24, 2025	May 23, 2026
Spectrum Analyzer9kHz- 40GHz	R&S	FSP40	100363	May 14, 2025	May 13, 2026
Software	Frad	EZ-EMC	FA-03A2 RE	\	\

6. Conducted Emissions

6.1 Block Diagram Of Test Setup



6.2 Limit

FREQUENCY (MHz)	Limit (dBuV)	
	Quas-peak	Average
0.15 -0.5	66 - 56 *	56 - 46 *
0.50 -5.0	56.00	46.00
5.0 -30.0	60.00	50.00

Notes:

1. *Decreasing linearly with logarithm of frequency.
2. The lower limit shall apply at the transition frequencies.

6.3 Test Procedure


Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

- The Product was placed on a nonconductive table 0.8 m above the horizontal ground reference plane, and 0.4 m from the vertical ground reference plane, and connected to the main through Line Impedance Stability Network (L.I.S.N.).
- The RBW of the receiver was set at 9 kHz in 150 kHz ~ 30MHz with Peak and AVG detector in Max Hold mode. Run the receiver's pre-scan to record the maximum disturbance generated from Product in all power lines in the full band.
- For each frequency whose maximum record was higher or close to limit, measure its QP and AVG values and record.

6.4 EUT Operating Conditions


The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

2017



6.5 Test Result

Temperature:	26 °C	Relative Humidity:	54%
Pressure:	101kPa	Phase:	L
Test Voltage :	AC 120V/60Hz	Test Mode:	Mode 3




Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.
3. Measurement=Reading Level+ Correct Factor
4. Over=Measurement-Limit

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.1500	42.00	10.57	52.57	66.00	-13.43	QP
2	0.1500	28.41	10.57	38.98	56.00	-17.02	AVG
3	0.2220	39.23	10.59	49.82	62.74	-12.92	QP
4	0.2220	25.80	10.59	36.39	52.74	-16.35	AVG
5	0.2940	35.96	10.60	46.56	60.41	-13.85	QP
6	0.2940	22.63	10.60	33.23	50.41	-17.18	AVG
7	0.3795	34.00	10.61	44.61	58.29	-13.68	QP
8	0.3795	20.80	10.61	31.41	48.29	-16.88	AVG
9	0.6720	33.30	10.65	43.95	56.00	-12.05	QP
10	0.6720	20.69	10.65	31.34	46.00	-14.66	AVG
11 *	0.8970	36.14	10.61	46.75	56.00	-9.25	QP
12	0.8970	24.16	10.61	34.77	46.00	-11.23	AVG

Temperature:	26 °C	Relative Humidity:	54%
Pressure:	101kPa	Phase:	N
Test Voltage :	AC 120V/60Hz	Test Mode:	Mode 3


Remark:


1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.
3. Measurement=Reading Level+ Correct Factor
4. Over=Measurement-Limit

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.1500	41.86	10.57	52.43	66.00	-13.57	QP
2	0.1500	28.89	10.57	39.46	56.00	-16.54	AVG
3	0.2220	39.28	10.59	49.87	62.74	-12.87	QP
4	0.2220	26.90	10.59	37.49	52.74	-15.25	AVG
5	0.2985	36.14	10.60	46.74	60.28	-13.54	QP
6	0.2985	23.28	10.60	33.88	50.28	-16.40	AVG
7	0.3704	33.35	10.61	43.96	58.49	-14.53	QP
8	0.3704	21.71	10.61	32.32	48.49	-16.17	AVG
9	0.8205	34.65	10.63	45.28	56.00	-10.72	QP
10	0.8205	25.89	10.63	36.52	46.00	-9.48	AVG
11 *	0.8970	37.23	10.61	47.84	56.00	-8.16	QP
12	0.8970	25.68	10.61	36.29	46.00	-9.71	AVG


7. Radiated Emissions

7.1 Block Diagram Of Test Setup

(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



7.2 Limit

FCC §15.209; §15.205.

Frequency	Field Strength	Distance	Field Strength Limit at 3m Distance	
(MHz)	uV/m	(m)	uV/m	dBuV/m
0.009 ~ 0.490	2400/F(kHz)	300	10000 * 2400/F(kHz)	20log ^{(2400/F(kHz))} + 80
0.490 ~ 1.705	24000/F(kHz)	30	100 * 24000/F(kHz)	20log ^{(24000/F(kHz))} + 40
1.705 ~ 30	30	30	100 * 30	20log ⁽³⁰⁾ + 40
30 ~ 88	100	3	100	20log ⁽¹⁰⁰⁾
88 ~ 216	150	3	150	20log ⁽¹⁵⁰⁾
216 ~ 960	200	3	200	20log ⁽²⁰⁰⁾
Above 960	500	3	500	20log ⁽⁵⁰⁰⁾

7.3 Test Procedure

Receiver Parameter	Setting
Attenuation	Auto
9kHz~150kHz	RBW 200Hz for QP
150kHz~30MHz	RBW 9kHz for QP
30MHz~1000MHz	RBW 120kHz for QP


Below 1GHz test procedure as below:

- The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- Different between above is the test site, change from Semi- Anechoic Chamber to fully Anechoic Chamber and change form table 0.8 metre to 1.5 metre(Above 18GHz the distance is 1 meter and table is 1.5 metre).
- Test the EUT in the lowest channel ,the middle channel ,the Highest channel.

7.4 Test Result

Below 30MHz

Temperature:	26°C	Relative Humidity:	54%
Pressure:	101 kpa	Test Voltage :	DC 3.85V
Test Mode :	Mode 1	Polarization:	Coaxial




Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.
2. Measurement=Reading Level+ Correct Factor
3. Over=Measurement-Limit

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	0.0123	76.93	-10.45	66.48	125.61	-59.13	QP
2	0.0216	71.30	-10.33	60.97	120.75	-59.78	QP
3	0.3220	71.04	-10.44	60.60	97.42	-36.82	QP
4 *	0.9625	47.47	-9.77	37.70	67.95	-30.25	QP
5	2.9008	35.99	-9.72	26.27	69.54	-43.27	QP
6	6.7988	39.83	-9.63	30.20	69.54	-39.34	QP

Temperature:	26°C	Relative Humidity:	54%
Pressure:	101 kpa	Test Voltage :	DC3.85V
Test Mode :	Mode 2	Polarization:	Coaxial



Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.
2. Measurement=Reading Level+ Correct Factor
3. Over=Measurement-Limit


No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	0.1442	68.26	-10.07	58.19	104.36	-46.17	QP
2	0.3817	65.97	-10.37	55.60	95.96	-40.36	QP
3	0.7304	46.99	-9.87	37.12	70.34	-33.22	QP
4 *	1.1413	50.17	-9.80	40.37	66.48	-26.11	QP
5	1.9025	41.43	-9.75	31.68	69.54	-37.86	QP
6	2.6748	38.82	-9.73	29.09	69.54	-40.45	QP

Between 30MHz – 1GHz

Temperature:	26°C	Relative Humidity:	54%
Pressure:	101 kPa	Test Voltage:	DC 3.85V
Test Mode:	Mode 1	Polarization:	Horizontal




Temperature:	26°C	Relative Humidity:	54%
Pressure:	101 kpa	Test Voltage :	DC 3.85V
Test Mode:	Mode 1	Polarization:	Vertical


Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.
2. Measurement=Reading Level+ Correct Factor
3. Over=Measurement-Limit

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	56.3948	38.21	-17.06	21.15	40.00	-18.85	QP
2	123.2655	37.02	-19.25	17.77	43.50	-25.73	QP
3	143.8295	35.46	-18.25	17.21	43.50	-26.29	QP
4	185.7882	42.02	-18.44	23.58	43.50	-19.92	QP
5	209.3129	43.23	-18.51	24.72	43.50	-18.78	QP
6 *	336.0352	45.12	-15.57	29.55	46.00	-16.45	QP


Temperature:	26°C	Relative Humidity:	54%
Pressure:	101 kPa	Test Voltage:	DC3.85V
Test Mode:	Mode 2	Polarization:	Horizontal


Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.
2. Measurement=Reading Level+ Correct Factor
3. Over=Measurement-Limit

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	199.9856	38.99	-18.64	20.35	43.50	-23.15	QP
2	281.0075	47.91	-16.96	30.95	46.00	-15.05	QP
3 *	339.5888	55.10	-15.49	39.61	46.00	-6.39	QP
4	605.6592	32.60	-9.12	23.48	46.00	-22.52	QP
5	878.3214	28.67	-4.58	24.09	46.00	-21.91	QP
6	955.4381	26.70	-2.24	24.46	46.00	-21.54	QP

Temperature:	26°C	Relative Humidity:	54%
Pressure:	101 kpa	Test Voltage :	DC3.85V
Test Mode:	Mode 2	Polarization:	Vertical


Remark:



1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.
2. Measurement=Reading Level+ Correct Factor
3. Over=Measurement-Limit

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	57.9993	33.46	-17.13	16.33	40.00	-23.67	QP
2	216.7828	38.10	-18.41	19.69	46.00	-26.31	QP
3	236.6447	42.58	-18.13	24.45	46.00	-21.55	QP
4 *	340.7817	40.80	-15.46	25.34	46.00	-20.66	QP
5	520.8882	29.82	-10.37	19.45	46.00	-26.55	QP
6	670.4893	28.27	-8.41	19.86	46.00	-26.14	QP

8. Bandwidth Test


1. Set RBW = 1%~5% OBW.
2. Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 20 dB relative to the maximum level measured in the fundamental emission.

TEST SETUP




Temperature:	26 °C	Relative Humidity:	54%
Pressure:	101kPa		

Frequency (KHz)	20dB bandwidth (KHz)	Result
174.2	2.703	Pass



Frequency (KHz)	20dB bandwidth (KHz)	Result
326.1	2.771	Pass




9. Antenna Requirements

For intentional device, according to FCC 47 CFR Section 15.203, An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.


The antenna used for this product is Inductive loop coil antenna.


10. EUT Test Setup Photographs

Conducted emissions



Radiated Measurement Photos







STATEMENT

- 1.The equipment lists are traceable to the national reference standards.
- 2.The test report can not be partially copied unless prior written approval is issued from our lab.
- 3.The test report is invalid without stamp of laboratory.
- 4.The test report is invalid without signature of person(s) testing and authorizing.
- 5.The test process and test result is only related to the Unit Under Test.
- 6.The quality system of our laboratory is in accordance with ISO/IEC17025.
- 7.If there is any objection to report, the client should inform issuing laboratory within 15 days from the date of receiving test report.

Address:

1-2/F., Building B, Pengzhou Industrial Park, No.158, Fuyuan 1st Road, Zhancheng, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, China

TEL:400-788-9558

P.C.: 518103

FAX:0755-33229357

Website:<http://www.chnbctc.com>

Consultation E-mail: bctc@bctc-lab.com.cn

Complaint/Advice E-mail: advice@bctc-lab.com.cn

***** END *****

CO.,LTD