

Label Location On EUT



DEENO GT

DEENO GT S1500

Model: PS151032S

Battery capacity: 1036.8Wh (36Ah/28.8V)

Battery type: LiFePO4

Total output power: 1500W

AC charging: 750W max

AC input voltage: 100-120V~ 50Hz/60Hz, 15A

Solar charging: 12V - 32V == 8A, 200W max

Car charging: 12V/24V == 8A, 192W max

AC output x3: 1500W (peak 3000W), 120V~ 50Hz/60Hz

USB-A x3: 5V == 3A, 9V == 2A, 12V == 1.5A

(54W max for the simultaneous output of 3 ports)

USB-C x2: 5V, 9V, 12V, 15V == 3A, 20V == 5A

(200W max for the simultaneous output of 2 ports)

Car charging output x1: 12V == 10A (120W max)

DC5.5*2.1 x1: 12V == 5A (60W max)

DC5.5*2.5 x1: 24V == 5A (120W max)

Wireless charging x1: 5V == 3A, 9V == 1.67A (15W max)

LED lighting power: 12W (four modes: 25% brightness, 50% brightness, 100% brightness, and SOS)

Discharging ambient temperature: -20°C - 45°C (-4°F - 113°F)

Charging ambient temperature: 0°C - 45°C (32°F - 113°F)

⚠ CAUTION

1. This product is forbidden to be placed near heat sources, such as fire or heating oven.
2. This product is forbidden to touch any liquids. Do not use this product in the rain or in a humid environment.
3. Do not disassemble or pierce this product in any way.
4. Do not short-circuit this product with wires or other metal objects.
5. Do not stack any heavy objects on this product.
6. Do not forcibly block the fan during use, or place this product in an unventilated and dusty place.



RoHS



UN38.3 210-210182 FCC-ID:2BAX6-PS151032S

REACH



Shenzhen Dineng
Technology Co., Ltd.

Made in china