

## MPE ESTIMATION

FCC ID: **2BB2P-D1**

1, In accordance with KDB447498D01V06 for Simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneous transmitting antennas incorporated in a host device, based on the calculated/estimated, numerically modeled or measured field strengths or power density, is  $\leq 1.0$ .

Frequency	Power density (mW/ cm <sup>2</sup> )	Averaging time(minutes)
300MHz----1.5GHz	F/1500	30
1.5GHz---100GHz	1.0	30

## 2, Estimation Result

For WIFI:

Mode	Max PK Output power(dBm)	Tune Up Power(dBm)	Max Tune Up power(mW)	Antenna Gain(dBi)	Antenna Gain (linear)	MPE (mW/cm <sup>2</sup> )
2.4G WIFI	18.58	18±1(19)	79.43	5	3.16	0.05000
$Pd = \frac{P_{out} * G}{4\pi r^2}$ ;						
Note:						
Note: The estimation distance is 20cm						
Note: PK Output power= conducted power.						
Conducted power see the test report <b>HK2306082388-E</b> , antenna gain=5dBi						

Per KDB 447498 D01 V06, when the minimum test separation distance is  $>20$  cm, a distance of 20 cm is applied to determine RF Exposure test exclusion. The test exclusion threshold is 0.05000mW/cm<sup>2</sup> which is  $< 1.0$ mW/cm<sup>2</sup>, RF Exposure testing is not required.

-----The End-----