

FCC TEST REPORT

FCC ID:2BB3J-TG-356

Report Number..... : BTF230725R01701

Date of Test..... July 12 to July 20, 2023

Date of issue : July 20, 2023

Total number of pages 42

Test Result : PASS

Testing Laboratory..... : Shenzhen ZKT Technology Co., Ltd.

Address : 1/F, No. 101, Building B, No. 6, Tangwei Community Industrial Avenue, Fuhai Street, Bao'an District, Shenzhen, China

Applicant's name : **Shenzhen Xiting Investment Consulting Co., Ltd.**

Address : 602, Building 5, Shenzhen Software Park, No. 2, Gaoxin Middle Second Road, Maling Community, Yuehai Street, Nanshan District, Shenzhen

Manufacturer's name : **Shenzhen Xiting Investment Consulting Co., Ltd.**

Address : 602, Building 5, Shenzhen Software Park, No. 2, Gaoxin Middle Second Road, Maling Community, Yuehai Street, Nanshan District, Shenzhen

Test specification:

Standard..... : FCC CFR Title 47 Part 15 Subpart C Section 15.249
ANSI C63.10:2013

Test procedure..... : /

Non-standard test method : N/A

Test Report Form No. : TRF-EL-111_V0

Test Report Form(s) Originator : BTF Testing

Master TRF : Dated: 2023-01-05

Note: All the test results in this report only related to the testing samples. Which can be duplicated completely for the legal use with approval of applicant; it shall not be reproduced except in full without the written approval of BTF Testing Lab (Shenzhen) Co., Ltd., All the objections should be raised within thirty days from the date of issue. To validate the report, you can contact us.

Product name..... : Portable Speaker with Bluetooth Wireless Technology

Trademark : MAGNAVOX, Craig, NEWTECH

Model/Type reference : TG-356,TG-357,TG-359,TG-363,TG-366,TG-506,TG-607,TG-619,
TG-623,TG-369,TG-167,TG-177,TG-193,TG-285,TG-375,TG-394,
TG-638,TG-639,TG-643,TG-647,TG-648,TG-809,TG-810,TG-812

Battery..... DC3.7V 800mAh

Ratings..... : AC100-240V,50/60Hz

Table of Contents	Page
1.VERSION	4
2.1SUMMARY OF TEST RESULTS	5
2.1.1 TEST FACILITY	6
2.1.2 MEASUREMENT UNCERTAINTY	6
3. GENERAL INFORMATION	7
3.1 GENERAL DESCRIPTION OF EUT	7
3.2 DESCRIPTION OF TEST MODES	8
3.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	9
3.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)	10
3.5 EQUIPMENTS LIST FOR ALL TEST ITEMS	11
4. EMC EMISSION TEST	15
4.1 CONDUCTED EMISSION MEASUREMENT	15
4.1.1 POWER LINE CONDUCTED EMISSION LIMITS	15
4.1.2 TEST PROCEDURE	15
4.1.3 DEVIATION FROM TEST STANDARD	15
4.1.4 1.3TEST SETUP	16
4.1.5 EUT OPERATING CONDITIONS	16
4.1.6 TEST RESULTS	17
4.2 RADIATED EMISSION MEASUREMENT	19
4.2.1 RADIATED EMISSION LIMITS	19
4.2.2 TEST PROCEDURE	20
4.2.3 1.4DEVIATION FROM TEST STANDARD	20
4.2.4 TEST SETUP	21
4.2.5 EUT OPERATING CONDITIONS	22
5. BANDWIDTH OF FREQUENCY BAND EDGE	33
5.1 TEST REQUIREMENT:	33
5.2 TEST PROCEDURE	33
5.3 DEVIATION FROM TEST STANDARD	33
5.4 TEST SETUP	33
5.5 EUT OPERATING CONDITIONS	34

Table of Contents	Page
5.6 TEST RESULT	35
6. CHANNEL BANDWIDTH	37
6.1 APPLIED PROCEDURES / LIMIT	37
6.2 TEST PROCEDURE	37
6.3 DEVIATION FROM STANDARD	37
6.4 TEST SETUP	37
6.5 EUT OPERATION CONDITIONS	37
6.6 TSET RESULTS	38
8.ANTENNA REQUIREMENT	41
9. TEST SETUP PHOTO	42
10. EUT CONSTRUCTIONAL DETAILS	42



Test Report Number: BTF230725R01701

1.VERSION

Report No.	Version	Description	Approved
BTF230725R01701	Rev.01	Initial issue of report	July 20, 2023

2.1 SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

FCC Part15 (15.249) , Subpart C			
Standard Section	Test Item	Judgment	Remark
FCC part 15.203	Antenna requirement	PASS	
FCC part 15.207	AC Power Line Conducted Emission	PASS	
FCC part 15.249	Fundamental & Radiated Spurious Emission Measurement	PASS	
FCC part 15.215 (c)	20dB Channel Bandwidth	PASS	
FCC part 15.205	Band Edge	PASS	

NOTE:

(1) "N/A" denotes test is not applicable in this Test Report

2.1.1 TEST FACILITY

BTF Testing Lab (Shenzhen) Co., Ltd.

Add. : F101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street, Bao'an District, Shenzhen, China

FCC Test Firm Registration Number: 518915

Designation Number: CN1330

2.1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95%.

No.	Item	Uncertainty
1	Conducted Emission Test	$\pm 1.38\text{dB}$
2	RF power conducted	$\pm 0.16\text{dB}$
3	Spurious emissions conducted	$\pm 0.21\text{dB}$
4	All emissions radiated(<1G)	$\pm 4.68\text{dB}$
5	All emissions radiated(>1G)	$\pm 4.89\text{dB}$
6	Temperature	$\pm 0.5^{\circ}\text{C}$
7	Humidity	$\pm 2\%$

3. GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

Product Name:	Portable Speaker with Bluetooth Wireless Technology
Model No.:	TG-356,TG-357,TG-359,TG-363,TG-366,TG-506,TG-607,TG-619, TG-623,TG-369,TG-167,TG-177,TG-193,TG-285,TG-375,TG-394, TG-638,TG-639,TG-643,TG-647,TG-648,TG-809,TG-810,TG-812
Model Different.:	Only for different colour and model name.
Serial No.:	N/A
Hardware Version:	HV1.0
Software Version:	SV1.0
Sample(s) Status:	Engineer sample
Operation Frequency:	2402MHz~2480MHz
Channel Numbers:	79
Channel Separation:	1MHz
Modulation Type:	GFSK, $\pi/4$ -DQPSK, 8-DPSK
Antenna Type:	PCB Antenna
Antenna gain:	0dBi
Power supply:	DC3.7V 800mAh
SWITCHING POWER ADAPTER:	N/A

Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2402MHz	21	2422MHz	41	2442MHz	61	2462MHz
2	2403MHz	22	2423MHz	42	2443MHz	62	2463MHz
3	2404MHz	23	2424MHz	43	2444MHz	63	2464MHz
4	2405MHz	24	2425MHz	44	2445MHz	64	2465MHz
5	2406MHz	25	2426MHz	45	2446MHz	65	2466MHz
6	2407MHz	26	2427MHz	46	2447MHz	66	2467MHz
7	2408MHz	27	2428MHz	47	2448MHz	67	2468MHz
8	2409MHz	28	2429MHz	48	2449MHz	68	2469MHz
9	2410MHz	29	2430MHz	49	2450MHz	69	2470MHz
10	2411MHz	30	2431MHz	50	2451MHz	70	2471MHz
11	2412MHz	31	2432MHz	51	2452MHz	71	2472MHz
12	2413MHz	32	2433MHz	52	2453MHz	72	2473MHz
13	2414MHz	33	2434MHz	53	2454MHz	73	2474MHz
14	2415MHz	34	2435MHz	54	2455MHz	74	2475MHz
15	2416MHz	35	2436MHz	55	2456MHz	75	2476MHz
16	2417MHz	36	2437MHz	56	2457MHz	76	2477MHz
17	2418MHz	37	2438MHz	57	2458MHz	77	2478MHz
18	2419MHz	38	2439MHz	58	2459MHz	78	2479MHz
19	2420MHz	39	2440MHz	59	2460MHz	79	2480MHz
20	2421MHz	40	2441MHz	60	2461MHz		

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Channel	Frequency
The lowest channel	2402MHz
The middle channel	2441MHz
The Highest channel	2480MHz

3.2 DESCRIPTION OF TEST MODES

Transmitting mode	Keep the EUT in continuously transmitting mode
Remark: During the test, the test voltage was tuned from 85% to 115% of the nominal rated supply	

voltage, and found that the worst case was under the nominal rated supply condition. So the report just shows that condition's data.

Enter test mode for the product, keep EUT in continuously transmitting status with hopping on mode with different packages; find the worst case is GFSK mode.

Test Software	BT Test Tool
Power level setup	<0dBm

3.3 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

Conducted Emission



Radiated Emission



Conducted Spurious



3.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
E-1	Portable Speaker with Bluetooth Wireless Technology	MAGNAVOX, Craig, NEWTECH	TG-356	N/A	EUT
E-2	Adapter	N/A	AC Adapter		Supply by Lab

Item	Shielded Type	Ferrite Core	Length	Note
C-1	NO	NO	0.8M	DC Line

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.

3.5 EQUIPMENTS LIST FOR ALL TEST ITEMS

Conducted Emission at AC power line					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Pulse Limiter	SCHWARZBECK	VTSD 9561-F	00953	2022-11-24	2023-11-23
Coaxial Switcher	SCHWARZBECK	CX210	CX210	2022-11-24	2023-11-23
V-LISN	SCHWARZBECK	NSLK 8127	01073	2022-11-24	2023-11-23
LISN	AFJ	LS16/110VAC	16010020076	2023-02-23	2024-02-22
EMI Receiver	ROHDE&SCHWARZ	ESCI3	101422	2022-11-24	2023-11-23

Occupied Bandwidth					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
RFTest software	/	V1.00	/	/	/
RF Control Unit	Techy	TR1029-1	/	2022-11-24	2023-11-23
RF Sensor Unit	Techy	TR1029-2	/	2022-11-24	2023-11-23
Programmable constant temperature and humidity box	ZZCKONG	ZZ-K02A	20210928007	2022-11-24	2023-11-23
Adjustable Direct Current Regulated Power Supply	Dongguan Tongmen Electronic Technology Co., LTD	etm-6050c	20211026123	2022-11-24	2023-11-23
WIDEBAND RADIO COMMUNICATION TESTER	Rohde & Schwarz	CMW500	161997	2022-11-24	2023-11-23
MXA Signal Analyzer	KEYSIGHT	N9020A	MY50410020	2022-11-24	2023-11-23

Maximum Conducted Output Power					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
RFTest software	/	V1.00	/	/	/
RF Control Unit	Techy	TR1029-1	/	2022-11-24	2023-11-23
RF Sensor Unit	Techy	TR1029-2	/	2022-11-24	2023-11-23
Programmable constant temperature and humidity box	ZZCKONG	ZZ-K02A	20210928007	2022-11-24	2023-11-23
Adjustable Direct Current Regulated Power Supply	Dongguan Tongmen Electronic Technology Co., LTD	etm-6050c	20211026123	2022-11-24	2023-11-23
WIDEBAND RADIO COMMUNICATION TESTER	Rohde & Schwarz	CMW500	161997	2022-11-24	2023-11-23
MXA Signal Analyzer	KEYSIGHT	N9020A	MY50410020	2022-11-24	2023-11-23

Power Spectral Density					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
RFTest software	/	V1.00	/	/	/
RF Control Unit	Techy	TR1029-1	/	2022-11-24	2023-11-23
RF Sensor Unit	Techy	TR1029-2	/	2022-11-24	2023-11-23

Programmable constant temperature and humidity box	ZZCKONG	ZZ-K02A	20210928007	2022-11-24	2023-11-23
Adjustable Direct Current Regulated Power Supply	Dongguan Tongmen Electronic Technology Co., LTD	etm-6050c	20211026123	2022-11-24	2023-11-23
WIDEBAND RADIO COMMUNICATION TESTER	Rohde & Schwarz	CMW500	161997	2022-11-24	2023-11-23
MXA Signal Analyzer	KEYSIGHT	N9020A	MY50410020	2022-11-24	2023-11-23

Emissions in non-restricted frequency bands					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
RFTest software	/	V1.00	/	/	/
RF Control Unit	Techy	TR1029-1	/	2022-11-24	2023-11-23
RF Sensor Unit	Techy	TR1029-2	/	2022-11-24	2023-11-23
Programmable constant temperature and humidity box	ZZCKONG	ZZ-K02A	20210928007	2022-11-24	2023-11-23
Adjustable Direct Current Regulated Power Supply	Dongguan Tongmen Electronic Technology Co., LTD	etm-6050c	20211026123	2022-11-24	2023-11-23
WIDEBAND RADIO COMMUNICATION TESTER	Rohde & Schwarz	CMW500	161997	2022-11-24	2023-11-23
MXA Signal Analyzer	KEYSIGHT	N9020A	MY50410020	2022-11-24	2023-11-23

Band edge emissions (Radiated)					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Coaxial cable Multiflex 141	Schwarzbeck	N/SMA 0.5m	517386	2023-03-24	2024-03-23
Preamplifier	SCHWARZBECK	BBV9744	00246	2022-11-24	2023-11-23
RE Cable	REBES Talent	UF1-SMASMAM-10m	21101566	2022-11-24	2023-11-23
RE Cable	REBES Talent	UF2-NMNM-10m	21101570	2022-11-24	2023-11-23
RE Cable	REBES Talent	UF1-SMASMAM-1m	21101568	2022-11-24	2023-11-23
RE Cable	REBES Talent	UF2-NMNM-1m	21101576	2022-11-24	2023-11-23
RE Cable	REBES Talent	UF2-NMNM-2.5m	21101573	2022-11-24	2023-11-23
POSITIONAL CONTROLLER	SKET	PCI-GPIB	/	/	/
Horn Antenna	SCHWARZBECK	BBHA9170	01157	2021-11-28	2023-11-27
EMI TEST RECEIVER	ROHDE&SCHWARZ	ESC17	101032	2022-11-24	2023-11-23
SIGNAL ANALYZER	ROHDE&SCHWARZ	FSQ40	100010	2022-11-24	2023-11-23
POSITIONAL CONTROLLER	SKET	PCI-GPIB	/	/	/

Broadband Preamplifier	SCHWARZBECK	BBV9718D	00008	2023-03-24	2024-03-23
Horn Antenna	SCHWARZBECK	BBHA9120D	2597	2022-05-22	2024-05-21
EZ EMC	Frad	FA-03A2 RE+	/	/	/
POSITIONAL CONTROLLER	SKET	PCI-GPIB	/	/	/
Log periodic antenna	SCHWARZBECK	VULB 9168	01328	2021-11-28	2023-11-27

Emissions in restricted frequency bands (below 1GHz)					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Coaxial cable Multiflex 141	Schwarzbeck	N/SMA 0.5m	517386	2023-03-24	2024-03-23
Preamplifier	SCHWARZBECK	BBV9744	00246	2022-11-24	2023-11-23
RE Cable	REBES Talent	UF1-SMASMAM-1 0m	21101566	2022-11-24	2023-11-23
RE Cable	REBES Talent	UF2-NMNM-10m	21101570	2022-11-24	2023-11-23
RE Cable	REBES Talent	UF1-SMASMAM-1 m	21101568	2022-11-24	2023-11-23
RE Cable	REBES Talent	UF2-NMNM-1m	21101576	2022-11-24	2023-11-23
RE Cable	REBES Talent	UF2-NMNM-2.5m	21101573	2022-11-24	2023-11-23
POSITIONAL CONTROLLER	SKET	PCI-GPIB	/	/	/
Horn Antenna	SCHWARZBECK	BBHA9170	01157	2021-11-28	2023-11-27
EMI TEST RECEIVER	ROHDE&SCHWARZ	ESC17	101032	2022-11-24	2023-11-23
SIGNAL ANALYZER	ROHDE&SCHWARZ	FSQ40	100010	2022-11-24	2023-11-23
POSITIONAL CONTROLLER	SKET	PCI-GPIB	/	/	/
Broadband Preamplifier	SCHWARZBECK	BBV9718D	00008	2023-03-24	2024-03-23
Horn Antenna	SCHWARZBECK	BBHA9120D	2597	2022-05-22	2024-05-21
EZ EMC	Frad	FA-03A2 RE+	/	/	/
POSITIONAL CONTROLLER	SKET	PCI-GPIB	/	/	/
Log periodic antenna	SCHWARZBECK	VULB 9168	01328	2021-11-28	2023-11-27

Emissions in restricted frequency bands (above 1GHz)					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Coaxial cable Multiflex 141	Schwarzbeck	N/SMA 0.5m	517386	2023-03-24	2024-03-23
Preamplifier	SCHWARZBECK	BBV9744	00246	2022-11-24	2023-11-23
RE Cable	REBES Talent	UF1-SMASMAM-1 0m	21101566	2022-11-24	2023-11-23
RE Cable	REBES Talent	UF2-NMNM-10m	21101570	2022-11-24	2023-11-23
RE Cable	REBES Talent	UF1-SMASMAM-1 m	21101568	2022-11-24	2023-11-23
RE Cable	REBES Talent	UF2-NMNM-1m	21101576	2022-11-24	2023-11-23
RE Cable	REBES Talent	UF2-NMNM-2.5m	21101573	2022-11-24	2023-11-23
POSITIONAL CONTROLLER	SKET	PCI-GPIB	/	/	/
Horn Antenna	SCHWARZBECK	BBHA9170	01157	2021-11-28	2023-11-27

EMI TEST RECEIVER	ROHDE&SCHWARZ	ESCI7	101032	2022-11-24	2023-11-23
SIGNAL ANALYZER	ROHDE&SCHWARZ	FSQ40	100010	2022-11-24	2023-11-23
POSITIONAL CONTROLLER	SKET	PCI-GPIB	/	/	/
Broadband Preamplifier	SCHWARZBECK	BBV9718D	00008	2023-03-24	2024-03-23
Horn Antenna	SCHWARZBECK	BBHA9120D	2597	2022-05-22	2024-05-21
EZ EMC	Frad	FA-03A2 RE+	/	/	/
POSITIONAL CONTROLLER	SKET	PCI-GPIB	/	/	/
Log periodic antenna	SCHWARZBECK	VULB 9168	01328	2021-11-28	2023-11-27

4. EMC EMISSION TEST

4.1 CONDUCTED EMISSION MEASUREMENT

Test Requirement:	FCC Part15 C Section 15.207
Test Method:	ANSI C63.10:2013
Test Frequency Range:	150KHz to 30MHz
Receiver setup:	RBW=9KHz, VBW=30KHz, Sweep time=auto

4.1.1 POWER LINE CONDUCTED EMISSION Limits

FREQUENCY (MHz)	Limit (dBuV)		Standard
	Quas -peak	Average	
0.15 -0.5	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	56.00	46.00	FCC
5.0 -30.0	60.00	50.00	FCC

Note:

(1) *Decreases with the logarithm of the frequency.


4.1.2 TEST PROCEDURE

- The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- LISN at least 80 cm from nearest part of EUT chassis.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

4.1.3 DEVIATION FROM TEST STANDARD

No deviation

4.1.4 TEST SETUP



- Note: 1.Support units were connected to second LISN.**
2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes


4.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

We pretest AC 120V and AC 230V, the worst voltage was AC 120V and the data recording in the report.

4.1.6 TEST RESULTS

Temperature :	26°C	Relative Humidity:	54%
Pressure :	101kPa	Phase :	L
Test Voltage :	AC 120V/60Hz		




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F
1	0.1905	37.38	11.32	48.70	64.01	-15.31	QP	P
2	0.1905	25.51	11.32	36.83	54.01	-17.18	AVG	P
3	0.2535	29.31	11.36	40.67	61.64	-20.97	QP	P
4	0.2535	18.36	11.36	29.72	51.64	-21.92	AVG	P
5	0.4425	29.23	11.31	40.54	57.01	-16.47	QP	P
6	0.4425	17.66	11.31	28.97	47.01	-18.04	AVG	P
7	0.5010	29.51	11.30	40.81	56.00	-15.19	QP	P
8	0.5144	17.47	11.30	28.77	46.00	-17.23	AVG	P
9	0.7529	14.23	11.31	25.54	46.00	-20.46	AVG	P
10	0.7709	25.63	11.31	36.94	56.00	-19.06	QP	P
11	3.1739	27.33	11.43	38.76	56.00	-17.24	QP	P
12	3.2909	11.49	11.42	22.91	46.00	-23.09	AVG	P

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Measurement Level = Reading level + Correct Factor

Temperature :	26℃	Relative Humidity:	54%
Pressure :	101kPa	Phase :	N
Test Voltage :	AC 120V/60Hz		



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F
1	0.1500	32.75	11.14	43.89	66.00	-22.11	QP	P
2	0.1544	6.06	11.15	17.21	55.76	-38.55	AVG	P
3	0.1949	37.14	11.26	48.40	63.83	-15.43	QP	P
4	0.1949	25.64	11.26	36.90	53.83	-16.93	AVG	P
5	0.2535	30.10	11.28	41.38	61.64	-20.26	QP	P
6	0.2535	18.69	11.28	29.97	51.64	-21.67	AVG	P
7	0.5190	17.62	11.30	28.92	46.00	-17.08	AVG	P
8	0.5279	30.68	11.29	41.97	56.00	-14.03	QP	P
9	0.7709	28.97	11.26	40.23	56.00	-15.77	QP	P
10	0.7933	15.35	11.25	26.60	46.00	-19.40	AVG	P
11	3.6150	29.32	11.43	40.75	56.00	-15.25	QP	P
12	3.6150	17.75	11.43	29.18	46.00	-16.82	AVG	P

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Measurement Level = Reading level + Correct Factor

4.2 RADIATED EMISSION MEASUREMENT

Test Requirement:	FCC Part15 C Section 15.209				
Test Method:	ANSI C63.10:2013				
Test Frequency Range:	9kHz to 25GHz				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Value
	9KHz-150KHz	Quasi-peak	200Hz	600Hz	Quasi-peak
	150KHz-30MHz	Quasi-peak	9KHz	30KHz	Quasi-peak
	30MHz-1GHz	Quasi-peak	100KHz	300KHz	Quasi-peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
		Peak	1MHz	10Hz	Average

4.2.1 RADIATED EMISSION LIMITS

Frequencies (MHz)	Field Strength (micровolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

The field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:

Fundamental frequency	Field strength of fundamental (millivolts/meter)	Field strength of harmonics (microvolts/meter)
902-928 MHz	50	500
2400-2483.5 MHz	50	500
5725-5875 MHz	50	500
24.0-24.25 GHz	250	2500

LIMITS OF RADIATED EMISSION MEASUREMENT

FREQUENCY (MHz)	Limit (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

4.2.2 TEST PROCEDURE

- a. The measuring distance of at 3 m shall be used for measurements at frequency up to 25GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- b. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-chamber test. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The height of the equipment or of the substitution antenna shall be 0.8m; above 1GHz, the height was 1.5m, the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- e. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- f. For the actual test configuration, please refer to the related Item –EUT Test Photos.
- g. For the radiated emission test above 1GHz:
Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response.
The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.

Note:


Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

4.2.3 DEVIATION FROM TEST STANDARD


No deviation

4.2.4 TEST SETUP


(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



(C) Radiated Emission Test-Up Frequency Above 1GHz



4.2.5 EUT OPERATING CONDITIONS


The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

4.2.6 TEST RESULTS (Between 9KHz – 30 MHz)

The emission from 9 kHz to 30MHz was pre-tested and found the result was 20dB lower than the limit, and according to 15.31(o) & RSS-Gen 6.13, the test result no need to reported.


Between 30MHz – 1GHz

Temperature:	26°C	Relative Humidity:	54%
Pressure:	101 kPa	Polarization:	Horizontal
Test Voltage:	AC 120V/60Hz		



No.	Frequency (MHz)	Reading (dBUV)	Factor (dB/m)	Level (dBUV/m)	Limit (dBUV/m)	Margin (dB)	Detector
1	97.9700	46.55	-21.27	25.28	43.50	-18.22	QP
2	190.7390	55.20	-20.30	34.90	43.50	-8.60	QP
3	259.2336	53.24	-19.68	33.56	46.00	-12.44	QP
4	423.5402	42.93	-14.22	28.71	46.00	-17.29	QP
5	560.6928	43.56	-9.27	34.29	46.00	-11.71	QP
6	839.1816	40.02	-2.47	37.55	46.00	-8.45	QP

Temperature:	26℃	Relative Humidity:	54%
Pressure:	101kPa	Polarization:	Vertical
Test Voltage:	AC 120V/60Hz		



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	41.4941	43.01	-16.93	26.08	40.00	-13.92	QP
2	65.4578	45.78	-18.88	26.90	40.00	-13.10	QP
3	121.9753	48.57	-21.33	27.24	43.50	-16.26	QP
4	192.4182	53.47	-20.38	33.09	43.50	-10.41	QP
5	560.6928	40.40	-9.27	31.13	46.00	-14.87	QP
6	704.2259	38.70	-7.47	31.23	46.00	-14.77	QP

Remarks:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

Field Strength of The Fundamental Signal

GFSK

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
2402.00	92.20	27.26	5.39	30.18	94.67	114.00	-19.33	Vertical
2402.00	91.53	27.26	5.39	30.18	94.00	114.00	-20.00	Horizontal
2441.00	90.32	27.33	5.43	30.06	93.02	114.00	-20.98	Vertical
2441.00	84.44	27.33	5.43	30.06	87.14	114.00	-26.86	Horizontal
2480.00	91.45	27.40	5.47	29.93	94.39	114.00	-19.61	Vertical
2480.00	88.27	27.40	5.47	29.93	91.21	114.00	-22.79	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
2402.00	80.75	27.26	5.39	30.18	83.22	94.00	-10.78	Vertical
2402.00	78.98	27.26	5.39	30.18	81.45	94.00	-12.55	Horizontal
2441.00	77.84	27.33	5.43	30.06	80.54	94.00	-13.46	Vertical
2441.00	73.98	27.33	5.43	30.06	76.68	94.00	-17.32	Horizontal
2480.00	81.41	27.40	5.47	29.93	84.35	94.00	-9.65	Vertical
2480.00	78.30	27.40	5.47	29.93	81.24	94.00	-12.76	Horizontal

 $\pi/4$ -DQPSK

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
2402.00	90.25	27.26	5.39	30.18	92.72	114.00	-21.28	Vertical
2402.00	88.22	27.26	5.39	30.18	90.69	114.00	-23.31	Horizontal
2441.00	86.60	27.33	5.43	30.06	89.30	114.00	-24.70	Vertical
2441.00	83.12	27.33	5.43	30.06	85.82	114.00	-28.18	Horizontal
2480.00	91.17	27.40	5.47	29.93	94.11	114.00	-19.89	Vertical
2480.00	87.31	27.40	5.47	29.93	90.25	114.00	-23.75	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
2402.00	79.06	27.26	5.39	30.18	81.53	94.00	-12.47	Vertical
2402.00	77.03	27.26	5.39	30.18	79.50	94.00	-14.50	Horizontal
2441.00	75.41	27.33	5.43	30.06	78.11	94.00	-15.89	Vertical
2441.00	71.93	27.33	5.43	30.06	74.63	94.00	-19.37	Horizontal
2480.00	79.98	27.40	5.47	29.93	82.92	94.00	-11.08	Vertical
2480.00	76.12	27.40	5.47	29.93	79.06	94.00	-14.94	Horizontal

8-DPSK

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
2402.00	90.53	27.26	5.39	30.18	93.00	114.00	-21.00	Vertical
2402.00	89.32	27.26	5.39	30.18	91.79	114.00	-22.21	Horizontal
2441.00	88.55	27.33	5.43	30.06	91.25	114.00	-22.75	Vertical
2441.00	83.51	27.33	5.43	30.06	86.21	114.00	-27.79	Horizontal
2480.00	90.81	27.40	5.47	29.93	93.75	114.00	-20.25	Vertical
2480.00	87.03	27.40	5.47	29.93	89.97	114.00	-24.03	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
2402.00	79.81	27.26	5.39	30.18	82.28	94.00	-11.72	Vertical
2402.00	77.42	27.26	5.39	30.18	79.89	94.00	-14.11	Horizontal
2441.00	76.50	27.33	5.43	30.06	79.20	94.00	-14.80	Vertical
2441.00	73.12	27.33	5.43	30.06	75.82	94.00	-18.18	Horizontal
2480.00	80.89	27.40	5.47	29.93	83.83	94.00	-10.17	Vertical
2480.00	77.18	27.40	5.47	29.93	80.12	94.00	-13.88	Horizontal

GFSK

Polar (H/V)	Frequency	Meter Reading	Pre-ampli fier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel:2402MHz									
V	4804.00	50.35	30.55	5.77	31.12	56.69	74.00	-17.31	Pk
V	4804.00	30.21	30.55	5.77	31.12	36.55	54.00	-17.45	AV
V	7206.00	48.44	30.33	6.32	36.04	60.47	74.00	-13.53	Pk
V	7206.00	30.92	30.33	6.32	36.04	42.95	54.00	-11.05	AV
V	9608.00	48.94	30.85	7.45	37.58	63.12	74.00	-10.88	Pk
V	9608.00	30.82	30.85	7.45	37.58	45.00	54.00	-9.00	AV
V	12010.00	49.04	31.02	8.99	39.10	66.11	74.00	-7.89	Pk
V	12010.00	30.82	31.02	8.99	39.10	47.89	54.00	-6.11	AV
H	4804.00	50.69	30.55	5.77	31.12	57.03	74.00	-16.97	Pk
H	4804.00	30.54	30.55	5.77	31.12	36.88	54.00	-17.12	AV
H	7206.00	49.33	30.33	6.32	36.04	61.36	74.00	-12.64	Pk
H	7206.00	30.49	30.33	6.32	36.04	42.52	54.00	-11.48	AV
H	9608.00	49.33	30.85	7.45	37.58	63.51	74.00	-10.49	Pk
H	9608.00	30.19	30.85	7.45	37.58	44.37	54.00	-9.63	AV
H	12010.00	48.73	31.02	8.99	39.10	65.80	74.00	-8.20	Pk
H	12010.00	29.59	31.02	8.99	39.10	46.66	54.00	-7.34	AV

Polar (H/V)	Frequency	Meter Reading	Pre-ampli fier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Middle Channel:2441MHz									
V	4882.00	50.83	30.55	5.77	31.46	57.51	74.00	-16.49	Pk
V	4882.00	31.72	30.55	5.77	31.46	38.40	54.00	-15.60	AV
V	7323.00	49.36	30.33	6.32	36.15	61.50	74.00	-12.50	Pk
V	7323.00	31.50	30.33	6.32	36.15	43.64	54.00	-10.36	AV
V	9764.00	49.43	30.85	7.45	37.76	63.79	74.00	-10.21	Pk
V	9764.00	31.40	30.85	7.45	37.76	45.76	54.00	-8.24	AV
V	12205.00	49.33	31.02	8.99	39.10	66.40	74.00	-7.60	Pk
V	12205.00	31.40	31.02	8.99	39.10	48.47	54.00	-5.53	AV
H	4882.00	52.19	30.55	5.77	31.46	58.87	74.00	-15.13	Pk
H	4882.00	31.75	30.55	5.77	31.46	38.43	54.00	-15.57	AV
H	7323.00	52.90	30.33	6.32	36.15	65.04	74.00	-8.96	Pk
H	7323.00	31.53	30.33	6.32	36.15	43.67	54.00	-10.33	AV
H	9764.00	52.80	30.85	7.45	37.76	67.16	74.00	-6.84	Pk
H	9764.00	31.53	30.85	7.45	37.76	45.89	54.00	-8.11	AV
H	12205.00	49.40	31.02	8.99	39.10	66.47	74.00	-7.53	Pk
H	12205.00	30.73	31.02	8.99	39.10	47.80	54.00	-6.20	AV

Polar (H/V)	Frequency	Meter Reading	Pre-ampli fier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
High Channel:2480MHz									
V	4960.00	48.96	30.55	5.77	31.79	55.97	74.00	-18.03	Pk
V	4960.00	30.50	30.55	5.77	31.79	37.51	54.00	-16.49	AV
V	7440.00	51.47	30.33	6.32	36.38	63.84	74.00	-10.16	Pk
V	7440.00	30.82	30.33	6.32	36.38	43.19	54.00	-10.81	AV
V	9920.00	51.47	30.85	7.45	36.50	64.57	74.00	-9.43	Pk
V	9920.00	31.31	30.85	7.45	36.50	44.41	54.00	-9.59	AV
V	12400.00	51.47	31.02	8.99	39.11	68.55	74.00	-5.45	Pk
V	12400.00	30.71	31.02	8.99	39.11	47.79	54.00	-6.21	AV
H	4960.00	49.05	30.55	5.77	31.79	56.06	74.00	-17.94	Pk
H	4960.00	30.72	30.55	5.77	31.79	37.73	54.00	-16.27	AV
H	7440.00	50.64	30.33	6.32	36.38	63.01	74.00	-10.99	Pk
H	7440.00	30.98	30.33	6.32	36.38	43.35	54.00	-10.65	AV
H	9920.00	51.21	30.85	7.45	36.50	64.31	74.00	-9.69	Pk
H	9920.00	31.08	30.85	7.45	36.50	44.18	54.00	-9.82	AV
H	12400.00	51.14	31.02	8.99	39.11	68.22	74.00	-5.78	Pk
H	12400.00	31.08	31.02	8.99	39.11	48.16	54.00	-5.84	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

$\pi/4$ -DQPSK

Polar (H/V)	Frequency	Meter Reading	Pre-ampli fier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel:2402MHz									
V	4804.00	50.81	30.55	5.77	31.12	57.15	74.00	-16.85	Pk
V	4804.00	30.57	30.55	5.77	31.12	36.91	54.00	-17.09	AV
V	7206.00	48.60	30.33	6.32	36.04	60.63	74.00	-13.37	Pk
V	7206.00	31.52	30.33	6.32	36.04	43.55	54.00	-10.45	AV
V	9608.00	48.60	30.85	7.45	37.58	62.78	74.00	-11.22	Pk
V	9608.00	31.08	30.85	7.45	37.58	45.26	54.00	-8.74	AV
V	12010.00	48.70	31.02	8.99	39.10	65.77	74.00	-8.23	Pk
V	12010.00	30.98	31.02	8.99	39.10	48.05	54.00	-5.95	AV
H	4804.00	51.15	30.55	5.77	31.12	57.49	74.00	-16.51	Pk
H	4804.00	31.00	30.55	5.77	31.12	37.34	54.00	-16.66	AV
H	7206.00	49.90	30.33	6.32	36.04	61.93	74.00	-12.07	Pk
H	7206.00	31.21	30.33	6.32	36.04	43.24	54.00	-10.76	AV
H	9608.00	49.92	30.85	7.45	37.58	64.10	74.00	-9.90	Pk
H	9608.00	31.23	30.85	7.45	37.58	45.41	54.00	-8.59	AV
H	12010.00	49.95	31.02	8.99	39.10	67.02	74.00	-6.98	Pk
H	12010.00	30.24	31.02	8.99	39.10	47.31	54.00	-6.69	AV

Polar (H/V)	Frequency	Meter Reading	Pre-ampli fier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Middle Channel:2441MHz									
V	4882.00	48.39	30.55	5.77	31.46	55.07	74.00	-18.93	Pk
V	4882.00	29.28	30.55	5.77	31.46	35.96	54.00	-18.04	AV
V	7323.00	47.09	30.33	6.32	36.15	59.23	74.00	-14.77	Pk
V	7323.00	29.11	30.33	6.32	36.15	41.25	54.00	-12.75	AV
V	9764.00	47.17	30.85	7.45	37.76	61.53	74.00	-12.47	Pk
V	9764.00	29.13	30.85	7.45	37.76	43.49	54.00	-10.51	AV
V	12205.00	47.15	31.02	8.99	39.10	64.22	74.00	-9.78	Pk
V	12205.00	29.14	31.02	8.99	39.10	46.21	54.00	-7.79	AV
H	4882.00	49.65	30.55	5.77	31.46	56.33	74.00	-17.67	Pk
H	4882.00	29.41	30.55	5.77	31.46	36.09	54.00	-17.91	AV
H	7323.00	50.36	30.33	6.32	36.15	62.50	74.00	-11.50	Pk
H	7323.00	29.21	30.33	6.32	36.15	41.35	54.00	-12.65	AV
H	9764.00	50.56	30.85	7.45	37.76	64.92	74.00	-9.08	Pk
H	9764.00	29.26	30.85	7.45	37.76	43.62	54.00	-10.38	AV
H	12205.00	51.11	31.02	8.99	39.10	68.18	74.00	-5.82	Pk
H	12205.00	29.19	31.02	8.99	39.10	46.26	54.00	-7.74	AV

Polar (H/V)	Frequency	Meter Reading	Pre-ampli fier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
High Channel:2480MHz									
V	4960.00	49.13	30.55	5.77	31.79	56.14	74.00	-17.86	Pk
V	4960.00	30.80	30.55	5.77	31.79	37.81	54.00	-16.19	AV
V	7440.00	51.44	30.33	6.32	36.38	63.81	74.00	-10.19	Pk
V	7440.00	30.69	30.33	6.32	36.38	43.06	54.00	-10.94	AV
V	9920.00	51.44	30.85	7.45	36.50	64.54	74.00	-9.46	Pk
V	9920.00	31.38	30.85	7.45	36.50	44.48	54.00	-9.52	AV
V	12400.00	51.56	31.02	8.99	39.11	68.64	74.00	-5.36	Pk
V	12400.00	31.08	31.02	8.99	39.11	48.16	54.00	-5.84	AV
H	4960.00	49.10	30.55	5.77	31.79	56.11	74.00	-17.89	Pk
H	4960.00	30.87	30.55	5.77	31.79	37.88	54.00	-16.12	AV
H	7440.00	50.41	30.33	6.32	36.38	62.78	74.00	-11.22	Pk
H	7440.00	31.01	30.33	6.32	36.38	43.38	54.00	-10.62	AV
H	9920.00	50.80	30.85	7.45	36.50	63.90	74.00	-10.10	Pk
H	9920.00	31.16	30.85	7.45	36.50	44.26	54.00	-9.74	AV
H	12400.00	51.11	31.02	8.99	39.11	68.19	74.00	-5.81	Pk
H	12400.00	29.93	31.02	8.99	39.11	47.01	54.00	-6.99	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

8-DPSK

Polar (H/V)	Frequency	Meter Reading	Pre-ampli fier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel:2402MHz									
V	4804.00	50.67	30.55	5.77	31.12	57.01	74.00	-16.99	Pk
V	4804.00	30.45	30.55	5.77	31.12	36.79	54.00	-17.21	AV
V	7206.00	47.34	30.33	6.32	36.04	59.37	74.00	-14.63	Pk
V	7206.00	31.45	30.33	6.32	36.04	43.48	54.00	-10.52	AV
V	9608.00	48.71	30.85	7.45	37.58	62.89	74.00	-11.11	Pk
V	9608.00	31.02	30.85	7.45	37.58	45.20	54.00	-8.80	AV
V	12010.00	48.50	31.02	8.99	39.10	65.57	74.00	-8.43	Pk
V	12010.00	30.39	31.02	8.99	39.10	47.46	54.00	-6.54	AV
H	4804.00	50.81	30.55	5.77	31.12	57.15	74.00	-16.85	Pk
H	4804.00	30.64	30.55	5.77	31.12	36.98	54.00	-17.02	AV
H	7206.00	49.54	30.33	6.32	36.04	61.57	74.00	-12.43	Pk
H	7206.00	31.02	30.33	6.32	36.04	43.05	54.00	-10.95	AV
H	9608.00	49.76	30.85	7.45	37.58	63.94	74.00	-10.06	Pk
H	9608.00	30.91	30.85	7.45	37.58	45.09	54.00	-8.91	AV
H	12010.00	49.99	31.02	8.99	39.10	67.06	74.00	-6.94	Pk
H	12010.00	29.97	31.02	8.99	39.10	47.04	54.00	-6.96	AV

Polar (H/V)	Frequency	Meter Reading	Pre-ampli fier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Middle Channel:2441MHz									
V	4882.00	50.12	30.55	5.77	31.46	56.80	74.00	-17.20	Pk
V	4882.00	31.10	30.55	5.77	31.46	37.78	54.00	-16.22	AV
V	7323.00	48.04	30.33	6.32	36.15	60.18	74.00	-13.82	Pk
V	7323.00	30.93	30.33	6.32	36.15	43.07	54.00	-10.93	AV
V	9764.00	49.12	30.85	7.45	37.76	63.48	74.00	-10.52	Pk
V	9764.00	31.18	30.85	7.45	37.76	45.54	54.00	-8.46	AV
V	12205.00	49.02	31.02	8.99	39.10	66.09	74.00	-7.91	Pk
V	12205.00	31.33	31.02	8.99	39.10	48.40	54.00	-5.60	AV
H	4882.00	51.49	30.55	5.77	31.46	58.17	74.00	-15.83	Pk
H	4882.00	31.23	30.55	5.77	31.46	37.91	54.00	-16.09	AV
H	7323.00	52.43	30.33	6.32	36.15	64.57	74.00	-9.43	Pk
H	7323.00	30.95	30.33	6.32	36.15	43.09	54.00	-10.91	AV
H	9764.00	52.38	30.85	7.45	37.76	66.74	74.00	-7.26	Pk
H	9764.00	31.65	30.85	7.45	37.76	46.01	54.00	-7.99	AV
H	12205.00	50.55	31.02	8.99	39.10	67.62	74.00	-6.38	Pk
H	12205.00	31.09	31.02	8.99	39.10	48.16	54.00	-5.84	AV

Polar (H/V)	Frequency	Meter Reading	Pre-ampli fier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
High Channel:2480MHz									
V	4960.00	48.85	30.55	5.77	31.79	55.86	74.00	-18.14	Pk
V	4960.00	30.01	30.55	5.77	31.79	37.02	54.00	-16.98	AV
V	7440.00	51.10	30.33	6.32	36.38	63.47	74.00	-10.53	Pk
V	7440.00	30.28	30.33	6.32	36.38	42.65	54.00	-11.35	AV
V	9920.00	51.17	30.85	7.45	36.50	64.27	74.00	-9.73	Pk
V	9920.00	31.00	30.85	7.45	36.50	44.10	54.00	-9.90	AV
V	12400.00	50.70	31.02	8.99	39.11	67.78	74.00	-6.22	Pk
V	12400.00	30.34	31.02	8.99	39.11	47.42	54.00	-6.58	AV
H	4960.00	48.88	30.55	5.77	31.79	55.89	74.00	-18.11	Pk
H	4960.00	30.54	30.55	5.77	31.79	37.55	54.00	-16.45	AV
H	7440.00	50.37	30.33	6.32	36.38	62.74	74.00	-11.26	Pk
H	7440.00	30.81	30.33	6.32	36.38	43.18	54.00	-10.82	AV
H	9920.00	51.03	30.85	7.45	36.50	64.13	74.00	-9.87	Pk
H	9920.00	31.80	30.85	7.45	36.50	44.90	54.00	-9.10	AV
H	12400.00	50.99	31.02	8.99	39.11	68.07	74.00	-5.93	Pk
H	12400.00	30.92	31.02	8.99	39.11	48.00	54.00	-6.00	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

5. BANDWIDTH OF FREQUENCY BAND EDGE

5.1 TEST REQUIREMENT:

Test Requirement:	FCC Part15 C Section 15.209 and 15.205				
Test Method:	ANSI C63.10: 2013				
Test Frequency Range:	All of the restrict bands were tested, only the worst band's (2310MHz to 2500MHz) data was showed.				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Value
	Above 1GHz	Peak	1MHz	3MHz	Peak
		Average	1MHz	3MHz	Average

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in § 15.209, whichever is the lesser attenuation

5.2 TEST PROCEDURE

Above 1GHz test procedure as below:

- The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- Test the EUT in the lowest channel, the Highest channel

Note:


Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

5.3 DEVIATION FROM TEST STANDARD

No deviation

5.4 TEST SETUP

Radiated Emission Test-Up Frequency Above 1GHz



5.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.


5.6 TEST RESULT

Temperature :	26 °C	Relative Humidity :	54%
Pressure :	101 kPa	Test Voltage :	AC 120V/60Hz
Test Mode :	TX Mode-GFSK-Worst Case		


Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2390.00	43.71	27.25	5.38	30.18	46.16	74.00	-27.84	Horizontal
2400.00	46.38	27.26	5.39	30.18	48.85	74.00	-25.15	Horizontal
2390.00	43.64	27.25	5.38	30.18	46.09	74.00	-27.91	Vertical
2400.00	43.30	27.26	5.39	30.18	45.77	74.00	-28.23	Vertical

2402MHz Horizontal



2402MHz Vertical




Temperature :	26 °C	Relative Humidity :	54%
Pressure :	101 kPa	Test Voltage :	AC 120V/60Hz
Test Mode :	TX Mode-GFSK-Worst Case		


Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	44.96	27.25	5.47	29.93	47.75	74.00	-26.25	Horizontal
2500.00	45.49	27.26	5.49	29.93	48.31	74.00	-25.69	Horizontal
2483.50	45.76	27.25	5.47	29.93	48.55	74.00	-25.45	Vertical
2500.00	47.01	27.26	5.49	29.93	49.83	74.00	-24.17	Vertical

2480MHz Horizontal



2480MHz Vertical



6. CHANNEL BANDWIDTH

Test Requirement:	FCC Part15 C Section 15.249/15.215
Test Method:	ANSI C63.10: 2013

6.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.249) , Subpart C			
Section	Test Item	Frequency Range (MHz)	Result
15.249(c)	Bandwidth	2400-2483.5	PASS


6.2 TEST PROCEDURE

1. Set resolution bandwidth (RBW) = 1-5% or DTS BW, not to exceed 100 kHz.
2. Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

6.3 DEVIATION FROM STANDARD

No deviation.

6.4 TEST SETUP



6.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

6.6 TSET RESULTS



Temperature :	26℃	Relative Humidity :	54%
Test Mode :	GFSK, $\pi/4$ -DQPSK, 8-DPSK	Test Voltage :	AC 120V/60Hz

Mode	Test channel	20dB Emission Bandwidth (MHz)	Result
GFSK	Lowest	0.974	Pass
	Middle	0.977	
	Highest	0.942	
$\pi/4$ -DQPSK	Lowest	1.352	Pass
	Middle	1.352	
	Highest	1.352	
8-DPSK	Lowest	1.328	Pass
	Middle	1.331	
	Highest	1.333	



Test plots

GFSK



$\pi/4$ -DQPSK



Lowest channel




Middle channel




Highest channel


8-DPSK



Lowest channel



Middle channel



Highest channel

8.ANTENNA REQUIREMENT

Standard requirement:	FCC Part15 C Section 15.203
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.	
EUT Antenna:	
The antennas are PCB antenna, the best case gain of the antennas are 0dBi, reference to the appendix II for details	

9. TEST SETUP PHOTO

Reference to the appendix I for details.

10. EUT CONSTRUCTIONAL DETAILS

Reference to the appendix II for details.

***** END OF REPORT *****