

Test Report

Product: Minilaptop

Trade Mark: N/A

Model Number: NA105H

FCC ID: 2BB3W-NA105H

Prepared for

ShenZhen ZhiWei Technology Co., Ltd
6th Floor, Bld 8, Lijincheng Industrial Park Longhua Street, Longhua District
shenzhen China

Prepared by

Shenzhen HongBiao Certification& Testing Co., Ltd
Room 102, 201, Building 2, Yuanwanggu RFID Industrial Park, Tongguan
Road, Tianliao Community, Yutang Street, Guangming District, Shenzhen,
China
Tel.: +86-755-2998 9321 Fax.: +86-755-2998 5110
Website: <http://www.sz-hongbiao.com>

Table of Contents

1	GENERAL DESCRIPTION	6
1.1	DESCRIPTION OF EUT	6
1.2	TEST MODE.....	6
1.3	OPERATION CHANNEL LIST.....	7
1.4	TEST SETUP	7
1.5	POWER SETTING CONFIGURATION PARAMETERS	8
1.6	ANCILLARY EQUIPMENT	8
2	SUMMARY OF TEST RESULT	9
3	TEST FACILITIES AND ACCREDITATIONS	10
3.1	TEST LABORATORY	10
3.2	ENVIRONMENTAL CONDITIONS	10
3.3	MEASUREMENT UNCERTAINTY	10
3.4	TEST SOFTWARE	11
4	LIST OF TEST EQUIPMENT	12
5	TEST ITEM AND RESULTS.....	14
5.1	ANTENNA REQUIREMENT	14
5.1.1	<i>Standard Requirement</i>	14
5.1.2	<i>Test Result</i>	14
5.2	CONDUCTED EMISSION.....	15
5.2.1	<i>Limits</i>	15
5.2.2	<i>Test Procedures</i>	15
5.2.3	<i>Test Setup</i>	16
5.2.4	<i>Test Result</i>	16
5.3	RADIATED EMISSION	19
5.3.1	<i>Limits</i>	19
5.3.2	<i>Test Procedures</i>	19
5.3.3	<i>Test Setup</i>	19
5.3.4	<i>Test Result</i>	20
5.3.5	<i>Radiated Band Edge</i>	25
5.3.6	<i>Spurious Emission in Restricted Band 1000MHz-25000MHz</i>	28
5.4	PEAK OUTPUT POWER	29
5.4.1	<i>Limit</i>	29
5.4.2	<i>Test Procedure</i>	29
5.4.3	<i>Test Setup</i>	29
5.4.4	<i>Test Results</i>	29
5.5	POWER SPECTRAL DENSITY.....	32
5.5.1	<i>Limit</i>	32
5.5.2	<i>Test Procedure</i>	32
5.5.3	<i>Test Setup</i>	32
5.5.4	<i>Test Results</i>	32
5.6	6dB BANDWIDTH	39
5.6.1	<i>Limit</i>	39
5.6.2	<i>Test Procedure</i>	39
5.6.3	<i>Test Setup</i>	39
5.6.4	<i>Test Results</i>	39
5.7	DUTY CYCLE	46
5.7.1	<i>Limit</i>	46

5.7.2 Test Procedure 46

5.7.3 Test Setup..... 46

5.7.4 Test Results 47

5.8 CONDUCTED BAND EDGE 57

5.8.1 Limit 57

5.8.2 Test Procedure 57

5.8.3 Test Setup..... 57

5.8.4 Test Results 57

5.9 SPURIOUS RF CONDUCTED EMISSIONS 64

5.9.1 Limit 64

5.9.2 Measuring Instruments 64

5.9.3 Test Procedure 64

5.9.4 Test Setup..... 64

5.9.5 Test Results 64

6 PHOTOGRAPHS OF THE TEST SETUP.....66

7 PHOTOGRAPHS OF THE EUT.....68

TEST RESULT CERTIFICATION

Applicant's Name..... : ShenZhen ZhiWei Technology Co., Ltd
Address : 6th Floor, Bld 8, Lijincheng Industrial Park Longhua Street,
Longhua District shenzhen China

Manufacturer's Name : ShenZhen ZhiWei Technology Co., Ltd
Address : 6th Floor, Bld 8, Lijincheng Industrial Park Longhua Street,
Longhua District shenzhen China

Product description

Product name : Minilaptop

Model Number : NA105H

Standards : FCC Part 15.247

Test procedure..... : IEEE/ANSI C63.10-2020
KDB 558074 D01 15.247 Meas Guidance v05r02


This device described above has been tested by Shenzhen HongBiao Certification& Testing Co., Ltd and the test results show that the equipment under test (EUT) is in compliance with the EMC requirements. And it is applicable only to the tested sample identified in the report.

Date of Test

Date (s) of performance of tests..... : June 20, 2025~ July 01, 2025

Test Result..... : **Pass**

Testing Engineer :




(Z o e S u)

Technical Manager :



(G a r y L u)

Authorized Signatory :



(L e o S u)

Revision History

[illegible]

1 General Description

1.1 Description of EUT

Product name:	Minilaptop
Model name:	NA105H
Series Model:	N/A
Different of series model:	N/A
Operation frequency:	IEEE 802.11b/g/n20/ax20: 2412~2462 MHz IEEE 802.11n40/ax40: 2422~2452 MHz
Modulation type::	IEEE 802.11b: DSSS (CCK, DQPSK, DBPSK) IEEE 802.11g/n: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11ax: OFDMA (1024QAM, 256QAM, 64QAM, 16QAM, QPSK, BPSK)
Bit Rate of transmitter:	IEEE 802.11b: Up to 11 Mbps IEEE 802.11g: Up to 54 Mbps IEEE 802.11n-HT20/HT40: Up to MCS15 IEEE 802.11ax-HE20/ HE40: Up to MCS11
Antenna type:	Internal Antenna
Antenna gain:	3.85dBi
Max. output power:	8.65dBm
Hardware version:	IP3-DNN20A
Software version:	DNN20AV3.54.rom
Battery:	Norminal Voltage: 7.6Vd.c Rated Capacity: 3800mAh, 28.88Wh Charge Limited Voltage: 8.7V
Power supply:	DC 12V from adapter AC 120V/60Hz
Adapter information:	Model: J302-1203000UX Input: 100-240V~50/60Hz 1.5A Output: 12.0V=3.0A 36.0W

1.2 Test Mode

Channel List for 802.11b/g/n/ax (20)

Channel	Channel	Frequency (MHz)
Low	01	2412

Middle	06	2437
High	11	2462

Channel List for 802.11n/ax (40)

Channel	Channel	Frequency (MHz)
Low	03	2422
Middle	06	2437
High	09	2452

Note: 802.11ax mode only support full resource unit size.

1.3 Operation Channel list

Channel List for 802.11b/g/n/ax (20)

Channel	Frequency (MHz)	Channel	Frequency (MHz)
01	2412	07	2442
02	2417	08	2447
03	2422	09	2452
04	2427	10	2457
05	2432	11	2462
06	2437	\	\

Channel List for 802.11n/ax (40)

Channel	Frequency (MHz)	Channel	Frequency (MHz)
03	2422	07	2442
04	2427	08	2447
05	2432	09	2452
06	2437	\	\

1.4 Test Setup

See photographs of the test setup in the report for the actual setup and connections between EUT and support equipment.

1.5 Power setting configuration parameters

During testing channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters.

Test software Version		Engineering mode	
Mode	802.11b/g	802.11n/ax 20	802.11n/ax 40
Parameters	Default	Default	Default
RF cable			
Description	Connector	Length	Supplied by
Antenna Cable	SMA	10cm	Applicant

Note: Disclaimer: the loss of RF cable is too small and can be ignored.

1.6 Ancillary Equipment

Equipment	Model	S/N	Manufacturer
/	/	/	/

2 Summary of Test Result

No.	Standard Section	Test Item	Result	Remark
1	15.203	Antenna Requirement	Pass	
2	15.247 (b)	Peak Output Power	Pass	
3	15.207	Conducted Emission	Pass	
4	15.247 (d) & 15.209	Radiated Spurious Emission	Pass	
5	15.247 (e)	Power Spectral Density	Pass	
6	15.247 (a)(2)	6dB Bandwidth	Pass	
7	558074 D01 15.247 Meas Guidance v05r02 Chapter 6	Duty Cycle	Pass	
8	15.205	Band Edge Emission	Pass	
9	15.247(d)	Spurious RF Conducted Emissions	Pass	

3 Test Facilities and Accreditations

3.1 Test Laboratory

Test Site	Shenzhen HongBiao Certification& Testing Co., Ltd
Test Site Location	Room 102, 201, Building 2, Yuanwanggu RFID Industrial Park, Tongguan Road, Tianliao Community, Yutang Street, Guangming District, Shenzhen, China
Telephone:	(86-755) 2998 9321
Fax:	(86-755) 2998 5110
FCC Registration No.:	CN1341
A2LA Certificate No.:	6765.01

3.2 Environmental Conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	15°C~35°C
Relative Humidity:	20%~75%
Air Pressure:	98kPa~101kPa

3.3 Measurement Uncertainty

The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

The data and results quoted in this document are true and accurate values, and uncertainties are not involved in the calculations.

In addition, components and mass production processes that are similar to testing equipment may introduce additional deviations, and the manufacturer is solely responsible for the continued compliance of the equipment.

Measurement Frequency Range	U, (dB)	Note
RF frequency	2×10^{-5}	
RF power, conducted	± 0.57 dB	
Conducted emission(150kHz~30MHz)	± 2.5 dB	
Radiated emission(9kHz-30MHz)	± 2.5 dB	
Radiated emission(30MHz~1GHz)	± 4.2 dB	
Radiated emission (above 1GHz)	± 4.7 dB	
Occupied Bandwidth	$\pm 3\%$	
Temperature	± 1 degree	
Humidity	± 5 %	

3.4 Test Software

Software name	Manufacturer	Model	Version
Conducted Emission test Software	Farad	EZ-EMC	EMC-CON 3A1.1+
Radiated Emission test Software	Farad	EZ-EMC	FA-03A2
RF Test System	MWRF	MTS 8310	2.0.0.0

4 List of Test Equipment

Radiation emission							
Item	Equipment No.	Equipment name	Manufacturer	Model	Serial No.	Calibration date	Due date
1	HB-E001	Horn Antenna	Schwarzbeck	BBHA 9120D	02592	2024-05-18	2026-05-17
2	HB-E002	Biconical log-periodic composite antenna	Schwarzbeck	VULB 9168	01340	2024-05-18	2026-05-17
3	HB-E003	SHF-EHF Horn	Schwarzbeck	BBHA 91270	01193	2024-05-18	2026-05-17
4	HB-E005	Preamplifier	Noyetec	LAN-0118	NYCM1420102	2025-05-07	2026-05-06
5	HB-E006	Preamplifier	Noyetec	LAN-1840	NYCM1420103	2025-05-07	2026-05-06
6	HB-E007	EMI TEST RECEIVER	R&S	ESR7	102520	2025-05-07	2026-05-06
7	HB-E009	POSITINAL COTROLLE R	Noyetec	N/A	N/A	/	/
8	HB-E013	RF switch	Noyetec	NY-RF4	NY0CM1420204	/	/
9	HB-E066	Illuminance Tester	TASI	TA8121	N/A	2025-05-13	2026-05-12
10	HB-E075	Active loop antenna	Schwarzbeck	FMZB 1519B	1519B-245	2024-05-18	2026-05-17
11	HB-E076	Preamplifier	Hewlett Packard	8447D	1937A02278	2025-05-07	2026-05-06
Conduction emission							
Item	Equipment No.	Equipment name	Manufacturer	Model	Serial No.	Calibration date	Due date
1	HB-E014	4 Path V-LISN	Schwarzbeck	NNLK 8121	00770	2025-05-07	2026-05-06
2	HB-E015	Pulse Limiter	Schwarzbeck	VTSD 9561-F	00949	2025-05-07	2026-05-06
3	HB-E016	ZN23201	Noyetec	ZN23201	N/A	2025-05-10	2026-05-09
4	HB-E059	Attenuator	Xianghua	TS2-6-1	220215166	2025-05-10	2026-05-09
5	HB-E069	EMI TEST RECEIVER	R&S	ESCI	N/A	2025-05-07	2026-05-06
RF							
Item	Equipment No.	Equipment name	Manufacturer	Model	Serial No.	Calibration date	Due date
1	HB-E041	MXG AnaioG Signal Generator	Agilent	N5181A	MY47070421	2025-05-07	2026-05-06

2	HB-E042	WIDEBAND RADIO COMMUNICA TION TESTER	R&S	CMW500	132108	2025-05-08	2026-05-07
3	HB-E043	MXG Anaio Signal Generator	Agilent	N5182A	US46240335	2025-05-08	2026-05-07
4	HB-E044	Signal& spectrum Analyzer	R&S	FSV3044	101264	2025-05-07	2026-05-06
5	HB-E045	RF Control Box	Noyetec	NY100-R FCB	N/A	2025-05-08	2026-05-07
6	HB-E058	Thermometer Clock Humidity Monitor	N/A	HTC-1S	N/A	2025-05-09	2026-05-08

Note:

1. The calibration interval of the above test instruments is 12&24 months and the calibrations are traceable to international system unit (SI).
2. The instrument RF Control Box, numbered HB-E045, contains power meter.

5 Test Item And Results

5.1 Antenna Requirement

5.1.1 Standard Requirement

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device

5.1.2 Test Result

The EUT antenna is Internal Antenna. It comply with the standard requirement. In case of replacement of broken antenna the same antenna type must be used.

5.2 Conducted Emission

5.2.1 Limits

Limits – Class B		
Frequency (MHz)	Limit (dBµV)	
	Quasi-Peak	Average
0.15 to 0.5	66 to 56*	56 to 46*
0.5 to 5	56	46
5 to 30	60	50
Note: 1. the tighter limit applies at the band edges. 2. the limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.		

5.2.2 Test Procedures

a) EUT Operating Conditions

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.


b) The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

- c) The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipment powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- d) Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- e) I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- f) LISN is at least 80 cm from nearest part of EUT chassis.


- g) For the actual test configuration, please refer to the related Item – photographs of the test setup.

5.2.3 Test Setup




5.2.4 Test Result

EUT:	Minilaptop	Model Name:	NA105H
Test Mode:	Charging + TX	Phase:	L
Test Voltage:	DC 12V from adapter AC 120V/60Hz		



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.618	33.44	10.11	43.55	56.00	-12.45	QP
2	0.618	19.86	10.11	29.97	46.00	-16.03	AVG
3	0.928	33.58	10.13	43.71	56.00	-12.29	QP
4	0.928	19.36	10.13	29.49	46.00	-16.51	AVG
5	1.631	34.37	10.27	44.64	56.00	-11.36	QP
6	1.631	16.80	10.27	27.07	46.00	-18.93	AVG
7	2.818	34.48	10.59	45.07	56.00	-10.93	QP
8	2.818	17.98	10.59	28.57	46.00	-17.43	AVG
9 *	4.601	35.07	11.21	46.28	56.00	-9.72	QP
10	4.601	19.19	11.21	30.40	46.00	-15.60	AVG
11	11.162	35.46	13.68	49.14	60.00	-10.86	QP
12	11.162	20.36	13.68	34.04	50.00	-15.96	AVG

EUT:	Minilaptop	Model Name:	NA105H
Test Mode:	Charging + TX	Phase:	N
Test Voltage:	DC 12V from adapter AC 120V/60Hz		



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.456	28.73	10.12	38.85	56.77	-17.92	QP
2	0.456	19.42	10.12	29.54	46.77	-17.23	AVG
3	0.474	30.03	10.12	40.15	56.44	-16.29	QP
4 *	0.474	23.66	10.12	33.78	46.44	-12.66	AVG
5	0.591	27.79	10.12	37.91	56.00	-18.09	QP
6	0.591	18.59	10.12	28.71	46.00	-17.29	AVG
7	0.793	27.68	10.12	37.80	56.00	-18.20	QP
8	0.793	18.38	10.12	28.50	46.00	-17.50	AVG
9	1.266	28.19	10.19	38.38	56.00	-17.62	QP
10	1.266	19.01	10.19	29.20	46.00	-16.80	AVG
11	11.697	30.58	13.79	44.37	60.00	-15.63	QP
12	11.697	18.96	13.79	32.75	50.00	-17.25	AVG

5.3 Radiated Emission

5.3.1 Limits




Frequencies (MHz)	Field Strength (micроволts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

5.3.2 Test Procedures

- The radiated emission tests were performed in the 3 meters.
- The EUT is placed on a turn table which is 0.8 meter above ground for below 1 GHz, and 1.5 m for above 1 GHz. The turn table is rotated 360 degrees to determine the position of the maximum emission level.
- The height of the test antenna shall vary between 1m to 4m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- If the peak mode measured value compliance with and lower than quasi peak mode limit, the EUT shall be deemed to meet QP limits and then no additional QP mode measurement performed.
- If the peak mode measured value compliance with and lower than average mode limit, the EUT shall be deemed to meet average limits and then no additional average mode measurement performed.
- For the actual test configuration, please refer to the related item – EUT test photos.

5.3.3 Test Setup

Radiated Emission Test-Up Frequency Below 30MHzRadiated Emission Test-Up Frequency 30MHz~1GHzRadiated emission test-up frequency above 1GHz**5.3.4 Test Result**

Below 30MHz

EUT:	Minilaptop	Model Name:	NA105H
Pressure:	1010 hPa	Test Voltage:	DC 7.6V from battery
Test Mode:	TX	Polarization:	--


Freq.	Reading	Limit	Margin	State
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F
--	--	--	--	Pass
--	--	--	--	Pass

Note:

1. For 9kHz-30MHz, the amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.
2. Distance extrapolation factor = $40 \log (\text{specific distance}/\text{test distance})$ (dB);
3. Limit line = specific limits (dBuV) + distance extrapolation factor.


Frequency range (30MHz – 1GHz)

EUT:	Minilaptop	Model Name:	NA105H
Test Mode:	TX	Phase:	Vertical
Test Voltage:	DC 7.6V from battery		



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1 *	33.4449	44.20	-14.88	29.32	40.00	-10.68	QP
2	42.1542	42.35	-13.90	28.45	40.00	-11.55	QP
3	47.8260	42.79	-14.02	28.77	40.00	-11.23	QP
4	51.4807	42.42	-14.10	28.32	40.00	-11.68	QP
5	59.2325	41.53	-14.63	26.90	40.00	-13.10	QP
6	118.6014	46.38	-15.63	30.75	43.50	-12.75	QP

EUT:	Minilaptop	Model Name:	NA105H
Test Mode:	TX	Phase:	Horizontal
Test Voltage:	DC 7.6V from battery		



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1 *	74.1351	39.87	-16.68	23.19	40.00	-16.81	QP
2	127.2176	39.83	-14.99	24.84	43.50	-18.66	QP
3	259.2338	38.40	-14.08	24.32	46.00	-21.68	QP
4	306.7537	35.97	-12.25	23.72	46.00	-22.28	QP
5	354.1831	36.60	-10.74	25.86	46.00	-20.14	QP
6	423.5403	32.71	-8.68	24.03	46.00	-21.97	QP

Frequency range (1GHz-25GHz)

Frequency (MHz)	Read Level (dBμV)	Cable loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type	Comment
Low Channel (2412 MHz)(802.11b)--Above 1G									
4824.161	43.61	4.83	33.6	30.80	51.24	74.00	-22.76	Pk	Vertical
4824.161	31.92	4.83	33.6	30.80	39.55	54.00	-14.45	AV	Vertical
7236.396	42.28	5.85	37.45	31.50	54.08	74.00	-19.92	Pk	Vertical
7236.396	32.03	5.85	37.45	31.50	43.83	54.00	-10.17	AV	Vertical
4824.154	43.22	4.83	33.6	30.80	50.85	74.00	-23.15	Pk	Horizontal
4824.154	31.98	4.83	33.6	30.80	39.61	54.00	-14.39	AV	Horizontal
7236.168	43.35	5.85	37.45	31.50	55.15	74.00	-18.85	Pk	Horizontal
7236.168	32.24	5.85	37.45	31.50	44.04	54.00	-9.96	AV	Horizontal
Middle Channel (2437 MHz)(802.11b)--Above 1G									
4874.112	42.61	4.88	33.75	30.80	50.44	74.00	-23.56	Pk	Vertical
4874.112	31.96	4.88	33.75	30.80	39.79	54.00	-14.21	AV	Vertical
7311.247	44.46	5.90	38.10	31.59	56.87	74.00	-17.13	Pk	Vertical
7311.247	32.56	5.90	38.10	31.59	44.97	54.00	-9.03	AV	Vertical
4874.132	43.80	4.88	33.75	30.80	51.63	74.00	-22.37	Pk	Horizontal
4874.132	32.03	4.88	33.75	30.80	39.86	54.00	-14.14	AV	Horizontal
7311.085	44.01	5.90	38.10	31.59	56.42	74.00	-17.58	Pk	Horizontal
7311.085	32.82	5.90	38.10	31.59	45.23	54.00	-8.77	AV	Horizontal
High Channel (2462 MHz)(802.11b)--Above 1G									
4924.169	43.31	4.93	34.04	30.08	52.20	74.00	-21.80	Pk	Vertical
4924.169	31.99	4.93	34.04	30.08	40.88	54.00	-13.12	AV	Vertical
7386.215	43.66	6.01	37.90	31.74	55.83	74.00	-18.17	Pk	Vertical
7386.215	32.41	6.01	37.90	31.74	44.58	54.00	-9.42	AV	Vertical
4924.045	44.28	4.93	34.04	30.08	53.17	74.00	-20.83	Pk	Horizontal
4924.045	32.30	4.93	34.04	30.08	41.19	54.00	-12.81	AV	Horizontal
7386.132	43.56	6.01	37.90	31.74	55.73	74.00	-18.27	Pk	Horizontal
7386.132	32.37	6.01	37.90	31.74	44.54	54.00	-9.46	AV	Horizontal

Note:

1. Emission Level= Antenna Factor + Cable Loss + Read Level - Preamp Factor
2. All other emissions more than 20dB below the limit.
3. The three modulated high, medium and low channels have been tested. The report only shows the worst mode. The worst mode is 802.11b.

5.3.5 Radiated Band Edge

Frequency (MHz)	Meter Reading (dBμV)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamplifier Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type	Comment
802.11b									
2310.00	46.18	3.40	27.80	32.41	44.69	74	-29.31	Pk	Horizontal
2310.00	33.42	3.40	27.80	32.41	32.07	54	-21.93	AV	Horizontal
2310.00	44.78	3.40	27.80	32.41	43.44	74	-30.56	Pk	Vertical
2310.00	33.63	3.40	27.80	32.41	32.22	54	-21.78	AV	Vertical
2390.00	45.72	3.45	27.70	32.49	44.10	74	-29.90	Pk	Vertical
2390.00	34.58	3.45	27.70	32.49	33.01	54	-20.99	AV	Vertical
2390.00	46.20	3.45	27.70	32.49	44.79	74	-29.21	Pk	Horizontal
2390.00	34.51	3.45	27.70	32.49	32.99	54	-21.01	AV	Horizontal
2483.50	47.25	3.48	28.53	32.55	46.51	74	-27.49	Pk	Vertical
2483.50	33.92	3.48	28.53	32.55	33.28	54	-20.72	AV	Vertical
2483.50	46.40	3.48	28.53	32.55	45.56	74	-28.44	Pk	Horizontal
2483.50	33.87	3.48	28.53	32.55	33.17	54	-20.83	AV	Horizontal
2500.00	45.36	3.49	29.20	32.66	45.27	74	-28.73	Pk	Vertical
2500.00	33.72	3.49	29.20	32.66	33.73	54	-20.27	AV	Vertical
2500.00	45.36	3.49	29.20	32.66	45.21	74	-28.79	Pk	Horizontal
2500.00	33.68	3.49	29.20	32.66	33.66	54	-20.34	AV	Horizontal
802.11g									
2310.00	45.94	3.40	27.80	32.41	44.69	74	-29.31	Pk	Horizontal
2310.00	33.46	3.40	27.80	32.41	32.07	54	-21.93	AV	Horizontal
2310.00	44.76	3.40	27.80	32.41	43.44	74	-30.56	Pk	Vertical
2310.00	33.58	3.40	27.80	32.41	32.22	54	-21.78	AV	Vertical
2390.00	45.63	3.45	27.70	32.49	44.10	74	-29.90	Pk	Vertical
2390.00	34.58	3.45	27.70	32.49	33.01	54	-20.99	AV	Vertical
2390.00	46.32	3.45	27.70	32.49	44.79	74	-29.21	Pk	Horizontal
2390.00	34.51	3.45	27.70	32.49	32.99	54	-21.01	AV	Horizontal
2483.50	47.07	3.48	28.53	32.55	46.51	74	-27.49	Pk	Vertical
2483.50	34.10	3.48	28.53	32.55	33.28	54	-20.72	AV	Vertical
2483.50	46.40	3.48	28.53	32.55	45.56	74	-28.44	Pk	Horizontal
2483.50	33.92	3.48	28.53	32.55	33.17	54	-20.83	AV	Horizontal
2500.00	45.48	3.49	29.20	32.66	45.27	74	-28.73	Pk	Vertical
2500.00	33.72	3.49	29.20	32.66	33.73	54	-20.27	AV	Vertical
2500.00	45.46	3.49	29.20	32.66	45.21	74	-28.79	Pk	Horizontal
2500.00	33.90	3.49	29.20	32.66	33.66	54	-20.34	AV	Horizontal

802.11n20									
2310.00	45.96	3.40	27.80	32.41	44.75	74	-29.25	Pk	Horizontal
2310.00	33.40	3.40	27.80	32.41	32.19	54	-21.81	AV	Horizontal
2310.00	44.76	3.40	27.80	32.41	43.55	74	-30.45	Pk	Vertical
2310.00	33.51	3.40	27.80	32.41	32.30	54	-21.70	AV	Vertical
2390.00	45.71	3.45	27.70	32.49	44.37	74	-29.63	Pk	Vertical
2390.00	34.52	3.45	27.70	32.49	33.18	54	-20.82	AV	Vertical
2390.00	46.25	3.45	27.70	32.49	44.91	74	-29.09	Pk	Horizontal
2390.00	34.44	3.45	27.70	32.49	33.10	54	-20.90	AV	Horizontal
2483.50	47.22	3.48	28.53	32.55	46.68	74	-27.32	Pk	Vertical
2483.50	34.02	3.48	28.53	32.55	33.48	54	-20.52	AV	Vertical
2483.50	46.13	3.48	28.53	32.55	45.59	74	-28.41	Pk	Horizontal
2483.50	33.88	3.48	28.53	32.55	33.34	54	-20.66	AV	Horizontal
2500.00	45.43	3.49	29.20	32.66	45.46	74	-28.54	Pk	Vertical
2500.00	33.74	3.49	29.20	32.66	33.77	54	-20.23	AV	Vertical
2500.00	45.19	3.49	29.20	32.66	45.22	74	-28.78	Pk	Horizontal
2500.00	33.79	3.49	29.20	32.66	33.82	54	-20.18	AV	Horizontal
802.11n40									
2310.00	46.10	3.40	27.80	32.41	44.89	74	-29.11	Pk	Horizontal
2310.00	33.54	3.40	27.80	32.41	32.33	54	-21.67	AV	Horizontal
2310.00	44.74	3.40	27.80	32.41	43.53	74	-30.47	Pk	Vertical
2310.00	33.57	3.40	27.80	32.41	32.36	54	-21.64	AV	Vertical
2390.00	45.64	3.45	27.70	32.49	44.30	74	-29.70	Pk	Vertical
2390.00	34.36	3.45	27.70	32.49	33.02	54	-20.98	AV	Vertical
2390.00	46.28	3.45	27.70	32.49	44.94	74	-29.06	Pk	Horizontal
2390.00	34.62	3.45	27.70	32.49	33.28	54	-20.72	AV	Horizontal
2483.50	47.24	3.48	28.53	32.55	46.70	74	-27.30	Pk	Vertical
2483.50	33.90	3.48	28.53	32.55	33.36	54	-20.64	AV	Vertical
2483.50	46.23	3.48	28.53	32.55	45.69	74	-28.31	Pk	Horizontal
2483.50	33.94	3.48	28.53	32.55	33.40	54	-20.60	AV	Horizontal
2500.00	45.34	3.49	29.20	32.66	45.37	74	-28.63	Pk	Vertical
2500.00	33.80	3.49	29.20	32.66	33.83	54	-20.17	AV	Vertical
2500.00	45.47	3.49	29.20	32.66	45.50	74	-28.50	Pk	Horizontal
2500.00	33.83	3.49	29.20	32.66	33.86	54	-20.14	AV	Horizontal

802.11ax20									
2310.00	46.07	3.40	27.80	32.41	44.86	74	-29.14	Pk	Horizontal
2310.00	33.49	3.40	27.80	32.41	32.28	54	-21.72	AV	Horizontal
2310.00	44.85	3.40	27.80	32.41	43.64	74	-30.36	Pk	Vertical
2310.00	33.67	3.40	27.80	32.41	32.46	54	-21.54	AV	Vertical
2390.00	45.59	3.45	27.70	32.49	44.25	74	-29.75	Pk	Vertical
2390.00	34.62	3.45	27.70	32.49	33.28	54	-20.72	AV	Vertical
2390.00	46.36	3.45	27.70	32.49	45.02	74	-28.98	Pk	Horizontal
2390.00	34.35	3.45	27.70	32.49	33.01	54	-20.99	AV	Horizontal
2483.50	47.16	3.48	28.53	32.55	46.62	74	-27.38	Pk	Vertical
2483.50	34.10	3.48	28.53	32.55	33.56	54	-20.44	AV	Vertical
2483.50	46.39	3.48	28.53	32.55	45.85	74	-28.15	Pk	Horizontal
2483.50	33.95	3.48	28.53	32.55	33.41	54	-20.59	AV	Horizontal
2500.00	45.40	3.49	29.20	32.66	45.43	74	-28.57	Pk	Vertical
2500.00	33.82	3.49	29.20	32.66	33.85	54	-20.15	AV	Vertical
2500.00	45.21	3.49	29.20	32.66	45.24	74	-28.76	Pk	Horizontal
2500.00	33.87	3.49	29.20	32.66	33.90	54	-20.10	AV	Horizontal
802.11ax40									
2310.00	46.14	3.40	27.80	32.41	44.93	74	-29.07	Pk	Horizontal
2310.00	33.36	3.40	27.80	32.41	32.15	54	-21.85	AV	Horizontal
2310.00	44.85	3.40	27.80	32.41	43.64	74	-30.36	Pk	Vertical
2310.00	33.69	3.40	27.80	32.41	32.48	54	-21.52	AV	Vertical
2390.00	45.44	3.45	27.70	32.49	44.10	74	-29.90	Pk	Vertical
2390.00	34.48	3.45	27.70	32.49	33.14	54	-20.86	AV	Vertical
2390.00	46.24	3.45	27.70	32.49	44.90	74	-29.10	Pk	Horizontal
2390.00	34.53	3.45	27.70	32.49	33.19	54	-20.81	AV	Horizontal
2483.50	47.32	3.48	28.53	32.55	46.78	74	-27.22	Pk	Vertical
2483.50	33.88	3.48	28.53	32.55	33.34	54	-20.66	AV	Vertical
2483.50	46.22	3.48	28.53	32.55	45.68	74	-28.32	Pk	Horizontal
2483.50	33.79	3.48	28.53	32.55	33.25	54	-20.75	AV	Horizontal
2500.00	45.41	3.49	29.20	32.66	45.44	74	-28.56	Pk	Vertical
2500.00	33.90	3.49	29.20	32.66	33.93	54	-20.07	AV	Vertical
2500.00	45.36	3.49	29.20	32.66	45.39	74	-28.61	Pk	Horizontal
2500.00	33.67	3.49	29.20	32.66	33.70	54	-20.30	AV	Horizontal

Note:

1. All Readings are Peak Value (VBW=3MHz) and AV Value (VBW=10Hz).
2. Emission Level= Antenna Factor + Cable Loss + Read Level - Preamp Factor.
3. All the modulation modes have been tested, and only the worst results are reflected in the report.

5.3.6 Spurious Emission in Restricted Band 1000MHz-25000MHz

All the modulation modes have been tested, and the worst result was report as below:

Frequency (MHz)	Read Level (dBμV)	Cable loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type	Comment
3260	44.02	3.89	30.04	32.85	45.10	74	-28.90	Pk	Vertical
3260	33.31	3.89	30.04	32.85	34.39	54	-19.61	AV	Vertical
3260	44.19	3.89	30.04	32.85	45.27	74	-28.73	Pk	Horizontal
3260	33.42	3.89	30.04	32.85	34.50	54	-19.50	AV	Horizontal
5332	43.29	5.00	34.03	31.00	51.32	74	-22.68	Pk	Vertical
5332	30.31	5.00	34.03	31.00	38.34	54	-15.66	AV	Vertical
5332	43.18	5.00	34.03	31.00	51.21	74	-22.79	Pk	Horizontal
5332	30.38	5.00	34.03	31.00	38.41	54	-15.59	AV	Horizontal
12500	44.59	8.46	39.30	31.30	61.05	74	-12.95	Pk	Vertical
12500	32.45	8.46	39.30	31.30	48.91	54	-5.09	AV	Vertical
12500	44.61	8.46	39.30	31.30	61.07	74	-12.93	Pk	Horizontal
12500	32.38	8.46	39.30	31.30	48.84	54	-5.16	AV	Horizontal

5.4 Peak Output Power

5.4.1 Limit


FCC Part15 Subpart C			
Section	Test Item	Limit	Frequency Range (MHz)
15.247(b)(3)	Peak output power	1 watt or 30dBm	2400-2483.5

5.4.2 Test Procedure

The maximum peak conducted output power may be measured using a broadband peak RF power meter.

The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall use a fast-responding diode detector.

5.4.3 Test Setup



5.4.4 Test Results

EUT:	Minilaptop	Model Name:	NA105H
Test Mode:	TX Mode	Test Voltage:	DC 7.6V from battery

802.11b

Test Channel	Frequency (MHz)	Maximum Peak Conducted Output Power(dBm)	Limit (dBm)
CH01	2412	7.33	30
CH06	2437	7.13	30
CH11	2462	7.15	30

802.11g

Test Channel	Frequency (MHz)	Maximum Peak Conducted Output Power(dBm)	Limit (dBm)
CH01	2412	8.31	30
CH06	2437	8.36	30
CH11	2462	8.65	30

802.11n20

Test Channel	Frequency (MHz)	Maximum Peak Conducted Output Power(dBm)	Limit (dBm)
CH01	2412	8.18	30
CH06	2437	8.05	30
CH11	2462	8.19	30

802.11n40

Test Channel	Frequency (MHz)	Maximum Peak Conducted Output Power(dBm)	Limit (dBm)
CH03	2422	8.22	30
CH06	2437	8.45	30
CH09	2452	8.39	30

802.11ax20

Test Channel	Frequency (MHz)	Maximum Peak Conducted Output Power(dBm)	Limit (dBm)
CH01	2412	7.66	30
CH06	2437	8.47	30
CH11	2462	7.87	30

802.11ax40

Test Channel	Frequency (MHz)	Maximum Peak Conducted Output Power(dBm)	Limit (dBm)
CH03	2422	8.22	30
CH06	2437	8.53	30
CH09	2452	8.15	30

5.5 Power Spectral Density


5.5.1 Limit

FCC Part15 (15.247) , Subpart C			
Section	Test Item	Limit	Frequency Range (MHz)
15.247	Power Spectral Density	8 dBm (in any 3kHz)	2400-2483.5

5.5.2 Test Procedure


1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to 1.5 times the DTS channel bandwidth.
3. Set the RBW ≥ 3 kHz.
4. Set the VBW $\geq 3 \times$ RBW.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

5.5.3 Test Setup




5.5.4 Test Results


802.11b			
Frequency	Power Density (dBm/3kHz)	Limit (dBm/3kHz)	Result
2412 MHz	-18.90	8	Pass
2437 MHz	-18.83	8	Pass
2462 MHz	-18.84	8	Pass




802.11g			
Frequency	Power Density (dBm/3kHz)	Limit (dBm/3kHz)	Result
2412 MHz	-24.07	8	Pass
2437 MHz	-24.17	8	Pass
2462 MHz	-23.81	8	Pass




802.11n20			
Frequency	Power Density (dBm/3kHz)	Limit (dBm/3kHz)	Result
2412 MHz	-22.94	8	Pass
2437 MHz	-23.17	8	Pass
2462 MHz	-22.75	8	Pass




802.11n40			
Frequency	Power Density (dBm/3kHz)	Limit (dBm/3kHz)	Result
2422 MHz	-26.40	8	Pass
2437 MHz	-26.03	8	Pass
2452 MHz	-26.15	8	Pass



802.11ax20			
Frequency	Power Density (dBm/3kHz)	Limit (dBm/3kHz)	Result
2412 MHz	-26.52	8	Pass
2437 MHz	-25.43	8	Pass
2462 MHz	-25.96	8	Pass



802.11ax40			
Frequency	Power Density (dBm/3kHz)	Limit (dBm/3kHz)	Result
2422 MHz	-28.30	8	Pass
2437 MHz	-28.14	8	Pass
2452 MHz	-28.32	8	Pass



5.6 6dB Bandwidth


5.6.1 Limit

FCC Part15 (15.247) , Subpart C			
Section	Test Item	Limit	Frequency Range (MHz)
15.247(a)(2)	Bandwidth	$\geq 500\text{kHz}$ (6dB bandwidth)	2400-2483.5

5.6.2 Test Procedure

1. Set RBW= 100 kHz.
2. Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

5.6.3 Test Setup




5.6.4 Test Results

EUT:	Minilaptop	Model Name:	NA105H
Pressure:	1012 hPa	Test Voltage:	DC 7.6V from battery
Test Mode:	TX b Mode /CH01, CH06, CH11		

Channel	Frequency (MHz)	6dB bandwidth (MHz)	Limit (kHz)	Result
CH01	2412	10.112	500	Pass
CH06	2437	10.084	500	Pass
CH11	2462	10.128	500	Pass

Test plots




EUT:	Minilaptop	Model Name:	NA105H
Pressure:	1012 hPa	Test Voltage:	DC 7.6V from battery
Test Mode:	TX g Mode /CH01, CH06, CH11		


Channel	Frequency (MHz)	6dB bandwidth (MHz)	Limit (kHz)	Result
CH01	2412	13.48	500	Pass
CH06	2437	13.58	500	Pass
CH11	2462	13.568	500	Pass

Test plots


TX CH 01



TX CH 06



TX CH 11




/

/

EUT:	Minilaptop	Model Name:	NA105H
Pressure:	1012 hPa	Test Voltage:	DC 7.6V from battery
Test Mode:	TX n20 Mode /CH01, CH06, CH11		

Channel	Frequency (MHz)	6dB bandwidth (MHz)	Limit (kHz)	Result
CH01	2412	16.184	500	Pass
CH06	2437	16.592	500	Pass
CH11	2462	16.024	500	Pass


Test plots



EUT:	Minilaptop	Model Name:	NA105H
Pressure:	1012 hPa	Test Voltage:	DC 7.6V from battery
Test Mode:	TX n40 Mode /CH03, CH06, CH09		

Channel	Frequency (MHz)	6dB bandwidth (MHz)	Limit (kHz)	Result
CH03	2422	30.968	500	Pass
CH06	2437	31.216	500	Pass
CH09	2452	31.072	500	Pass


Test plots



EUT:	Minilaptop	Model Name:	NA105H
Pressure:	1012 hPa	Test Voltage:	DC 7.6V from battery
Test Mode:	TX ax20 Mode /CH01, CH06, CH11		

Channel	Frequency (MHz)	6dB bandwidth (MHz)	Limit (kHz)	Result
CH01	2412	19.092	500	Pass
CH06	2437	19.128	500	Pass
CH11	2462	19.056	500	Pass


Test plots



EUT:	Minilaptop	Model Name:	NA105H
Pressure:	1012 hPa	Test Voltage:	DC 7.6V from battery
Test Mode:	TX ax40 Mode /CH03, CH06, CH09		

Channel	Frequency (MHz)	6dB bandwidth (MHz)	Limit (kHz)	Result
CH03	2422	37.824	500	Pass
CH06	2437	37.92	500	Pass
CH09	2452	38.104	500	Pass

Test plots



5.7 Duty Cycle

5.7.1 Limit

No limit requirement.

5.7.2 Test Procedure

The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the on and off times of the transmitted signal. Set the center frequency of the instrument to the center frequency of the transmission. Set $RBW \geq OBW$ if possible; otherwise, set RBW to the largest available value. Set $VBW \geq RBW$. Set detector = peak or average. The zero-span measurement method shall not be used unless both RBW and VBW are $> 50/T$ and the number of sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring duty cycle shall not be used if $T \leq 16.7$ microseconds.)

The transmitter output is connected to the Spectrum Analyzer. We tested according to the zero-span measurement method, 6.0(b) in KDB 558074 D01 DTS Meas Guidance v05r02.

The largest available value of RBW is 8 MHz and VBW is 50 MHz. The zero-span method of measuring duty cycle shall not be used if $T \leq 6.25$ microseconds. ($50/6.25 = 8$)

The zero-span method was used because all measured T data are > 6.25 microseconds and both RBW and VBW are $> 50/T$.

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.

The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously.

The EUT was operating in controlled its channel.

Use the following spectrum analyzer settings:

Span = Zero Span

RBW = 10MHz (the largest available value)

VBW = 10MHz ($\geq$ RBW)

Number of points in Sweep > 100


Detector function = peak

Trace = Clear write

Measure Total and Ton

Calculate Duty Cycle = $Ton / Total$

5.7.3 Test Setup



5.7.4 Test Results

EUT:	Minilaptop	Model Name:	NA105H
Pressure:	1012 hPa	Test Voltage:	DC 7.6V from battery
Test Mode:	TX b/g/n(20/40) Mode / CH06		

Mode	Data rate	Frequency (MHz)	T _{on} (ms)	T _{total} (ms)	Duty Cycle (%)	Correction Factor (dB)	1/T (kHz)
b	11 Mbps	2412	12.192	12.208	99.87	0	0.08
b	11 Mbps	2437	12.194	12.208	99.89	0	0.08
b	11 Mbps	2462	12.194	12.210	99.87	0	0.08
g	54 Mbps	2412	2.024	2.526	80.13	0.96	0.49
g	54 Mbps	2437	2.024	2.526	80.13	0.96	0.49
g	54 Mbps	2462	2.024	2.526	80.13	0.96	0.49
n20	MCS15	2412	1.888	2.390	79	1.02	0.53
n20	MCS15	2437	1.888	2.390	79	1.02	0.53
n20	MCS15	2462	1.888	2.390	79	1.02	0.53
n40	MCS15	2422	0.928	1.012	64.9	1.88	1.08
n40	MCS15	2437	0.928	1.430	64.9	1.88	1.08
n40	MCS15	2452	0.928	1.430	64.9	1.88	1.08
ax20	MCS15	2412	3.862	4.152	96.07	0.17	0.26
ax20	MCS15	2437	3.862	4.016	96.17	0.17	0.26
ax20	MCS15	2462	3.862	4.016	96.17	0.17	0.26
ax40	MCS15	2422	1.958	2.134	91.75	0.37	0.51
ax40	MCS15	2437	1.956	2.182	89.64	0.47	0.51
ax40	MCS15	2452	1.958	2.054	95.33	0.21	0.51

Note:

1. Duty Cycle = T_{on} / T_{total}
2. Correction Factor = $10 \log (1 / \text{Duty Cycle})$
3. $1 / T = 1 / T_{on}$



