



Solutions

**FCC 47 CFR PART 15 SUBPART C
ISED RSS-247 ISSUE 3**

TEST REPORT

For

Constant Current LED Driver

MODEL NUMBER: SIF85-I1800/120-347/T/D1/F/APP D

**SERIES MODEL NUMBER: SIF30-I0420/120-347/T/D1/F/APP D,
SIF50-I0900/120-347/T/D1/F/APP D**

PROJECT NUMBER: 4791781639

REPORT NUMBER: 4791781639-1

FCC ID: 2BB69-HTWT004

IC: 33920-HTWT004

ISSUE DATE: Jul. 16, 2025

Prepared for

**FCC: JIANGSU EVER-TIE LIGHTING INC
IC: EVERTIELIGHTING**

Prepared by

**UL-CCIC COMPANY LIMITED
No. 2, Chengwan Road, Suzhou Industrial Park, Suzhou 215122, China
Tel: +86 512-6808 6400
Fax: +86 512-6808 4099
Website: www.ul.com**

Revision History

Rev.	Issue Date	Revisions	Revised By
V0	07/16/2025	Initial Issue	

TABLE OF CONTENTS

1. ATTESTATION OF TEST RESULTS.....	4
2. TEST METHODOLOGY	6
3. FACILITIES AND ACCREDITATION.....	6
4. CALIBRATION AND UNCERTAINTY	7
4.1. <i>MEASURING INSTRUMENT CALIBRATION</i>	7
4.2. <i>MEASUREMENT UNCERTAINTY</i>	7
5. EQUIPMENT UNDER TEST	8
5.1. <i>DESCRIPTION OF EUT.....</i>	8
5.2. <i>MAXIMUM OUTPUT POWER.....</i>	9
5.3. <i>CHANNEL LIST.....</i>	9
5.4. <i>TEST CHANNEL CONFIGURATION.....</i>	9
5.5. <i>THE WORSE CASE POWER SETTING PARAMETER.....</i>	9
5.6. <i>DESCRIPTION OF AVAILABLE ANTENNAS</i>	10
5.7. <i>THE WORSE CASE CONFIGURATIONS.....</i>	10
5.8. <i>TEST ENVIRONMENT</i>	10
5.9. <i>DESCRIPTION OF TEST SETUP</i>	11
5.10. <i>MEASURING INSTRUMENT AND SOFTWARE USED</i>	13
6. MEASUREMENT METHODS.....	14
7. ANTENNA PORT TEST RESULTS	15
7.1. <i>ON TIME AND DUTY CYCLE</i>	15
7.2. <i>6 dB BANDWIDTH AND 99% OCCUPIED BANDWIDTH.....</i>	17
7.3. <i>CONDUCTED OUTPUT POWER</i>	25
7.4. <i>POWER SPECTRAL DENSITY</i>	27
7.5. <i>CONDUCTED BANDEDGE AND SPURIOUS EMISSIONS</i>	32
8. RADIATED TEST RESULTS	47
8.1. <i>LIMITS AND PROCEDURE</i>	47
8.2. <i>TEST ENVIRONMENT</i>	54
8.3. <i>RESTRICTED BANDEDGE</i>	54
8.4. <i>SPURIOUS EMISSIONS.....</i>	63
9. AC POWER LINE CONDUCTED EMISSIONS.....	95
10. ANTENNA REQUIREMENTS	98

1. ATTESTATION OF TEST RESULTS

Applicant Information

Company Name: FCC: JIANGSU EVER-TIE LIGHTING INC
IC: EVERTIELIGHTING
Address: FCC: No 18, East Fuxing Rd, NETDA Nantong, Jiangsu 226015
China
IC: No 18, East Fuxing Rd Nantong, Jiangsu 226015 China

EUT Description

Product Name: Constant Current LED Driver
Model Name: SIF85-I1800/120-347/T/D1/F/APP D
Series Model Name: SIF30-I0420/120-347/T/D1/F/APP D,
SIF50-I0900/120-347/T/D1/F/APP D
Model Difference: The three models are identical except the sampling resistors of
the power supply.
Sample Number: 8485434-S001
Data of Receipt Sample: May. 21, 2025
Test Date: May. 21, 2025~ Jue. 26, 2025

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
CFR 47 Part 15 Subpart C	
ISED RSS-247 Issue 3	PASS
ISED RSS-GEN Issue 5	

Summary of Test Results			
Clause	Test Items	FCC&ISED Rules	Test Results
1	6 dB Bandwidth and 99% Occupied Bandwidth	FCC 15.247 (a) (2) RSS-247 Clause 5.2 (a) RSS-Gen Clause 6.7	PASS
2	Conducted Power	FCC 15.247 (b) (3) RSS-247 Clause 5.4 (d) RSS-Gen Clause 6.12	PASS
3	Power Spectral Density	FCC 15.247 (e) RSS-247 Clause 5.2 (b)	PASS
4	Conducted Band edge And Spurious emission	FCC 15.247 (d) RSS-247 Clause 5.5 RSS-GEN Clause 6.13	PASS
5	Radiated Band edges and Spurious emission	FCC 15.247 (d) FCC 15.209 FCC 15.205 RSS-247 Clause 5.5 RSS-GEN Clause 6.13 RSS-GEN Clause 8.9 RSS-GEN Clause 8.10	PASS
6	Conducted Emission Test for AC Power Port	FCC 15.207 RSS-GEN Clause 8.8	PASS
7	Antenna Requirement	FCC 15.203 RSS-GEN Clause 6.8	PASS

Note:
The measurement result for the sample received is < Pass > according to < ANSI C63.10-2013, FCC 47 CFR Part 2, FCC 47 CFR Part 15C, ISED RSS-247, ISED RSS-Gen > when < Simple Acceptance > decision rule is applied.

Prepared By:

Tom Tang

Tom Tang

Reviewed By:

Emily Wang

Emily Wang

Authorized By:

Kevin Shen

Kevin Shen

2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with KDB 558074 D01 15.247 Meas Guidance v05r02, 414788 D01 Radiated Test Site v01r01, FCC 47 CFR Part 2, FCC 47 CFR Part 15, ANSI C63.10-2013, ISED RSS-247 Issue 3 and ISED RSS-GEN Issue 5.

3. FACILITIES AND ACCREDITATION

Accreditation Certificate	<p>A2LA (Certificate No.: 4829.01) UL-CCIC COMPANY LIMITED has been assessed and proved to be in compliance with A2LA.</p> <p>FCC (FCC Designation No.: CN1247) UL-CCIC COMPANY LIMITED has been recognized to perform compliance testing on equipment subject to the Commission's Declaration of Conformity (DoC) and Certification rules.</p> <p>IC (IC Designation No.: 25056; CAB No.: CN0073) UL-CCIC COMPANY LIMITED has been recognized to perform compliance testing on equipment subject to the Commission's Declaration of Conformity (DoC) and Certification rules.</p>
---------------------------	--

Note 1: All tests measurement facilities use to collect the measurement data are located at No. 2, Chengwan Road, Suzhou Industrial Park, Suzhou 215122, China

Note 2: For below 30MHz, lab had performed measurements at test anechoic chamber and comparing to measurements obtained on an open field site. These measurements below 30MHz had been correlated to measurements performed on an OFS.

Note 3: The test anechoic chamber in UL-CCIC COMPANY LIMITED had been calibrated and compared to the open field sites and the test anechoic chamber is shown to be equivalent to or worst case from the open field site.

4. CALIBRATION AND UNCERTAINTY

4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations and is traceable to recognized national standards.

4.2. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Test Item	Uncertainty
Conduction emission	3.1dB
DTS Bandwidth	1.9%
Maximum Conducted Output Power	1.3dB
Maximum Power Spectral Density Level	1.5dB
Band-edge Compliance	1.9%
Unwanted Emissions in Non-restricted Freq Bands	9kHz-30MHz: ± 0.90 dB 30MHz-1GHz: ± 1.5 dB 1GHz-12.75GHz: ± 1.9 dB 12.75GHz-26.5GHz: ± 2.1 dB
Radiation Emission test (include Fundamental emission) (9kHz-30MHz)	3.4dB
Radiation Emission test (include Fundamental emission) (30MHz-1GHz)	3.4dB
Radiation Emission test (1GHz to 26GHz) (include Fundamental emission)	3.5dB (1GHz-18GHz) 3.9dB (18GHz-26.5GHz)
Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.	

5. EQUIPMENT UNDER TEST

5.1. DESCRIPTION OF EUT

Equipment:	Constant Current LED Driver	
Model Name:	SIF85-I1800/120-347/T/D1/F/APP D	
Technology:	Bluetooth - Low Energy	
Transmit Frequency Range:	2402 MHz ~ 2480 MHz	
Modulation:	GFSK	
Data Rate:	LE 1M	1 Mbps
	LE 2M	2 Mbps
Test Software of EUT:	EMI_TEST (manufacturer declare)	
Antenna Type:	Rod Antenna	
Antenna Gain:	1.66 dBi	
	Note 1: The product has only one transmission chain and four antennas are provided. Note 2: This data is provided by customer and our lab isn't responsible for this data.	

5.2. MAXIMUM OUTPUT POWER

Bluetooth Mode	Frequency (MHz)	Channel Number	Max Output Power(dBm)
BLE 1M	2402-2480	0-39[40]	-0.08
BLE 2M	2402-2480	0-39[40]	-0.24

5.3. CHANNEL LIST

Channel	Frequency (MHz)						
0	2402	11	2424	22	2446	33	2468
1	2404	12	2426	23	2448	34	2470
2	2406	13	2428	24	2450	35	2472
3	2408	14	2430	25	2452	36	2474
4	2410	15	2432	26	2454	37	2476
5	2412	16	2434	27	2456	38	2478
6	2414	17	2436	28	2458	39	2480
7	2416	18	2438	29	2460	/	/
8	2418	19	2440	30	2462	/	/
9	2420	20	2442	31	2464	/	/
10	2422	21	2444	32	2468	/	/

5.4. TEST CHANNEL CONFIGURATION

Test Mode	Test Channel		Frequency
GFSK	Low Channel	CH 0	2402MHz
	Middle Channel	CH 19	2440MHz
	High Channel	CH 39	2480MHz

5.5. THE WORSE CASE POWER SETTING PARAMETER

The Worse Case Power Setting Parameter under 2400 ~ 2483.5MHz Band				
Test Software		EMI_TEST		
Modulation Type	Transmit Antenna Number	Test Channel		
		LCH	MCH	HCH
GFSK	1	default	default	default

5.6. DESCRIPTION OF AVAILABLE ANTENNAS

Ant.	Frequency (MHz)	Model	Antenna Type	Antenna Gain (dBi)
1	2400-2483.5	IPEX-GB-P6N-370	Rod Antenna	1.66

Note: This data is provided by customer and our lab isn't responsible for this data.

Test Mode	Transmit and Receive Mode	Description
BLE 1M	<input checked="" type="checkbox"/> 1TX, 1RX	Antenna1 can be used as transmitting/receiving antenna independently.
BLE 2M	<input checked="" type="checkbox"/> 1TX, 1RX	Antenna1 can be used as transmitting/receiving antenna independently.

5.7. THE WORSE CASE CONFIGURATIONS

For BLE module, the product only supports 1 Mbps and 2 Mbps, both the two data rate were tested and the test result was recorded in this report.

5.8. TEST ENVIRONMENT

Environment Parameter	Selected Values During Tests	
Relative Humidity	55 ~ 65%	
Atmospheric Pressure:	101kPa	
Temperature	TN	23 ~ 28°C
Voltage:	VL	N/A
	VN	AC 120V
	VH	N/A

Note: VL= Lower Extreme Test Voltage

VN= Nominal Voltage

VH= Upper Extreme Test Voltage

TN= Normal Temperature

5.9. DESCRIPTION OF TEST SETUP

SUPPORT EQUIPMENT

Item	Equipment	Brand Name	Model Name	Description
1	Laptop	ThinkPad	E590	/

I/O PORT


Cable No	Port	Connector Type	Cable Type	Cable Length(m)	Remarks
1	USB	USB-TTL	USB	100cm Length	/

ACCESSORY

Item	Accessory	Brand Name	Model Name	Description
1	/	/	/	/

TEST SETUP

The EUT can work in an engineer mode with a software through a laptop.

SETUP DIAGRAM FOR TESTS

5.10. MEASURING INSTRUMENT AND SOFTWARE USED

Conducted Emissions Test (Instrument)							
Used	Equipment	Manufacturer	Model No.	Serial No.	Upper Last Cal.	Last Cal.	Next Cal.
<input checked="" type="checkbox"/>	EMI Test Receiver	R&S	ESR3	126700	2023-11-25	2024-11-02	2025-11-01
<input checked="" type="checkbox"/>	Two-Line V-Network	R&S	ENV216	126701	2023-11-25	2024-11-02	2025-11-01
Conducted Emissions Test (Software)							
Used	Description		Manufacturer	Name		Version	
<input checked="" type="checkbox"/>	Software for Conducted Emissions Test		R&S	EMC32		9.25.00	
Radiated Emissions Test (Instrument)							
Used	Equipment	Manufacturer	Model No.	Serial No.	Upper Last Cal.	Last Cal.	Next Cal.
<input checked="" type="checkbox"/>	EMI test receiver	R&S	ESR7	222993	2024-03-23	2025-03-15	2026-03-14
<input checked="" type="checkbox"/>	EMI test receiver	R&S	ESR26	126703	2023-11-25	2024-11-02	2025-11-01
<input checked="" type="checkbox"/>	Spectrum Analyzer	R&S	FSV3044	222992	2024-03-23	2025-03-15	2026-03-14
<input checked="" type="checkbox"/>	Receiver Antenna (9kHz-30MHz)	Schwarzbeck	FMZB 1513	155456	2021-06-03	2024-05-27	2027-05-26
<input checked="" type="checkbox"/>	Receiver Antenna (30MHz-1GHz)	Schwarzbeck	VULB 9168	171952	2021-07-05	2024-07-04	2027-07-03
<input checked="" type="checkbox"/>	Receiver Antenna (1GHz-18GHz)	R&S	HF907	126705	2022-02-28	2025-02-17	2028-02-16
<input checked="" type="checkbox"/>	Receiver Antenna (18GHz-26.5GHz)	Schwarzbeck	BBHA9170	126706	2022-02-28	2025-02-17	2028-02-16
<input checked="" type="checkbox"/>	Pre-amplification (To 18GHz)	Tonscned	TAP01018050	224539	2023-10-10	2024-10-10	2025-10-09
<input checked="" type="checkbox"/>	Pre-amplification (To 18GHz)	R&S	SCU-18D	134667	2023-11-25	2024-11-02	2025-11-01
<input checked="" type="checkbox"/>	Pre-amplification (To 26.5GHz)	R&S	SCU-26D	135391	2023-11-25	2024-11-02	2025-11-01
<input checked="" type="checkbox"/>	Band Reject Filter	Wainwright	WRCGV12-2375-2400-2485-2510-40SS	1	2023-12-18	2024-11-02	2025-11-01
<input checked="" type="checkbox"/>	High Pass Filter	COM-MW	ZBF13-3-18G-01	2	2023-12-18	2024-11-02	2025-11-01
Radiated Emissions Test (Software)							
Used	Description		Manufacturer	Name		Version	
<input checked="" type="checkbox"/>	Software for Radiated Emissions Test		Tonscend	JS32-RE		5.0.0.2	
Antenna Port Test (Instrument)							
Used	Equipment	Manufacturer	Model No.	Serial No.	Upper Last Cal.	Last Cal.	Next Cal.
<input checked="" type="checkbox"/>	Spectrum Analyzer	Keysight	N9010B	155368	2024-03-23	2025-03-15	2026-03-14
<input checked="" type="checkbox"/>	Power Meter	MWT	MW100-RFCB	221694	2024-03-23	2025-03-15	2026-03-14
<input checked="" type="checkbox"/>	Power Meter	Anritsu	MA24406A	12896	2024-03-23	2025-03-15	2026-03-14
<input checked="" type="checkbox"/>	Attenuator	PASTERNACK	PE7087-6	1624	/	2024-11-04	2025-11-03
Antenna Port Test (Software)							
Used	Description		Manufacturer	Name		Version	
<input checked="" type="checkbox"/>	Software for Antenna Port Test		Tonscend	JS1120-3 Test System		V3.2.22	

6. MEASUREMENT METHODS

No.	Test Item	KDB Name	Section
1	6 dB Bandwidth and 99% Occupied Bandwidth	KDB 558074 D01 15.247 Meas Guidance v05r02	8.2
2	Output Power	KDB 558074 D01 15.247 Meas Guidance v05r02	8.3.2.3 (11.9.1.3 Method PKPM of ANSI C63.10)
3	Power Spectral Density	KDB 558074 D01 15.247 Meas Guidance v05r02	8.4 (11.10.2 Method PKPSD of ANSI C63.10)
4	Out-of-band emissions in non-restricted bands	KDB 558074 D01 15.247 Meas Guidance v05r02	8.5
5	Out-of-band emissions in restricted bands	KDB 558074 D01 15.247 Meas Guidance v05r02	8.6
6	Band-edge	KDB 558074 D01 15.247 Meas Guidance v05r02	8.7
7	Conducted Emission Test for AC Power Port	ANSI C63.10-2013	6.2

7. ANTENNA PORT TEST RESULTS

7.1. ON TIME AND DUTY CYCLE


LIMITS

None; for reporting purposes only

PROCEDURE

FCC KDB 558074 Zero-Span Spectrum Analyzer Method

TEST SETUP



TEST ENVIRONMENT

Temperature	22°C	Relative Humidity	56%
Atmosphere Pressure	101kPa	Test Voltage	AC 120V

TEST RESULTS TABLE


Mode	On Time (msec)	Period (msec)	Duty Cycle x (Linear)	Duty Cycle (%)	Duty Cycle Correction Factor (db)	1/T Minimum VBW (kHz)	Final VBW (kHz)
BLE 1M	100	100	1	100%	0	0.01	0.01
BLE 2M	100	100	1	100%	0	0.01	0.01

Note: 1) Duty Cycle Correction Factor=10log(1/x).

2) Where: x is Duty Cycle (Linear)

3) Where: T is On Time (transmit duration)

TEST GRAPHS
BLE 1M ON TIME AND DUTY CYCLE MID CHANNEL

BLE 2M ON TIME AND DUTY CYCLE MID CHANNEL


7.2. 6 dB BANDWIDTH AND 99% OCCUPIED BANDWIDTH

LIMITS

FCC Part15 (15.247), Subpart C			
Section	Test Item	Limit	Frequency Range (MHz)
FCC 47 CFR 15.247(a)(2) ISED RSS-247 5.2 (a)	6dB Bandwidth	$\geq 500\text{kHz}$	2400-2483.5
ISED RSS-Gen Clause 6.7	99% Occupied Bandwidth	For reporting purposes only	2400-2483.5

TEST PROCEDURE


Refer to ANSI C63.10-2013 clause 11.8 for DTS bandwidth and clause 6.9 for Occupied Bandwidth.

Connect the EUT to the spectrum analyser and use the following settings:

Center Frequency	The centre frequency of the channel under test
Frequency Span	Peak
Detector	For 6 dB Bandwidth: 100 kHz For 99% Occupied Bandwidth: 1% to 5% of the occupied bandwidth
RBW	For 6 dB Bandwidth: $\geq 3 \times \text{RBW}$ For 99% Occupied Bandwidth: $\geq 3 \times \text{RBW}$
VBW	Max hold
Trace	Max hold
Sweep	Auto couple

- Use the 99% power bandwidth function of the instrument, allow the trace to stabilize and report the measured bandwidth.
- Allow the trace to stabilize and measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

TEST SETUP



TEST ENVIRONMENT

Temperature	22°C	Relative Humidity	56%
Atmosphere Pressure	101kPa	Test Voltage	AC 120V

TEST RESULTS TABLE


Test Mode	Test Channel	6dB bandwidth (MHz)	99% bandwidth (MHz)	Result
BLE 1M	LCH	0.680	1.0347	Pass
	MCH	0.676	1.0327	Pass
	HCH	0.680	1.0197	Pass
BLE 2M	LCH	1.372	2.0456	Pass
	MCH	1.400	2.0558	Pass
	HCH	1.360	2.0265	Pass



TEST GRAPHS

6dB Bandwidth

Test Mode	Test Channel	Verdict
BLE 1M	LCH	PASS
		

Test Mode	Test Channel	Verdict
BLE 1M	MCH	PASS
		







99% Bandwidth

Test Mode	Test Channel	Verdict
BLE 1M	LCH	PASS
		

Test Mode	Test Channel	Verdict
BLE 1M	MCH	PASS
		

Test Mode	Test Channel	Verdict
BLE 1M	HCH	
 <p>KEYSIGHT Input RF Coupling: DC RL → Align: Auto</p> <p>Input Z: 50 Ω Corrections: Off Preamp: Off Trig: Free Run Center Freq: 2.48000000 GHz Freq Ref: int (S) Attenu: 30 dB Gate: Off Avg/Hold: 200/200 #IF Gain: Low Radio Siz: None</p> <p>1 Graph</p> <p>Ref Lvl Offset: 8.23 dB Ref Value: 20.00 dBm</p> <p>Mkr1: 2.4799 GHz -2.61 dBm</p> <p>Scale/Div: 10.0 dB</p> <p>Log</p> <p>10.0 8.00 6.00 4.00 2.00 0.00 -2.00 -4.00 -6.00 -8.00 -10.00 -12.00 -14.00 -16.00 -18.00 -20.00 -22.00 -24.00 -26.00 -28.00 -30.00 -32.00 -34.00 -36.00 -38.00 -40.00 -42.00 -44.00 -46.00 -48.00 -50.00 -52.00 -54.00 -56.00 -58.00 -60.00 -62.00 -64.00 -66.00 -68.00 -70.00</p> <p>Center: 2.46 GHz #Video BW: 130.0 kHz Span: 4 MHz #Res BW: 43.000 kHz Sweep Time: 6.60 ms (1001 pts)</p> <p>2 Metrics</p> <p>Occupied Bandwidth: 1.0197 MHz Total Power: 6.97 dBm</p> <p>Transmit Freq Error: -42.070 kHz % of OBW Power: 99.00 %</p> <p>x dB Bandwidth: 1.288 MHz x dB: -26.00 dB</p>	 <p>Frequency</p> <p>Center Frequency: 2.48000000 GHz</p> <p>Span: 4.0000 MHz</p> <p>CF Step: 400.000 kHz</p> <p>Auto</p> <p>Man</p> <p>Freq Offset: 0 Hz</p> <p>Pass</p> <p>Jun 03, 2025 8:42:06 PM</p>	

Test Mode	Test Channel	Verdict
BLE 2M	LCH	
 <p>KEYSIGHT Input RF Coupling: DC RL → Align: Auto</p> <p>Input Z: 50 Ω Corrections: Off Preamp: Off Trig: Free Run</p> <p>Freq Ref. Int (S) Gate: Off #IF Gain: Low Avg/Hold: 200/200 Radio Std: None</p> <p>Center Frequency: 2.40200000 GHz</p> <p>Span: 4.0000 MHz</p> <p>CF Step: 400.00 kHz</p> <p>Auto / Man</p> <p>Freq Offset: 0 Hz</p> <p>Ref Lvl Offset: 8.15 dB Ref Value: 20.00 dBm</p> <p>Mkr1: 2.4020 GHz -4.64 dBm</p> <p>1 Graph</p> <p>Log</p> <p>10.0</p> <p>0.0</p> <p>-10.0</p> <p>-20.0</p> <p>-30.0</p> <p>-40.0</p> <p>-50.0</p> <p>-60.0</p> <p>-70.0</p> <p>Center 2.402 GHz</p> <p>#Video BW 130.00 kHz</p> <p>Span 4 MHz</p> <p>#Res BW 43.000 kHz</p> <p>Sweep Time 6.60 ms (1001 pts)</p> <p>2 Metrics</p> <p>Occupied Bandwidth: 2.0456 MHz</p> <p>Transmit Freq Error: -44.640 kHz</p> <p>x dB Bandwidth: 2.566 MHz</p> <p>Total Power: 7.21 dBm</p> <p>% of OSB Power: 99.00 %</p> <p>x dB: -26.00 dB</p>	PASS	

Test Mode	Test Channel	Verdict												
BLE 2M	MCH	PASS												
 <p>Test Mode: BLE 2M Test Channel: MCH Verdict: PASS</p> <p>Spectrum Analyzer 1 KEYSIGHT Input RF: Agilent, DC Input Z: 50 Ω, Attenu: 30 dB, Trig: Free Run, Center Freq: 2.440000000 GHz, Avg/Hold: 200/200, Ref/Gain: Low, Regin: Std. None RL: Align: Auto, Freq Ref: int (S)</p> <p>1 Graph Ref Lvl Offset 8.23 dB, Ref Value 20.00 dBm, Scale/Div 10.0 dB, Mkr1 2.4401 GHz, -3.31 dBm</p> <p>Log, Center 2.44 GHz, #Video BW 130.00 kHz, Span 4 MHz, Sweep Time 6.60 ms (1001 pts), #Res BW 43.000 kHz</p> <p>2 Metrics</p> <table border="1"> <tr> <td>Occupied Bandwidth</td> <td>2.0558 MHz</td> <td>Total Power</td> <td>7.29 dBm</td> </tr> <tr> <td>Transmit Freq Error</td> <td>-41.692 kHz</td> <td>% of OBW Power</td> <td>99.00 %</td> </tr> <tr> <td>dB Bandwidth</td> <td>2.523 MHz</td> <td>dB</td> <td>-26.00 dB</td> </tr> </table> <p>Jun 03, 2025 8:51:10 PM</p>			Occupied Bandwidth	2.0558 MHz	Total Power	7.29 dBm	Transmit Freq Error	-41.692 kHz	% of OBW Power	99.00 %	dB Bandwidth	2.523 MHz	dB	-26.00 dB
Occupied Bandwidth	2.0558 MHz	Total Power	7.29 dBm											
Transmit Freq Error	-41.692 kHz	% of OBW Power	99.00 %											
dB Bandwidth	2.523 MHz	dB	-26.00 dB											

Test Mode	Test Channel	Verdict												
BLE 2M	HCH	PASS												
 <p>Test Mode: BLE 2M Test Channel: HCH Verdict: PASS</p> <p>Spectrum Analyzer 1 KEYSIGHT Input RF: Agilent, DC Input Z: 50 Ω, Attenu: 30 dB, Trig: Free Run, Center Freq: 2.480000000 GHz, Avg/Hold: 200/200, Ref/Gain: Low, Regin: Std. None RL: Align: Auto, Freq Ref: int (S)</p> <p>1 Graph Ref Lvl Offset 8.23 dB, Ref Value 20.00 dBm, Scale/Div 10.0 dB, Mkr1 2.4799 GHz, -4.30 dBm</p> <p>Log, Center 2.48 GHz, #Video BW 130.00 kHz, Span 4 MHz, Sweep Time 6.60 ms (1001 pts), #Res BW 43.000 kHz</p> <p>2 Metrics</p> <table border="1"> <tr> <td>Occupied Bandwidth</td> <td>2.0265 MHz</td> <td>Total Power</td> <td>7.34 dBm</td> </tr> <tr> <td>Transmit Freq Error</td> <td>-38.101 kHz</td> <td>% of OBW Power</td> <td>99.00 %</td> </tr> <tr> <td>dB Bandwidth</td> <td>2.577 MHz</td> <td>dB</td> <td>-26.00 dB</td> </tr> </table> <p>Jun 03, 2025 8:55:34 PM</p>			Occupied Bandwidth	2.0265 MHz	Total Power	7.34 dBm	Transmit Freq Error	-38.101 kHz	% of OBW Power	99.00 %	dB Bandwidth	2.577 MHz	dB	-26.00 dB
Occupied Bandwidth	2.0265 MHz	Total Power	7.34 dBm											
Transmit Freq Error	-38.101 kHz	% of OBW Power	99.00 %											
dB Bandwidth	2.577 MHz	dB	-26.00 dB											

7.3. CONDUCTED OUTPUT POWER

LIMITS

FCC Part15 (15.247), Subpart C			
Section	Test Item	Limit	Frequency Range (MHz)
FCC 15.247(b)(3) ISED RSS-247 5.4 (d) RSS-Gen Clause 6.12	Output Power	1 watt or 30dBm	2400-2483.5


TEST PROCEDURE

Place the EUT on the table and set it in the transmitting mode.
 Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the Power sensor.
 Measure the power of each channel.
 PK Detector used for PK result.

TEST ENVIRONMENT

Temperature	22°C	Relative Humidity	56%
Atmosphere Pressure	101kPa	Test Voltage	AC 120V

TEST SETUP



TEST RESULTS TABLE

Test Mode	Test Channel	Maximum Conducted Output Power (PK)		LIMIT
		dBm	dBm	
BLE 1M	LCH	-0.08		30
	MCH	-0.15		30
	HCH	-0.27		30
BLE 2M	LCH	-0.24		30
	MCH	-0.28		30
	HCH	-0.34		30

7.4. POWER SPECTRAL DENSITY

LIMITS

FCC Part15 (15.247), Subpart C			
Section	Test Item	Limit	Frequency Range (MHz)
FCC §15.247 (e) ISED RSS-247 5.2 (b)	Power Spectral Density	8 dBm/3 kHz	2400-2483.5

TEST PROCEDURE

Refer to FCC KDB 558074, connect the UUT to the spectrum analyser and use the following settings:

Center Frequency	The centre frequency of the channel under test
Detector	Peak
RBW	$3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$
VBW	$\geq 3 \times \text{RBW}$
Span	$1.5 \times \text{DTS bandwidth}$
Trace	Max hold
Sweep time	Auto couple.


Allow trace to fully stabilize and use the peak marker function to determine the maximum amplitude level within the RBW.

If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

TEST ENVIRONMENT


Temperature	22°C	Relative Humidity	56%
Atmosphere Pressure	101kPa	Test Voltage	AC 120V

TEST SETUP



TEST RESULTS TABLE

Test Mode	Test Channel	Maximum Peak power spectral density (dBm/30kHz)	Result
BLE 1M	LCH	-2.67	Pass
	MCH	-2.82	Pass
	HCH	-2.44	Pass
BLE 1M	LCH	-4.15	Pass
	MCH	-3.65	Pass
	HCH	-3.92	Pass

TEST GRAPHS


Test Mode	Test Channel	Verdict
BLE 1M	MCH	PASS
		

Test Mode	Test Channel	Verdict
BLE 1M	HCH	PASS
		

Test Mode	Test Channel	Verdict
BLE 2M	LCH	PASS
 <p>The screenshot shows a Keysight Spectrum Analyzer interface. The main display shows a spectrum with a single peak labeled 'Mkr1 2.402 065 9 GHz -4.15 dBm'. The center frequency is set to 2.402000 GHz, and the span is 2.058 MHz. The x-axis scale is logarithmic (Log). The measurement parameters are: Input RF: 2.402000 GHz, #Aver: 20 dB, PWD: Best Wide, Date: Off, IF Gain: Low, Sig Track: Off, Ref Lvl: 10.00 dBm, Ref Lvl Offset: 8.15 dB, Scale/Div: 10 dB, #Video BW: 100 kHz, #Res BW: 30 kHz, Sweep: 2.20 ms (1001 pts). The right panel displays various settings such as Center Frequency, Span, Auto Tune, and X Axis Scale.</p>		

Test Mode	Test Channel	Verdict
BLE 2M	MCH	PASS
 <p>The screenshot shows a Keysight Spectrum Analyzer interface. The main display shows a spectrum with a single peak labeled 'Mkr1 2.439 727 0 GHz -3.65 dBm'. The center frequency is set to 2.4397270 GHz, and the span is 2.100 MHz. The x-axis scale is logarithmic (Log). The measurement parameters are: Input RF: 2.4397270 GHz, #Aver: 20 dB, PWD: Best Wide, Date: Off, IF Gain: Low, Sig Track: Off, Ref Lvl: 10.00 dBm, Ref Lvl Offset: 8.23 dB, Scale/Div: 10 dB, #Video BW: 100 kHz, #Res BW: 30 kHz, Sweep: 2.27 ms (1001 pts). The right panel displays various settings such as Center Frequency, Span, Auto Tune, and X Axis Scale.</p>		

Test Mode	Test Channel	Verdict
BLE 2M	HCH	PASS
		

7.5. CONDUCTED BANDEDGE AND SPURIOUS EMISSIONS

LIMITS

FCC Part15 (15.247), Subpart C		
Section	Test Item	Limit
FCC §15.247 (d) RSS-247 Clause 5.5 RSS-GEN Clause 6.13	Conducted Bandedge and Spurious Emissions	20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power

TEST PROCEDURE

Refer to FCC KDB 558074, connect the UUT to the spectrum analyser and use the following settings:


Center Frequency	The centre frequency of the channel under test
Detector	Peak
RBW	100 kHz
VBW	$\geq 3 \times$ RBW
Span	1.5 x DTS bandwidth
Trace	Max hold
Sweep time	Auto couple.

Use the peak marker function to determine the maximum PSD level.

Span	Set the center frequency and span to encompass frequency range to be measured
Detector	Peak
RBW	100 kHz
VBW	$\geq 3 \times$ RBW
measurement points	\geq span/RBW
Trace	Max hold
Sweep time	Auto couple.

Use the peak marker function to determine the maximum amplitude level.

TEST SETUP



Form-ULID-008536-14 V5.0

UL-CCIC COMPANY LIMITED

This report shall not be reproduced except in full, without the written approval of UL-CCIC COMPANY LIMITED.

TEST ENVIRONMENT

Temperature	22°C	Relative Humidity	56%
Atmosphere Pressure	101kPa	Test Voltage	AC 120V

PART 1: REFERENCE LEVEL MEASUREMENT

TEST RESULTS TABLE

Test Mode	Test Channel	Result[dBm]
BLE 1M	LCH	-0.22
	MCH	-0.29
	HCH	-0.37
BLE 2M	LCH	-1.42
	MCH	-0.99
	HCH	-1.73

TEST GRAPHS











PART 2: CONDUCTED BANDEDGE**TEST RESULTS TABLE**

Test Mode	Test Channel	Result	Verdict
BLE 1M	LCH	Refer to the Test Graph	PASS
	HCH	Refer to the Test Graph	PASS
BLE 1M	LCH	Refer to the Test Graph	PASS
	HCH	Refer to the Test Graph	PASS

TEST GRAPHS

Test Mode	Test Channel	Verdict																																																																																				
BLE 1M	LCH	PASS																																																																																				
 <p>LCH Test Results:</p> <p>Marker Data:</p> <table border="1"> <thead> <tr> <th>Marker</th> <th>Trace</th> <th>Scale</th> <th>X (GHz)</th> <th>Y (dBm)</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>N</td> <td>1</td> <td>2.400 000 GHz</td> <td>-52.96 dBm</td> </tr> <tr> <td>2</td> <td>N</td> <td>1</td> <td>2.390 000 GHz</td> <td>-55.20 dBm</td> </tr> <tr> <td>3</td> <td>N</td> <td>1</td> <td>2.310 000 GHz</td> <td>-54.91 dBm</td> </tr> <tr> <td>4</td> <td>N</td> <td>1</td> <td>2.338 430 GHz</td> <td>-50.90 dBm</td> </tr> <tr> <td>5</td> <td>N</td> <td>1</td> <td>2.352 500 GHz</td> <td>-50.90 dBm</td> </tr> </tbody> </table> <p>Marker Table:</p> <table border="1"> <thead> <tr> <th>Mode</th> <th>Trace</th> <th>Scale</th> <th>X</th> <th>Y</th> <th>Function</th> <th>Function Width</th> <th>Function Value</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>N</td> <td>1</td> <td>f</td> <td>2.400 000 GHz</td> <td>-52.96 dBm</td> <td></td> <td></td> </tr> <tr> <td>2</td> <td>N</td> <td>1</td> <td>f</td> <td>2.390 000 GHz</td> <td>-55.20 dBm</td> <td></td> <td></td> </tr> <tr> <td>3</td> <td>N</td> <td>1</td> <td>f</td> <td>2.310 000 GHz</td> <td>-54.91 dBm</td> <td></td> <td></td> </tr> <tr> <td>4</td> <td>N</td> <td>1</td> <td>f</td> <td>2.338 430 GHz</td> <td>-50.90 dBm</td> <td></td> <td></td> </tr> <tr> <td>5</td> <td>N</td> <td>1</td> <td>f</td> <td>2.352 500 GHz</td> <td>-50.90 dBm</td> <td></td> <td></td> </tr> <tr> <td>6</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	Marker	Trace	Scale	X (GHz)	Y (dBm)	1	N	1	2.400 000 GHz	-52.96 dBm	2	N	1	2.390 000 GHz	-55.20 dBm	3	N	1	2.310 000 GHz	-54.91 dBm	4	N	1	2.338 430 GHz	-50.90 dBm	5	N	1	2.352 500 GHz	-50.90 dBm	Mode	Trace	Scale	X	Y	Function	Function Width	Function Value	1	N	1	f	2.400 000 GHz	-52.96 dBm			2	N	1	f	2.390 000 GHz	-55.20 dBm			3	N	1	f	2.310 000 GHz	-54.91 dBm			4	N	1	f	2.338 430 GHz	-50.90 dBm			5	N	1	f	2.352 500 GHz	-50.90 dBm			6							
Marker	Trace	Scale	X (GHz)	Y (dBm)																																																																																		
1	N	1	2.400 000 GHz	-52.96 dBm																																																																																		
2	N	1	2.390 000 GHz	-55.20 dBm																																																																																		
3	N	1	2.310 000 GHz	-54.91 dBm																																																																																		
4	N	1	2.338 430 GHz	-50.90 dBm																																																																																		
5	N	1	2.352 500 GHz	-50.90 dBm																																																																																		
Mode	Trace	Scale	X	Y	Function	Function Width	Function Value																																																																															
1	N	1	f	2.400 000 GHz	-52.96 dBm																																																																																	
2	N	1	f	2.390 000 GHz	-55.20 dBm																																																																																	
3	N	1	f	2.310 000 GHz	-54.91 dBm																																																																																	
4	N	1	f	2.338 430 GHz	-50.90 dBm																																																																																	
5	N	1	f	2.352 500 GHz	-50.90 dBm																																																																																	
6																																																																																						

Test Mode	Test Channel	Verdict																																																																																									
BLE 1M	HCH	PASS																																																																																									
 <p>HCH Test Results:</p> <p>Marker Data:</p> <table border="1"> <thead> <tr> <th>Marker</th> <th>Trace</th> <th>Scale</th> <th>X (GHz)</th> <th>Y (dBm)</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>N</td> <td>1</td> <td>2.483 50 GHz</td> <td>-54.23 dBm</td> </tr> <tr> <td>2</td> <td>N</td> <td>1</td> <td>2.500 00 GHz</td> <td>-53.81 dBm</td> </tr> <tr> <td>3</td> <td>N</td> <td>1</td> <td>2.547 84 GHz</td> <td>-50.89 dBm</td> </tr> <tr> <td>4</td> <td>N</td> <td>1</td> <td>2.550 000 GHz</td> <td>-50.89 dBm</td> </tr> <tr> <td>5</td> <td>N</td> <td>1</td> <td>2.570 000 GHz</td> <td>-50.89 dBm</td> </tr> <tr> <td>6</td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table> <p>Marker Table:</p> <table border="1"> <thead> <tr> <th>Mode</th> <th>Trace</th> <th>Scale</th> <th>X</th> <th>Y</th> <th>Function</th> <th>Function Width</th> <th>Function Value</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>N</td> <td>1</td> <td>f</td> <td>2.483 50 GHz</td> <td>-54.23 dBm</td> <td></td> <td></td> </tr> <tr> <td>2</td> <td>N</td> <td>1</td> <td>f</td> <td>2.500 00 GHz</td> <td>-53.81 dBm</td> <td></td> <td></td> </tr> <tr> <td>3</td> <td>N</td> <td>1</td> <td>f</td> <td>2.547 84 GHz</td> <td>-50.89 dBm</td> <td></td> <td></td> </tr> <tr> <td>4</td> <td>N</td> <td>1</td> <td>f</td> <td>2.550 000 GHz</td> <td>-50.89 dBm</td> <td></td> <td></td> </tr> <tr> <td>5</td> <td>N</td> <td>1</td> <td>f</td> <td>2.570 000 GHz</td> <td>-50.89 dBm</td> <td></td> <td></td> </tr> <tr> <td>6</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	Marker	Trace	Scale	X (GHz)	Y (dBm)	1	N	1	2.483 50 GHz	-54.23 dBm	2	N	1	2.500 00 GHz	-53.81 dBm	3	N	1	2.547 84 GHz	-50.89 dBm	4	N	1	2.550 000 GHz	-50.89 dBm	5	N	1	2.570 000 GHz	-50.89 dBm	6					Mode	Trace	Scale	X	Y	Function	Function Width	Function Value	1	N	1	f	2.483 50 GHz	-54.23 dBm			2	N	1	f	2.500 00 GHz	-53.81 dBm			3	N	1	f	2.547 84 GHz	-50.89 dBm			4	N	1	f	2.550 000 GHz	-50.89 dBm			5	N	1	f	2.570 000 GHz	-50.89 dBm			6							
Marker	Trace	Scale	X (GHz)	Y (dBm)																																																																																							
1	N	1	2.483 50 GHz	-54.23 dBm																																																																																							
2	N	1	2.500 00 GHz	-53.81 dBm																																																																																							
3	N	1	2.547 84 GHz	-50.89 dBm																																																																																							
4	N	1	2.550 000 GHz	-50.89 dBm																																																																																							
5	N	1	2.570 000 GHz	-50.89 dBm																																																																																							
6																																																																																											
Mode	Trace	Scale	X	Y	Function	Function Width	Function Value																																																																																				
1	N	1	f	2.483 50 GHz	-54.23 dBm																																																																																						
2	N	1	f	2.500 00 GHz	-53.81 dBm																																																																																						
3	N	1	f	2.547 84 GHz	-50.89 dBm																																																																																						
4	N	1	f	2.550 000 GHz	-50.89 dBm																																																																																						
5	N	1	f	2.570 000 GHz	-50.89 dBm																																																																																						
6																																																																																											




PART 3: CONDUCTED SPURIOUS EMISSION**TEST RESULTS TABLE**


Test Mode	Test Channel	Result	Verdict
BLE 1M	LCH	Refer to the Test Graph	PASS
	MCH	Refer to the Test Graph	PASS
	HCH	Refer to the Test Graph	PASS
BLE 2M	LCH	Refer to the Test Graph	PASS
	MCH	Refer to the Test Graph	PASS
	HCH	Refer to the Test Graph	PASS

TEST GRAPHS

Test Mode	Channel	Verdict
BLE 1M	LCH	PASS



Test Mode	Channel	Verdict
BLE 1M	MCH	PASS



Test Mode	Channel	Verdict
BLE 1M	HCH	PASS

HCH SPURIOUS EMISSION_30MHz~1GHz

HCH SPURIOUS EMISSION_1GHz~26.5GHz


Test Mode	Channel	Verdict
BLE 2M	LCH	PASS




Test Mode	Channel	Verdict
BLE 2M	MCH	PASS

MCH SPURIOUS EMISSION_30MHz~1GHz

MCH SPURIOUS EMISSION_1GHz~26.5GHz


Test Mode	Channel	Verdict
BLE 2M	HCH	PASS



8. RADIATED TEST RESULTS

8.1. LIMITS AND PROCEDURE

LIMITS

Please refer to FCC §15.205 and §15.209, ISED RSS-247 Clause 5.5, ISED RSS-GEN Clause 8.9&6.13 (Transmitter)

Radiation Disturbance Test Limit for ISED (9kHz-1GHz)

Except where otherwise indicated in the applicable RSS, radiated emissions shall comply with the field strength limits shown in table 5 and table 6. Additionally, the level of any transmitter unwanted emission shall not exceed the level of the transmitter's fundamental emission.

Table 5 – General field strength limits at frequencies above 30 MHz

Frequency (MHz)	Field strength (μ V/m at 3 m)
30 – 88	100
88 – 216	150
216 – 960	200
Above 960	500

Table 6 – General field strength limits at frequencies below 30 MHz

Frequency	Magnetic field strength (H-Field) (μ A/m)	Measurement distance (m)
9 - 490 kHz ^{Note 1}	6.37/F (F in kHz)	300
490 - 1705 kHz	63.7/F (F in kHz)	30
1.705 - 30 MHz	0.08	30

Note 1: The emission limits for the ranges 9-90 kHz and 110-490 kHz are based on measurements employing a linear average detector.

Please refer to FCC KDB 558074

Radiation Disturbance Test Limit for FCC (Class B) (9kHz-1GHz)

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
960~1000	500	3

Note: 1) At frequencies at or above 30 MHz, measurements may be performed at a distance other than what is specified provided: measurements are not made in the near field except where it can be shown that near field measurements are appropriate due to the characteristics of the device; and it can be demonstrated that the signal levels needed to be measured at the distance employed can be detected by the measurement equipment. Measurements shall not be performed at a distance greater than 30 meters unless it can be further demonstrated that measurements at a distance of 30 meters or less are impractical. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse linear-distance for field strength measurements; inverse-linear-distance-squared for power density measurements).

(2) At frequencies below 30 MHz, measurements may be performed at a distance closer than that specified in the regulations; however, an attempt should be made to avoid making measurements in the near field. Pending the development of an appropriate measurement procedure for measurements performed below 30 MHz, when performing measurements at a closer distance than specified, the results shall be extrapolated to the specified distance by either making measurements at a minimum of two distances on at least one radial to determine the proper extrapolation factor or by using the square of an inverse linear distance extrapolation factor (40 dB/decade). This paragraph (f) shall not apply to Access BPL devices operating below 30 MHz.

Radiation Disturbance Test Limit for FCC (Above 1G)

Frequency (MHz)	dB(uV/m) (at 3 meters)	
	Peak	Average
Above 1000	74	54

Restricted bands of operation


MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
¹ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(²)
13.36-13.41			

Note: ¹Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

²Above 38.6c

TEST SETUP AND PROCEDURE

Below 30MHz




The setting of the spectrum analyser

RBW	200 Hz (From 9kHz to 0.15MHz) / 9kHz (From 0.15MHz to 30MHz)
VBW	200 Hz (From 9kHz to 0.15MHz) / 9kHz (From 0.15MHz to 30MHz)
Sweep	Auto
Detector	Peak/QP/Average
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013
2. The EUT was arranged to its worst case and then turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both Horizontal, Face-on and Face-off polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 0.8 meter above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a 1m height antenna tower.
5. The radiated emission limits are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector
6. For measurement below 1GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
7. For the actual test configuration, please refer to the related item in this test report
(Photographs of the Test Configuration)
8. The limits in FCC 47 CFR, Part 15, Subpart C, paragraph 15.209 (a), are identical to those in RSS-GEN Section 8.9, Table 6, since the measurements are performed in terms of magnetic field strength and converted to electric field strength levels (as reported in the table) using the free space impedance of 377Ω . For example, the measurement frequency X kHz resulted in a level of Y dBuV/m, which is equivalent to $Y - 51.5 = Z$ dBuA/m, which has the same margin, W dB, to the corresponding RSS-GEN Table 6 limit as it has to be 15.209(a) limit.

Below 1G




The setting of the spectrum analyser

RBW	120 kHz
VBW	300 kHz
Sweep	Auto
Detector	Peak/QP
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 12 mm above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement below 1GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
6. For the actual test configuration, please refer to the related item in this test report (Photographs of the Test Configuration)

Above 1G




The setting of the spectrum analyser

RBW	1 MHz
VBW	PEAK:3 MHz AVG: See note6
Sweep	Auto
Detector	Peak
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 12mm above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement above 1GHz, the emission measurement will be measured by the peak detector. This peak level, once corrected, must comply with the limit specified in Section 15.209.
6. For measurements above 1 GHz, the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 3 MHz for peak measurements; and 1 MHz resolution bandwidth with video bandwidth $\geq 1/T$ but not less than the setting list in section 7.1 when use peak detector, max hold to be run for at least $[50 * (1/\text{Duty Cycle})]$ traces for average measurements. For the Duty Cycle need to refer the results in section 7.1.
7. For the actual test configuration, please refer to the related item in this test report (Photographs of the Test Configuration)

X axis, Y axis, Z axis positions:



Note 1: For all radiated test, EUT in each of three orthogonal axis emissions had been tested, but only the worse case (Y axis) data recorded in the report.

Note 2: The antenna can be tilted from 0° to 90°. All these angles were tested, but only the data for the worst-case (0°) condition were included in the report

8.2. TEST ENVIRONMENT

Temperature	22°C	Relative Humidity	56%
Atmosphere Pressure	101kPa	Test Voltage	AC 120V


8.3. RESTRICTED BANDEDGE

TEST RESULT TABLE

Test Mode	Channel	Puw(dBm)	Verdict
BLE 1M	LCH	<Limit	PASS
	HCH	<Limit	PASS

TEST GRAPHS

Test Mode	Channel	Polarization	Verdict
BLE 1M	LCH	Horizontal	PASS




PK Result:

No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	[MHz]	[dBuV/m]	[dB]				
1	2364.2830	39.42	13.59	53.01	74.00	-20.99	Horizontal
2	2390.0000	37.23	13.72	50.95	74.00	-23.05	Horizontal

Note: 1. Peak result: Peak detector, RBW: 1 MHz, VBW: 3 MHz.
2. Average result: Peak detector, RBW: 1 MHz, VBW: 1/T MHz (refer to clause 7.1.).
3. Measurement = Reading Level + Correct Factor.
4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.


Test Mode	Channel	Polarization	Verdict
BLE 1M	LCH	Vertical	PASS


PK Result:

No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	[MHz]	[dB _{BuV/m}]	[dB]	[dB _{BuV/m}]	[dB _{BuV/m}]	[dB]	
1	2373.5654	39.61	13.70	53.31	74.00	-20.69	Vertical
2	2390.0000	36.90	13.72	50.62	74.00	-23.38	Vertical

Note: 1. Peak result: Peak detector, RBW: 1 MHz, VBW: 3 MHz.
2. Average result: Peak detector, RBW: 1 MHz, VBW: 1/T MHz (refer to clause 7.1.).
3. Measurement = Reading Level + Correct Factor.
4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

Test Mode	Channel	Polarization	Verdict
BLE 1M	HCH	Horizontal	PASS


PK Result:


No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	[MHz]	[dBuV/m]	[dB]	[dBuV/m]	[dBuV/m]	[dB]	
1	2483.5000	37.95	14.12	52.07	74.00	-21.93	Horizontal
2	2500.6501	40.70	14.19	54.89	74.00	-19.11	Horizontal

AV Result:

No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	[MHz]	[dBuV/m]	[dB]	[dBuV/m]	[dBuV/m]	[dB]	
1	2500.6501	30.21	14.19	44.40	54.00	-9.60	Horizontal

Note: 1. Peak result: Peak detector, RBW: 1 MHz, VBW: 3 MHz.
2. Average result: Peak detector, RBW: 1 MHz, VBW: 1/T MHz (refer to clause 7.1.).
3. Measurement = Reading Level + Correct Factor.
4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

Test Mode	Channel	Polarization	Verdict
BLE 1M	HCH	Vertical	PASS


PK Result:


No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	[MHz]	[dBuV/m]	[dB]	[dBuV/m]	[dBuV/m]	[dB]	
1	2483.5000	37.57	14.12	51.69	74.00	-22.31	Vertical
2	2515.9520	40.62	14.48	55.10	74.00	-18.90	Vertical

AV Result:

No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	[MHz]	[dBuV/m]	[dB]	[dBuV/m]	[dBuV/m]	[dB]	
1	2515.9520	30.60	14.48	45.08	54.00	-8.92	Vertical

Note: 1. Peak result: Peak detector, RBW: 1 MHz, VBW: 3 MHz.
2. Average result: Peak detector, RBW: 1 MHz, VBW: 1/T MHz (refer to clause 7.1.).
3. Measurement = Reading Level + Correct Factor.
4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.


Test Mode	Channel	Polarization	Verdict
BLE 2M	LCH	Horizontal	PASS


PK Result:

No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	[MHz]	[dBuV/m]	[dB]	[dBuV/m]	[dBuV/m]	[dB]	
1	2354.5131	40.05	13.53	53.58	74.00	-20.42	Horizontal
2	2390.0000	36.85	13.72	50.57	74.00	-23.43	Horizontal

Note: 1. Peak result: Peak detector, RBW: 1 MHz, VBW: 3 MHz.
2. Average result: Peak detector, RBW: 1 MHz, VBW: 1/T MHz (refer to clause 7.1.).
3. Measurement = Reading Level + Correct Factor.
4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.


Test Mode	Channel	Polarization	Verdict
BLE 2M	LCH	Vertical	PASS


PK Result:

No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	[MHz]	[dBuV/m]	[dB]	[dBuV/m]	[dBuV/m]	[dB]	
1	2362.1265	39.96	13.55	53.51	74.00	-20.49	Vertical
2	2390.0000	37.61	13.72	51.33	74.00	-22.67	Vertical

Note: 1. Peak result: Peak detector, RBW: 1 MHz, VBW: 3 MHz.
2. Average result: Peak detector, RBW: 1 MHz, VBW: 1/T MHz (refer to clause 7.1.).
3. Measurement = Reading Level + Correct Factor.
4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

Test Mode	Channel	Polarization	Verdict
BLE 2M	HCH	Horizontal	PASS


PK Result:


No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	[MHz]	[dBuV/m]	[dB]	[dBuV/m]	[dBuV/m]	[dB]	
1	2483.5000	37.72	14.12	51.84	74.00	-22.16	Horizontal
2	2504.0930	40.97	14.27	55.24	74.00	-18.76	Horizontal

AV Result:

No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	[MHz]	[dBuV/m]	[dB]	[dBuV/m]	[dBuV/m]	[dB]	
1	2504.0930	30.24	14.27	44.51	54.00	-9.49	Horizontal

Note: 1. Peak result: Peak detector, RBW: 1 MHz, VBW: 3 MHz.
2. Average result: Peak detector, RBW: 1 MHz, VBW: 1/T MHz (refer to clause 7.1.).
3. Measurement = Reading Level + Correct Factor.
4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

Test Mode	Channel	Polarization	Verdict
BLE 2M	HCH	Vertical	PASS


PK Result:

No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	[MHz]	[dBuV/m]	[dB]	[dBuV/m]	[dBuV/m]	[dB]	
1	2483.5000	38.61	14.12	52.73	74.00	-21.27	Vertical
2	2500.8526	39.91	14.20	54.11	74.00	-19.89	Vertical

AV Result:

No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	[MHz]	[dBuV/m]	[dB]	[dBuV/m]	[dBuV/m]	[dB]	
1	2500.8526	30.41	14.20	44.61	54.00	-9.39	Vertical

Note: 1. Peak result: Peak detector, RBW: 1 MHz, VBW: 3 MHz.
2. Average result: Peak detector, RBW: 1 MHz, VBW: 1/T MHz (refer to clause 7.1.).
3. Measurement = Reading Level + Correct Factor.
4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

8.4. SPURIOUS EMISSIONS

TEST RESULTS TABLE

1) For 1GHz~18GHz

Test Mode	Channel	Puw(dBm)	Verdict
BLE 1M	LCH	<Limit	PASS
	MCH	<Limit	PASS
	HCH	<Limit	PASS
BLE 2M	LCH	<Limit	PASS
	MCH	<Limit	PASS
	HCH	<Limit	PASS

Note:

Through pre-testing all the test modes and test channels, but only the data of the worst case is included in this test report.

2) For 9kHz~30MHz

Test Mode	Channel	Puw(dBm)	Verdict
BLE 1M	MCH	<Limit	PASS

Note:

Through pre-testing all the test modes and test channels, but only the data of the worst case is included in this test report.

3) For 30MHz~1GHz

Test Mode	Channel	Puw(dBm)	Verdict
BLE 1M	MCH	<Limit	PASS

Note:

Through pre-testing all the test modes and test channels, but only the data of the worst case is included in this test report.

4) For 18GHz~26.5GHz


Test Mode	Channel	Puw(dBm)	Verdict
BLE 1M	MCH	<Limit	PASS

Note:

Through pre-testing all the test modes and test channels, but only the data of the worst case is included in this test report.

Part 1: 1GHz~6.5GHz
HARMONICS AND SPURIOUS EMISSIONS


Test Mode	Channel	Polarization	Verdict
BLE 1M	LCH	Horizontal	PASS


PK Result:

No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	[MHz]	[dBuV/m]	[dB]	[dBuV/m]	[dBuV/m]	[dB]	
1	1255.0944	42.72	-1.98	40.74	74.00	-33.26	Horizontal
2	2492.0615	37.96	5.71	43.67	74.00	-30.33	Horizontal
3	4692.3365	36.07	15.70	51.77	74.00	-22.23	Horizontal
4	5429.4287	34.98	17.56	52.54	74.00	-21.46	Horizontal
5	5925.8657	34.89	18.77	53.66	74.00	-20.34	Horizontal
6	6331.5414	34.17	19.39	53.56	74.00	-20.44	Horizontal

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
4. Peak: Peak detector.
5. For below 6.5GHz part, filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band Reject Filter losses.
6. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

Test Mode	Channel	Polarization	Verdict
BLE 1M	LCH	Vertical	PASS



PK Result:

No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	[MHz]	[dBuV/m]	[dB]	[dBuV/m]	[dBuV/m]	[dB]	
1	1185.6482	46.68	-1.95	44.73	74.00	-29.27	Vertical
2	1255.0944	46.66	-1.98	44.68	74.00	-29.32	Vertical
3	1394.6743	42.40	-1.45	40.95	74.00	-33.05	Vertical
4	4785.1606	37.71	14.63	52.34	74.00	-21.66	Vertical
5	6029.0036	35.34	18.16	53.50	74.00	-20.50	Vertical
6	6326.0408	33.90	19.31	53.21	74.00	-20.79	Vertical

Note:

1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
4. Peak: Peak detector.
5. For below 6.5GHz part, filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band Reject Filter losses.
6. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

Test Mode	Channel	Polarization	Verdict
BLE 1M	MCH	Horizontal	PASS



PK Result:

No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	[MHz]	[dBuV/m]	[dB]	[dBuV/m]	[dBuV/m]	[dB]	
1	1255.0944	43.68	-1.98	41.70	74.00	-32.30	Horizontal
2	4118.2023	35.29	13.88	49.17	74.00	-24.83	Horizontal
3	4670.3338	36.02	15.27	51.29	74.00	-22.71	Horizontal
4	5443.1804	35.49	17.39	52.88	74.00	-21.12	Horizontal
5	5736.7796	35.73	17.88	53.61	74.00	-20.39	Horizontal
6	6440.1800	34.81	18.92	53.73	74.00	-20.27	Horizontal

Note:

1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
4. Peak: Peak detector.
5. For below 6.5GHz part, filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band Reject Filter losses.
6. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

Test Mode	Channel	Polarization	Verdict
BLE 1M	MCH	Vertical	PASS



PK Result:

No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	[MHz]	[dBuV/m]	[dB]	[dBuV/m]	[dBuV/m]	[dB]	
1	1184.9606	47.28	-1.93	45.35	74.00	-28.65	Vertical
2	1255.0944	46.12	-1.98	44.14	74.00	-29.86	Vertical
3	1324.5406	41.84	-1.47	40.37	74.00	-33.63	Vertical
4	5188.0860	36.97	15.43	52.40	74.00	-21.60	Vertical
5	5695.5244	36.09	17.60	53.69	74.00	-20.31	Vertical
6	6183.0229	34.68	18.91	53.59	74.00	-20.41	Vertical

Note:

1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
4. Peak: Peak detector.
5. For below 6.5GHz part, filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band Reject Filter losses.
6. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

Test Mode	Channel	Polarization	Verdict
BLE 1M	HCH	Horizontal	PASS



PK Result:

No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	[MHz]	[dBuV/m]	[dB]	[dBuV/m]	[dBuV/m]	[dB]	
1	1185.6482	39.91	-1.95	37.96	74.00	-36.04	Horizontal
2	1254.4068	43.56	-1.97	41.59	74.00	-32.41	Horizontal
3	4932.9916	36.35	15.33	51.68	74.00	-22.32	Horizontal
4	5439.0549	35.13	17.31	52.44	74.00	-21.56	Horizontal
5	5740.9051	35.23	18.03	53.26	74.00	-20.74	Horizontal
6	5883.9230	35.60	17.78	53.38	74.00	-20.62	Horizontal

Note:

1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
4. Peak: Peak detector.
5. For below 6.5GHz part, filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band Reject Filter losses.
6. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

Test Mode	Channel	Polarization	Verdict
BLE 1M	HCH	Vertical	PASS



PK Result:

No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	[MHz]	[dBuV/m]	[dB]	[dBuV/m]	[dBuV/m]	[dB]	
1	1184.9606	45.58	-1.93	43.65	74.00	-30.35	Vertical
2	1255.0944	47.19	-1.98	45.21	74.00	-28.79	Vertical
3	1393.9867	41.34	-1.44	39.90	74.00	-34.10	Vertical
4	5362.0453	36.57	16.21	52.78	74.00	-21.22	Vertical
5	5861.9202	35.51	17.94	53.45	74.00	-20.55	Vertical
6	6325.3532	33.82	19.29	53.11	74.00	-20.89	Vertical

Note:

1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
4. Peak: Peak detector.
5. For below 6.5GHz part, filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band Reject Filter losses.
6. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

Test Mode	Channel	Polarization	Verdict
BLE 2M	LCH	Horizontal	PASS



PK Result:

No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	[MHz]	[dBuV/m]	[dB]				
1	1184.9606	40.77	-1.93	38.84	74.00	-35.16	Horizontal
2	1254.4068	42.52	-1.97	40.55	74.00	-33.45	Horizontal
3	4470.9339	36.69	14.03	50.72	74.00	-23.28	Horizontal
4	5042.3178	35.95	15.84	51.79	74.00	-22.21	Horizontal
5	5925.8657	34.46	18.77	53.23	74.00	-20.77	Horizontal
6	6424.3655	34.27	18.94	53.21	74.00	-20.79	Horizontal

Note:

1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
4. Peak: Peak detector.
5. For below 6.5GHz part, filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band Reject Filter losses.
6. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

Test Mode	Channel	Polarization	Verdict
BLE 2M	LCH	Vertical	PASS



PK Result:

No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	[MHz]	[dBuV/m]	[dB]	[dBuV/m]	[dBuV/m]	[dB]	
1	1184.9606	44.80	-1.93	42.87	74.00	-31.13	Vertical
2	1255.0944	46.50	-1.98	44.52	74.00	-29.48	Vertical
3	1393.9867	42.41	-1.44	40.97	74.00	-33.03	Vertical
4	5655.6445	35.31	17.43	52.74	74.00	-21.26	Vertical
5	5995.9995	35.34	18.36	53.70	74.00	-20.30	Vertical
6	6202.2753	35.26	18.52	53.78	74.00	-20.22	Vertical

Note:

1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
4. Peak: Peak detector.
5. For below 6.5GHz part, filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band Reject Filter losses.
6. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

Test Mode	Channel	Polarization	Verdict
BLE 2M	MCH	Horizontal	PASS



PK Result:

No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	[MHz]	[dBuV/m]	[dB]	[dBuV/m]	[dBuV/m]	[dB]	
1	1254.4068	42.40	-1.97	40.43	74.00	-33.57	Horizontal
2	3205.0881	37.36	9.26	46.62	74.00	-27.38	Horizontal
3	4125.0781	36.58	13.66	50.24	74.00	-23.76	Horizontal
4	5522.9404	36.66	16.66	53.32	74.00	-20.68	Horizontal
5	5758.7823	35.13	18.21	53.34	74.00	-20.66	Horizontal
6	6059.2574	35.45	18.20	53.65	74.00	-20.35	Horizontal

Note:

1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
4. Peak: Peak detector.
5. For below 6.5GHz part, filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band Reject Filter losses.
6. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.


Test Mode	Channel	Polarization	Verdict
BLE 2M	MCH	Vertical	PASS


PK Result:

No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	[MHz]	[dBuV/m]	[dB]	[dBuV/m]	[dBuV/m]	[dB]	
1	1184.9606	44.64	-1.93	42.71	74.00	-31.29	Vertical
2	1254.4068	47.12	-1.97	45.15	74.00	-28.85	Vertical
3	1393.9867	42.81	-1.44	41.37	74.00	-32.63	Vertical
4	4663.4579	36.12	15.01	51.13	74.00	-22.87	Vertical
5	5950.6188	35.52	18.47	53.99	74.00	-20.01	Vertical
6	6460.8076	34.63	19.06	53.69	74.00	-20.31	Vertical

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
4. Peak: Peak detector.
5. For below 6.5GHz part, filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band Reject Filter losses.
6. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

Test Mode	Channel	Polarization	Verdict
BLE 2M	HCH	Horizontal	PASS



PK Result:

No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	[MHz]	[dBuV/m]	[dB]	[dBuV/m]	[dBuV/m]	[dB]	
1	1184.9606	40.52	-1.93	38.59	74.00	-35.41	Horizontal
2	1255.0944	42.42	-1.98	40.44	74.00	-33.56	Horizontal
3	3991.6865	38.01	12.87	50.88	74.00	-23.12	Horizontal
4	4250.9064	37.08	13.77	50.85	74.00	-23.15	Horizontal
5	5560.0700	36.02	17.03	53.05	74.00	-20.95	Horizontal
6	5923.8030	34.51	18.73	53.24	74.00	-20.76	Horizontal

Note:

1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
4. Peak: Peak detector.
5. For below 6.5GHz part, filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band Reject Filter losses.
6. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

Test Mode	Channel	Polarization	Verdict
BLE 2M	HCH	Vertical	PASS


PK Result:


No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	[MHz]	[dBuV/m]	[dB]	[dBuV/m]	[dBuV/m]	[dB]	
1	1184.9606	46.17	-1.93	44.24	74.00	-29.76	Vertical
2	1254.4068	45.06	-1.97	43.09	74.00	-30.91	Vertical
3	1393.9867	42.42	-1.44	40.98	74.00	-33.02	Vertical
4	4697.1496	36.01	15.24	51.25	74.00	-22.75	Vertical
5	6038.6298	35.51	18.15	53.66	74.00	-20.34	Vertical
6	6374.1718	34.33	19.44	53.77	74.00	-20.23	Vertical

Note:

1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
4. Peak: Peak detector.
5. For below 6.5GHz part, filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band Reject Filter losses.
6. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

Part 2: 6.5GHz~18GHz
HARMONICS AND SPURIOUS EMISSIONS

Test Mode	Channel	Polarization	Verdict
BLE 1M	LCH	Horizontal	PASS


PK Result:


No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	[MHz]	[dBuV/m]	[dB]	[dBuV/m]	[dBuV/m]	[dB]	
1	7205.9007	50.82	4.11	54.93	74.00	-19.07	Horizontal
2	8417.8647	44.16	6.31	50.47	74.00	-23.53	Horizontal
3	15607.7010	40.93	13.48	54.41	74.00	-19.59	Horizontal
4	16540.7551	39.11	16.55	55.66	74.00	-18.34	Horizontal
5	16961.9952	37.84	16.89	54.73	74.00	-19.27	Horizontal
6	17700.9626	38.30	19.28	57.58	74.00	-16.42	Horizontal
7	17961.1826	36.12	20.55	56.67	74.00	-17.33	Horizontal

AV Result:

No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	[MHz]	[dBuV/m]	[dB]	[dBuV/m]	[dBuV/m]	[dB]	
1	7205.9007	44.95	4.11	49.06	54.00	-4.94	Horizontal
2	15607.7010	30.24	13.48	43.72	54.00	-10.28	Horizontal
3	16540.7551	28.52	16.55	45.07	54.00	-8.93	Horizontal
4	16961.9952	27.98	16.89	44.87	54.00	-9.13	Horizontal
5	17700.9626	28.17	19.28	47.45	54.00	-6.55	Horizontal
6	17961.1826	25.79	20.55	46.34	54.00	-7.66	Horizontal

Note: 1. Measurement = Reading Level + Correct Factor.
2. If peak result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak result: Peak detector, RBW: 1 MHz, VBW: 3 MHz.
4. Average result: Peak detector, RBW: 1 MHz, VBW: 1/T MHz(refer to clause 7.1.).
5. For above 6.5GHz part, filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for HPF losses.
6. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

Test Mode	Channel	Polarization	Verdict
BLE 1M	LCH	Vertical	PASS


PK Result:


No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	[MHz]	[dBuV/m]	[dB]	[dBuV/m]	[dBuV/m]	[dB]	
1	7204.4631	49.20	4.13	53.33	74.00	-20.67	Vertical
2	8791.6615	44.26	6.32	50.58	74.00	-23.42	Vertical
3	9588.1360	44.40	6.43	50.83	74.00	-23.17	Vertical
4	16204.3380	39.04	15.61	54.65	74.00	-19.35	Vertical
5	16507.6885	39.86	16.69	56.55	74.00	-17.45	Vertical
6	16967.7460	38.42	16.85	55.27	74.00	-18.73	Vertical
7	17712.4641	37.72	19.38	57.10	74.00	-16.90	Vertical

AV Result:

No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	[MHz]	[dBuV/m]	[dB]	[dBuV/m]	[dBuV/m]	[dB]	
1	16204.3380	28.29	15.61	43.90	54.00	-10.10	Vertical
2	16507.6885	29.94	16.69	46.63	54.00	-7.37	Vertical
3	16967.7460	27.56	16.85	44.41	54.00	-9.59	Vertical
4	17712.4641	28.71	19.38	48.09	54.00	-5.91	Vertical

Note: 1. Measurement = Reading Level + Correct Factor.
2. If peak result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak result: Peak detector, RBW: 1 MHz, VBW: 3 MHz.
4. Average result: Peak detector, RBW: 1 MHz, VBW: 1/T MHz(refer to clause 7.1.).
5. For above 6.5GHz part, filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for HPF losses.
6. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

Test Mode	Channel	Polarization	Verdict
BLE 1M	MCH	Horizontal	PASS


PK Result:

No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	[MHz]	[dBuV/m]	[dB]	[dBuV/m]	[dBuV/m]	[dB]	
1	6553.1941	47.53	3.39	50.92	74.00	-23.08	Horizontal
2	7319.4774	49.65	3.97	53.62	74.00	-20.38	Horizontal
3	14421.6152	40.63	13.03	53.66	74.00	-20.34	Horizontal
4	15360.4201	40.59	13.51	54.10	74.00	-19.90	Horizontal
5	16493.3117	38.95	16.63	55.58	74.00	-18.42	Horizontal
6	16918.8649	38.12	16.78	54.90	74.00	-19.10	Horizontal
7	17700.9626	37.47	19.28	56.75	74.00	-17.25	Horizontal


AV Result:

No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	[MHz]	[dBuV/m]	[dB]	[dBuV/m]	[dBuV/m]	[dB]	
1	15360.4201	30.49	13.51	44.00	54.00	-10.00	Horizontal
2	16493.3117	29.34	16.63	45.97	54.00	-8.03	Horizontal
3	16918.8649	28.16	16.78	44.94	54.00	-9.06	Horizontal
4	17700.9626	28.62	19.28	47.90	54.00	-6.10	Horizontal

Note:

1. Measurement = Reading Level + Correct Factor.
2. If peak result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak result: Peak detector, RBW: 1 MHz, VBW: 3 MHz.
4. Average result: Peak detector, RBW: 1 MHz, VBW: 1/T MHz(refer to clause 7.1.).
5. For above 6.5GHz part, filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for HPF losses.
6. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

Test Mode	Channel	Polarization	Verdict
BLE 1M	MCH	Vertical	PASS


PK Result:

No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	[MHz]	[dBuV/m]	[dB]	[dBuV/m]	[dBuV/m]	[dB]	
1	7319.4774	48.66	3.97	52.63	74.00	-21.37	Vertical
2	8220.9026	44.32	6.13	50.45	74.00	-23.55	Vertical
3	14887.4234	41.55	12.76	54.31	74.00	-19.69	Vertical
4	15893.7992	39.64	14.69	54.33	74.00	-19.67	Vertical
5	16512.0015	38.99	16.72	55.71	74.00	-18.29	Vertical
6	16928.9286	38.14	16.78	54.92	74.00	-19.08	Vertical
7	17675.0844	38.79	18.97	57.76	74.00	-16.24	Vertical


AV Result:

No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	[MHz]	[dBuV/m]	[dB]	[dBuV/m]	[dBuV/m]	[dB]	
1	14887.4234	31.47	12.76	44.23	54.00	-9.77	Vertical
2	15893.7992	29.13	14.69	43.82	54.00	-10.18	Vertical
3	16512.0015	29.33	16.72	46.05	54.00	-7.95	Vertical
4	16928.9286	28.71	16.78	45.49	54.00	-8.51	Vertical
5	17675.0844	27.97	18.97	46.94	54.00	-7.06	Vertical

Note:

1. Measurement = Reading Level + Correct Factor.
2. If peak result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak result: Peak detector, RBW: 1 MHz, VBW: 3 MHz.
4. Average result: Peak detector, RBW: 1 MHz, VBW: 1/T MHz (refer to clause 7.1.).
5. For above 6.5GHz part, filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for HPF losses.
6. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

Test Mode	Channel	Polarization	Verdict
BLE 1M	HCH	Horizontal	PASS


PK Result:


No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	[MHz]	[dBuV/m]	[dB]	[dBuV/m]	[dBuV/m]	[dB]	
1	7438.8049	46.99	4.21	51.20	74.00	-22.80	Horizontal
2	8252.5316	44.61	6.25	50.86	74.00	-23.14	Horizontal
3	15348.9186	40.46	13.49	53.95	74.00	-20.05	Horizontal
4	15852.1065	38.86	15.00	53.86	74.00	-20.14	Horizontal
5	16493.3117	38.60	16.63	55.23	74.00	-18.77	Horizontal
6	17712.4641	37.98	19.38	57.36	74.00	-16.64	Horizontal
7	17989.9362	35.85	20.63	56.48	74.00	-17.52	Horizontal

AV Result:

No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	[MHz]	[dBuV/m]	[dB]	[dBuV/m]	[dBuV/m]	[dB]	
1	16493.3117	29.03	16.63	45.66	54.00	-8.34	Horizontal
2	17712.4641	27.79	19.38	47.17	54.00	-6.83	Horizontal
3	17989.9362	26.24	20.63	46.87	54.00	-7.13	Horizontal

Note: 1. Measurement = Reading Level + Correct Factor.
2. If peak result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak result: Peak detector, RBW: 1 MHz, VBW: 3 MHz.
4. Average result: Peak detector, RBW: 1 MHz, VBW: 1/T MHz(refer to clause 7.1.).
5. For above 6.5GHz part, filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for HPF losses.
6. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

Test Mode	Channel	Polarization	Verdict
BLE 1M	HCH	Vertical	PASS


PK Result:

No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	[MHz]	[dBuV/m]	[dB]	[dBuV/m]	[dBuV/m]	[dB]	
1	7438.8049	47.18	4.21	51.39	74.00	-22.61	Vertical
2	7621.3902	44.97	5.29	50.26	74.00	-23.74	Vertical
3	15696.8371	39.89	14.06	53.95	74.00	-20.05	Vertical
4	16491.8740	39.98	16.66	56.64	74.00	-17.36	Vertical
5	16957.6822	37.77	16.88	54.65	74.00	-19.35	Vertical
6	17709.5887	37.87	19.36	57.23	74.00	-16.77	Vertical
7	17975.5594	36.01	20.60	56.61	74.00	-17.39	Vertical


AV Result:

No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	[MHz]	[dBuV/m]	[dB]	[dBuV/m]	[dBuV/m]	[dB]	
1	16491.8740	29.74	16.66	46.40	54.00	-7.60	Vertical
2	16957.6822	27.31	16.88	44.19	54.00	-9.81	Vertical
3	17709.5887	28.02	19.36	47.38	54.00	-6.62	Vertical
4	17975.5594	25.89	20.60	46.49	54.00	-7.51	Vertical

Note:

1. Measurement = Reading Level + Correct Factor.
2. If peak result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak result: Peak detector, RBW: 1 MHz, VBW: 3 MHz.
4. Average result: Peak detector, RBW: 1 MHz, VBW: 1/T MHz(refer to clause 7.1.).
5. For above 6.5GHz part, filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for HPF losses.
6. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

Test Mode	Channel	Polarization	Verdict
BLE 2M	LCH	Horizontal	PASS


PK Result:

No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	[MHz]	[dBuV/m]	[dB]	[dBuV/m]	[dBuV/m]	[dB]	
1	7207.3384	50.70	4.10	54.80	74.00	-19.20	Horizontal
2	15111.7015	40.45	13.20	53.65	74.00	-20.35	Horizontal
3	15630.7038	40.57	13.66	54.23	74.00	-19.77	Horizontal
4	16542.1928	39.13	16.55	55.68	74.00	-18.32	Horizontal
5	16943.3054	37.77	16.83	54.60	74.00	-19.40	Horizontal
6	17755.5944	37.92	19.52	57.44	74.00	-16.56	Horizontal
7	17926.6783	36.19	20.16	56.35	74.00	-17.65	Horizontal


AV Result:

No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	[MHz]	[dBuV/m]	[dB]	[dBuV/m]	[dBuV/m]	[dB]	
1	7207.3384	42.78	4.10	46.88	54.00	-7.12	Horizontal
2	15630.7038	30.22	13.66	43.88	54.00	-10.12	Horizontal
3	16542.1928	28.60	16.55	45.15	54.00	-8.85	Horizontal
4	16943.3054	28.40	16.83	45.23	54.00	-8.77	Horizontal
5	17755.5944	28.33	19.52	47.85	54.00	-6.15	Horizontal
6	17926.6783	25.88	20.16	46.04	54.00	-7.96	Horizontal

Note:

1. Measurement = Reading Level + Correct Factor.
2. If peak result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak result: Peak detector, RBW: 1 MHz, VBW: 3 MHz.
4. Average result: Peak detector, RBW: 1 MHz, VBW: 1/T MHz(refer to clause 7.1.).
5. For above 6.5GHz part, filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for HPF losses.
6. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

Test Mode	Channel	Polarization	Verdict
BLE 2M	LCH	Vertical	PASS


PK Result:

No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	[MHz]	[dBuV/m]	[dB]	[dBuV/m]	[dBuV/m]	[dB]	
1	7204.4631	48.44	4.13	52.57	74.00	-21.43	Vertical
2	14901.8002	40.83	12.73	53.56	74.00	-20.44	Vertical
3	15636.4546	40.42	13.68	54.10	74.00	-19.90	Vertical
4	16513.4392	39.51	16.71	56.22	74.00	-17.78	Vertical
5	16911.6765	38.06	16.64	54.70	74.00	-19.30	Vertical
6	17708.1510	37.50	19.35	56.85	74.00	-17.15	Vertical
7	17955.4319	35.96	20.50	56.46	74.00	-17.54	Vertical


AV Result:

No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	[MHz]	[dBuV/m]	[dB]	[dBuV/m]	[dBuV/m]	[dB]	
1	15636.4546	29.41	13.68	43.09	54.00	-10.91	Vertical
2	16513.4392	29.71	16.71	46.42	54.00	-7.58	Vertical
3	16911.6765	28.00	16.64	44.64	54.00	-9.36	Vertical
4	17708.1510	28.10	19.35	47.45	54.00	-6.55	Vertical
5	17955.4319	26.61	20.50	47.11	54.00	-6.89	Vertical

Note:

1. Measurement = Reading Level + Correct Factor.
2. If peak result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak result: Peak detector, RBW: 1 MHz, VBW: 3 MHz.
4. Average result: Peak detector, RBW: 1 MHz, VBW: 1/T MHz (refer to clause 7.1.).
5. For above 6.5GHz part, filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for HPF losses.
6. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

Test Mode	Channel	Polarization	Verdict
BLE 2M	MCH	Horizontal	PASS


PK Result:

No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	[MHz]	[dBuV/m]	[dB]	[dBuV/m]	[dBuV/m]	[dB]	
1	7318.0398	49.01	3.98	52.99	74.00	-21.01	Horizontal
2	8075.6970	44.84	5.83	50.67	74.00	-23.33	Horizontal
3	15330.2288	40.29	13.44	53.73	74.00	-20.27	Horizontal
4	16517.7522	38.97	16.67	55.64	74.00	-18.36	Horizontal
5	17003.6880	37.94	16.76	54.70	74.00	-19.30	Horizontal
6	17690.8989	38.34	19.15	57.49	74.00	-16.51	Horizontal
7	17968.3710	36.21	20.52	56.73	74.00	-17.27	Horizontal


AV Result:

No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	[MHz]	[dBuV/m]	[dB]	[dBuV/m]	[dBuV/m]	[dB]	
1	16517.7522	29.63	16.67	46.30	54.00	-7.70	Horizontal
2	17003.6880	26.75	16.76	43.51	54.00	-10.49	Horizontal
3	17690.8989	27.72	19.15	46.87	54.00	-7.13	Horizontal
4	17968.3710	26.17	20.52	46.69	54.00	-7.31	Horizontal

Note:

1. Measurement = Reading Level + Correct Factor.
2. If peak result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak result: Peak detector, RBW: 1 MHz, VBW: 3 MHz.
4. Average result: Peak detector, RBW: 1 MHz, VBW: 1/T MHz(refer to clause 7.1.).
5. For above 6.5GHz part, filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for HPF losses.
6. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

Test Mode	Channel	Polarization	Verdict
BLE 2M	MCH	Vertical	PASS


PK Result:

No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	[MHz]	[dBuV/m]	[dB]	[dBuV/m]	[dBuV/m]	[dB]	
1	7318.0398	48.69	3.98	52.67	74.00	-21.33	Vertical
2	8376.1720	45.02	6.07	51.09	74.00	-22.91	Vertical
3	14883.1104	41.66	12.72	54.38	74.00	-19.62	Vertical
4	16184.2105	39.21	15.56	54.77	74.00	-19.23	Vertical
5	16546.5058	39.20	16.55	55.75	74.00	-18.25	Vertical
6	17693.7742	37.92	19.18	57.10	74.00	-16.90	Vertical
7	17929.5537	36.13	20.18	56.31	74.00	-17.69	Vertical


AV Result:

No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	[MHz]	[dBuV/m]	[dB]	[dBuV/m]	[dBuV/m]	[dB]	
1	14883.1104	31.40	12.72	44.12	54.00	-9.88	Vertical
2	16184.2105	28.69	15.56	44.25	54.00	-9.75	Vertical
3	16546.5058	28.42	16.55	44.97	54.00	-9.03	Vertical
4	17693.7742	28.41	19.18	47.59	54.00	-6.41	Vertical
5	17929.5537	25.80	20.18	45.98	54.00	-8.02	Vertical

Note:

1. Measurement = Reading Level + Correct Factor.
2. If peak result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak result: Peak detector, RBW: 1 MHz, VBW: 3 MHz.
4. Average result: Peak detector, RBW: 1 MHz, VBW: 1/T MHz (refer to clause 7.1.).
5. For above 6.5GHz part, filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for HPF losses.
6. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

Test Mode	Channel	Polarization	Verdict
BLE 2M	HCH	Horizontal	PASS


PK Result:

No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	[MHz]	[dBuV/m]	[dB]	[dBuV/m]	[dBuV/m]	[dB]	
1	7438.8049	46.10	4.21	50.31	74.00	-23.69	Horizontal
2	8386.2358	44.29	6.27	50.56	74.00	-23.44	Horizontal
3	14885.9857	41.30	12.75	54.05	74.00	-19.95	Horizontal
4	16514.8769	39.04	16.70	55.74	74.00	-18.26	Horizontal
5	16869.9837	37.98	16.73	54.71	74.00	-19.29	Horizontal
6	17699.5249	38.39	19.27	57.66	74.00	-16.34	Horizontal
7	17953.9942	36.04	20.48	56.52	74.00	-17.48	Horizontal


AV Result:

No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	[MHz]	[dBuV/m]	[dB]	[dBuV/m]	[dBuV/m]	[dB]	
1	14885.9857	30.41	12.75	43.16	54.00	-10.84	Horizontal
2	16514.8769	29.31	16.70	46.01	54.00	-7.99	Horizontal
3	16869.9837	27.00	16.73	43.73	54.00	-10.27	Horizontal
4	17699.5249	28.01	19.27	47.28	54.00	-6.72	Horizontal
5	17953.9942	25.73	20.48	46.21	54.00	-7.79	Horizontal

Note:

1. Measurement = Reading Level + Correct Factor.
2. If peak result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak result: Peak detector, RBW: 1 MHz, VBW: 3 MHz.
4. Average result: Peak detector, RBW: 1 MHz, VBW: 1/T MHz (refer to clause 7.1.).
5. For above 6.5GHz part, filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for HPF losses.
6. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

Test Mode	Channel	Polarization	Verdict
BLE 2M	HCH	Vertical	PASS


PK Result:

No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	[MHz]	[dBuV/m]	[dB]	[dBuV/m]	[dBuV/m]	[dB]	
1	7622.8279	44.84	5.28	50.12	74.00	-23.88	Vertical
2	8803.1629	44.59	6.32	50.91	74.00	-23.09	Vertical
3	14870.1713	40.76	12.74	53.50	74.00	-20.50	Vertical
4	16491.8740	39.20	16.66	55.86	74.00	-18.14	Vertical
5	16809.6012	37.57	16.97	54.54	74.00	-19.46	Vertical
6	17665.0206	38.12	18.89	57.01	74.00	-16.99	Vertical
7	17979.8725	35.78	20.67	56.45	74.00	-17.55	Vertical

AV Result:


No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	[MHz]	[dBuV/m]	[dB]	[dBuV/m]	[dBuV/m]	[dB]	
1	16491.8740	29.37	16.66	46.03	54.00	-7.97	Vertical
2	16809.6012	27.68	16.97	44.65	54.00	-9.35	Vertical
3	17665.0206	27.28	18.89	46.17	54.00	-7.83	Vertical
4	17979.8725	26.30	20.67	46.97	54.00	-7.03	Vertical

Note:

1. Measurement = Reading Level + Correct Factor.
2. If peak result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak result: Peak detector, RBW: 1 MHz, VBW: 3 MHz.
4. Average result: Peak detector, RBW: 1 MHz, VBW: 1/T MHz(refer to clause 7.1.).
5. For above 6.5GHz part, filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for HPF losses.
6. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

Part 3: 18GHz~26.5GHz
SPURIOUS EMISSIONS 18GHz ~ 26.5GHz (WORST-CASE CONFIGURATION)


Test Mode	Channel	Polarization	Verdict
BLE 1M	MCH	Horizontal	PASS


PK Result:

No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	[MHz]	[dBuV/m]	[dB]	[dBuV/m]	[dBuV/m]	[dB]	
1	18742.1242	50.19	-6.22	43.97	74.00	-30.03	Horizontal
2	19938.1938	48.60	-5.13	43.47	74.00	-30.53	Horizontal
3	22184.9685	49.25	-5.41	43.84	74.00	-30.16	Horizontal
4	22878.6379	48.83	-3.78	45.05	74.00	-28.95	Horizontal
5	24060.2560	48.21	-2.66	45.55	74.00	-28.45	Horizontal
6	25206.1706	50.26	-3.40	46.86	74.00	-27.14	Horizontal

Note: 1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
3. Measurement = Reading Level + Correct Factor.
4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

Test Mode	Channel	Polarization	Verdict
BLE 1M	MCH	Vertical	PASS



PK Result:

No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	[MHz]	[dBuV/m]	[dB]	[dBuV/m]	[dBuV/m]	[dB]	
1	18658.8159	49.88	-6.34	43.54	74.00	-30.46	Vertical
2	20086.1086	48.63	-5.14	43.49	74.00	-30.51	Vertical
3	22870.9871	48.26	-3.79	44.47	74.00	-29.53	Vertical
4	23999.0499	48.41	-2.61	45.80	74.00	-28.20	Vertical
5	25194.2694	49.92	-3.41	46.51	74.00	-27.49	Vertical
6	25510.5010	49.14	-3.18	45.96	74.00	-28.04	Vertical

Note: 1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.
3. Measurement = Reading Level + Correct Factor.
4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

Part 4: 30MHz~1GHz
SPURIOUS EMISSIONS 30MHz ~ 1GHz (WORST-CASE CONFIGURATION)


Test Mode	Channel	Polarization	Verdict
BLE 1M	MCH	Horizontal	PASS



No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	[MHz]	[dBuV/m]	[dB]	[dBuV/m]	[dBuV/m]	[dB]	
1	37.6638	11.86	19.22	31.08	40.00	-8.92	Peak
2	101.4962	14.94	15.86	30.80	43.50	-12.70	Peak
3	139.7180	15.98	19.89	35.87	43.50	-7.63	Peak
4	196.2746	21.43	17.28	38.71	43.50	-4.79	Peak
5	264.2784	22.62	19.72	42.34	46.00	-3.66	Peak
6	328.8869	13.24	21.96	35.20	46.00	-10.80	Peak

Note: 1. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.
2. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.
3. Measurement = Reading Level + Correct Factor.

Test Mode	Channel	Polarization	Verdict
BLE 1M	MCH	Vertical	PASS




No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	[MHz]	[dBuV/m]	[dB]	[dBuV/m]	[dBuV/m]	[dB]	
1	33.4923	6.18	18.79	24.97	40.00	-15.03	Peak
2	39.5070	16.27	19.43	35.70	40.00	-4.30	Peak
3	141.4641	8.06	20.05	28.11	43.50	-15.39	Peak
4	189.2899	13.54	17.75	31.29	43.50	-12.21	Peak
5	263.9874	14.48	19.71	34.19	46.00	-11.81	Peak
6	453.2533	6.63	25.12	31.75	46.00	-14.25	Peak

Note: 1. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.
2. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.
3. Measurement = Reading Level + Correct Factor.

Part 5: 9kHz~30MHz
SPURIOUS EMISSIONS 9kHz ~ 30MHz (WORST CASE CONFIGURATION-FACE ON)

Test Mode	Channel	Frequency Range	Verdict
BLE 1M	MCH	9kHz~150kHz	PASS




No.	Frequency	Reading Level	Correct Factor	FCC Result	FCC Limit	ISED Result	ISED Limit	Margin	Remark
	[MHz]	[dB _{uV}]	[dB/m]	[dB _{uV/m}]	[dB _{uV/m}]	[dB _{uA/m}]	[dB _{uA/m}]	[dB]	
1	0.0101	21.81	-61.90	-40.09	47.54	87.63	-3.96	-87.63	Peak
2	0.0204	22.19	-61.74	-39.55	41.39	80.94	-10.11	-80.94	Peak
3	0.0353	16.87	-61.60	-44.73	36.65	81.38	-14.85	-81.38	Peak
4	0.0585	14.00	-61.60	-47.60	32.26	79.86	-19.24	-79.86	Peak
5	0.1274	11.12	-61.72	-50.60	25.51	76.11	-25.99	-76.11	Peak
6	0.1429	13.00	-61.73	-48.73	24.50	73.23	-27.00	-73.23	Peak

Note:

1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV and QP limit, AV and QP Result are deemed to comply with AV limit.
3. All 3 polarizations(Horizontal, Face-on and Face-off) of the loop antenna had been tested, but only the worst data recorded in the report.

Test Mode	Channel	Frequency Range	Verdict
BLE 1M	MCH	150kHz~490kHz	PASS




No.	Frequency	Reading Level	Correct Factor	FCC Result	FCC Limit	ISED Result	ISED Limit	Margin	Remark
	[MHz]	[dBuV]	[dB/m]	[dBuV/m]	[dBuV/m]	[dBuA/m]	[dBuA/m]	[dB]	
1	0.1964	28.73	-61.77	-33.04	21.74	87.63	-29.76	-54.78	Peak
2	0.2862	24.73	-61.81	-37.08	18.47	80.94	-33.03	-55.55	Peak
3	0.3789	24.38	-61.83	-37.45	16.03	81.38	-35.47	-53.48	Peak
4	0.4091	24.19	-61.84	-37.65	15.28	79.86	-36.22	-52.93	Peak
5	0.4292	23.86	-61.85	-37.99	14.70	76.11	-36.80	-52.69	Peak
6	0.4684	22.69	-61.87	-39.18	13.63	73.23	-37.87	-52.81	Peak

Note:

1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV and QP limit, AV and QP Result are deemed to comply with AV limit.
3. All 3 polarizations(Horizontal, Face-on and Face-off) of the loop antenna had been tested, but only the worst data recorded in the report.

Test Mode	Channel	Frequency Range	Verdict
BLE 1M	MCH	490kHz~30MHz	PASS



No.	Frequency	Reading Level	Correct Factor	FCC Result	FCC Limit	ISED Result	ISED Limit	Margin	Remark
	[MHz]	[dBuV]	[dB/m]	[dBuV/m]	[dBuV/m]	[dBuA/m]	[dBuA/m]	[dB]	
1	0.5018	20.10	-21.89	-1.79	33.59	35.38	-17.91	-35.38	Peak
2	0.5815	19.79	-21.89	-2.10	32.31	34.41	-19.19	-34.41	Peak
3	0.7586	16.12	-21.87	-5.75	30.00	35.75	-21.50	-35.75	Peak
4	0.9297	12.47	-21.87	-9.40	28.24	37.64	-23.26	-37.64	Peak
5	1.3695	10.70	-21.84	-11.14	24.87	36.01	-26.63	-36.01	Peak
6	2.6828	7.77	-21.80	-14.03	29.54	43.57	-21.96	-43.57	Peak

Note:

1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV and QP limit, AV and QP Result are deemed to comply with AV limit.
3. All 3 polarizations(Horizontal, Face-on and Face-off) of the loop antenna had been tested, but only the worst data recorded in the report.

9. AC POWER LINE CONDUCTED EMISSIONS

LIMITS


Please refer to FCC §15.207 (a)

FREQUENCY (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15 -0.5	66 - 56 *	56 - 46 *
0.50 -5.0	56.00	46.00
5.0 -30.0	60.00	50.00

TEST ENVIRONMENT


Temperature	22°C	Relative Humidity	56%
Atmosphere Pressure	101kPa	Test Voltage	AC 120V

TEST SETUP AND PROCEDURE



The EUT is put on a table of non-conducting material that is 12 mm high. The vertical conducting wall of shielding is located 40cm to the rear of the EUT. The power line of the EUT is connected to the AC mains through an Artificial Mains Network (A.M.N.). A EMI Measurement Receiver (R&S Test Receiver ESR3) is used to test the emissions from both sides of AC line. According to the requirements in Section 6.2 of ANSI C63.10-2013. Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-Peak and average detector mode. The bandwidth of EMI test receiver is set at 9kHz.


The arrangement of the equipment is installed to meet the standards and operating in a manner, which tends to maximize its emission characteristics in a normal application.

LINE L RESULTS (WORST-CASE CONFIGURATION)

Final Result

Frequency [MHz]	QuasiPeak [dBµV]	Average [dBµV]	Limit [dBµV]	Margin [dB]	Meas. Time [ms]	Bandwidth [kHz]	Line	Filter	Corr. [dB]
0.167413	---	48.89	55.09	6.20	1500.0	9.000	L1	OFF	9.6
0.167413	58.43	---	65.09	6.66	1500.0	9.000	L1	OFF	9.6
0.251988	---	24.23	51.69	27.46	1500.0	9.000	L1	OFF	9.6
0.251988	39.21	---	61.69	22.49	1500.0	9.000	L1	OFF	9.6
0.418650	---	21.02	47.48	26.45	1500.0	9.000	L1	OFF	9.6
0.418650	33.06	---	57.48	24.41	1500.0	9.000	L1	OFF	9.6
0.622625	---	17.81	46.00	28.19	1500.0	9.000	L1	OFF	9.6
0.622625	33.64	---	56.00	22.36	1500.0	9.000	L1	OFF	9.6
0.664913	---	17.98	46.00	28.02	1500.0	9.000	L1	OFF	9.6
0.664913	33.67	---	56.00	22.33	1500.0	9.000	L1	OFF	9.6
0.766900	---	20.93	46.00	25.07	1500.0	9.000	L1	OFF	9.6
0.766900	33.40	---	56.00	22.60	1500.0	9.000	L1	OFF	9.6

Note:

1. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.
2. Test setup: RBW: 200 Hz (9 kHz—150 kHz), 9 kHz (150 kHz—30 MHz).
3. Step size: 80Hz (0.009MHz-0.15MHz), 4 kHz (0.15MHz-30MHz), Scan time: auto.
4. The extension cord/outlet strip was calibrated with the LISN as required by ANSI C63.10:2013 Clause 6.2.2.
5. Pre-testing all test modes and channels and find the MCH of BLE 1M which is the worst case, so only the worst case is included in this test report.

LINE N RESULTS (WORST-CASE CONFIGURATION)

Final Result

Frequency [MHz]	QuasiPeak [dB μ V]	Average [dB μ V]	Limit [dB μ V]	Margin [dB]	Meas. Time [ms]	Bandwidth [kHz]	Line	Filter	Corr. [dB]
0.167413	---	49.31	55.09	5.78	1500.0	9.000	N	OFF	9.5
0.167413	59.19	---	65.09	5.90	1500.0	9.000	N	OFF	9.5
0.659938	---	18.30	46.00	27.70	1500.0	9.000	N	OFF	9.6
0.659938	33.98	---	56.00	22.02	1500.0	9.000	N	OFF	9.6
0.809188	---	17.90	46.00	28.10	1500.0	9.000	N	OFF	9.6
0.809188	34.22	---	56.00	21.78	1500.0	9.000	N	OFF	9.6
0.878838	---	13.19	46.00	32.81	1500.0	9.000	N	OFF	9.6
0.878838	27.29	---	56.00	28.71	1500.0	9.000	N	OFF	9.6
1.229575	---	8.38	46.00	37.62	1500.0	9.000	N	OFF	9.6
1.229575	17.59	---	56.00	38.41	1500.0	9.000	N	OFF	9.6
1.540513	---	7.12	46.00	38.88	1500.0	9.000	N	OFF	9.6
1.540513	14.19	---	56.00	41.81	1500.0	9.000	N	OFF	9.6

Note:

1. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.
2. Test setup: RBW: 200 Hz (9 kHz—150 kHz), 9 kHz (150 kHz—30 MHz).
3. Step size: 80Hz (0.009MHz-0.15MHz), 4 kHz (0.15MHz-30MHz), Scan time: auto.
4. The extension cord/outlet strip was calibrated with the LISN as required by ANSI C63.10:2013 Clause 6.2.2.
5. Pre-testing all test modes and channels and find the MCH of BLE 1M which is the worst case, so only the worst case is included in this test report.

10. ANTENNA REQUIREMENTS

APPLICABLE REQUIREMENTS

Please refer to FCC §15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Please refer to FCC §15.247(b)(4)

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

ANTENNA GAIN

The antenna gain of EUT is less than 6 dBi

END OF REPORT