

RF Test Data for Bluetooth (BDR+EDR) (Conducted Measurements)

General Description of EUT	
Product Name:	SmartWatch
Test Model:	T3MAX
Sample ID:	202307-0081-1-2#
Environmental Conditions	
Temperature:	25℃
Relative Humidity:	55%
Test Voltage:	DC 3.7V
Test Engineer:	Huang jian ping
Note: For a more detailed features description, please refer to the report TBR-C-202307-0081-31 The report only show the worst case data.	

Contents


1. -20dB Emission Bandwidth.....	3
1.1. Test Result	3
1.2. Test Graphs	4
2. Occupied Channel Bandwidth.....	7
2.1. Test Result	7
2.2. Test Graphs	8
3. Maximum conducted output power	11
3.1. Test Result	11
3.2. Test Graphs	12
4. Carrier frequency separation	15
4.1. Test Result	15
4.2. Test Graphs	16
5. Time of occupancy	17
5.1. Test Result	17
5.2. Test Graphs	18
6. Number of hopping channels.....	21
6.1. Test Result	21
6.2. Test Graphs	22
7. Band edge measurements	23
7.1. Test Result	23
7.2. Test Graphs	24
8. Conducted Spurious Emission	28
8.1. Test Result	28
8.2. Test Graphs	29
9. Duty Cycle.....	38
9.1. Test Result	38
9.2. Test Graphs	39
10. Emissions in Restricted Bands	42
10.1. Test Result	42
10.2. Test Graphs	44

1. -20dB Emission Bandwidth

1.1. Test Result

TestMode	Antenna	Channel	-20db EBW[MHz]	Limit[MHz]	Verdict
DH5	Ant1	2402	1.04	---	---
		2441	1.05	---	---
		2480	1.05	---	---
2DH5	Ant1	2402	1.34	---	---
		2441	1.34	---	---
		2480	1.35	---	---
3DH5	Ant1	2402	1.30	---	---
		2441	1.30	---	---
		2480	1.29	---	---


1.2. Test Graphs




2DH5_Ant1_2402




2DH5_Ant1_2441



2DH5_Ant1_2480




3DH5_Ant1_2402



3DH5_Ant1_2441



3DH5_Ant1_2480



2. Occupied Channel Bandwidth


2.1. Test Result

TestMode	Antenna	Channel	OCB [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
DH5	Ant1	2402	0.95	2401.4306	2402.3806	---	---
		2441	0.965	2440.4246	2441.3896	---	---
		2480	0.974	2479.4156	2480.3896	---	---
2DH5	Ant1	2402	1.214	2401.3137	2402.5275	---	---
		2441	1.229	2440.3077	2441.5365	---	---
		2480	1.247	2479.2957	2480.5425	---	---
3DH5	Ant1	2402	1.217	2401.2987	2402.5155	---	---
		2441	1.223	2440.2957	2441.5185	---	---
		2480	1.226	2479.2957	2480.5215	---	---


2.2. Test Graphs




2DH5_Ant1_2402




2DH5_Ant1_2441



2DH5_Ant1_2480




3DH5_Ant1_2402



3DH5_Ant1_2441



3DH5_Ant1_2480



3. Maximum conducted output power

3.1. Test Result

TestMode	Antenna	Channel	Result[dBm]	Limit[dBm]	Verdict
DH5	Ant1	2402	0.98	≤20.97	PASS
		2441	0.92	≤20.97	PASS
		2480	0.66	≤20.97	PASS
2DH5	Ant1	2402	1.76	≤20.97	PASS
		2441	1.52	≤20.97	PASS
		2480	1.32	≤20.97	PASS
3DH5	Ant1	2402	2.24	≤20.97	PASS
		2441	1.72	≤20.97	PASS
		2480	1.81	≤20.97	PASS

3.2.Test Graphs




2DH5_Ant1_2402




2DH5_Ant1_2441




2DH5_Ant1_2480




3DH5_Ant1_2402



3DH5_Ant1_2441



3DH5_Ant1_2480



4. Carrier frequency separation

4.1. Test Result

TestMode	Antenna	Channel	Result[MHz]	Limit[MHz]	Verdict
DH5	Ant1	Hop	1.023	≥ 0.700	PASS
2DH5	Ant1	Hop	1.046	≥ 0.900	PASS
3DH5	Ant1	Hop	1.041	≥ 0.867	PASS

4.2.Test Graphs




5. Time of occupancy


5.1. Test Result

TestMode	Antenna	Channel	BurstWidth [ms]	TotalHops [Num]	Result[s]	Limit[s]	Verdict
DH1	Ant1	Hop	0.373	320	0.119	≤0.4	PASS
DH3	Ant1	Hop	1.621	160	0.259	≤0.4	PASS
DH5	Ant1	Hop	2.862	106.67	0.305	≤0.4	PASS
2DH1	Ant1	Hop	0.383	320	0.123	≤0.4	PASS
2DH3	Ant1	Hop	1.626	160	0.26	≤0.4	PASS
2DH5	Ant1	Hop	2.868	106.67	0.306	≤0.4	PASS
3DH1	Ant1	Hop	0.384	320	0.123	≤0.4	PASS
3DH3	Ant1	Hop	1.625	160	0.26	≤0.4	PASS
3DH5	Ant1	Hop	2.869	106.67	0.306	≤0.4	PASS


5.2.Test Graphs




2DH1_Ant1_Hop




2DH3_Ant1_Hop




2DH5_Ant1_Hop




3DH1_Ant1_Hop



3DH3_Ant1_Hop



3DH5_Ant1_Hop




6. Number of hopping channels

6.1. Test Result

TestMode	Antenna	Channel	Result[Num]	Limit[Num]	Verdict
DH5	Ant1	Hop	79	≥15	PASS
2DH5	Ant1	Hop	79	≥15	PASS
3DH5	Ant1	Hop	79	≥15	PASS

6.2.Test Graphs





7. Band edge measurements


7.1. Test Result

TestMode	Antenna	ChName	Channel	RefLevel [dBm]	Result [dBm]	Limit [dBm]	Verdict
DH5	Ant1	Low	2402	0.93	-50.76	≤-19.07	PASS
		High	2480	0.26	-51.59	≤-19.74	PASS
		Low	Hop_2402	0.23	-53.09	≤-19.77	PASS
		High	Hop_2480	-0.07	-52.26	≤-20.07	PASS
2DH5	Ant1	Low	2402	0.84	-50.14	≤-19.16	PASS
		High	2480	-0.06	-51.12	≤-20.06	PASS
		Low	Hop_2402	-0.49	-53.24	≤-20.49	PASS
		High	Hop_2480	-0.30	-52.11	≤-20.3	PASS
3DH5	Ant1	Low	2402	0.51	-51.87	≤-19.49	PASS
		High	2480	-0.17	-51.14	≤-20.17	PASS
		Low	Hop_2402	-2.89	-52.22	≤-22.89	PASS
		High	Hop_2480	0.21	-52.74	≤-19.79	PASS


7.2. Test Graphs








2DH5_Ant1_High_Hop_2480



3DH5_Ant1_Low_2402



3DH5_Ant1_High_2480