

# Radio Test Report

Report No: STS2307076H01

Issued for

Shenzhen Lexqi Electronic Technology Co.,Ltd

12F, Building D, Huilongda Industrial Park, Shilong  
Community, Shiyan Street, Baoan District, Shenzhen

**Product Name:** smart watch

**Brand Name:** Biaoniu

**Model Name:** H23

**FCC ID:** 2BB8OH23

**Test Standard:** FCC 47CFR §2.1093

Any reproduction of this document must be done in full. No single part of this document may be reproduced without permission from STS, all test data presented in this report is only applicable to presented test sample.



## Test Report Certification

**Applicant's Name**.....: Shenzhen Lexqi Electronic Technology Co.,Ltd  
Address .....: 12F, Building D, Huilongda Industrial Park, Shilong  
Community, Shiyan Street, Baoan District, Shenzhen

**Manufacturer's Name** .....: Shenzhen Dashengzheng Electronic Co.,Ltd  
Address .....: 12F, Building D, Huilongda Industrial Park, Shilong  
Community, Shiyan Street, Baoan District, Shenzhen

### Product Description

Product Name.....: smart watch

Brand .....: Biaoniu

Model Name .....: H23

**Standards** .....: FCC 47CFR §2.1093  
447498 D04 Interim General RF Exposure Guidance v01

This report shall not be reproduced except in full, without the written approval of STS, this document  
only be altered or revised by STS, personal only, and shall be noted in the revision of the document.

**Date of Test** .....:

Date of receipt of test item .....: 18 July 2023

Date (s) of performance of tests .....: 18 July 2023 ~ 20 July 2023

Date of Issue .....: 20 July 2023

Test Result .....: **Pass**

Testing Engineer : *Aaron Bu*

(Aaron Bu)

Technical Manager : *Sean She*

(Sean she)

Authorized Signatory : *Chris Chen*

(Chris Chen)





## TABLE OF CONTENTS

<b>1. GENERAL INFORMATION</b>	<b>5</b>
1.1 GENERAL DESCRIPTION OF THE EUT	5
1.2 TEST FACTORY	5
<b>2. FCC 47CFR §2.1093 REQUIREMENT</b>	<b>6</b>
2.1 TEST STANDARDS	6
2.2 LIMIT	6
2.3 TEST RESULT	9

**Revision History**

Rev.	Issue Date	Report No.	Effect Page	Contents
00	20 July 2023	STS2307076H01	ALL	Initial Issue



## 1. GENERAL INFORMATION

### 1.1 GENERAL DESCRIPTION OF THE EUT

Product Name	smart watch								
Brand	Biaoniu								
Model Number	H23								
Series Model(s)	H22,H26,H27,H28,H29								
Model Difference	Only the appearance is different								
Product Description	<p>The EUT is smart watch.</p> <table border="1"><tr><td>Operation Frequency:</td><td>2402~2480 MHz</td></tr><tr><td>Modulation Type:</td><td>BT BR(1Mbps): GFSK BT EDR(2Mbps): π/4-DQPSK BT EDR(3Mbps): 8DPSK BLE: GFSK</td></tr><tr><td>Antenna gain:</td><td>2.02dBi</td></tr><tr><td>Antenna Designation:</td><td>Monopole Type</td></tr></table>	Operation Frequency:	2402~2480 MHz	Modulation Type:	BT BR(1Mbps): GFSK BT EDR(2Mbps): π/4-DQPSK BT EDR(3Mbps): 8DPSK BLE: GFSK	Antenna gain:	2.02dBi	Antenna Designation:	Monopole Type
Operation Frequency:	2402~2480 MHz								
Modulation Type:	BT BR(1Mbps): GFSK BT EDR(2Mbps): π/4-DQPSK BT EDR(3Mbps): 8DPSK BLE: GFSK								
Antenna gain:	2.02dBi								
Antenna Designation:	Monopole Type								
Rating	Input :5V/230mA								
Hardware Version	MOY.M81006.02								
Software Version	MOY-DHO3-2.04								

### 1.2 TEST FACTORY

SHENZHEN STS TEST SERVICES CO., LTD

Add. : 101, Building B, Zhuoke Science Park, No.190 Chongqing Road, ZhanChengShequ, Fuhai Sub-District, Bao'an District, Shenzhen, Guang Dong, China

FCC test Firm Registration Number: 625569

IC test Firm Registration Number: 12108A

A2LA Certificate No.: 4338.01



## 2. FCC 47CFR §2.1093 REQUIREMENT

### 2.1 TEST STANDARDS

Follow the maximum permissible exposure (MPE) limits specified in 447498 D04 Interim General Radio Frequency Exposure Guidelines v01. The gain of the antenna used in the product was extracted from the supplied antenna data sheet and the maximum total power input to the antenna was also measured. Calculate the distance from the product to the MPE limit by the formula.

### 2.2 LIMIT

For single RF sources (i.e., any single fixed RF source, mobile device, or portable device, as defined in paragraph (b)(2) of this section): A single RF source is exempt if:

(A) The available maximum time-averaged power is no more than 1 mW, regardless of separation distance. This exemption may not be used in conjunction with other exemption criteria other than those in paragraph (b)(3)(ii)(A) of Part 1.1307. Medical implant devices may only use this exemption and that in paragraph (b)(3)(ii)(A);

(B) Or the available maximum time-averaged power or effective radiated power (ERP), whichever is greater, is less than or equal to the threshold  $P_{th}$  (mW) described in the following formula. This method shall only be used at separation distances (cm) from 0.5 centimeters to 40 centimeters and at frequencies from 0.3 GHz to 6 GHz (inclusive).  $P_{th}$  is given by:

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

Where

$$x = -\log_{10} \left( \frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right) \text{ and } f \text{ is in GHz;}$$

and

$$ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

$d$  = the separation distance (cm);



(C) Or using below table and the minimum separation distance (R in meters) from the body of a nearby person for the frequency (f in MHz) at which the source operates, the ERP (watts) is no more than the calculated value prescribed for that frequency. For the exemption in Table 1 to apply, R must be at least  $\lambda/2\pi$ , where  $\lambda$  is the free-space operating wavelength in meters. If the ERP of a single RF source is not easily obtained, then the available maximum time-averaged power may be used in lieu of ERP if the physical dimensions of the radiating structure(s) do not exceed the electrical length of  $\lambda/4$  or if the antenna gain is less than that of a half-wave dipole (1.64 linear value).

RF Source frequency (MHz)	Threshold ERP(watts)
0.3-1.34	$1,920 R^2$ .
1.34-30	$3,450 R^2/f^2$ .
30-300	$3.83 R^2$ .
300-1,500	$0.0128 R^2f$ .
1,500-100,000	$19.2R^2$ .



For multiple RF sources: Multiple RF sources are exempt if:

(A) The available maximum time-averaged power of each source is no more than 1 mW and there is a separation distance of two centimeters between any portion of a radiating structure operating and the nearest portion of any other radiating structure in the same device, except if the sum of multiple sources is less than 1 mW during the time-averaging period, in which case they may be treated as a single source (separation is not required). This exemption may not be used in conjunction with other exemption criteria other than those in paragraph (b)(3)(i)(A) of Part 1.1307. Medical implant devices may only use this exemption and that in paragraph (b)(3)(i)(A).

(B) in the case of fixed RF sources operating in the same time-averaging period, or of multiple mobile or portable RF sources within a device operating in the same time averaging period, if the sum of the fractional contributions to the applicable thresholds is less than or equal to 1 as indicated in the following equation.

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure\ Limit_k} \leq 1$$

Where:

a = number of fixed, mobile, or portable RF sources claiming exemption using paragraph (b)(3)(i)(B) of Part 1.1307 for  $P_{th,i}$ , including existing exempt transmitters and those being added.

b = number of fixed, mobile, or portable RF sources claiming exemption using paragraph (b)(3)(i)(C) of Part 1.1307 for Threshold ERP, including existing exempt transmitters and those being added.

c = number of existing fixed, mobile, or portable RF sources with known evaluation for the specified minimum distance including existing evaluated transmitters.

$P_i$  = the available maximum time-averaged power or the ERP, whichever is greater, for fixed, mobile, or portable RF source  $i$  at a distance between 0.5 cm and 40 cm (inclusive).

$P_{th,i}$  = the exemption threshold power ( $P_{th,i}$ ) according to paragraph (b)(3)(i)(B) of this section for fixed, mobile, or portable RF source  $i$ .

$ERP_j$  = the ERP of fixed, mobile, or portable RF source  $j$ .

$ERP_{th,j}$  = exemption threshold ERP for fixed, mobile, or portable RF source  $j$ , at a distance of at least  $\lambda/2\pi$  according to the applicable formula of paragraph (b)(3)(i)(C) of Part 1.1307.

$Evaluated_k$  = the maximum reported SAR or MPE of fixed, mobile, or portable RF source  $k$  either in the device or at the transmitter site from an existing evaluation at the location of exposure.

$Exposure\ Limit_k$  = either the general population/uncontrolled maximum permissible exposure (MPE) or specific absorption rate (SAR) limit for each fixed, mobile, or portable RF source  $k$ , as applicable from § 1.1310.



## 2.3 TEST RESULT

Turn up

Mode	Detector	Turn up Power
BT	AV	0.5±1dBm
BLE	AV	0±1dBm

Protocol	Fre. (GHz)	Separation distance (cm)	Max Turn up power (dBm)	ANT Gain ( dBi)	Max EIRP (dBm)	Max EIRP (mW)	Limit (mW)	Ratio	Result
BT	2.402	0.5	1.5	2.02	3.52	2.249	2.788	0.807	Pass
BLE	2.402	0.5	1	2.02	3.02	2.004	2.788	0.719	Pass

Note: 1. The Maximum power is less than the limit, complies with the exemption requirements.

\*\*\*\*\*END OF THE REPORT\*\*\*\*\*