



Lejin RF

Shenzhen Lejin radio frequency technology Co., LTD

SPECIFICATIONS FOR APPROVAL

Customer Name: Sorenson Communications, LLC

Product Name: 2.4G Antenna

Product Model: P3

Part Number: LJT02-23112508-R0A

Write By : Mingjin Li

Issued Date: 2023-11-25

CUSTOMER

ENGINEER R&D DEPT	BUSSINESS DEPT	APPROVAL

LEJIN

R&D DEPT	ENGINEER DEPT	APPROVAL

REV	MODIFIED DESCRIPTION	DATE	REMARK
V1.0	Initial Draft Release	2023/11/25	



Lejin RF

Shenzhen Lejin radio frequency technology Co., LTD

Index

1. Cover	1
2. Index	2
3. Product Specification	3
4. Test Equipment & Conditions	3
5. Test Report	4
6. Reliability Test	5
7. Assemble type	5
8. Product Drawing	6



Lejin RF

Shenzhen Lejin radio frequency technology Co., LTD

3. Product Specification

A. Electrical Characteristics	
Frequency	2400MHz ~2525 MHz
VSWR	<2.0
Efficiency	≥40%
Impedance	50Ohm
Polarization	Linear
Gain(2.4G)	≤2.07dB
B. Material & Mechanical Characteristics	
Material of Radiator	Copper tube
Cable Type	Φ1.13mm,L70mm,black
Connector Type	IPX1
Dimension	Φ4.4mm*24.0mm
C. Environmental	
Operation Temperature	- 20 °C ~ + 70 °C
Storage Temperature	- 30 °C ~ + 85 °C
Humidity	40%~95%

4. Test Equipment & Conditions

1. Network Analyzers Agilent 8753D/5071C

2. HSPA and LTE protocol test set R&S CMW500 -PT

3. Communications Test Set Agilent 8960

4. 3D Chamber Test System




Chart 1 Test topology



Lejin RF

Shenzhen Lejin radio frequency technology Co., LTD

5. Test Report

5.1 Voltage Standing Wave Ratio(VSWR).




Chart 2 VSWR

5.2 Efficient and gain.

Passive	Freq(MHz)	2400	2410	2420	2430	2440	2450	2460	2470	2480	2490	2500	2510	2520	2530
Test For	Effi(%)	57.66	63.34	56.48	57.02	59.82	59.12	55.64	60.81	55.18	50.44	51.01	49.47	53.37	51.65
2.4GHz	Gain(dBi)	1.93	1.97	1.86	2.02	2.07	2.02	1.91	1.83	1.85	1.85	1.87	1.85	1.79	1.88



6. Reliability Test

Test Item		Test condition	Equipment	Specification	Result
1	Low Temp. Storage Test	Temperature: -30°C, Time:48hrs Test condition: Placing antenna in a Low/High Temperature Chamber, keep the temp is 25 °C and humidity is 65% for one hour, then step-down the temp. to -30 °C in one hour, store antenna for 44 hours; step-up temp to 25°C,test antenna after 2 hours.	Temp.&Hum. Tester	No material deformation is allowed. Electronic Performance is ok .	PASS
2	High Temp./High Humid Storage Test	Temperature: 85°C Humidity: 85% RH Time:48hrs Test condition: Placing antenna in a Low/High Temperature Chamber, keep the temp is 25 °C and humidity is 65% for one hour, then step-up the temp. to 80 °C and the humidity up to 85% in one hour, store antenna for 44 hours; step-down temp to 25 °C ,test antenna after 2 hours.	Temp.&Hum. Tester	No material deformation is allowed. Electronic Performance is ok .	PASS
3	Salt-Spray 6 pray Test	Placing antenna in the Salt-Spray Tester ,set the test condition , Temp: 35 ± 2 °C Humidity: 85% NaCl salt spray : 5 ± 1 %.PH value :6.5~7.2 Testtime:24hours	Salt-Spray Tester	No color change No appear rusting	PASS


7. Assemble type

8. Product Drawing



线材焊钢管图

Unit: mm



	深圳市乐进射频科技有限公司					
	④	Third Angle	Project	ALK	Date	2023-11-25
	0~10	±0.05	①	0.02	Part Name	Designed by
	10~18	±0.10	②	0.03	Part No.	Checked by
	18~30	±0.12	③	0.02	Material	RF
	30~40	±0.15	④	0.04	DWG No.	Approved by
	40~	±0.20	Angle	±0.5°		Unit mm Scale 1:1 Rev A
Rev	Description		Date	Remark	Location	
1	2	3	4	5	6	7
						8