



BUREAU  
VERITAS

Test Report No.: PSU-QSU2306120115EM01



Certificate #6613.01

## EMC TEST REPORT

Applicant:	Unplugged Technologies Ltd.
Address:	3 Hakidma St., Yokneam 2066731, Israel

Manufacturer or Supplier:	Unplugged Technologies Ltd.
Address:	3 Hakidma St., Yokneam 2066731, Israel
Product:	UP Phone 1
Brand Name:	UP Phone
Model Name:	UP01
FCC ID:	2BBCUP01
Date of tests:	Jul. 03, 2023 ~Sep. 28, 2023

The submitted sample of the above equipment has been tested for according to the requirements of the following standards:

- FCC Part 15, Subpart B, Class A  
 FCC Part 15, Subpart B, Class B  
 ANSI C63.4:2014

**CONCLUSION: The submitted sample was found to COMPLY with the test requirement**

Prepared by Chao Wu Engineer / Mobile Department	Approved by Peibo Sun Manager / Mobile Department

Date: Sep. 28, 2023

Date: Sep. 28, 2023

This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.



BUREAU  
VERITAS

Test Report No.: PSU-QSU2306120115EM01

## TABLE OF CONTENTS

<b>TABLE OF CONTENTS .....</b>	<b>2</b>
<b>RELEASE CONTROL RECORD .....</b>	<b>3</b>
<b>1 GENERAL INFORMATION .....</b>	<b>4</b>
1.1 GENERAL DESCRIPTION OF EUT .....	4
1.2 SUMMARY OF TEST RESULTS .....	8
1.3 MEASUREMENT UNCERTAINTY .....	9
1.4 DESCRIPTION OF TEST MODES .....	10
1.5 DESCRIPTION OF SUPPORT UNITS .....	12
<b>2 EMISSION TEST .....</b>	<b>13</b>
2.1 CONDUCTED EMISSION MEASUREMENT .....	13
2.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT .....	13
2.1.2 TEST INSTRUMENTS .....	13
2.1.3 TEST PROCEDURES .....	14
2.1.4 DEVIATION FROM TEST STANDARD .....	14
2.1.5 TEST SETUP .....	15
2.1.6 EUT OPERATING CONDITIONS .....	15
2.1.7 TEST RESULTS .....	16
2.2 RADIATED EMISSION MEASUREMENT .....	18
2.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT .....	18
2.2.2 TEST INSTRUMENTS .....	19
2.2.3 TEST PROCEDURE .....	20
2.2.4 DEVIATION FROM TEST STANDARD .....	21
2.2.5 TEST SETUP .....	22
2.2.6 EUT OPERATING CONDITIONS .....	23
2.2.7 TEST RESULTS .....	24
<b>3 APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB .....</b>	<b>28</b>



BUREAU  
VERITAS

Test Report No.: PSU-QSU2306120115EM01

## RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
PSU-QSU2306120115EM01	Original release	Sep. 28, 2023



BUREAU  
VERITAS

Test Report No.: PSU-QSU2306120115EM01

## 1 GENERAL INFORMATION

### 1.1 GENERAL DESCRIPTION OF EUT

PRODUCT*	UP Phone 1	
BRAND NAME*	UP Phone	
MODEL NAME*	UP01	
NOMINAL VOLTAGE*	3.87Vdc (Battery)	
MODULATION TYPE*	BT_LE	GFSK
	Bluetooth	GFSK, π/4-DQPSK, 8DPSK
	FM	FM
	NFC	ASK
	WLAN	DSSS, OFDM, OFDMA
	GPS/GALILEO/GLOASS/BDS	BPSK
	GSM/GPRS/EDGE	GMSK, 8PSK
	WCDMA	BPSK/QPSK
	LTE	QPSK/16QAM/64QAM
	5G NR	DFT-s-OFDM(π/2BPSK,QPSK,16QAM,64QAM,256QAM); CP-OFDM(QPSK,16QAM,64QAM,256QAM);
OPERATING FREQUENCY*	Bluetooth/BT_LE	2402MHz ~ 2480MHz
	FM	87.5MHz ~ 108MHz
	NFC	13.56 MHz
	WLAN	2412 ~ 2462MHz for 11b/g/n(HT20/40)/ax(20/40) 5180 ~ 5240MHz, 5260 ~ 5320 MHz, 5745 ~ 5825 MHz for 11a/ n(HT20)/ n(HT40) / ac(VHT20)/ ac(VHT40) / ac(VHT80)/ ax(20/40/80)
	GPS/GALILEO/GLOASS/BDS	1559MHz ~ 1610MHz
	GSM	824.2MHz ~ 848.8MHz (FOR GSM 850) 1850.2MHz ~ 1909.8MHz (FOR GSM 1900)



BUREAU  
VERITAS

Test Report No.: PSU-QSU2306120115EM01

OPERATING FREQUENCY	WCDMA	1852.4MHz ~ 1907.6MHz (FOR WCDMA Band 2) 1712.4MHz ~ 1752.6MHz (FOR WCDMA Band 4) 826.4MHz ~ 846.6MHz (FOR WCDMA Band 5)
	LTE	1850.7MHz ~ 1909.3MHz (FOR LTE Band2) 1710.7MHz ~ 1754.3MHz (FOR LTE Band4) 824.7MHz ~ 848.3MHz (FOR LTE Band5) 2502.5MHz ~ 2567.5MHz (FOR LTE Band7) 699.7MHz ~ 715.3MHz (FOR LTE Band12) 779.5MHz ~ 784.5MHz (FOR LTE Band13) 706.5MHz ~ 713.5MHz (FOR LTE Band17) 1850.7MHz ~ 1914.3MHz (FOR LTE Band25) 814.7MHz ~ 848.3MHz (FOR LTE Band26) 2572.5MHz ~ 2617.5MHz (FOR LTE Band38) 2498.5MHz ~ 2687.5MHz (FOR LTE Band41) 3452.5MHz ~ 3597.5MHz (FOR LTE Band42) 3602.5MHz ~ 3697.5MHz (FOR LTE Band43) 3552.5MHz ~ 3697.5MHz (FOR LTE Band48) 1710.7MHz ~ 1779.3MHz (FOR LTE Band66) 665.5MHz ~ 695.5MHz (FOR LTE Band71) CA_B2-B4 CA_B2-B5 CA_B2-B12 CA_B2-B13 CA_B2-B66 CA_B4-B5 CA_B4-B12 CA_B4-B13 CA_B5-B66 CA_B12-B66 CA_B13-B66
	5G NR	<b>SA/NSA:</b> n2 (1852.5MHz ~ 1907.5MHz) n5 (826.5MHz ~ 846.5MHz) n7 (2502.5MHz ~ 2567.5MHz) n12 (701.5MHz ~ 713.5MHz) n25 (1852.5MHz ~ 1912.5MHz) n38 (2575MHz ~ 2615MHz) n41 (2501.01 ~ 2685MHz) n48 (3555 ~ 3694.98MHz) n66 (1712.5 ~ 1777.5MHz) n71 (665.5 ~ 695.5MHz) n77 (Part27Q) (3455.01 ~ 3544.98MHz) n77 (Part27O) (3705 ~ 3974.97MHz) n78 (Part27Q) (3455.01 ~ 3544.98MHz)



BUREAU  
VERITAS

Test Report No.: PSU-QSU2306120115EM01

	<p>n78(Part 27O) (3705 ~ 3794.97MHz)</p> <p><b>NSA:</b></p> <p>DC_B2-N5 DC_B13-N2 DC_B2-N41 DC_B2-N66 DC_N2-B66 DC_B2-N71 DC_B2-N77 DC_B3-N41 DC_B66-N5 DC_B13-N66 DC_N25-B66 DC_B41-N41 DC_B66-N41 DC_B66-N71 DC_B2-N77</p> <p><b>CA:</b></p> <p>CA_N2-N48 CA_N2-N77 CA_N5-N48 CA_N5-N66 CA_N5+N77 CA_N48-N66 CA_N66-N71</p>
<b>HW VERSION*</b>	M156-MUB-V2
<b>SW VERSION*</b>	NR_D011.13_N_UP01_1.000.01
<b>I/O PORTS*</b>	Refer to user's manual
<b>CABLE SUPPLIED*</b>	N/A
<b>ACCESSORY DEVICES*</b>	Refer to note as below

**NOTE:**

1. \*Since the above data and/or information is provided by the client relevant results or conclusions of this report are only made for these data and/or information, Test Lab is not responsible for the authenticity, integrity and results of the data and information and/or the validity of the conclusion.
2. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
3. For the test results, the EUT had been tested with all conditions. But only the worst case was shown in the test report.



BUREAU  
VERITAS

Test Report No.: PSU-QSU2306120115EM01

**List of Accessory:**

ACCESSORIES	Brand	MODEL / SPECIFICATION
CPU	MediaTek	MT6893
eMMC 1 (=ROM 1)	Sandisk	SDINFDK4-256G
eMMC 2 (=ROM 2)	Samsung	KLUEG4RHGB-B0E1
eMMC 3 (=ROM 3)	Samsung	KLUEG4RHGB-B0E1
eMMC 4 (=ROM 4)	Samsung	KLUEG4RHGB-B0E1
RAM 1	Hynix	H9HKNNNFBNMAVAR-NEH
RAM 2	Samsung	K3UH7H70BM-AGCL
BT/WLAN Module	MediaTek	/
NFC chipset	ST	/
Battery	/	Power Rating: 16.98Wh



BUREAU  
VERITAS

Test Report No.: PSU-QSU2306120115EM01

## 1.2 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 15, Subpart B			
Standard Section	Test Item	Result	Test lab*
FCC Part 15, Subpart B, Class B ANSI C63.4:2014	Conducted Test	Compliance	A
	Radiated Emission Test (30MHz ~ 1GHz)	Compliance	A
	Radiated Emission Test (Above 1GHz)	Compliance	A

### \*Test Lab Information Reference

#### Lab A:

Huarui 7Layers High Technology (Suzhou) Co., Ltd.

#### Lab Address:

Tower N, Innovation Center, 88 Zhuyi Road, High-tech District, Suzhou City, Anhui Province

#### Accredited Test Lab Cert 6613.01

The FCC Site Registration No. is 434559; The Designation No. is CN1325.



BUREAU  
VERITAS

Test Report No.: PSU-QSU2306120115EM01

### 1.3 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of  $k=2$ .

MEASUREMENT	FREQUENCY	UNCERTAINTY
Conducted emissions	150kHz ~ 30MHz	±2.70dB
	30MHz~1GHz	±4.98dB
	1GHz ~6GHz	±4.70dB
	6GHz ~18GHz	±4.60dB
	18GHz ~40GHz	±4.12dB



BUREAU  
VERITAS

Test Report No.: PSU-QSU2306120115EM01

## 1.4 DESCRIPTION OF TEST MODES

Test Mode	Test Condition
<b>Radiated emission test</b>	
1	GSM 850 Idle + USB Cable + adapter + BT Idle + wifi 2.4G idle + GPS Rx + SIM + SD
2	PCS 1900 Idle + USB Cable + adapter + BT Idle + wifi 5G idle + Glonass Rx + SIM + SD
3	WCDMA B2 idle + USB Cable + adapter + BT Idle + wifi 2.4G idle + Galileo Rx + SIM + SD + Front Camera On
4	WCDMA B4 idle + USB Cable + adapter + BT Idle + wifi 5G idle + BDS Rx + SIM + SD + Back Camera On
5	WCDMA B5 idle + USB Cable + adapter + BT Idle + wifi 2.4G idle + GPS Rx + SIM + SD + FM RX
6	LTE B7 idle + USB Cable + adapter + BT Idle + wifi 5G idle + BDS Rx + SIM + SD + MPG4
7	LTE B12 idle + USB Cable + adapter + BT Idle + wifi 2.4G idle + GPS Rx + SIM + SD + NFC
8	LTE B13 idle + USB Cable + adapter + BT Idle + wifi 5G idle + Glonass Rx + SIM + SD
9	LTE B25 idle + USB Cable + adapter + BT Idle + wifi 5G idle + BDS Rx + SIM + SD
10	LTE B26 idle + USB Cable + adapter + BT Idle + wifi 2.4G idle + GPS Rx + SIM + SD
11	LTE B41 idle + USB Cable + adapter + BT Idle + wifi 2.4G idle + Galileo Rx + SIM + SD
12	LTE B42 idle + USB Cable + adapter + BT Idle + wifi 5G idle + BDS Rx + SIM + SD
13	LTE B43 idle + USB Cable + adapter + BT Idle + wifi 2.4G idle + GPS Rx + SIM + SD
14	LTE B48 idle + USB Cable + adapter + BT Idle + wifi 5G idle + Glonass Rx + SIM + SD
15	LTE B66 idle + USB Cable + adapter + BT Idle + wifi 2.4G idle + Galileo Rx + SIM + SD
16	LTE B71 idle + USB Cable + adapter + BT Idle + wifi 5G idle + BDS Rx + SIM + SD
17	N7 idle + USB Cable + adapter + BT Idle + wifi 2.4G idle + Galileo Rx + SIM + SD
18	N12 idle + USB Cable + adapter + BT Idle + wifi 5G idle + BDS Rx + SIM + SD
19	N25 idle + USB Cable + adapter + BT Idle + wifi 2.4G idle + GPS Rx + SIM + SD
20	N41 idle + USB Cable + adapter + BT Idle + wifi 2.4G idle + Galileo Rx + SIM + SD
21	N48 idle + USB Cable + adapter + BT Idle + wifi 5G idle + BDS Rx + SIM + SD
22	N66 idle + USB Cable + adapter + BT Idle + wifi 2.4G idle + GPS Rx + SIM + SD
23	N71 idle + USB Cable + Data Transmission + Glonass Rx + SIM + EUT to Notebook + SD
24	N78 idle + USB Cable + Data Transmission + Galileo Rx + SIM + Notebook to EUT + SD



BUREAU  
VERITAS

Test Report No.: PSU-QSU2306120115EM01

Test Mode	Test Condition
<b>Conducted emission test</b>	
1	GSM 850 Idle + USB Cable + adapter + BT Idle + wifi 2.4G idle + GPS Rx + SIM + SD
2	PCS 1900 Idle + USB Cable + adapter + BT Idle + wifi 5G idle + Glonass Rx + SIM + SD
3	WCDMA B2 idle + USB Cable + adapter + BT Idle + wifi 2.4G idle + Galileo Rx + SIM + SD + Front Camera On
4	WCDMA B4 idle + USB Cable + adapter + BT Idle + wifi 5G idle + BDS Rx + SIM + SD + Back Camera On
5	WCDMA B5 idle + USB Cable + adapter + BT Idle + wifi 2.4G idle + GPS Rx + SIM + SD + FM RX
6	LTE B7 idle + USB Cable + adapter + BT Idle + wifi 5G idle + BDS Rx + SIM + SD
7	LTE B12 idle + USB Cable + adapter + BT Idle + wifi 2.4G idle + GPS Rx + SIM + SD + MPG4
8	LTE B13 idle + USB Cable + adapter + BT Idle + wifi 5G idle + Glonass Rx + SIM + SD + NFC
9	LTE B25 idle + USB Cable + adapter + BT Idle + wifi 5G idle + BDS Rx + SIM + SD
10	LTE B26 idle + USB Cable + adapter + BT Idle + wifi 2.4G idle + GPS Rx + SIM + SD
11	LTE B41 idle + USB Cable + adapter + BT Idle + wifi 2.4G idle + Galileo Rx + SIM + SD
12	LTE B42 idle + USB Cable + adapter + BT Idle + wifi 5G idle + BDS Rx + SIM + SD
13	LTE B43 idle + USB Cable + adapter + BT Idle + wifi 2.4G idle + GPS Rx + SIM + SD
14	LTE B48 idle + USB Cable + adapter + BT Idle + wifi 5G idle + Glonass Rx + SIM + SD
15	LTE B66 idle + USB Cable + adapter + BT Idle + wifi 2.4G idle + Galileo Rx + SIM + SD
16	LTE B71 idle + USB Cable + adapter + BT Idle + wifi 5G idle + BDS Rx + SIM + SD
17	N7 idle + USB Cable + adapter + BT Idle + wifi 2.4G idle + Galileo Rx + SIM + SD
18	N12 idle + USB Cable + adapter + BT Idle + wifi 5G idle + BDS Rx + SIM + SD
19	N25 idle + USB Cable + adapter + BT Idle + wifi 2.4G idle + GPS Rx + SIM + SD
20	N41 idle + USB Cable + adapter + BT Idle + wifi 2.4G idle + Galileo Rx + SIM + SD
21	N48 idle + USB Cable + adapter + BT Idle + wifi 5G idle + BDS Rx + SIM + SD
22	N66 idle + USB Cable + adapter + BT Idle + wifi 2.4G idle + GPS Rx + SIM + SD
23	N71 idle + USB Cable + Data Transmission + Glonass Rx + SIM + EUT to Notebook + SD
24	N78 idle + USB Cable + Data Transmission + Galileo Rx + SIM + Notebook to EUT + SD

**NOTE:**

1. For radiated emission test, test mode 24 was the verification case and only this mode was presented in this report
2. For conducted emission test, test mode 6 was the verification case and only this mode was presented in this report



BUREAU  
VERITAS

Test Report No.: PSU-QSU2306120115EM01

## 1.5 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

### FOR ALL TESTS

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	Laptop	Lenovo	Thinkpad E14	SL10W47313	N/A
2	Micro SD	SAM SUNG	N/A	N/A	N/A
3	FM signal generator	Rohde&Schwarz	SMB 100A	182185	N/A
4	GPS Simulator+Antenna	Rohde&Schwarz	SMBV100A	261436	N/A
5	Universal radio communication tester	Rohde&Schwarz	CMW500	169399	N/A
6	WIFI Router	HUAWEI	N/A	N/A	N/A
7	Adapter	N/A	N/A	N/A	N/A
8	USB Cable	N/A	N/A	N/A	N/A

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	USB Line: Shielded, Detachable 1m;



BUREAU  
VERITAS

Test Report No.: PSU-QSU2306120115EM01

## 2 EMISSION TEST

### 2.1 CONDUCTED EMISSION MEASUREMENT

#### 2.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

##### TEST STANDARD: FCC Part 15, Subpart B (Section: 15.107 a CLASS B)

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dB $\mu$ V)	
	Quasi-peak	Average
0.15 ~ 0.5	66 to 56	56 to 46
0.5 ~ 5	56	46
5 ~ 30	60	50

##### TEST STANDARD: FCC Part 15, Subpart B (Section: 15.107 b CLASS A)

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dB $\mu$ V)	
	Quasi-peak	Average
0.15 ~ 0.5	79	66
0.5 ~ 30	73	60

**NOTE:** 1. The lower limit shall apply at the transition frequencies.

2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.
3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

#### 2.1.2 TEST INSTRUMENTS

Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Due Date
EMI Test Receiver	Rohde&Schwarz	ESR3	102749	Feb.25,22	Feb.24,24
ELEKTRA test software	Rohde&Schwarz	ELEKTRA	NA	N/A	N/A
LISN network	Rohde&Schwarz	ENV216	102640	Feb.17,22	Feb.16,24
CABLE	Rohde&Schwarz	W61.01	N/A	Apr.28,23	Oct.27,23
CABLE	Rohde&Schwarz	W601	N/A	Apr.28,23	Oct.27,23
EMI Test Receiver	Rohde&Schwarz	ESR3	102749	Feb.25,22	Feb.24,24

**NOTE:** 1. The test was performed in CE shielded room.



### 2.1.3 TEST PROCEDURES

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150 kHz to 30MHz was searched. Emission levels under (Limit - 20dB) were not recorded.


**NOTE:** All modes of operation were investigated and the worst-case emissions are reported.

### 2.1.4 DEVIATION FROM TEST STANDARD

No deviation.



## 2.1.5 TEST SETUP



**Note:**

1. Support units were connected to second LISN.
2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

For the actual test configuration, please refer to the attached file (Test Setup Photo).

## 2.1.6 EUT OPERATING CONDITIONS

- a. Turned on the power and connected of all equipment.
- b. EUT was operated according to the use type described in the manufacturer's specifications or the user's manual.

BUREAU  
VERITAS

Test Report No.: PSU-QSU2306120115EM01


## 2.1.7 TEST RESULTS

Worst case data:

TEST VOLTAGE	Input 120 Vac, 60 Hz		Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9 kHz	
ENVIRONMENTAL CONDITIONS	26deg. C, 51%RH		TESTED BY	Chao Wu	

Rg	Frequency [MHz]	QPK Level [dB $\mu$ V]	QPK Limit [dB $\mu$ V]	QPK Margin [dB]	CAV Level [dB $\mu$ V]	CAV AVG Limit [dB $\mu$ V]	CAV Margin [dB]	Correction [dB]	Line	Meas. BW [kHz]
1	0.182	39.32	64.42	25.10	34.49	54.42	19.93	12.20	L1	9.000
1	0.456	36.57	56.77	20.20	30.45	46.77	16.32	11.76	L1	9.000
1	1.973	34.87	56.00	21.13	21.43	46.00	24.57	11.76	L1	9.000
1	5.663	30.33	60.00	29.67	23.44	50.00	26.56	11.80	L1	9.000
1	12.548	20.99	60.00	39.01	14.63	50.00	35.37	11.84	L1	9.000
1	29.702	24.39	60.00	35.61	17.97	50.00	32.03	11.90	L1	9.000

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
  2. The emission levels of other frequencies were very low against the limit.
  3. Margin value = Limit value- Emission level
  4. Correction factor = Insertion loss + Cable loss + Attenuate
  5. Emission Level = Correction Factor + Reading Value.



BUREAU  
VERITAS

Test Report No.: PSU-QSU2306120115EM01

TEST VOLTAGE	Input 120 Vac, 60 Hz			Detector Function & Resolution Bandwidth		Quasi-Peak (QP) / Average (AV), 9 kHz		
ENVIRONMENTAL CONDITIONS	26deg. C, 51%RH			TESTED BY		Chao Wu		

Rg	Frequency [MHz]	QPK Level [dB $\mu$ V]	QPK Limit [dB $\mu$ V]	QPK Margin [dB]	CAV Level [dB $\mu$ V]	CAV AVG Limit [dB $\mu$ V]	CAV Margin [dB]	Correction [dB]	Line	Meas. BW [kHz]
1	0.155	38.14	65.75	27.61	28.63	55.75	27.12	12.14	N	9.000
1	0.506	41.28	56.00	14.72	30.21	46.00	15.79	12.78	N	9.000
1	1.338	35.96	56.00	20.04	27.17	46.00	18.83	12.74	N	9.000
1	3.633	30.92	56.00	25.08	21.72	46.00	24.28	12.75	N	9.000
1	9.011	20.58	60.00	39.42	14.18	50.00	35.82	12.79	N	9.000
1	29.913	23.37	60.00	36.63	17.07	50.00	32.93	12.88	N	9.000

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
  2. The emission levels of other frequencies were very low against the limit.
  3. Margin value = Limit value- Emission level
  4. Correction factor = Insertion loss + Cable loss + Attenuate
  5. Emission Level = Correction Factor + Reading Value.





BUREAU  
VERITAS

Test Report No.: PSU-QSU2306120115EM01

## 2.2 RADIATED EMISSION MEASUREMENT

### 2.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

#### TEST STANDARD: FCC Part 15, Subpart B (Section: 15.109)

Emissions radiated outside of the specified bands, shall be according to the general radiated limits as following:

Radiated Emissions Limits at 3 meters (dB $\mu$ V/m)		
Frequencies (MHz)	FCC 15B Class A	FCC 15B Class B
30-88	49	40
88-216	53.5	43.5
216-960	56	46
960-1000	59.5	54
Above 1000	Avg: 59.5 Peak: 79.5	Avg: 54 Peak: 74

#### Frequency Range (For unintentional radiators)

Highest frequency generated or used in the device or on which the device operates or tunes (MHz)	Upper frequency of measurement range (MHz)
Below 1.705	30
1.705-108	1000
108-500	2000
500-1000	5000
Above 1000	5 <sup>th</sup> harmonic of the highest frequency or 40GHz, whichever is lower

- NOTE:**
1. The lower limit shall apply at the transition frequencies.
  2. Emission level (dB $\mu$ V/m) = 20 log Emission level (uV/m).
  3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.
  4. QP detector shall be applied if not specified.



BUREAU  
VERITAS

Test Report No.: PSU-QSU2306120115EM01

## 2.2.2 TEST INSTRUMENTS

### Frequency range below 1GHz

Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Due Date
3m Semi-anechoic Chamber	TDK	9m*6m*6m	HRSW-SZ-EMC-02Chamber	Nov.24,22	Nov.23,25
Bilog Antenna	SCHWARZBECK	VULB 9163	1264	Feb.28,22	Feb.27,24
EMI Test Receiver	R&S	ESW44	101973	Feb.25,22	Feb.24,24
Measurement Software	R&S	ELEKTRA	N/A	N/A	N/A
Pre-Amplifier	R&S	SCU08F1	101028	Sep.16,22	Sep.15,24
CABLE	R&S	W13.01	N/A	Apr.28,23	Oct.27,23
CABLE	R&S	W13.02	N/A	Apr.28,23	Oct.27,23
CABLE	R&S	W12.14	N/A	Apr.28,23	Oct.27,23

### Frequency range above 1GHz

Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Due Date
3m Fully-anechoic Chamber	TDK	9m*6m*6m	HRSW-SZ-EMC-01Chamber	Nov.24,22	Nov.23,25
Horn Antenna	ETS-LINDGREN	3117	227836	Aug.22,22	Aug.21,24
EMI Test Receiver	R&S	ESW44	101973	Feb.25,22	Feb.24,24
Pre-Amplifier	R&S	SCU08F1	101028	Sep.16,22	Sep.15,24
Measurement Software	R&S	ELEKTRA	N/A	N/A	N/A
CABLE	R&S	W13.01	N/A	Apr.28,23	Oct.27,23
CABLE	R&S	W13.02	N/A	Apr.28,23	Oct.27,23
CABLE	R&S	W12.14	N/A	Apr.28,23	Oct.27,23

**NOTE:** 1. The calibration interval of the above test instruments is 6 months or 24 months or 36 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.

2. The test was performed in 3m Chamber.



BUREAU  
VERITAS

Test Report No.: PSU-QSU2306120115EM01

## 2.2.3 TEST PROCEDURE

### <Frequency Range below 1GHz>

The basic test procedure was in accordance with ANSI C63.4:2014 (section 12).

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from 1 meter to 4 meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1GHz.

#### NOTE:

1. The resolution bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
3. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) (if the raw value not contains the amplifier);
4. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) – Amplifier Gain(dB) (if the raw value contains the amplifier).
5. Margin value = Limit value -Emission level.



BUREAU  
VERITAS

Test Report No.: PSU-QSU2306120115EM01

### <Frequency Range above 1GHz>

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter fully-anechoic chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. The bore sight should be used during the test above 1GHz.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz

#### NOTE:

- 1.The resolution bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
- 2.The resolution bandwidth is 1MHz and video bandwidth of test receiver/spectrum analyzer is 3MHz for Peak detection at frequency above 1GHz. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and video bandwidth of test receiver/spectrum analyzer is 1Hz for Average detection (AV) at frequency above 1GHz.
- 3.For measurement of frequency above 1000 MHz, the EUT was set 3 meters away from the receiver antenna.
- 4.Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
- 5.Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) (if the raw value not contains the amplifier);
- 6.Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) – Amplifier Gain(dB) (if the raw value contains the amplifier)
- 7.Margin value = Limit value- Emission level.


### 2.2.4 DEVIATION FROM TEST STANDARD

No deviation.




## 2.2.5 TEST SETUP

<Frequency Range below 1GHz>



<Frequency Range above 1GHz>



**Note:** Above 1G is a directional antenna

depends on the EUT height and the antenna 3dB bandwidth both, refer to section 7.3 of CISPR 16-2-3.



**BUREAU  
VERITAS** Test Report No.: PSU-QSU2306120115EM01

## 2.2.6 EUT OPERATING CONDITIONS

Same as item 2.1.6.

**BUREAU  
VERITAS****Test Report No.: PSU-QSU2306120115EM01**

## 2.2.7 TEST RESULTS


**Worst case:**

<b>TEST VOLTAGE</b>	Input 120 Vac, 60 Hz	<b>FREQUENCY RANGE</b>	30-1000 MHz
<b>ENVIRONMENTAL CONDITIONS</b>	23deg. C, 70%RH	<b>DETECTOR FUNCTION &amp; RESOLUTION BANDWIDTH</b>	Quasi-Peak, 120 kHz
<b>TESTED BY</b>	Chao Wu		

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M**

Rg	Frequency [MHz]	QPK Level [dB $\mu$ V/m]	QPK Limit [dB $\mu$ V/m]	QPK Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]	Meas. BW [kHz]
1	40.282	15.89	40.00	24.11	-18.45	H	359	2	120.000
1	55.657	22.16	40.00	17.84	-18.43	H	1	2	120.000
1	123.945	22.46	43.50	21.04	-22.50	H	1	2	120.000
1	241.654	26.06	46.00	19.94	-17.16	H	277.9	1	120.000
1	499.335	15.91	46.00	30.09	-12.68	H	355	2	120.000
1	666.466	19.83	46.00	26.17	-11.27	H	1	1	120.000

- REMARKS:**
1. Peak detector quick scan is shown on the graph and final quasi-peak detector data is measured corresponding to relevant limit and recorded in the data table.
  2. Negative sign (-) in the margin column signify levels below the limit.
  3. Frequency range scanned: 30MHz to 1000MHz.
  4. Only emissions significantly above the equipment noise floor are reported.



BUREAU  
VERITAS


Test Report No.: PSU-QSU2306120115EM01

TEST VOLTAGE	Input 120 Vac, 60 Hz	FREQUENCY RANGE	30-1000 MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70 %RH	DETECTOR FUNCTION & RESOLUTION BANDWIDTH	Quasi-Peak, 120 kHz
TESTED BY	Chao Wu		

## ANTENNA POLARITY &amp; TEST DISTANCE: VERTICAL AT 3 M

Rg	Frequency [MHz]	QPK Level [dB $\mu$ V/m]	QPK Limit [dB $\mu$ V/m]	QPK Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]	Meas. BW [kHz]
1	55.657	18.29	40.00	21.71	-18.43	V	358.5	1	120.000
1	76.075	7.29	40.00	32.71	-24.10	V	88.1	2	120.000
1	125.933	14.43	43.50	29.07	-22.78	V	355.6	2	120.000
1	246.504	23.32	46.00	22.68	-16.97	V	359.1	1	120.000
1	389.725	16.39	46.00	29.61	-13.10	V	132.1	1	120.000
1	499.529	21.34	46.00	24.66	-12.67	V	0.9	2	120.000

- REMARKS:**
1. Peak detector quick scan is shown on the graph and final quasi-peak detector data is measured corresponding to relevant limit and recorded in the data table.
  2. Negative sign (-) in the margin column signify levels below the limit.
  3. Frequency range scanned: 30MHz to 1000MHz.
  4. Only emissions significantly above the equipment noise floor are reported.



BUREAU  
VERITAS

Test Report No.: PSU-QSU2306120115EM01


TEST VOLTAGE	Input 120 Vac, 60 Hz	FREQUENCY RANGE	1-18 GHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70 %RH	DETECTOR FUNCTION & RESOLUTION BANDWIDTH	Peak/Average, 1 MHz
TESTED BY	Chao Wu		

## ANTENNA POLARITY &amp; TEST DISTANCE: HORIZONTAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dB $\mu$ V/m]	PK+ Limit [dB $\mu$ V/m]	PK+ Margin [dB]	AVG Level [dB $\mu$ V/m]	AVG Limit [dB $\mu$ V/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]	Meas. BW [kHz]
1	4,533.500	47.69	74.00	26.31	34.89	54.00	19.11	11.09	H	5	1	1,000.000
1	7,467.500	53.48	74.00	20.52	39.76	54.00	14.24	16.03	H	0.9	2	1,000.000
2	16,736.000	52.12	74.00	21.88	41.55	54.00	12.45	16.06	H	12.1	2	1,000.000

**REMARKS:**

1. Peak detector quick scan is shown on the graph and final quasi-peak detector data is measured corresponding to relevant limit and recorded in the data table.
2. Negative sign (-) in the margin column signify levels below the limit.
3. Frequency range scanned: 1GHz to 5th harmonic of the highest frequency or 40GHz, whichever is lower. For frequency above 18GHz, the emission was tested 20db below the limit so the data not recorded in the sheet.
4. Only emissions significantly above the equipment noise floor are reported.





BUREAU  
VERITAS

Test Report No.: PSU-QSU2306120115EM01


TEST VOLTAGE	Input 120 Vac, 60 Hz	FREQUENCY RANGE	1-18 GHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70 %RH	DETECTOR FUNCTION & RESOLUTION BANDWIDTH	Peak/Average, 1 MHz
TESTED BY	Chao Wu		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dB $\mu$ V/m]	PK+ Limit [dB $\mu$ V/m]	PK+ Margin [dB]	AVG Level [dB $\mu$ V/m]	AVG Limit [dB $\mu$ V/m]	Avg Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]	Meas. BW [kHz]
1	4,425.000	47.85	74.00	26.15	35.18	54.00	18.82	10.72	V	0.9	2	1,000.000
1	5,656.000	48.29	74.00	25.71	35.43	54.00	18.57	12.68	V	193.3	2	1,000.000
1	7,491.000	52.71	74.00	21.29	39.75	54.00	14.25	16.13	V	355.7	2	1,000.000

**REMARKS:**

1. Peak detector quick scan is shown on the graph and final quasi-peak detector data is measured corresponding to relevant limit and recorded in the data table.
2. Negative sign (-) in the margin column signify levels below the limit.
3. Frequency range scanned: 1GHz to 5th harmonic of the highest frequency or 40GHz, whichever is lower. For frequency above 18GHz, the emission was tested 20db below the limit so the data not recorded in the sheet.
4. Only emissions significantly above the equipment noise floor are reported.





**BUREAU  
VERITAS** Test Report No.: PSU-QSU2306120115EM01

### **3 APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB**

No any modifications were made to the EUT by the lab during the test.

**---END---**