



Test Report No.: PSU-QSU2306120115RF12



Certificate #6613.01

FCC TEST REPORT

(Part 15, Subpart C)

Applicant:	Unplugged Technologies Ltd.
Address:	3 Hakidma St., Yokneam 2066731, Israel


Manufacturer or Supplier:	Unplugged Technologies Ltd.
Address:	3 Hakidma St., Yokneam 2066731, Israel
Product:	UP Phone 1
Brand Name:	UP Phone
Model Name:	UP01
FCC ID:	2BBCUP01
Date of tests:	Jul. 03, 2023 ~ Oct. 08, 2023

The tests have been carried out according to the requirements of the following standard:

FCC Part 15, Subpart C, Section 15.247

ANSI C63.10-2013

CONCLUSION: The submitted sample was found to COMPLY with the test requirement

Prepared by Chao Wu Engineer / Mobile Department	Approved by Peibo Sun Manager / Mobile Department
 Date: Oct. 08, 2023	 Date: Oct. 08, 2023

This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.



TABLE OF CONTENTS

RELEASE CONTROL RECORD	7
1 SUMMARY OF TEST RESULTS.....	8
1.1 MEASUREMENT UNCERTAINTY	9
2 GENERAL INFORMATION	10
2.1 GENERAL DESCRIPTION OF EUT	10
2.2 DESCRIPTION OF TEST MODES	12
2.2.1 CONFIGURATION OF SYSTEM UNDER TEST	13
2.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL.....	13
2.3 DUTY CYCLE OF TEST SIGNAL	17
2.4 GENERAL DESCRIPTION OF APPLIED STANDARDS	18
2.5 DESCRIPTION OF SUPPORT UNITS	18
3 TEST TYPES AND RESULTS.....	19
3.1 CONDUCTED EMISSION MEASUREMENT	19
3.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT	19
3.1.2 TEST INSTRUMENTS.....	19
3.1.3 TEST PROCEDURES	20
3.1.4 DEVIATION FROM TEST STANDARD	20
3.1.5 TEST SETUP	21
3.1.6 EUT OPERATING CONDITIONS	21
3.1.7 TEST RESULTS	22
3.2 RADIATED EMISSION MEASUREMENT	24
3.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT	24
3.2.2 TEST INSTRUMENTS.....	25
3.2.3 TEST PROCEDURES	26
3.2.4 DEVIATION FROM TEST STANDARD	26
3.2.5 TEST SETUP	27
3.2.6 EUT OPERATING CONDITIONS	28
3.2.7 TEST RESULTS	29
3.3 6 DB BANDWIDTH MEASUREMENT	165
3.3.1 LIMITS OF 6DB BANDWIDTH MEASUREMENT	165
3.3.2 TEST INSTRUMENTS.....	165
3.3.3 TEST PROCEDURE.....	166
3.3.4 DEVIATION FROM TEST STANDARD	167



3.3.5	TEST SETUP	167
3.3.6	EUT OPERATING CONDITIONS	167
3.3.7	TEST RESULTS	168
3.4	CONDUCTED OUTPUT POWER.....	169
3.4.1	LIMITS OF CONDUCTED OUTPUT POWER MEASUREMENT	169
3.4.2	TEST SETUP	169
3.4.3	TEST INSTRUMENTS.....	169
3.4.4	TEST PROCEDURES	169
3.4.5	DEVIATION FROM TEST STANDARD	169
3.4.6	EUT OPERATING CONDITIONS	169
3.4.7	TEST RESULTS	170
3.4.7.1	MAXIMUM PEAK OUTPUT POWER	170
3.4.7.2	AVERAGE OUTPUT POWER (FOR REFERENCE).....	171
3.5	POWER SPECTRAL DENSITY MEASUREMENT	172
3.5.1	LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT	172
3.5.2	TEST SETUP	172
3.5.3	TEST INSTRUMENTS.....	172
3.5.4	TEST PROCEDURE.....	172
3.5.5	DEVIATION FROM TEST STANDARD	172
3.5.6	EUT OPERATING CONDITION	172
3.5.7	TEST RESULTS	173
3.6	OUT OF BAND EMISSION MEASUREMENT	174
3.6.1	LIMITS OF OUT OF BAND EMISSION MEASUREMENT.....	174
3.6.2	TEST SETUP	174
3.6.3	TEST INSTRUMENTS.....	174
3.6.4	TEST PROCEDURE.....	174
3.6.5	DEVIATION FROM TEST STANDARD	175
3.6.6	EUT OPERATING CONDITION	175
3.6.7	TEST RESULTS	175
3.7	ANTENNA REQUIREMENTS.....	176
3.7.1	STANDARD APPLICABLE	176
3.7.2	ANTENNA CONNECTED CONSTRUCTION.....	176
3.7.3	ANTENNA GAIN	176
4	PHOTOGRAPHS OF THE TEST CONFIGURATION	177
5	MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB	
	178	



BUREAU
VERITAS

Test Report No.: PSU-QSU2306120115RF12

6 APPENDIX 1.....	179
WLAN 2.4G	179
DTS BANDWIDTH	179
TEST RESULT	179
TEST GRAPHS.....	180
OCCUPIED CHANNEL BANDWIDTH	188
TEST RESULT	188
TEST GRAPHS.....	189
MAXIMUM CONDUCTED OUTPUT POWER	198
TEST RESULT PEAK	198
TEST RESULT AVERAGE	198
MAXIMUM POWER SPECTRAL DENSITY.....	200
TEST RESULT	200
TEST GRAPHS.....	202
BAND EDGE MEASUREMENTS	214
TEST RESULT	214
TEST GRAPHS.....	215
CONDUCTED SPURIOUS EMISSION.....	221
TEST RESULT	221
TEST GRAPHS.....	222
DUTY CYCLE	230
TEST RESULT	230
TEST GRAPHS.....	231
WLAN_OFDMA.....	233
NORMAL AX MODE	233
DTS BANDWIDTH	233
TEST RESULT	233
TEST GRAPHS.....	234
OCCUPIED CHANNEL BANDWIDTH	240
TEST RESULT	240
TEST GRAPHS.....	241
MAXIMUM CONDUCTED OUTPUT POWER	247
TEST RESULT	247
MAXIMUM POWER SPECTRAL DENSITY.....	249
TEST RESULT	249
TEST GRAPHS.....	250



BAND EDGE MEASUREMENTS	256
TEST RESULT	256
TEST GRAPHS.....	257
CONDUCTED SPURIOUS EMISSION.....	261
TEST RESULT	261
TEST GRAPHS.....	263
DUTY CYCLE	281
TEST RESULT	281
TEST GRAPHS.....	282
RU AX MODE.....	288
DTS BANDWIDTH	288
TEST RESULT	288
TEST GRAPHS.....	290
OCCUPIED CHANNEL BANDWIDTH	304
TEST RESULT	304
TEST GRAPHS.....	306
MAXIMUM CONDUCTED OUTPUT POWER	320
TEST RESULT	320
MAXIMUM POWER SPECTRAL DENSITY.....	323
TEST RESULT	323
TEST GRAPHS.....	325
BAND EDGE MEASUREMENTS	339
TEST RESULT	339
TEST GRAPHS.....	340
CONDUCTED SPURIOUS EMISSION.....	352
TEST RESULT	352
TEST GRAPHS.....	355
DUTY CYCLE	397
TEST RESULT	397
TEST GRAPHS.....	398
7 APPENDIX 2 BLE	412
DTS BANDWIDTH	412
TEST RESULT	412
TEST GRAPHS.....	413
OCCUPIED CHANNEL BANDWIDTH	417
TEST RESULT	417

**Test Report No.: PSU-QSU2306120115RF12**

TEST GRAPHS.....	418
MAXIMUM CONDUCTED OUTPUT POWER	422
TEST RESULT PEAK	422
TEST RESULT AVERAGE.....	422
MAXIMUM POWER SPECTRAL DENSITY.....	423
TEST RESULT	423
TEST GRAPHS.....	424
BAND EDGE MEASUREMENTS	428
TEST RESULT	428
TEST GRAPHS.....	429
CONDUCTED SPURIOUS EMISSION.....	431
TEST RESULT	431
TEST GRAPHS.....	432
DUTY CYCLE	438
TEST RESULT	438
TEST GRAPHS.....	439



Test Report No.: PSU-QSU2306120115RF12

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
PSU-QSU2306120115RF12	Original release	Oct. 08, 2023



1 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC PART 15, SUBPART C (SECTION 15.247)			
STANDARD SECTION	TEST TYPE AND LIMIT	RESULT	TEST LAB
15.207	AC Power Conducted Emission	Compliance	B
15.205 15.209	Radiated Emissions	Compliance	B
15.247(d)	Out of band Emission Measurement	Compliance	A/B
15.247(a)(2)	6dB bandwidth	Compliance	A/B
15.247(b)	Conducted Output power	Compliance	A/B
15.247(e)	Power Spectral Density	Compliance	A/B
15.203	Antenna Requirement	Compliance	A/B

Note : 1.Except RSE, other data please refer to Appendix 1 (for WIFI-2.4G) and Appendix 2 (for BLE).
2. WLAN(normal mode& RU-OFDMA)2.4G supports SISO&MIMO mode , the whole testing have assessed the MIMO mode by referring to their maximum conducted power.
3. For WIFI-2.4G, RSE had been tested on SISO&MIMO mode of EUT. The worst case was found on MIMO mode, only the worst case data had been reported in the report.

*Test Lab Information Reference

Lab A:

BV 7Layers Communications Technology (Shenzhen) Co., Ltd

Lab Address:

No.B102, Dazu Chuangxin Mansion, North of Beihuan Avenue, North Area, Hi-Tech Industrial Park, Nanshan District, Shenzhen, Guangdong, China

Accredited Test Lab Cert 3939.01

FCC Site Registration No. : 525120; Designation No. : CN1171;

Lab B:

Huarui 7Layers High Technology (Suzhou) Co., Ltd.

Lab Address:

Tower N, Innovation Center, 88 Zhuyi Road, High-tech District, Suzhou City, Anhui Province

Accredited Test Lab Cert 6613.01

The FCC Site Registration No. is 434559; The Designation No. is CN1325.



1.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	UNCERTAINTY
AC Power Conducted emissions	±2.70dB
Radiated emissions (9KHz~30MHz)	±2.68dB
Radiated emissions (30MHz~1GHz)	±4.98dB
Radiated emissions (1GHz ~6GHz)	±4.70dB
Radiated emissions (6GHz ~18GHz)	±4.60dB
Radiated emissions (18GHz ~40GHz)	±4.12dB
Conducted emissions	±4.01dB
Occupied Channel Bandwidth	±43.58KHz
Conducted Output power	±2.06dB
Power Spectral Density	±0.85 dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k = 2$.



2 GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

PRODUCT*	UP Phone 1
BRAND NAME*	UP Phone
MODEL NAME*	UP01
NOMINAL VOLTAGE*	3.87Vdc (battery)
MODULATION *	DSSS, OFDM, GFSK, OFDMA
TRANSMISSION RATE	802.11b: 11/ 5.5/ 2.0 / 1.0 Mbps 802.11g: 54/ 48/ 36 / 24 / 18 / 9/ 6 Mbps 802.11n20: up to 144.4 Mbps 802.11n40: up to 300 Mbps BT_LE: 1 Mbps/2 Mbps 802.11ax 20 (RU242): up to 286.8Mbps 802.11ax 40 (RU484): up to 573.5Mbps
OPERATING FREQUENCY	2412-2462MHz for 11b/g/n(HT20/40) 2402-2480MHz for BT-LE(GFSK) 2412-2462MHz for ax(20M RU242)/ax (40M RU484)
MAX. OUTPUT POWER	WLAN: 941.89 mW (Maximum) BT-LE: 41.78mW (Maximum) RU WLAN: 867.04mW (Maximum)
ANTENNA TYPE*	ANT 0: PIFA Antenna with -0.5dBi gain for BT/WIFI ANT 1: PIFA Antenna with -0.5dBi gain for WIFI
HW VERSION*	M156-MUB-V2
SW VERSION*	NR_D011.13_N_UP01_1.000.01
I/O PORTS*	Refer to user's manual
CABLE SUPPLIED*	N/A



BUREAU
VERITAS

Test Report No.: PSU-QSU2306120115RF12

NOTE:

1. *Since the above data and/or information is provided by the client relevant results or conclusions of this report are only made for these data and/or information , Test Lab is not responsible for the authenticity, integrity and results of the data and information and/or the validity of the conclusion.
2. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
3. The EUT incorporates a MIMO function. Physically, the EUT provides two transmitters and two receivers.

MODULATION MODE	TX/RX FUNCTION
802.11b	2TX /2RX
802.11g	2TX /2RX
802.11n (20MHz)	2TX /2RX
802.11n (40MHz)	2TX /2RX
802.11ax (20MHz RU 26/52/106/242)	2TX /2RX
802.11ax (40MHz RU 242/484)	2TX /2RX
BT_LE(1MHz)	1TX /1RX
BT_LE(2MHz)	1TX /1RX

4. For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.

List of Accessory:

ACCESSORIES	Brand	MODEL / SPECIFICATION
CPU	MediaTek	MT6893
eMMC 1 (=ROM 1)	Sandisk	SDINFDK4-256G
eMMC 2 (=ROM 2)	Samsung	KLUEG4RHGB-B0E1
eMMC 3 (=ROM 3)	Samsung	KLUEG4RHGB-B0E1
eMMC 4 (=ROM 4)	Samsung	KLUEG4RHGB-B0E1
RAM 1	Hynix	H9HKNNNFBMAVAR-NEH
RAM 2	Samsung	K3UH7H70BM-AGCL
BT/WLAN Module	MediaTek	/
NFC chipset	ST	/
Battery	/	Power Rating: 16.98Wh



2.2 DESCRIPTION OF TEST MODES

11 channels are provided for 802.11b, 802.11g and 802.11n (HT20), 802.11ax20 (RU 242):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
1	2412 MHz	7	2442 MHz
2	2417 MHz	8	2447 MHz
3	2422 MHz	9	2452 MHz
4	2427 MHz	10	2457 MHz
5	2432 MHz	11	2462 MHz
6	2437 MHz		

7 channels are provided for 802.11n (HT40), 802.11ax40 (RU 484):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
3	2422 MHz	7	2442 MHz
4	2427 MHz	8	2447 MHz
5	2432 MHz	9	2452 MHz
6	2437 MHz		

40 channels are provided for BT-LE (GFSK):

CHANNEL	FREQ. (MHZ)	CHANNEL	FREQ. (MHZ)	CHANNEL	FREQ. (MHZ)	CHANNEL	FREQ. (MHZ)
0	2402	10	2422	20	2442	30	2462
1	2404	11	2424	21	2444	31	2464
2	2406	12	2426	22	2446	32	2466
3	2408	13	2428	23	2448	33	2468
4	2410	14	2430	24	2450	34	2470
5	2412	15	2432	25	2452	35	2472
6	2414	16	2434	26	2454	36	2474
7	2416	17	2436	27	2456	37	2476
8	2418	18	2438	28	2458	38	2478
9	2420	19	2440	29	2460	39	2480



2.2.1 CONFIGURATION OF SYSTEM UNDER TEST

Please see section 5 photographs of the test configuration for reference.

2.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports.

The worst case was found when positioned on Y axis for radiated emission. Following test modes were selected for the final test, and the final worst case is marked in boldface and recorded in the report:

EUT CONFIGURE MODE	APPLICABLE TO				MODE
	RE<1G	RE≥1G	PLC	APCM	
-	√	√	√	√	-

Where **RE<1G**: Radiated Emission below 1GHz **RE≥1G**: Radiated Emission above 1GHz

PLC: Power Line Conducted Emission

APCM: Antenna Port Conducted Measurement

NOTE: No need to concern of Conducted Emission due to the EUT is powered by battery.

RADIATED EMISSION TEST (BELOW 1GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION	DATA RATE (Mbps)
802.11g	3 to 9	6	OFDM	MCS0
BT-LE	0 to 39	19	GFSK	1.0



BUREAU
VERITAS

Test Report No.: PSU-QSU2306120115RF12

RADIATED EMISSION TEST (ABOVE 1GHz):

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION	DATA RATE (Mbps)
802.11b	1 to 11	1, 6, 11	DSSS	1.0
802.11g	1 to 11	1, 6, 11	OFDM	6.0
802.11n HT20	1 to 11	1, 6, 11	OFDM	MCS0
802.11n HT40	3 to 9	3,6,9	OFDM	MCS0
BT-LE	0 to 39	0,19, 39	GFSK	1.0
BT-LE	1 to 38	38	GFSK	2.0
802.11ax 20 (RU 242)	1 to 11	1, 11	OFDMA	MCS0
802.11ax 40 (RU 484)	3 to 9	3, 9	OFDMA	MCS0

POWER LINE CONDUCTED EMISSION TEST

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION	DATA RATE (Mbps)
802.11ax 40 (RU 484)	3 to 9	3	OFDMA	MCS0



BANDEdge MEASUREMENT:

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION	DATA RATE (Mbps)
802.11b	1 to 11	1, 6, 11	DSSS	1.0
802.11g	1 to 11	1, 6, 11	OFDM	6.0
802.11n HT20	1 to 11	1, 6, 11	OFDM	MCS0
802.11n HT40	3 to 9	3,6,9	OFDM	MCS0
BT-LE	0 to 39	0,19, 39	GFSK	1.0
BT-LE	1 to 38	38	GFSK	2.0
802.11ax 20 (RU 242)	1 to 11	1,11	OFDMA	MCS0
802.11ax 40 (RU 484)	3 to 9	3 ,9	OFDMA	MCS0



ANTENNA PORT CONDUCTED MEASUREMENT:

- This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION	DATA RATE (Mbps)
802.11b	1 to 11	1, 6, 11	DSSS	1.0
802.11g	1 to 11	1, 6, 11	OFDM	6.0
802.11n HT20	1 to 11	1, 6, 11	OFDM	MCS0
802.11n HT40	3 to 9	3,6,9	OFDM	MCS0
BT-LE	0 to 39	0,19,39	GFSK	1.0
BT-LE	1 to 38	38	GFSK	2.0
802.11ax 20 (RU 242)	1 to 11	1,11	OFDMA	MCS0
802.11ax 40 (RU 484)	3 to 9	3 ,9	OFDMA	MCS0

TEST CONDITION:

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	TEST VOLTAGE	TESTED BY
RE<1G	23deg. C, 70%RH	DC 3.87V By Adapter	Chao Wu
RE≥1G	23deg. C, 70%RH	DC 3.87V By Adapter	Chao Wu
PLC	25deg. C, 52%RH	DC 3.87V By Adapter	Chao Wu
APCM	25deg. C, 60%RH	DC 3.87V By Adapter	Chao Wu



2.3 DUTY CYCLE OF TEST SIGNAL

Please Refer to Appendix1/2 Of this test report.

WORST-CASE DATA:

Measured Duty Cycle		
Mode	Duty Cycle [%]	
	ANT1/2	
WIFI 2.4GHz	11B	100
	11G	96.19
	11N20	96.67
	11N40	93.48
	11ax20	96.23
	11ax40	93.10
	11ax 20 (RU 242)	99.02
	11ax 40 (RU 484)	95.58
BT LE	BT4.0	84.68
	BT5.0	57.09

Note:

Duty cycle of test signal is < 98%, duty factor shall be considered.



2.4 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C, Section 15.247

KDB 558074 D01 DTS Meas Guidance v05r02

ANSI C63.10-2013

Note :

1. All test items have been performed and recorded as per the above standards.
2. The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (Certification). The test report has been issued separately.

2.5 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	Laptop	Lenovo	ThinkPad E14	HRSW00024	N/A
2	Adapter	N/A	N/A	N/A	N/A

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	N/A



3 TEST TYPES AND RESULTS

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dB μ V)	
	Quasi-peak	Average
0.15 ~ 0.5	66 to 56	56 to 46
0.5 ~ 5	56	46
5 ~ 30	60	50

NOTE: 1. The lower limit shall apply at the transition frequencies.
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.
3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

3.1.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
EMI Test Receiver	Rohde&Schwarz	ESR3	102749	Feb.25,22	Feb.24,24
ELEKTRA test software	Rohde&Schwarz	ELEKTRA	NA	N/A	N/A
LISN network	Rohde&Schwarz	ENV216	102640	Feb.17,22	Feb.16,24
CABLE	Rohde&Schwarz	W61.01	N/A	Apr.28,23	Oct.27,23
CABLE	Rohde&Schwarz	W601	N/A	Apr.28,23	Oct.27,23

NOTE:

1. The test was performed in CE shielded room.
2. The calibration interval of the above test instruments is 6 months or 24 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.



3.1.3 TEST PROCEDURES


- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

NOTE: All modes of operation were investigated and the worst-case emissions are reported.

3.1.4 DEVIATION FROM TEST STANDARD

No deviation.

3.1.5 TEST SETUP



Note:

1. Support units were connected to second LISN.
2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

For the actual test configuration, please refer to the attached file (Test Setup Photo).

3.1.6 EUT OPERATING CONDITIONS

- Turned on the power and connected of all equipment.
- EUT was operated according to the type used was description in manufacturer's specifications or the User's Manual.

BUREAU
VERITAS

Test Report No.: PSU-QSU2306120115RF12

3.1.7 TEST RESULTS


CONDUCTED WORST-CASE DATA:

Frequency Range	150KHz ~ 30MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9 kHz
Input Power	120Vac, 60Hz	Environmental Conditions	26deg. C, 51%RH
Tested By	Chao Wu		

Rg	Frequency [MHz]	QPK Level [dB μ V]	QPK Limit [dB μ V]	QPK Margin [dB]	CAV Level [dB μ V]	CAV AVG Limit [dB μ V]	CAV Margin [dB]	Correction [dB]	Line	Meas. BW [kHz]
1	0.182	37.84	64.42	26.58	27.68	54.42	26.74	12.20	L1	9.000
1	0.510	38.25	56.00	17.75	23.77	46.00	22.23	11.75	L1	9.000
1	1.329	31.29	56.00	24.71	22.15	46.00	23.85	11.75	L1	9.000
1	3.102	27.67	56.00	28.33	19.95	46.00	26.05	11.78	L1	9.000
1	7.584	25.60	60.00	34.40	18.26	50.00	31.74	11.81	L1	9.000
1	12.701	18.66	60.00	41.34	11.29	50.00	38.71	11.84	L1	9.000

REMARKS: 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.

2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Limit value -Emission level
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.



BUREAU
VERITAS


Test Report No.: PSU-QSU2306120115RF12

Frequency Range	150KHz ~ 30MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9 kHz
Input Power	120Vac, 60Hz	Environmental Conditions	26deg. C, 51%RH
Tested By	Chao Wu		

Rg	Frequency [MHz]	QPK Level [dB μ V]	QPK Limit [dB μ V]	QPK Margin [dB]	CAV Level [dB μ V]	CAV AVG Limit [dB μ V]	CAV Margin [dB]	Correction [dB]	Line	Meas. BW [kHz]
1	0.182	38.99	64.42	25.43	29.86	54.42	24.56	12.22	N	9.000
1	0.506	37.30	56.00	18.70	33.84	46.00	12.16	12.78	N	9.000
1	2.027	33.47	56.00	22.53	19.34	46.00	26.66	12.74	N	9.000
1	4.223	30.15	56.00	25.85	22.34	46.00	23.66	12.76	N	9.000
1	10.878	23.19	60.00	36.81	17.58	50.00	32.42	12.80	N	9.000
1	19.113	25.57	60.00	34.43	20.29	50.00	29.71	12.85	N	9.000

REMARKS: 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.

2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Limit value - Emission level
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.





3.2 RADIATED EMISSION MEASUREMENT

3.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).

FREQUENCIES (MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dB_uV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

BUREAU
VERITAS

Test Report No.: PSU-QSU2306120115RF12

3.2.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
Pre-Amplifier	R&S	SCU18F1	100815	Aug.30,22	Aug.29,24
Pre-Amplifier	R&S	SCU08F1	101028	Sep.16,22	Sep.15,24
Signal Generator	R&S	SMB100A	182185	Feb.16,22	Feb.15,24
3m Fully-anechoic Chamber	TDK	9m*6m*6m	HRSW-SZ-EMC-01Chamber	Nov.25,22	Nov.24,25
3m Semi-anechoic Chamber	TDK	9m*6m*6m	HRSW-SZ-EMC-02Chamber	Nov.25,22	Nov.24,25
EMI TEST Receiver	R&S	ESW44	101973	Feb.25,22	Feb.24,24
Bilog Antenna	SCHWARZBEC K	VULB 9163	1264	Feb.28,22	Feb.27,24
Horn Antenna	ETS-LINDGREN	3117	227836	Aug.22,22	Aug.21,24
Horn Antenna (18GHz-40GHz)	Steatite Q-par Antennas	QMS 00880	23486	Feb.23,22	Feb.22,24
Horn Antenna	Steatite Q-par Antennas	QMS 00208	23485	Aug.22,22	Aug.21,24
Loop Antenna	SCHWARZ	HFH2-Z2/Z2E	100976	Feb.23,22	Feb.22,24
WIDEBANDRADIO COMMUNICATION TESTER	R&S	CMW500	169399	Jun.27,22	Jun.26,24
Test Software	ELEKTRA	ELEKTRA4.32	N/A	N/A	N/A
Open Switch and Control Unit	R&S	OSP220	101964	N/A	N/A
DC Source	HYELEC	HY3010B	551016	Aug.31,22	Aug.30,24
Hygrothermograph	DELI	20210528	SZ014	Sep.06,22	Sep.05,24
PC	LENOVO	E14	HRSW0024	N/A	N/A
TMC-AMI18843A(CABLE)	R&S	HF290-NMNM-7.00M	N/A	N/A	N/A
TMC-AMI18843A(CABLE)	R&S	HF290-NMNM-4.00M	N/A	N/A	N/A
CABLE	R&S	W13.02	N/A	Apr.28,23	Oct.27,23
CABLE	R&S	W12.14	N/A	Apr.28,23	Oct.27,23

NOTE:

1. The calibration interval of the above test instruments is 6 months or 24 months or 36 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.
2. The test was performed in 3m Chamber.
3. The FCC Site Registration No. is 434559; The Designation No. is CN1325.



3.2.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters (for below 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, For battery operated equipment, the equipment tests shall be perform using fresh batteries. The turntable was rotated to maximize the emission level.

Note:


1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 3MHz for RMS Average (Duty cycle < 98%) for Average detection (AV) at frequency above 1GHz, then the measurement results was added to a correction factor ($10 \log(1/\text{duty cycle})$).
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz (Duty cycle $\geq 98\%$) for Average detection (AV) at frequency above 1GHz.
5. All modes of operation were investigated and the worst-case emissions are reported.

3.2.4 DEVIATION FROM TEST STANDARD


No deviation

3.2.5 TEST SETUP

<Frequency Range 9KHz~30MHz >




< Frequency Range 30MHz~1GHz >





<Frequency Range above 1GHz>



Note: Above 1G is a directional antenna

Depends on the EUT height and the antenna 3dB beamwidth both, refer to section 7.3 of CISPR 16-2-3.

For the actual test configuration, please refer to the attached file (Test Setup Photo).

3.2.6 EUT OPERATING CONDITIONS

- Set the EUT under full load condition and placed them on a testing table.
- Set the transmitter part of EUT under transmission condition continuously at specific channel frequency.
- The necessary accessories enable the EUT in full functions.

BUREAU
VERITAS

Test Report No.: PSU-QSU2306120115RF12

3.2.7 TEST RESULTS

NOTE : The 9K~30MHz amplitude of spurious emissions attenuated more than 20 dB below the permissible value is not required in the report.

BELOW 1GHz WORST-CASE DATA:

30 MHz – 1GHz data:


802.11g:

CHANNEL	TX Channel 6	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	30MHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
Rg	Frequency [MHz]	PK+ Level [dB μ V/m]	PK+: QPK Limit [dB μ V/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
1	51.631	33.98	40.00	6.02	-7.53	H	359.1	2
1	107.988	28.10	43.50	15.40	-9.17	H	358	2
1	164.200	23.10	43.50	20.40	-11.40	H	5.1	1
1	284.286	24.84	46.00	21.16	-6.03	H	127.4	1
1	566.604	29.04	46.00	16.96	-2.72	H	127.4	1
1	882.970	33.93	46.00	12.07	2.64	H	5.1	2

REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Limit value- Emission level.






CHANNEL	TX Channel 6	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	30MHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dB μ V/m]	PK+ QPK Limit [dB μ V/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
1	45.472	31.85	40.00	8.15	-7.47	V	359.1	1
1	86.988	24.78	40.00	15.22	-11.97	V	260.1	2
1	147.467	20.17	43.50	23.33	-12.30	V	127.4	2
1	251.742	24.10	46.00	21.90	-7.00	V	5.2	1
1	445.791	28.42	46.00	17.58	-3.81	V	359.1	1
1	866.916	31.23	46.00	14.77	2.42	V	1	2

REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Limit value- Emission level.



BUREAU
VERITAS

Test Report No.: PSU-QSU2306120115RF12

ABOVE 1GHz WORST-CASE DATA:

Note: 1. For radiated emissions testing , the full testing range of different modes have been scanned , only the worst case harmonic data is reported in the sheet.


2. All other emissions were greater than 20dB below the limit was not recorded

802.11b:

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M


Rg	Frequency [MHz]	PK+ Level [dB μ V/m]	PK+ Limit [dB μ V/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
1	2,389.000	49.42	74.00	24.58	7.08	H	0.9	2
1	2,390.000	48.51	74.00	25.49	7.08	H	133.1	1
1	2,413.500	108.37			7.19	H	4.2	1





Test Report No.: PSU-QSU2306120115RF12

Rg	Frequency [MHz]	AVG Level [dB μ V/m]	AVG Limit [dB μ V/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
1	2,388.000	35.50	54.00	18.50	7.08	H	181	1
1	2,390.000	35.70	54.00	18.30	7.08	H	135.5	1
1	2,413.000	104.02			7.19	H	5.6	1






BUREAU
VERITAS

Test Report No.: PSU-QSU2306120115RF12

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M


Rg	Frequency [MHz]	PK+ Level [dB μ V/m]	PK+ Limit [dB μ V/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
1	2,389.500	48.09	74.00	25.91	7.08	V	0.9	2
1	2,390.000	48.37	74.00	25.63	7.08	V	179	2
1	2,414.000	97.14			7.20	V	179	2



BUREAU
VERITAS

Test Report No.: PSU-QSU2306120115RF12

Rg	Frequency [MHz]	AVG Level [dB μ V/m]	AVG Limit [dB μ V/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
1	2,389.000	33.92	54.00	20.08	7.08	V	176.5	2
1	2,390.000	34.00	54.00	20.00	7.08	V	176.5	2
1	2,411.500	97.87			7.17	V	176.5	2



REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Limit value- Emission level.
2. 2.412MHz: Fundamental frequency.




BUREAU
VERITAS

Test Report No.: PSU-QSU2306120115RF12

CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dB μ V/m]	PK+ Limit [dB μ V/m]	PK+ Margin [dB]	AVG Level [dB μ V/m]	AVG Limit [dB μ V/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
2	4,874.000	52.84	74.00	21.16	44.10	54.00	9.90	15.49	H	267.4	2
2	7,536.000	59.88	74.00	14.12	46.29	54.00	7.71	21.69	H	1	2






BUREAU
VERITAS

Test Report No.: PSU-QSU2306120115RF12

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dB μ V/m]	PK+ Limit [dB μ V/m]	PK+ Margin [dB]	AVG Level [dB μ V/m]	AVG Limit [dB μ V/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
2	4,874.000	54.17	74.00	19.83	45.05	54.00	8.95	15.49	V	98.6	1
2	7,427.500	60.05	74.00	13.95	46.86	54.00	7.14	21.42	V	359	2



REMARKS:


1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Limit value- Emission level.
2. 2437MHz: Fundamental frequency.



CHANNEL	TX Channel 11	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M


Rg	Frequency [MHz]	PK+ Level [dB μ V/m]	PK+ Limit [dB μ V/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
2	2,460.500	108.05			7.40	H	5	1
2	2,483.500	49.32	74.00	24.68	7.36	H	13.5	2
2	2,484.500	49.65	74.00	24.35	7.36	H	0.9	2





Test Report No.: PSU-QSU2306120115RF12

Rg	Frequency [MHz]	AVG Level [dB μ V/m]	AVG Limit [dB μ V/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
2	2,461.000	104.45			7.40	H	5	1
2	2,483.500	35.58	54.00	18.42	7.36	H	78.6	2
2	2,487.000	36.14	54.00	17.86	7.36	H	5	1






Test Report No.: PSU-QSU2306120115RF12

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dB μ V/m]	PK+ Limit [dB μ V/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
2	2,463.500	95.29			7.39	V	66.2	1
2	2,483.500	46.66	74.00	27.34	7.36	V	1	2
2	2,488.000	47.68	74.00	26.32	7.36	V	359	2



BUREAU
VERITAS

Test Report No.: PSU-QSU2306120115RF12

Rg	Frequency [MHz]	AVG Level [dB μ V/m]	AVG Limit [dB μ V/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
2	2,461.000	93.45			7.40	V	68.7	1
2	2,483.500	32.40	54.00	21.60	7.36	V	1	1
2	2,484.500	32.40	54.00	21.60	7.36	V	221.9	2



REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Limit value- Emission level.
2. 2462MHz: Fundamental frequency.




BUREAU
VERITAS Test Report No.: PSU-QSU2306120115RF12

802.11g

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dB μ V/m]	PK+ Limit [dB μ V/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
1	2,387.560	48.46	74.00	25.54	6.73	H	82.1	1
1	2,390.000	48.37	74.00	25.63	6.75	H	353.4	1
3	2,413.641	102.09			6.85	H	124	1





BUREAU
VERITAS

Test Report No.: PSU-QSU2306120115RF12

Rg	Frequency [MHz]	AVG Level [dB μ V/m]	AVG Limit [dB μ V/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
1	2,387.000	34.43	54.00	19.57	6.72	H	128.6	1
1	2,390.000	35.71	54.00	18.29	6.75	H	128.6	1
1	2,413.600	90.56			6.87	H	80.7	2






BUREAU
VERITAS

Test Report No.: PSU-QSU2306120115RF12


ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dB μ V/m]	PK+ Limit [dB μ V/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
1	2,388.120	45.66	74.00	28.34	6.73	V	5.1	1
1	2,390.000	45.78	74.00	28.22	6.75	V	354.8	2
1	2,407.720	93.60			6.85	V	184.7	1





Rg	Frequency [MHz]	AVG Level [dB μ V/m]	AVG Limit [dB μ V/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
1	2,387.280	32.08	54.00	21.92	6.73	V	190.7	1
1	2,390.000	32.48	54.00	21.52	6.75	V	190.7	1
1	2,409.960	82.24			6.86	V	4.5	1



REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Limit value- Emission level.
2. 2412MHz: Fundamental frequency.




BUREAU
VERITAS

Test Report No.: PSU-QSU2306120115RF12

CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M


Rg	Frequency [MHz]	PK+ Level [dB μ V/m]	PK+ Limit [dB μ V/m]	PK+ Margin [dB]	AVG Level [dB μ V/m]	AVG Limit [dB μ V/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
2	4,874.000	51.85	74.00	22.15	40.61	54.00	13.39	15.49	H	359.1	2
2	7,899.000	57.96	74.00	16.04	44.92	54.00	9.08	22.15	H	322.2	2





ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dB μ V/m]	PK+ Limit [dB μ V/m]	PK+ Margin [dB]	AVG Level [dB μ V/m]	AVG Limit [dB μ V/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
2	4,874.500	50.85	74.00	23.15	40.20	54.00	13.80	15.49	V	30.6	2
2	7,444.500	59.62	74.00	14.38	47.45	54.00	6.55	21.50	V	359	1



REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Limit value- Emission level.
2. 2437MHz: Fundamental frequency.




BUREAU
VERITAS

Test Report No.: PSU-QSU2306120115RF12

CHANNEL	TX Channel 11	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M


Rg	Frequency [MHz]	PK+ Level [dB μ V/m]	PK+ Limit [dB μ V/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
4	2,463.480	102.38			6.69	H	5	1
2	2,483.500	55.89	74.00	18.11	6.74	H	129.8	1
2	2,486.800	53.00	74.00	21.00	6.76	H	220.6	2





Test Report No.: PSU-QSU2306120115RF12

Rg	Frequency [MHz]	AVG Level [dB μ V/m]	AVG Limit [dB μ V/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
2	2,463.040	90.09			6.69	H	30.4	2
2	2,483.000	36.70	54.00	17.30	6.74	H	30.4	2
2	2,486.080	36.11	54.00	17.89	6.75	H	77.1	2






BUREAU
VERITAS

Test Report No.: PSU-QSU2306120115RF12


ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dB μ V/m]	PK+ Limit [dB μ V/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
2	2,463.280	95.46			6.69	V	165.5	2
2	2,483.500	48.13	74.00	25.87	6.74	V	215.8	2
2	2,484.640	46.54	74.00	27.46	6.75	V	189.5	1





Rg	Frequency [MHz]	AVG Level [dB μ V/m]	AVG Limit [dB μ V/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
2	2,460.640	85.26			6.68	V	129.7	2
2	2,483.000	33.32	54.00	20.68	6.74	V	177.4	2
2	2,485.120	33.25	54.00	20.75	6.75	V	177.4	2



REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Limit value- Emission level.
2. 2462MHz: Fundamental frequency.



BUREAU
VERITAS


Test Report No.: PSU-QSU2306120115RF12

802.11n (20MHz)

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M


Rg	Frequency [MHz]	PK+ Level [dB μ V/m]	PK+ Limit [dB μ V/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
1	2,388.960	48.99	74.00	25.01	6.74	H	82	1
1	2,390.000	48.22	74.00	25.78	6.75	H	80.7	2
1	2,413.880	101.99			6.88	H	129.8	1





Test Report No.: PSU-QSU2306120115RF12

Rg	Frequency [MHz]	AVG Level [dB μ V/m]	AVG Limit [dB μ V/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
1	2,381.960	33.83	54.00	20.17	6.69	H	176.3	1
1	2,390.000	36.00	54.00	18.00	6.75	H	359	2
1	2,411.360	92.41			6.87	H	129.8	1






BUREAU
VERITAS

Test Report No.: PSU-QSU2306120115RF12

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dB μ V/m]	PK+ Limit [dB μ V/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
1	2,386.720	45.56	74.00	28.44	6.72	V	282.9	1
1	2,390.000	45.41	74.00	28.59	6.75	V	173.8	2
1	2,410.800	95.68			6.86	V	4.6	1





BUREAU
VERITAS

Test Report No.: PSU-QSU2306120115RF12

Rg	Frequency [MHz]	AVG Level [dB μ V/m]	AVG Limit [dB μ V/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
1	2,384.480	31.96	54.00	22.04	6.71	V	268.3	2
1	2,390.000	33.09	54.00	20.91	6.75	V	188.3	1
1	2,411.080	84.67			6.87	V	188.3	1



REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Limit value- Emission level.
2. 2412MHz: Fundamental frequency.




BUREAU
VERITAS Test Report No.: PSU-QSU2306120115RF12

CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M


Rg	Frequency [MHz]	PK+ Level [dB μ V/m]	PK+ Limit [dB μ V/m]	PK+ Margin [dB]	AVG Level [dB μ V/m]	AVG Limit [dB μ V/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
2	4,874.000	51.20	74.00	22.80	40.35	54.00	13.65	15.49	H	359.1	2
2	7,964.500	58.30	74.00	15.70	45.68	54.00	8.32	22.67	H	90.2	2





ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dB μ V/m]	PK+ Limit [dB μ V/m]	PK+ Margin [dB]	AVG Level [dB μ V/m]	AVG Limit [dB μ V/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
2	4,874.000	51.66	74.00	22.34	40.42	54.00	13.58	15.49	V	359.1	1
2	6,845.000	58.45	74.00	15.55	44.58	54.00	9.42	20.63	V	0.9	2



REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Limit value-Emission level.
2. 2437MHz: Fundamental frequency.




BUREAU
VERITAS

Test Report No.: PSU-QSU2306120115RF12

CHANNEL	TX Channel 11	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M


Rg	Frequency [MHz]	PK+ Level [dB μ V/m]	PK+ Limit [dB μ V/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
4	2,459.910	100.14			6.69	H	221	2
2	2,483.500	52.39	74.00	21.61	6.74	H	82.1	1
2	2,484.880	53.26	74.00	20.74	6.75	H	220.6	2





BUREAU
VERITAS Test Report No.: PSU-QSU2306120115RF12

Rg	Frequency [MHz]	AVG Level [dB μ V/m]	AVG Limit [dB μ V/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
2	2,459.680	89.56			6.68	H	5.2	1
2	2,483.000	35.12	54.00	18.88	6.74	H	5.2	1
2	2,485.120	34.90	54.00	19.10	6.75	H	5.2	1






BUREAU
VERITAS

Test Report No.: PSU-QSU2306120115RF12


ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dB μ V/m]	PK+ Limit [dB μ V/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
2	2,464.720	91.60			6.69	V	141.8	1
2	2,483.500	46.04	74.00	27.96	6.74	V	43.8	1
2	2,484.160	47.30	74.00	26.70	6.74	V	153.6	2





Rg	Frequency [MHz]	AVG Level [dB μ V/m]	AVG Limit [dB μ V/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
2	2,463.520	82.55			6.69	V	176.3	2
2	2,483.000	32.50	54.00	21.50	6.74	V	176.3	2
2	2,485.600	32.50	54.00	21.50	6.75	V	176.3	2

**REMARKS:**

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Limit value-Emission level .
2. 2462MHz: Fundamental frequency.



BUREAU
VERITAS


Test Report No.: PSU-QSU2306120115RF12

802.11n (40MHz)

CHANNEL	TX Channel 3	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M


Rg	Frequency [MHz]	PK+ Level [dB μ V/m]	PK+ Limit [dB μ V/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
3	2,384.910	45.54	74.00	28.46	6.71	H	138.2	1
3	2,390.000	46.60	74.00	27.40	6.75	H	220.6	2
3	2,425.830	97.33			6.90	H	5.1	1





Test Report No.: PSU-QSU2306120115RF12


Rg	Frequency [MHz]	AVG Level [dB μ V/m]	AVG Limit [dB μ V/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
3	2,386.890	32.07	54.00	21.93	6.72	H	5.1	1
3	2,390.000	33.62	54.00	20.38	6.75	H	5.1	1
3	2,430.120	85.87			6.85	H	5.1	1






ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dB μ V/m]	PK+ Limit [dB μ V/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
3	2,389.200	46.25	74.00	27.75	6.74	V	175	2
3	2,390.000	45.42	74.00	28.58	6.75	V	232.6	1
3	2,430.780	90.48			6.85	V	175	2





Rg	Frequency [MHz]	AVG Level [dB μ V/m]	AVG Limit [dB μ V/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
3	2,386.890	31.14	54.00	22.86	6.72	V	173.9	2
3	2,390.000	31.85	54.00	22.15	6.75	V	173.9	2
3	2,429.130	79.24			6.86	V	173.9	2



REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Limit value-Emission level.
2. 2422MHz: Fundamental frequency.




BUREAU
VERITAS

Test Report No.: PSU-QSU2306120115RF12

CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dB μ V/m]	PK+ Limit [dB μ V/m]	PK+ Margin [dB]	AVG Level [dB μ V/m]	AVG Limit [dB μ V/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
2	4,874.000	52.36	74.00	21.64	40.46	54.00	13.54	15.49	H	1	2
2	7,264.000	58.50	74.00	15.50	44.94	54.00	9.06	21.57	H	269.8	2






BUREAU
VERITAS

Test Report No.: PSU-QSU2306120115RF12

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dB μ V/m]	PK+ Limit [dB μ V/m]	PK+ Margin [dB]	Avg Level [dB μ V/m]	Avg Limit [dB μ V/m]	Avg Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
2	4,874.000	52.67	74.00	21.33	40.45	54.00	13.55	15.49	V	0.9	2
2	7,074.500	58.78	74.00	15.22	45.91	54.00	8.09	22.30	V	359	2



REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Limit value—Emission level.
2. 2437MHz: Fundamental frequency.




BUREAU
VERITAS

Test Report No.: PSU-QSU2306120115RF12

CHANNEL	TX Channel 9	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dB μ V/m]	PK+ Limit [dB μ V/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
4	2,456.480	99.15			6.68	H	7.3	1
4	2,483.500	50.26	74.00	23.74	6.74	H	7.3	1
4	2,484.020	51.40	74.00	22.60	6.74	H	7.3	1






BUREAU
VERITAS

Test Report No.: PSU-QSU2306120115RF12

Rg	Frequency [MHz]	AVG Level [dB μ V/m]	AVG Limit [dB μ V/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
4	2,449.680	86.48			6.67	H	153.8	1
4	2,483.500	36.91	54.00	17.09	6.74	H	5.2	1
4	2,484.020	37.62	54.00	16.38	6.74	H	5.2	1






Test Report No.: PSU-QSU2306120115RF12


ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dB μ V/m]	PK+ Limit [dB μ V/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
4	2,455.120	90.34			6.68	V	163.3	1
4	2,483.500	46.63	74.00	27.37	6.74	V	98.7	1
4	2,485.040	46.56	74.00	27.44	6.75	V	173.9	2





Rg	Frequency [MHz]	AVG Level [dB μ V/m]	AVG Limit [dB μ V/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
4	2,450.020	78.98			6.67	V	138.2	1
4	2,483.500	32.93	54.00	21.07	6.74	V	138.2	1
4	2,485.040	32.73	54.00	21.27	6.75	V	175.1	2



REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Limit value-Emission level.
2. 2452MHz: Fundamental frequency.



BUREAU
VERITAS

Test Report No.: PSU-QSU2306120115RF12


2.4G WIFI-SU

802.11ax (20MHz) (SU242):

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dB μ V/m]	PK+ Limit [dB μ V/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
1	2,389.000	70.05	74.00	3.95	7.08	H	147.9	2
1	2,390.000	70.02	74.00	3.98	7.08	H	4.9	1
1	2,417.500	111.41			7.23	H	4.9	1






BUREAU
VERITAS

Test Report No.: PSU-QSU2306120115RF12

Rg	Frequency [MHz]	AVG Level [dB μ V/m]	AVG Limit [dB μ V/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
1	2,389.500	45.83	54.00	8.17	7.08	H	5.7	1
1	2,390.000	46.85	54.00	7.15	7.08	H	5.7	1
1	2,411.000	96.59			7.17	H	114.1	1






BUREAU
VERITAS

Test Report No.: PSU-QSU2306120115RF12

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M


Rg	Frequency [MHz]	PK+ Level [dB μ V/m]	PK+ Limit [dB μ V/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
1	2,388.500	61.69	74.00	12.31	7.08	V	201.7	2
1	2,390.000	60.82	74.00	13.18	7.08	V	0.9	2
1	2,413.500	105.66			7.19	V	112.9	1



BUREAU
VERITAS

Test Report No.: PSU-QSU2306120115RF12

Rg	Frequency [MHz]	AVG Level [dB μ V/m]	AVG Limit [dB μ V/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
1	2,389.000	39.00	54.00	15.00	7.08	V	296.1	2
1	2,390.000	39.34	54.00	14.66	7.08	V	296.1	2
1	2,411.000	90.62			7.17	V	296.1	2



REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Limit value-Emission level.
2. 2412MHz: Fundamental frequency.




BUREAU
VERITAS

Test Report No.: PSU-QSU2306120115RF12

CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M


Rg	Frequency [MHz]	PK+ Level [dB μ V/m]	PK+ Limit [dB μ V/m]	PK+ Margin [dB]	AVG Level [dB μ V/m]	AVG Limit [dB μ V/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
2	4,874.000	50.64	74.00	23.36	40.14	54.00	13.86	15.25	H	359	2
2	7,311.000	56.53	74.00	17.47	45.95	54.00	8.05	21.10	H	1	2





ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dB μ V/m]	PK+ Limit [dB μ V/m]	PK+ Margin [dB]	AVG Level [dB μ V/m]	AVG Limit [dB μ V/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
2	4,874.000	50.19	74.00	23.81	39.97	54.00	14.03	15.25	V	1	2
2	7,311.000	56.12	74.00	17.88	46.19	54.00	7.81	21.10	V	8.8	2



REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Limit value—Emission level.
2. 2437MHz: Fundamental frequency.



Test Report No.: PSU-QSU2306120115RF12

CHANNEL	TX Channel 11	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dB μ V/m]	PK+ Limit [dB μ V/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
2	2,459.500	112.32			7.40	H	359	1
2	2,483.500	67.57	74.00	6.43	7.36	H	204.1	2
2	2,484.500	69.31	74.00	4.69	7.36	H	46.2	2

