
FCC Test Report

Report No.: AGC15733240401FR01

FCC ID : 2BBCYDM-R89UV

APPLICATION PURPOSE : Original Equipment

PRODUCT DESIGNATION : Dual Band Digital Two Way Radio

BRAND NAME : LISHENG

MODEL NAME : DM-R89UV

APPLICANT : Lisheng Communications Co., Ltd.

DATE OF ISSUE : May 14, 2024

STANDARD(S) : FCC Part 90 Subpart I

REPORT VERSION : V1.0

Attestation of Global Compliance (Shenzhen) Co., Ltd



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd
Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: <http://www.agccert.com/>



Report Revise Record

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	May 14, 2024	Valid	Initial Release

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the “Dedicated Testing/Inspection Stamp” is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd
Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: <http://www.agccert.com/>

Table of Contents

1. General Information	5
2. Product Information	6
2.1 Product Technical Description	6
2.2 Test Frequency List	8
2.3 Related Submittal(S) / Grant (S)	9
2.4 Test Methodology	9
2.5 Calculation of Emission Indicators	9
2.6 Special Accessories	9
2.7 Equipment Modifications	9
3. Test Environment	10
3.1 Address of The Test Laboratory	10
3.2 Test Facility	10
3.3 Environmental Conditions	11
3.4 Measurement Uncertainty	11
3.5 List of Equipment Used	12
4. System Test Configuration	14
4.1 EUT Configuration	14
4.2 EUT Exercise	14
4.3 Configuration of Tested System	14
4.4 Equipment Used in Tested System	14
4.5 Summary of Test Results	15
5. Description of Test Modes	16
6. Frequency Stability	17
6.1 Provisions Applicable	17
6.2 Measurement Procedure	17
6.3 Measurement Setup	17
6.4 Measurement Result	18
7. 26dB Emission Bandwidth and 99% Occupied Bandwidth	22
7.1 Provisions Applicable	22
7.2 Measurement Procedure	22
7.3 Measurement Setup	22
7.4 Measurement Result	23
8. Spurious Radiated Emission	30
8.1 Provisions Applicable	30
8.2 Measurement Procedure	30
8.3 Measurement Setup	30
8.4 Measurement Result	32
8.5 Emission Mask Measurement Part	47
9. Modulation Characteristics	53
9.1 Provisions Applicable	53

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

9.2 Measurement Procedure.....	53
9.3 Measurement Setup	53
9.4 Measurement Result	54
10. Maximum Transmitter Power	58
10.1 Provisions Applicable	58
10.2 Measurement Procedure.....	58
10.3 Measurement Setup	58
10.4 Measurement Result	60
11. Spurious Emission on Antenna Port.....	65
11.1 Provisions Applicable.....	65
11.2 Measurement Procedure	65
11.3 Measurement Setup	65
11.4 Measurement Result	66
12. Transmitter Frequency Behavior	76
12.1 Provisions Applicable	76
12.2 Measurement Setup	76
12.3 Measurement Procedure.....	77
12.4 Measurement Result	79
13. Audio Low Pass Filter Response	81
13.1 Provisions Applicable	81
13.2 Measurement Procedure.....	82
13.3 Measurement Setup	82
13.4 Measurement Result	83
Appendix I: Photographs of Test Setup.....	85
Appendix II: Photographs of Test EUT	85

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the “Dedicated Testing/Inspection Stamp” is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

1. General Information

Applicant	Lisheng Communications Co., Ltd.
Address	5#, Chongxiang St., Econ. & Tech. Area, Quanzhou, Fujian, China
Manufacturer	Lisheng Communications Co., Ltd.
Address	5#, Chongxiang St., Econ. & Tech. Area, Quanzhou, Fujian, China
Factory	Lisheng Communications Co., Ltd.
Address	5#, Chongxiang St., Econ. & Tech. Area, Quanzhou, Fujian, China
Product Designation	Dual Band Digital Two Way Radio
Brand Name	LISHENG
Test Model	DM-R89UV
Date of receipt of test item	Apr. 01, 2024
Date of Test	Apr. 01, 2024~May 14, 2024
Deviation from Standard	No any deviation from the test method
Condition of Test Sample	Normal
Test Result	Pass
Test Report Form No	AGCER-FCC-PMR-V1

Note: The test results of this report relate only to the tested sample identified in this report.

Prepared By



Bibo Zhang
(Project Engineer)

May 14, 2024

Reviewed By



Calvin Liu
(Reviewer)

May 14, 2024

Approved By



Max Zhang
Authorized Officer

May 14, 2024

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd

Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd

Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: <http://www.agccert.com/>

2. Product Information

2.1 Product Technical Description

Communication Type	Voice / Data (Voice /Tone only)	
Operation Frequency Range	From 136MHz to 174MHz--VHF	
	From 400MHz to 470MHz--UHF	
Hardware Version	AR-55A-UV V1.0	
Software Version	AR55A-DMR-E01.13	
Modulation Type	Analog Voice:	FM
	Digital (Voice + Data):	4FSK
Digital Type	DMR	
Channel Separation	Analog Voice:	12.5 kHz
	Digital (Voice + Data):	12.5 kHz
Support Data Rate	9600bps	
Emission Designator	Analog Voice:	☒ VHF:9K97F3E-5W-12.5kHz
		☒ VHF:9K96F3E-1W-12.5kHz
		☒ UHF:10K0F3E-5W-12.5kHz
		☒ UHF:10K0F3E-1W-12.5kHz
	Digital (Voice + Data):	☒ VHF:7K27F1D-5W-12.5kHz
		☒ VHF:7K37F1W-1W-12.5kHz
		☒ UHF:7K37F1D-5W-12.5kHz
		☒ UHF:7K55F1W-1W-12.5kHz
Rated Output Power	VHF:5W/1W/UHF:5W/1W (It was fixed by the manufacturer, any individual can't arbitrarily change it.)	
Maximum Transmitter Power	VHF: 36.76dBm(5W-Analog)	VHF: 36.60dBm(5W-Digital)
	VHF: 29.85dBm(1W-Analog)	VHF: 29.84dBm(1W-Digital)
	UHF: 36.27dBm(5W-Analog)	UHF: 36.53dBm(5W-Digital)
	UHF: 29.88dBm(1W-Analog)	UHF: 29.90dBm(1W-Digital)
Antenna Designation	Detachable Antenna	
Antenna Gain	2.5dBi	
Frequency Tolerance	1.099ppm	
Power Supply	DC 7.4V 2200mAh by battery	
Adapter Information	Input: AC 100-240V 50/60Hz, 0.2A Output: DC 12V 500mA	

Note:

1. The product has the same digital working characters when operating in both two digitized voice/data mode. So only one set of test results for digital modulation modes are provided in this test report.
2. This equipment is capable of supporting a minimum data rate of 4800 bits per second per 6.25 kHz of channel bandwidth. DMR interphone's bandwidth is 12.5 kHz, and it has a double time slot, one is the speech

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

time slot, one is the data time slot, just language sequence is satisfied with 4800 bps/6.25 kHz BW.

3. The actual working frequency band of the device is UHF: 400-470MHz. According to the frequency division requirements of KDB634817 and the federal frequency allocation requirements, the working frequency band t

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the “Dedicated Testing/Inspection Stamp” is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd

Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd

Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: <http://www.agccert.com/>

2.2 Test Frequency List

Operation mode	Channel Separation	Operation Frequency Range	Test channel	Test Frequency
Analog/ Digital	12.5 kHz	400-470MHz	Bottom	406.125 MHz
	12.5 kHz	400-470MHz	Middle	453.2125 MHz
	12.5 kHz	400-470MHz	Middle	458.2125 MHz
	12.5 kHz	400-470MHz	Top	469.975 MHz
Analog/ Digital	12.5 kHz	136-174MHz	Bottom	136.025 MHz
	12.5 kHz	136-174MHz	Middle	155.7525 MHz
	12.5 kHz	136-174MHz	Top	173.975 MHz

Note:

In section KDB 634817 D01 Sections II) (f) (1) and (2):

Test at least one frequency in each band for each rule part applied under and ensure the device is capable of operating on the frequency under each rule part. This requirement may result in testing on multiple frequencies. Testing on one frequency may be acceptable if multiple listed bands for a rule part with a continuous frequency range are split to remove a conflict with other rules and the technical requirements in the split bands are the same. Additional requirements for RF exposure may apply.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd
Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/

2.3 Related Submittal(S) / Grant (S)

This submittal(s) (test report) is intended for FCC ID: **2BBCYDM-R89UV**, filing to comply with Part 2, Part 90 of the Federal Communication Commission rules.

2.4 Test Methodology

The tests were performed according to following standards:

No.	Identity	Document Title
1	FCC 47 CFR Part 90	Private Land Mobile Radio Services
2	FCC 47 CFR Part 2	Frequency allocations and radio treaty matters; general rules and regulations
3	ANSI TIA-102.CAAA-E	Project 25 Digital C4FM/CQPSK Transceiver Measurement Methods
4	ANSI/TIA-603-E-2016	Land Mobile FM or PM Communications Equipment Measurement and Performance Standards
5	ANSI C63.26-2015	American National Standard for Compliance Testing of Transmitters Used in Licensed Radio Services
6	KDB 971168 D01	KDB 971168 D01 Power Meas License Digital Systems v03r01
7	KDB 579009 D03	KDB 579009 D03 Applications Part 90 Refarming Bands v01
8	KDB 634817 D01	KDB 634817 D01 Freq Range Listing for Grants v04r01

2.5 Calculation of Emission Indicators

FCC Rules and Regulations Part 2.202: Necessary Bandwidth and Emission Bandwidth

For FM Mode (ChannelSpacing: 12.5kHz)

Emission Designator 11K0F3E

In this case, the maximum modulating frequency is 3.0 kHz with a 2.5 kHz deviation.

$BW = 2(M+D) = 2*(3.0 \text{ kHz} + 2.5 \text{ kHz}) = 11 \text{ kHz} = 11K0$

F3E portion of the designator represents an FM voice transmission.

Therefore, the entire designator for 12.5 kHz channel spacing FM mode is 11K0F3E.

For Digital Mode (Channel Spacing: 12.5 kHz)

Emission Designator 7K60F1D and 7K60F1W

The 99% energy rule was used for digital mode. It basically states that 99% of the modulation energy falls within X kHz, in this case, 7.60 kHz.

F1D and F1W portion of the designator indicates digital information.

Therefore, the entire designator for 12.5 kHz channel spacing digital mode is 7K60F1D and 7K60F1W.

2.6 Special Accessories

Not available for this EUT intended for grant.

2.7 Equipment Modifications

Not available for this EUT intended for grant.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd

Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd

Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/

3. Test Environment

3.1 Address of The Test Laboratory

Laboratory: Attestation of Global Compliance (Shenzhen) Co., Ltd.

Address: 1-2/F, Building 19, Junfeng Industrial Park, Chongqing Road, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

3.2 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

CNAS-Lab Code: L5488

Attestation of Global Compliance (Shenzhen) Co., Ltd. has been assessed and proved to follow CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories.)

A2LA-Lab Cert. No.: 5054.02

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to follow ISO/IEC 17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

FCC-Registration No.: 975832

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files with Registration 975832.

IC-Registration No.: 24842(CAB identifier: CN0063)

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the Certification and Engineering Bureau of Industry Canada. The acceptance letter from the IC is maintained in our files with Registration 24842.

3.3 Environmental Conditions

	Normal Conditions	Extreme Conditions
Temperature range (°C)	15 - 35	-20 - 50
Relative humidity range	20 % - 75 %	20 % - 75 %
Pressure range (kPa)	86 - 106	86 - 106
Power supply	DC 7.4V	LV DC 6.29V /HV DC 8.51V
Note: The Extreme Temperature and Extreme Voltages declared by the manufacturer.		

3.4 Measurement Uncertainty

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95%.

Test Items	Measurement Uncertainty
Frequency stability	$\pm 0.5\%$
Transmitter power conducted	$\pm 0.8\text{dB}$
Transmitter power Radiated	$\pm 1.3\text{dB}$
Conducted spurious emission 9kHz-40 GHz	$\pm 2.7\text{dB}$
Conducted Emission	$\pm 3.2\text{ dB}$
Radiated Emission below 1GHz	$\pm 3.9\text{ dB}$
Radiated Emission above 1GHz	$\pm 4.8\text{ dB}$
Occupied Channel Bandwidth	$\pm 2\%$
FM deviation	$\pm 2\%$
Audio level	$\pm 0.98\text{dB}$
Low Pass Filter Response	$\pm 0.65\text{dB}$
Modulation Limiting	0.42 %
Transient Frequency Behavior	6.8 %

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

3.5 List of Equipment Used

● RF Conducted Test System							
Used	Equipment No.	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
☒	AGC-ER-E086	Spectrum Analyzer	KEYSIGHT	N9020A	MY53300860	2023-06-01	2024-05-31
☒	AGC-EM-E002	Wireless Connectivity Tester	HP	8920B	US35010161	2023-06-02	2024-06-01
☐	AGC-EM-E001	Digital Connectivity Tester	Aeroflex	3920B	N/A	2023-06-02	2024-06-01
☒	AGC-ER-E059	Signal Generator	Agilent	N5182B	MY53050647	2024-02-01	2025-01-31
☒	AGC-ER-E037	Signal Generator	Agilent	N5182A	MY50140530	2023-06-01	2024-05-31
☒	AGC-ER-E075	Small Environmental Tester	SH-242	ESPEC	93008290	2022-08-03	2024-08-02
☒	AGC-EM-A007	30dB Attenuator	Weinachel	58-30-33	ML030	2023-06-01	2024-05-31
☒	AGC-EM-E040	Directional coupler	Werlatone	C5571-10	99463	2024-02-01	2026-01-31
☒	--	RF Connection Cable	N/A	1#	N/A	Each time	N/A
☒	--	RF Connection Cable	N/A	2#	N/A	Each time	N/A

● Radiated Spurious Emission							
Used	Equipment No.	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
☒	AGC-EM-E046	EMI Test Receiver	R&S	ESCI	10096	2024-02-01	2025-01-31
☒	AGC-EM-E061	Spectrum Analyzer	Agilent	N9010A	MY53470504	2023-06-01	2024-05-31
☒	AGC-ER-E032	Universal Radio Communication Tester	R&S	CMW500	120909	2023-07-05	2024-07-04
☒	AGC-EM-E086	Loop Antenna	ZHINAN	ZN30900C	18051	2024-03-05	2026-03-04
☒	AGC-EM-E001	Wideband Antenna	SCHWARZBECK	VULB9168	D69250	2023-05-11	2025-05-10
☒	AGC-EM-E005	Wideband Antenna	SCHWARZBECK	VULB9168	VULB9168-494	2023-01-05	2025-01-04
☒	AGC-EM-E029	Broadband Ridged Horn Antenna	ETS	3117	00034609	2024-03-31	2025-03-30
☒	AGC-EM-E102	Broadband Ridged Horn Antenna	ETS	3117	00154520	2023-06-03	2024-06-02
☐	AGC-EM-E082	Horn Antenna	SCHWARZBECK	BBHA 9170	#768	2023-11-13	2024-11-12
☒	AGC-EM-E146	Pre-amplifier	ETS	3117-PA	00246148	2022-08-04	2024-08-03
☐	AGC-EM-E021	Pre-amplifier	MITEQ	AM-4A-000115	1465421	2022-06-08	2024-06-07
☒	AGC-ER-E037	Signal Generator	Agilent	N5182A	MY50140530	2023-06-01	2024-05-31
☐	AGC-EM-A139	6dB Attenuator	Eeatsheep	LM-XX-6-5W	N/A	2023-06-09	2024-06-08
☒	AGC-EM-A088	UHF Filter	N/A	N/A	N/A	2023-06-01	2024-05-31
☐	AGC-EM-A089	VHF Filter	N/A	N/A	N/A	2023-06-01	2024-05-31
☐	AGC-EM-E110	Low Pass Filter	N/A	N/A	N/A	2023-06-01	2024-05-31

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

● Test Software					
Used	Equipment No.	Test Equipment	Manufacturer	Model No.	Version Information
☒	AGC-EM-S004	RE Test System	Tonscend	TS ⁺ Ver2.1(JS32-RE)	4.0.0.0

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the “Dedicated Testing/Inspection Stamp” is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd
Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: <http://www.agccert.com/>

4. System Test Configuration

4.1 EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commission's requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

4.2 EUT Exercise

The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

4.3 Configuration of Tested System

Fig. 2-1 Configuration of Tested System



Table 2-1 Equipment Used in Tested System

4.4 Equipment Used in Tested System

The following peripheral devices and interface cables were connected during the measurement:

☒ Test Accessories Come From The Laboratory

No.	Equipment	Model No.	Manufacturer	Specification Information	Cable
1	Load Antenna	HG-E10	Amphenol	Terminator DC -3G 50W	N/A

☒ Test Accessories Come From The Manufacturer

No.	Equipment	Model No.	Manufacturer	Specification Information	Cable
1	Battery	R88D-BAT	LISHENG	DC 7.4V, 2200mAh	N/A
2	Adapter	NLA050120W1A6	N/A	Input: AC 100-240V~50/60Hz 0.2A MaX Output: DC 12V 500mA	N/A
3	Charger	N/A	N/A	Input: DC 12V 500mA Output: DC 8.4V 0.45A	N/A
4	Antenna	N/A	N/A	N/A	N/A
5	USB Cable	N/A	N/A	N/A	N/A
6	Back Clip	N/A	N/A	N/A	N/A

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

4.5 Summary of Test Results

Item	FCC Rules	Description Of Test	Result
1	47 CFR FCC PART 90	Antenna Equipment	Pass
2	§90.205& 2.1046	Maximum Transmitter Power	Pass
3	§90.207& 2.1047	Modulation Characteristic	Pass
4	§2.1047	Audio Low Pass Filter Response	Pass
5	§90.209& 2.1049	26dB Emission Bandwidth and 99% Occupied Bandwidth	Pass
6	§90.210& 2.1049	Emission Mask	Pass
7	§90.213& 2.1055	Frequency Tolerance	Pass
8	§90.214	Transmitter Frequency Behavior	Pass
9	§90.210& 2.1051	Spurious Emission on Antenna Port	Pass
10	§90.210& 2.1053	Spurious Radiated Emission	Pass

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the “Dedicated Testing/Inspection Stamp” is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

5. Description of Test Modes

The EUT (**Dual Band Digital Two Way Radio**) has been tested under normal operating condition. (The top channel, the middle channel and the bottom channel) are chosen for testing at each channel separation.

No.	Test Mode Description	Channel Separation
1	TX Bottom channel-VHF	12.5 kHz
2	TX Middle channel-VHF	12.5 kHz
3	TX Middle channel-VHF	12.5 kHz
4	TX Top channel-UHF	12.5 kHz
5	TX Bottom channel-UHF	12.5 kHz
6	TX Middle channel-UHF	12.5 kHz
7	TX Middle channel-VHF	12.5 kHz
8	TX Top channel-UHF	12.5 kHz

Note:

1. Only the result of the worst case was recorded in the report, if no other cases.
2. The battery is full-charged during the test.
3. For Radiated Emission, 3axis were chosen for testing for each applicable mode.
4. For Conducted Test method, a temporary antenna connector is provided by the manufacture.
5. Manufacturers use computer PC programming software to switch and operate frequency points, refer to the instructions for details

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd
Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: <http://www.agccert.com/>

6. Frequency Stability

6.1 Provisions Applicable

- According to FCC §2.1055, §90.213, the frequency stability shall be measured with variation of ambient temperature from -30°C to $+50^{\circ}\text{C}$ centigrade.
- According to FCC Part 2 Section 2.1055(d)(2), for battery powered equipment, the frequency stability shall be measured with reducing primary supply voltage to the battery operating end point, which is specified by the manufacturer.
- According to FCC Part 90 Section 90.213, the frequency tolerance must be maintained within 0.00025% for 12.5 kHz channel separation and 0.0001% for 6.25 kHz channel separation.

6.2 Measurement Procedure


6.2.1 Frequency stability versus environmental temperature

- Setup the configuration per figure 1 for frequencies measurement inside an environment chamber, Install new battery in the EUT.
- Turn on EUT and set SA center frequency to the EUT radiated frequency. Set SA Resolution Bandwidth to 1kHz and Video Resolution Bandwidth to 1kHz and Frequency Span to 50kHz. Record this frequency as reference frequency.
- Set the temperature of chamber to 50°C . Allow sufficient time (approximately 30 min) for the temperature of the chamber to stabilize. While maintaining a constant temperature inside the chamber, turn the EUT on and measure the EUT operating frequency.
- Repeat step 2 with a 10°C decreased per stage until the lowest temperature -30°C is measured, record all measured frequencies on each temperature step.

6.2.2 Frequency stability versus input voltage

- Setup the configuration per figure 1 for frequencies measured at temperature if it is within 15°C to 25°C . Otherwise, an environment chamber set for a temperature of 20°C shall be used. The EUT shall be powered by DC 7.4V.
- Set SA center frequency to the EUT radiated frequency. Set SA Resolution Bandwidth to 1 kHz and Video Resolution Bandwidth to 1kHz. Record this frequency as reference frequency.
- Supply the EUT primary voltage at the operating end point which is specified by manufacturer and record the frequency.

6.3 Measurement Setup



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

6.4 Measurement Result

12.5 kHz Channel Separation, Analog modulation, Assigned Frequency For VHF-5W						
Test conditions		Frequency error (ppm)			Limit (ppm)	Result
Voltage (V)	Temp (°C)	Test Frequency (MHz)				
		136.025	155.7525	173.975		
7.40	-30	0.940	0.653	0.885	5	Pass
	-20	0.603	1.028	0.920		
	-10	0.638	0.654	1.064		
	0	1.085	1.008	0.785		
	10	0.662	0.633	0.808		
	20	0.950	0.955	0.540		
	30	1.078	0.761	0.900		
	40	0.557	0.862	0.869		
	50	0.551	0.998	0.695		
8.51	20	0.582	1.038	0.580		
6.29	20	0.793	0.951	0.613		

12.5 kHz Channel Separation, Analog modulation, Assigned Frequency For VHF-1W						
Test conditions		Frequency error (ppm)			Limit (ppm)	Result
Voltage (V)	Temp (°C)	Test Frequency (MHz)				
		136.025	155.7525	173.975		
7.40	-30	0.532	0.688	0.752	5	Pass
	-20	0.544	0.951	1.096		
	-10	1.032	0.645	0.800		
	0	1.017	0.957	0.592		
	10	0.530	0.535	0.932		
	20	0.506	0.698	0.567		
	30	0.971	1.050	0.998		
	40	0.953	0.556	0.670		
	50	0.990	0.571	0.991		
8.51	20	0.951	0.827	0.737		
6.29	20	0.645	0.761	0.683		

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

12.5 kHz Channel Separation, Analog modulation, Assigned Frequency For UHF-5W							
Test conditions		Frequency error (ppm)				Limit (ppm)	Result
Voltage (V)	Temp (°C)	Test Frequency (MHz)					
		406.125	453.2125	458.2125	469.975		
7.40	-30	0.996	0.688	0.813	0.728	5	Pass
	-20	0.793	0.524	0.695	0.659		
	-10	0.670	0.957	0.593	0.346		
	0	0.760	0.581	1.024	0.612		
	10	0.621	0.559	0.990	0.384		
	20	0.507	0.503	0.768	0.601		
	30	0.784	0.898	0.625	0.397		
	40	0.528	0.784	0.544	0.816		
	50	1.015	0.747	0.959	0.663		
8.51	20	1.044	0.844	0.789	0.307		
6.29	20	0.888	0.714	0.770	0.661		

12.5 kHz Channel Separation, Analog modulation, Assigned Frequency For UHF-1W							
Test conditions		Frequency error (ppm)				Limit (ppm)	Result
Voltage (V)	Temp (°C)	Test Frequency (MHz)					
		406.125	453.2125	458.2125	469.975		
7.40	-30	0.795	0.925	0.711	0.461	5	Pass
	-20	0.902	1.033	0.929	0.485		
	-10	1.079	0.673	0.583	0.908		
	0	1.006	0.892	0.891	0.428		
	10	1.074	0.929	0.863	0.344		
	20	0.659	0.783	0.871	0.642		
	30	0.521	0.507	0.955	0.620		
	40	0.706	0.711	0.992	0.945		
	50	0.816	0.571	0.983	0.372		
8.51	20	0.835	1.094	0.761	0.502	5	Pass
6.29	20	0.650	0.993	0.629	0.687		

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

12.5 kHz Channel Separation, Digital modulation, Assigned Frequency For VHF-5W						
Test conditions		Frequency error (ppm)			Limit (ppm)	Result
Voltage (V)	Temp (°C)	Test Frequency (MHz)				
		136.025	155.7525	173.975		
7.40	-30	0.684	0.912	0.781	5	Pass
	-20	0.654	0.782	0.765		
	-10	0.898	0.603	0.742		
	0	0.912	0.611	0.563		
	10	1.099	0.557	0.652		
	20	1.032	0.573	0.725		
	30	0.522	0.652	0.559		
	40	0.856	0.653	0.353		
	50	0.913	0.889	0.450		
8.51	20	0.602	0.496	0.437		
6.29	20	0.704	0.307	0.518		

12.5 kHz Channel Separation, Digital modulation, Assigned Frequency For VHF-1W						
Test conditions		Frequency error (ppm)			Limit (ppm)	Result
Voltage (V)	Temp (°C)	Test Frequency (MHz)				
		136.025	155.7525	173.975		
7.40	-30	0.828	0.789	0.742	5	Pass
	-20	1.018	0.444	0.390		
	-10	0.522	0.647	0.340		
	0	0.689	0.428	0.559		
	10	0.959	0.533	0.605		
	20	0.662	0.609	0.713		
	30	0.704	0.570	0.423		
	40	0.837	0.328	0.954		
	50	0.711	0.548	0.738		
8.51	20	0.987	0.399	0.605		
6.29	20	0.718	0.665	0.939		

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

12.5 kHz Channel Separation, Digital modulation, Assigned Frequency For UHF-5W							
Test conditions		Frequency error (ppm)				Limit (ppm)	Result
Voltage (V)	Temp (°C)	Test Frequency (MHz)					
		406.125	453.2125	458.2125	469.975		
7.40	-30	0.507	0.983	0.900	0.323	5	Pass
	-20	0.565	0.533	1.068	0.909		
	-10	0.825	0.907	0.843	0.551		
	0	0.668	0.983	0.755	0.313		
	10	0.537	0.804	0.799	0.822		
	20	1.011	0.801	0.622	0.602		
	30	0.962	0.579	0.868	0.955		
	40	0.716	1.039	0.614	0.465		
	50	0.546	0.925	0.664	0.834		
8.51	20	0.797	0.960	0.707	0.899		
6.29	20	0.664	0.756	0.620	0.946		

12.5 kHz Channel Separation, Digital modulation, Assigned Frequency For UHF-1W							
Test conditions		Frequency error (ppm)				Limit (ppm)	Result
Voltage (V)	Temp (°C)	Test Frequency (MHz)					
		406.125	453.2125	458.2125	469.975		
7.40	-30	0.900	0.796	0.863	0.557	5	Pass
	-20	0.519	0.547	0.873	0.500		
	-10	1.064	0.972	0.874	0.927		
	0	0.915	0.916	1.045	0.904		
	10	0.941	0.754	0.538	0.428		
	20	0.654	0.905	0.732	0.752		
	30	0.825	0.831	0.948	0.404		
	40	0.753	0.914	0.626	0.707		
	50	0.501	0.805	0.862	0.652		
8.51	20	0.968	0.745	0.662	0.372		
6.29	20	0.763	0.603	0.576	0.727		

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

7. 26dB Emission Bandwidth and 99% Occupied Bandwidth

7.1 Provisions Applicable


FCC Part 90.209 & FCC Part 2.1049:

The authorized bandwidth shall be 11.25 kHz for 12.5 kHz channel separation and 6 kHz for 6.25 kHz channel separation.

7.2 Measurement Procedure

1. The EUT was modulated by 2.5kHz sine wave audio signal; the level of the audio signal employed is 16dB greater than that necessary to produce 50% of rated system deviation.
2. Rated system deviation is 2.5 kHz for 12.5kHz channel spacing.
3. Spectrum set as follow:
4. Centre frequency = fundamental frequency.
5. Span=50kHz for 12.5kHz channel spacing.
6. RBW=100Hz, VBW=300Hz, Sweep = auto.
7. Detector function = peak, Trace = max hold.
8. Set 99% Occupied Bandwidth and 26dB Occupied Bandwidth.
9. Measure and record the results in the test report.

7.3 Measurement Setup



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

7.4 Measurement Result


Measurement Result of VHF-Analog Modulation-5W				
Operating Frequency	12.5 kHz Channel Separation			
	Occupied Bandwidth	Emission Bandwidth	Limits	Result
136.025 MHz	9.952 kHz	10.16 kHz	11.25 kHz	Pass
155.7525 MHz	9.971 kHz	10.17 kHz	11.25 kHz	Pass
173.975 MHz	9.974 kHz	10.18 kHz	11.25 kHz	Pass
Measurement Result of VHF-Analog Modulation-1W				
Operating Frequency	12.5 kHz Channel Separation			
	Occupied Bandwidth	Emission Bandwidth	Limits	Result
136.025 MHz	9.952 kHz	10.17 kHz	11.25 kHz	Pass
155.7525 MHz	9.953 kHz	10.17 kHz	11.25 kHz	Pass
173.975 MHz	9.959 kHz	10.17 kHz	11.25 kHz	Pass
Measurement Result of UHF-Analog Modulation-5W				
Operating Frequency	12.5 kHz Channel Separation			
	Occupied Bandwidth	Emission Bandwidth	Limits	Result
406.125 MHz	9.966 kHz	10.17 kHz	11.25 kHz	Pass
453.2125 MHz	10.015 kHz	10.19 kHz	11.25 kHz	Pass
458.2125 MHz	10.002 kHz	10.18 kHz	11.25 kHz	Pass
469.975 MHz	9.940 kHz	10.16 kHz	11.25 kHz	Pass
Measurement Result of UHF-Analog Modulation-1W				
Operating Frequency	12.5 kHz Channel Separation			
	Occupied Bandwidth	Emission Bandwidth	Limits	Result
406.125 MHz	9.950 kHz	10.17 kHz	11.25 kHz	Pass
453.2125 MHz	10.004 kHz	10.18 kHz	11.25 kHz	Pass
458.2125 MHz	10.002 kHz	10.18 kHz	11.25 kHz	Pass
469.975 MHz	9.956 kHz	10.17 kHz	11.25 kHz	Pass

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Measurement Result of VHF-Digital Modulation-5W				
Operating Frequency	12.5 kHz Channel Separation			
	Occupied Bandwidth	Emission Bandwidth	Limits	Result
136.025 MHz	7.113 kHz	9.532 kHz	11.25 kHz	Pass
155.7525 MHz	7.276 kHz	9.273 kHz	11.25 kHz	Pass
173.975 MHz	7.211 kHz	9.690 kHz	11.25 kHz	Pass
Measurement Result of VHF-Digital Modulation-1W				
Operating Frequency	12.5 kHz Channel Separation			
	Occupied Bandwidth	Emission Bandwidth	Limits	Result
136.025 MHz	7.367 kHz	9.684 kHz	11.25 kHz	Pass
155.7525 MHz	7.277 kHz	9.568 kHz	11.25 kHz	Pass
173.975 MHz	7.442 kHz	9.160 kHz	11.25 kHz	Pass
Measurement Result of UHF-Digital Modulation-5W				
Operating Frequency	12.5 kHz Channel Separation			
	Occupied Bandwidth	Emission Bandwidth	Limits	Result
406.125 MHz	7.314 kHz	8.519 kHz	11.25 kHz	Pass
453.2125 MHz	7.237 kHz	9.928 kHz	11.25 kHz	Pass
458.2125 MHz	7.373 kHz	9.612 kHz	11.25 kHz	Pass
469.975 MHz	7.218 kHz	10.06 kHz	11.25 kHz	Pass
Measurement Result of UHF-Digital Modulation-1W				
Operating Frequency	12.5 kHz Channel Separation			
	Occupied Bandwidth	Emission Bandwidth	Limits	Result
406.125 MHz	7.549 kHz	9.596 kHz	11.25 kHz	Pass
453.2125 MHz	7.440 kHz	9.648 kHz	11.25 kHz	Pass
458.2125 MHz	7.510 kHz	9.770 kHz	11.25 kHz	Pass
469.975 MHz	7.336 kHz	9.783 kHz	11.25 kHz	Pass


Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Test plot as follows:




Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.


12.5kHz, FM Modulation:406.125MHz-5W




12.5kHz, FM Modulation:453.2125MHz-5W




12.5kHz, FM Modulation:458.2125MHz-5W




12.5kHz, FM Modulation:469.975MHz-5W



12.5kHz, FM Modulation:406.125MHz-1W




12.5kHz, FM Modulation:453.2125MHz-1W




Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.


12.5kHz, FM Modulation:458.2125MHz-1W




12.5kHz, FM Modulation:469.975MHz-1W




12.5kHz,4FSK Modulation:136.025MHz-5W




12.5kHz, 4FSK Modulation:155.7525MHz-5W



12.5kHz, 4FSK Modulation:173.975MHz-5W




12.5kHz,4FSK Modulation:136.025MHz-1W




Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.


12.5kHz, 4FSK Modulation:155.7525MHz-1W




12.5kHz, 4FSK Modulation:173.975MHz-1W




12.5kHz, 4FSK Modulation:406.125MHz-5W




12.5kHz, 4FSK Modulation:453.2125MHz-5W



12.5kHz, 4FSK Modulation:458.2125MHz-5W




12.5kHz, 4FSK Modulation:469.975MHz-5W




Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.


12.5kHz, 4FSK Modulation:406.125MHz-1W




12.5kHz, 4FSK Modulation:453.2125MHz-1W



12.5kHz, 4FSK Modulation:458.2125MHz-1W



12.5kHz, 4FSK Modulation:469.975MHz-1W



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

8. Spurious Radiated Emission

8.1 Provisions Applicable

According to FCC §2.1053 and §90.210, the power of each unwanted emission shall be less than Transmitted Power as specified below for transmitters designed to operate with each channel separation.

Emission Mask D -for 12.5 kHz Channel Separation:

- (1) On any frequency removed from the center of the authorized bandwidth f_0 to 5.625 kHz removed from f_0 : Zero dB.
- (2) On any frequency removed from the center of the authorized bandwidth by a displacement Frequency (f_d in kHz) f_0 of more than 5.625 kHz but no more than 12.5 kHz: At least $7.27(f_d - 2.88 \text{ kHz})$ dB
- (3) On any frequency removed from the center of the authorized bandwidth by a displacement Frequency (f_d in kHz) f_0 of more than 12.5 kHz: At least $50 + 10 \log(P)$ dB or 70 dB, whichever is lesser attenuation.

8.2 Measurement Procedure

1. On a test site, the EUT shall be placed on a turntable, and in the position closest to the normal use as declared by the user.
2. The test antenna shall be oriented initially for vertical polarization located 3m from the EUT to correspond to the transmitter.
3. The output of the antenna shall be connected to the measuring receiver and either a peak or quasi-peak detector was used for the measurement as indicated on the report. The detector selection is based on how close the emission level was approaching the limit.
4. The transmitter shall be switched on; if possible, without the modulation and the measurement receiver shall be tuned to the frequency of the transmitter under test.
5. The test antenna shall be raised and lowered through the specified range of height until the measuring receiver detects a maximum signal level.
6. The transmitter shall then be rotated through 360° in the horizontal plane, until the maximum signal level is detected by the measuring receiver.
7. The test antenna shall be raised and lowered again through the specified range of height until the measuring receiver detects a maximum signal level.
8. The maximum signal level detected by the measuring receiver shall be noted.
9. The measurement shall be repeated with the test antenna set to horizontal polarization.
10. (Replace the antenna with a proper Antenna (substitution antenna)).
11. The substitution antenna shall be oriented for vertical polarization and, if necessary, the length of the substitution antenna shall be adjusted to correspond to the frequency of transmitting.
12. The substitution antenna shall be connected to a calibrated signal generator.
13. If necessary, the input attenuator setting of the measuring receiver shall be adjusted in order to increase the sensitivity of the measuring receiver.
14. The test antenna shall be raised and lowered through the specified range of the height to ensure that the maximum signal is received.
15. The input signal to substitution antenna shall be adjusted to the level that produces a level detected by the measuring receiver, that is equal to the level noted while the transmitter radiated power was measured, corrected for the change of input attenuation setting of the measuring receiver.
16. The input level to the substitution antenna shall be recorded as power level in dBm, corrected for any change of input attenuator setting of the measuring receiver.
17. The measurement shall be repeated with the test antenna and the substitution antenna oriented for horizontal polarization.

8.3 MEASUREMENT SETUP



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15 days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd



Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd

Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: <http://www.agccert.com/>

Radiated Emissions 30MHz to 1GHz Test setup



Radiated Emissions Above 1GHz Test setup



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the “Dedicated Testing/Inspection Stamp” is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd

Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd

Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: <http://www.agccert.com/>

8.4 Measurement Result

The RF output of the EUT was connected to a spectrum analyzer through appropriate attenuation. The resolution bandwidth of the spectrum analyzer was set at 100 kHz for below 1GHz, and 1MHz for above 1GHz. Sufficient scans were taken to show any out of band emissions up to 10 harmonic.

In the semi-anechoic chamber, setup as illustrated above the DUT placed on the 0.8m height of Turn Table, rotated the table 45 degree each interval to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1m to 4m to find the maximum polar radiated power for each degree interval. The "Read Value" is the spectrum reading of maximum power value.

The substitution antenna is substituted for DUT at the same position and signals generator (S.G) export the CW signal to the substitution antenna via a TX cable. The receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1m to 4m to find the maximum radiation power. Record the power level of maximum radiation power from spectrum. So, the Measured substitution value = Ref level of S.G + TX cables loss – Substituted Antenna Gain.

EIRP = "Read Value" + Measured substitution value + 2.15.


Test limit calculation:

Preliminary calculation	Final Result
At least $50 + 10 \log(P) = 50 + 10 \log(5) = 56.99$ (dB)	Limit=P- Preliminary calculation= $36.99 - 56.99 = -20$ dBm
At least $50 + 10 \log(P) = 50 + 10 \log(1) = 50.00$ (dB)	Limit=P- Preliminary calculation= $30.00 - 50.00 = -20$ dBm

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.


Attestation of Global Compliance(Shenzhen)Co., Ltd
Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd
Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: <http://www.agccert.com/>

Test Mode:	TX:136.025MHz-FM	Polarity:	Horizontal
------------	------------------	-----------	------------



NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	408.3	-79.01	-49.13	-20.00	29.13	29.88	196	Horizontal
2	544.1	-79.66	-46.96	-20.00	26.96	32.70	50	Horizontal
3	680.87	-79.68	-44.76	-20.00	24.76	34.92	282	Horizontal
4	816.67	-75.33	-37.81	-20.00	17.81	37.52	59	Horizontal
5	1224.4474	-44.16	-48.25	-20.00	28.25	-4.09	59	Horizontal
6	2176.2926	-49.06	-46.86	-20.00	26.86	2.20	0	Horizontal

Test Mode:	TX:136.025MHz-FM	Polarity:	Vertical
------------	------------------	-----------	----------



NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	271.53	-78.02	-49.64	-20.00	29.64	28.38	45	Vertical
2	408.3	-67.35	-37.47	-20.00	17.47	29.88	328	Vertical
3	544.1	-67.18	-34.48	-20.00	14.48	32.70	345	Vertical
4	680.87	-71.03	-36.11	-20.00	16.11	34.92	360	Vertical
5	952.47	-81.21	-42.67	-20.00	22.67	38.54	9	Vertical
6	1224.4474	-36.97	-41.06	-20.00	21.06	-4.09	27	Vertical


Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd

Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd


Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/

Test Mode:	TX:155.7525MHz-FM	Polarity:	Horizontal
------------	-------------------	-----------	------------



NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	311.3	-68.26	-40.19	-20.00	20.19	28.07	150	Horizontal
2	623.64	-71.84	-37.05	-20.00	17.05	34.79	287	Horizontal
3	778.84	-62.60	-25.76	-20.00	5.76	36.84	0	Horizontal
4	935.01	-79.48	-41.26	-20.00	21.26	38.22	158	Horizontal
5	1869.587	-44.34	-43.92	-20.00	23.92	0.42	350	Horizontal
6	2180.9931	-45.09	-42.89	-20.00	22.89	2.20	350	Horizontal

Test Mode:	TX:155.7525MHz-FM	Polarity:	Vertical
------------	-------------------	-----------	----------



NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	467.47	-69.86	-38.56	-20.00	18.56	31.30	358	Vertical
2	623.64	-64.96	-30.17	-20.00	10.17	34.79	342	Vertical
3	778.84	-61.95	-25.11	-20.00	5.11	36.84	18	Vertical
4	935.01	-73.90	-35.68	-20.00	15.68	38.22	18	Vertical
5	1245.5996	-32.21	-36.30	-20.00	16.30	-4.09	342	Vertical
6	1558.1808	-34.39	-37.80	-20.00	17.80	-3.41	333	Vertical


Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd

Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd


Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/

Test Mode:	TX:173.975MHz-FM	Polarity:	Horizontal
------------	------------------	-----------	------------



NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	348.16	-72.46	-44.14	-20.00	24.14	28.32	180	Horizontal
2	521.79	-69.35	-37.08	-20.00	17.08	32.27	44	Horizontal
3	696.39	-60.74	-25.72	-20.00	5.72	35.02	27	Horizontal
4	870.02	-64.70	-27.42	-20.00	7.42	37.28	61	Horizontal
5	1740.324	-35.65	-36.82	-20.00	16.82	-1.17	78	Horizontal
6	2262.0762	-39.18	-36.89	-20.00	16.89	2.29	316	Horizontal

Test Mode:	TX:173.975MHz-FM	Polarity:	Vertical
------------	------------------	-----------	----------



NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	521.79	-58.27	-26.00	-20.00	6.00	32.27	350	Vertical
2	696.39	-60.09	-25.07	-20.00	5.07	35.02	325	Vertical
3	870.02	-62.51	-25.23	-20.00	5.23	37.28	358	Vertical
4	1392.4892	-24.12	-28.23	-20.00	8.23	-4.11	360	Vertical
5	1740.324	-28.31	-29.48	-20.00	9.48	-1.17	360	Vertical
6	2435.9936	-34.00	-31.54	-20.00	11.54	2.46	9	Vertical


Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd

Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd


Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/

Test Mode:	TX:406.125MHz-FM	Polarity:	Horizontal
------------	------------------	-----------	------------



NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	1218.5719	-21.38	-25.46	-20.00	5.46	-4.08	304	Horizontal
2	2030.5781	-28.47	-26.42	-20.00	6.42	2.05	10	Horizontal
3	3249.1749	-28.63	-26.73	-20.00	6.73	1.90	20	Horizontal
4	3655.7656	-26.68	-24.32	-20.00	4.32	2.36	296	Horizontal
5	4467.7718	-29.78	-25.47	-20.00	5.47	4.31	304	Horizontal
6	6091.7842	-31.66	-24.79	-20.00	4.79	6.87	270	Horizontal

Test Mode:	TX:406.125MHz-FM	Polarity:	Vertical
------------	------------------	-----------	----------



NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	812.79	-69.41	-31.85	-20.00	11.85	37.56	325	Vertical
2	1218.5719	-25.33	-29.41	-20.00	9.41	-4.08	20	Vertical
3	2030.5781	-34.29	-32.24	-20.00	12.24	2.05	256	Vertical
4	2842.5843	-35.99	-34.15	-20.00	14.15	1.84	307	Vertical
5	3655.7656	-33.98	-31.62	-20.00	11.62	2.36	105	Vertical
6	6091.7842	-36.68	-29.81	-20.00	9.81	6.87	333	Vertical


Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd

Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd


Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/

Test Mode:	TX:453.2125MHz-FM	Polarity:	Horizontal
------------	-------------------	-----------	------------



NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	2719.1969	-30.79	-28.70	-20.00	8.70	2.09	0	Horizontal
2	3172.7923	-27.07	-25.28	-20.00	5.28	1.79	12	Horizontal
3	3626.3876	-27.55	-25.21	-20.00	5.21	2.34	274	Horizontal
4	4078.8079	-27.24	-24.44	-20.00	4.44	2.80	300	Horizontal
5	4532.4032	-29.85	-25.38	-20.00	5.38	4.47	308	Horizontal
6	5892.0142	-31.12	-24.62	-20.00	4.62	6.50	257	Horizontal

Test Mode:	TX:453.2125MHz-FM	Polarity:	Vertical
------------	-------------------	-----------	----------



NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	906.88	-78.38	-40.71	-20.00	20.71	37.67	309	Vertical
2	2719.1969	-39.43	-37.34	-20.00	17.34	2.09	317	Vertical
3	4078.8079	-36.60	-33.80	-20.00	13.80	2.80	266	Vertical
4	5438.4188	-40.88	-35.19	-20.00	15.19	5.69	300	Vertical
5	5892.0142	-31.49	-24.99	-20.00	4.99	6.50	334	Vertical
6	6345.6096	-37.76	-30.40	-20.00	10.40	7.36	266	Vertical


Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd

Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd


Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/

Test Mode:	TX:458.2125MHz-FM	Polarity:	Horizontal
------------	-------------------	-----------	------------



NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	3208.0458	-27.17	-25.33	-20.00	5.33	1.84	275	Horizontal
2	3666.3416	-26.64	-24.28	-20.00	4.28	2.36	291	Horizontal
3	4124.6375	-27.66	-24.68	-20.00	4.68	2.98	300	Horizontal
4	4581.7582	-30.20	-25.68	-20.00	5.68	4.52	308	Horizontal
5	5498.3498	-29.69	-23.90	-20.00	3.90	5.79	258	Horizontal
6	5956.6457	-32.17	-25.56	-20.00	5.56	6.61	266	Horizontal


Test Mode:	TX:458.2125MHz-FM	Polarity:	Vertical
------------	-------------------	-----------	----------



NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	2749.75	-37.73	-35.70	-20.00	15.70	2.03	321	Vertical
2	4124.6375	-39.54	-36.56	-20.00	16.56	2.98	329	Vertical
3	4582.9333	-40.66	-36.14	-20.00	16.14	4.52	252	Vertical
4	5498.3498	-38.30	-32.51	-20.00	12.51	5.79	295	Vertical
5	5956.6457	-31.19	-24.58	-20.00	4.58	6.61	337	Vertical
6	6414.9415	-41.91	-34.42	-20.00	14.42	7.49	268	Vertical


Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Test Mode:	TX:469.975MHz-FM	Polarity:	Horizontal
------------	------------------	-----------	------------



NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	3290.304	-30.12	-28.15	-20.00	8.15	1.97	16	Horizontal
2	3760.351	-30.03	-27.63	-20.00	7.63	2.40	272	Horizontal
3	4230.398	-26.75	-23.36	-20.00	3.36	3.39	289	Horizontal
4	4700.445	-29.74	-25.09	-20.00	5.09	4.65	314	Horizontal
5	5639.3639	-33.68	-27.64	-20.00	7.64	6.04	255	Horizontal
6	6109.4109	-31.55	-24.65	-20.00	4.65	6.90	272	Horizontal


Test Mode:	TX:469.975MHz-FM	Polarity:	Vertical
------------	------------------	-----------	----------



NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	1410.116	-34.22	-38.34	-20.00	18.34	-4.12	302	Vertical
2	2820.257	-36.76	-34.88	-20.00	14.88	1.88	310	Vertical
3	4230.398	-37.00	-33.61	-20.00	13.61	3.39	345	Vertical
4	4700.445	-39.35	-34.70	-20.00	14.70	4.65	310	Vertical
5	5639.3639	-41.00	-34.96	-20.00	14.96	6.04	319	Vertical
6	6109.4109	-38.57	-31.67	-20.00	11.67	6.90	268	Vertical


Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Test Mode:	TX:136.025MHz-4FSK	Polarity:	Horizontal
------------	--------------------	-----------	------------



NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	408.3	-78.06	-48.18	-20.00	28.18	29.88	179	Horizontal
2	544.1	-78.09	-45.39	-20.00	25.39	32.70	0	Horizontal
3	680.87	-79.57	-44.65	-20.00	24.65	34.92	110	Horizontal
4	816.67	-74.25	-36.73	-20.00	16.73	37.52	85	Horizontal
5	1224.4474	-43.52	-47.61	-20.00	27.61	-4.09	59	Horizontal
6	2176.2926	-48.36	-46.16	-20.00	26.16	2.20	351	Horizontal

Test Mode:	TX:136.025MHz-4FSK	Polarity:	Vertical
------------	--------------------	-----------	----------



NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	271.53	-79.03	-50.65	-20.00	30.65	28.38	1	Vertical
2	408.3	-66.25	-36.37	-20.00	16.37	29.88	326	Vertical
3	544.1	-64.99	-32.29	-20.00	12.29	32.70	326	Vertical
4	680.87	-70.16	-35.24	-20.00	15.24	34.92	360	Vertical
5	952.47	-80.85	-42.31	-20.00	22.31	38.54	27	Vertical
6	1224.4474	-36.33	-40.42	-20.00	20.42	-4.09	360	Vertical


Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd

Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd


Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/

Test Mode:	TX:155.7525MHz-4FSK	Polarity:	Horizontal
------------	---------------------	-----------	------------



NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	311.3	-69.96	-41.89	-20.00	21.89	28.07	138	Horizontal
2	623.64	-75.33	-40.54	-20.00	20.54	34.79	284	Horizontal
3	778.84	-61.44	-24.60	-20.00	4.60	36.84	9	Horizontal
4	935.01	-76.53	-38.31	-20.00	18.31	38.22	190	Horizontal
5	1869.587	-44.60	-44.18	-20.00	24.18	0.42	104	Horizontal
6	2180.9931	-44.22	-42.02	-20.00	22.02	2.20	9	Horizontal

Test Mode:	TX:155.7525MHz-4FSK	Polarity:	Vertical
------------	---------------------	-----------	----------



NO.	Freq. [MHz]	Reading [dBm]	Level [dBm]	Limit [dBm]	Margin [dB]	Factor [dB]	Angle [°]	Polarity
1	311.3	-72.18	-44.11	-20.00	24.11	28.07	76	Vertical
2	467.47	-71.86	-40.56	-20.00	20.56	31.30	33	Vertical
3	623.64	-66.38	-31.59	-20.00	11.59	34.79	316	Vertical
4	778.84	-61.91	-25.07	-20.00	5.07	36.84	7	Vertical
5	935.01	-69.65	-31.43	-20.00	11.43	38.22	7	Vertical
6	1246.7747	-32.71	-36.80	-20.00	16.80	-4.09	342	Vertical

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd

Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd

Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/