



RF TEST REPORT

Product Name: LTE Vehicular Communicator

Model Name: LM500, LM500-A, LM500C, LM500-E, LM500-D, LM500-G,
LM500-H, LM500-M, LM500-P, LM500-S, LM500-X

FCC ID: 2BBDV-LM500

Issued For : Shenzhen Lynknex Communications Co., Ltd.

Room 101,103 Building A5, Hangcheng Innovative Park,
Bao'an District, Shenzhen, China

Issued By : Shenzhen LGT Test Service Co., Ltd.

Room 205, Building 13, Zone B, Zhenxiong Industrial Park,
No.177, Renmin West Road, Jinsha, Kengzi Street,
Pingshan District, Shenzhen, Guangdong, China

Report Number: LGT23L081HA01

Sample Received Date: Dec. 18, 2023

Date of Test: Dec. 18, 2023 – Jan. 15, 2024

Date of Issue: Jan. 15, 2024

The test report is effective only with both signature and specialized stamp. This report shall not be reproduced except in full without the written approval of the Laboratory. The results in this report only apply to the tested sample.



TEST REPORT CERTIFICATION

Applicant: Shenzhen Lynknox Communications Co., Ltd.

Address: Room 101,103 Building A5, Hangcheng Innovative Park, Bao'an District, Shenzhen, China

Manufacture: Shenzhen Lynknox Communications Co., Ltd.

Address: Room 101,103 Building A5, Hangcheng Innovative Park, Bao'an District, Shenzhen, China

Product Name: LTE Vehicular Communicator

Trademark: LYNKSYS

Model Name: LM500, LM500-A, LM500C, LM500-E, LM500-D, LM500-G, LM500-H, LM500-M, LM500-P, LM500-S, LM500-X

Sample Status: Normal

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
FCC 47 CFR §2.1091 KDB 447498 D01 General RF Exposure Guidance v06	PASS

Prepared by:

Zane Shan

Zane Shan
Engineer

Approved by:

Vita Li

Vita Li
Technical Director





TABLE OF CONTENTS

1 . GENERAL INFORMATION	5
1.1 GENERAL DESCRIPTION OF THE EUT	5
1.2 TEST LABORATORY	5
2 . FCC 47CFR §2.1091 REQUIREMENT	6
2.1 TEST STANDARDS	6
2.2 LIMIT	6
2.3 EUT OPERATION CONDITION	6
2.4 CLASSIFICATION	6
2.5 TEST RESULT	7



Revision History

Rev.	Issue Date	Revisions
00	Jan. 15, 2024	Initial Issue



1. GENERAL INFORMATION

1.1 GENERAL DESCRIPTION OF THE EUT

Product Name:	LTE Vehicular Communicator	
Trademark:	LYNKSYS	
Model Name:	LM500	
Series Model:	LM500-A, LM500C, LM500-E, LM500-D, LM500-G, LM500-H, LM500-M, LM500-P, LM500-S, LM500-X	
Model Difference:	Only the model is different.	
Frequency Bands:	Bluetooth	2402-2480MHz
	2.4G WLAN	802.11b/g/n(20MHz): 2412~2462MHz 802.11n(40MHz):2422~2452MHz
	5G WLAN	IEEE 802.11a/n(HT20): 5.180GHz-5.825GHz IEEE 802.11n(HT40): 5.190GHz-5.795GHz
	GSM	850: 824 MHz ~ 849MHz 1900: 1850 MHz ~ 1910MHz
	WCDMA	Band V: 824 MHz ~ 849 MHz Band II: 1850 MHz ~ 1910 MHz Band IV: 1710 MHz ~ 1755 MHz
	LTE	LTE Band 2:1850~1910MHz LTE Band 4:1710~1755MHz LTE Band 5: 824~849MHz LTE Band 7: 2500~2570MHz LTE Band 12: 699-716MHz LTE Band 13: 777-787MHz LTE Band 17: 704~716MHz
Rating:	Input: DC 12~24V	
Hardware Version:	R620_MB_V2.0	
Software Version:	N/A	

1.2 TEST LABORATORY

Company Name:	Shenzhen LGT Test Service Co., Ltd.
Address:	Room 205, Building 13, Zone B, Zhenxiong Industrial Park, No.177, Renmin West Road, Jinsha, Kengzi Street, Pingshan District, Shenzhen, Guangdong, China
Accreditation Certificate	A2LA Certificate No.: 6727.01
	FCC Registration No.: 746540
	CAB ID: CN0136



2. FCC 47CFR §2.1091 REQUIREMENT

2.1 TEST STANDARDS

The limit for Maximum Permissible Exposure (MPE) specified in FCC 1.1310 is followed. The gain of the antennas used in the product is extracted from the Antenna data sheets provided and also the maximum total power input to the antenna is measured. Through the Friis transmission formula and the maximum gain of the antenna, we can calculate the distance, away from the product, where the limit of MPE is reached.

Although the Friis Transmission formula is far field assumption, the calculated result of that is an over-prediction for near field power density. It is taken as worst case to specify the safety range.

2.2 LIMIT

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environmental impact of the human exposure to radio-frequency (RF) radiation as specified in 1.1307 (b)

Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)
Limits for Occupational / controlled Exposures			
300 - 1500	--	--	F/300
1500 – 100000	--	--	5.0
Limits for General population / Uncontrolled Exposure			
300 - 1500	--	--	F/1500
1500 – 100000	--	--	1.0

F= Frequency in MHz

Friis Formula

Friis Transmission Formula: $P_d = (P_{out} * G) / (4\pi r^2)$

Where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = Distance between observation point and the center of radiator in cm

If we know the maximum gain of the antenna and the total output power to the antenna, through calculation, we will know MPE value at distance 20cm.

2.3 EUT OPERATION CONDITION

EUT was enabled to transmit and receive at lowest, middle and highest channels.

2.4 CLASSIFICATION

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. Warning statement to the user for keeping at least 20cm or more separation distance from the antenna should be included in the User manual. So, this device is classified as Mobile device.



2.5 TEST RESULT

Turn up Result

Mode	Turn up Power
GSM 850	31±1dBm
GSM 1900	27.5±1dBm
WCDMA B2	20.5±1dBm
WCDMA B4	20.5±1dBm
WCDMA B5	21±1dBm
LTE B2	20.5±1dBm
LTE B4	20.5±1dBm
LTE B5	21±1dBm
LTE B7	20.5±1dBm
LTE B12	21±1dBm
LTE B13	21±1dBm
LTE B17	21±1dBm
BT-GFSK	-1±1dBm
BT-π/4-DQPSK	-2±1dBm
BT-8DPSK	-2±1dBm
BLE-GFSK	-1±1dBm
2.4G WIFI-802.11b	8.5±1dBm
2.4G WIFI-802.11g	7.5±1dBm
2.4G WIFI-802.11n(HT20)	6±1dBm
2.4G WIFI-802.11n(HT40)	6.5±1dBm
5G WIFI-802.11a	6±1dBm
5G WIFI-802.11n(HT20)	4±1dBm
5G WIFI-802.11n(HT40)	4±1dBm



The MPE result of worst mode:

RF Function	Frequency (MHz)	Max Turn up Power (dBm)	Duty cycle factor	Max Power (dBm)	Max Power (mW)	ANT Gain (dBi)	ANT Gain (gain of antenna in linear scale)	Power Density (mW/cm ²)	Limit (mW/cm ²)	Ratio	Result
GSM (1Slot)	824.2	32	-9.03	22.97	198.15	1	1.26	0.050	0.566	0.088	Pass
WCDMA	826.4	22	0	22	158.49	1	1.26	0.040	0.564	0.070	Pass
LTE	829	22	0	22	158.49	1	1.26	0.040	1	0.040	Pass

RF Function	Frequency (MHz)	Max Turn up Power (dBm)	Max Turn up Power (mW)	ANT Gain (dBi)	ANT Gain (gain of antenna in linear scale)	Power Density (mW/cm ²)	Limit (mW/cm ²)	Ratio	Result
BT	2402	0.00	1.00	4.72	2.96	0.001	1	0.001	Pass
2.4G WIFI	2422	9.50	8.91	4.72	2.96	0.005	1	0.005	Pass
5G WIFI	5785	7.00	5.01	3.77	2.38	0.002	1	0.002	Pass

The max MPE of simultaneous transmission:

$$\text{GSM}(0.088) + \text{WIFI}(0.005) = 0.093 < 1$$

Note:

1. The Maximum Power Density is less than the limit, complies with the exemption requirements.

*** END OF THE REPORT ***