

Page 1 of 10 FCC ID: 2BBGK-S7 Report No.: LCSA05235163EC

RF Exposure Evaluation

For

Shenzhen Xincheng Times Technology Co.,Ltd

Electric Scooter for Kids

Test Model: S7

Additional Model No.: Please Refer to Page 6

Prepared for : Shenzhen Xincheng Times Technology Co.,Ltd

Address : 104-105, Block C, Donghai Wang Building, No. 369 Bulong Road,

Ma'antang Community, Bantian Street, Longgang District, Shenzhen

Prepared by : Shenzhen LCS Compliance Testing Laboratory Ltd.

Address : 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei,

Shajing Street, Baoan District, Shenzhen, 518000, China

Tel : (+86)755-82591330 Fax : (+86)755-82591332 Web : www.LCS-cert.com

Mail : webmaster@LCS-cert.com

Date of receipt of test sample : May 26, 2025

Number of tested samples : 2

Sample No. : A250521112-1, A250521112-2

Serial number : Prototype

Date of Test : May 26, 2025 ~ June 09, 2025

Date of Report : June 09, 2025





Page 2 of 10 FCC ID: 2BBGK-S7 Report No.: LCSA05235163EC

RF Exposure Evaluation

Report Reference No.: LCSA05235163EC

Date of Issue: June 09, 2025

Testing Laboratory Name: Shenzhen LCS Compliance Testing Laboratory Ltd.

Address......: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei,

Shajing Street, Baoan District, Shenzhen, 518000, China

Testing Location/ Procedure.....: Full application of Harmonised standards ■

Partial application of Harmonised standards

Applicant's Name.....: Shenzhen Xincheng Times Technology Co.,Ltd

Address.....: 104-105, Block C, Donghai Wang Building, No. 369 Bulong Road,

Ma'antang Community, Bantian Street, Longgang District, Shenzhen

Test Specification

Standard: FCC KDB publication 447498 D01 General RF Exposure Guidance

v06

FCC CFR 47 part1 1.1310 FCC CFR 47 part2 2.1093

Test Report Form No......: : TRF-4-E-215 A/0

TRF Originator.....: Shenzhen LCS Compliance Testing Laboratory Ltd.

Master TRF.....: Dated 2011-03

Shenzhen LCS Compliance Testing Laboratory Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen LCS Compliance Testing Laboratory Ltd. is acknowledged as copyright owner and source of the material. Shenzhen LCS Compliance Testing Laboratory Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test Item Description.....: Electric Scooter for Kids

 Trade Mark
 : N/A

 Test Model
 : S7

Ratings.....: Input: 29.4V=1.0A

For AC Adapter Input: 100-240V~, 50/60Hz, 1.2A Max.

Adapter Output: 29.4V=1.0A, 29.4W

DC 25.2V by Battery, 5.2Ah

Result: PASS

Compiled by: Supervised by: Approved by:

Nadia Zhon

Nadia Zhou/ Administrator

Jack Liu/ Technique principal

Gavin Liang/ Manager







FCC ID: 2BBGK-S7 Report No.: LCSA05235163EC

RF Exposure Evaluation

Test Report No.: LCSA05235163EC June 09, 2025

Date of issue

: Electric Scooter for Kids Test Model..... : S7 : Shenzhen Xincheng Times Technology Co.,Ltd Applicant..... 104-105, Block C, Donghai Wang Building, No. 369 Bulong Road, : Ma'antang Community, Bantian Street, Longgang District, Address..... Shenzhen Telephone..... Fax..... : Shenzhen Xincheng Times Technology Co.,Ltd Manufacturer..... : 104-105, Block C, Donghai Wang Building, No. 369 Bulong Road, Address..... Ma'antang Community, Bantian Street, Longgang District, Shenzhen Telephone..... Fax..... : / : Shenzhen Xincheng Times Technology Co.,Ltd Factory..... Address..... : 104-105, Block C, Donghai Wang Building, No. 369 Bulong Road, Ma'antang Community, Bantian Street, Longgang District, Shenzhen Telephone..... Fax.....

Test Result	PASS
-------------	------

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000 China



Page 4 of 10

FCC ID: 2BBGK-S7

Revision History

Report Version	Issue Date	Revision Content	Revised By
000	June 09, 2025	Initial Issue	

TH拉测股份 LCS Tosting Lab TET 立语检测股份

IST 工訊檢測股份

Report No.: LCSA05235163EC

区 立讯检测股份 LCS Testing Lab

化型 LCS Testing Lab

上 立语检测股份 LCS Testing Lab IST 工语检测器协 LOS Testing Lat

医工工研检测股份 LCS Testing Lab

NSG 立讯检测股份 LCS Testing Lab

工道模型测度的 LCS Testing Lab

直立
TEST LCS Testing Lab

工资 工资检测股份









FCC ID: 2BBGK-S7

TABLE OF CONTENTS

TABLE OF CONTENTS				
Description			Page	
1. PRODUCT INFORMAT	ΓΙΟΝ		6	
2. EVALUATION METHO	D AND LIMIT		7	
3. REFER EVALUATION	METHOD		7	
4. CONDUCTED POWER	RESULTS		8	
5. MANUFACTURING TO	LERANCE		9	
6. EVALUATION RESUL	TS		10	
7. CONCLUSION	<u> </u>		10	
8. DESCRIPTION OF TES	ST FACILITY	Till Caling Lab	10	
9. MEASUREMENT UNC	ERTAINTY	l res	10	













Report No.: LCSA05235163EC











Page 6 of 10 FCC ID: 2BBGK-S7 Report No.: LCSA05235163EC

1. Product Information

EUT	:	Electric Scooter for Kids
Test Model	VX S	S7 Marting Line Testing Line Te
Additional Model No.	1	S7 Ultra, S7Pro, S7Pro Max, S7Max, S7 Plus
Model Declaration	:	PCB board, structure and internal of these model(s) are the same, So no additional models were tested
Ratings	:	Input: 29.4V-1.0A For AC Adapter Input: 100-240V~, 50/60Hz, 1.2A Max. Adapter Output: 29.4V-1.0A, 29.4W DC 25.2V by Battery, 5.2Ah
Hardware Version	:	V1.0
Software Version	:	V1.0
Bluetooth	:	
Frequency Range	:	2402MHz~2480MHz
Channel Number	:	79 channels for Bluetooth V5.1(DSS) 40 channels for Bluetooth V5.1 (DTS)
Channel Spacing	:	1MHz for Bluetooth V5.1 (DSS) 2MHz for Bluetooth V5.1 (DTS)
Modulation Type	:	GFSK, π/4-DQPSK, 8-DPSK for Bluetooth V5.1(DSS) GFSK for Bluetooth V5.1 (DTS)
Bluetooth Version	:	V5.1
Antenna Description	w:	PCB Antenna, 0.07dBi(Max.)
Exposure category	1	General population/uncontrolled environment
EUT Type	:	Production Unit
Device Type	:	Portable Device
Note: For a more detail	ed a	antenna description, please refer to the antenna specifications or the

Note: For a more detailed antenna description, please refer to the antenna specifications or the antenna report provided by the customer.



















Page 7 of 10 FCC ID: 2BBGK-S7 Report No.: LCSA05235163EC

2. Evaluation method and Limit

According to KDB447498 D01 General RF Exposure Guidance v06 Section 4.3.1 Standalone SAR test exclusion considerations: "Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Test Exclusion Threshold condition, listed below, is satisfied. These test exclusion conditions are based on source-based time-averaged maximum conducted output power of the RF channel requiring evaluation, adjusted for tune-up tolerance, and the minimum test separation distance required for the exposure conditions.22 The minimum test separation distance is determined by the smallest distance from the antenna and radiating structures or outer surface of the device, according to the host form factor, exposure conditions and platform requirements, to any part of the body or extremity of a user or bystander (see 5) of section 4.1). To qualify for SAR test exclusion, the test separation distances applied must be fully explained and justified by the operating configurations and exposure conditions of the transmitter and applicable host platform requirements, typically in the SAR measurement or SAR analysis report, according to the required published RF exposure KDB procedures. When no other RF exposure testing or reporting is required, a statement of justification and compliance must be included in the equipment approval, in lieu of the SAR report, to qualify for the SAR test exclusion. When required, the device specific conditions described in the other published RF exposure KDB procedures must be satisfied before applying these SAR test exclusion provisions; for example, handheld PTT two-way radios, handsets, laptops & tablets etc."

[(max. power of channel, including tune-up tolerance, mW)/ (min. test separation distance, mm)] \cdot [\sqrt{f} (GHz)] \leq 3.0 for 1-g SAR and \leq 7.5 for 10-g extremity SAR, where:

- f (GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

 The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm
 and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test
 separation distance is < 5 mm, a distance of 5 mm according to f) in section 4.1 is applied to
 determine SAR test exclusion.

When one of the following test exclusion conditions is satisfied for all combinations of simultaneous transmission configurations, further equipment approval is not required to incorporate transmitter modules in host devices that operate in the mixed mobile and portable host platform exposure conditions. The grantee is responsible for documenting this according to Class I permissive change requirements. Antennas that qualify for standalone SAR test exclusion must apply the estimated standalone SAR to determine simultaneous transmission test exclusion. a) The $[\sum$ of (the highest measured or estimated SAR for each standalone antenna configuration, adjusted for maximum tune-up tolerance) / 1.6 W/kg] + $[\sum$ of MPE ratios] is \leq 1.0.

b) The SAR to peak location separation ratios of all simultaneously transmitting antenna pairs operating in portable device exposure conditions are all \leq 0.04, and the [\sum of MPE ratios] is \leq 1.0.

3. Refer Evaluation Method

ANSI C95.1–1999: IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz.

FCC KDB publication 447498 D01 General RF Exposure Guidance v06: Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies.

FCC CFR 47 part1 1.1310: Radiofrequency radiation exposure limits.

FCC CFR 47 part2 2.1093: Radiofrequency radiation exposure evaluation: portable devices



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China



Page 8 of 10

FCC ID: 2BBGK-S7 Report No.: LCSA05235163EC

4. Conducted Power Results

<BT>

		S-3111 D.>~	
Mode	Channel	Frequency (MHz)	Peak Conducted Output Power (dBm)
	0	2402	2.67
GFSK	39	2441	1.69
	78	2480	0.81
	0	2402	3.27
π/4DQPSK	39	2441	2.37
	78	2480	0.82
	0	2402	3.61
8DPSK	39	2441	2.64
	78	2480	1.07

<BLE>

Mode	Channel	Frequency (MHz)	Peak Conducted Output Power (dBm)
	0	2402	-4.57
BLE 1M	19	2440	-4.42
	39	2480	-4.30
	0	2402	-4.53
BLE 2M	19	2440	-4.39
	39	2480	-4.25





上CS Testing Lab





Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China





5. Manufacturing Tolerance

FCC ID: 2BBGK-S7

Report No.: LCSA05235163EC

<BT>

	TVS: -///// 135-	75: - 1111 12.				
	GFSK	(Peak)				
Channel	Channel 0	Channel 39	Channel 78			
Target (dBm)	2.0	1.0	0			
Tolerance ±(dB)	1.0	1.0	1.0			
	π/4DQPS	SK (Peak)				
Channel	Channel 0	Channel 39	Channel 78			
Target (dBm)	3.0	2.0	0			
Tolerance ±(dB) 1.0		1.0	1.0			
	8DPSK (Peak)					
Channel	Channel 0	Channel 39	Channel 78			
Target (dBm)	3.0	2.0	1.0 5 705			
Tolerance ±(dB)	1.0	1.0	1.0			

<BLE>

	BLE 1M (Peak)						
	Channel Channel 0 Channel 19 Channel 39						
	Target (dBm)	-4.0	-4.0	-4.0			
	Tolerance ±(dB)	1.0	1.0	1.0			
		BLE 2N	l (Peak)				
上语检	Channel	Channel 0	Channel 19	Channel 39			
MST CST	Target (dBm)	-4.0	-4.0	-4.0			
100	Tolerance ±(dB)	1.0	1.0	1.0			
LCS TO	Target (dBm)	-4.0	-4.0	-4.0			













Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen,



Page 10 of 10

FCC ID: 2BBGK-S7 Report No.: LCSA05235163EC

6. Evaluation Results

6.1 Standalone Evaluation

<BT:

Modulation Type	Frequency (GHz)	Antenna Distance		output ower	SAR Test Exclusion Threshold	SAR Test Exclusion
Туре	(GHZ)	(mm)	dBm	mW	Tillesholu	LXCIUSIOII
GFSK	2.402	5	3.0	1.9953	0.6185< 3.0	Yes
π/4DQPSK	2.402	5	4.0	2.5119	0.7786< 3.0	Yes
8DPSK	2.402	5	4.0	2.5119	0.7786< 3.0	Yes

<BLE 1M>

Modulation Type	Frequency	Antenna F Distance		output ower	SAR Test Exclusion Threshold	SAR Test Exclusion
туре	(GHz)	(mm)	dBm	mW	Tillesilolu	LXCIUSION
GFSK	2.480	5	-3.0	0.5012	0.1579< 3.0	Yes

<BLE 2M>

Modulation Type	Frequency (GHz)	i i lligianco i nower		•	SAR Test Exclusion Threshold	SAR Test Exclusion
Туре	(GF12)	(mm)	dBm	mW	Tillesiloid	LXCIUSIOIT
GFSK	2.480	5	-3.0	0.5012	0.1579< 3.0	Yes

Remark:

- 1. Output power including tune up tolerance;
- 2. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to f) in section
- 4.1 is applied to determine SAR test exclusion.

6.2 Simultaneous Transmission for SAR Exclusion

The sample support one BT modular. No need consider simultaneous transmission.

7. Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1093 for the uncontrolled RF Exposure and SAR Exclusion Threshold per KDB 447498 v06.

8. Description of Test Facility

NVLAP Accreditation Code is 600167-0.

FCC Designation Number is CN5024.

CAB identifier is CN0071.

CNAS Registration Number is L4595.

Test Firm Registration Number: 254912.

9. Measurement Uncertainty

BT/BLE:

Test Item		Frequency Range	Uncertainty	Note
Output power	:	1GHz-40GHz	±0.57dB	(1)

(1). This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

THE END OF REPORT.....



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China