



15.4 TEST DATA

[TestMode: TX mode]; [Line: Nutral]; [Power: 120V/60Hz]



Test Result: Pass

[TestMethod: TX mode]; [Line: Line]; [Power:120V/60Hz]


Test Result: Pass

16 RADIATED SPURIOUS EMISSIONS


Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 6.4,6.5,6.6
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Charlie
Temperature	25°C
Humidity	60%

16.1 LIMITS

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

16.2 BLOCK DIAGRAM OF TEST SETUP



16.3 PROCEDURE

- For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.


Remark:

- 1) For emission below 1GHz, through pre-scan found the worst case is the lowest channel. Only the worst case is recorded in the report.
- 2) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:
Final Test Level = Receiver Reading + Antenna Factor + Cable Factor - Preamplifier Factor
- 3) Scan from 9kHz to 25GHz, the disturbance above 12.75GHz and below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported. fundamental frequency is blocked by filter, and only spurious emission is shown.
- 4) For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.

16.4 TEST DATA


Below 1GHz

[TestMode: TX]; [Polarity: Horizontal]



Test Result: Pass

[TestMode: TX]; [Polarity: Vertical]




Site: Polarization: **Vertical** Temperature: (C)
Limit: FCC Part15 Class B Power: Humidity: %RH
EUT: Outdoor Carabiner BluetoothSpeaker
M/N: SP-2315A
Mode: TX mode
Note:

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	35.1278	-0.04	23.08	23.04	40.00	-16.96	QP	P	
2	57.3923	-0.17	22.88	22.71	40.00	-17.29	QP	P	
3	125.4457	0.03	21.66	21.69	43.50	-21.81	QP	P	
4	161.4742	1.02	22.77	23.79	43.50	-19.71	QP	P	
5	444.8514	0.46	27.13	27.59	46.00	-18.41	QP	P	
6 *	801.7863	1.40	33.98	35.38	46.00	-10.62	QP	P	

Test Result: Pass

Above 1GHz

[TestMode: TX lowest channel]; [Polarity: Horizontal]




Site	Polarization: Horizontal	Temperature: (C)
Limit: FCC Part15 (PK)	Power:	Humidity: %RH
EUT: Outdoor Carabiner BluetoothSpeaker		
M/N: SP-2315A		
Mode: TX-L		
Note:		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over				
							dBuV	dB	dBuV/m	dB	Detector
1		4804.000	38.54	4.51	43.05	74.00	-30.95			peak	
2		6017.250	42.98	3.57	46.55	74.00	-27.45			peak	
3		7206.000	39.04	7.41	46.45	74.00	-27.55			peak	
4		8226.250	40.26	8.56	48.82	74.00	-25.18			peak	
5		9601.000	39.62	11.58	51.20	74.00	-22.80			peak	
6	*	11328.25	39.55	13.39	52.94	74.00	-21.06			peak	

Test Result: Pass

[TestMode:TX lowest channel]; [Polarity: Vertical]




Site: Limit: FCC Part15 (PK) Polarization: **Vertical** Temperature: (C)
EUT: Outdoor Carabiner BluetoothSpeaker Power: Humidity: %RH
M/N: SP-2315A
Mode: TX-L
Note:

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	
			Level	Factor	ment		Detector	Comment
		MHz	dBuV	dB	dBuV/m	dB		
1		4804.000	40.31	4.51	44.82	74.00	-29.18	peak
2		5782.250	41.86	6.27	48.13	74.00	-25.87	peak
3		7206.000	39.22	7.41	46.63	74.00	-27.37	peak
4		8743.250	39.54	9.94	49.48	74.00	-24.52	peak
5		9608.000	37.46	11.59	49.05	74.00	-24.95	peak
6	*	11833.50	39.49	13.00	52.49	74.00	-21.51	peak

Test Result: Pass

[TestMode: TX middle channel]; [Polarity: Horizontal]



Site Polarization: **Horizontal** Temperature: (°C)

Limit: FCC Part15 (PK) Power: Humidity: %RH

EUT: Outdoor Carabiner BluetoothSpeaker

M/N: SP-2315A


Mode: TX-M

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over							
							MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		4877.500	45.39	4.59	49.98	74.00	-24.02			peak				
2		5758.750	39.49	6.40	45.89	74.00	-28.11			peak				
3		7323.000	37.75	7.82	45.57	74.00	-28.43			peak				
4		8320.250	40.33	8.84	49.17	74.00	-24.83			peak				
5		9764.000	38.73	11.76	50.49	74.00	-23.51			peak				
6	*	11316.50	39.27	13.39	52.66	74.00	-21.34			peak				

Test Result: Pass

[TestMode: TX middle channel]; [Polarity: Vertical]




Site: Polarization: **Vertical** Temperature: (C)
Limit: FCC Part15 (PK) Power: Humidity: %RH
EUT: Outdoor Carabiner BluetoothSpeaker
M/N: SP-2315A
Mode: TX-M
Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over				
							dBuV	dB	dBuV/m	dB	Detector
1		4882.000	39.25	4.60	43.85	74.00	-30.15			peak	
2		6017.250	42.72	3.57	46.29	74.00	-27.71			peak	
3		7323.000	38.68	7.82	46.50	74.00	-27.50			peak	
4		8473.000	40.17	9.31	49.48	74.00	-24.52			peak	
5		9764.000	37.61	11.76	49.37	74.00	-24.63			peak	
6	*	11457.50	38.75	13.48	52.23	74.00	-21.77			peak	

Test Result: Pass

[TestMode: TX highest channel]; [Polarity: Horizontal]




Site	Polarization: Horizontal	Temperature: (C)
Limit: FCC Part15 (PK)	Power:	Humidity: %RH
EUT: Outdoor Carabiner BluetoothSpeaker		
M/N: SP-2315A		
Mode: TX-H		
Note:		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over				
							dBuV	dB	dBuV/m	dB	Detector
1		4959.750	42.84	5.47	48.31	74.00	-25.69			peak	
2		5841.000	39.81	6.49	46.30	74.00	-27.70			peak	
3		7440.000	39.02	8.24	47.26	74.00	-26.74			peak	
4		8461.250	39.24	9.25	48.49	74.00	-25.51			peak	
5		9920.000	35.81	11.96	47.77	74.00	-26.23			peak	
6	*	11316.50	39.58	13.39	52.97	74.00	-21.03			peak	

Test Result: Pass

[TestMode: TX highest channel]; [Polarity: Vertical]



Site: Limit: FCC Part15 (PK) Polarization: **Vertical** Temperature: (C)
EUT: Outdoor Carabiner BluetoothSpeaker Power: Humidity: %RH
M/N: SP-2315A
Mode: TX-H
Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over				
							dBuV	dB	dBuV/m	dB	Detector
1		4960.000	38.82	5.47	44.29	74.00	-29.71			peak	
2		5899.750	40.10	6.75	46.85	74.00	-27.15			peak	
3		7440.000	38.42	8.24	46.66	74.00	-27.34			peak	
4		8461.250	40.13	9.25	49.38	74.00	-24.62			peak	
5		9920.000	35.98	11.96	47.94	74.00	-26.06			peak	
6	*	11751.25	39.41	12.98	52.39	74.00	-21.61			peak	

Test Result: Pass

17 RADIATED EMISSIONS WHICH FALL IN THE RESTRICTED BANDS


Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 6.10.5
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Charlie
Temperature	25 °C
Humidity	60%

17.1 LIMITS

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

17.2 BLOCK DIAGRAM OF TEST SETUP



17.3 PROCEDURE

- For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.

Remark 1: Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor

Remark 2: For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.

BlueAsia

17.4 TEST DATA

[TestMode: TX lowest channel]; [Polarity: Horizontal]


Radiated Emission Measurement

Project No.: RE

Data :#5

2023/7/8

107.0 dBuV/m



Site

Polarization: **Horizontal**

Temperature: (C)

Limit: FCC Part15 (PK)

Power:

Humidity: %RH

EUT: Outdoor Carabiner BluetoothSpeaker

M/N: SP-2315A


Mode: TX-L

Note:

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1		2310.000	42.98	-4.40	38.58	74.00	-35.42	peak	
2	*	2390.000	43.56	-4.31	39.25	74.00	-34.75	peak	

Test Result: Pass

[TestMode: TX lowest channel]; [Polarity: Vertical]




Site: Limit: FCC Part15 (PK) Polarization: **Vertical** Temperature: (C)
EUT: Outdoor Carabiner BluetoothSpeaker Power: Humidity: %RH
M/N: SP-2315A
Mode: TX-L
Note:

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over			
			Level	Factor	ment					
			MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	*	2310.000	43.36	-4.40	38.96	74.00	-35.04		peak	
2		2390.000	43.03	-4.31	38.72	74.00	-35.28		peak	

Test Result: Pass

[TestMode: TX highest channel]; [Polarity: Horizontal]



Site Polarization: **Horizontal** Temperature: (C)

Limit: FCC Part15 (PK) Power: Humidity: %RH

EUT: Outdoor Carabiner BluetoothSpeaker

M/N: SP-2315A

Mode: TX-H

Note:-

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over		
							dB	dBuV/m	Detector
1	*	2483.500	46.03	-4.64	41.39	74.00	-32.61		peak
2		2500.000	43.57	-4.75	38.82	74.00	-35.18		peak

Test Result: Pass


[TestMode: TX highest channel]; [Polarity: Vertical]

Radiated Emission Measurement

Project No.: RE

Data :#8

2023/7/8



Site Polarization: **Vertical** Temperature: (C)

Limit: FCC Part15 (PK) Power: Humidity: %RH

EUT: Outdoor Carabiner Bluetooth Speaker

M/N: SP-2315A

Mode: TX-H

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over		
							dB	dBuV/m	Detector
1	*	2483.500	44.08	-4.64	39.44	74.00	-34.56		peak
2		2500.000	43.14	-4.75	38.39	74.00	-35.61		peak

Test Result: Pass