


TEST REPORT

Applicant: Heilongjiang Huida Technology Co., Ltd
Address: Building 1. Science and Technology Innovation
Headquarters, Shenzhen(Harbin)industrial Park,
No.288 Zhigu Street, Songbei District, Harbin,
China
Equipment Type: Terminal
Model Name: HD501B
Brand Name: HUIDA TECH
FCC ID: 2BBNT- HD501B
Test Standard: 47 CFR Part 15 Subpart C
(refer to section 3.1)
Sample Arrival Date: Nov. 27, 2024
Test Date: Dec. 05, 2024 - Dec. 10, 2024
Date of Issue: Feb. 14, 2025

ISSUED BY:

Shenzhen BALUN Technology Co., Ltd.

Tested by: Li Ganming**Checked by:** Ye Hongji**Approved by:** Sunny Zou
(Technical Director)

Revision History

Version	Issue Date	Revisions
<u>Rev. 01</u>	<u>Feb. 14, 2025</u>	<u>Initial Issue</u>

TABLE OF CONTENTS

1	GENERAL INFORMATION	4
1.1	Test Laboratory	4
1.2	Test Location	4
2	PRODUCT INFORMATION	5
2.1	Applicant Information	5
2.2	Manufacturer Information	5
2.3	General Description for Equipment under Test (EUT)	5
2.4	Technical Information	6
3	SUMMARY OF TEST RESULTS	8
3.1	Test Standards	8
3.2	Test Verdict	8
4	GENERAL TEST CONFIGURATIONS	9
4.1	Test Environments	9
4.2	Test Equipment List	9
4.3	Test Software List	9
4.4	Measurement Uncertainty	10
4.5	Description of Test Setup	10
4.6	Measurement Results Explanation Example	13
5	TEST ITEMS	14
5.1	Antenna Requirements	14
5.2	Output Power	15
5.3	Occupied Bandwidth	17
5.4	Conducted Spurious Emission	18
5.5	Band Edge (Authorized-band band-edge)	20

5.6	Conducted Emission	22
5.7	Radiated Spurious Emission	23
5.8	Band Edge (Restricted-band band-edge).....	28
5.9	Power Spectral density (PSD).....	29
ANNEX A	TEST RESULT	30
A.1	Output Power	30
A.2	Occupied Bandwidth	32
A.3	Conducted Spurious Emissions	37
A.4	Band Edge (Authorized-band band-edge).....	46
A.5	Conducted Emissions.....	50
A.6	Radiated Emission	51
A.7	Band Edge (Restricted-band band-edge).....	65
A.8	Power Spectral Density (PSD)	67
ANNEX B	TEST SETUP PHOTOS	70
ANNEX C	EUT EXTERNAL PHOTOS	70
ANNEX D	EUT INTERNAL PHOTOS	70

1 GENERAL INFORMATION

1.1 Test Laboratory

Name	Shenzhen BALUN Technology Co., Ltd.
Address	Block B, 1/F, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Phone Number	+86 755 6685 0100

1.2 Test Location

Name	Shenzhen BALUN Technology Co., Ltd.
Location	☒ Block B, 1/F, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
	☐ 1/F, Building B, Ganghongji High-tech Intelligent Industrial Park, No. 1008, Songbai Road, Yangguang Community, Xili Sub-district, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Accreditation Certificate	The laboratory is a testing organization accredited by FCC as a accredited testing laboratory. The designation number is CN1196.

2 PRODUCT INFORMATION

2.1 Applicant Information

Applicant	Heilongjiang Huida Technology Co., Ltd
Address	Building 1. Science and Technology Innovation Headquarters, Shenzhen(Harbin)Industrial Park, No.288 Zhigu Street, Songbei District, Harbin, China

2.2 Manufacturer Information

Manufacturer	Heilongjiang Huida Technology Co., Ltd
Address	Building 1. Science and Technology Innovation Headquarters, Shenzhen(Harbin)Industrial Park, No.288 Zhigu Street, Songbei District, Harbin, China

2.3 General Description for Equipment under Test (EUT)

EUT Name	Terminal
Model Name Under Test	HD501B
Series Model Name	HD408MBDS-2.5GD, HD408BD-2.5GD, HD501, HD501E, HD408
Description of Model name differentiation	All models are same with electrical parameters and internal circuit structure, but only differ in model name. (this information provided by the applicant)
Hardware Version	408_SC200R_P1_2
Software Version	hd501_international_v3
Dimensions (Approx.)	N/A
Weight (Approx.)	N/A

2.4 Technical Information

Network and Wireless connectivity	3G Network WCDMA/HSDPA/HSUPA Band 2/4/5 4G Network LTE FDD Band 2/4/5/7/12/13/14/17/25/26/66/71 LTE TDD Band 41 WIFI 802.11a, 802.11b, 802.11g and 802.11n GPS, GLONASS, Galileo, IRNSS, BDS, QZSS, Radio RX
-----------------------------------	--

The requirement for the following technical information of the EUT was tested in this report:

Frequency Range	802.11b/g/n(20 MHz): 2.412 GHz - 2.462 GHz $f_c = 2412 \text{ MHz} + (N-1) \times 5 \text{ MHz}$, where - f_c = "Operating Frequency" in MHz, - N = "Channel Number" with the range from 1 to 11. 802.11n(40 MHz): 2.422 GHz - 2.452 GHz $f_c = 2412 \text{ MHz} + (N-1) \times 5 \text{ MHz}$, where - f_c = "Operating Frequency" in MHz, - N = "Channel Number" with the range from 3 to 9.
Modulation Type	DSSS, OFDM
Product Type	☒ Mobile ☐ Portable ☐ Fix Location
Antenna System (eg., MIMO, Smart Antenna)	N/A
Categorization as Correlated or Completely Uncorrelated	N/A
Antenna Type	PCB Antenna
Antenna Gain	2.86 dBi
About the Product	Only the WIFI 802.11b, 802.11g and 802.11n (HT20/40) was tested in this report.

Modulation technology	Modulation Type	Transfer Rate (Mbps)(Single RF path)
DSSS (802.11b)	DBPSK	1
	DQPSK	2
	CCK	5.5/11
OFDM (802.11g)	BPSK	6/9
	QPSK	12/18
	16QAM	24/36
	64QAM	48/54
OFDM (802.11n-20 MHz)	BPSK	6.5/7.2
	QPSK	13/19.5/14.4/21.7
	16QAM	26/39/28.9/43.3
	64QAM	52/58.5/65/57.8/65/72.2
OFDM (802.11n-40 MHz)	BPSK	13.5/15
	QPSK	27/40.5/30/45
	16QAM	54/81/60/90
	64QAM	108/121.5/135/120/150

Note: Preliminary tests were performed in different data rate in above table to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

Test Items	Mode	Data Rate	Channel	
Output Power	11b/11g/11n20/11n40	1/6/6.5/13.5 Mbps	1/6/11	3/6/9
Occupied Bandwidth	11b/11g/11n20/11n40	1/6/6.5/13.5 Mbps	1/6/11	3/6/9
Conducted Spurious Emission	11b/11g/11n20/11n40	1/6/6.5/13.5 Mbps	1/6/11	3/6/9
Conducted Emission	11b/11g/11n20/11n40	1/6/6.5/13.5 Mbps	1/6/11	3/6/9
Radiated Spurious Emission	11b/11g/11n20/11n40	1/6/6.5/13.5 Mbps	1/6/11	3/6/9
Band Edge	11b/11g/11n20/11n40	1/6/6.5/13.5 Mbps	1/6/11	3/6/9
Power spectral density (PSD)	11b/11g/11n20/11n40	1/6/6.5/13.5 Mbps	1/6/11	3/6/9

Note: The above EUT information in section 2.4 was declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or user's manual.

3 SUMMARY OF TEST RESULTS

3.1 Test Standards

No.	Identity	Document Title
1	47 CFR Part 15, Subpart C	Intentional radiators of radio frequency equipment
2	ANSI C63.10-2013	American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices
3	KDB Publication 558074 D01v05r02	GUIDANCE FOR COMPLIANCE MEASUREMENTS ON DIGITAL TRANSMISSION SYSTEM, FREQUENCY HOPPING SPREAD SPECTRUM SYSTEM, AND HYBRID SYSTEM DEVICES OPERATING UNDER SECTION 15.247 OF THE FCC RULES

3.2 Test Verdict

No.	Description	FCC PART No.	Test Result	Verdict
1	Antenna Requirement	15.203	--	Pass ^{Note 1}
2	Output Power	15.247 (b)	ANNEX A.1	Pass
3	Occupied Bandwidth	15.247 (a)	ANNEX A.2	Pass
4	Conducted Spurious Emission	15.247 (d)	ANNEX A.3	Pass
5	Band Edge(Authorized-band band-edge)	15.247 (d)	ANNEX A.4	Pass
6	Conducted Emission	15.207	ANNEX A.5	N/A ^{Note 2}
7	Radiated Spurious Emission	15.209; 15.247 (d)	ANNEX A.6	Pass
8	Band Edge(Restricted-band band-edge)	15.209; 15.247 (d)	ANNEX A.7	Pass
9	Power spectral density (PSD)	15.247 (e)	ANNEX A.8	Pass

Note ¹: The EUT has a permanently and irreplaceable attached antenna, which complies with the requirement FCC 15.203.

Note ²: The EUT is a vehicle equipment, so the Conducted Emission test is not applicable.

4 GENERAL TEST CONFIGURATIONS

4.1 Test Environments

During the measurement, the normal environmental conditions were within the listed ranges:

Relative Humidity	44% to 61%	
Atmospheric Pressure	100 kPa to 102 kPa	
Temperature	NT (Normal Temperature)	+20.1°C to +25.9°C
Working Voltage of the EUT	NV (Normal Voltage)	12 V

4.2 Test Equipment List

Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
Spectrum Analyzer	KEYSIGHT	N9020A	MY46471071	2024.07.04	2025.07.03
Power Sensor	KEYSIGHT	U2063XA	MY58000251	2024.07.04	2025.07.03
Spectrum Analyzer	KEYSIGHT	N9020A	MY50531259	2024.08.01	2025.07.31
Signaling Unit	ROHDE&SCHWARZ	CMW500	171150	2024.05.22	2025.05.21
Test Antenna-Horn	SCHWARZBECK	BBHA 9120D	02460	2024.05.16	2027.05.15
Test Antenna-Horn	A-INFO	LB-180400KF	J211060273	2024.06.15	2027.06.14
Anechoic Chamber	RAINFORD	9m*6m*6m	140	2024.07.28	2027.07.27
Amplifier	COM-MV	LSCX_LNA1-12G-01	7210214	2024.08.01	2025.07.31
Amplifier	COM-MV	XKu_LNA7-18G-01	7210209	2024.08.01	2025.07.31
Amplifier	COM-MV	KA LNA18 40G-01	18050001	2024.12.05	2025.12.04
EMI Receiver	ROHDE&SCHWARZ	ESRP	101036	2024.08.01	2025.07.31
Test Antenna-Bi-Log	SCHWARZBECK	VULB 9168	9168-01162	2023.08.04	2026.08.03
Test Antenna-Loop	SCHWARZBECK	FMZB 1519	1519-037	2024.01.23	2025.01.22
Amplifier	COM-MV	ZT30-1000M	B2018054558	2024.11.28	2025.11.27
Anechoic Chamber	EMC Electronic Co., Ltd	20.10*11.60*7.35m	130	2024.07.13	2027.07.12

4.3 Test Software List

Description	Manufacturer	Software Version	Serial No.	Applicable test Setup
BL410R	BALUN	V2.1.1.488	N/A	The section 4.5.1
BL410E	BALUN	V22.930	N/A	The section 4.5.2&4.5.3&4.5.4&4.5.5

4.4 Measurement Uncertainty

The following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2.

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

Parameters	Uncertainty
Occupied Channel Bandwidth	2.8%
RF output power, conducted	1.28 dB
Power Spectral Density, conducted	1.30 dB
Unwanted Emissions, conducted	1.84 dB
All emissions, radiated	5.36 dB
Temperature	0.8℃
Humidity	4%


4.5 Description of Test Setup

4.5.1 For Antenna Port Test

Conducted value (dBm) = Measurement value (dBm) + cable loss (dB)


For example: the measurement value is 10 dBm and the cable 0.5dBm used, then the final result of EUT:

Conducted value (dBm) = 10 dBm + 0.5 dB = 10.5 dBm




(Diagram 1)

4.5.2 For AC Power Supply Port Test




(Diagram 2)

4.5.3 For Radiated Test (Below 30 MHz)




(Diagram 3)

4.5.4 For Radiated Test (30 MHz-1 GHz)



(Diagram 4)

4.5.5 For Radiated Test (Above 1 GHz)



(Diagram 5)

4.6 Measurement Results Explanation Example

4.6.1 For conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

4.6.2 For radiated band edges and spurious emission test:

$$E = \text{EIRP} - 20\log D + 104.8$$

where:

E = electric field strength in dB μ V/m,

EIRP = equivalent isotropic radiated power in dBm

D = specified measurement distance in meters.

EIRP = Measure Conducted output power Value (dBm) + Maximum transmit antenna gain (dBi) + the appropriate maximum ground reflection factor (dB)

5 TEST ITEMS

5.1 Antenna Requirements

5.1.1 Relevant Standards

FCC §15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of § 15.211, § 15.213, § 15.217, § 15.219, or § 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

If directional gain of transmitting antennas is greater than 6 dBi, the power shall be reduced by the same level in dB comparing to gain minus 6 dBi. For the fixed point-to-point operation, the power shall be reduced by one dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

5.1.2 Antenna Anti-Replacement Construction

The Antenna Anti-Replacement as following method:

Protected Method	Description
The antenna is embedded in the product.	An embedded-in antenna design is used.

Reference Documents	Item
Photo	Please refer to the EUT Photo documents.

5.1.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.

5.2 Output Power

5.2.1 Test Limit

FCC § 15.247(b)

For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements.

5.2.2 Test Setup

See section 4.5.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.2.3 Test Procedure

Maximum peak conducted output power

The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall utilize a fast-responding diode detector.

The EUT shall be transmitted at its maximum power control level.

Maximum conducted (average) output power (Reporting Only)

a) As an alternative to spectrum analyzer or EMI receiver measurements, measurements may be performed using a wideband RF power meter with a thermocouple detector or equivalent if all of the conditions listed below are satisfied.

- 1) The EUT is configured to transmit continuously, or to transmit with a constant duty factor.
 - 2) At all times when the EUT is transmitting, it shall be transmitting at its maximum power control level.
 - 3) The integration period of the power meter exceeds the repetition period of the transmitted signal by at least a factor of five.
- b) If the transmitter does not transmit continuously, measure the duty cycle (x) of the transmitter output signal.
- c) Measure the average power of the transmitter. This measurement is an average over both the on and off periods of the transmitter.
- d) Adjust the measurement in dBm by adding $10\log(1/x)$, where x is the duty cycle.

Measurements of duty cycle

The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the on and off times of the transmitted signal.

Set the center frequency of the instrument to the center frequency of the transmission.

Set $RBW \geq OBW$ if possible; otherwise, set RBW to the largest available value.

Set $VBW \geq RBW$. Set detector = peak or average.

The zero-span measurement method shall not be used unless both RBW and VBW are $> 50/T$ and the number of sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring duty cycle shall not be used if $T \leq 16.7$ microseconds.)

5.2.4 Test Result

Please refer to ANNEX A.1.

5.3 Occupied Bandwidth

5.3.1 Limit

FCC §15.247(a)

Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. In order to make an accurate measurement, set the span greater than RBW. The 6 dB bandwidth must be greater than 500 kHz.

5.3.2 Test Setup

See section 4.5.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.3.3 Test Procedure

Use the following spectrum analyzer settings:

Set RBW = 100 kHz.

Set the video bandwidth (VBW) ≥ 3 RBW.

Detector = Peak.

Trace mode = max hold.

Sweep = auto couple.

Allow the trace to stabilize.

Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

5.3.4 Test Result

Please refer to ANNEX A.2.

5.4 Conducted Spurious Emission

5.4.1 Limit

FCC §15.247(d)

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

5.4.2 Test Setup

See section 4.5.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.4.3 Test Procedure

The DTS rules specify that in any 100 kHz bandwidth outside of the authorized frequency band, the power shall be attenuated according to the following conditions:

- a) If the maximum peak conducted output power procedure was used to demonstrate compliance as described in 9.1, then the peak output power measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz (i.e., 20 dBc).
- b) If maximum conducted (average) output power was used to demonstrate compliance as described in 9.2, then the peak power in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 30 dB relative to the maximum in-band peak PSD level in 100 kHz (i.e., 30 dBc).
- c) In either case, attenuation to levels below the 15.209 general radiated emissions limits is not required.

The following procedures shall be used to demonstrate compliance to these limits. Note that these procedures can be used in either an antenna-port conducted or radiated test set-up. Radiated tests must conform to the test site requirements and utilize maximization procedures defined herein.

Reference level measurement

Establish a reference level by using the following procedure:

Set instrument center frequency to DTS channel center frequency.

Set the span to ≥ 1.5 times the DTS bandwidth.

Set the RBW = 100 kHz.

Set the VBW $\geq 3 \times$ RBW.

Detector = peak.

Sweep time = auto couple.

Trace mode = max hold.

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum PSD level.

Emission level measurement

Use the following spectrum analyzer settings:

Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic. Typically, several plots are required to cover this entire span.

Set the RBW = 100 kHz.

Set the VBW $\geq 3 \times$ RBW.

Detector = peak.

Sweep time = auto couple.

Trace mode = max hold.

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum amplitude level.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) are attenuated by at least the minimum requirements specified in 11.1 a) or 11.1 b). Report the three highest emissions relative to the limit.

5.4.4 Test Result

Please refer to ANNEX A.3.

5.5 Band Edge (Authorized-band band-edge)

5.5.1 Limit

FCC §15.247(d)

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

5.5.2 Test Setup

See section 4.5.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.5.3 Test Procedure

The following procedures may be used to determine the peak or average field strength or power of an unwanted emission that is within 2 MHz of the authorized band edge. If a peak detector is utilized, use the procedure described in 13.2.1. Use the procedure described in 13.2.2 when using an average detector and the EUT can be configured to transmit continuously (i.e., duty cycle $\geq 98\%$). Use the procedure described in 13.2.3 when using an average detector and the EUT cannot be configured to transmit continuously but the duty cycle is constant (i.e., duty cycle variations are less than ± 2 percent). Use the procedure described in 13.2.4 when using an average detector for those cases where the EUT cannot be configured to transmit continuously and the duty cycle is not constant (duty cycle variations equal or exceed 2 percent).

When using a peak detector to measure unwanted emissions at or near the band edge (within 2 MHz of the authorized band), the following integration procedure can be used.

Set instrument center frequency to the frequency of the emission to be measured (must be within 2 MHz of the authorized band edge).

Set span to 2 MHz

RBW = 100 kHz.

VBW $\geq 3 \times$ RBW.

Detector = peak.

Sweep time = auto.

Trace mode = max hold.

Allow sweep to continue until the trace stabilizes (required measurement time may increase for low duty cycle applications)

Compute the power by integrating the spectrum over 1 MHz using the analyzer's band power measurement function with band limits set equal to the emission frequency (femission) ± 0.5 MHz. If the instrument does not have a band power function, then sum the amplitude levels (in power units) at 100 kHz intervals extending across the 1 MHz spectrum defined by femission ± 0.5 MHz.

Standard method(The 99% OBW of the fundamental emission is without 2 MHz of the authorized band):

Span: Wide enough to capture the peak level of the emission operating on the channel closest to the band edge, as well as any modulation products that fall outside of the authorized band of operation.

Reference level: As required to keep the signal from exceeding the maximum instrument input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than $[10 \log (\text{OBW/RBW})]$ below the reference level. Specific guidance is given in 4.1.5.2.

Attenuation: Auto (at least 10 dB preferred).

Sweep time: Coupled.

Resolution bandwidth: 100 kHz.

Video bandwidth: 300 kHz.

Detector: Peak.

Trace: Max hold.

5.5.4 Test Result

Please refer to ANNEX A.4.

5.6 Conducted Emission

5.6.1 Limit

FCC §15.207

For an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 Ω line impedance stabilization network (LISN).

Frequency range (MHz)	Conducted Limit (dB μ V)	
	Quai-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
0.50 - 30	60	50

5.6.2 Test Setup

See section 4.5.2 for test setup description for the AC power supply port. The photo of test setup please refer to ANNEX B.

5.6.3 Test Procedure

The maximum conducted interference is searched using Peak (PK), if the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. Refer to recorded points and plots below.

Devices subject to Part 15 must be tested for all available U.S. voltages and frequencies (such as a nominal 120 VAC, 50/60 Hz and 240 VAC, 50/60 Hz) for which the device is capable of operation. A device rated for 50/60 Hz operation need not be tested at both frequencies provided the radiated and line conducted emissions are the same at both frequencies.

5.6.4 Test Result

Please refer to ANNEX A.5.

5.7 Radiated Spurious Emission

5.7.1 Limit

FCC §15.209&15.247(d)

Radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength ($\mu\text{V}/\text{m}$)	Measurement Distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

Note:

1. For Above 1000 MHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit.
2. For above 1000 MHz, limit field strength of harmonics: 54dBuV/m@3m (AV) and 74dBuV/m@3m (PK).

5.7.2 Test Setup

See section 4.5.3 to 4.5.5 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.7.3 Test Procedure

Since the emission limits are specified in terms of radiated field strength levels, measurements performed to demonstrate compliance have traditionally relied on a radiated test configuration. Radiated measurements remain the principal method for demonstrating compliance to the specified limits; however antenna-port conducted measurements are also now acceptable to demonstrate compliance (see below for details). When radiated measurements are utilized, test site requirements and procedures for maximizing and measuring radiated emissions that are described in ANSI C63.10 shall be followed.

Antenna-port conducted measurements may also be used as an alternative to radiated measurements for demonstrating compliance in the restricted frequency bands. If conducted measurements are performed, then proper impedance matching must be ensured and an additional radiated test for cabinet/case spurious emissions is required.

General Procedure for conducted measurements in restricted bands

- a) Measure the conducted output power (in dBm) using the detector specified (see guidance regarding measurement procedures for determining quasi-peak, peak, and average conducted output power, respectively).
- b) Add the maximum transmit antenna gain (in dBi) to the measured output power level to determine the EIRP level (see guidance on determining the applicable antenna gain)
- c) Add the appropriate maximum ground reflection factor to the EIRP level (6 dB for frequencies ≤ 30 MHz, 4.7 dB for frequencies between 30 MHz and 1000 MHz, inclusive and 0 dB for frequencies > 1000 MHz).
- d) For devices with multiple antenna-ports, measure the power of each individual chain and sum the EIRP of all chains in linear terms (e.g., Watts, mW).
- e) Convert the resultant EIRP level to an equivalent electric field strength using the following relationship:

$$E = \text{EIRP} - 20\log D + 104.8$$

where:

E = electric field strength in dB μ V/m,

EIRP = equivalent isotropic radiated power in dBm

D = specified measurement distance in meters.

- f) Compare the resultant electric field strength level to the applicable limit.
- g) Perform radiated spurious emission test.

Quasi-Peak measurement procedure

The specifications for measurements using the CISPR quasi-peak detector can be found in Publication 16 of the International Special Committee on Radio Frequency Interference (CISPR) of the International Electrotechnical Commission.

As an alternative to CISPR quasi-peak measurement, compliance can be demonstrated to the applicable emission limits using a peak detector.

Peak power measurement procedure

Peak emission levels are measured by setting the instrument as follows:

- a) RBW = as specified in Table 1.
- b) VBW $\geq 3 \times$ RBW.
- c) Detector = Peak.
- d) Sweep time = auto.
- e) Trace mode = max hold.
- f) Allow sweeps to continue until the trace stabilizes. (Note that the required measurement time may be

longer for low duty cycle applications).

Table 1—RBW as a function of frequency

Frequency	RBW
9-150 kHz	200-300 Hz
0.15-30 MHz	9-10 kHz
30-1000 MHz	100-120 kHz
> 1000 MHz	1 MHz

If the peak-detected amplitude can be shown to comply with the average limit, then it is not necessary to perform a separate average measurement.

Trace averaging across on and off times of the EUT transmissions followed by duty cycle correction

If continuous transmission of the EUT (i.e., duty cycle ≥ 98 percent) cannot be achieved and the duty cycle is constant (i.e., duty cycle variations are less than ± 2 percent), then the following procedure shall be used:

- a) The EUT shall be configured to operate at the maximum achievable duty cycle.
- b) Measure the duty cycle, x , of the transmitter output signal as described in section 6.0.
- c) RBW = 1 MHz (unless otherwise specified).
- d) VBW $\geq 3 \times$ RBW.
- e) Detector = RMS, if $\text{span}/(\# \text{ of points in sweep}) \leq (\text{RBW}/2)$. Satisfying this condition may require increasing the number of points in the sweep or reducing the span. If this condition cannot be satisfied, then the detector mode shall be set to peak.
- f) Averaging type = power (i.e., RMS).
 - 1) As an alternative, the detector and averaging type may be set for linear voltage averaging.
 - 2) Some instruments require linear display mode in order to use linear voltage averaging. Log or dB averaging shall not be used.
- g) Sweep time = auto.
- h) Perform a trace average of at least 100 traces.
- i) A correction factor shall be added to the measurement results prior to comparing to the emission limit in order to compute the emission level that would have been measured had the test been performed at 100 percent duty cycle. The correction factor is computed as follows:
 - 1) If power averaging (RMS) mode was used in step f), then the applicable correction factor is $10 \log(1/x)$, where x is the duty cycle.
 - 2) If linear voltage averaging mode was used in step f), then the applicable correction factor is $20 \log(1/x)$, where x is the duty cycle.
 - 3) If a specific emission is demonstrated to be continuous (≥ 98 percent duty cycle) rather than turning on and off with the transmit cycle, then no duty cycle correction is required for that emission.

NOTE: Reduction of the measured emission amplitude levels to account for operational duty factor is not permitted. Compliance is based on emission levels occurring during transmission - not on an average across on and off times of the transmitter.

Determining the applicable transmit antenna gain

A conducted power measurement will determine the maximum output power associated with a restricted band emission; however, in order to determine the associated EIRP level, the gain of the transmitting antenna (in dBi) must be added to the measured output power (in dBm).

Since the out-of-band characteristics of the EUT transmit antenna will often be unknown, the use of a conservative antenna gain value is necessary. Thus, when determining the EIRP based on the measured conducted power, the upper bound on antenna gain for a device with a single RF output shall be selected as the maximum in-band gain of the antenna across all operating bands, or 2 dBi, whichever is greater. However, for devices that operate in multiple frequency bands while using the same transmit antenna, the highest gain of the antenna within the operating band nearest in frequency to the restricted band emission being measured may be used in lieu of the overall highest gain when the emission is at a frequency that is within 20 percent of the nearest band edge frequency, but in no case shall a value less than 2 dBi be used.

See KDB 662911 for guidance on calculating the additional array gain term when determining the effective antenna gain for a EUT with multiple outputs occupying the same or overlapping frequency ranges in the same band.

Radiated spurious emission test

An additional consideration when performing conducted measurements of restricted band emissions is that unwanted emissions radiating from the EUT cabinet, control circuits, power leads, or intermediate circuit elements will likely go undetected in a conducted measurement configuration. To address this concern, a radiated test shall be performed to ensure that emissions emanating from the EUT cabinet (rather than the antenna port) also comply with the applicable limits.

For these cabinet radiated spurious emission measurements the EUT transmit antenna may be replaced with a termination matching the nominal impedance of the antenna. Procedures for performing radiated measurements are specified in ANSI C63.10. All detected emissions shall comply with the applicable limits.

The measurement frequency range is from 30 MHz to the 10th harmonic of the fundamental frequency. The Turn Table is actuated to turn from 0° to 360°, and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. Mid channels on all channel bandwidth verified. Only the worst RB size/offset presented.

The power of the EUT transmitting frequency should be ignored.

All Spurious Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for $f \geq 1$ GHz, 100 kHz for $f < 1$ GHz

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

5.7.4 Test Result

Please refer to ANNEX A.6.

5.8 Band Edge (Restricted-band band-edge)

5.8.1 Limit

FCC §15.209&15.247(d)

Radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

5.8.2 Test Setup

See section 4.5.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.8.3 Test Procedure

The measurement frequency range is from 9 kHz to the 10th harmonic of the fundamental frequency. The Turn Table is actuated to turn from 0° to 360°, and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. Mid channels on all channel bandwidth verified. Only the worst RB size/offset presented.

The power of the EUT transmitting frequency should be ignored.

All Spurious Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for $f \geq 1$ GHz, 100 kHz for $f < 1$ GHz

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported, Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.

For transmitters operating above 1 GHz repeat the measurement with an average detector.

5.8.4 Test Result

Please refer to ANNEX A.7.

5.9 Power Spectral density (PSD)

5.9.1 Limit

FCC §15.247(e)

The same method of determining the conducted output power shall be used to determine the power spectral density. If a peak output power is measured, then a peak power spectral density measurement is required. If an average output power is measured, then an average power spectral density measurement should be used.

5.9.2 Test Setup

See section 4.5.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.9.3 Test Procedure

Set analyzer center frequency to DTS channel center frequency.

Set the span to 1.5 times the DTS bandwidth.

Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.

Set the VBW $\geq 3 \text{ RBW}$.

Detector = peak.

Sweep time = auto couple.

Trace mode = max hold.

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum amplitude level within the RBW.

If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

5.9.4 Test Result

Please refer to ANNEX A.8.

ANNEX A TEST RESULT

A.1 Output Power

Duty Cycle

Test Mode	On Time (ms)	On+Off time (ms)	Duty Cycle
802.11b	8.208	8.244	99.56%
802.11g	1.358	1.381	98.33%
802.11n-20 MHz	1.274	1.296	98.30%
802.11n-40 MHz	0.632	0.655	96.49%

Peak Power Test Data

802.11b Mode:

Channel	Measured Output Peak Power		Limit		Verdict
	dBm	mW	dBm	mW	
Low	18.47	70.31	30	1000	Pass
Middle	18.52	71.12			Pass
High	18.41	69.34			Pass

802.11g Mode:

Channel	Measured Output Peak Power		Limit		Verdict
	dBm	mW	dBm	mW	
Low	20.69	117.22	30	1000	Pass
Middle	21.11	129.12			Pass
High	21.03	126.77			Pass

802.11n-20 MHz Mode:

Channel	Measured Output Peak Power		Limit		Verdict
	dBm	mW	dBm	mW	
Low	20.70	117.49	30	1000	Pass
Middle	21.08	128.23			Pass
High	21.06	127.64			Pass

802.11n-40 MHz Mode:

Channel	Measured Output Peak Power		Limit		Verdict
	dBm	mW	dBm	mW	
Low	20.86	121.90	30	1000	Pass
Middle	21.20	131.83			Pass
High	20.91	123.31			Pass

Average Power Test Data

802.11b Mode:

Channel	Measured Output Average Power		Limit		Verdict
	dBm	mW	dBm	mW	
Low	15.51	35.56	30	1000	Pass
Middle	15.58	36.14			Pass
High	15.50	35.48			Pass

802.11g Mode:

Channel	Measured Output Average Power		Limit		Verdict
	dBm	mW	dBm	mW	
Low	15.53	35.73	30	1000	Pass
Middle	15.93	39.17			Pass
High	15.86	38.55			Pass

802.11n-20 MHz Mode:

Channel	Measured Output Average Power		Limit		Verdict
	dBm	mW	dBm	mW	
Low	15.57	36.06	30	1000	Pass
Middle	15.93	39.17			Pass
High	15.89	38.82			Pass

802.11n-40 MHz Mode:

Channel	Measured Output Average Power		Limit		Verdict
	dBm	mW	dBm	mW	
Low	15.65	36.73	30	1000	Pass
Middle	15.99	39.72			Pass
High	15.70	37.15			Pass

A.2 Occupied Bandwidth

Test Data

802.11b Mode:

Channel	6 dB Bandwidth (MHz)	99% Bandwidth (MHz)	6 dB Bandwidth Limits (kHz)
Low	8.700000	13.225000	≥ 500
Middle	8.700000	13.142000	≥ 500
High	9.200000	13.240000	≥ 500

802.11g Mode:

Channel	6 dB Bandwidth (MHz)	99% Bandwidth (MHz)	6 dB Bandwidth Limits (kHz)
Low	16.600000	17.990000	≥ 500
Middle	16.600000	17.884000	≥ 500
High	16.600000	18.111000	≥ 500

802.11n-20MHz Mode:

Channel	6 dB Bandwidth (MHz)	99% Bandwidth (MHz)	6 dB Bandwidth Limits (kHz)
Low	17.800000	18.721000	≥ 500
Middle	17.800000	18.686000	≥ 500
High	17.800000	18.899000	≥ 500

802.11n-40MHz Mode:

Channel	6 dB Bandwidth (MHz)	99% Bandwidth (MHz)	6 dB Bandwidth Limits (kHz)
Low	35.400000	36.414000	≥ 500
Middle	35.200000	36.460000	≥ 500
High	35.400000	36.531000	≥ 500

Test Plots

6 dB Bandwidth

802.11b LOW CHANNEL



802.11b MIDDLE CHANNEL



802.11b HIGH CHANNEL



802.11g LOW CHANNEL



802.11g MIDDLE CHANNEL



802.11g HIGH CHANNEL



802.11n-20 MHz LOW CHANNEL



802.11n-20 MHz MIDDLE CHANNEL



802.11n-20 MHz HIGH CHANNEL



802.11n-40 MHz LOW CHANNEL



802.11n-40 MHz MIDDLE CHANNEL




802.11n-40 MHz HIGH CHANNEL




99% Bandwidth


802.11b LOW CHANNEL



802.11b MIDDLE CHANNEL




802.11b HIGH CHANNEL




802.11g LOW CHANNEL




802.11g MIDDLE CHANNEL




802.11g HIGH CHANNEL




802.11n-20 MHz LOW CHANNEL




802.11n-20 MHz MIDDLE CHANNEL




802.11n-20 MHz HIGH CHANNEL




802.11n-40 MHz LOW CHANNEL



802.11n-40 MHz MIDDLE CHANNEL



802.11n-40 MHz HIGH CHANNEL



A.3 Conducted Spurious Emissions

Test Data

802.11b Mode:

Channel	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
Low	-32.82	7.18	-12.82	Pass
Middle	-33.92	7.44	-12.56	Pass
High	-34.10	7.10	-12.90	Pass

802.11g Mode:

Channel	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
Low	-38.08	4.48	-15.52	Pass
Middle	-37.66	4.85	-15.15	Pass
High	-38.78	4.96	-15.05	Pass

802.11n-20MHz Mode:

Channel	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
Low	-37.58	4.45	-15.55	Pass
Middle	-38.13	4.78	-15.22	Pass
High	-36.60	4.90	-15.11	Pass

802.11n-40MHz Mode:


Channel	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
Low	-37.69	2.21	-17.79	Pass
Middle	-39.35	2.38	-17.62	Pass
High	-36.87	2.21	-17.79	Pass

Test Plots


802.11b LOW CHANNEL CARRIER LEVEL



802.11b LOW CHANNEL, SPURIOUS 30 MHz ~ 3 GHz




802.11b LOW CHANNEL, SPURIOUS 2 GHz ~ 25 GHz




802.11b MIDDLE CHANNEL CARRIER LEVEL




802.11b MIDDLE CHANNEL, SPURIOUS 30 MHz ~ 3 GHz




802.11b MIDDLE CHANNEL, SPURIOUS 2 GHz ~ 25 GHz




802.11b HIGH CHANNEL CARRIER LEVEL




802.11b HIGH CHANNEL, SPURIOUS 30 MHz ~ 3 GHz




802.11b HIGH CHANNEL, SPURIOUS 2 GHz ~ 25 GHz




802.11g LOW CHANNEL CARRIER LEVEL




802.11g LOW CHANNEL, SPURIOUS 30 MHz ~ 3 GHz




802.11g LOW CHANNEL, SPURIOUS 2 GHz ~ 25 GHz




802.11g MIDDLE CHANNEL CARRIER LEVEL




802.11g MIDDLE CHANNEL, SPURIOUS 30 MHz ~ 3 GHz




802.11g MIDDLE CHANNEL, SPURIOUS 2 GHz ~ 25 GHz




802.11g HIGH CHANNEL CARRIER LEVEL






802.11g HIGH CHANNEL, SPURIOUS 2 GHz ~ 25 GHz




802.11g HIGH CHANNEL, SPURIOUS 30 MHz ~ 3 GHz




802.11n-20 MHz LOW CHANNEL CARRIER LEVEL

802.11n-20 MHz LOW CHANNEL, SPURIOUS
30 MHz ~ 3 GHz802.11n-20 MHz LOW CHANNEL, SPURIOUS
2 GHz ~ 25 GHz


802.11n-20 MHz MIDDLE CHANNEL CARRIER LEVEL




802.11n-20 MHz MIDDLE CHANNEL, SPURIOUS 30 MHz ~ 3 GHz




802.11n-20 MHz MIDDLE CHANNEL, SPURIOUS 2 GHz ~ 25 GHz




802.11n-20 MHz HIGH CHANNEL CARRIER LEVEL






802.11n-20 MHz HIGH CHANNEL, SPURIOUS 2 GHz ~ 25 GHz




802.11n-20 MHz HIGH CHANNEL, SPURIOUS 30 MHz ~ 3 GHz




802.11n-40 MHz LOW CHANNEL CARRIER LEVEL

802.11n-40 MHz LOW CHANNEL, SPURIOUS
30 MHz ~ 3 GHz802.11n-40 MHz LOW CHANNEL, SPURIOUS
2 GHz ~ 25 GHz


802.11n-40 MHz MIDDLE CHANNEL CARRIER LEVEL




802.11n-40 MHz MIDDLE CHANNEL, SPURIOUS 30 MHz ~ 3 GHz




802.11n-40 MHz MIDDLE CHANNEL, SPURIOUS 2 GHz ~ 25 GHz




802.11n-40 MHz HIGH CHANNEL CARRIER LEVEL



802.11n-40 MHz HIGH CHANNEL, SPURIOUS 2 GHz ~ 25 GHz



802.11n-40 MHz HIGH CHANNEL, SPURIOUS 30 MHz ~ 3 GHz



A.4 Band Edge (Authorized-band band-edge)

Note: The 99% OBW of the fundamental emission is without 2 MHz of the authorized band.

Test Data

802.11b Mode:

Channel	Measured Max. Band Edge Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
Low Channel	-42.00	7.18	-12.82	Pass
High Channel	-46.37	7.10	-12.90	Pass

802.11g Mode:

Channel	Measured Max. Band Edge Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
Low Channel	-24.00	4.48	-15.52	Pass
High Channel	-35.52	4.96	-15.05	Pass

802.11n-20 MHz Mode:

Channel	Measured Max. Band Edge Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
Low Channel	-22.54	4.45	-15.55	Pass
High Channel	-30.71	4.90	-15.11	Pass

802.11n-40 MHz Mode:

Channel	Measured Max. Band Edge Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
Low Channel	-25.55	2.21	-17.79	Pass
High Channel	-31.94	2.21	-17.79	Pass

Test Plots

802.11b LOW CHANNEL, CARRIER LEVEL




802.11b LOW CHANNEL, BAND EDGE




802.11b HIGH CHANNEL, CARRIER LEVEL




802.11b HIGH CHANNEL, BAND EDGE




802.11g LOW CHANNEL, CARRIER LEVEL




802.11g LOW CHANNEL, BAND EDGE




802.11g HIGH CHANNEL, CARRIER LEVEL



802.11g HIGH CHANNEL, BAND EDGE




802.11n-20 MHz LOW CHANNEL, CARRIER LEVEL




802.11n-20 MHz LOW CHANNEL, BAND EDGE




802.11n-20 MHz HIGH CHANNEL, CARRIER LEVEL




802.11n-20 MHz HIGH CHANNEL, BAND EDGE




802.11n-40 MHz LOW CHANNEL, CARRIER LEVEL




802.11n-40 MHz LOW CHANNEL, BAND EDGE



802.11n-40 MHz HIGH CHANNEL, CARRIER LEVEL



802.11n-40 MHz HIGH CHANNEL, BAND EDGE



A.5 Conducted Emissions

Note: Not applicable.

A.6 Radiated Emission

Note ¹: The symbol of “--” in the table which means not application.

Note ²: For the test data above 1 GHz, According the ANSI C63.10-2013, where limits are specified for both average and peak (or quasi-peak) detector functions, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement.


Note ³: The low frequency, which started from 9 kHz to 30 MHz, was pre-scanned and the result which was 20 dB lower than the limit line per 15.31(o) was not reported.

Note ⁴: The EUT is working in the Normal link mode below 1 GHz. All modes have been tested and normal link mode is worst.

Test Data and Plots

30 MHz to 1 GHz, ANT H


10m RE Test Case_FCC Certification_FCC 15C 30MHz-1GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	55.456	15.50	-26.16	29.5	14.00	Peak	2.00	200	Horizontal	Pass
2	155.826	17.05	-25.43	33.0	15.95	Peak	7.00	200	Horizontal	Pass
3	233.164	30.98	-27.90	35.5	4.52	Peak	2.00	200	Horizontal	Pass
4	258.863	29.54	-26.51	35.5	5.96	Peak	0.00	200	Horizontal	Pass
5	301.775	31.07	-24.87	35.5	4.43	Peak	4.00	200	Horizontal	Pass
6	367.233	31.29	-23.33	35.5	4.21	Peak	2.00	200	Horizontal	Pass

30 MHz to 1 GHz, ANT V

10m RE Test Case_FCC Certification_FCC 15C 30MHz-1GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	105.156	21.15	-29.67	33.0	11.85	Peak	31.00	100	Vertical	Pass
2	157.523	23.70	-25.65	33.0	9.30	Peak	10.00	100	Vertical	Pass
3	178.373	24.28	-26.96	33.0	8.72	Peak	0.00	100	Vertical	Pass
4	229.043	29.68	-28.54	35.5	5.82	Peak	13.00	100	Vertical	Pass
5	383.962	25.52	-22.53	35.5	9.98	Peak	34.00	100	Vertical	Pass
6	857.446	28.04	-11.89	35.5	7.46	Peak	0.00	100	Vertical	Pass

Note ¹: The marked spikes near 2400 MHz with circle should be ignored because they are Fundamental signal.

Note ²: The spurious above 18G is noise only, do not show on the report.

1 GHz to 18 GHz, ANT H 802.11b Low Channel

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1327.606	44.72	74.0	29.28	Peak	90.00	100	Horizontal	Pass
1**	1327.606	34.83	54.0	19.17	AV	90.00	100	Horizontal	Pass
2	2997.642	53.22	74.0	20.78	Peak	225.00	300	Horizontal	Pass
2**	2997.642	39.83	54.0	14.17	AV	225.00	300	Horizontal	Pass
3	4932.096	52.28	74.0	21.72	Peak	358.00	200	Horizontal	Pass
3**	4932.096	44.29	54.0	9.71	AV	358.00	200	Horizontal	Pass
4	6808.503	54.38	74.0	19.62	Peak	11.00	300	Horizontal	Pass
4**	6808.503	46.69	54.0	7.31	AV	11.00	300	Horizontal	Pass
5	13412.867	54.88	74.0	19.12	Peak	144.00	400	Horizontal	Pass
5**	13412.867	43.99	54.0	10.01	AV	144.00	400	Horizontal	Pass
6	17424.188	58.57	74.0	15.43	Peak	257.00	400	Horizontal	Pass
6**	17424.188	47.39	54.0	6.61	AV	257.00	400	Horizontal	Pass

1 GHz to 18 GHz, ANT V 802.11b Low Channel

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1329.158	47.74	74.0	26.26	Peak	99.00	200	Vertical	Pass
1**	1329.158	36.49	54.0	17.51	AV	99.00	200	Vertical	Pass
2	2980.642	52.28	74.0	21.72	Peak	33.00	200	Vertical	Pass
2**	2980.642	44.05	54.0	9.95	AV	33.00	200	Vertical	Pass
3	4851.183	48.96	74.0	25.04	Peak	186.00	200	Vertical	Pass
3**	4851.183	40.10	54.0	13.90	AV	186.00	200	Vertical	Pass
4	6607.210	51.48	74.0	22.52	Peak	34.00	200	Vertical	Pass
4**	6607.210	46.59	54.0	7.41	AV	34.00	200	Vertical	Pass
5	13434.921	53.61	74.0	20.39	Peak	327.00	200	Vertical	Pass
5**	13434.921	44.46	54.0	9.54	AV	327.00	200	Vertical	Pass
6	17415.289	59.82	74.0	14.18	Peak	92.00	100	Vertical	Pass
6**	17415.289	45.20	54.0	8.80	AV	92.00	100	Vertical	Pass

1 GHz to 18 GHz, ANT H 802.11b Middle Channel

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1331.107	47.45	74.0	26.55	Peak	138.00	100	Horizontal	Pass
1**	1331.107	39.63	54.0	14.37	AV	138.00	100	Horizontal	Pass
2	2996.109	48.02	74.0	25.98	Peak	113.00	300	Horizontal	Pass
2**	2996.109	43.87	54.0	10.13	AV	113.00	300	Horizontal	Pass
3	4933.004	54.63	74.0	19.37	Peak	345.00	200	Horizontal	Pass
3**	4933.004	44.05	54.0	9.95	AV	345.00	200	Horizontal	Pass
4	6806.141	52.52	74.0	21.48	Peak	4.00	400	Horizontal	Pass
4**	6806.141	44.88	54.0	9.12	AV	4.00	400	Horizontal	Pass
5	13415.181	57.24	74.0	16.76	Peak	196.00	300	Horizontal	Pass
5**	13415.181	47.27	54.0	6.73	AV	196.00	300	Horizontal	Pass
6	17426.541	54.41	74.0	19.59	Peak	31.00	100	Horizontal	Pass
6**	17426.541	45.18	54.0	8.82	AV	31.00	100	Horizontal	Pass

1 GHz to 18 GHz, ANT V 802.11b Middle Channel

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1333.435	47.51	74.0	26.49	Peak	1.00	200	Vertical	Pass
1**	1333.435	39.20	54.0	14.80	AV	1.00	200	Vertical	Pass
2	2978.280	51.15	74.0	22.85	Peak	297.00	400	Vertical	Pass
2**	2978.280	39.33	54.0	14.67	AV	297.00	400	Vertical	Pass
3	4854.475	48.74	74.0	25.26	Peak	142.00	200	Vertical	Pass
3**	4854.475	38.20	54.0	15.80	AV	142.00	200	Vertical	Pass
4	6608.699	57.02	74.0	16.98	Peak	150.00	200	Vertical	Pass
4**	6608.699	43.06	54.0	10.94	AV	150.00	200	Vertical	Pass
5	13438.548	57.34	74.0	16.66	Peak	244.00	300	Vertical	Pass
5**	13438.548	44.06	54.0	9.94	AV	244.00	300	Vertical	Pass
6	17416.302	57.71	74.0	16.29	Peak	295.00	200	Vertical	Pass
6**	17416.302	46.10	54.0	7.90	AV	295.00	200	Vertical	Pass

1 GHz to 18 GHz, ANT H 802.11b High Channel

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1327.976	41.67	74.0	32.33	Peak	144.00	400	Horizontal	Pass
1**	1327.976	38.89	54.0	15.11	AV	144.00	400	Horizontal	Pass
2	2998.618	47.69	74.0	26.31	Peak	15.00	100	Horizontal	Pass
2**	2998.618	44.22	54.0	9.78	AV	15.00	100	Horizontal	Pass
3	4932.570	53.85	74.0	20.15	Peak	252.00	200	Horizontal	Pass
3**	4932.570	40.98	54.0	13.02	AV	252.00	200	Horizontal	Pass
4	6803.679	54.31	74.0	19.69	Peak	320.00	400	Horizontal	Pass
4**	6803.679	43.07	54.0	10.93	AV	320.00	400	Horizontal	Pass
5	13414.014	55.37	74.0	18.63	Peak	315.00	300	Horizontal	Pass
5**	13414.014	45.62	54.0	8.38	AV	315.00	300	Horizontal	Pass
6	17427.144	57.68	74.0	16.32	Peak	269.00	400	Horizontal	Pass
6**	17427.144	45.45	54.0	8.55	AV	269.00	400	Horizontal	Pass

1 GHz to 18 GHz, ANT V 802.11b High Channel

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1336.775	42.24	74.0	31.76	Peak	163.00	300	Vertical	Pass
1**	1336.775	36.22	54.0	17.78	AV	163.00	300	Vertical	Pass
2	2984.037	47.99	74.0	26.01	Peak	106.00	200	Vertical	Pass
2**	2984.037	39.43	54.0	14.57	AV	106.00	200	Vertical	Pass
3	4850.687	47.72	74.0	26.28	Peak	228.00	200	Vertical	Pass
3**	4850.687	39.40	54.0	14.60	AV	228.00	200	Vertical	Pass
4	6606.249	54.46	74.0	19.54	Peak	351.00	100	Vertical	Pass
4**	6606.249	45.63	54.0	8.37	AV	351.00	100	Vertical	Pass
5	13438.544	56.21	74.0	17.79	Peak	175.00	100	Vertical	Pass
5**	13438.544	46.02	54.0	7.98	AV	175.00	100	Vertical	Pass
6	17419.701	54.81	74.0	19.19	Peak	265.00	200	Vertical	Pass
6**	17419.701	48.09	54.0	5.91	AV	265.00	200	Vertical	Pass

1 GHz to 18 GHz, ANT H 802.11g Low Channel

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1331.177	44.39	74.0	29.61	Peak	212.00	200	Horizontal	Pass
1**	1331.177	34.09	54.0	19.91	AV	212.00	200	Horizontal	Pass
2	2998.411	50.87	74.0	23.13	Peak	270.00	200	Horizontal	Pass
2**	2998.411	43.23	54.0	10.77	AV	270.00	200	Horizontal	Pass
3	4930.978	54.57	74.0	19.43	Peak	129.00	200	Horizontal	Pass
3**	4930.978	43.55	54.0	10.45	AV	129.00	200	Horizontal	Pass
4	6809.269	56.52	74.0	17.48	Peak	222.00	400	Horizontal	Pass
4**	6809.269	42.36	54.0	11.64	AV	222.00	400	Horizontal	Pass
5	13410.233	52.66	74.0	21.34	Peak	171.00	100	Horizontal	Pass
5**	13410.233	45.20	54.0	8.80	AV	171.00	100	Horizontal	Pass
6	17423.101	55.67	74.0	18.33	Peak	279.00	400	Horizontal	Pass
6**	17423.101	46.78	54.0	7.22	AV	279.00	400	Horizontal	Pass

1 GHz to 18 GHz, ANT V 802.11g Low Channel

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1330.787	45.43	74.0	28.57	Peak	287.00	400	Vertical	Pass
1**	1330.787	37.96	54.0	16.04	AV	287.00	400	Vertical	Pass
2	2985.660	50.82	74.0	23.18	Peak	201.00	400	Vertical	Pass
2**	2985.660	44.28	54.0	9.72	AV	201.00	400	Vertical	Pass
3	4856.341	51.04	74.0	22.96	Peak	48.00	200	Vertical	Pass
3**	4856.341	40.21	54.0	13.79	AV	48.00	200	Vertical	Pass
4	6604.742	52.18	74.0	21.82	Peak	124.00	100	Vertical	Pass
4**	6604.742	45.50	54.0	8.50	AV	124.00	100	Vertical	Pass
5	13438.830	55.83	74.0	18.17	Peak	30.00	200	Vertical	Pass
5**	13438.830	47.31	54.0	6.69	AV	30.00	200	Vertical	Pass
6	17417.963	54.54	74.0	19.46	Peak	57.00	100	Vertical	Pass
6**	17417.963	47.37	54.0	6.63	AV	57.00	100	Vertical	Pass

1 GHz to 18 GHz, ANT H 802.11g Middle Channel

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1328.518	44.24	74.0	29.76	Peak	24.00	200	Horizontal	Pass
1**	1328.518	34.70	54.0	19.30	AV	24.00	200	Horizontal	Pass
2	2997.609	47.94	74.0	26.06	Peak	229.00	400	Horizontal	Pass
2**	2997.609	43.92	54.0	10.08	AV	229.00	400	Horizontal	Pass
3	4936.042	54.58	74.0	19.42	Peak	357.00	200	Horizontal	Pass
3**	4936.042	40.04	54.0	13.96	AV	357.00	200	Horizontal	Pass
4	6804.702	57.32	74.0	16.68	Peak	15.00	300	Horizontal	Pass
4**	6804.702	46.89	54.0	7.11	AV	15.00	300	Horizontal	Pass
5	13411.201	55.51	74.0	18.49	Peak	330.00	400	Horizontal	Pass
5**	13411.201	49.15	54.0	4.85	AV	330.00	400	Horizontal	Pass
6	17422.698	56.93	74.0	17.07	Peak	119.00	200	Horizontal	Pass
6**	17422.698	47.29	54.0	6.71	AV	119.00	200	Horizontal	Pass

1 GHz to 18 GHz, ANT V 802.11g Middle Channel

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1329.883	44.79	74.0	29.21	Peak	336.00	200	Vertical	Pass
1**	1329.883	36.24	54.0	17.76	AV	336.00	200	Vertical	Pass
2	2979.671	48.58	74.0	25.42	Peak	113.00	200	Vertical	Pass
2**	2979.671	40.18	54.0	13.82	AV	113.00	200	Vertical	Pass
3	4851.149	52.17	74.0	21.83	Peak	231.00	200	Vertical	Pass
3**	4851.149	39.84	54.0	14.16	AV	231.00	200	Vertical	Pass
4	6609.389	54.88	74.0	19.12	Peak	165.00	100	Vertical	Pass
4**	6609.389	45.70	54.0	8.30	AV	165.00	100	Vertical	Pass
5	13432.283	56.35	74.0	17.65	Peak	56.00	400	Vertical	Pass
5**	13432.283	44.91	54.0	9.09	AV	56.00	400	Vertical	Pass
6	17413.607	56.53	74.0	17.47	Peak	219.00	200	Vertical	Pass
6**	17413.607	47.54	54.0	6.46	AV	219.00	200	Vertical	Pass

1 GHz to 18 GHz, ANT H 802.11g High Channel

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1332.072	43.59	74.0	30.41	Peak	150.00	400	Horizontal	Pass
1**	1332.072	39.66	54.0	14.34	AV	150.00	400	Horizontal	Pass
2	2994.554	48.11	74.0	25.89	Peak	107.00	100	Horizontal	Pass
2**	2994.554	42.98	54.0	11.02	AV	107.00	100	Horizontal	Pass
3	4937.794	53.88	74.0	20.12	Peak	127.00	200	Horizontal	Pass
3**	4937.794	44.18	54.0	9.82	AV	127.00	200	Horizontal	Pass
4	6803.713	56.53	74.0	17.47	Peak	38.00	400	Horizontal	Pass
4**	6803.713	44.22	54.0	9.78	AV	38.00	400	Horizontal	Pass
5	13411.408	54.01	74.0	19.99	Peak	279.00	400	Horizontal	Pass
5**	13411.408	47.00	54.0	7.00	AV	279.00	400	Horizontal	Pass
6	17426.282	57.08	74.0	16.92	Peak	125.00	200	Horizontal	Pass
6**	17426.282	49.54	54.0	4.46	AV	125.00	200	Horizontal	Pass

1 GHz to 18 GHz, ANT V 802.11g High Channel

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1336.599	45.67	74.0	28.33	Peak	70.00	100	Vertical	Pass
1**	1336.599	34.76	54.0	19.24	AV	70.00	100	Vertical	Pass
2	2979.588	48.54	74.0	25.46	Peak	191.00	100	Vertical	Pass
2**	2979.588	42.92	54.0	11.08	AV	191.00	100	Vertical	Pass
3	4857.497	49.48	74.0	24.52	Peak	32.00	200	Vertical	Pass
3**	4857.497	38.60	54.0	15.40	AV	32.00	200	Vertical	Pass
4	6610.971	52.92	74.0	21.08	Peak	155.00	300	Vertical	Pass
4**	6610.971	44.27	54.0	9.73	AV	155.00	300	Vertical	Pass
5	13437.347	57.35	74.0	16.65	Peak	313.00	300	Vertical	Pass
5**	13437.347	46.34	54.0	7.66	AV	313.00	300	Vertical	Pass
6	17415.941	58.89	74.0	15.11	Peak	210.00	400	Vertical	Pass
6**	17415.941	48.85	54.0	5.15	AV	210.00	400	Vertical	Pass

1 GHz to 18 GHz, ANT H 802.11n20 Low Channel

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1331.304	46.12	74.0	27.88	Peak	211.00	400	Horizontal	Pass
1**	1331.304	35.62	54.0	18.38	AV	211.00	400	Horizontal	Pass
2	2994.467	48.64	74.0	25.36	Peak	271.00	100	Horizontal	Pass
2**	2994.467	40.00	54.0	14.00	AV	271.00	100	Horizontal	Pass
3	4934.481	51.19	74.0	22.81	Peak	211.00	200	Horizontal	Pass
3**	4934.481	43.84	54.0	10.16	AV	211.00	200	Horizontal	Pass
4	6806.085	52.46	74.0	21.54	Peak	4.00	300	Horizontal	Pass
4**	6806.085	46.50	54.0	7.50	AV	4.00	300	Horizontal	Pass
5	13412.429	58.45	74.0	15.55	Peak	19.00	300	Horizontal	Pass
5**	13412.429	49.38	54.0	4.62	AV	19.00	300	Horizontal	Pass
6	17422.529	58.96	74.0	15.04	Peak	155.00	400	Horizontal	Pass
6**	17422.529	46.61	54.0	7.39	AV	155.00	400	Horizontal	Pass

1 GHz to 18 GHz, ANT V 802.11n20 Low Channel

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1334.553	47.43	74.0	26.57	Peak	139.00	300	Vertical	Pass
1**	1334.553	39.82	54.0	14.18	AV	139.00	300	Vertical	Pass
2	2979.895	49.92	74.0	24.08	Peak	266.00	300	Vertical	Pass
2**	2979.895	40.69	54.0	13.31	AV	266.00	300	Vertical	Pass
3	4851.665	49.07	74.0	24.93	Peak	256.00	200	Vertical	Pass
3**	4851.665	42.64	54.0	11.36	AV	256.00	200	Vertical	Pass
4	6603.972	52.85	74.0	21.15	Peak	309.00	400	Vertical	Pass
4**	6603.972	45.69	54.0	8.31	AV	309.00	400	Vertical	Pass
5	13437.198	53.06	74.0	20.94	Peak	188.00	200	Vertical	Pass
5**	13437.198	45.56	54.0	8.44	AV	188.00	200	Vertical	Pass
6	17417.401	55.69	74.0	18.31	Peak	271.00	300	Vertical	Pass
6**	17417.401	48.18	54.0	5.82	AV	271.00	300	Vertical	Pass

1 GHz to 18 GHz, ANT H 802.11n20 Middle Channel

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1331.469	46.44	74.0	27.56	Peak	88.00	200	Horizontal	Pass
1**	1331.469	38.09	54.0	15.91	AV	88.00	200	Horizontal	Pass
2	2993.622	50.26	74.0	23.74	Peak	36.00	300	Horizontal	Pass
2**	2993.622	42.70	54.0	11.30	AV	36.00	300	Horizontal	Pass
3	4931.198	52.85	74.0	21.15	Peak	126.00	200	Horizontal	Pass
3**	4931.198	44.42	54.0	9.58	AV	126.00	200	Horizontal	Pass
4	6810.259	53.92	74.0	20.08	Peak	128.00	300	Horizontal	Pass
4**	6810.259	46.17	54.0	7.83	AV	128.00	300	Horizontal	Pass
5	13408.968	54.09	74.0	19.91	Peak	261.00	100	Horizontal	Pass
5**	13408.968	48.14	54.0	5.86	AV	261.00	100	Horizontal	Pass
6	17422.735	58.98	74.0	15.02	Peak	347.00	100	Horizontal	Pass
6**	17422.735	45.20	54.0	8.80	AV	347.00	100	Horizontal	Pass

1 GHz to 18 GHz, ANT V 802.11n20 Middle Channel

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1332.872	43.19	74.0	30.81	Peak	15.00	100	Vertical	Pass
1**	1332.872	39.39	54.0	14.61	AV	15.00	100	Vertical	Pass
2	2983.303	50.73	74.0	23.27	Peak	355.00	200	Vertical	Pass
2**	2983.303	44.70	54.0	9.30	AV	355.00	200	Vertical	Pass
3	4857.940	49.25	74.0	24.75	Peak	190.00	200	Vertical	Pass
3**	4857.940	37.77	54.0	16.23	AV	190.00	200	Vertical	Pass
4	6606.694	53.17	74.0	20.83	Peak	51.00	100	Vertical	Pass
4**	6606.694	42.19	54.0	11.81	AV	51.00	100	Vertical	Pass
5	13433.450	57.25	74.0	16.75	Peak	234.00	300	Vertical	Pass
5**	13433.450	45.13	54.0	8.87	AV	234.00	300	Vertical	Pass
6	17417.280	58.19	74.0	15.81	Peak	85.00	100	Vertical	Pass
6**	17417.280	49.19	54.0	4.81	AV	85.00	100	Vertical	Pass

1 GHz to 18 GHz, ANT H 802.11n20 High Channel

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1329.708	46.59	74.0	27.41	Peak	113.00	100	Horizontal	Pass
1**	1329.708	35.99	54.0	18.01	AV	113.00	100	Horizontal	Pass
2	2999.575	48.04	74.0	25.96	Peak	228.00	300	Horizontal	Pass
2**	2999.575	39.80	54.0	14.20	AV	228.00	300	Horizontal	Pass
3	4934.949	48.81	74.0	25.19	Peak	333.00	200	Horizontal	Pass
3**	4934.949	38.91	54.0	15.09	AV	333.00	200	Horizontal	Pass
4	6808.180	54.53	74.0	19.47	Peak	335.00	400	Horizontal	Pass
4**	6808.180	42.95	54.0	11.05	AV	335.00	400	Horizontal	Pass
5	13409.357	57.15	74.0	16.85	Peak	93.00	300	Horizontal	Pass
5**	13409.357	44.31	54.0	9.69	AV	93.00	300	Horizontal	Pass
6	17429.796	55.92	74.0	18.08	Peak	335.00	300	Horizontal	Pass
6**	17429.796	45.78	54.0	8.22	AV	335.00	300	Horizontal	Pass

1 GHz to 18 GHz, ANT V 802.11n20 High Channel

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1336.698	46.16	74.0	27.84	Peak	260.00	400	Vertical	Pass
1**	1336.698	38.29	54.0	15.71	AV	260.00	400	Vertical	Pass
2	2980.373	50.56	74.0	23.44	Peak	230.00	100	Vertical	Pass
2**	2980.373	40.60	54.0	13.40	AV	230.00	100	Vertical	Pass
3	4854.255	50.71	74.0	23.29	Peak	154.00	200	Vertical	Pass
3**	4854.255	38.00	54.0	16.00	AV	154.00	200	Vertical	Pass
4	6607.595	54.73	74.0	19.27	Peak	232.00	200	Vertical	Pass
4**	6607.595	47.88	54.0	6.12	AV	232.00	200	Vertical	Pass
5	13431.689	57.76	74.0	16.24	Peak	184.00	200	Vertical	Pass
5**	13431.689	47.53	54.0	6.47	AV	184.00	200	Vertical	Pass
6	17416.345	56.04	74.0	17.96	Peak	337.00	400	Vertical	Pass
6**	17416.345	45.12	54.0	8.88	AV	337.00	400	Vertical	Pass

1 GHz to 18 GHz, ANT H 802.11n40 Low Channel

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1328.528	43.14	74.0	30.86	Peak	222.00	400	Horizontal	Pass
1**	1328.528	34.43	54.0	19.57	AV	222.00	400	Horizontal	Pass
2	2996.579	52.90	74.0	21.10	Peak	120.00	300	Horizontal	Pass
2**	2996.579	42.29	54.0	11.71	AV	120.00	300	Horizontal	Pass
3	4937.749	54.65	74.0	19.35	Peak	253.00	200	Horizontal	Pass
3**	4937.749	42.15	54.0	11.85	AV	253.00	200	Horizontal	Pass
4	6810.528	53.80	74.0	20.20	Peak	181.00	300	Horizontal	Pass
4**	6810.528	47.58	54.0	6.42	AV	181.00	300	Horizontal	Pass
5	13414.035	55.49	74.0	18.51	Peak	129.00	100	Horizontal	Pass
5**	13414.035	46.11	54.0	7.89	AV	129.00	100	Horizontal	Pass
6	17426.777	56.79	74.0	17.21	Peak	167.00	400	Horizontal	Pass
6**	17426.777	50.15	54.0	3.85	AV	167.00	400	Horizontal	Pass

1 GHz to 18 GHz, ANT V 802.11n40 Low Channel

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1328.919	47.24	74.0	26.76	Peak	271.00	300	Vertical	Pass
1**	1328.919	39.92	54.0	14.08	AV	271.00	300	Vertical	Pass
2	2980.247	49.94	74.0	24.06	Peak	309.00	100	Vertical	Pass
2**	2980.247	42.46	54.0	11.54	AV	309.00	100	Vertical	Pass
3	4851.117	47.07	74.0	26.93	Peak	154.00	200	Vertical	Pass
3**	4851.117	40.55	54.0	13.45	AV	154.00	200	Vertical	Pass
4	6607.383	56.78	74.0	17.22	Peak	268.00	200	Vertical	Pass
4**	6607.383	43.74	54.0	10.26	AV	268.00	200	Vertical	Pass
5	13438.464	53.62	74.0	20.38	Peak	260.00	300	Vertical	Pass
5**	13438.464	49.31	54.0	4.69	AV	260.00	300	Vertical	Pass
6	17414.586	58.16	74.0	15.84	Peak	126.00	100	Vertical	Pass
6**	17414.586	49.51	54.0	4.49	AV	126.00	100	Vertical	Pass

1 GHz to 18 GHz, ANT H 802.11n40 Middle Channel

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1330.507	45.55	74.0	28.45	Peak	346.00	200	Horizontal	Pass
1**	1330.507	37.76	54.0	16.24	AV	346.00	200	Horizontal	Pass
2	2997.841	47.31	74.0	26.69	Peak	297.00	400	Horizontal	Pass
2**	2997.841	40.95	54.0	13.05	AV	297.00	400	Horizontal	Pass
3	4935.959	50.81	74.0	23.19	Peak	294.00	200	Horizontal	Pass
3**	4935.959	42.85	54.0	11.15	AV	294.00	200	Horizontal	Pass
4	6806.303	57.31	74.0	16.69	Peak	146.00	100	Horizontal	Pass
4**	6806.303	42.70	54.0	11.30	AV	146.00	100	Horizontal	Pass
5	13411.302	54.04	74.0	19.96	Peak	67.00	100	Horizontal	Pass
5**	13411.302	44.15	54.0	9.85	AV	67.00	100	Horizontal	Pass
6	17429.487	56.97	74.0	17.03	Peak	165.00	200	Horizontal	Pass
6**	17429.487	45.77	54.0	8.23	AV	165.00	200	Horizontal	Pass

1 GHz to 18 GHz, ANT V 802.11n40 Middle Channel

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1333.080	42.65	74.0	31.35	Peak	122.00	300	Vertical	Pass
1**	1333.080	37.55	54.0	16.45	AV	122.00	300	Vertical	Pass
2	2979.422	49.29	74.0	24.71	Peak	254.00	100	Vertical	Pass
2**	2979.422	38.89	54.0	15.11	AV	254.00	100	Vertical	Pass
3	4856.850	48.64	74.0	25.36	Peak	218.00	200	Vertical	Pass
3**	4856.850	43.40	54.0	10.60	AV	218.00	200	Vertical	Pass
4	6604.657	55.64	74.0	18.36	Peak	300.00	100	Vertical	Pass
4**	6604.657	43.88	54.0	10.12	AV	300.00	100	Vertical	Pass
5	13432.444	53.23	74.0	20.77	Peak	83.00	300	Vertical	Pass
5**	13432.444	45.48	54.0	8.52	AV	83.00	300	Vertical	Pass
6	17412.992	58.79	74.0	15.21	Peak	232.00	100	Vertical	Pass
6**	17412.992	47.83	54.0	6.17	AV	232.00	100	Vertical	Pass

1 GHz to 18 GHz, ANT H 802.11n40 High Channel

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1329.004	45.66	74.0	28.34	Peak	4.00	100	Horizontal	Pass
1**	1329.004	37.75	54.0	16.25	AV	4.00	100	Horizontal	Pass
2	3000.120	48.88	74.0	25.12	Peak	314.00	100	Horizontal	Pass
2**	3000.120	40.55	54.0	13.45	AV	314.00	100	Horizontal	Pass
3	4931.697	53.10	74.0	20.90	Peak	128.00	200	Horizontal	Pass
3**	4931.697	43.60	54.0	10.40	AV	128.00	200	Horizontal	Pass
4	6808.230	53.05	74.0	20.95	Peak	11.00	200	Horizontal	Pass
4**	6808.230	42.61	54.0	11.39	AV	11.00	200	Horizontal	Pass
5	13409.717	56.58	74.0	17.42	Peak	22.00	400	Horizontal	Pass
5**	13409.717	43.95	54.0	10.05	AV	22.00	400	Horizontal	Pass
6	17427.316	55.62	74.0	18.38	Peak	360.00	300	Horizontal	Pass
6**	17427.316	45.66	54.0	8.34	AV	360.00	300	Horizontal	Pass

1 GHz to 18 GHz, ANT V 802.11n40 High Channel

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1330.966	42.85	74.0	31.15	Peak	39.00	300	Vertical	Pass
1**	1330.966	40.22	54.0	13.78	AV	39.00	300	Vertical	Pass
2	2979.745	51.27	74.0	22.73	Peak	30.00	300	Vertical	Pass
2**	2979.745	44.05	54.0	9.95	AV	30.00	300	Vertical	Pass
3	4857.602	52.04	74.0	21.96	Peak	242.00	200	Vertical	Pass
3**	4857.602	42.47	54.0	11.53	AV	242.00	200	Vertical	Pass
4	6610.358	54.78	74.0	19.22	Peak	245.00	200	Vertical	Pass
4**	6610.358	42.16	54.0	11.84	AV	245.00	200	Vertical	Pass
5	13434.443	55.58	74.0	18.42	Peak	316.00	100	Vertical	Pass
5**	13434.443	44.59	54.0	9.41	AV	316.00	100	Vertical	Pass
6	17419.049	58.90	74.0	15.10	Peak	148.00	200	Vertical	Pass
6**	17419.049	49.74	54.0	4.26	AV	148.00	200	Vertical	Pass

A.7 Band Edge (Restricted-band band-edge)

Note ¹: The lowest and highest channels are tested to verify the band edge emissions. Please refer to the following the plots for emissions values.

Note ²: The test data all are tested in the vertical and horizontal antenna which the trace is max hold. So these plots have shown the worst case.

Note ³: According the ANSI C63.10-2013, where limits are specified for both average and peak (or quasi-peak) detector functions, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement.

Test Data

802.11b LOW CHANNEL

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2384.991	57.06	74.0	16.94	Peak	114.00	200	Horizontal	Pass
1**	2384.991	50.56	54.0	3.44	AV	114.00	200	Horizontal	Pass
2	2390.000	53.33	74.0	20.67	Peak	65.00	300	Horizontal	Pass
2**	2390.000	46.55	54.0	7.45	AV	65.00	300	Horizontal	Pass

802.11b HIGH CHANNEL

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2483.500	56.01	74.0	17.99	Peak	288.00	300	Horizontal	Pass
1**	2483.500	45.9	54.0	8.10	AV	288.00	300	Horizontal	Pass
2	2488.648	58.49	74.0	15.51	Peak	289.00	300	Horizontal	Pass
2**	2488.648	48.85	54.0	5.15	AV	289.00	300	Horizontal	Pass

802.11g LOW CHANNEL

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2383.835	56.37	74.0	17.63	Peak	267.00	300	Horizontal	Pass
1**	2383.835	48.88	54.0	5.12	AV	267.00	300	Horizontal	Pass
2	2390.000	56.96	74.0	17.04	Peak	198.00	100	Horizontal	Pass
2**	2390.000	45.33	54.0	8.67	AV	198.00	100	Horizontal	Pass

802.11g HIGH CHANNEL

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2483.500	54.26	74.0	19.74	Peak	111.00	300	Horizontal	Pass
1**	2483.500	46.53	54.0	7.47	AV	111.00	300	Horizontal	Pass
2	2488.826	57.75	74.0	16.25	Peak	355.00	200	Horizontal	Pass
2**	2488.826	46.38	54.0	7.62	AV	355.00	200	Horizontal	Pass

802.11n20 LOW CHANNEL

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2383.708	59.18	74.0	14.82	Peak	102.00	200	Horizontal	Pass
1**	2383.708	49.78	54.0	4.22	AV	102.00	200	Horizontal	Pass
2	2390.000	56.74	74.0	17.26	Peak	70.00	300	Horizontal	Pass
2**	2390.000	44.51	54.0	9.49	AV	70.00	300	Horizontal	Pass

802.11n20 HIGH CHANNEL

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2483.500	55.39	74.0	18.61	Peak	125.00	200	Horizontal	Pass
1**	2483.500	48.07	54.0	5.93	AV	125.00	200	Horizontal	Pass
2	2488.665	56.48	74.0	17.52	Peak	345.00	100	Horizontal	Pass
2**	2488.665	46.18	54.0	7.82	AV	345.00	100	Horizontal	Pass

802.11n40 LOW CHANNEL

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2384.059	56.36	74.0	17.64	Peak	54.00	200	Horizontal	Pass
1**	2384.059	50.46	54.0	3.54	AV	54.00	200	Horizontal	Pass
2	2390.000	55.7	74.0	18.30	Peak	98.00	300	Horizontal	Pass
2**	2390.000	44.2	54.0	9.80	AV	98.00	300	Horizontal	Pass

802.11n40 HIGH CHANNEL

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2483.500	54.14	74.0	19.86	Peak	288.00	100	Horizontal	Pass
1**	2483.500	44.92	54.0	9.08	AV	288.00	100	Horizontal	Pass
2	2488.175	56.42	74.0	17.58	Peak	330.00	100	Horizontal	Pass
2**	2488.175	48.98	54.0	5.02	AV	330.00	100	Horizontal	Pass

A.8 Power Spectral Density (PSD)

Test Data

802.11b Mode:

Channel	Spectral power density (dBm/3kHz)	Limit (dBm/3kHz)
Low	-6.851	8
Middle	-6.004	8
High	-7.425	8

802.11g Mode:

Channel	Spectral power density (dBm/3kHz)	Limit (dBm/3kHz)
Low	-10.487	8
Middle	-9.154	8
High	-10.329	8

802.11n-20 MHz Mode:

Channel	Spectral power density (dBm/3kHz)	Limit (dBm/3kHz)
Low	-9.751	8
Middle	-10.517	8
High	-9.948	8

802.11n-40 MHz Mode:

Channel	Spectral power density (dBm/3kHz)	Limit (dBm/3kHz)
Low	-12.168	8
Middle	-12.687	8
High	-11.939	8

Test Plots

802.11b LOW CHANNEL




802.11b MIDDLE CHANNEL




802.11b HIGH CHANNEL




802.11g LOW CHANNEL




802.11g MIDDLE CHANNEL




802.11g HIGH CHANNEL




802.11n-20 MHz LOW CHANNEL




802.11n-20 MHz MIDDLE CHANNEL



802.11n-20 MHz HIGH CHANNEL




802.11n-40 MHz LOW CHANNEL



802.11n-40 MHz MIDDLE CHANNEL



802.11n-40 MHz HIGH CHANNEL



ANNEX B TEST SETUP PHOTOS

Please refer the document “BL-SZ24B1326-AR.PDF”.

ANNEX C EUT EXTERNAL PHOTOS

Please refer the document “BL-SZ24B1326-AW.PDF”.

ANNEX D EUT INTERNAL PHOTOS

Please refer the document “BL-SZ24B1326-AI.PDF”.

Statement

1. The laboratory guarantees the scientificity, accuracy and impartiality of the test, and is responsible for all the information in the report, except the information provided by the customer. The customer is responsible for the impact of the information provided on the validity of the results.
2. The report without China inspection body and laboratory Mandatory Approval (CMA) mark has no effect of proving to the society.
3. For the report with CNAS mark or A2LA mark, the items marked with "☆" are not within the accredited scope.
4. This report is invalid if it is altered, without the signature of the testing and approval personnel, or without the "inspection and testing dedicated stamp" or test report stamp.
5. The test data and results are only valid for the tested samples provided by the customer.
6. This report shall not be partially reproduced without the written permission of the laboratory.
7. Any objection shall be raised to the laboratory within 30 days after receiving the report.

--END OF REPORT--