



RF Exposure Evaluation

FCC ID: 2BBPLJSTRVB4M

Product	:	mouse
Model Name	:	PY-UKJSTRVB4-M
Brand	:	N/A
Report No.	:	PTC25052811502E-FC02
 Prepared for		
Truststone Group, LLC		
1370 Broadway 9th floor New York NY 10018		
 Prepared by		
Precise Testing & Certification Co., Ltd.		
Building 1, No. 6, Tongxin Road, Dongcheng Street, Dongguan, Guangdong, China.		



Report No.: PTC25052811502E-FC02

TEST RESULT CERTIFICATION

Applicant's name : Truststone Group, LLC.
Address : 1370 Broadway 9th floor | New York NY 10018
Manufacture's name : Truststone Group, LLC
Address : 1370 Broadway 9th floor | New York NY 10018
Product name : mouse
Model name : PY-UKJSTRVB4-M
Test procedure : 2.1093 , KDB 447498 D01 v06
Test Date : Feb. 16, 2025 to June. 17, 2025
Date of Issue : June. 17, 2025
Test Result : PASS

This device described above has been tested by PTC, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of PTC, this document may be altered or revised by PTC, personal only, and shall be noted in the revision of the document.

Test Engineer:

A handwritten signature in black ink, appearing to read "Jack Zhou".

Jack Zhou / Engineer

Technical Manager:

A handwritten signature in black ink, appearing to read "Simon Pu".

Simon Pu / Manager



Contents

	Page
2 TEST SUMMARY	4
2.1 TEST SITE	4
2.2 MEASUREMENT UNCERTAINTY	4
3 GENERAL INFORMATION	5
3.1 GENERAL DESCRIPTION OF E.U.T	5
4 RF EXPOSURE	6
4.1 REQUIREMENTS	6
4.2 THE PROCEDURES / LIMIT	6
4.3 TEST RESULT	7



2 Test Summary

Test Items	Test Requirement	Result
Maximum Permissible Exposure (Exposure of Humans to RF Fields)	15.247 (i)	PASS
Remark:		
N/A: Not Applicable		

2.1 Test Site

Precise Testing & Certification Co., Ltd

Address: Building 1, No. 6, Tongxin Road, Dongcheng Street, Dongguan, Guangdong, China

FCC Registration Number: 790290

A2LA Certificate No.: 4408.01

IC Registration Number: 12191A

FCC Designation Number: CN1219

2.2 Measurement Uncertainty

Parameter	Uncertainty
RF output power, conducted	±1.0dB
Power Spectral Density, conducted	±2.2dB
Radio Frequency	± 1 x 10 ⁻⁶
Bandwidth	± 1.5 x 10 ⁻⁶
Time	±2%
Duty Cycle	±2%
Temperature	±1°C
Humidity	±5%
DC and low frequency voltages	±3%
Conducted Emissions (150kHz~30MHz)	±3.64dB
Radiated Emission(9kHz~30MHz)	±3.15dB
Radiated Emission(30MHz~1GHz)	±5.03dB
Radiated Emission(1GHz~25GHz)	±4.74dB



3 General Information

3.1 General Description of E.U.T.

Product	:	keyboard
Model Name	:	PY-UKJSTRVB4-M
Specification	:	PY-JSTRVB4-BLS,OG-JSTRBE-BLK
Operating frequency	:	BLE
Modulation	:	2402-2480MHz for BLE
Number of Channel	:	40 channels for BLE
Antenna installation	:	GFSK For BLE;
Antenna Gain	:	PCB antenna
Power supply	:	2.34 dBi
Hardware Version	:	DC 1.5V
Software Version	:	1.0
Test sample No.	:	1.0



4 RF Exposure

4.1 Requirements

Test Requirement : FCC Part 15.247(i) and 1.1307b(1)

Evaluation Method : KDB 447498 D01 General RF Exposure Guidance v06

4.2 The procedures / limit

The 1-g and 10-g SAR test exclusion thresholds for 100MHz to 6GHz at test separation distances \leq 50mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})]^*[\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g SAR extremity SAR, where}$

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison.

The test exclusions are applicable only when the minimum test separation distance is \leq 50mm and for transmission frequencies between 100MHz and 6GHz. When the minimum test separation distance is $< 5\text{mm}$, a distance of 5mm is applied to determine SAR test exclusion

Routine SAR evaluation refers to that specifically required by § 2.1093, using measurements or computer simulation. When routine SAR evaluation is not required, portable transmitters with output power greater than the applicable low threshold require SAR evaluation to qualify for TCB approval.



4.3 Test Result

Channel (MHz)	Maximum output power (dBm)	Tune up tolerance (dBm)	Max Tune Up Power (mW)	Distance (mm)	Calculation results	Limit	Operating Mode
2402	1.42	1.42±1	1.745822	5	0.541149	3	BLE_1M

Remark:

1. Calculate in the worst-case mode.
2. Max. Tune Up Power is declared by manufacturer, and used to calculate.

*****THE END REPORT*****